



(51) International Patent Classification:

<i>A45D 2/00</i> (2006.01)	<i>A45D 1/02</i> (2006.01)
<i>A45D 37/00</i> (2006.01)	<i>A45D 2/22</i> (2006.01)
<i>A45D 1/00</i> (2006.01)	<i>A45D 6/06</i> (2006.01)
<i>A45D 2/40</i> (2006.01)	<i>A45D 1/04</i> (2006.01)
<i>A45D 2/42</i> (2006.01)	<i>A45D 2/36</i> (2006.01)
<i>A45D 2/12</i> (2006.01)	<i>A45D 4/00</i> (2006.01)

(21) International Application Number:

PCT/US2013/074937

(22) International Filing Date:

13 December 2013 (13.12.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/713,444 13 December 2012 (13.12.2012) US

(71) Applicant: **CONAIR CORPORATION** [US/US]; One Cummings Point Road, Stamford, CT 06902 (US).

(72) Inventor: **LEUNG, Anthony, Kit Lun**; Flat B. 6/f, Block 12, Braemar Hill Mansion, North Point, Kong Kong, 06468 (CN).

(74) Agents: **SCHMIDT, Joseph, W.** et al.; Carter, Deluca, Farrell & Schmidt, LLP, 445 Broad Hollow Road, Melville, NY 11747 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: HAIR STYLING APPARATUS




FIG. 1

(57) Abstract: A hair styling apparatus includes first and second handle members adapted for movement between an open position for receiving hair therebetween and a closed condition adjacent the hair, a heating element associated with at least one of said first and second handle members and a cartridge mountable to said first handle member and having a hair treatment agent for dispensing and treating hair disposed between the first and second handle members. The treatment agent may include a conditioning, strengthening, repairing or revitalizing fluid. An ultrasonic transducer may be associated with said cartridge. The transducer is actuatable to heat the treatment agent to affect at least partial vaporization thereof for release adjacent the heating elements and application to the hair.



Published:

— *with international search report (Art. 21(3))*

HAIR STYLING APPARATUS

BACKGROUND

1. Technical Field

[0001] The present disclosure relates to an apparatus for treating hair, and, more particularly, relates to a hair styling apparatus incorporating a cartridge with an ultrasound transducer for heating and at least partially vaporizing a hair treatment agent dispensable from the cartridge.

2. Background of the Related Art

[0002] Hair straightener apparatus typically include two pivotal handles which are hinged at one end and pivot about the hinge between open and closed positions. Heating heads extend from each handle and have inner surfaces comprised of a heatable material, usually metal, for straightening or styling hair. An electric heater element located beneath each heatable surface is activated to warm the surfaces to a desired temperature. The inner surfaces are positionable around hair to be styled, and the hinged handles are moved to a closed position bringing the heated inner surfaces in contact with the hair. The gripped handles are then slid along the hair strands until the hair exits from the heads. One example of a hair straightener apparatus is disclosed in commonly assigned U.S. Patent No. **7,178,532**, the entire contents of which are incorporated by reference herein.

SUMMARY

[0003] Accordingly, the present disclosure is directed to further enhancements in hair straightener apparatti. In accordance with one embodiment, a hair styling apparatus includes first and second handle members adapted for movement between an open position for receiving hair therebetween and a closed position adjacent the hair, a heating element associated with at least one of the first and second handle members and a cartridge mountable to the first handle member and having a hair treatment agent for dispensing and treating hair disposed between the first and second handle members. The treatment agent may include a conditioning, strengthening, repairing or revitalizing fluid.

[0004] An ultrasonic transducer may be associated with the cartridge. The transducer is actuatable to heat the treatment agent to affect at least partial vaporization thereof for release adjacent the heating elements and application to the hair. The cartridge may define a cartridge vapor outlet with the transducer being positioned adjacent the cartridge vapor outlet. The transducer may have channels for permitting the at least partially vaporized treatment agent to pass through the transducer and the cartridge vapor outlet.

[0005] The heating element of the at least one of the first and second handle members may define a channel, which is positioned adjacent the cartridge outlet to convey vaporized treatment agent along the heating element. In one embodiment, the first and second handle members include respective first and second heating elements with each the heating element having the channel for conveying the vaporized treatment agent.

[0006] A manually actuated ultrasonic power switch for selectively activating and deactivating the transducer. The cartridge may include electrical contacts in electrical communication with the transducer, and wherein the first handle member includes corresponding handle contacts for engaging the electrical contacts of the cartridge for supplying power to the transducer.

[0007] The cartridge may be dimensioned and adapted for releasable mounting to the first handle member. A cartridge release member may be mounted to the first handle member. The cartridge release member is movable to cause release of the cartridge from the first handle member. The cartridge may include a cover, which is movable between an open condition to permit introduction of the treatment agent within the cartridge and a closed position. The cartridge may define an internal chamber for accommodating the treatment agent. An absorbent member may be disposed within the internal chamber for containing the treatment agent. The absorbent member is adjacent the transducer whereby heat generated by the transducer causes at least partial vaporization of the treatment agent within the absorbent member. In embodiments, a container having the treatment agent is releasably mountable to the cartridge.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] Various embodiments of the present disclosure are described hereinbelow with references to the drawings, wherein:

[0009] **FIGS. 1-2** are perspective views of a hair styling apparatus in accordance with the principles of the present disclosure illustrating the first and second handle members and the cartridge mounted to the first handle member;

[0010] **FIGS. 3-5** are top plan, side elevation and axial views, respectively of the hair styling apparatus;

[0011] **FIG. 6** is a perspective view of the hair styling apparatus illustrating the cartridge removed;

[0012] **FIG. 7** is a top plan view of the cartridge;

[0013] **FIG. 8** is a side cross-sectional view of the cartridge taken along the lines 8-8 of **FIG. 7**;

[0014] **FIG. 9** is an enlarged isolated view of the area of detail designated in **FIG. 8**;

[0015] **FIG. 10** is a schematic view illustrating a mechanism for releasably mounting the cartridge to the first handle member;

[0016] **FIG. 11** is a perspective view of the hair styling apparatus with the second handle member removed illustrating application of the vaporized hair treatment agent to the subject's hair; and

[0017] **FIGS. 12A-12C** are perspective views of three embodiments of the cartridge member illustrated in relation to the hair styling apparatus.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIEMENTS

[0018] Referring now in detail to the drawings and, in particular, to **FIGS. 1-5**, the hair styling apparatus **100** in accordance with the principles of the present invention is illustrated. The hair styling apparatus **100** may be in the form of a hair straightener utilized to generally straighten the hair of the subject. However, it is envisioned that the hair styling apparatus may include surfaces to shape, crimp or affect any styling effect to the subject's hair.

[0019] The hair styling apparatus **100** includes first and second handle members **102, 104** connected to each other through a hinge **106**, of a conventional type. The hinge **106** typically incorporates a spring to normally bias the first and second members **102, 104** to the open position depicted in **FIGS. 1** and **2**. The first and second handle members **102, 104** are adapted to pivot about the hinge **106** between the open position of **FIGS. 1** and **2** and the closed position depicted in **FIGS. 3-5**. The first handle member **102** includes a cartridge **108** and a cartridge release button **110**, which releases the cartridge **108** from the first handle member **102**. Generally, the cartridge **108** contains a hair treatment agent, which is released in an at least partially vaporized state, between the first and second handle members **102, 104** for application to the subject's hair. The cartridge **108** will be discussed in greater detail hereinbelow.

[0020] Each of the first and second handle members **102, 104** includes a heating element or plate **110** at the end remote from the hinge **106**. The heating plates **110** are heated by conventional electrical means (not shown) known in the art, so that hair can be positioned therebetween for styling. Each heating plate **110** includes a centrally disposed channel **112** respectively extending lengthwise or longitudinally with respect to the longitudinal axes "k1, k2" of the respective handle members **102, 104**. The channels **112** may be offset with respect to the

respective axes “k1, k2”, may be non-linear, arcuate, sinusoidal or any other shape. The channels 112 convey the at least partially vaporized treatment agent, which is released from the cartridge 108 within the heating plates 110 for application to the hair of the subject. The second handle member 104 includes a pocket or recess 114 (FIG. 1), which is dimensioned to correspondingly accommodate at least a segment of the cartridge 108 when the first and second handle members 102, 104 are in the closed position.

[0021] The first and second handle members 102, 104 may include an on/off power switch 116, a power-on indicator or light 118 (such as an LED indicator or the like) for indicating activation of the apparatus 100 and a power cord 120 for supplying power. Contacts 122 on each of the first and second handle member 102, 104 may be provided to power the heating plates only when the first and second handle members 102, 104 are in the closed position. The first handle member 102 further includes an ultrasound power switch 124 and an ultrasound power indicator 126 such as an LED or the like - the function of which will be discussed in greater detail herein below.

[0022] Referring now to FIG. 6, in conjunction with FIGS. 7-9, the cartridge 108 will be discussed in detail. The cartridge 108 includes a cartridge housing 128 having a first internal chamber 130 defining a reservoir for accommodating the treatment agent 132. The treatment agent may be argan oil. Argan oil is extracted from the fruits of the argan tree, *argania spinosa*, that is endemic to Morocco. The hair care composition may solely contain argan oil, or may include argan oil in combination with other ingredients. Examples of other ingredients include pharmaceutically active agents, moisturizers, hydration agents, penetration agents, preservatives, emulsifiers, natural or synthetic oils, solvents, surfactants, detergents, gelling agents, emollients, antioxidants, fragrances, fillers, thickeners, waxes, odor absorbers, dyestuffs, coloring agents,

powders, viscosity-controlling agents, buffers, protectants, pH regulators, chelating agents, humectants, conditioners, glitter, mica, minerals, silicones, polyphenols, sunblocks, phytomedicinals, and combinations thereof, as well as other additives typically used in hair care products as appreciated by those skilled in the art.

[0023] In embodiments, the hair care composition may include argan oil and emollients and/or conditioning agents, alone or in combination with other ingredients as discussed above. In embodiments, the hair care composition includes argan oil and silicone. Silicone includes, for example, silicone oils and oils having a hydrocarbon backbone, silicone oils combining cyclic polydimethylsiloxanes, α,ω -hydroxylated polydimethylsiloxanes, α,ω -trimethylsilyl polydimethylsiloxanes, polyorganosiloxanes such as polyalkylmethylsiloxanes, polymethylphenylsiloxanes, polydiphenylsiloxanes, aminosilicone derivatives, silicone waxes, copolyether silicones (such as the oil MIRASIL DMCO sold by Rhone-Poulenc, or DC 190 sold by Dow Corning) or mixed silicone derivatives including various types of derivatization (such as polyalkylmethyl-siloxane/copolyether silicone mixed copolymers). An argan/silicon conditioning agent may strengthen, repair or condition hair, while potentially adding shine to the hair.

[0024] Other suitable emollients include, for example alkylmonoglycerides, alkyldiglycerides, and/or triglycerides such as oils extracted from plants and vegetables (palm oil, coconut oil, cotton seed oil, soybean oil, sunflower oil, olive oil, grape seed oil, sesame oil, ground nut oil, castor oil, combinations thereof, and the like), oils of marine origin (fish oils, etc.) and derivatives of these oils, such as hydrogenated oils, lanolin derivatives, mineral oils or paraffinic oils, perhydrosqualane, squalene, diols such as 1,2-propanediol and 1,3-butanediol, cetyl alcohol, stearyl alcohol, oleyl alcohol, polyethylene glycols or polypropylene glycols, and

fatty esters such as isopropyl palmitate, 2-ethylhexyl cocoate, myristyl myristate, esters of lactic acid, stearic acid, behenic acid, isostearic acid.

[0025] In embodiments, the hair care composition may include argan oil and conditioners, alone or in combination with other ingredients. Conditioners include, for example, those of natural or synthetic origin, such as those known under the generic CTFA name "Polyquaternium", for instance the MIRAPOL A15® or MIRAPOL 550® polymers from Rhone-Poulenc, cationic polysaccharide derivatives (cationic derivatives of cellulose, of guar or of carob), such as cocodimonium hydroxyethyl cellulose, guar hydroxypropyl trimonium chloride, hydroxypropyl guar hydroxypropyl trimonium chloride (JAGUAR C13S®, JAGUAR C162® sold by Rhone-Poulenc), volatile or non-volatile silicone derivatives, for instance amodimethicone, cyclomethicones, water-insoluble, non-volatile polyorganosiloxanes, for instance oils, resins or gums, such as diphenyldimethicone gums, combinations thereof, and the like.

[0026] Examples of other additives which may be useful in the hair care composition include additives for promoting moisturization of the hair and/or skin (wetting agents), for instance certain carbohydrates (for example glycerol or sorbitol), polyethylene glycols or polypropylene glycols, alkoxylated derivatives of sugars or of sugar derivatives (for example methylglucose), water-soluble or water-dispersible polymers such as collagen or certain non-allergenic derivatives of marine or plant proteins (for example wheat protein hydrolysates). Thickeners, such as natural hydrocolloids (guar gum, carob gum, tara gum, etc.) or hydrocolloids derived from fermentation processes, such as xanthan gum, polysaccharides extracted from seaweed, such as carrageenans, and polycarbohydrate derivatives such as modified celluloses (for example hydroxyethylcellulose, carboxymethylcellulose), or nonionic derivatives (for example

hydroxypropylguar), anionic derivatives (carboxymethylguar) or nonionic/anionic mixed derivatives, such as carboxy-hydroxypropyl-guars or nonionic/cationic derivatives, can also be present.

[0027] Referring still to **FIGS. 6-9**, the cartridge housing **128** may have a cartridge valve or cover **134** (**FIG. 8**), which permits access to the first internal chamber **130**. The cover **134** may be movable between the closed position and the open position depicted in phantom in **FIG. 8** to permit filling/refilling of the treatment agent **132** within the first internal chamber **130** of the cartridge housing **128**. The cartridge housing **128** further includes a second internal chamber **136** in fluid communication with the first internal chamber **130**. The second internal chamber **136** may have an absorbent member **138** such as a sponge, wicking material or the like, which collects and stores a volume of the treatment agent **132**.

[0028] The cartridge **108** has an ultrasound emitter or transducer **140** such as a piezo electric transducer or the like. The piezo electric transducer **140** may be any conventional piezo electric transducer adapted to oscillate to generate energy in the form of heat. The transducer **140** may be disc shaped and mounted at each end within opposed channels **142** defined within the cartridge housing **128** adjacent or across a cartridge vapor outlet opening **146** of the cartridge housing **128** (see also **FIG. 6**). An elastomeric o-ring gasket or seal **148** comprising an elastomeric material or the like may extend within each channel **144** to form a fluid tight seal about the ends of transducer **142**. The transducer **142** further includes one or more micro-openings or channels **150** extending therethrough in communication with the second internal chamber **136** to permit release of the vaporized treatment agent.

[0029] The cartridge **108** further includes one or more power contacts or pins **152** in electrical communication with the transducer **142**. The power pins **152** are received within

corresponding power receptacles **154** disposed within the first handle member **102** adjacent the cartridge receiving recess **156** of the first handle member **102** (**FIG. 6**). The power receptacles **154** include electrical contacts, which are in communication with the ultrasound power switch **124** and the electrical cord **122** to selectively supply power to the transducer **142**. Thus, upon mounting of the cartridge **108** fully within the cartridge receiving recess **156** of the first handle member **102**, the contact pins **152** of the cartridge **108** establish electrical contact with the contacts within the pin receiving receptacles **154** of the first handle member **102**. The cartridge receiving recess **156** is correspondingly dimensioned to accommodate the cartridge **108** in a manner to reduce the profile of the first handle member **102**.

[0030] The cartridge housing **128** may have at least one locking detent **158**, which is selectively engaged by the cartridge release button **110** to releasably secure the cartridge **108** relative to the first handle member **102**. Any type of releasable connection means are envisioned including, e.g., tongue and groove arrangements, bayonet couplings, sliding release arrangements or the like. In one embodiment schematically depicted in **FIG. 10**, the cartridge release button **110** includes a depending resilient member **160**, which is receivable within the locking detent **158** of the cartridge housing **128**. Depression of the release button **110** will cause the resilient member **160** to deflect in the direction “m” and become released from the locking detent **158**, thereby permitting removal of the cartridge **108** from the cartridge receiving recess **156** of the first handle member **102**.

[0031] The use of the hair styling apparatus **100** for styling hair will now be discussed. The cartridge **108** filled with the hair treatment agent **132** is mounted within the outer cartridge receiving recess **156** of the first handle member **102**. Electrical contact is established between the contact pins **152** of the cartridge housing **128** and the contacts within the pin receiving

receptacles **154** of the first handle member **102**. The power switch **118** is activated to charge the heating elements **110** of the first and second handle members **102, 104**. The subject's hair is positioned between the open first and second handle members **102, 104** (FIGS. 1 and 2) and the first and second handle members **102, 104** are moved to the closed position of FIGS. 3-5. The hair is treated, e.g., straightened, as it passes along the heating elements **110**. When it is desired to apply the hair treatment agent **132**, the transducer power switch **124** is activated causing the transducer **142** to oscillate. As the transducer **142** oscillates, heat is generated sufficient to at least partially vaporize the treatment agent **132** within the absorbent member **138** in the second internal chamber **136**. As depicted in FIGS. 9 and 11, the vaporized treatment agent "**132v**" is released through the micro-openings **150** extending through the transducer **140** and out the cartridge vapor outlet opening **146** of the cartridge housing **128**. FIG. 11 depicts the first handle member **102** removed for illustration purposes. The vaporized treatment agent "**132v**" communicates through the opening of the first handle member, and is conveyed through the channels **112** of the first and second handle members **102, 104** for application to the subject's hair. The treatment agent **132v** released in the vaporized state from the absorbent or wicking member **138** is continuously replenished with the treatment agent stored within the first internal chamber **130**. The ultrasound transducer **140** may be deactivated at any time during the procedure via the ultrasound power switch **124**. In the event more treatment agent **132** is needed, the cartridge **108** is released from the first handle member **102** by depression of the cartridge release button **110**. The closure seal or cover of the cartridge **134** may be opened, and additional treatment agent **132** is introduced within the first internal chamber **130**. The cover **134** is closed and the cartridge **108** is reinserted into the cartridge receiving recess **156** of the first handle member **102**.

[0032] The wicking or absorbent member **138** maintains the treatment agent in the liquid state adjacent the transducer **140** while preventing the liquid treatment agent from interfering with the functioning of the transducer **140**. When subjected to heat generated by the transducer **140**, the treatment agent **132** at least partially vaporizes for release through the channels **150** of the transducer **140**. The vaporized treatment agent **132v** will not interfere with the functioning of the transducer. The vaporized treatment agent **132v** also protects the hair when subjected to the heat of the heating elements **110**.

[0033] FIGS 12A-12C illustrate alternate embodiments of the cartridge **108**. In FIG. 12A, the cartridge **200** is similar to the cartridge **108** of the first embodiment and incorporates a cover **202** which is selectively opened and closed to permit access to the internal chambers for refilling of the treatment agent. In FIG. 12B, the cartridge **300** includes a threaded opening **302** which receives a threaded bottle member **304** containing the treatment agent. The bottle **304** may replace the first internal chamber and supply the treatment agent to the absorbent member. Upon emptying of the bottle **304**, the bottle may be released and replaced with a new bottle of agent or refilled and connected to the cartridge **300**. In FIG. 12C, a flexible pouch **308**, e.g., a foil pouch, having a threaded segment **310** may be received within the threaded opening **302** of the cartridge **300**. Multiple pouches **308** may be provided as replacement pouches during use of the apparatus **100**.

[0034] The above description and the drawings are provided for the purpose of describing embodiments of the present disclosure and are not intended to limit the scope of the disclosure in any way. It will be apparent to those skilled in the art that various modifications and variations can be made without departing from the spirit or scope of the disclosure. Thus, it is intended that

the present disclosure cover the modifications and variations of this disclosure provided they come within the scope of the appended claims and their equivalents.

WHAT IS CLAIMED IS:

1. A hair styling apparatus, which comprises:
first and second handle members adapted for movement between an open position for receiving hair therebetween and a closed condition adjacent the hair;
a heating element associated with at least one of said first and second handle members; and
a cartridge mountable to said first handle member, said cartridge including a hair treatment agent for dispensing and treating hair disposed between said first and second handle members.
2. The hair styling apparatus according to claim 1 including an ultrasonic transducer associated with said cartridge, said transducer actuatable to heat the treatment agent to effect at least partial vaporization thereof for release adjacent said heating element and application to the hair.
3. The hair styling apparatus according to claim 2 wherein said cartridge defines a cartridge vapor outlet, said transducer positioned adjacent said cartridge vapor outlet within said cartridge.
4. The hair styling apparatus according to claim 3 wherein said transducer has channels for permitting said at least partially vaporized treatment agent to pass through said transducer and said cartridge vapor outlet.

5. The hair styling apparatus according to claim 3 wherein said heating element defines a channel, said channel positioned adjacent said cartridge outlet to convey vaporized treatment agent along said heating element.

6. The hair styling apparatus according to claim 4 wherein said first and second handle members include respective first and second heating elements, each said heating element having said channel for conveying the vaporized treatment agent.

7. The hair styling apparatus according to claim 3 including a manually actuated ultrasonic power switch for selectively activating and deactivating said transducer.

8. The hair styling apparatus according to claim 3 wherein said cartridge includes electrical contacts in electrical communication with said transducer, and wherein said first handle member includes corresponding handle contacts for engaging said electrical contacts of said cartridge for supplying power to said transducer.

9. The hair styling apparatus according to claim 2 wherein said cartridge is dimensioned and adapted for releasable mounting to said first handle member.

10. The hair styling apparatus according to claim 9 including a cartridge release member mounted to said first handle member, said cartridge release member movable to cause release of said cartridge from said first handle member.

11. The hair styling apparatus according to claim **2** wherein said cartridge includes a cover, said cover being movable between an open condition to permit introduction of said treatment agent within said cartridge and a closed condition.


12. The hair styling apparatus according to claim **9** wherein said cartridge defines an internal chamber for accommodating said treatment agent.

13. The hair styling apparatus according to claim **12** including an absorbent member within said internal chamber for containing said treatment agent, said absorbent member adjacent said transducer whereby heat generated by said transducer causes at least partial vaporization of said treatment agent within said absorbent member.

14. The hair styling apparatus according to claim **11** including a container releasably mountable to said cartridge, said container including said treatment agent.

15. The hair styling apparatus according to claim **1** wherein said treatment agent includes a conditioning, strengthening, repairing or revitalizing fluid.

16. The hair styling apparatus according to claim **15** said treatment agent includes ARGAN oil.






FIG. 3




FIG. 4




FIG. 5








FIG. 10





三
 三
 〇
 三
 三



INTERNATIONAL SEARCH REPORT		International application No. PCT/US13/74937						
A. CLASSIFICATION OF SUBJECT MATTER IPC: A45D 2/00 (2006.01), 37/00 (2006.01), 1/00 (2006.01), 2/40 (2006.01), 2/42 (2006.01), 2/12 (2006.01), 1/02 (2006.01), 2/22 (2006.01), 6/06 (2006.01), 1/04 (2006.01), 2/36 (2006.01), 4/00 (2006.01) USPC: 132/221,224-229 According to International Patent Classification (IPC) or to both national classification and IPC								
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) U.S. : 132/221,224-229 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) US-PGPUB, USPAT, USOCR, DERWENT: cartridge, ultrasonic, transducer								
C. DOCUMENTS CONSIDERED TO BE RELEVANT <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th style="width: 10%; padding: 5px;">Category *</th> <th style="width: 70%; padding: 5px;">Citation of document, with indication, where appropriate, of the relevant passages</th> <th style="width: 20%; padding: 5px;">Relevant to claim No.</th> </tr> <tr> <td style="text-align: center; vertical-align: top; padding: 5px;">X --- Y</td> <td style="padding: 5px;">US 2013/0192625 A1 (MIGLIORI et al.) 01 August 2013 (01.08.2013), see entire document.</td> <td style="text-align: center; vertical-align: top; padding: 5px;">1 and 15 ----- 16</td> </tr> </table>			Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.	X --- Y	US 2013/0192625 A1 (MIGLIORI et al.) 01 August 2013 (01.08.2013), see entire document.	1 and 15 ----- 16
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.						
X --- Y	US 2013/0192625 A1 (MIGLIORI et al.) 01 August 2013 (01.08.2013), see entire document.	1 and 15 ----- 16						
☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.								
<table style="width: 100%;"> <tr> <td style="width: 50%; vertical-align: top;"> * Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed </td> <td style="width: 50%; vertical-align: top;"> "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family </td> </tr> </table>			* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family				
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family							
Date of the actual completion of the international search 14 January 2014 (14.01.2014)		Date of mailing of the international search report 17 JAN 2014						
Name and mailing address of the ISA/US Mail Stop PCT, Attn: ISA/US Commissioner for Patents P.O. Box 1450 Alexandria, Virginia 22313-1450 Facsimile No. (571) 273-3201		Authorized officer William Krynski Telephone No. 571-272-1700						