



US 20170199011A1

(19) **United States**(12) **Patent Application Publication**
Beck(10) **Pub. No.: US 2017/0199011 A1**(43) **Pub. Date: Jul. 13, 2017**(54) **PERSONAL TACTICAL SYSTEM**(71) Applicant: **Tyr Tactical, LLC**, Peoria, AZ (US)(72) Inventor: **Jason Beck**, Peoria, AZ (US)(73) Assignee: **Tyr Tactical, LLC**, Peoria, AZ (US)(21) Appl. No.: **15/257,745**(22) Filed: **Sep. 6, 2016**

No. 61/384,560, filed on Sep. 20, 2010, provisional application No. 61/355,089, filed on Jun. 15, 2010, provisional application No. 62/289,089, filed on Jan. 29, 2016.

Publication Classification(51) **Int. Cl.****F41H 1/02** (2006.01)**A41D 1/04** (2006.01)**F41H 5/04** (2006.01)(52) **U.S. Cl.**CPC **F41H 1/02** (2013.01); **F41H 5/0485** (2013.01); **A41D 1/04** (2013.01)**Related U.S. Application Data**


(63) Continuation-in-part of application No. PCT/US2016/040989, filed on Jul. 5, 2016, Continuation-in-part of application No. 14/497,508, filed on Sep. 26, 2014, Continuation-in-part of application No. 14/497,486, filed on Sep. 26, 2014, now Pat. No. 9,435,614, Continuation-in-part of application No. 13/161,322, filed on Jun. 15, 2011.

(60) Provisional application No. 62/188,595, filed on Jul. 3, 2015, provisional application No. 61/883,140, filed on Sep. 26, 2013, provisional application No. 61/883,121, filed on Sep. 26, 2013, provisional application

(57)

ABSTRACT

Implementations described and claimed herein provide a personal tactical system configured to be worn by an individual for protection against threats. In one implementation, the personal tactical system includes one or more internal components disposed in an interior formed by an outer layer and an inner layer. The internal components include a flexible body armor, a ballistic plate, a ballistic frame, and/or a ballistic plate cover.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8








FIG. 11A

FIG. 11B








FIG. 12












FIG. 17





FIG. 18






FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27

PERSONAL TACTICAL SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation-in-part of Patent Cooperation Treaty Application No. PCT/US2016/040989, entitled “Female Protective Vest” and filed on Jul. 5, 2016, which claims priority under 35 U.S.C. §119 to U.S. Provisional Application No. 62/188,595, entitled “Female Protective Vest” an filed on Jul. 3, 2015. The present application is further a continuation-in-part of U.S. patent application Ser. No. 14/497,508, entitled “Ballistic Vest System with a Ballistic Ridge Component” and filed on Sep. 26, 2014, which claims priority under 35 U.S.C. §119 to U.S. Provisional Application No. 61/883,140, entitled “Ballistic Vest System with a Ballistic Ridge Component” an filed on Sep. 26, 2013. The present application is further a continuation-in-part of U.S. patent application Ser. No. 14/497,486, entitled “Ballistic Vest System with a Ballistic Vein Component” and filed on Sep. 26, 2014, which claims priority under 35 U.S.C. §119 to U.S. Provisional Application No. 61/883,121, entitled “Ballistic Vest System with a Ballistic Vein Component” an filed on Sep. 26, 2013. The present application is further a continuation-in-part of U.S. patent application Ser. No. 13/161,322, entitled “High Performance Composite Fabric” and filed on Jun. 15, 2011, which claims priority under 35 U.S.C. §119 to U.S. Provisional Application No. 61/384,560, entitled “Kevlar Backed Nylon Tactical Material” and filed on Sep. 20, 2010 and to U.S. Provisional Application No. 61/355,089, entitled “High Performance Composite Fabric” and filed on Jun. 15, 2010.

[0002] The present application further claims priority under 35 U.S.C. §119 to U.S. Provisional Application No. 62/289,089, entitled “Flexible Body Armor” and filed on Jan. 29, 2016.

[0003] Each of the above-referenced applications is incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0004] Aspects of the present disclosure relate to personal tactical systems and more particularly to tactical vests and other tactical devices configured to be worn by an individual for protection against threats.

BACKGROUND

[0005] Tactical systems, including vests, carriers, belts, cummerbunds, ballistic accessories (e.g., shoulder protection, pouches, abdomen protection, groin protection, leg protection, bicep/deltoid upper arm protection, etc.) and the like, are worn by a human or animal to protect against penetration to the body from ballistic projectiles and shrapnel from explosions, as well as to absorb the impact force caused by such threats. Conventional systems typically achieve a compromise at best, sacrificing at least one of performance, longevity, comfort, mobility, protection, and the like to attain another. It is with these observations in mind, among others, that various aspects of the present disclosure were conceived and developed.

SUMMARY

[0006] Implementations described and claimed herein address the foregoing problems by providing a personal tactical system. In one implementation, a tactical system

includes one or more internal components disposed in an interior formed by an outer layer and an inner layer. The internal components include at least one of a flexible body armor, a ballistic plate, a ballistic frame, or a ballistic plate cover. Other implementations are also described and recited herein. Further, while multiple implementations are disclosed, still other implementations of the presently disclosed technology will become apparent to those skilled in the art from the following detailed description, which shows and describes illustrative implementations of the presently disclosed technology. As will be realized, the presently disclosed technology is capable of modifications in various aspects, all without departing from the spirit and scope of the presently disclosed technology. Accordingly, the drawings and detailed description are to be regarded as illustrative in nature and not limiting.

BRIEF DESCRIPTIONS OF THE DRAWINGS

[0007] FIG. 1 is a front view of an example tactical system in the form of a tactical vest with internal components shown.

[0008] FIG. 2 is a perspective view of the tactical vest of FIG. 1.

[0009] FIG. 3 shows a back view of the tactical vest of FIG. 1.

[0010] FIG. 4 shows a side perspective view of the tactical vest of FIG. 1 with a cummerbund belt buckle released.

[0011] FIG. 5 illustrates an example outer layer of the tactical system.

[0012] FIG. 6 depicts an example ballistic plate of the tactical system.

[0013] FIG. 7 shows a perspective view of an example ballistic plate cover of the tactical system.

[0014] FIG. 8 illustrates the ballistic plate cover engaged to the ballistic plate.

[0015] FIG. 9 is a perspective view of another example ballistic plate cover of the tactical system.

[0016] FIG. 10 is a perspective view of another example ballistic plate cover of the tactical system.

[0017] FIG. 11A and 11B show front perspective and back perspective views of the ballistic plate cover of FIG. 10.

[0018] FIG. 12 illustrates example panels of a ballistic filler for a flexible body armor, including a first panel, a second panel, and a third panel.

[0019] FIG. 13 illustrates the first panel of the ballistic filler, including a first subpanel of woven fabric and a second subpanel of unidirectional laminates.

[0020] FIG. 14 depicts the first panel of the ballistic filler with the first subpanel stitched directly to the second subpanel.

[0021] FIG. 15 shows the second panel of the ballistic filler formed from a plurality of stitched layers of unidirectional laminates.

[0022] FIG. 16 illustrates the third panel of the ballistic filler formed by a plurality of layers of unidirectional laminates.

[0023] FIG. 17 depicts a ballistic arrangement of the ballistic filler, including the first panel backed by the second panel, which is backed by the third panel.

[0024] FIG. 18 shows the ballistic filler with the first panel, the second panel, and the third panel connected using closure stitching.

[0025] FIG. 19 illustrates edge tape applied to a portion of a periphery of the ballistic filler for heat sealing.

[0026] FIG. 20 illustrates example operations for manufacturing a ballistic filler.

[0027] FIG. 21 shows a front view of an example flexible body armor with a female shape.

[0028] FIG. 22 illustrates the ballistic plate displaced at an angle relative to the flexible body armor of FIG. 21.

[0029] FIG. 23 shows a perspective cut-away view of the flexible body armor of FIG. 21.

[0030] FIG. 24 illustrates example operations for manufacturing a tactical vest with a female shape.

[0031] FIG. 25 illustrates an example frame disposed adjacent to the flexible body armor.

[0032] FIGS. 26 and 27 each show another example frame.

DETAILED DESCRIPTION

[0033] Aspects of the present disclosure involve personal tactical systems configured to be worn or otherwise used by an individual for protection against threats, including ballistic projectiles and shrapnel from explosions. In one aspect, internal components, including a ballistic plate, a ballistic plate cover, flexible body armor, and/or a frame, are disposed in an interior of the tactical system. The interior is formed between an outer layer and an inner layer.

[0034] The presently disclosed technology relates generally to personal tactical systems. The various example implementations are described herein in the context of a tactical vest. It will be appreciated, however, that the presently disclosed technology is applicable in the context of other tactical systems, including, but not limited to, other tactical vests, carriers, belts, cummerbunds, tactical accessories (e.g., shoulder protection, pouches, abdomen protection, groin protection, leg protection, bicep/deltoid upper arm protection, etc.) and the like.

[0035] To begin a detailed description of an example personal tactical system 100 in the form of a tactical vest, reference is made to FIG. 1-4. In one implementation, the tactical system 100 includes one or more internal components 102 insertable or otherwise disposed in an interior 104 of the tactical system 100. The internal components 102 of the tactical system 100 include a flexible body armor 110, a ballistic plate 112, a ballistic frame 114, and/or the like. The internal components 102 increase ballistic protection, decrease side spall and back face deformation, and provide structure to the tactical system 100, among other advantages. The interior 104 may be, for example, a pocket or similar enclosure formed by an outer layer 106 and an inner layer 108 of the tactical system 100. In some implementations the tactical system 100 includes one or more intermediate layers between the outer layer 106 and the inner layer 108.

[0036] As shown in FIG. 1, the outer layer 106 is exposed to an outside environment and is distal from the inner layer 108 to the wearer of the tactical system 100. Stated differently, the inner layer 108 faces the wearer and the outer layer 106 faces away from the wearer. In one implementation, the outer layer 106 is made from a lightweight hybrid material with superior abrasion, tear, and fire resistance characteristics, while providing load carriage support and improved durability, particularly in high-wear areas, such as corners, edges, seams, and exposed areas. The lightweight hybrid material of the outer layer 106 may be, for example, a laminate of 500-denier nylon and 200-400-denier para-aramid fibers in an ultra-tight weave. In one implementation,

the inner surface 108 is made from a material that is antimicrobial and fire resistant treated.

[0037] In the context of a tactical vest, the tactical system 100 includes a front carrier 124 and a back carrier 126 each extending between a proximal end 116 and a distal end 118 and between a first side 120 and a second side 122. In one implementation, the sides 120-122 are shaped to accommodate the anatomy and movement of the wearer's arms, and the proximal end 116 is shaped to accommodate the anatomy and movement of the wearer's collar and neck area.

[0038] Further, the front carrier 124 may be shaped to accommodate the anatomy of a female wearer. As such, in one implementation, the front carrier 124 has a carrier female shape formed by an upper portion, a set of lateral portions, and a lower portion. The carrier female shape permits a full range of motion by and provides support to the female wearer, while maximizing comfort. The back carrier 126 similarly includes an upper back portion and a lower back portion adapted to maximize comfort without inhibiting motion of the female wearer.

[0039] In one implementation, the tactical system 100 includes a front carrier pocket 134 extending from or otherwise attached to the front carrier 124. The front carrier pocket 134 may define the interior 104 be adapted to receive and hold one or more of the internal components 102.

[0040] For example, the ballistic plate 112 may be disposed within the front carrier pocket 134 with a strike face oriented away from the wearer and a back face oriented towards the inner layer 108. The ballistic plate 112 is a hard plate configured to provide ballistic protection against projectiles or shrapnel impacting a strike face of the ballistic plate 112.

[0041] A ballistic plate cover may wrap around at least a portion of a periphery of the ballistic plate 112 to provide additional protection against side spall created by augmentation of the ballistic plate 112. Such a ballistic plate cover further improves the structure of the front carrier pocket 134 and enhances area coverage and range of motion for increased ergonomics and performance, while providing additional ballistic coverage beyond a front edge of the ballistic plate 112 and beyond side edges of the ballistic plate 112. In one implementation, the ballistic plate cover provides approximately one inch of additional ballistic coverage beyond a front edge of the ballistic plate 112 and approximately 0.5 inches of additional ballistic coverage beyond side edges of the ballistic plate 112.

[0042] In addition, the tactical system 100 may include a ballistic flap that covers an opening to the front carrier pocket 134 and is configured to cover and protect the bottom portion of the ballistic plate 112 when disposed within the front carrier pocket 134. The ballistic flap may be made from a soft armor material similar to the flexible body armor 110 that, in combination with the ballistic plate cover, assists in preventing side spall and backside deformation along the bottom portion of the ballistic plate 112. In one implementation, the tactical system 100 includes a soft armor liner that extends along the peripheral edge of the front carrier pocket 134 to provide further protection to the ballistic plate 112. The soft armor liner may be sewn along a peripheral edge of the front carrier pocket 134 such that the soft armor liner at least substantially covers a peripheral edge of the ballistic plate cover when the ballistic plate 112 is disposed within the front carrier pocket 134. In some implementations, the soft armor liner may be a strip of soft armor material (e.g.,

similar material to the outer layer **106**), while in other implementations the soft armor liner may substantially or completely line the interior of the front carrier pocket **134**.

[0043] The flexible body armor **110** may be disposed in the front carrier pocket **134** behind the ballistic plate **112** on the back face side to provide additional protection and force absorption. In one implementation, the flexible body armor **110** is made from a ballistic fiber comprising at least a portion of woven fabric stitched directly to unidirectional laminates. The woven fabric is generated from ultrahigh molecular weight polyethylene (UHMWPE) fiber, which when used in conjunction with the unidirectional laminates, is effective as anti-ballistic ply structures. A ballistic arrangement of the ballistic filler includes the UHMWPE woven fabric being backed by unidirectional laminates. More specifically, the ballistic arrangement constitutes one or more regions where one or more plies of UHMWPE woven fabric are backed by one or more plies of unidirectional laminates. As used in the present disclosure, respective to each region, “backed” refers to plies residing closer to a wearer, and “fronted” refers to plies closer to a strike face of the outer layer **106**. In one implementation, one or more of the regions comprised of UHMWPE woven fabric backed by unidirectional laminate are stitched together uniformly using a quilt pattern or some other uniform stitching pattern.

[0044] A ballistic frame **114** may be disposed within the front carrier pocket **134** behind or in front of the flexible body armor **110**. The ballistic frame **114** includes a body configured to improve overall load carriage performance of the front carrier pocket **134** and the tactical system **100** by providing a rigid platform to add weight. The frame body further reduces fatigue by improving the structure of the tactical system **100** by retaining the flexible body armor **110** in a configuration that prevents bunching and provides support to the ballistic plate **112** to improve edge hit protection. The ballistic frame **114** is loose from or otherwise unattached to the flexible body armor **110** within the front carrier pocket **134**. The ballistic frame **114** absorbs and otherwise dissipates energy from an impact of a projectile against the ballistic plate **112** and/or the flexible body armor **110**. The ballistic frame **114** body may be solid or have one or more openings therethrough. The inner layer **108** may include one or more pads **132** to enhance comfort and further dissipate forces generated from an impact. The pads **132** may be sized and shaped to mirror the openings in the ballistic frame **114**.

[0045] In one implementation, the back carrier **126** includes a releasable back panel **148**, which may be used to releasably connect to or otherwise secure one or more protective devices and/or to integrate with other tactical devices. The back carrier **148** may include a back carrier pocket within, adjacent to, or in place of the releasable back panel **148** to receive and hold one or more internal components **102**. In one implementation, the releasable back panel **148** is releasably engaged to the back carrier **126** with a zipper assembly.

[0046] The front carrier **124** is connected to the back carrier **126** at the proximal end **116** and/or the distal end **118**. In one implementation, the front carrier **124** is connected to the back carrier **126** at the distal end **118** with a cummerbund having a first cummerbund portion **128** and a second cummerbund portion **130**. It will be appreciated, however, that a belt, straps, or other side connections may supplement or be

used in place of the cummerbund. One or more of the cummerbund sections **128** and **130** may be connected to the front carrier **124** using a cummerbund buckle **140** disposed within a pocket.

[0047] In one implementation, the front carrier **124** is connected to the back carrier **126** at the proximal end **116** with shoulder portions, including a first shoulder strap **136** and a second shoulder strap **138**. The shoulder straps **136** and **138** may each be adjustable. For example, the first shoulder strap **136** and the second shoulder strap **138** may each loop through a shoulder buckle forming an adjustment portion. The adjustment portions may be secured, for example, using paired hook and loop fasteners. In one implementation, the shoulder straps **136** and **138** each include a shoulder pad with a low to enhance comfort and provide additional load distribution.

[0048] In the context of a tactical vest, the tactical system **100** may include a cutaway system permitting single-handed release. In one implementation, the cutaway system includes a plurality of buckles, which when released permit the tactical vest to be easily and quickly removed. The plurality of buckles may include, for example, the shoulder buckles **142** and **144** and the cummerbund buckle(s) **140**. In one implementation, the plurality of buckles are connected to a quick-release tab **146** via corresponding wires. When the quick-release tab **146** is pulled, each of the plurality of buckles is automatically disengaged, facilitating the removal of the tactical vest. The cutaway system may be reengaged and the tactical vest reassembled by reengaging the plurality of buckles. In one implementation, the wires are housed within the interior **104** and in communication with the buckles using one or more pockets or openings.

[0049] In one implementation, each of the plurality of buckles are connected to the cutaway system via one or more wires to release the buckles upon pulling of the quick-release tab **146**. For example, the cummerbund buckle **140** may include a female buckle portion and a male buckle portion. The female buckle portion includes an opening adapted to receive a body of the male buckle portion and slots to releasably engage buckle arms of the male buckle portion. In one implementation, a releasing member is connected to a wire of the cutaway system and configured to displace the buckle arms. When the quick-release tab **146** is pulled, the wires of the cutaway system are displaced, which displaces the releasing member and in turn the buckle arms, thereby disengaging the male buckle portion from the female buckle portion. The shoulder buckles **142** and **144** may include similar features and functionality.

[0050] For a detailed description of the outer layer **106**, reference is made to FIG. 5. In one implementation, the outer layer **106** is a composite of a first layer **204** facing an outside environment **200** and a second layer **206** facing in a direction **202** inwardly toward the interior **104**. Stated differently, the first layer **206** is backed by the second layer **206**. The first layer **204** and the second layer **206** form a lightweight hybrid material with superior abrasion, tear, and fire resistance characteristics that provides load carriage support and improved durability, particularly in load carriage points **208**, such as corners, edges, seams, high wear areas, and exposed areas.

[0051] In one implementation, the first layer **204** is a synthetic fabric outer layer. For example, the first layer **204** may be a nylon fabric, such as a high-performance Nylon-6,6. The weight of the nylon fabric of the first layer **204** may

be between approximately 200 and 1000 denier, and in one particular example implementation, the weight is about 500 denier.

[0052] The second layer **206** may be a backing layer made from a high strength, damage resistant material. More particularly, the second layer **206** may be made of high tenacity polymer fibers, including, but not limited to, aramid fibers, para-aramid fibers, para-aramid synthetic fibers, high performance polyethylene fibers, and/or other materials having a high tensile strength-to-weight ratio. Examples of materials from which the second layer **206** may be made include, without limitation: Kevlar®, Twaron, terephthaloyl chloride (TCI), and high molecular weight polyethylene (HMWPE). Other suitable materials include polybenzobisoxazole fibers (PBO), ballistic nylon, and/or heat resistant aramid fiber products such as Nomex® and Protera® fabrics. The fibers of the second layer **206** may have a tensile strength greater than about 2000 MPa (or greater than about 7 grams per denier) and an elastic modulus greater than about 60 GPa.

[0053] In one implementation, high performance polymer fibers for the second layer **206** are utilized in the form of a woven fabric, including for example woven fabrics generally used for repelling and trapping hand driven sharp objects such as knives, awls, shanks and the like. An exemplary woven fabric for the second layer **206** may be constructed from yarn of anywhere between about 100 and 1200 denier and aerial densities in the range of 3 to 10 ounces per square yard (“OSY”). For example, fabrics constructed of yams in the 200 to 300 denier range, and aerial densities in the 3 to 4 OSY range may be used where the tactical system **100** is a ballistic accessory, such as a pouch, small duffel, backpacks, or the like. Alternatively, where the tactical system **100** is heavier, such as a large suitcase or equipment bag, larger yams in the 700 to 1200 denier range and densities in the 7 to 10 OSY range may be used. In one particular example implementation where the tactical system **100** is a tactical vest, the first layer **204** is made from a 500-denier nylon and the second layer **206** is made from 200-400-denier para-aramid fibers.

[0054] The woven fabric of the second layer **206** may be formed of a relatively tight, puncture resistant weave, comprising, for example, at least 40 fibers per inch in a first (warp) direction and at least 40 fibers per inch in a second (fill) direction. In one implementation, the second layer **206** comprises a weave with between 60 and 72 fibers per inch in both the warp and fill directions. In addition, the fabric of the second layer **206** may be formed by tightly weaving multi-filament yarns to obtain a warp yarn “density” or “cover” in excess of 100 percent at the center of the fill yarn and a fill yarn density or cover in excess of 75 percent as measured between two warp ends. Such ultra-tight weaves may comprise in excess of 100 fibers per inch in the warp and fill directions and filament crossovers in the range of about 50,000,000 (fifty million) filament crossovers per square inch up to 90,000,000 (ninety million) filament crossovers per square inch.

[0055] In one example, the second layer **206** is Dupont™ Kevlar® Correctional™, which is an extremely tight weave utilizing filaments one fourth the size of comparable materials. Another suitable commercially available material is a woven puncture resistant product sold under the trademark TURTLESKIN by Warwick Mills, Inc., of New Ipswich, N.H. The weight of the second layer **206** may range between approximately 200 and 300 denier where the tactical system

100 includes lightweight personal gear such as packs and pouches and between approximately 500 and 1000 denier where the tactical system **100** includes larger, heavier articles, such as large suitcases and equipment duffels.

[0056] In one implementation, the first layer **204** and the second layer **206** are consolidated into a unitary composite fabric using any suitable technique such as lamination, bonding, stitching, and/or the like. Suitable bonding methods include, for example, the use of various types of adhesives, such as air-drying adhesives, chemically setting adhesives, radiation activated adhesives such as ultraviolet (UV) activated dental adhesives, hot-melt adhesives, and pressure sensitive adhesives. An adhesive may be pre-applied on at least one of the first layer **204** or the second layer **206** or separately introduced during a lamination process. In one implementation, the first layer **204** and the second layer **206** are laminated under heat and pressure using a solid, polymer based thermoplastic adhesive, such as a polyamide, polyester, elastomeric urethane, or polyolefin polymer. For example, the first layer **204** may be laminated to the second layer **206** using a dry, non-woven mat, or web of a polymer-based thermoplastic or other thermoplastic adhesives. The first layer **204** and the second layer **206** and the thermoplastic adhesive may be supplied from respective adjacent spools and fed through a laminating machine with the thermoplastic web sandwiched between the first layer **204** and the second layer **206**.

[0057] As noted above, the first layer **204** and the second layer **206** may also be consolidated using various types of Pressure Sensitive Adhesives, also referred to as “PSA”s. PSAs are distinguished from most other types of adhesives in that they bond on contact, rather than through a solidifying process such as evaporation, chemical reaction, or melting. PSAs are usually based on an elastomer compounded with a suitable tackifier (e.g., a rosin ester). The elastomers may include those based on natural rubber, Nitriles, Butyl rubber, Acrylics, Styrene block copolymers, vinyl ethers, Ethylene-vinyl acetate, and various silicon rubbers. In one implementation, the PSA comprises an acrylic adhesive such as a permanent assembly tape or an acrylic sheet.

[0058] The strength of the second layer **206** makes the composite material of the outer layer **106** particularly beneficial in the load carriage points **208** of the tactical system **100**. Examples of the load carriage points **208** include, without limitation, corners of ammunition pouches, fragmentation pouches, radio communication pouches, armor pockets in armor plate carriers, and/or load carriage points. In ballistic vests and ballistic armor carriers the outer layer **106** also increases longevity and strength of load carriage points **208**, particularly once the outer layer **106** is sewn through. Seams can be further strengthened by folding the seam over to double or triple thickness prior to stitching. In addition, any tears or de-laminations in the first layer **204** of the outer layer **106** can be temporarily field repaired by re-attaching the damaged first layer **204** to the intact second layer **206** using a fast setting adhesive such as Cyanoacrylate liquid adhesive. Alternatively, if portions of the first layer **204** are missing or worn away making re-attachment impractical, the intact second layer **206** can instead simply be left exposed, and if desired, temporarily disguised using a suitably colored paint or ink marker.

[0059] Although the composite fabric of the outer layer **106** has been described primarily in terms of the first layer

204 and the second layer **206**, the outer layer **106** may comprise additional or different layers. For example, the outer layer **106** may comprise a plurality of outer layers similar to the first layer **204**, or a plurality of backing layers similar to the second layer **206**, or multiple layers of each. In addition, the layers may be arranged in various configurations, such as two backing layers of the second layer **206** on one side of a single outer layer of the first layer **204**, or a sandwich configuration with an outer layer of the first layer **204** on either side of one or more backing layers of the second layer **206**. The composite fabric of the outer layer **106** may also be combined with various other material layers, such as a liner made of a breathable or insulative type of fabric or material. The additional materials may be consolidated or attached to the first layer **204** and/or the second layer **206** using any of the above described methods and materials. Further, various other combinations of layers and materials are contemplated as foreseeable, and intended to fall within the scope of the high performance composite fabric of the outer layer **106**.

[0060] Turning to FIG. 6, in one implementation, the ballistic plate **112** includes a body with a strike face **300** disposed opposite a back face **302**. A peripheral edge **304** extends along a periphery of the body between the strike face **300** and the back face **302**. A non-peripheral area **306** of the ballistic plate **112** extends from a center of each of the strike face **300** and the back face **302** towards a peripheral area disposed near the peripheral edge **304**.

[0061] As can be understood from FIGS. 7-11B, in one implementation, a ballistic plate cover **400** may wrap around at least a portion of the peripheral area of the ballistic plate **112** to provide additional protection against back face deformation and/or side spall created by augmentation of the ballistic plate **112**. Back face deformation occurs when a ballistic projectile impacts the strike face **300** and causes the back face **302** to deform or bulge outwardly. Side spall occurs when a ballistic projectile impacts the peripheral area of the ballistic plate **112** such that shrapnel from the ballistic projectile impact and/or debris of material from the impacted portion of the ballistic plate **112** potentially penetrates the flexible body armor **110** and/or injure the wearer.

[0062] The ballistic plate cover **400** further enhances area coverage and range of motion for increased ergonomics and performance, while providing additional ballistic coverage beyond the ballistic plate **112** in a direction outward from the strike face **300** and in a direction outward from the peripheral edge **304**. In one implementation, the ballistic plate cover **400** provides approximately one inch of additional ballistic coverage beyond the strike face **300** and approximately 0.5 inches of additional ballistic coverage beyond the peripheral edge **304**.

[0063] The ballistic plate cover **400** includes a body extending from a proximal end **402** to a distal end **404**. The body of the ballistic plate cover **400** may be made from a polyethylene material or other types of thermoplastic materials. For example, the body of the ballistic plate cover **400** may be made from a stretchable and elastic spandex material reinforced with a unidirectional and/or aramid material.

[0064] In one implementation, the body of the ballistic plate cover **400** includes a peripheral portion including side portions **406** extending proximally to a top portion **414**. The peripheral portion may have a variety of shapes mirroring a shape of the peripheral edge **304** of the ballistic plate **112**. For example, the peripheral portion may extend linearly

and taper inwardly in a proximal direction. More particularly, the peripheral portion **406** may include the side portions **406** extending parallel to each other and then tapering inwardly at tapered portions **412** until reaching the top portion **414**. The peripheral portion includes an inner peripheral surface **410**.

[0065] In one implementation, the body of the ballistic plate cover **400** includes a back portion **416** connected to the peripheral portion. For example, the back portion **416** may be connected at an edge of the peripheral portion, such that the back portion **416** is disposed inwardly from the side portions **406**, the tapered portions **412**, and/or the top portion **414**.

[0066] The back portion **416** includes an inner back surface **418**. In one implementation, the inner back surface **418** is disposed at an angle relative to the inner peripheral surface **410**. For example, the inner back surface **418** and the inner peripheral surface **410** may be disposed perpendicularly to each other. The inner back surface **418** and the inner peripheral surface **410** collectively form a receiving portion **420**, such as an open-ended slot or a channel, configured to receive the body of the ballistic plate **112**. In one implementation, the receiving portion **420** releasably engages the ballistic plate **112**. In another implementation, the receiving portion **420** is secured to the ballistic plate **112** with an adhesive or similar engaging mechanisms.

[0067] As shown in FIG. 8, in one implementation, the receiving portion **420** engages the ballistic plate **112**, such that at least a portion of the peripheral edge **304** is covered. In the example shown in FIG. 8, the peripheral portion of the ballistic plate cover **400** covers side portions and a proximal portion of the peripheral edge **304** with a distal portion left exposed. Further, the receiving portion **420** may engage the ballistic plate **112** such that at least a portion of the peripheral area of the strike face **300** and/or the back face **302** is covered. In the example shown in FIG. 8, the back portion **416** covers at least a portion of the peripheral area of the back face **302** along the portions of the peripheral edge **304** covered by the peripheral portion of the ballistic plate cover **400**.

[0068] As can be understood from FIG. 9, in one implementation, the body of the ballistic plate cover **400** further includes a bottom portion **422** of the peripheral portion disposed opposite the top portion **414** and a front portion **424** disposed opposite the back portion **416**. The front portion **424** is connected to the peripheral portion. For example, the front portion **424** may be connected at an edge of the peripheral portion, such that the front portion **424** is disposed inwardly from the side portions **406**, the tapered portions **412**, and/or the top portion **414** and parallel to the back portion **416**.

[0069] The front portion **424** includes an inner front surface **426** facing the inner back surface **418**. In one implementation, the inner front surface **426** is disposed at an angle relative to the inner peripheral surface **410** and parallel to the inner back surface **418**. For example, the inner back surface **418** and the inner front surface **424** may each be disposed perpendicularly to the inner peripheral surface **410**. The inner back surface **418**, the inner front surface **424**, and the inner peripheral surface **410** collectively form the receiving portion **420**.

[0070] As can be understood from FIG. 9, in one implementation, the receiving portion **420** engages the ballistic plate **112**, such that an entirety of the peripheral edge **304** is

covered. Further, the receiving portion 420 may engage the ballistic plate 112 such that an entirety of the peripheral area of the strike face 300 and/or the back face 302 is covered. In the example of FIG. 9, the back portion 416 covers an entirety of the peripheral area of the back face 302 and the front portion 424 covers an entirety of the peripheral area of the strike face 300. In one implementation, the body of the ballistic plate cover 400 defines an opening 428 exposing the non-peripheral area 306 of the ballistic plate 112.

[0071] Turning to FIGS. 10-11B, in one implementation, the body of the ballistic plate cover 400 further includes one or more middle portions 430 extending between the top portion 414 and the bottom portion 414. The middle portion 430 may be engaged to the inner back surface 418 and/or the inner front surface 424. The middle portion 430 provides further structural support to maintain the ballistic plate 112 within the receiving portion 420 of the ballistic plate cover 400.

[0072] As discussed herein, the body of the ballistic plate cover 400 may have a variety of shapes, including, but not limited to, rectangular, circular, elliptical, triangular, polygonal, angles, contoured, and/or the like. In the example shown in FIG. 10-11B, the body of the ballistic plate cover 400 has a rectangular shape with the peripheral portion including side portions 406 extending linearly between the top portion 414 and the bottom portion 422. Portions or an entirety of the body of the ballistic plate cover 400 may be made from aramid/unidirectional material and/or a stretchable fabric composite material and may be stitched or otherwise connected or be of unitary construction. In one implementation, the ballistic plate cover 400 includes a soft armor padding disposed in one or more places and made from a similar material to the flexible body armor 110.

[0073] For a detailed description of an example of the flexible body armor 110, reference is made to FIGS. 12-20. As can be understood from FIG. 12, in one implementation, ballistic filler for the flexible body armor 110 includes a first panel 500 having a first subpanel 502 and a second subpanel 504, a second panel 506, and a third panel 508.

[0074] Referring to FIG. 13, in one implementation, the first panel 500 of the ballistic filler of the flexible body armor 110 includes the first subpanel 502 as a plurality of layers of woven fabric generated from UHMWPE fiber and a second subpanel 504 as a plurality of layers of unidirectional laminate. In one particular implementation, the first subpanel 502 comprises three layers 510 of JPS 17517 woven fabric, and the second subpanel 504 comprises four layers 512 of SB117 unidirectional laminates. Tape 514 holds the layers 510 of the first subpanel 502 together and holds the layers 512 of the second subpanel 504 together.

[0075] Turning to FIG. 14, in one implementation, the first subpanel 502 is stitched directly to the second subpanel 504 to form the first panel 500. The first subpanel 502 is backed by the second panel 504. Tape 516 disposed at one or more of the edges may hold the first subpanel 202 to the second subpanel 204 during stitching.

[0076] In one implementation, the stitching comprises a first set of stitching lines 518 parallel to each other and oriented in a first direction and a second set of stitching lines 520 parallel to each other and oriented in a second direction. The first direction may be perpendicular to the second direction to form a quilted square pattern. In one implementation, the first direction and the second direction are both diagonal relative to the proximal end 116 and the distal end

118. Other stitching methods and arrangements are contemplated. In one implementation, a first edge stitching 522 and a second edge stitching 524 extend around a perimeter of the first panel 500 at a distance from the edge (e.g., approximately $\frac{1}{8}$ inches and $\frac{1}{8}$ inches from the edge with $\pm \frac{1}{8}$ inches apart).

[0077] Turning to FIG. 15, the second panel 506 of the ballistic filler for the flexible body armor 110 is shown. In one implementation, the second panel 506 is formed from a plurality of layers 526 of unidirectional laminates. In one implementation, the plurality of layers 526 is fifteen layers of SB115. The plurality of layers 526 may be held together with tape 528 for stitching. In one implementation, the stitching comprises a first stitching line 530 and a second stitching line 532. The stitching lines 530 and 532 form an "X" shape across the plurality of layers 526 from the proximal end 116 to the distal end 118, with the ends spaced an equal distance such that if the proximal and distal end points of the stitching lines 530 and 532 were joined a rectangle would be formed.

[0078] FIG. 16 illustrates the third panel 508 of the ballistic filler for the flexible body armor 110 formed by a plurality of layers 534 of unidirectional laminates. In one implementation, the plurality of layers 534 is two layers of SB117. The plurality of layers 534 are not sewn and are held together with tape 536 for combining with the first panel 500 and the second panel 506.

[0079] As shown in FIG. 17, a ballistic arrangement of the ballistic filler for the flexible body armor 110, includes the first panel 500 backed by the second panel 506, which is backed by the third panel 508, such that the subpanel 502 of the woven fiber is the layer most proximal to the strike face towards the outer layer 106. FIG. 18 illustrates the ballistic filler for the flexible body armor 110 with the first panel 500, the second panel 506, and the third panel 508 connected using proximal closure stitching 538 and distal closure stitching 540 disposed at the proximal end 116 and the distal end 118, respectively. In one implementation, the closure stitching 538 and 540 comprises two passes of three inch O/C 1.5 inches left and right. As shown in FIG. 19, edge tape 542 may be applied to a portion of a periphery of the ballistic filler for the flexible body armor 110 for heat sealing.

[0080] FIG. 20 illustrates example operations 600 for manufacturing a ballistic filler for the flexible body armor 110. In one implementation, an operation 602 forms a first panel comprising a first subpanel of woven fabric and a second subpanel of unidirectional laminate. An operation 604 stitches the first subpanel to the second subpanel. An operation 606 stitches a plurality of layers of unidirectional laminate to form a second panel, and an operation 608 forms a third panel from a plurality of layers of unidirectional laminate. An operation 610 forms a ballistic filler from the first panel, the second panel, and the third panel, and an operation 612 stitches the ballistic filler at a proximal end and a distal end. An operation 614 applies edge tape to at least a portion of a periphery of the ballistic filler, and an operation 616 heat seals the ballistic filler to form the flexible body armor 110.

[0081] The ballistic filler for the flexible body armor 110 provides numerous advantages over monolithic and other hybrid designs. For example, the flexible body armor is comfortable, durable, flexible, lightweight, and provides increased performance, including resistance to ballistic pen-

etration, back face deformation performance, resistance to mechanical fatigue, and resistance to fragmentation threat, and the like.

[0082] In one implementation, the ballistic filler of the flexible body armor **110** has distinct regions. At least one region comprises a stitch consolidated assembly of one or more plies of woven fabric generated from UHMWPE yarn disposed in front of one or more flexible ballistic ply structures generated from a high strength yarn.

[0083] The flexible ballistic ply structures may be, for example, a resin impregnated woven fabrics, unidirectional laminates, multi-axial fabrics, and/or the like. In one implementation, the flexible ballistic ply structures can be generated using high strength yarns including, without limitation, aromatic polyamides such as poly(p-phenylene terephthalamide), poly(metaphenylene isophthalamide), p-phenylenebenzobisoxazole, polybenzoxazole, polybenzothiazole, aromatic unsaturated polyesters such as polyethylene terephthalate, aromatic polyimides, aromatic polyamideimides, aromatic polyesteramideimides, aromatic polyetheramideimides and aromatic polyesterimides or copolymers of any of the above mentioned classes of materials, and ultra high molecular weight polyethylene, or any combination of these yarns. In another implementation, the flexible ballistic ply structures are woven fabrics generated from high strength fiber are woven structures produced using yarns containing aromatic polyamides including poly(p-phenylene terephthalamide), poly(metaphenylene isophthalamide), p-phenylenebenzobisoxazole, polybenzoxazole, polybenzothiazole, aromatic unsaturated polyesters such as polyethylene terephthalate, aromatic polyimides, aromatic polyamideimides, aromatic polyesteramideimides, aromatic polyetheramideimides and aromatic polyesterimides or copolymers of any of the above mentioned classes of materials or any combinations of these yarns.

[0084] In one implementation, at least one region of the ballistic filler of the flexible body armor **110** comprises one or more plies of unstitched ballistic ply structures generated from a high strength yarn, which may have a tenacity greater than about 7 grams/denier. The unstitched ballistic ply structures may include woven fabrics, resin impregnated woven fabrics, unidirectional laminates, or multi-axial fabrics generated from yarns containing aromatic polyamides including poly(p-phenylene terephthalamide), poly(metaphenylene isophthalamide), p-phenylenebenzobisoxazole, polybenzoxazole, polybenzothiazole, aromatic unsaturated polyesters such as polyethylene terephthalate, aromatic polyimides, aromatic polyamideimides, aromatic polyesteramideimides, aromatic polyetheramideimides and aromatic polyesterimides or copolymers of any of the above mentioned classes of materials, and ultra high molecular weight polyethylene or any combinations of these yarns.

[0085] Any one of the stitch consolidated assemblies of plies of the ballistic filler for the flexible body armor **110** is achieved using any stitching thread and any type of stitching method to achieve through-thickness connectivity of the plies, including chain stitching or lock stitching to secure all plies in the assembly together. In one implementation, a stitching pattern that is uniform across the surface of the entire assembly is used. Such a uniform stitching pattern may be, for example, a grid pattern (quilt pattern), co-linear rows of stitching, concentric circles, a spiral, and/or the like. In another implementation, the stitching pattern of any one of the stitch-consolidated assembly of plies is not uniform

across the surface of the entire assembly. As described herein, the ballistic filler for the flexible body armor **110** includes a stitched consolidated region and a free ply region. In one implementation, the weight fraction of the stitch consolidated region is no greater than 50% the overall weight of the ballistic filler. Further, the ballistic filler of the flexible body armor **110** includes at least one region of woven fabric stitched directly to unidirectional fabric.

[0086] As can be understood from FIGS. **21-24**, the flexible body armor **110** may be generated for the natural shape of a female wearer, while providing a full range of motion and support and eliminating excess compression on the breast tissue.

[0087] As can be understood from FIGS. **21** and **22**, in one implementation, a female shape **700** of the flexible body armor **110** is formed from an upper portion **702**, a set of lateral portions **704** and a lower portion **706**. The set of lateral portions **704** connect the upper portion **702** to the lower portion **706**.

[0088] In one implementation, the upper portion **702** includes a set of upper side edges **716** each extending distally from a top edge **714**. The upper side edges **716** may further extend along a contour to enhance ergonomics and accommodate the anatomy of a female wearer. For example, the upper side edges **716** may each extend inwardly from the top edge **714** in a direction generally towards a central axis **730** extending from the proximal end **116** of the flexible body armor **110** to the distal end **118**. The top edges **714** are connected by a center edge **710**, which may be a contoured. In one implementation, the center edge **710** contours distally from each of the top edges **714** until reaching a central point. The top edges **714** may contour from the upper side edges **716** into the center edge **710**.

[0089] In one implementation, each of the upper side edges **716** is connected to the lateral portion **704** at an upper valley **718**. An edge of each of the lateral portions **704** extends from the upper valley **718** in a direction generally outwardly away from the central axis **730** to a lower valley **722**. In one implementation, each of the lateral portions **704** includes a lateral peak **720**. The edge of each of the lateral portions **704** may include a first edge extending from the upper valley **718** to the lateral peak **720** and a second edge extending from the lateral peak **720** to the lower valley **722**. The first edge, lateral peak **720**, and the second edge may extend outwardly at angle along a line, forming a generally straight line angling from the upper valley **718** to the lower valley **722**. In another implementation, the first edge contours from the upper valley **718** to the lateral peak **720**, and the second edge contours from the lower valley **722** to the lateral peak **720**.

[0090] The lower portion **706** is connected to the upper portion **702** with the set of lateral portions **704**. In one implementation, the lower valleys **722** of the lateral portions **704** connect to a set of outwardly extending edges **724** of the lower portion **706**. Stated differently, the lower valley **722** connects the second edge of the lateral portion **704** to the outwardly extending edge **724**. The outwardly extending edges **724** may each be disposed at an angle relative to lower side edges **726** of the lower portion **706** and extend outwardly from the lower valleys **722** to the lower side edges **726**. In one implementation, the lower side edges **726** each extend distally from the outwardly extending edges **724** to a bottom edge **712**, which may extend horizontally between the lower side edges **726**.

[0091] Each of the lateral portions 704 may include lateral darts extending from the edge of the lateral portion 704 inwardly and distally. In one implementation, the lateral darts form cup portions 728. As can be understood in FIG. 22, the lateral darts are each adapted to displace a ballistic hard plate 300 to eliminate excess compression on the breast tissue of the female wearer. The lateral darts displace a proximal end the body of ballistic plate 112 in a direction away from the inner surface 108 of the front carrier 124 and the flexible body armor 110 (i.e., a direction away from the wearer). As such, a central axis 732 of the ballistic plate 112 is disposed at an angle relative to the central axis 730 of the flexible body armor 110. The front carrier 124 may similarly incorporate the female shape 700, such that the ballistic plate 112 is maintained in the front carrier pocket 134 in an orientation generally parallel to the body of the wearer, preventing projectiles from moving through the ballistic protection into the body of the wearer, while eliminating compression on the breast tissue by displacing the proximal end of the ballistic plate 112 outwardly.

[0092] Turning to FIG. 23, in one implementation, the one or more panels 708 includes a first panel 734 having one or more layers and a second panel 736 having one or more layers. The first panel 734 includes an inner surface 738 and the second panel 736 has an inner surface 740. In one implementation, the lateral darts are each formed from one or more raised pleats. For example, a first raised pleat 42 may be formed along the inner surface 738 of the first panel 734, and a second raised pleat 744 may be formed along the inner surface 740 of the second panel 736. The raised pleats 742 and 744 may each extend from a center area 746 of a respective cup portion 728 to a periphery 750. In one implementation, the raised pleats 742 and 744 form free space 748 of the cup portion 728 between the first panel 734 and the second panel 736. The raised pleats 742 and 744 may each be formed using a plurality of sewing lines extending from the center area 746 to the periphery 750. In one implementation, the lateral darts formed from the raised pleats 742 and 744 extend from the center area 746 to an edge of the lateral portion 704 of the flexible body armor 110 disposed between the upper valley 718 and the lower valley 722. After the raised pleats 742 and 744 are formed, the first panel 734 may be attached to the second panel 736, for example, using sewing, lamination (e.g., with an adhesive,) to form the flexible body armor 110.

[0093] FIG. 24 illustrates example operations 800 for manufacturing a female tactical vest. In one implementation, an operation 802 forms a front carrier having an upper portion connected to a lower portion with opposing lateral darts. An operation 804 forms a first panel from a plurality of layers of ballistic material. An operation 806 stitches a plurality of sewing lines along the first panel to form a first set of raised pleats, which may include one or more raised pleats. An operation 808 forms a second panel from a plurality of layers of ballistic material. An operation 810 stitches a plurality of sewing lines along the second panel to form a second set of raised pleats, which may include one or more raised pleats. An operation 812 stitches or otherwise attaches the first panel to the second panel with the first set of raised pleats oriented relative to the second set of raised pleats to form a cup in a soft ballistic armor. An operation 814 orients the soft ballistic armor along the front carrier, for example, in an interior of the front carrier.

[0094] Turning to FIGS. 25-27, it will be appreciated that the ballistic frame 114 may be disposed behind or in front of and loose from the flexible body armor 110 within the interior 104. The ballistic frame 114 includes a frame body 900 configured to improve overall load carriage performance of the tactical system 100 by providing a rigid platform to add weight. The frame body 900 may be disposed loose or secured within the interior 104 to provide structural support to the outer layer 106, the inner layer 108, and/or other aspects of the tactical system 100. In one implementation, the frame body 900 is configured to support a load. The frame body 900 reduces fatigue by improving the structure of the tactical system 100 by retaining the flexible body armor 110 in a configuration that prevents bunching and provides support to the ballistic plate 112 to improve edge hit protection. The frame body 900 may be made from a polyethylene material, an ABS plastic material, an aramid fiber material, and/or other ballistics force dissipating material.

[0095] The ballistic frame 114 is unattached to the flexible body armor 110 within the interior 104, such as the front carrier pocket 134 where the tactical system 100 is a tactical vest. The ballistic frame 114 absorbs and otherwise dissipates energy from an impact of a projectile against the ballistic plate 112 and/or the flexible body armor 110. The ballistic frame 114 may be disposed in the interior 104 together with the flexible body armor 110 or without the flexible body armor 110.

[0096] In one implementation, the flexible body armor 110 is disposed within the interior 104 of the tactical system 100 and made from a force dissipating material. The ballistic frame 114 is disposed within the interior of the ballistic vest adjacent to and detached from the soft body armor component. The ballistic frame 114 may be disposed within the interior 104 between the outer layer 106 and the flexible body armor 110 or between the inner layer 108 and the flexible body armor 110. Stated differently, the ballistic frame 114 may be backed by the flexible body armor 110 or the flexible body armor 110 may be backed by the ballistic frame 114.

[0097] The ballistic frame 114 thus provides an additional protective layer to the flexible body armor 110 in some implementations, further dissipating the forces generated by the impact of a ballistic projectile and/or shrapnel against the flexible body armor 110. Another aspect of the ballistic frame 114 is a structural component that provides a framework to the tactical system 100 that is exterior to the flexible body armor 110 and provides structural integrity and prevents sagging of the outer layer 106 and other portions of the tactical system 100.

[0098] The frame body 900 may be solid or have one or more openings 902 therethrough. The openings 902 may have a variety of shapes including, but not limited to, circular, rectangular, elliptical, triangular, hexagonal, star, trapezoidal, angled, and/or contoured. The openings 902 may be symmetrical along at least one axis 906 of the frame body 900. For example, the openings 902 may include a first set of openings vertically aligned and a second set of openings vertically and/or horizontally aligned, with the first set of openings and the second set of openings being symmetrical.

[0099] The frame body 900 may have a variety of shapes, for example, asymmetrical, symmetrical, circular, square, rectangular, hexagonal, contoured, angled, and/or polygo-

nal. The frame body **900** may be planar or extend along one or more angles or curves. Further, the frame body **900** may be sized and shaped based on a coverage area for protecting the wearer. The coverage area may include a deltoid area, a bicep area, a neck area, a yoke area, a collar area, and/or an extremity area.

[0100] In one implementation, the frame body **900** extends between a peripheral edge shaped based on ergonomics of the wearer and/or to mirror a shape of the flexible body armor **110** and/or the ballistic plate **112**. For example, the frame body **900** may have a shape similar to the female shape **700**. The peripheral edge may include a bottom edge **910** connected to a top edge **912** with a set of side edges **908**. In one implementation, a width of the frame body **900** tapers proximally toward the top edge **912**. Stated differently, the peripheral edge may include tapered edges **914** connecting the side edges **908** to the top edge **912**. In another implementation, the side edges **908** extend proximally beyond the top edge **912** and peaks **916** curve to connect to the side edges **908** to the top edge **912**.

[0101] While the present disclosure has been described with reference to various implementations, it will be understood that these implementations are illustrative and that the scope of the disclosure is not limited to them. Many variations, modifications, additions, and improvements are possible. More generally, implementations in accordance with the present disclosure have been described in the context of particular examples. Functionality may be separated or combined in blocks differently in various implementations of the disclosure or described with different terminology. These and other variations, modifications, additions, and improvements may fall within the scope of the disclosure as defined in the claims that follow.

1. A tactical system comprising:
 - an inner layer;
 - an outer layer disposed opposite the inner layer and forming an interior, the outer layer comprising a composite fabric;
 - one or more load carriage points disposed along the outer layer;
 - a first layer of the composite fabric disposed at the one or more load carriage points, the first layer comprising a woven synthetic fabric, the first layer facing outwardly in a direction away from the inner layer; and
 - a second layer of the composite fabric backing the first layer at the one or more load carriage points, the second layer comprising a woven fabric of para-aramid fibers, an attachment of the first layer to the second layer providing a structural support to the one or more load carriage points.
2. The tactical system of claim 1, wherein the woven synthetic fabric is nylon having a weight of at least 200 denier and the woven fabric of para-aramid fibers of the second layer has a weight of at least 100 denier and an aerial density of at least 3 ounces per square yard.
3. The tactical system of claim 1, wherein the attachment of the first layer to the second layer includes at least one of: laminating the first layer to the second layer under heat pressure using a thermoplastic bonding agent; or using an adhesive.
4. The tactical system of claim 1, wherein the one or more load carriage points includes at least one of a pouch, a pocket, a corner, or a seam.

5. The tactical system of claim 1, wherein the outer layer and the inner layer are deployed in at least one of: a tactical vest; a tactical garment; or tactical equipment.

6. The tactical system of claim 1, wherein the outer layer is exposed to an outside environment.

7. The tactical system of claim 1, wherein the weight of the first layer is 500 denier and the weight of the para-aramid fibers is 200 denier.

8. The tactical system of claim 1, wherein the weight of the first layer is less than 1000 denier and the weight of the para-aramid fibers is less than 1200 denier.

9. A tactical system comprising:

- an outer layer exposed to an outside environment, the outer layer comprising a composite fabric;
- one or more load carriage points disposed along the outer layer;
- a first layer of the composite fabric disposed at the one or more load carriage points, the first layer comprising a woven synthetic fabric, the first layer facing the outside environment; and
- a second layer of the composite fabric backing the first layer at the one or more load carriage points, the second layer comprising a woven fabric of para-aramid fibers, an attachment of the first layer to the second layer providing a structural support to the one or more load carriage points.

10. The tactical system of claim 9, wherein the woven synthetic fabric is nylon having a weight of at least 200 denier and the woven fabric of para-aramid fibers of the second layer has a weight of at least 100 denier and an aerial density of at least 3 ounces per square yard.

11. The tactical system of claim 9, wherein the attachment of the first layer to the second layer includes laminating the first layer to the second layer under heat pressure using a thermoplastic bonding agent.

12. The tactical system of claim 9, wherein the weight of the first layer is 500 denier and the weight of the para-aramid fibers is 200 denier.

13. The tactical system of claim 9, wherein the weight of the first layer is less than 1000 denier.

14. The tactical system of claim 9, wherein the weight of the para-aramid fibers is less than 1200 denier.

15. The tactical system of claim 9, wherein the aerial density of the para-aramid fibers is less than 10 ounces per square yard.

16. The tactical system of claim 9, wherein the weave of the para-aramid fibers has at least 40 fibers per inch in a warp direction and at least 40 fibers per inch in a fill direction.

17. The tactical system of claim 9, wherein the weave of the para-aramid fibers has a warp yarn density in excess of 100 percent and a fill yarn density in excess of 75 percent.

18. The tactical system of claim 9, wherein the weave of the para-aramid fibers has filament crossovers of at least 50 million filament crossovers per square inch.

19. The tactical system of claim 9, wherein the filament crossovers are less than 90 million filament crossovers per square inch.

20. The tactical system of claim 9, wherein the para-aramid fibers have a tensile strength of at least 2000 MPa and an elastic modulus of at least 60 GPa.

* * * * *