



US009058838B2

(12) **United States Patent**
Widergren

(10) **Patent No.:** **US 9,058,838 B2**
(45) **Date of Patent:** ***Jun. 16, 2015**

(54) **MULTIMEDIA STORAGE SYSTEMS AND METHODS**

20/005 (2013.01); *G11B 20/00659* (2013.01);
G11B 20/00746 (2013.01);
(Continued)

(75) Inventor: **Robert D. Widergren**, Morgan Hill, CA (US)

(58) **Field of Classification Search**
CPC G06F 21/00; G11B 20/21
USPC 713/193
See application file for complete search history.

(73) Assignee: **MO-DV, INC.**, Campbell, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,015,886 A 5/1991 Choi et al.
5,584,023 A 12/1996 Hsu

(Continued)

FOREIGN PATENT DOCUMENTS

WO WO 2008/012699 A1 1/2008

OTHER PUBLICATIONS

International Search Report and Written Opinion, PCT/US05/15269, Dec. 18, 2006, 4 pgs.

(Continued)

Primary Examiner — Dant Shaifer Harriman
(74) *Attorney, Agent, or Firm* — Blakely, Sokoloff, Taylor & Zafman LLP

(21) Appl. No.: **13/236,505**

(22) Filed: **Sep. 19, 2011**

(65) **Prior Publication Data**

US 2012/0011375 A1 Jan. 12, 2012

Related U.S. Application Data

(63) Continuation of application No. 12/397,295, filed on Mar. 3, 2009, now Pat. No. 8,027,471, which is a continuation of application No. 10/848,224, filed on May 17, 2004, now Pat. No. 7,508,943.

(60) Provisional application No. 60/471,151, filed on May 16, 2003, provisional application No. 60/502,851, filed on Sep. 12, 2003.

(51) **Int. Cl.**
G11B 20/00 (2006.01)
G06F 21/10 (2013.01)


(Continued)

(52) **U.S. Cl.**
CPC *G11B 20/0021* (2013.01); *G06F 21/10* (2013.01); *G06F 21/6236* (2013.01); *G06F 21/78* (2013.01); *G06F 2221/2107* (2013.01); *G06F 2221/2153* (2013.01); *G11B 20/00086* (2013.01); *G11B 20/00115* (2013.01); *G11B*

(57) **ABSTRACT**

An article of manufacture includes a machine-readable medium that stores a multimedia content file in a first format and multiple program sets. Each program set is a version of software that, when executed by a respective electronic system, produces the multimedia content file in a second format for use in the respective electronic system. A first program set is compatible with a first operating system executed by a first electronic system and a second program set is compatible with a second operating system executed by a second electronic system. The second operating system is distinct from the first operating system.

15 Claims, 3 Drawing Sheets



- (51) **Int. Cl.**
G06F 21/62 (2013.01)
G06F 21/78 (2013.01)
G11B 20/12 (2006.01)
- (52) **U.S. Cl.**
 CPC *G11B 20/00884* (2013.01); *G11B 20/1254*
 (2013.01); *G11B 2220/61* (2013.01)

(56) **References Cited**
 U.S. PATENT DOCUMENTS

5,677,953	A	10/1997	Dolphin	
5,812,204	A	9/1998	Baker et al.	
5,828,897	A	10/1998	Kirsch et al.	
5,923,757	A	7/1999	Hocker et al.	
5,936,945	A	8/1999	Shibata et al.	
5,940,506	A	8/1999	Chang et al.	
6,041,386	A	3/2000	Bello	
6,052,711	A	4/2000	Gish	
6,079,047	A	6/2000	Cotugno et al.	
6,233,347	B1	5/2001	Chen et al.	
6,240,184	B1	5/2001	Huynh et al.	
6,285,398	B1	9/2001	Shinsky et al.	
6,295,645	B1 *	9/2001	Brewer	717/178
6,385,667	B1	5/2002	Estakhri et al.	
6,396,937	B2	5/2002	Chen et al.	
6,400,826	B1	6/2002	Chen et al.	

6,499,056	B1	12/2002	Kitamura et al.	
6,590,604	B1 *	7/2003	Tucker et al.	348/14.13
6,735,676	B1	5/2004	Kanda et al.	
6,820,055	B2	11/2004	Saindon et al.	
6,904,493	B2 *	6/2005	Chiao et al.	711/103
6,993,509	B2	1/2006	Vidich et al.	
7,009,655	B2 *	3/2006	Huang	348/441
7,149,721	B1 *	12/2006	Sites et al.	705/59
7,295,608	B2	11/2007	Reynolds et al.	
2002/0025141	A1	2/2002	Matsumoto et al.	
2004/0052233	A1	3/2004	Skog et al.	
2004/0228169	A1	11/2004	Widergren	
2005/0005149	A1	1/2005	Hirota et al.	
2005/0216548	A1	9/2005	Wormington et al.	
2006/0150257	A1	7/2006	Leung et al.	
2006/0202232	A1	9/2006	Takami	
2007/0008422	A1	1/2007	Huang	

OTHER PUBLICATIONS

Toshiba Press Releases, "Toshiba's SD-Card-Based Digital Rights Management System Opens Up Full Potential of Digital Content Distribution Market," Jul. 17, 2003, 2 pgs.
 International Search Report and Written Opinion, PCT/US2010/039911, Dec. 10, 2010, 8 pages.
 International Search Report and Written Opinion, PCT/US2011/051587, Dec. 22, 2011, 12 pages.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3

MULTIMEDIA STORAGE SYSTEMS AND METHODS

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. application Ser. No. 12/397,295, filed Mar. 3, 2009, which is a continuation of U.S. application Ser. No. 10/848,224, filed May 17, 2004, now U.S. Pat. No. 7,508,943, entitled "Multimedia Storage Systems and Methods," which claims priority to U.S. Provisional Application No. 60/471,151, filed May 16, 2003, and U.S. Provisional Application No. 60/502,851, filed Sep. 12, 2003, all of which are incorporated herein by reference in their entirety.

BACKGROUND

Multimedia cards (MMCs) and other storage card formats are well known today as a means of providing external memory capacity for storing information of interest to a user. Such cards are used principally in handheld devices, such as digital cameras, cell phones and personal digital assistants (PDAs).

A disadvantage associated with these cards is their reliance on the software loaded in the handheld device to process (e.g., decode, expand, etc.) the content (e.g., digital photographs, video games, etc.) that the cards contain. Such processing programs must be in the memory of the handheld device to which the cards are attached. This means that the handheld device must have sufficient memory to retain the processing program. It also means that the handheld device must have a processing program capable of decoding/decrypting the particular encoding/encryption format of the content in the card.

SUMMARY OF THE INVENTION

According to an embodiment of the invention, an article of manufacture includes a machine-readable medium. The medium has stored thereon a first data set in a first format and a second data set that when executed by an electronic system is operable to produce the first data set in a second format.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a logical block diagram of a memory card according to an embodiment of the present invention.

FIG. 2 is a logical block diagram of a memory portion of the card of FIG. 1 according to an embodiment of the present invention.

FIG. 3 is a logical block diagram of an electronic system operable to cooperate with the card of FIG. 1 according to an embodiment of the present invention.

DETAILED DESCRIPTION

An embodiment of the present invention enables many different devices to present a non-compressed, compressed, expanded and/or encrypted multimedia file stored on a single-format storage device. This may be achieved by storing the multimedia file, along with the player/decoder and/or decryption programs required to process the file, on the same device.

FIG. 1 illustrates a memory card 10 according to an embodiment of the present invention. The memory card includes a controller 20, which may be implemented by hardware or software, operable to communicate with a presenta-

tion device (not shown in FIG. 1) via an interface portion 30 that, in an embodiment, includes at least one contact pin known in the art.

The controller 20 is coupled to a memory portion 40. Depending on the nature of the memory portion 40, the card 10, in varying embodiments, may be characterized, for example, as a read-only memory (ROM) or Read/Write (e.g., flash) card.

The controller 20 is further coupled to an identification register 80 that stores a unique identification number, such as a manufacturer's serial or batch number (discussed below in greater detail), associated with the card 10. Each component of the card 10 is disposed within or on a housing 90.

Preferably, the card 10 is of a standard physical form factor used in many hardware devices such as cell phones, personal digital assistant devices, cameras, etc. As such, these hardware devices are enabled to read data off the card 10 because of existing industry input/output standards, such as the MMC form factor specified by the MMC association.

Prior to being loaded into the memory portion 40, a multimedia content file 50, such as, for example, an audio clip, video clip, or video game, is encoded and/or encrypted according to an appropriate scheme or schemes. For ease of discussion, the following exemplary description will assume that both encryption and encoding are applied to a given multimedia file, although embodiments of the present invention contemplate application of only one of encoding or encryption, as appropriate.

After being encoded and encrypted, the file 50, as illustrated in FIG. 2, is loaded into the memory portion 40. Also as illustrated in FIG. 2, a plurality of player/decoder program files 60a-60c and a plurality of decryption program files 70a-70c may also be loaded into the memory portion 40. In an alternative embodiment, the card may include a plurality of memory portions and the file 50 may be stored on a memory portion separate from the memory portion on which the programs 60, 70 are stored. Moreover, it should be appreciated that more than one file 50 and corresponding programs 60, 70 may be stored on a single card 10.

Each program 60a-60c is a different version of the same decoder software and is compatible with a respective different type of electronic system with which the card 10 may cooperate, and/or is compatible with a respective different operating system employable by an electronic system. Moreover, the decoder, of which each program 60a-60c is a different version, corresponds to the scheme used to encode the file 50, and is thus required in order to decode the file 50. Similarly, each program 70a-70c is a different version of the same decryption software and is compatible with a respective different type of electronic system with which the card 10 may cooperate, and/or is compatible with a respective different operating system employable by an electronic system. Moreover, the decryption software, of which each program 70a-70c is a different version, corresponds to the scheme used to encrypt the file 50, and is thus required in order to decrypt the file 50.

Although only three decoder/player programs 60a-60c and decryption programs 70a-70c are illustrated in FIG. 2, it should be appreciated that the number of decoder/player programs 60 and decryption programs 70 that the memory portion 40 may store is limited only by practicability. As such, the memory portion 40 may store decoder/player programs 60 and decryption programs 70 compatible with all commercially available handheld-device operating systems, enabling the card 10 to cooperate with a wide variety of devices equipped to present visual and/or auditory information.

The controller **20** may be employed to read and write content, such as the file **50**, stored on the card **10**. This controller **20** is useful because the applications envisioned for an embodiment of the card **10** may involve multiple read cycles (e.g., in the many thousands), and many fewer write cycles (e.g., of one to one hundred times). Such applications may further require reading and writing the identification number of the card **10** as the player/decoder program files **60** and/or decryption program files **70** are loaded on those cards **10** of the read/write type.

During manufacture of the card **10**, the manufacturer assigns a code thereto. If the card **10** is rewritable, the card **10** typically is assigned an individual serial number code. If the card **10** is of the masked ROM type, the card **10** typically is given a batch code. Each of these codes may be stored in a register included in the card **10**. During the process of loading the programs **60**, **70** on a card **10**, the manufacturer's code associated with that card **10** is linked to the file **50** and/or programs **60**, **70** by associating the code with the file **50** and/or programs **60**, **70**. As such, and as further discussed below, if the code stored in a register of a card does not correspond to the code linked to the programs **60**, **70** stored thereon, the programs **60**, **70** will optionally decode, not decode and/or decrypt the content stored on the card. This feature of an embodiment of the invention serves to discourage unauthorized copying of programs **60**, **70** and files **50** from card to card. In this manner, the card **10**, itself, can perform the function of a dongle.

FIG. **3** illustrates cooperation between the card **10** and an electronic system **100**, such as a handheld device, according to an embodiment of the present invention. The card **10** may be physically coupled (e.g., docked) to the electronic system **100** by means of an interface **101**. Optionally, the card **10** may be coupled to the electronic system **100** (associated) by means of a wireless interface **101**. As such, the interface **101** is coupleable to each component of the card **10**. The electronic system **100** may include a processor **110**, a memory **120** and a display device **130**, such as a liquid crystal display (LCD). An operating system (OS) **140**, such as, for example, Palm OS®, Microsoft® Pocket PC, Symbian, or Linux, is stored in the memory **120**.

Handheld device operating systems typically contain instructions enabling an inserted or associated memory card to run an autoexecute/autoload program on the device. According to an embodiment of the present invention, the card **10** is partially formatted using a file allocation table (FAT) format per the standard for an MMC card. Using this file format, a directory **150** (FIG. **2**) is made and named for a host device (e.g., PocketPC 2577), such as the electronic system **100** with which the card **10** will cooperate. This directory **150** includes at least one autoloading program **160** compatible with the particular type of electronic system **100** and may include several programs **160**, each of which may be compatible with a respective different electronic system **100** and/or operating system associated therewith.

In operation, according to an embodiment of the invention, a user of the electronic system **100** docks the card **10** with the interface **101**. In such an embodiment, at least a portion of the housing **90** is receivable by the interface **101**.

An autoloading program **160**, compatible with the system **100** and executed by the processor **110**, queries the register **80** in order to verify that the number stored therein matches the number associated with the file **50** and/or programs **60**, **70** during the prior encoding and/or encryption of the file **50**. Alternatively, the autoloading program **160** may be executed by the controller **20** in order to perform this verification function. If the numbers do not match, indicating that the

contents of the memory **40** have been copied to the card **10** without authorization, the loading process is optionally halted. If, however, the numbers do match, the program **160** identifies at least one characteristic of the system **100**, such as, for example, the type of operating system **140** employed by the system **100**, and verifies desired read/write capabilities associated with the card **10**.

The electronic system **100** may then present on the display **130** a menu (not shown) of multimedia content stored on the card **10** that may be available to the user. Using an input device, such as, for example, a stylus or cursor control, the user then selects the desired entertainment content for presentation.

A decoder program **60** and decryption program **70**, each corresponding to the selected file **50** and the detected OS **140** and/or type of electronic system **100**, are loaded into the memory **120** for execution by the processor **110**. In turn, and in a known manner, execution of the programs **60** and **70** by the processor **110** produces a decoded and decrypted version of the file **50** for presentation to the user.

In an embodiment of the invention, the video and/or audio decoding algorithm **60** supplied with the file **50** may be an improved version that is less complex and may process information faster with higher throughput than the algorithms sometimes found on the existing electronic systems **100** themselves (i.e., an originally installed decoder, if any). The supplied algorithm **60** may have a higher video throughput than the algorithm on the electronic system **100**.

In an embodiment, the decoder/player programs **60** and decryption programs **70** are stored from the card **10** into the memory **120** of the electronic system **100** during operation, and thus do not go through a formal program install. As such, the programs **60**, **70** disappear from the memory **120** when the player/decoding and/or decryption process is terminated/completed or the card **10** removed. The OS **140** of the electronic system **100** allocates the used program memory back into a scratch pool on completion. As such, the decoder/player programs **60** and decryption programs **70** are not accessible to all but the most sophisticated programmers for copying. This feature is advantageous in that it makes consumer pirating of the content file **50** more difficult.

In an embodiment of the invention, the decoder program **60** will function as a "rolling" decoder. This means that when the file **50** is compressed it will be so with a unique code-table format. The code-table format is changed with respect to each file **50** compressed. There may be a finite set of different code tables (e.g., 128), each set up for a particular version of the decoder program **60**. Consequently, only a particular decoder program **60** that is loaded on a card **10** can be used to decompress an associated file **50** stored on the card **10**. As such, each compression format serves as a form of encryption and the decoder program **60** serves as the key.

Similarly, a rolling decrypter may be employed in an embodiment of the invention. In a rolling decrypter implementation, the physical encryption process is changed with respect to each file **50** encrypted. This is alternatively or additionally implemented by interchanging data fields within the compressed data in a random or approximately random pattern specified by a key that is used by the decrypter program to place data fields in the correct order.

In an embodiment of the present invention, protection of content is achieved through the use of systematically or randomly encrypted occasional bytes. This is useful because decryption of all content, decoder, or controller software requires significant processor power. For example, if video content is encrypted, the processor power required for decoding is significant. An embodiment of the present invention

includes encrypting only occasional pieces of the file **50** that the decoder and or player-decoder code recognizes (hidden message) in order to play the following frame/short audio/video sequence correctly.

This encryption is thus, in an embodiment, a multi-level multi-key encryption (rolling decoder feature) comprising a 1st level "soft" encryption that is done to all bits of digital content and a 2nd level "hard" encryption done to selected portions of the file **50** (e.g. select bytes of video key-frames). This method reduces processing overhead and lowers the impact of decryption on playback efficiency. This method further makes a user's playback of any straight (undecrypted) content impossible. Attempts by a user to play back content without the rolling decoder player program will not yield playback.

In an embodiment, rather than use a single key, a set of keys is used to encrypt/decrypt each content file **50**. An algorithm is used to select the correct key from the set at any given time. Further, using multiple keys increases the difficulty in reverse engineering the encryption algorithm.

Another benefit of this on-the-fly decryption is that the entire file **50** is never decrypted at once into memory **120** and can thus not be copied easily by a user into another unencrypted file for subsequent non-encrypted playback.

The rolling decoder is separate from 128-bit rolling encryption/decryption and also watermarking technologies already developed and in the public domain and which may, in an embodiment, also be utilized. To illustrate, the decoder for video "A" on one card production run would not decode the video on the video "B" card run even assuming that the encryption was broken. This is because the key set and/or encryption technique and content encoder algorithm are changeable for each released card product through the concept of the rolling decoder. This is possible since each product is shipped with a matching player program in binary form on the same card. This technique reduces the impact of unauthorized acquisition or discovery of a previous card's key set or content encoder algorithm.

In varying embodiments, the above-discussed encryption and/or digital rights methods can be used in combination or alone.

Rewritable storage cards can be written to multiple times (100,000 to 1 million) before they will fail. In a "write once" or "write multiple" card, a controller circuit within the card restricts the writing to one time or a few times (i.e., 2 to 100,000) only. In a masked memory card, the data is etched into the memory at the manufacturing site and write circuitry is not provided.

Where a write once controller circuit is used, the controller circuit restricts the writing to only once. There are controller circuits that count the write cycles and limit them to a particular number. MMC cards of this class are utilized in an embodiment of the present invention.

In contrast, as an example, one can write present-day flash memory many times, almost without limit, and the controller circuit allows this functionality. Out of every batch of flash memory that should allow tens of thousands of rewrites, there is defective memory produced that can be written to only 1000 times or fewer. This memory is typically considered defective and thrown away. As such this lower-capability memory is available at a lower cost than the fully capable memory. An embodiment of the present invention uses these lower-capability flash memory cards to reduce cost. In this case, the controller circuit is implemented as a processor **20** executing a program adjusted to limit the number of times that the card **10** can be written.

An embodiment of the present invention employs a controller program or circuit **20** that utilizes memory **40** capable of only a limited number of write operations otherwise considered defective because the memory **40** can only accept a limited number of write cycles or has a low write-data rate. The feature of the card **10** capable of more than one write operation is particularly useful to video and audio content vendors. For example, in the music business, when some audio, or alternatively video cards don't sell, the cards can be returned by the distributor or retailer for re-loading of a file **50** and decoder **60** with an alternative, preferably a newer, more saleable, set of audio or video tracks with decoder. For these cards returned for reprocessing, new content loading can be used to put a different, likely newer song or video on the same card. This reprocessing and reloading of additional and/or essentially different content and decoder allows vendors and distributors to reuse the cards **10** to lower their costs.

The feature of a controller **20** that allows only a limited number of write operations is further useful because a limited write capability is part of the digital rights management strategy of industries such as music, video, gaming, etc. Compliance with the digital rights management strategy of these industries may be accomplished by placing a third software component on the card **10**. This software is called content protection software (CPS). It is placed on the card **10** so people cannot easily copy the content in a first card to a second card and have the content play correctly from the second card.

One function of the CPS is that it is self-enabled to detect that it has been placed on a flash memory card (a card capable of multiple writes). When this state is detected by the CPS code, the CPS code may interact with the content decoder program such that the card content is prevented from playing on a hardware device.

With reference to video encoding, the well-known Sissler Video Correction Fully Automatic Encoding Algorithm (SVCFAEA) takes the raw video and makes it easier to encode using motion blur technologies. With SVCFAEA, if there is not enough power in the computer to process the video playback at full frame speed, then the video content is modified so it visually looks nearly the same and yet takes less memory and can be decoded at visually pleasing speeds. In an embodiment of the present invention, the SVCFAEA algorithm is used to modify the file **50** to be loaded on the card **10** by using a series of varying filters. These filters are applied by measurement of the amount of quantization to be retained in the file **50**. This process is designed to reduce the data rate required of the decoder such that frames are not dropped by the decoder during the decoding operation. The SVCFAEA process is particularly useful as it is an automated manufacturing process as opposed to a manual process. This reduces the cost of manufacture of the files **50**.

Preparation of a card **10** carrying a file **50** may be achieved, in an embodiment, in a particular manner. An application is assessed to determine the appropriate type of storage card (e.g., flash or read only). A permutation of a rolling decoder may be selected. Audio/video in digital form accessible to a PC workstation may be obtained. The Video may be preprocessed to acceptable dimensions. Nominally this may be 240 lines by 320 pixels. The frame rate may be reduced to one half of the original with a target of 15-20 frames per second. The complexity of the video may be assessed with respect to both intra-frame detail and inter-frame motion. Frame-by-frame filtering may be performed where deemed appropriate. Brightness may be adjusted by computing the histogram of the luma pixels and adding sufficient bias to each pixel such that no more than 5%, for example, of all luma pixels are

above a nominal saturation level. The audio/video sequence may be encoded with rate control imposed. The average required quantization levels may be recorded. Periods of heavy quantization (combining of individual data items into fewer data items to reduce heavy decoding requirements) may be ascertained. These may be candidate areas for further filtering. The encoded data may be transferred to a test card with an embedded AC player program. Using a handheld device, the video may be played. The complete video may be monitored, paying particular attention to the heavily quantized areas, brightness saturation and audio quality. Parameters may be readjusted and the coding/testing process from above may be repeated.

It should be appreciated that implementations of embodiments described herein need not be limited to memory storage cards. For example, embodiments of the invention may be realized in the use of compact discs (CDs), digital video discs (DVDs), any flash or read only (non-volatile memory), floppy disks, Flash Drives, smart cards or any storage media that supports digital storage. Consequently, the electronic storage system **100** may alternatively include personal computers, workstations, or any other device operable to process digital media.

It should further be appreciated that an embodiment of the invention may be achieved by modulating a signal to carry the multimedia file **50**, along with the player/decoder and/or decryption programs required to process the file.

The preceding discussion is presented to enable a person skilled in the art to make and use the invention. Various modifications to the disclosed embodiments will be readily apparent to those skilled in the art, and the generic principles herein may be applied to other embodiments and applications without departing from the spirit and scope of the present invention. Thus, the present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features disclosed herein.

What is claimed is:

1. An electronic system, comprising:

a first processor;

memory coupled to the first processor;

operating system software stored in the memory and executable by the first processor to display a menu of multimedia content stored in a multimedia content file; and

a removable flash memory device, coupled to the first processor by an interface, the removable memory device having stored thereon:

a first data set in a first encoded format, the first data set including the multimedia content file;

a second data set, which when executed by a processor in an electronic system produces the first data set in a second decoded format for use in the electronic system,

wherein the second data set includes decoder software and decryption software for decoding and decrypting the first data set, and an autoloading program that is executable by the processor and is compatible with the operating system software;

a first code stored on the removable memory device, separate from the first data set and the second data set, to identify the removable memory device; and

a second code in the first data set or the second data set, wherein the second data set, when executed by the processor, compares the first code to the second code, wherein the removable flash memory device includes a code stored in a register included in the removable flash

memory device and linked to the first and second data sets, such that if the code stored in the register does not correspond to a code linked to the decoder software and decryption software of the second data set, the decoder software and decryption software will not decode or decrypt the first data set.

2. The electronic system of claim **1**, wherein the electronic system is a handheld electronic device.

3. The electronic system of claim **1**, wherein the electronic system is a handheld electronic device having a wireless interface and a display.

4. The electronic system of claim **1**, wherein the use in the electronic system includes displaying content in the multimedia content file on a display of the electronic system.

5. The electronic system of claim **1**, wherein the second data set includes a plurality of autoloading programs to be executed by one of a plurality of operating systems of a plurality of electronic systems.

6. The electronic system of claim **1**, wherein the first encoded format is one of a plurality of encoded formats for a plurality of operating systems of a plurality of electronic systems; wherein the decoder software is one of a plurality of decoder software to be executed by one of the plurality of operating systems of the plurality of electronic systems; and wherein the decryption software is one of a plurality of decryption software to be executed by one of the plurality of operating systems of the plurality of electronic systems.

7. The electronic system of claim **1**, wherein the decoder software is a first software program to decompress the first data set, and wherein the decryption software is a second software program to encrypted bytes of the first data set.

8. The electronic system of claim **1**, wherein the removable flash memory device has a standard physical form factor usable in one of a cell phone, a personal digital assistant device, and a camera.

9. The electronic system of claim **1**, wherein the decoder software functions as a "rolling" decoder to decode a first level "soft" encryption that is done to all bits of the first encoded format and a second level "hard" encryption done to selected portions of the first encoded format.

10. A method of operating an electronic system having a processor and memory storing operating system software that is executable by the processor, the method comprising:

receiving a removable flash memory device at an interface, the removable flash memory device having stored thereon:

a first data set in a first encoded format, the first data set including a multimedia content file;

a second data set, which when executed by a processor in an electronic system produces the first data set in a second decoded format for use in the electronic system,

wherein the second data set includes decoder software and decryption software for decoding and decrypting the first data set, and an autoloading program that is executable by the processor and is compatible with the operating system software;

executing the second data set, in conjunction with the operating system software, to produce the first data set in the second decoded format for use in the electronic system;

storing a first code on the removable memory device, separate from the first data set and the second data set, to identify the removable memory device; and

storing a second code in the first data set or the second data set, wherein executing the second data set includes comparing the first code to the second code, wherein the removable flash memory device includes a code stored

9

in a register included in the removable flash memory device and linked to the first and second data sets, such that if the code stored in the register does not correspond to a code linked to the decoder software and decryption software of the second data set, the decoder software and decryption software will not decode or decrypt the first data set.

11. The method of claim **10**, including preventing execution of at least one of the decoder software and decryption software if the first code does not match the second code.

12. The method of claim **10**, wherein the use in the electronic system includes displaying content in the multimedia content file on a display of the electronic system.

13. An electronic system, comprising:

a first processor;

memory coupled to the first processor;

operating system software in the memory and executable by the first processor; and

a removable memory device, coupled to the processor by an interface, the removable memory device having stored thereon:

a first data set in a first format, the first data set including a multimedia content file; and

a second data set, wherein the second data set is a version of software that, when executed by a respective electronic system, produces the first data set in a second format for use in the respective electronic system, wherein the second data set includes a first autoload program version executable by a first processor in a

10

first electronic system utilizing a first operating system, and a second autoload program version that is distinct from the first software version and that is executable by a second processor in a second electronic system utilizing a second operating system that is distinct from the first operating system, wherein the autoload program checks an individual code identifying the removable memory device and stored on the removable memory device with a code linked to the first data set and stored on the removable memory device, and halts execution of the autoload program if the code identifying the removable memory device does not match the code linked to the first data set.

14. The electronic system of claim **13**, wherein the code is a serial number code or a batch code identifying the removable flash memory device, and is stored in a register included in the removable flash memory device.

15. The electronic system of claim **13**, wherein the autoload program checks an individual code identifying the removable flash memory device and stored on the removable memory device with a code linked to the decode software and stored on the removable memory device, and a code linked to the decryption software and stored on the removable memory device, and halts execution of the autoload program if the code identifying the removable flash memory device does not match the code linked to the decode software or the code linked to the decryption software.

* * * * *