



(51) International Patent Classification:

E06B 3/46 (2006.01) E04B 2/74 (2006.01)
E04F 13/08 (2006.01)

(21) International Application Number:

PCT/EP2018/071405

(22) International Filing Date:

07 August 2018 (07.08.2018)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

102018000004060 29 March 2018 (29.03.2018) IT

(71) Applicant: ECLISSE S.R.L. [IT/IT]; VIA SERNAGLIA, 76, 31053 PIEVE DI SOLIGO (IT).

(72) Inventor: DE FAVERI, Luigi; VIA VITTORIA, 114, 31020 REFRONTOLO (IT).

(74) Agent: MODIANO, Micaela; MODIANO & PARTNERS, Via Meravigli, 16, 20123 Milano (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,

(54) Title: METHOD FOR OBTAINING A VERTICAL OR HORIZONTAL PROFILED ELEMENT FOR THE INTERCONNECTION OF PLASTERBOARD PANELS TO WALLS AND ELEMENT OBTAINED WITH SUCH METHOD




Fig. 2

(57) Abstract: A method for obtaining a vertical or horizontal profiled element (1) for the interconnection of plasterboard panels (2) to walls (10), in particular to plasterboard walls that can be applied to in-wall frames for retractable sliding doors or for the provision of drywall dividing walls. The method entails a continuous machining of a metallic lamina by punching or drawing or rolling obtained by using two rollers, one acting as a die and the other acting as a punch, so as to obtain on the metallic lamina a plurality of holes (13), which are uniformly distributed according to a series of mutually parallel rows.



MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

METHOD FOR OBTAINING A VERTICAL OR HORIZONTAL
PROFIED ELEMENT FOR THE INTERCONNECTION OF
PLASTERBOARD PANELS TO WALLS AND ELEMENT OBTAINED
WITH SUCH METHOD

5 The present application relates to a method for obtaining a vertical or horizontal profiled element for the interconnection of plasterboard panels to walls, in particular to plasterboard walls that can be applied to in-wall frames for retractable sliding doors or for the provision of drywall dividing walls, and to the element obtained with such method.

10 Nowadays it is known to provide door frames which involve the use of an in-wall frame, positioned inside a wall, in which a door or a panel is slideably associated and which is also known as a "retractable door".

 This solution allows to reduce the space occupation of the door in a room by virtue of the possibility to make it slide into the in-wall frame: it is
15 thus possible to use the space adjacent to the door, which would instead be occupied by doors of the type hinged laterally to a frame.

 In the known art, the in-wall frame embedded in the wall is usually constituted by a frame that comprises a plurality of horizontal and vertical profiled elements, a pair of front posts, an abutment post and a rear post, all
20 connected by horizontal crossmembers made of metal plate, preferably aluminum, the whole defining a containment case of the panel or of the door.

 The components of the in-wall frame are usually provided by way of machining operations that substantially involve the folding of a metallic
25 lamina.

 Above the casing there protrudes, along an axis which is longitudinal to the casing and is extended on the opposite side with respect to the containment casing, a rail which is concealed by a profiled element that is commonly called an "upper crossmember" or "pocket header" or also
30 "fanlight".

Trolleys are associated slideably within the track and are coupled to the upper edge of the door or panel in order to allow the sliding thereof in and out of the in-wall frame.

Usually the abutment post that acts as a terminal for the abutment of the front edge of the door or panel is associated with the end of the rail that is not associated with the vertical posts.

Such conventional door frames thus use metallic profiled elements that can be mounted together and are sold for example in kit form for assembly.

To this end this same applicant is owner of Italian utility model no. 278468 which discloses a framework for walls or panels made of plasterboard which is constituted by a first element which is adapted to act as an upper crossmember for the front and rear upright members and also by a rail/guide for sliding trolleys for supporting a door, said framework being furthermore constituted by brackets for centering an upper framework and for supporting the walls or panels made of plasterboard.

Although this solution is valid, it exhibits a drawback in that, in general, in such solutions, which are also known as in-wall frames for drywall buildings, the external finish of the wall is obtained by superimposing plasterboard panels on the structure which are then affixed by way of using conventional affixing systems such as screws, both self-tapping and non-self-tapping.

Such method entails the necessity of having to make holes in the metal plate that constitutes the horizontal crossmembers arranged to support the plasterboard panels, such metal plate having a smooth perforation base.

Therefore a certain pressure has to be exerted, which entails an initial bending of the profiled element, which increases with the increase of the thrust that the installation technician has to exert using the screw gun, thus making perforation of the metal difficult.

It should be noted moreover that the plasterboard panels are basically

panels adapted to fill in the metallic structures or frames, both on one side and on the other, and they are provided by way of a mixture of plaster or the like that is compressed so as to reach a determined thickness and is inserted in a sandwich-like manner between two layers of cellulose material,
5 commonly paper.

Such paper covering to all intents and purposes forms a skin and stratifies the layer of plaster, the result obtained is a panel that is commonly called "plasterboard panel".

The layer of plaster ensures thickness and insulation, but on its own it
10 would break easily, and when screwing it to the structure it would crumble at the fastening point. The compactness of the panel is ensured by the two coverings in paper, and the hold at the fastening point is given by the fastening of the head of the screw, which compresses the skin or layer of paper onto the underlying plaster. It is therefore necessary, for an optimal
15 and secure fastening, that the thin paper layer does not break.

In order to overcome the mentioned drawbacks, some makers provide structures in which profiled elements are used with reduced thicknesses in order to be perforated more easily; this however entails a weakening of the profiled element, on which adapted ribbing has to be provided in order to
20 stiffen it.

The result that is obtained, although functional, is however a compromise between rigidity/bending and thickness, and in any case it entails a complexity of construction in the profiled element and a higher implementation cost for it.

25 Other makers provide systems in which horizontal crossmembers are used to support and fasten the plasterboard panels, and these crossmembers are made of wood instead of metal.

Such solutions can help in the fastening operation, in that wood can be perforated easier than metal; however, wooden crossmembers are more
30 flexible than metallic solutions as it is not possible to produce them with

greater thicknesses than the latter, in order to ensure that the entire structure can be accommodated in the cross-section/thickness of the wall and at the same time is able to arrange the sliding door or panel inside it.

Another drawback that can be found in the prior art is constituted by
5 the fact that the consistency of plasterboard panels has not a high-density and therefore makes such material friable, while instead the underlying metallic horizontal crossmembers have a high surface hardness and have a smooth perforation base on which the plasterboard panels lay.

It can therefore happen that the tip of the fastening screw subjected to
10 pressure during screwing can laterally slide, thus being screwed not perpendicular to the crossmember, with the consequence that it has to be screwed in deeper in order to ensure that the head of the screw is co-planar with the surface of the facade outside the wall; this brings the risk that the tip of the screw might protrude too far inside the in-wall frame and damage
15 the door or panel when it slides and is accommodated inside the compartment.

Systems are known in which horizontal crossmembers are used, in which the resting surface of the panels is embossed so as to create, by way of a calendering operation, an incision of a desired pattern: this solution
20 only allows to try to prevent the tip of the screw from sliding beyond a certain measurement determined by the pattern obtained, but it does not prevent the screw from sliding and it therefore does not solve the problem mentioned earlier, while contributing to increasing the structural complexity of the profiled element and the corresponding implementation costs.

25 The aim of the present invention is therefore to solve the above mentioned technical problems, eliminating the drawbacks in the cited prior art and hence providing a method for obtaining a profiled element that allows to achieve the optimal and rapid support/placement and/or the fastening of plasterboard panels adapted to define the sides of an in-wall
30 frame for doors or panels that slide in-wall, and which can be installed in

frames for providing plasterboard walls.

Within this aim, an object of the invention is to provide a profiled element that offers a considerable simplicity of construction and installation and which at the same time allows to obtain the fastening of normal
5 plasterboard panels stably, durably and quickly.

Another object of the present invention is to obtain a profiled element whose correct coupling to the panel is obtained irrespective of the ability of the installation technician, who has only to screw the screws in any position of the profiled element without exerting particular pressure.

10 Another object is to provide a usable profiled element to which to fasten plasterboard walls, which has an optimal functionality and strength and which moreover allows to have a particularly reduced thicknesses.

Another object is to provide a profiled element that enables a facilitated fastening thereto of plasterboard panels even by people with no
15 special training and with conventional or standard means for screwing that are easy available.

Another object is to provide a profiled element that allows to apply plasterboard panels thereto while safeguarding their structural integrity.

Another object is to provide an invention that is structurally simple,
20 which can be provided with conventional systems and machines, and which has low cost.

This aim and these and other objects which will become better apparent hereinafter are achieved by a method for obtaining a vertical or horizontal profiled element 1 for the interconnection of plasterboard panels
25 2 to walls 10, characterized in that it provides for a continuous machining of a metallic lamina by punching or drawing or rolling obtained by using two rollers, one acting as a die and the other acting as a punch, so as to obtain on said metallic lamina a plurality of holes 13, which are uniformly distributed according to a series of mutually parallel rows, in said method the side or
30 diameter $D1$ and the center distance $D2$ between two of said holes 13 that

are mutually closer and the thickness S of said planar surface 12 being defined by the following proportions: $D2 \geq S$, $0.4 \leq S \leq 1.5$ and $D1 \leq 3S$.

Further characteristics and advantages of the invention will become better apparent from the detailed description of a particular but not exclusive embodiment, illustrated by way of non-limiting example in the accompanying drawings, wherein:

Figure 1 is a partially cross-sectional perspective view of an in-wall frame for doors or panels;

Figure 2 is a perspective view from above of a horizontal crossmember;

Figure 3 is a detail showing the holes provided on the profiled element;

Figure 4 is a perspective view from below of a horizontal crossmember;

Figure 5 is a detail showing the holes provided on the profiled element, in the previous figure;

Figure 6 is a plan view of a part of the horizontal crossmember in the region with the holes;

Figure 7 is a sectional view along the line VII-VII in Figure 6;

Figure 8 is a cross-sectional view taken along the line VIII-VIII in Fig. 6;

Figure 9 is a detail showing the holes in a plan view;

Figure 10 is an exploded view of a profiled element, a panel, and a screw;

Figures 11 to 15 are cross-sectional views of the step of inserting a screw into a hole.

In the exemplary embodiments that follow, individual characteristics, given in relation to specific examples, may actually be interchanged with other different characteristics that exist in other exemplary embodiments.

With reference to the figures, the reference numeral 1 generally

designates a profiled element with which plasterboard walls or panels 2 can be associated.

The profiled element 1 can be constituted by one or more horizontal 3 or vertical 4 profiled elements, by one or more front posts 5, by one or more abutment posts 6, by one or more rear posts 7, by one or more horizontal crossmembers 8, by one or more upper crossmembers 9 for the rear posts 7, front posts 5 and abutment posts 6 and also by a support for a rail/guide (not shown) for sliding trolleys (not shown) with which sliding doors or leaves (not shown) are associated, all made of metal plate.

10 In the specific embodiment, the use is shown of a profiled element 1 in its various forms used to achieve the support/placement and/or the fastening of plasterboard panels 2 adapted to define the walls 10 of an in-wall frame 11 for doors or panels which can slide in-wall or which can be installed in frames for providing plasterboard walls.

15 In the specific embodiment shown, the upper crossmember 9 furthermore connects the abutment post 6 which is fixed to the opposite end from the rear post 7, and the front posts 5 are arranged approximately at the same distance between the rear posts 7 and the front posts 5.

20 The rear posts 7 and the front posts 5 are transversely connected by the horizontal crossmembers 8 and are positioned at a vertical distance from each other such as to divide the length of the rear post 7 and front posts 5 into approximately identical parts.

25 The method allows to obtain, starting from a metallic lamina, a profiled element 1 that has, in each one of its embodiments, the horizontal 3 or vertical 4 profiled element, the front post 5, the abutment post 6, the rear post 7, the horizontal crossmember 8, the upper crossmember 9, a planar surface 12 on which a plurality of holes 13 is provided, which are uniformly distributed according to a series of mutually parallel rows.

30 The holes 13, which are through holes, can be obtained by way of a step of perforating the planar surface 12, which is obtained by way of

punching or even by drawing, for example by way of a continuous machining which can be obtained by way of rolling and therefore using two rollers, one acting as a die (which determines the shape and the perforation of the metallic lamina so as to obtain the various holes 13), and the other
5 acting as a punch (which determines the external shape of each one of the holes 13).

In the specific embodiment shown the method also allows to obtain, for each horizontal crossmember 8 and at the longitudinal sides of the planar surface 12, one or more ridges or, as illustrated, two side edges or folds 15a,
10 15b and two wings 16a, 16b which give the horizontal crossmember 8 a substantially omega-like shape; such machining strengthens the profiled element and makes it less flexible.

As mentioned, the holes 13, which are obtained by deforming the planar surface 12, are distributed uniformly according to a series of
15 mutually parallel rows, so as to obtain, between two adjacent rows, an upper surface 17 which thus delimits each distinct row of laterally adjacent holes 13 and is substantially shaped like an upturned U which determines a surface that is inclined in the direction of the adjacent holes 13 that are arranged at its sides.

Each one of the holes 13 has, in plan view, a substantially conical
20 shape 18 which provides a guide for the needle-like tip 50 of a fastening screw 51 to move toward the axis 52 of the corresponding hole 13 if the tip is arranged either on the upper surface 17 or at the side walls or surfaces (indicated in clockwise order) 13a, 13b, 17a, 13c, 13d and 17b of each hole
25 13 and of the upper surface 17.

A perforated conical tab 20 protrudes, at each hole 13, at the lower surface 19 which is opposite the upper surface 17 and produces a localized increase in the thickness S of the planar surface 12.

In a plan view the holes 13 have, considering both the upper surface
30 17 and the lower surface 19, a substantially X-like shape.

The side or diameter D1 of each one of the holes 13 that are present on the planar surface 12 of the profiled element 1, and therefore of each one of the horizontal profiled element 3, the vertical profiled element 4, the front post 5, the abutment post 6, the rear post 7, the horizontal crossmember 8, the upper crossmember 9, is equal to or smaller than three times the measure of the thickness S of the planar surface 12 that constitutes the profiled element 1 [$D1 \leq 3S$].

The center distance D2 between two of the holes 13 that are mutually closer is equal to or greater than the thickness S of the profiled element 1 [$D2 \geq S$].

The thickness S of the profiled element 1 is comprised between 0.4 and 1.5 millimeters [$0.4 \leq S \leq 1.5$].

The presence and the particular arrangement of the holes 13 at the planar surface 12 enables an installation technician, once a plasterboard wall or panel 2 is placed alongside a profiled element 1, whether it is a horizontal 3 or vertical 4 profiled element, a front post 5, an abutment post 6, a rear post 7, a horizontal crossmember 8, an upper crossmember 9, to fasten it by positioning the screw in any point of the plasterboard wall or panel 2, making sure that the tip of that screw will intercept one of the holes 13 and therefore allows to achieve an optimal interconnection.

As illustrated in fact in Figures 11 and 12, if the tip 50 of a screw 51 is positioned at a hole 13, so as to affect one of the side walls or surfaces 13a, 13b, 17a, 13c, 13d, and 17b of the hole 13, it penetrates directly into the profiled element 1 and its head 53 compresses the skin or layer of paper onto the underlying plaster of the plasterboard panel 2 without breaking the thin paper layer.

If instead, as shown in Figures 13 to 15, the tip 50 of the screw 51 is positioned at an intermediate point between two adjacent holes 13 and therefore at the upper surface 17 i.e. when the displacement axis of the screw toward a hole 13 is greater, a minimal degree of offset is obtained in

any case and, by virtue of both the curved shape of the upper surface 17 and the shape structure of the holes 13, the tip 50 is guided toward the hole 13.

In this case too the head 53 of the screw 51, which has the characteristic trumpet shape, once screwed in, does not protrude from the surface of the panel 2 and does not break the surface layer/skin of the panel 2, thus ensuring a properly carried out fastening.

Thus it has been found that the method has achieved the set aim and objects, by allowing to obtain a profiled element that allows to achieve the optimal and rapid support/placement and/or the fastening of plasterboard panels adapted to define the sides of an in-wall frame for doors or panels that slide in-wall, and which can be installed in frames for providing plasterboard walls, such profiled element having at the same time a considerable simplicity of construction and installation and allowing to obtain the fastening of normal plasterboard panels stably, durably and quickly.

The needle-line tip 50 of the screws 51 for the plasterboard panels, in fact, once in contact with the region of the planar surface 12 that has the holes 13, finds a guiding portion whatever its initial positioning; since the needle-like tip 50 of the screw 51 never finds a planar surface, it always slides into the holes 13, which are close together so as not to shift the axis of the screw too far and this is a great screwing advantage for the installation technician.

The invention therefore resolves the problem of conveying the screw 51 to the nearest hole 13 to which its tip 50 is arranged, without such choice needing to be made by the installation technician, who has only to screw the screws 51 in any position, within the dimensions of the profiled element 1 underlying the panel that has the holes 13, without exerting particular pressure, and proceed until the head 53 of the screw 51 is flush with the surface of the panel 2; such operation is very light because high pressure is not needed to make a hole in the metal of the underlying profiled element 1.

The profiled element 1 furthermore maintains particularly reduced thicknesses and allows to fasten plasterboard walls thereto even by people with no special training and with conventional or standard means for screwing that are easily available.

5 The invention is of course susceptible of numerous modifications and variations, all of which are within the scope of the appended claims.

Thus it does not matter that the fastening needs to be carried out with a double plasterboard panel 2.

10 The materials used, as well as the dimensions that constitute the individual components of the invention, may of course be more pertinent according to the specific requirements.

The various means of achieving certain different functions certainly need not coexist only in the embodiment shown, but may be present in many embodiments, even if they are not shown. The characteristics indicated
15 above as advantageous, convenient or the like, may also be missing or be substituted by equivalent characteristics.

The disclosures in Italian Patent Application No. 102018000004060 from which this application claims priority are incorporated herein by reference.

20 Where technical features mentioned in any claim are followed by reference signs, those reference signs have been included for the sole purpose of increasing the intelligibility of the claim profiled elements and accordingly, such reference signs do not have any limiting effect on the interpretation of each element identified by way of example by such
25 reference signs.

CLAIMS

1. A method for obtaining a vertical or horizontal profiled element (1) for the interconnection of plasterboard panels (2) to walls (10), characterized in that it provides for a continuous machining of a metallic lamina by punching or drawing or rolling obtained by using two rollers, one acting as a die and the other acting as a punch, so as to obtain on said metallic lamina a plurality of holes (13), which are uniformly distributed according to a series of mutually parallel rows, in said method the side or diameter (D1) and the center distance (D2) between two of said holes (13) that are mutually closer and the thickness (S) of said planar surface (12) being defined by the following proportions: $D2 \geq S$, $0.4 \leq S \leq 1.5$ and $D1 \leq 3S$.

2. The method according to claim 1 for obtaining a profiled element (1), characterized in that the profiled element is constituted by one or more horizontal (3) or vertical (4) profiled elements, by one or more front posts (5), by one or more abutment posts (6), by one or more rear posts (7), by one or more horizontal crossmembers (8), by one or more upper crossmembers (9) for said rear posts (7), said front posts (5) and said abutment posts (6) and also by a support for a track/guide for sliding trolleys with which sliding doors or leaves are associated, all made of metal plate, which is used to achieve the support/resting and/or the fixing of plasterboard panels (2) that are adapted to define said walls (10) of an in-wall frame (11) for retractable sliding doors or panels or for installation in frames for the provision of plasterboard walls, said holes (13), being through holes that are obtained by way of a step of perforating a planar surface (12), which is present in said metallic lamina, obtained by punching or even drawing by a continuous machining which can be obtained by way of rolling and therefore using two rollers, one acting as a die, which determines the shape and the perforation of said metallic lamina so as to obtain said holes (13), and the other acting as a punch and determining the external shape of each one of said holes (13).

3. A vertical or horizontal profiled element (1) for the interconnection of plasterboard panels (2) to walls (10), characterized in that it has a planar surface (12) on which there is a plurality of holes (13) which are uniformly distributed according to a series of mutually parallel rows, the side or diameter (D1) of which is equal to or smaller than three times the measurement of the thickness (S) of said planar surface (12) which constitutes said profiled element (1) [$D1 \leq 3S$], the center distance (D2) between two of said holes (13) that are mutually closer being equal to or greater than the thickness (S) of said profile (1) [$D2 \geq S$], said thickness (S) being comprised between 0.4 and 1.5 millimeters [$0.4 \leq S \leq 1.5$].

4. The profiled element (1) according to claim 3, characterized in that it is constituted by one or more horizontal (3) or vertical (4) profiled elements, by one or more front posts (5), by one or more abutment posts (6), by one or more rear posts (7), by one or more horizontal crossmembers (8), by one or more upper crossmembers (9) for said rear posts (7), said front posts (5) and said abutment posts (6) and also by a support for a track/guide for sliding trolleys with which sliding doors or leaves are associated, all made of metal plate, which is used to achieve the support/resting and/or the fixing of plasterboard panels (2) that are adapted to define said walls (10) of an in-wall frame (11) for retractable doors or panels or for installation in frames for the provision of plasterboard walls, characterized in that said plurality of holes (13) are distributed uniformly according to a series of mutually parallel rows, so as to obtain, between two adjacent rows, an upper surface (17) which delimits each distinct row of said laterally adjacent holes (13) and is substantially shaped like an upturned U which determines a surface that is inclined in the direction of the adjacent holes (13) that are arranged at its sides.

5. The profiled element (1) according to one or more of claims 2 - 4, characterized in that each one of said holes (13) has, in plan view, a substantially conical shape (18) which provides a guide for the needle-like

tip (50) of a fastening screw (51) to move toward the axis (52) of the corresponding hole (13) if said tip is arranged either on said upper surface (17) or at said side walls or surfaces (13a, 13b, 17a, 13c, 13d and 17b) of each one of said holes (13) and of said upper surface (17).

5 6. The profiled element (1) according to one or more of claims 2 - 5, characterized in that a perforated conical tab (20) protrudes, at each one of said holes (13), at the lower surface (19) which is opposite said upper surface (17) and produces a localized increase in the thickness (S) of said planar surface (12).

10 7. The profiled element (1) according to one or more of claims 2 - 6, characterized in that in a plan view said holes (13) have, considering both said upper surface (17) and said lower surface (19), a substantially X-like shape.

 8. The profiled element (1) according to one or more of claims 2 - 7,
15 characterized in that the side or diameter (D1) of each one of said holes (13) that are provided on said planar surface (12) of said profiled element (1), and therefore of each one of said horizontal profiled element (3), said vertical profiled element (4), said front post (5), said abutment post (6), said rear post (7), said horizontal crossmember (8), and said upper crossmember
20 (9), is equal to or smaller than three times the measure of the thickness (S) of said planar surface (12) that constitutes said profiled element (1) [D1≤3S].

 9. The profiled element (1) according to one or more of claims 2 - 8,
25 characterized in that the center distance (D2) between two of said holes (13) that are mutually closer is equal to or greater than the thickness (S) of said profiled element (1) [D2≥S].

 10. The profiled element (1) according to one or more of claims 2 - 9, characterized in that its thickness (S) is comprised between 0.4 and 1.5 millimeters [0.4≤S≤1.5].

30 11. The profiled element (1) according to one or more of claims 2 -

10, characterized in that the shape and the arrangement of said holes (13) and said side walls or surfaces (13a, 13b, 17a, 13c, 13d, 17b) guides the penetration of said tip (50) of said screw (51), regardless of its arrangement on the side of said planar surface (12) that has said holes (13), into an adjacent single hole (13), and said head (53) of said screw (51) compresses the skin or layer of paper onto the underlying plaster of said plasterboard panel (2) without breaking the thin paper layer.

12. The profiled element (1) according to one or more of claims 2 - 11, characterized in that it has, at the longitudinal sides of said planar surface (12), one or more ridges or two side edges or folds (15a, 15b) and two wings (16a, 16b) which give said profiled element (1) a substantially omega-like shape.




Fig. 5




Fig. 4




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12

8 / 8




Fig. 13




Fig. 14




Fig. 15

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2018/071405

A. CLASSIFICATION OF SUBJECT MATTER
 INV. E06B3/46 E04F13/08 E04B2/74
 ADD.
 According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED
 Minimum documentation searched (classification system followed by classification symbols)
 E06B E04B E04F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)
 EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2009/223167 A1 (ANDERSON JEFFREY A [US]) 10 September 2009 (2009-09-10) paragraphs [0004], [0015] - [0024]; figures -----	1,3,5,6,8-12
X	US 2009/013633 A1 (AUBUCHON GORDON [US]) 15 January 2009 (2009-01-15) paragraphs [0004], [0005], [0015] - [0026], [0033] - [0035], [0039] - [0043]; figures -----	1,3-12
Y	EP 2 299 043 A1 (S C S P A [IT]) 23 March 2011 (2011-03-23) paragraph [0004]; figures 5,8 -----	2
Y		2
A		12

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search 10 December 2018	Date of mailing of the international search report 14/12/2018
--	---

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer Gallego, Adoración
--	---

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2018/071405

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2009223167	A1	10-09-2009	NONE

US 2009013633	A1	15-01-2009	NONE

EP 2299043	A1	23-03-2011	EP 2299043 A1 23-03-2011
			ES 2398049 T3 13-03-2013
			IT 1395877 B1 26-10-2012
