




(86) Date de dépôt PCT/PCT Filing Date: 2000/12/15
(87) Date publication PCT/PCT Publication Date: 2001/07/05
(45) Date de délivrance/Issue Date: 2008/04/15
(85) Entrée phase nationale/National Entry: 2002/05/29
(86) N° demande PCT/PCT Application No.: ES 2000/000473
(87) N° publication PCT/PCT Publication No.: 2001/047721
(30) Priorité/Priority: 1999/12/23 (ESP 9902829)

(51) Cl.Int./Int.Cl. *B41N 3/08* (2006.01),
B41F 7/32 (2006.01)
(72) Inventeur/Inventor:
ROMERO SALVO, GERARDO ANTONIO, ES
(73) Propriétaire/Owner:
DELTA GRAF, S.A., ES
(74) Agent: ROBIC

(54) Titre : SOLUTION MOUILLANTE POUR PLAQUES D'IMPRESION OFFSET ET PROCEDE ET DISPOSITIF
UTILISES POUR SA PREPARATION
(54) Title: DAMPING SOLUTION FOR OFFSET PRINTING PLATES AND METHOD AND DEVICE FOR THE
PREPARATION THEREOF



(57) Abrégé/Abstract:

The invention concerns a solution consisting of between 95 % to 97 % water and between 3 % to 5 % additive containing by weight: between 0 % and 0.5 % by weight of sodium hexametaphosphate; between 0 % and 1.5 % ascorbic acid; between 0 % and 1 % preventol; between 0 % and 1 % sodium benzoate; between 0 % and 1 % citric acid; between 2 % and 10 % glycerin; between 0 % and 0.1 % lemon; between 50 % and 75 % sorbitol; between 1 % and 2 % acetic acid; between 3 % and 7 % sodium citrate; between 0 % and 1 % sodium oleate and between 15 % and 30 % osmosised water. The method for preparing the solution includes an oxygen-adsorption phase involving jet spraying recirculated solution fractions on the free surface of the solution, said fractions traversing a helicoidal conduit at high speed and being projected forming a 90° outlet cone.



(12) SOLICITUD INTERNACIONAL PUBLICADA EN VIRTUD DEL TRATADO DE COOPERACIÓN
EN MATERIA DE PATENTES (PCT)(19) Organización Mundial de la Propiedad
Intelectual
Oficina internacional(43) Fecha de publicación internacional
5 de Julio de 2001 (05.07.2001)

PCT


(10) Número de Publicación Internacional
WO 01/47721 A1

- (51) Clasificación Internacional de Patentes⁷: **B41N 3/08**
- (21) Número de la solicitud internacional: PCT/ES00/00473
- (22) Fecha de presentación internacional:
15 de Diciembre de 2000 (15.12.2000)
- (25) Idioma de presentación: español
- (26) Idioma de publicación: español
- (30) Datos relativos a la prioridad:
P 9902829 23 de Diciembre de 1999 (23.12.1999) ES
- (71) Solicitante (*para todos los Estados designados salvo US*):
DELTA GRAF, S.A. [ES/ES]; Calle Montnegre, 18-24,
E-08029 Barcelona (ES).
- (72) Inventor; e
- (75) Inventor/Solicitante (*para US solamente*): **ROMERO SALVO, Gerardo Antonio** [ES/ES]; Calle Montnegre, 18-24, E-08029 Barcelona (ES).
- (74) Mandatario: **SUGRAÑES MOLINE, Pedro**; Calle Provenza, 304, E-08008 Barcelona (ES).
- (81) Estados designados (*nacional*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

[Continúa en la página siguiente]

(54) Title: DAMPING SOLUTION FOR OFFSET PRINTING PLATES AND METHOD AND DEVICE FOR THE PREPARATION THEREOF

(54) Título: SOLUCION HUMECTANTE PARA PLANCHAS DE IMPRESION OFFSET Y PROCEDIMIENTO Y DISPOSITIVO PARA SU PREPARACION



(57) Abstract: The invention concerns a solution consisting of between 95 % to 97 % water and between 3 % to 5 % additive containing by weight: between 0 % and 0.5 % by weight of sodium hexametaphosphate; between 0 % and 1.5 % ascorbic acid; between 0 % and 1 % preventol; between 0 % and 1 % sodium benzoate; between 0 % and 1 % citric acid; between 2 % and 10 % glycerin; between 0 % and 0.1 % lemon; between 50 % and 75 % sorbitol; between 1 % and 2 % acetic acid; between 3 % and 7 % sodium citrate; between 0 % and 1 % sodium oleate and between 15 % and 30 % osmosised water. The method for preparing the solution includes an oxygen-adsorption phase involving jet spraying recirculated solution fractions on the free surface of the solution, said fractions traversing a helicoidal conduit at high speed and being projected forming a 90° outlet cone.

[Continúa en la página siguiente]



WO 01/47721 A1

WO 01/47721 A1

(84) **Estados designados (regional):** patente ARIPO (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), patente euroasiática (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), patente europea (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), patente OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Publicada:

— *Con informe de búsqueda internacional.*

Para códigos de dos letras y otras abreviaturas, véase la sección "Guidance Notes on Codes and Abbreviations" que aparece al principio de cada número regular de la Gaceta del PCT.

(57) **Resumen:** La solución está formada por entre un 95 y un 97 % de agua y entre un 3 y un 5 % de un aditivo que contiene, en peso: entre 0 y 0'5 % en peso de hexametáfosfato sódico, entre 0 y 1'5 % de ácido ascórbico, entre 0 y 1 % de preventol, entre 0 y 1 % de benzoato sódico, entre 0 y 1 % de ácido cítrico, entre 2 y 10 % de glicerina, entre 0 y 0'1 % de limonal, entre 50 y 75 % de sorbitol, entre 1 y 2 % de ácido acético, entre 3 y 7 % de citrato sódico, entre 0 y 1 % de oleato sódico, y entre 15 y 30 % de agua osmotizada. El procedimiento para la preparación de la solución comprende una fase de adsorción de oxígeno proyectando a chorro sobre la superficie libre de la solución fracciones recirculadas de la misma, que atraviesan a alta velocidad un conducto helicoidal y se proyectan formando un cono de salida de 90°.

DAMPING SOLUTION FOR OFFSET PRINTING PLATES AND METHOD
AND DEVICE FOR THE PREPARATION THEREOF

Technical sector of the invention.-

The invention relates to a humidifying solution for offset print sheet and to a procedure and to a device for the preparation of said humidifying solution.

10 Specifically, the humidifying solution of the invention is of the type that are formed by between 95% and 97% of water and between 3% and 5% of an additive which contains sodium citrate, acetic acid, citric acid and sodium benzoate.

The procedure to obtain the humidifying solution to which the invention refers is of the type which contains a preliminary phase of oxygen adsorption by the means of projecting a thrust, over the free surface of the humidifying solution, of recycled fractions of the humidifying solution.

20 The device for the preparation of the humidifying solution according to the invention is of the type which contains a main container reservoir for the solution, an outlet pipe for the solution provided with a first pump that recycles part of the solution back to some means for thrust propulsion of the recycled fraction over the free surface of the solution, which is present in an annex container reservoir, main and independent from it, a feeding pipe which communicates said annex compartment with the humidifying bucket for the humidifying cylinder of an offset printing machine and a feedback pipe for the solution in the humidifying bucket to main container reservoir.

30

State of the art.-

- 2 -

The offset printing is an indirect printing fashion in which three cylinders are used: the printing sheet is mounted on the first cylinder; the second cylinder transmits the image to a second cylinder, which is covered by a rubber layer, which prints the paper which traverses between itself and a third cylinder which is only for pressing purposes. The pressing sheet is covered with photo-sensible emulsions in the shape of colloids which, when exposed to light, polymerize creating some surface zones which are lipophilic or similar to printing ink, which are fat bodies and hidrophilic metallic zones without images, which repel the ink.

A first set of rollers provide the printing ink to the first cylinder that the sheet has and the other set of rollers wets the sheet. The image zones accept ink, while the blank ones reject it. The addition of wetness to the sheet is achieved using what are called wetting systems.

The offset printing is a system based in surface physic and chemical phenomena, that is it is not a system based on relief, like typography, flexography, tampography, etc., but it is a planographic system in which the phase previous to the transferring of the ink to the paper consists in chemical attractions and repulsions between the different lipophilic and hidrophilic substances. Therefore, both the water and the ink must have a set of adequate physical and chemical characteristics that allow that the process be the right one.

Around this idea, and keeping in mind that the water with which the offset machines work is regular network water, there is the need to add some special additives to the water so that it gets determined properties in pH and surface tension, among others.

- 3 -

Among the wetting systems, the water alcohol system can be pointed out. It consists in adding, besides some additives, between 10% and 12% of isopropyl alcohol to the water. The water alcohol system is the most developed and extended one because the quality parameters with this system are far better than with any other system, for example those called in the "integral" and "conventional" techniques. The basis for this good behavior is that the isopropyl alcohol provides a good interfacial tension between the water and the ink which brings the consequence a better water in the ink emulsion, so the printed ink is more vivid than with any other known wetting system.

Some other additional advantages are that the wetting system with isopropyl alcohol provides a higher viscosity that allows a more uniform image transference, a faster drying speed and a decrease in the surface tension that allows the water layer over the sheet to be very thin and to have a lower tendency to the mechanical emulsion.

However, for some years now, very rigorous studies are being conducted on the possible toxicity that the isopropyl alcohol based systems can present due to a prolonged exposure. In this sense, some countries have absolutely forbidden its use, while in some others its use has been largely restricted and in our country it is on its way to being forbidden for good.

Apart from toxicity, they present storing difficulty problems and danger of inflammability.

Many manufacturers have unsuccessfully tried to formulate additives that satisfy the aforementioned quality needs and refrains completely from using the isopropyl alcohol. The reason of the failed tries is in essence that the need to have to reduce the sur-

- 4 -

face tension to avoid that the water ink emulsion to levels which can be compared to the water alcohol system obligates the use of tensoactives of group III. A larger concentration of these tensoactives originates a decrease in the interphase by affinity between the ink fat acids and the tensoactives hydro-carburated strings. The tensoactives cause a great deal of foam and, because they are no volatile, they remain in the ink rollers, thus accumulating and causing operating problems.

The former, together with the impossibility to form stable colloids based on other substances that reduce the surface tension and maintain a larger water ink interphase are the main reasons why it has been impossible to substitute the isopropyl alcohol.

European patent number EP-A-0 770 501 introduces some improvements in wetting systems for offset printing, consisting in feeding the wetting system with a dissolution based on water and some determined additive. The dissolution is subjected to some collision phenomena during which it acquires, due to an adsorption process, an important amount of oxygen, with which it is achieved that the dissolution that wets the printing sheet, based on which the impression is made, acquires a large amount of free oxygen, thus increasing the water ink inter-phase.

Also, the EP-A-0 770 501 describes the device for the preparation of the solution, which consists of a main container reservoir for the solution, an outlet pipe provided with a first pump that recycles part of the solution towards some means for thrust projection of the recycled fraction over the free surface of the present solution in a compartment annex to the main container and independent from it, a feeding pipe, which communicates said annex compartment with the wetting bucket of the wetting

cylinder of an offset printing machine and a feedback pipe for the wetting bucket solution to the main container reservoir.

Said improvements and device, even if they have a correct functionality and provide a good final quality, lacks the collision of the recycled fraction against the free surface and does not achieve a constant adsorption isothermal on the surface of the solution, which would be desirable for getting a
10 larger uniformity of extension of the humidifying layers over the printing sheet.

The goal of the invention is to provide an effective solution to all problems listed above.

Summary of the Invention.-

To that extent, the invention makes public the humidifying solution, which in essence is characterized in that the aforementioned additive contains
20 between 0.0% and 0.5% in weight of sodium hexameta-phosphate, between 0.0% and 1.5% in weight of ascorbic acid, between 0.0% and 1.0% in weight of sodium benzoate, between 0.0% and 1.0% in weight of citric acid, between 2% and 10% in weight of glycerin, between 0.0% and 0.1 % in weight of limonal, between 50% and 75% in weight of sorbitol, between 1% and 2% in weight of acetic acid, between 3% and 7% in weight of sodium citrate, between 0.0 and 1.0% in weight of sodium oleate and between 15% and 30% in weight of osmotic water.

According to one other feature of the humidify-
30 ing solution of the invention, the aforementioned additive is constituted by 0.1% in weight of sodium hexametaphosphate, 0.3% in weight of ascorbic acid, 0.2% in weight of preventol, 0.2% in weight of sodium benzoate, 0.2% in weight of citric acid, 5% in weight of glycerin, 0.05% in weight of limonal, 65% in

- 6 -

weight of sorbitol, 1.5% in weight of acetic acid, 5% in weight of sodium citrate, 0.2% in weight of sodium oleate, and 22.25% in weight of osmotic water.

5 The invention also has the goal to a method to obtain the aforementioned humidifying solution, characterized in that the solution is forced to flow at high speed by a pipe with a helicoidal configuration and is projected thus forming a 90-degree solid angle output cone, in such a way that a part of the
10 particles of the projected thrust collide against the free surface of the humidifying solution, obtaining on said free surface a isothermal of constant adsorption.

According to one other feature of the invention,
15 the humidifying solution is projected at a lineal speed between 1.3 m/s and 220 m/s and at a pressure up to 1,500 kg/cm².

According to one other feature of the invention, said lineal speed is 60 m/s and said pressure is 250
20 kg/cm².

Another goal of the invention is a device for the preparation of a humidifying solution according to the invention using the method described above, which in essence is characterized in that the afore-
25 mentioned projection means are constituted by an injector which makes the solution turn at high angular speeds in a helicoidal trajectory and subject to very high pressures, so that the solution is projected forming a output cone of 90 degrees of solid
30 angle, so that a part of the particles of the projected thrust collide against a deflecting surface and the rest of the particles collide against a free surface of the humidifying solution an isothermal of constant adsorption.

35 Preferably, the aforementioned injector has an initial acceleration part in a helicoidal trajectory

- 7 -

and right after it a second diffusion part of toroidal configuration, so that the humidifying solution is projected over said free surface and against said deflecting surface at a lineal speed between 1.3 m/s
5 and 220 m/s and at a pressure up to 1,500 kg/cm².

In an actual realization of the invention, the lineal speed is 60 m/s and said pressure is 250 kg/cm².

10 According to one other feature of the invention, said deflecting surface makes an angle of between 0 degrees and 30 degrees with said liquid free surface.

Preferably, said deflecting surface (4) makes a 15-degree angle with the said liquid free surface.

15 Brief description of the drawings.-

Next, there is a description of an actual realization of the invention, although not exclusive, for whose better understanding a set of drawings is accompanied, give merely as non-limiting examples, in
20 which:

Figure 1 is a schematic view of a device according to the invention; and

Figure 2 is a section representation of an injector according to the invention in which a cut has been
25 made for a better understanding.

Detailed description of the drawings.-

In said drawings, it can be seen that the device according to the invention comprises a main container
30 reservoir 1 for the humidifying solution 18 for the wetting cylinder 14 of an offset printing machine. The set has an compartment 5 annex to the main reservoir 1, destined for containing a fraction 19 of the recircled humidifying solution 18. The free surface
35 13 of the annex compartment 5 is at a higher level than the free surface 20 of the main reservoir 1.

- 8 -

The main container reservoir 1 is connected to an output pipe 2 for the humidifying solution 18, provided with a first pump 7 that pushes to the annex compartment 5 the recircled fraction 19, which is projected at high speed and pressure by the means of an injector 3, in such a way that the interior of the compartment 5 is subjected to pressure.

The annex compartment 5 is provided in its interior with a deflecting surface 4, destined for receiving the impact of part of the recycled fraction thrust 19 of the humidifying solution 18 when it is projected by the injector 3.

It has been proven that an effective way to take into practicality the device of the invention is the one in which the deflecting surface 4 makes an angle of between 0 degrees and 30 degrees with said liquid free surface, with the optimal solution being that whose angle is 15 degrees.

In Figure 2, it can be seen that the injector 3 has a first acceleration part 16 in helicoidal trajectory and, right after it a second diffusion part 17 with toroidal configuration, which makes the solution turn at high angular speeds in a helicoidal trajectory and at high pressures. The humidifying solution 18 is projected by injector 3 forming a output cone 15 of 90 degree of solid angle. Part of the particles of the thrust collide against the deflecting surface 4 and the rest of the particles, against the free surface 13 of the humidifying solution, obtaining on said surface a constant adsorption isothermal. Injector 3 can provide a lineal speed between 1.3 m/s and 220 m/s and a pressure of up to 1,500 kg/cm², preferably 60 m/s and 250 kg/cm², respectively.

The annex compartment 5 is communicated, via a feeding pipe 8, with the one with which it connects

- 9 -

with its lower part, with a wetting bucket 10 of the wetting cylinder 14 of the offset printing machine, and to a feedback pipe 12 for the humidifying solution 18 from the wetting bucket 10 to the main container reservoir 1. The fraction of the humidifying solution that goes from the annex compartment 5 to the wetting bucket 10 is pushed by a second pump 9. The feedback pipe 12 is provided with a third pump 11, for the remaining fraction of the humidifying solution 18 that has not been incorporated to the printing sheet.

The annex compartment 5 is also communicated with the main reservoir 1 with the aid of a spiller 6 that spills because of gravity and in collaboration with the present pressure within the annex compartment 5.

The described device is particularly designed for the execution of the method of the invention for the preparation of the humidifying solution 18 for the offset printing sheets.

Said humidifying solution 18 is formed by between 95% and 97% of water and between 3% and 5% of an additive which contains between 0.0% and 0.5% in weight of sodium hexametaphosphate, between 0.0% and 1.5% in weight of ascorbic acid, between 0.0% and 1.0% in weight of sodium benzoate, between 0.0% and 1.0% in weight of citric acid, between 2% and 10% in weight of glycerin, between 0.0% and 0.1 % in weight of limonal, between 50% and 75% in weight of sorbitol, between 1% and 2% in weight of acetic acid, between 3% and 7% in weight of sodium citrate, between 0.0 and 1.0 % in weight of sodium oleate and between 15% and 30% in weight of osmotic water.

The composition of the cited additive is constituted by 0.1% in weight of sodium hexametaphosphate, 0.3% in weight of ascorbic acid, 0.2% in weight of

- 10 -

preventol, 0.2% in weight of sodium benzoate, 0.2% in weight of citric acid, 5% in weight of glycerin, 0.05% in weight of limonal, 65% in weight of sorbitol, 1.5% in weight of acetic acid, 5% in weight of sodium citrate, 0.2% in weight of sodium oleate, and 22.25% in weight of osmotic water.

The method of the invention is based on modifying the molecular structure of the water for the humidifying by forming gas surfaces of O₂ similar to those formed with colloids in association, achieving that all the humidifying solution layer applied to the printing sheet acquires a large amount of free oxygen.

In essence, on the surface 13 of the humidifying solution 18 some "vapor gas surfaces" are formed, which are obtained by subjecting the solution to colliding phenomena at high speed and pressure, projecting with the means of injector 3 a recycled fraction of the solution, this volume being the one that feeds in a continuous way the wetting system. Next, an explanation for the physical and chemical phenomena which rule the aforementioned structural modification of water is given.

A colloid differs from a dissolution basically in the size of the particles: from 0,1 mm to 1 mm in the first case and between 1 mm and several mm in the case of the colloids. There exist three types of colloids, namely: colloidal dispersions, macromolecule solutions and association colloids.

Next, the fundamentals of the association colloids are explained briefly, which are, among the three types listed, the ones that pertain to the physics and chemistry of the offset printing.

The substances that in solution get the name of association colloids are basically soaps and humidifying agents.

- 11 -

In the conventional additives that are currently used in the printing industry, humidifying agents in one or several varieties are found. In a generic way, it can be said that these additives generally
5 are aliphatic or mixed (aliphatic and aromatic) strings along with very strong polar groups to make them soluble.

Taking into consideration their insolubility, in absence of said additives, of these strings in dissolution, the situation thermodynamically more stable
10 is the grouping in what is called as micelles. And on the surface, the situation of a lesser energy is verified with the polar group in dissolution and the hydrophobic string outside the water.

These surfaces that have the property to present less surface tension than pure water are known as "gas vapor surfaces". The interactions that exist are always solute-solvent, because if only solute-solute interactions existed, it would be before homogeneous
15 surfaces, or even condensed, which are not the right kind for the case that occupies us.
20

Taking the former into consideration, it is understood that the creation of any new surface in an association colloid originates instantaneously a gas vapor surface, the general base for the working of the wetting additives.
25

If ink is spread on a surface of pure water, the ink will rapidly spread on the water forming a layer. This happens because the so-called "Initial Extension Coefficient (S)" is zero or positive. The initial extension coefficient is given by the formula:
30

$$S = \gamma_w - (\gamma_w / t - \gamma_t)$$

where γ_w is the tension component in the inter-phase water-ink with respect to the horizontal, t is the size of the bubbles created and γ_t the tangent
35

- 12 -

component force in the interphase water-ink, or to the contact angle.

When a conventional additive is added to water, it happens that there is no extension, in part because the surface tension has been decreased and in part because γ_w has ceased to be null and has taken the value of 30 degrees. Therefore, these two causes make the system to be stable in the condensed form.

However, in this new case, the value of γ_w/t has decreased. That is, the addition of a humidifying has reduced the surface tension.

In theory, it could be assumed that adding only alcohol to water and thus reducing the surface tension something similar should happen. However, it does not work that way. In any event, it is necessary the presence of a humidifying for the system to be stable in condensed state. The tension in the interphase with only alcohol is not large enough to produce this effect.

For that purpose, like it has already been said, the presence of an additive that in a similar way to prior case modifies the contact angle is required. However, the value of γ_w/t with alcohol is comparatively rather bigger and this is the fundamental cause for its good working.

Because it is impossible to form stable colloids (without tensoactives) to reduce the surface tension, and knowing that all the current existing substitutions have a behavior which is not particularly good or acceptable, the principles of the invention achieve solving the problem by the means a completely different approach.

It has been proceeded to try a similar adsorption to the Langmuir Type 1, that is, an adsorption in which the adsorption speed of a gas over a solid,

- 13 -

v, depends on a constant K1, of the fraction of covered surface, D, and on the pressure, P:

$$v = K1 (1 - D) * P$$

In the case of the system of the invention, besides the pressure, because it is an adsorption over the surface of a liquid, the speed of condensation has been proven to depend on a factor related to the number of collisions of air bubbles and also on their size of over the liquid surface. Therefore, the speed can be represented by the following formula:

$$v = K3 (1 - D) * P * C$$

Where

$$c = f(N, t)$$

Where N is the number of collisions per time unit.

Where N is the number of collisions per time unit.

The system of the invention does not work over a Gibbs isothermal, in which the adsorption processes are stable and always measurable depending on the concentration of the humidifying and on the variation of the surface tension with its concentration, as it would be according to the following equation:

$$R = C/RT (dt/dc)T$$

But it produces a reversible adsorption isothermal in which:

$$V = K2 * D$$

And in which an internal fraction of volume of the humidifying solution does not present these conditions at any moment, but only the free surface 13 of the humidifying solution present in the annex compartment 5 originates this phenomenon.

Therefore, it has been determined that the increase of the interfacial tensions derived from function C can be obtained from experiments in which it has been worked with the following parameters:

- 14 -

- a) different formulations, with different sensibilities of the emulsion to the air;
- b) different speed of the fluid under pressure over the volume to deal with;
- 5 c) different ratio surface-volume of the fluid to deal with;
- d) different collecting zones of the fluid to pump to the water tray 10 (Figure 1); and
- 10 e) different additional treatments of turbulence over the water tray 10, only in specific cases.

The procedure according to the invention achieves that the water that the wetting rollers 14 collect from the water trays 10 gets to O₂ adsorption conditions to the sheet, adequate for, on one side to
15 create interphase tension higher than that of the water alcohol system, and on the other a layer of water so thin it does not cause excessive emulsion.

This phenomenon happens thanks to the O₂ adsorption on the water surface in contact with the wetting
20 roller 14, gets transmitted with the rest of the system's wetting roller, and from those to the hydrophilic zone of the sheet.

An expert on this sector of the technique is aware of the fact that the additive does not incorporate
25 any tensoactive from group III. A wetting dissolution with a tensoactive and without adsorption treatment produces spreading of the ink over the water as a consequence of that the surface tension of the water does not decrease, and therefore the extension
30 coefficient is zero or positive, which is not desirable.

However, the method of the invention, once the O₂ adsorption over the surface of the wetting water has happened, not only there is no extension but the
35 speed of flocculation of a thin layer of ink (tested

- 15 -

in a laboratory and machine) is much larger than in water-additive-alcohol.

5 This means that the extension coefficient is less in the system according to the invention than in the conventional water-alcohol, which means a clear advantage.

10 The printers know from experience that in the inmerser roller 14 of a water-alcohol wetting system, the chromate must present, as it runs, an aspect of a thin water layer, which is indicative that the surface tension is the ideal mixture. When the surface tension increases (for instance, because the alcohol concentration has decreased) this thin layer breaks causing water extension problems over the rollers and
15 the sheet, obligating them to increase the system water flow and the speed.

The adsorption on the surface that the system of the invention produces, creates a situation similar to that of the alcohol, and even when the resulting
20 surface tension of the additive is close to 72 dinas/cm it is deduced that when the system of the invention has produced enough surface O₂ adsorption, the same phenomenon happens over the inmerser roller as a consequence of the fact that the surface tension
25 over said roller has decreased.

From the experimental development, test undertaken in workshops and in real tests the following results are obtained, which will be clear for an expert on the technique:

- 30 - isopropylic alcohol total elimination;
- more uniformity of the extension of the ink over the sheet;
- a thinner and more homogeneous over the sheet;
- lower emulsion of water over ink;
35 - better extension of ink over the set with less water and less paper particles;

- 16 -

- colors more vivid;
- ink savings of up to 14% in normal offset and even higher in UV;
- higher drying speed of the ink;
- 5 - reduction and in some cases of anti-spot dusts;
- better "wet over wet" impression in a multicolor machine with a higher ink transparency;
- important improvement of the "additionability" and "trapping";
- 10 - better "impasted";
- better contrast;
- better gain point;
- less stops for cleaning and the rubber layer; and
- better reproduction of the weft between 1% and
- 15 99%, with very good results with special wefts, such as the "stochastics".

Although the present invention has been explained hereinabove by way of a preferred embodiment thereof, it should be pointed out that any modifications to this preferred embodiment within the scope of the appended claims is not deemed to alter or change the nature and scope of the present invention.

WHAT IS CLAIMED IS:

1. Humidifying solution for offset printing sheet, of the type formed by between 95% and 97% of water and between 3% and 5% of an additive which contains sodium citrate, acetic acid, citric acid and sodium benzoate, characterized in that the aforementioned additive contains between 0.0% and 0.5% in weight of sodium hexametaphosphate, between 0.0% and 1.5% in weight of ascorbic acid, between 0.0% and 1.0% in weight of preventol, between 0.0% and 1.0% in weight of sodium benzoate, between 0.0% and 1.0% in weight of citric acid, between 2% and 10% in weight of glycerin, between 0.0% and 0.1% in weight of limonal, between 50% and 75% in weight of sorbitol, between 1% and 2% in weight of acetic acid, between 3% and 7% in weight of sodium citrate, between 0.0 and 1.0% in weight of sodium oleate and between 15% and 30% in weight of osmotic water.
2. Humidifying solution according to claim 1, characterized in that the cited additive is constituted by 0.1% in weight of sodium hexametaphosphate, 0.3% in weight of ascorbic acid, 0.2% in weight of preventol, 0.2% in weight of sodium benzoate, 0.2% in weight of citric acid, 5% in weight of glycerin, 0.05% in weight of limonal, 65% in weight of sorbitol, 1.5% in weight of acetic acid, 5% in weight of sodium citrate, 0.2% in weight of sodium oleate, and 22.25% in weight of osmotic water.
3. Method for the preparation of a humidifying solution according to claim 1 or 2, of the type which comprises a preliminary phase for the adsorption of oxygen, according to the steps of:
 - thrusting of recycled fractions of the solution over the free surface of humidifying solution, forcing the solutions to flow at high speed with a pipe with a helicoidal configuration resulting in a 90-degree solid angle output cone,

– in such a way that a part of the particles of they projected thrust collide against the free surface of the humidifying solution, obtaining on said free surface an isothermal of constant adsorption.

4. Method according to claim 3, characterized in that the humidifying solution is projected at a lineal speed comprised between 1.3 and 220 m/s and at a pressure up to 1,500 kg/cm².

5. Method according to claim 4, characterized in that the aforementioned lineal speed is 60 m/s and the aforementioned pressure is 250 kg/cm².

10 6. Device for the preparation of a humidifying solution according to claims 1 or 2 using the method described by any one of claims 3 to 5, of the type which comprise a main container (1) for the solution, an outlet pipe (2) for the solution provided with a first pump (7) the recycles part of the solution to a means for thrusting the recycled fraction over the free surface (13) of the solution which is present in an compartment (5) annex to the main container and independent from it, a feeding pipe (8) which communicates said annex compartment with the humidifying bucket (10) of the humidifying cylinder (14) of an offset printing machine, and a feedback pipe (12) for the solution from the humidifying bucket to the main container (1), characterized because the aforementioned projection means are constituted by an injector (3) which makes the solution turn at high
20 angular speeds in a helicoidal trajectory and subject to very high pressures, so that the solution is projected forming a output cone (15) of 90 degrees of solid angle, so that a part of the particles of the projected thrust collide against a deflecting surface (4) and the rest of the particles collide against a free surface (13) of the humidifying solution, thus getting in said surface an isothermal of constant adsorption.

7. Device according to claim 6, characterized in that the aforementioned injector (3) has an initial acceleration part (16) in a helicoidal trajectory and right after it a second diffusion part (17) of toroidal configuration, so that the

humidifying solution is projected over said free surface (13) and against said deflecting surface (4) at a lineal speed between 1.3 m/s and 220 m/s and at a pressure up to 1,500 kg/cm².

8. Device according to claim 7, characterized in that said lineal speed is 60 m/s and said pressure is 250 kg/cm².



9. Device according to claim 6, characterized in that said deflecting surface (4) makes an angle of between 0 degrees and 30 degrees with said liquid free surface (13).

10. Device according to claim 9, characterized in that said deflecting surface (4) makes a 15-degree angle with the said liquid free surface (13).

WO 01/47721

PCT/ES00/00473

1 / 1

**FIG. 1****FIG. 2**

