



US 20070060956A1


(19) **United States**(12) **Patent Application Publication****Nassif**(10) **Pub. No.: US 2007/0060956 A1**(43) **Pub. Date: Mar. 15, 2007**(54) **METHOD AND APPARATUS FOR VARIABLE CAPACITANCE DEFIBRILLATION**(52) **U.S. Cl. .... 607/5**(76) **Inventor: Rabih C. Nassif, Corona, CA (US)**(57) **ABSTRACT**

Correspondence Address:


**PATTERSON, THUENTE, SKAAR &  
CHRISTENSEN, P.A.****4800 IDS CENTER****80 SOUTH 8TH STREET****MINNEAPOLIS, MN 55402-2100 (US)**(21) **Appl. No.: 11/223,782**(22) **Filed: Sep. 9, 2005****Publication Classification**(51) **Int. Cl.****A61N 1/39**

(2006.01)


An Automated External Defibrillator (AED) for delivering therapeutic electrical energy to a patient's heart comprising at least one variable capacitance capacitor having a large positive voltage coefficient such that a given amount of energy can be stored at a lower voltage than a traditional fixed capacitor having an equivalent capacitance. Due to the variable capacitance capacitor's ability to store energy at a lower voltage, initial defibrillation current levels are reduced effectively minimizing the risk of tissue damage caused by high initial current levels. In addition, the use of a variable capacitance capacitor reduces the amount of current decay throughout the discharge cycle as opposed to current AED designs utilizing fixed capacitance capacitors which experience an exponential decline in defibrillation current during the discharge cycle.




**Fig. 1a**




**Fig. 1b**



**Fig. 2a**



**Fig. 2b**



**Fig. 2c**




FIG. 3





FIG. 4



## METHOD AND APPARATUS FOR VARIABLE CAPACITANCE DEFIBRILLATION

### BACKGROUND OF THE INVENTION

#### [0001] 1. Field of the Invention

[0002] The present invention is directed to methods and apparatus for defibrillation of a patient's cardiac cell membrane. More specifically, the methods and apparatus of the present invention are directed to the delivery of shocking defibrillation waveforms using at least one variable capacitance capacitor having a large positive voltage coefficient such that energy can be stored at a lower voltage as compared to a traditional fixed capacitance capacitor with an equivalent capacitance.

#### [0003] 2. Description of the Related Art

[0004] Cardiac arrhythmias, such as ventricular fibrillation and ventricular tachycardia, are electrical malfunctions of the heart, in which regular electrical impulses in the heart are replaced by irregular, rapid impulses. These irregular, rapid impulses can cause the heart to stop normal contractions, thereby interrupting blood flow therethrough. Such an interruption in blood flow can cause organ damage or even death.

[0005] Normal heart contractions, and thus normal blood flow, can be restored to a patient through application of electric shock. This procedure, which is called defibrillation, has proven highly effective at treating patients with cardiac arrhythmias, provided that it is administered within minutes of the arrhythmia. To deliver this electric shock, defibrillators, either implantable or portable, have been developed with the intent of quickly delivering life saving treatment.

[0006] Portable automatic external defibrillators (hereinafter "AEDs") are often used in facilities drawing large crowds of people such as shopping malls, sporting arenas, office buildings and the like. An AED is typically used by trained emergency medical system personnel, though AEDs typically include step-by-step instructions combined with various sensors that make them usable by almost anyone in an emergency situation.

[0007] A typical AED comprises various electrical and electronic components including a controller, a battery circuit, a detector circuit and a discharge circuit. Generally, the discharge circuit includes at least one capacitor for storing energy from the battery circuit and subsequently discharging that energy in the form of defibrillation waveform when requested by the controller. Unfortunately, the capacitors traditionally used in AED's may discharge at initial current levels sufficient enough to cause tissue damage. Furthermore, these traditional capacitors suffer an exponentially steep decline in the level of the defibrillation current as the capacitor discharges.

### SUMMARY OF THE INVENTION

[0008] The present invention addresses the aforementioned drawbacks associated with the capacitor technology presently utilized in AED's. For example, according to one aspect, the present invention includes at least one variable capacitance capacitor having a large positive voltage coefficient, i.e., a capacitor whose capacitance drastically increases with the amount of charge it contains. The at least

one variable capacitance capacitor can store a given amount of energy at a much lower voltage than traditional fixed capacitors having equivalent capacitance ratings. As such, the AED of the present invention allows for a much lower initial current during defibrillation to reduce the risk of tissue damage. Furthermore, the AED of the present invention is better able to maintain the current level of the defibrillation charge throughout the AED discharge sequence. Finally, the lower initial current allows the use of electrical components having lower ratings and capacities to reduce assembly and manufacturing costs.

### BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1a is a perspective view of an automated external defibrillator in a storage disposition.

[0010] FIG. 1b is a perspective view of the automated external defibrillator of FIG. 1 in an operable disposition.

[0011] FIG. 2 is a biphasic defibrillation model of the present invention.

[0012] FIG. 2a depicts a basic defibrillation circuit.

[0013] FIG. 2b depicts a basic defibrillation circuit for generating a monophasic waveform.

[0014] FIG. 2c depicts a basic defibrillation circuit for generating a biphasic waveform.

[0015] FIG. 3 depicts a comparison of Voltage versus Time for a defibrillator comprising a traditional fixed capacity capacitor and a defibrillator comprising a variable capacitance capacitor.

[0016] FIG. 4 depicts a comparison of Power versus Time for a defibrillator comprising a traditional fixed capacity capacitor and a defibrillator comprising a variable capacitance capacitor.

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0017] The present invention is directed to a defibrillation system for use in treating patients who have suffered from cardiac arrhythmias. As depicted in FIG. 1a, an automated external defibrillator (AED) 100 comprises a plastic case 102 having a carrying handle 104. As is more clearly illustrated in FIG. 1b, plastic case 102 further comprises a lid 106 selectively covering an electrode compartment 108. Electrode component 108 comprises an electrode connector 110, a speaker 112 and a diagnostic panel (not shown). A pair of electrodes 114 adapted for attachment to a patient are connected to electrode connector 110. Electrodes 114 are typically stored within electrode compartment 108 and may be preconnected to electrode connector 110 during storage of the AED 100.

[0018] The operation of AED 100 is described briefly below. A rescue mode of AED 100 is initiated when lid 106 is opened to access electrodes 114 as depicted in FIG. 2. The opening of lid 106 is detected by AED 100 to effectively turn on the device. Once turned on, AED 100 performs a short test routine. A user applies electrodes 114 to the patient such that AED 100 can measure patient specific parameters, such as impedance, voltage, current, charge or other measurable parameters of the patient. The patient specific parameters are

then utilized to design and administer optimal waveform, either monophasic or biphasic, as described below.

[0019] If the AED 100 detects a shockable condition, the AED initiates the charging of a plurality of self-contained capacitors using a self-contained energy source, typically a detachable battery pack. The AED 100 then uses the patient specific parameters to calculate an optimal waveform for discharge to the patient. The energy stored within the plurality of capacitors is then discharged through the electrodes 114 to defibrillate the heart. For more detail with respect to the physical structure of AED 100 or the process of AED testing, sensing patient specific parameters, determining shockable conditions, charging capacitors and discharging waveforms, reference is made to Applicant's issued U.S. Pat. No. 5,645,571, which is commonly assigned to the assignee of the present invention and is hereby incorporated by reference in its entirety.

[0020] In a simplest form, a defibrillation circuit for AED 100 can be depicted as shown in FIG. 2a where  $C_1$ , represents a capacitor,  $V_s$  represents the voltage between the electrodes  $R_H$  represents the resistance of the heart. Further variations on the defibrillation circuit for AED 100 are shown in FIG. 2b representing a monophasic waveform circuit, and FIG. 2c depicting a biphasic waveform circuit. Within FIGS. 2b and 2c,  $C_M$  and  $R_M$  represent membrane series capacitance and resistance of a single cell,  $V_M$  represents the voltage across the cell membrane and  $C_1$  and  $C_2$  refer to a first and second capacitors, or capacitor banks, respectively. In its simplest form, electrodes 114 communicate patient specific parameters to the AED 100 such that the patient resistance can be determined. Based on this resistance, the AED 100 discharges the capacitors to generate and deliver the shocking waveform, in either a monophasic or biphasic form. For more detail with respect to determining patient resistance and optimizing a shocking waveform, reference is made to Applicant's issued U.S. Pat. No. 6,411,846, which is commonly assigned to the assignee of the present invention and is hereby incorporated by reference in its entirety.

[0021] With respect to the present invention, the capacitors depicted within FIGS. 2a, 2b and 2c are variable capacitance capacitors. Generally, these variable capacitance capacitors each have a large positive voltage coefficient. The large positive voltage coefficient causes the capacitance of these variable capacitance capacitors to increase with a corresponding increase in the amount of charge being stored. A representative variable capacitance capacitor is the Pulse Power line of multilayer ceramic chip capacitors manufactured by Novacap.

[0022] The use of variable capacitance capacitors within the defibrillation circuits of FIGS. 2a, 2b and 2c has two significant advantages over the fixed capacitance capacitors presently used in defibrillation circuits. First, by storing energy at a lower voltage, the defibrillation circuit can deliver an initial defibrillation current at a current level lower than prior art designs such that the risk of tissue damage from said current is reduced. Secondly, the level of the defibrillation current is maintained avoiding the exponential decay in current level experienced by prior art designs.

[0023] With respect to the discharge characteristics of the variable capacitance capacitors, the characteristics are represented by the equation:

$$V=Q/C$$

Eq. 1

where V is the capacitor voltage, Q is the charge amount and C is the capacitance. From this equation, it will be obvious that as capacitance decreases with the charge amount, the capacitor voltage is "lifted" such that it is prevented from decaying at an exponential rate. As the capacitor voltage is related to the defibrillation current by the equation:

$$V=I*Z$$

Eq. 2

where V is the capacitor voltage, I is the defibrillation current and Z is the patient impedance, the defibrillation current follows the same behavior as the capacitor voltage, i.e., it is "lifted" such that it is prevented from decaying at an exponential rate, since the patient impedance remains essentially constant throughout the defibrillation discharge.

[0024] In practice, the benefits of the present invention are easily observable by comparing the defibrillation characteristics of a biphasic waveform generated using a traditional fixed capacitor rated for 200 uF at 0 volts with a biphasic waveform generated using a variable capacitance capacitor rated at 100 uF. For purposes of comparison, the patient impedance is assumed constant, i.e., 50. Using the aforementioned equations, data is generated for both traditional fixed capacitors as well as variable capacitance capacitors. Using this data, a graph of voltage versus time is illustrated in FIG. 3, while a graph of Power versus Time is illustrated in FIG. 4 to demonstrate the rate of energy transfer. The data used to generate FIGS. 3 and 4 is:

Time (ms)	Voltage (V) Fixed Capacitor	Delivery Rate (J/ms) Fixed Capacitor	Voltage (V) Variable Capacitor	Delivery Rate (J/ms) Variable Capacitor
0	2000		1750	
.5	1900	39.0	1692	30.1
.10	1805	35.2	1683	28.5
.15	1715	31.8	1633	27.9
.20	1629	28.7	1617	26.5
.25	1548	25.9	1573	25.8
.30	1470	23.4	1552	24.6
.35	1397	21.1	1512	23.8
.40	1327	19.0	1488	22.7
.45	1260	17.2	1451	21.9
.50	1197	15.5	1412	20.8
.55	1138	14.0	1378	19.7

[0025] As illustrated by the graph of FIG. 3, the biphasic waveform using the traditional fixed capacitor is storing 2000 V as compared to the approximately 1750 V stored by the variable capacitance capacitor. Based on the aforementioned equations, generation of a biphasic waveform using the traditional fixed capacitor will have a higher initial current potentially causing tissue damage as compared to the variable capacitance capacitor. Furthermore, the characteristics of the variable capacitance capacitor will result in a greatly reduced voltage decay as time proceeds such that the effective defibrillation current can be maintained for a longer period. In comparison, the traditional fixed capacitor must have a high initial voltage to insure that it maintains an effective defibrillation current level throughout the exponential decay in voltage over time. Along these same lines, FIG. 4 illustrates that the use of a variable capacitance capacitor allows energy to be transferred through the biphasic waveform starting at a lower initial rate and maintaining the rate for a longer period in comparison to waveforms generated using traditional fixed capacitors.

[0026] The present invention has been described with respect to particular illustrative embodiments. It is to be understood that the invention is not limited to the above-described embodiments and modifications thereto, and that various changes and modifications may be made by those of ordinary skill in the art without departing from the spirit and scope of the appended claims.

1. A defibrillation apparatus, wherein said defibrillation apparatus delivers a shocking waveform to produce a desired cardiac response in the cardiac cell membrane of a patient, the apparatus comprising:

a pair of electrodes, wherein said pair of electrodes are securable to said patient; and

an electronic circuit, wherein said electronic circuit is operably coupled to said pair of electrodes, wherein said electronic circuit includes an energy storage portion that comprises at least one variable capacitance capacitor and wherein said electronic circuit initiates delivery of said shocking waveform through said pair of electrodes upon detection of a shockable condition within said cardiac cell membrane.

2. The defibrillation apparatus of claim 1, wherein said at least one variable capacitance capacitor of said energy storage portion stores a charge at a first voltage level, and wherein said first voltage level is less than the voltage level of a comparable non-variable capacitor that stores the substantially same charge and is capable of replacing said at least one variable capacitance capacitor within said energy storage portion.

3. The defibrillation apparatus of claim 1, wherein the defibrillation apparatus is an Automated External Defibrillator.

4. The defibrillation apparatus of claim 1, wherein the at least one variable capacitance capacitor has a large positive voltage coefficient.

5. The defibrillation apparatus of claim 1, wherein the shocking waveform is a biphasic waveform.

6. The defibrillation apparatus of claim 1, wherein the electronic circuit further comprises an energy source wherein said energy source is a detachable battery pack.

7. The defibrillation apparatus of claim 1, wherein the energy storage portion comprises a plurality of variable capacitance capacitors arranged in either a parallel or series orientation.

8. The defibrillation apparatus of claim 7, wherein the plurality of variable capacitance capacitors define at least two charging banks within the energy storage portion.

9. The defibrillation apparatus of claim 1 wherein the energy storage portion further comprises at least one fixed capacitance capacitor.

10. A method for generating a shocking waveform for application to a cardiac cell membrane of a patient, the method comprising the steps of:

sensing at least one patient specific parameter to determine if defibrillation of said cardiac cell membrane is required;

charging an energy storage portion, wherein said energy storage portion comprises at least one variable capacitance capacitor; and

discharging the energy storage portion in the form of a defibrillation waveform; and

delivering said defibrillation waveform to said cardiac cell membrane of said patient.

11. The method of claim 10, wherein said step of charging an energy storage portion comprises charging said at least one variable capacitance capacitor to first voltage level and wherein said first voltage level is less than the voltage level of a comparable non-variable capacitor that stores substantially the same charge and is capable of replacing said at least one variable capacitance capacitor within said energy source.

12. The method of claim 10, wherein the at least one variable capacitance capacitor has a large positive voltage coefficient.

13. The method of claim 10, wherein the pair of electrodes are removably attachable to the patient.

14. The method of claim 10, wherein the shocking waveform is a biphasic waveform.

15. The method of claim 10, wherein the charging step further comprises charging a plurality of variable capacitance capacitors with an energy source, the plurality of variable capacitance capacitors arranged in either a series or parallel orientation.

16. The method of claim 15, wherein the plurality of variable capacitance capacitors define at least two distinct charging banks.

17. The method of claim 15, wherein the energy source is a detachable battery pack.

18. The method of claim 10, wherein the charging step further comprises charging at least one fixed capacitance capacitor.

19. A method of sustaining a level of defibrillation current during the delivery of a defibrillation waveform to the cardiac cell membrane of a patient, the method comprising the steps of:

sensing at least one patient specific parameter to determine if defibrillation of said cardiac cell membrane is required;

charging an energy storage portion, wherein said energy storage portion comprises at least one variable capacitance capacitor; and

discharging the energy storage portion in the form of a defibrillation waveform, wherein upon discharging the energy storage portion a level of a defibrillation current of said energy source decays at a substantially linear rate; and

delivering said defibrillation waveform to said cardiac cell membrane of said patient.

20. A method of sustaining a level of defibrillation current during the delivery of a defibrillation waveform to the cardiac cell membrane of a patient, the method comprising the steps of:

sensing at least one patient specific parameter to determine if defibrillation of said cardiac cell membrane is required;

charging an energy storage portion, wherein said energy storage portion comprises at least one variable capacitance capacitor; and

discharging the energy storage portion in the form of a defibrillation waveform, wherein said at least one variable capacitance capacitor has an initial defibrillation current and wherein said initial defibrillation current is

less than the initial defibrillation current of a comparable non-variable capacitor capable that is capable of replacing said variable capacitance capacitor within said energy storage portion; and

delivering said defibrillation waveform to said cardiac cell membrane of said patient.

\* \* \* \* \*