



US 20030066978A1

(19) **United States**  
(12) **Patent Application Publication** (10) **Pub. No.: US 2003/0066978 A1**  
**Enerson** (43) **Pub. Date: Apr. 10, 2003**

(54) **MALE LUER VALVE**

(52) **U.S. Cl.** ..... **251/86; 251/149.6; 604/905**

(76) **Inventor: Jon R. Enerson, Port Richey, FL (US)**

Correspondence Address:  
**TREXLER, BUSHNELL, GIANGIORGI,**  
**BLACKSTONE & MARR, LTD.**  
**105 W. ADAMS STREET**  
**CHICAGO, IL 60603 (US)**

(57) **ABSTRACT**

A valve that has at least one internal port on a valve core and at least one an internal slot in a valve body. The valve core is biased into a position wherein the port of the valve core is aligned with a sealing surface of the valve body thereby prohibiting fluid flow through the valve. The valve core is slidable such that the port of the valve core becomes aligned with the internal slot of the valve body thereby allowing fluid flow through the valve. Another valve includes a self-aligning valve seat carrier which is pivotably engaged with a valve core member. The self-aligning valve seat carrier engages a sealing surface in a valve body to prohibit fluid flow through the valve, but the valve core is slidable such that the self-aligning valve seat carrier disengages from the sealing surface in order to allow fluid flow through the valve.

(21) **Appl. No.: 10/261,375**

(22) **Filed: Oct. 1, 2002**

**Related U.S. Application Data**

(60) **Provisional application No. 60/327,817, filed on Oct. 9, 2001.**

**Publication Classification**

(51) **Int. Cl.<sup>7</sup> ..... F16L 37/28**




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8





FIG. 9



## MALE LUER VALVE

### BACKGROUND

[0001] This invention generally relates to valves such as luer lock valves which are used primarily in the medical field, and more specifically relates to a slidable type of valve used primarily in the medical field.

[0002] Slidable valves presently exist for use in the medical field. Such valves provide that the valve is initially biased into a closed position, where fluid cannot flow through the valve, and one or more internal components of the valve are slidable within the valve to actuate the valve into an open position, where fluid can flow through the valve.

[0003] One type of medical valve is the subject of U.S. patent application Ser. No. 09/523,354, and is shown in **FIGS. 1 and 2** of the present application. Specifically, **FIG. 1** shows the valve **10** in the closed position (wherein fluid cannot flow through the valve), and **FIG. 2** shows the valve **10** in the open position (wherein fluid can flow through the valve). The valve **10** includes a valve body **12**, a valve poppet **14** with luer taper (with sealing member **16** thereon), an internal resilient valve stem **18**, a metal compression spring **20** and a valve plug **22**, all of which are within the flow path of fluid moving through the valve (the arrows **24** shown in **FIG. 2** illustrate the fluid flow path (in one of two possible directions) through the valve **10**). The valve stem **18** may include flutes or ribs on an external surface **26** thereof to facilitate fluid flow around the stem **18** when the valve **10** is in the open position.

[0004] In use, engagement or mating structure **28**, such as a syringe, another valve or some other structure, engages the valve poppet **14**, pushing it generally into the valve body **12** causing the valve **10** to move from the closed position as shown in **FIG. 1** to the open position as shown in **FIG. 2**. As shown in **FIG. 2**, when the valve **10** is in the open position, the valve stem **18** is disengaged from a valve seat **30** in the valve **10**. This provides that fluid can ultimately flow from a bore **32** provided in the valve poppet **14** to an area **34** adjacent the periphery of the valve stem **18**, or vice versa if the fluid is flowing in the opposite direction.

[0005] In the case where the fluid flows from left-to-right in **FIG. 2**, fluid initially enters the bore **32** in the valve poppet **14** (i.e. from the mating structure **28**), and travels to a notch **36** in the valve poppet **14** (and/or to a notch (not shown) in surface **38** of the valve stem **18**). The valve stem **18** deflects the fluid to an area **34** adjacent the periphery of the valve stem **18**, and the fluid flows along the external surface **26** of the valve stem **18** (and along the ribs, if provided, on the external surface **26** of the valve stem **18**), past the valve seat **30**, along the compression spring **20**, and out the plug **22**, and specifically between fins of the plug **22** and out the valve **10**. In the opposite direction, fluid flows into the plug **22** of the valve **10**, along the compression spring **20**, past the valve seat **30**, along the periphery of the valve stem **18** (and along the ribs, if provided, on the external surface **26** of the valve stem **18**), to the notch **36** in the valve poppet **14** (and/or to a notch (not shown) in surface **38** of the valve stem **18**), and through the bore **32** in the valve poppet **14** to the mating structure **28**.

[0006] The overall design of the valve shown in **FIGS. 1 and 2**—being that there are so many components in the fluid

flow path—results in substantial restriction to fluid flow through the valve **10**. As a result, the valve **10** cannot effectively conduct fluids having viscosities of 1.0 to 1.5 centipoise and above. Additionally, the design provides that there are numerous cavities or “dead areas” for entrapment of fluid within the valve **10**. The existence of dead areas, and the fact that there so many components in the fluid flow path, creates turbulence in the fluid flow as the fluid flows through the valve **10**. The turbulence renders the valve **10** a poor candidate for transmitting human blood, blood products, or any other material which is sensitive to turbulence. With regard to blood, concerns of lysis (i.e. damage to blood cells) and retention of clotted blood within the valve **10** gives rise to problems with possible infusion of thrombotics or fibrous re-injection into a patient. The low viscosity conduction limits of the valve design shown in **FIGS. 1 and 2** restrict its utilization for high viscosity materials, thus limiting broader employment of the valve in a clinical environment.

[0007] Furthermore, the design shown in **FIGS. 1 and 2** provides that while the valve poppet **14** is installed through the one end **40** of the valve **10**, the other components (i.e. the valve stem **18**, compression spring **20**, and plug **22**) are installed through the other end **42**. This complicates and increases the cost of the assembly process.

### OBJECTS AND SUMMARY

[0008] A general object of an embodiment of the present invention is to provide a valve which has increased flow rate and an unobstructed fluid flow path.

[0009] Another object of an embodiment of the present invention is to provide a valve which has fewer components within the fluid flow path.

[0010] Still another object of an embodiment of the present invention is to provide a valve which causes less turbulence to the fluid flow.

[0011] Still yet another object of an embodiment of the present invention is to provide a valve which minimizes the residual volume (i.e. “dead areas”) contributing to fluid entrapment.

[0012] Still yet another object of an embodiment of the present invention is to provide a method of assembling a valve wherein components are installed through one end of a valve body, but not the other.

[0013] Briefly, and in accordance with at least one of the foregoing objects, an embodiment of the present invention provides a valve that has at least one internal port which aligns with an internal slot to permit fluid flow. Specifically, the valve includes a valve body that has a sealing surface and at least one internal slot. A valve core is disposed in the valve body, and the valve core includes at least one port. Spring means is engaged with the valve body and valve core, and the spring means biases the valve core into a closed position wherein the port of the valve core is aligned with the sealing surface of the valve body thereby prohibiting fluid flow through the valve. The valve core is slidable within the valve body such that the valve is actuated into an open position wherein the port of the valve core becomes aligned with the internal slot of the valve body thereby allowing fluid flow through the valve. Preferably, at least one end of the valve is configured for a luer lock fitting.



[0014] A bore extends through the valve core, along a longitudinal axis thereof, and the bore defines a fluid flow area. The one or more ports on the valve core which align with the sealing surface of the valve body when the valve is in the closed position and with the one or more slots in the valve body when the valve is in the open position consists of one or more openings in a wall of the valve core. The valve body also includes a fluid flow area. Hence, a fluid flow path through the valve is defined by the fluid flow area defined through the valve core (i.e. the bore and the one or more ports) and the fluid flow area of the valve body. The spring means is generally between the valve body and valve core, but is not within the fluid flow path through the valve.

[0015] Preferably, each slot in the valve body is larger than each respective port of the valve core, and each port of the valve core is larger than a cross-sectional diameter of the bore which extends through the valve core. Preferably, the valve core includes two ports and the valve body includes two corresponding slots which align with each other when the valve core slides within the valve body to the open position. The ports of the valve core and the slots of the valve body are preferably 180 degrees apart relative to each other.

[0016] Preferably, a first sealing member and a second sealing member are disposed on the valve core, where the first sealing member engages the sealing surface of the valve body whether the valve core is in the open or the closed position, and the second sealing member engages with the sealing surface of the valve body when the valve core is in the closed position, but disengages from the sealing surface of the valve body when the valve core is in the open position. The valve core may include at least one barb which abuts against an internal surface of the valve body when the valve core is biased into the closed position by the spring means. Preferably, the valve body includes a pocket, the valve core includes a shoulder, and the spring means is disposed in the pocket of the valve body and engages the shoulder of the valve core. Again, preferably the spring means is generally between the valve body and valve core, but is not within the fluid flow path through the valve. As an alternative to the sealing members, a resilient material may be over-molded or co-injected on the valve core to enhance the seal with the structure which is engaged with the valve and to enhance the seal between the valve core and valve body.

[0017] Another embodiment of the present invention provides a valve that includes a self-aligning valve seat carrier which is pivotably or adjustably engaged with a valve core member. Specifically, the valve includes a valve body which includes a sealing surface, and the valve core is disposed in the valve body. The self-aligning valve seat carrier also includes a sealing surface. Spring means is engaged with the valve body and the valve core, and the spring means biases the valve core into a closed position wherein the sealing surface of the self-aligning valve seat carrier engages the sealing surface of the valve body thereby prohibiting fluid flow through the valve. The valve core is slidable within the valve body such that the valve is actuated to an open position wherein the sealing surface of the self-aligning valve seat carrier disengages from the sealing surface of the valve body thereby allowing fluid flow through the valve.

[0018] The self-aligning valve seat carrier may take several different configurations. For example, the self-aligning

valve seat carrier may include a pair of arms which engage corresponding recessed grooves proximate the end of the valve core, may include a ball which engages a corresponding socket on the valve core, or may include a barb which engages corresponding structure on an end of the valve core. A sealing member may be disposed on the valve seat carrier, or a sealing material may be co-injected or over-molded onto the exterior surface thereof.

[0019] Another aspect of the present invention provides a method of assembling a valve. The method includes installing a plurality of components through one end of a valve body, and installing no components through an opposite end of the valve body. Hence, the assembly process is simplified and less costly.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0020] The organization and manner of the structure and operation of the invention, together with further objects and advantages thereof, may best be understood by reference to the following description, taken in connection with the accompanying drawings, wherein like reference numerals identify like elements in which:

[0021] FIG. 1 is a side, cross-sectional view of the valve which is the subject of U.S. patent application Ser. No. 09/523,354, showing the valve in a closed position;

[0022] FIG. 2 is a view similar to FIG. 1, but showing the valve in an open position;

[0023] FIG. 3 is a side, cross-sectional view of a valve which is in accordance with an embodiment of the present invention, showing the valve in a closed position;

[0024] FIG. 4 is a view similar to FIG. 3, but showing the valve in an open position;

[0025] FIG. 5 is an exploded view of the valve shown in FIGS. 3 and 4, illustrating that the valve is assembled from a distal end of the valve body;

[0026] FIG. 6 is a side, cross-sectional view of a valve which is in accordance with another embodiment of the present invention;

[0027] FIG. 7 is a set of views relating to a valve which is in accordance with still yet another embodiment of the present invention, specifically there are three side, cross-sectional views—a top-most partial cross-sectional view showing the valve in the closed position, a middle partial cross-sectional view showing the valve in the open position, and a bottom-most partial cross-sectional view showing pivoting of a self-aligning valve seat carrier of the valve—as well as a plan view of the bottom of a valve core of the valve with the valve seat carrier removed;

[0028] FIG. 8 is a set of views similar to FIG. 7, but relating to a valve which is in accordance with still yet another embodiment of the present invention; and

[0029] FIG. 9 is a set of views similar to FIGS. 7 and 8, but relating to a valve which is in accordance with still yet another embodiment of the present invention.

#### DESCRIPTION

[0030] While the present invention may be susceptible to embodiment in different forms, there are shown in the

drawings, and herein will be described in detail, embodiments thereof with the understanding that the present description is to be considered an exemplification of the principles of the invention and is not intended to limit the invention to that as illustrated and described herein.

[0031] Several different valves are shown in FIGS. 3-9. A valve **100a** which is in accordance with a first embodiment of the present invention is shown in FIGS. 3-5, a valve **100b** which is in accordance with a second embodiment of the present invention is shown in FIG. 6, a valve **100c** which is in accordance with a third embodiment of the present invention is shown in FIG. 7, a valve **100d** which is in accordance with a fourth embodiment of the present invention is shown in FIG. 8, and a valve **100e** which is in accordance with a fifth embodiment of the present invention is shown in FIG. 9.

[0032] Each of the valves shown in FIGS. 3-9 provides that fewer components are within the fluid flow path. As a result, each valve provides increased flow rate, a relatively unobstructed fluid flow path, and less turbulent fluid flow. Additionally, each valve minimizes the residual volume (i.e. "dead areas") contributing to fluid entrapment, and each provides enhanced backpressure tolerance when the valve is in the closed position. Additionally, the valves are inexpensive and easy to manufacture. Specifically, the valves shown in FIGS. 3-6 provide that assembly can be performed solely through one end of the valve body, as opposed to some components having to be installed through one end of the valve body and other components of the valve having to be installed through the other end of the valve body during the assembly process.

[0033] The valve **100a** shown in FIGS. 3-5 will be described first and then the differences between the other valves **100b-100e** and the valve **100a** shown in FIGS. 3-5 will be described. The valve **100a** shown in FIGS. 3-5 includes a valve core **102a**, a pair of sealing members **104a**, **106a** which are disposed on the valve core **102a**, a valve body **108a**, and spring means **110a** which is disposed in the valve body **108a**, generally between the valve core **102a** and the valve body **108a**. The valve core **102a** and valve body **108a** are preferably made of plastic, while the sealing members **104a**, **106a** are preferably made of rubber or silicone, and the spring means **110a** is preferably made of metal.

[0034] As shown, the valve body **108a** is a generally hollow, cylindrical component having a central throughbore **112a**. The valve body **108a** may be made of, for example, clear plastic. The valve body **108a** has a distal end **114a** as well as a proximal end **116a** which is generally opposite the distal end **114a**. As shown in FIG. 5, both the valve core **102a** (including the sealing members **104a**, **106a** which are disposed thereon) and the spring means **110a** are installed through the distal end **114a** of the valve body **108a** to assemble the valve **100a**.

[0035] The distal end **114a** of the valve body is preferably configured for a male luer fitting. Specifically, the valve body **108a** preferably includes threading **118a** at the distal end **114a** for engagement with corresponding mating structure **120** (see FIG. 4), such as a syringe, another valve, or some other structure, in a luer lock arrangement.

[0036] The valve body **108a** includes a main body wall **122a** which effectively defines the external surface of the

valve **100a**, and internal walls **124a** which are connected to the main body wall **122a**. As will be described more fully later herein, the internal walls **124a** define sealing surfaces **126a** which cooperate with ports **130a** on the valve core **102a** to prevent fluid flow through the valve **100a**.

[0037] The internal walls **124a** of the valve body **108a** and the main body wall **122a** of the valve body **108a** define a pocket **132a**, and the spring means **110a** is disposed in the pocket **132a**. Specifically, the spring means **110a** is preferably a metal compression spring which has one end disposed in the pocket **132a** in the valve body **108a** and has an opposite end contactably engaged with a shoulder **134a** on the valve core **102a**. The end **135a** of the valve core **102a** preferably includes barbs **136a**, or some other suitable structure, for generally retaining the valve core **102a** in the valve body **108a**, and preventing the valve core **102a** from being pushed completely out of the valve body **108a** by the compression spring **110a** (via contactable engagement with internal surface **138a** of the valve body **108a**—see FIG. 3). Additionally, the barbs **136a** provide that the valve core **102a** can be snapped into the valve body **108a** through the distal end **114a** during assembly (see FIG. 5).

[0038] The valve core **102a** is a generally hollow, cylindrical member having a central throughbore **140a**. The central throughbore **140a** extends along a longitudinal axis **142a** of the valve core **102a** and defines a fluid flow area. The valve core **102a** includes a forward portion **144a**, middle portion **146a** which provides shoulder **134a**, and a rearward portion **148a**. Consistent with the configuration of the distal end **114a** of the valve body **108a**, the forward portion **144a** of the valve core **102a** preferably has a male luer taper to facilitate the luer lock engagement with the corresponding mating structure. Specifically, preferably the forward portion **144a** of the valve core **102a** has a standard ANSI/ISO luer configuration. The middle portion **146a** of the valve core **102a** (which provides shoulder **134a**) contactably engages an internal surface **150a** of the valve body **108a** and is disposed between the forward (**144a**) and rearward (**148a**) portions of the valve core **102a**. As shown in FIG. 4, when mating structure **120**, such as a syringe, another valve, or some other structure is engaged with the valve **100a**, the structure **120** pushably engages the middle portion **146a** of the valve core **102a** causing the valve core **102a** to translate or slide relative to the valve body **108a** which causes the compression spring **110a** to compress and the valve **100a** to actuate into the open position as shown in FIG. 4.

[0039] As shown in FIGS. 3-5, the valve core **102a** includes a pair of ports **130a** on the rearward portion **148a** of the valve core **102a**. The ports **130a** are effectively openings through the surface of the valve core **102a**, in communication with the central throughbore **140a** (and the fluid flow area defined thereby). Preferably, the ports **130a** on the valve core **102a** are 180 degrees apart relative to each other along the external circumferential surface of the rearward portion **148a** of the valve core **102a**.

[0040] The valve **100a** shown in FIGS. 3-5 provides that there are a pair of sealing members **104a**, **106a** disposed on the valve core **102a** proximate the ports **130a** on the valve core **102a**. The sealing members **104a**, **106a** may comprise o-rings. Specifically, one sealing member **104a** is disposed on the valve core **102a** between the ports **130a** and the

middle portion **146a** of the valve core **102a**, and another sealing member **106a** is disposed on the valve core **102a** between the ports **130a** and the end **135a** of the valve core **102a**. As shown in FIG. 5, glands **151a** are preferably provided on the external surface of the valve core **102a** for seating the sealing members **104a**, **106a** on the valve core **102a**.

[0041] The valve **100a** is configured such that the one sealing member **104a** always remains engaged with the sealing surfaces **126a** in the valve **100a** which are provided by the internal walls **124a** of the valve body **108a** regardless of whether the valve **100a** is in the closed (see FIG. 3) or open (see FIG. 4) position. Sealing member **104a** prevents fluid from leaking into the area in which the spring **110a** is located, and does so regardless of whether the valve **100a** is in the closed (see FIG. 3) or open (see FIG. 4) position. The valve **100a** is configured such that the other sealing member **106a** is engaged with the sealing surfaces **126a** when the valve **100a** is in the closed position (see FIG. 3), but becomes disengaged therefrom when the valve **100a** is actuated into the open position (see FIG. 4). Hence, the sealing member **106a** prevents fluid communication between the valve ports **130a** and a fluid flow area **152a** of the valve body **108a** when the valve **100a** is in the closed (see FIG. 3) position.

[0042] Additionally, the valve **100a** is configured such that the ports **130a** on the valve core **102a** align with the sealing surfaces **126a** in the valve **100a** when the valve **100a** is in the closed position (see FIG. 3), but move out of alignment with the sealing surfaces **126a** when the valve **100a** is actuated into the open position (see FIG. 4).

[0043] The valve body **108a** includes internal slots **154a** which correspond with the ports **130a** in the valve core **102a**, and fluid flow area **152a** of the valve body **108a** is adjacent the slots **154a**. Preferably, each of the slots **154a** in the valve body **108a** is larger than each of the respective ports **130a** of the valve core **102a**, and each of the ports **130a** of the valve core **102a** is larger than a cross-sectional diameter **156a** of the central throughbore **140a** which extends through the valve core **102a**. This limits the fluid flow only to that permitted by the inside diameter **156a** of the standard ANSI/ISO luer configuration, which comprises the distal end **114a** of the valve core **102a**.

[0044] The valve core **102a** also includes a seal surface **160a** on its rearward portion **148a** which effectively seals off the slots **154a** on the valve body **108a** when the valve **100a** is in the closed position as shown in FIG. 3. However, when the valve **100a** is actuated into the open position (see FIG. 4), the ports **130a** of the valve core **102a** move out of alignment with the sealing surfaces **126a** of the valve **100a** and into alignment with the corresponding slots **154a** in the valve body **108a**, thereby defining a fluid flow path through the valve **100a** (one possible fluid flow direction is represented by arrows **162a** shown in FIG. 4). Specifically, in a direction from left-to-right in FIG. 4, the fluid flow path is: into the throughbore **140a** in the valve core **102a**, through the ports **130a** in the valve core **102a**, through the corresponding slots **154a** in the valve body **108a**, into the fluid flow area **152a** of the valve body **108a** and out the end **162a** of the valve **100a**. In the other direction, i.e. in a direction from right-to-left in FIG. 4, the fluid flow path is: into the end **162a** of the valve **100a**, through the slots **154a** in the

valve body **108a**, through the ports **130a** in the valve core **102a**, and along (and out) the throughbore **140a** in the valve core **102a**.

[0045] Before mating structure **120**, such as a syringe, another valve, or some other structure is engaged with the valve **100a**, the valve **100a** is in the closed position as shown in FIG. 3. In the closed position, the valve core **102a** is biased into the closed position by the spring means **110a**, the ports **130a** in the valve core **102a** are aligned with the sealing surfaces **126a** in the valve body **108a**, and both sealing members **104a**, **106a** on the valve core **102a** sealingly engage the sealing surfaces **126a**, thereby preventing fluid flow between the central throughbore **140a** in the valve core **102a** and the fluid flow area **152a** in the valve body **108a**. When mating structure **120** engages the valve **100a**, the mating structure **120** pushes the valve core **102a** into the valve body **108a**, causing the valve **100a** to be actuated into the open position as shown in FIG. 4. In the open position, the spring **110a** is compressed, the ports **130a** in the valve core **102a** are aligned with the corresponding slots **154a** in the valve body **108a**, and only sealing member **104a** on the valve core **102a** remains sealingly engaged with the sealing surfaces **126a**. Hence, fluid flow is permitted between the central throughbore **140a** in the valve core **102a** and the fluid flow area **152a** in the valve body **108a**.

[0046] The valve **100b** shown in FIG. 6 is very similar to that shown in FIGS. 3-5, and includes a valve core **102b**, a valve body **108b** and a spring means **110b** very much like the valve **100a** shown in FIGS. 3-5. However, instead of providing that two sealing members, such as o-rings, are disposed on the valve core, the valve **100b** shown in FIG. 6 provides that a sealing material **104b** is co-injected or over-molded onto the exterior surface of the valve core **102b**, on the forward **144b** and rearward **148b** portions. Functionally, the sealing material **104b** which is on the rearward portion **148b** of the valve core **100b** performs the same function as the sealing members **104a**, **106a** shown in FIGS. 3-5. The sealing material **104b** which is on the forward portion **144b** of the valve core **102b** works to provide a seal between the mating structure **120** and the valve core **102b**. The sealing material **104b** which is co-injected or over-molded onto the exterior surface of the valve core **102b** may consist of a rigid substrate material with a different resilient outer surface material shell. The employment of co-injection or over-molding for the valve core **104b** eliminates the requirement of o-ring seals in the design (see FIGS. 3-5) and further reduces the component part count.

[0047] The valves **100c**, **100d**, **100e** shown in FIGS. 7-9 are similar to that shown in FIGS. 3-6, and each includes a valve core **102c**, **102d**, **102e**, valve body **108c**, **108d**, **108e** and spring means **110c**, **110d** (valve **100e** also includes spring means much like the other valves **100a**-**100d**, but the spring means is not specifically shown). However, unlike the valves **100a**, **100b** shown in FIGS. 3-6, each of the valves **100c**, **100d**, **100e** shown in FIGS. 7-9 includes a self-aligning valve seat carrier **200c**, **200d**, **200e** which is pivotally engaged (see the bottom-most cross-sectional view of FIGS. 7-9) with the valve core **102c**, **102d**, **102e**. The valve body **108c**, **108d**, **108e** of each of the valves **100c**, **100d**, **100e** includes a sealing surface **126c**, **126d**, **126e** which, as shown in FIGS. 7-9, may consist of an inclined surface which is inside the valve body **108c**, **108d**, **108e**. The

self-aligning valve seat carrier **200c**, **200d**, **200e** also includes a sealing surface **202c**, **202d**, **202e** provided by, for example, a sealing member which is disposed thereon.

[0048] The spring means **110c**, **110d** of each valve is engaged with the valve body **108c**, **108d**, **108e** and the valve core **102c**, **102d**, **102e**, and the spring means **110c**, **110d** biases the valve core **102c**, **102d**, **102e** into a closed position (see the top-most cross-sectional view of each of FIGS. 7-9) wherein the sealing surface **202c**, **202d**, **202e** of the self-aligning valve seat carrier **200c**, **200d**, **200e** engages the sealing surface **126c**, **126d**, **126e** of the valve body **108c**, **108d**, **108e**, thereby prohibiting fluid flow through the valve **100c**, **100d**, **100e**.

[0049] When mating structure **120** engages the valve core **102c**, **102d**, **102e**, the valve core **102c**, **102d**, **102e** slides within the valve body **108c**, **108d**, **108e** such that the valve **100c**, **100d**, **100e** is actuated to an open position (see the middle cross-sectional view of each of FIGS. 7-9) wherein the sealing surface **202c**, **202d**, **202e** on the self-aligning valve seat carrier **200c**, **200d**, **200e** disengages from the sealing surface **126c**, **126d**, **126e** of the valve body **108c**, **108d**, **108e** thereby allowing fluid flow through the valve **100c**, **100d**, **100e** (as represented by arrows **206c**, **206d**, **206e**). In the valve **100c** shown in FIG. 7, the self-aligning valve seat carrier **200c** preferably includes a hollow portion **210c** that terminates in one or more openings **212c** that allows fluid to flow through the valve seat carrier **200c**. In the other valves **100d**, **100e**, the bottom **214d**, **214e** of the valve core **102d**, **102e** provides openings **216d**, **216e** which allow fluid flow between fingers **218d**, **218e**.

[0050] The self-aligning valve seat carrier may take several different configurations. For example, in the valve **100c** shown in FIG. 7, the self-aligning valve seat carrier **200c** includes a pair of arms **220c** which engage corresponding recessed grooves **222c** proximate the bottom **214c** of the valve core **102c**. The sealing member **202c** which is disposed on the valve seat carrier **200c** may consist of an o-ring. Alternatively, a sealing material may be co-injected or over-molded onto the exterior surface of the valve seat carrier.

[0051] In the valve **100d** shown in FIG. 8, the self-aligning valve seat carrier **200d** includes a ball **230d** which engages a corresponding socket **232d** on the valve core **102d**, wherein the socket **232d** is provided via the four fingers **218d** which are at the bottom **214d** of the valve core **102d** (see the bottom-most view of FIG. 8). In the valve shown in FIG. 9, the self-aligning valve seat carrier **200e** includes a barb **230e** which engages corresponding structure **232e** on the end **214e** of the valve core **102e**, wherein the corresponding structure **232e** is provided via the four fingers **218e** which are at the bottom **214e** of the valve core **102e** (see the bottom-most view of FIG. 9). The sealing member **202d**, **202e** which is disposed on each of the valve seat carriers **200d**, **200e** shown in FIGS. 8 and 9 may consist of an attached resilient seal material, wherein an additional seal is preferably provided at the valve carrier **200d**, **200e**/valve body **108d**, **108d** interface. Alternatively, a sealing material may be co-injected or over-molded onto the exterior surface of the valve seat carrier **200d**, **200e** in each of the valves **100d**, **100e** shown in FIGS. 8 and 9.

[0052] Regardless, the fact that each valve seat carrier **200c**, **200d**, **200e** is pivotable and self-aligning provides that

each valve seat carrier **200c**, **200d**, **200e** can articulate (as shown in the bottom-most cross-sectional view of each of FIGS. 7-9), and an enhanced seal is achieved between the sealing surface **126c**, **126d**, **126e** of the valve body **108c**, **108d**, **108e** and the valve seat carrier **200c**, **200d**, **200e** when the valve **100c**, **100d**, **100e** is in the closed position (the top-most cross-sectional view of each of FIGS. 7-9).

[0053] The bottom **214c**, **214d**, **214e** of each of the valve cores **102c**, **102d**, **102e** is shown in the bottom view of each of FIGS. 7-9. As shown, each of the valve cores **102d**, **102e** of valves **100d**, **100e** includes fingers **218d**, **218e** which engage the valve seat carrier **200d**, **200e**. With regard to the arrangement shown in FIG. 8, wherein the valve seat carrier **200d** includes a ball **230d** which is received in a corresponding socket **232d** in the end **214d** of the valve core **102d**, in the closed position (the top view of FIG. 8), the fingers **218d** of the valve core **102d** are prevented from outward deflection by the valve body **108d**. This prevents pressure exerted by the compression spring **100d** from disengaging the ball **232d** of the valve seat carrier **200d** and allows the valve core **102d** to escape from the assembly. In the open position (the middle view of FIG. 8), the fingers **218d** of the valve core **102d** are free to deflect outward by the ball **232d** sufficiently to allow the ball **232d** of the valve seat carrier **200d** to be snapped into location and allow the valve seat carrier **200d** to pivot, i.e. have angular movement.

[0054] Each of the valves **100a**-**100e** shown in FIGS. 3-9 provides that fewer components are within the fluid flow path, that flow rate is increased (when the valve is open), that there is a relatively unobstructed fluid flow path, and that there is less turbulence introduced into the flow. Additionally, each valve minimizes dead areas which can contribute to fluid entrapment, and each provides enhanced backpressure tolerance when the valve is in the closed position. Additionally, the valves are inexpensive and easy to manufacture.

[0055] Specifically, valves **100a** and **100b** provide that assembly can be performed solely through one end (i.e. end **114a** shown in FIG. 5) of the valve body **108a**, **108b**, as opposed to some components having to be installed through one end of the valve body and other components of the valve having to be installed through the other end of the valve body during the assembly process.

[0056] While embodiments of the present invention are shown and described, it is envisioned that those skilled in the art may devise various modifications of the present invention without departing from the spirit and scope of the foregoing disclosure.

What is claimed is:

1. A valve comprising: a valve body which includes a sealing surface and at least one internal slot; a valve core disposed in said valve body and including at least one port; spring means engaged with said valve body and said valve core, said spring means biasing said valve core into a closed position wherein said port of said valve core is aligned with said sealing surface of said valve body thereby prohibiting fluid flow through said valve, said valve core being slidable generally within said valve body to an open position wherein said port of said valve core is aligned with said internal slot of said valve body thereby allowing fluid flow through said valve.

2. A valve as defined in claim 1, wherein said valve core includes a body and a bore through said body along a longitudinal axis of said body, wherein said body of said valve core includes a wall and said port comprises an opening in said wall.

3. A valve as defined in claim 2, wherein said valve body includes a fluid flow area and the bore through said body of said valve core defines a fluid flow area, wherein a fluid flow path through said valve is defined by said fluid flow area defined by said bore through said body of said valve core and said fluid flow area of said valve body, and said spring means is not within said fluid flow path through said valve.

4. A valve as defined in claim 2, wherein said slot in said valve body is larger than said port of said valve core, and said port of said valve core is larger than a cross-sectional diameter of said bore through said valve core.

5. A valve as defined in claim 1, wherein said valve core includes two ports and said valve body includes two slots, said valve core being slidable generally within said valve body to an open position wherein said ports of said valve core are aligned with said slots of said valve body thereby allowing fluid flow through said valve.

6. A valve as defined in claim 5, wherein said ports of said valve core are 180 degrees apart and said slots of said valve body are 180 degrees apart.

7. A valve as defined in claim 1, wherein said slot in said valve body is larger than said port of said valve core.

8. A valve as defined in claim 1, wherein at least one end of said valve is configured for a Luer lock fitting.

9. A valve as defined in claim 1, further comprising at least one sealing member disposed on said valve core and engaged with said sealing surface of said valve body.

10. A valve as defined in claim 1, further comprising a first sealing member disposed on said valve core, said first sealing member engaged with said sealing surface of said valve body when said valve core is in said open and closed positions, and further comprising a second sealing member disposed on said valve core, said second sealing member engaged with said sealing surface of said valve body when said valve core is in said closed position, but disengaged from said sealing surface of said valve body when said valve core is in said open position.

11. A valve as defined in claim 1, said valve core including at least one barb which abuts against an internal surface of said valve body when said valve core is biased into said closed position by said spring means.

12. A valve as defined in claim 1, wherein said valve body includes a pocket and said valve core includes a shoulder, wherein said spring means is disposed in said pocket of said valve body and engages said shoulder of said valve core.

13. A valve as defined in claim 1, further comprising a resilient material at least one of over-molded and co-injected on said valve core.

14. A valve as defined in claim 13, wherein said resilient material is disposed on said valve core proximate said port.

15. A valve comprising: a valve body which includes a sealing surface; a valve core disposed in said valve body; a self-aligning valve seat member pivotably engaged with said valve core, said self-aligning valve seat member including a sealing surface; and spring means engaged with said valve body and said valve core, said spring means biasing said valve core into a closed position wherein said sealing surface of said self-aligning valve seat member engages said sealing surface of said valve body thereby prohibiting fluid flow through said valve, said valve core being slidable generally within said valve body to an open position wherein said sealing surface of said self-aligning valve seat member disengages from said sealing surface of said valve body thereby allowing fluid flow through said valve.

16. A valve as defined in claim 15, wherein said self-aligning valve seat member includes a hollow portion which allows fluid flow through the self-aligning valve seat member.

17. A valve as defined in claim 15, wherein said self-aligning valve seat member includes a barb which engages said valve core.

18. A valve as defined in claim 15, wherein said self-aligning valve seat member includes a ball which engages a corresponding socket on said valve core.

19. A valve comprising: a valve body which includes a first sealing surface and a second sealing surface; a valve core disposed in said valve body; a sealing member disposed on said valve core and engaged with said first sealing surface of said valve body; a self-aligning valve seat member pivotably engaged with said valve core; a sealing member disposed on said self-aligning valve seat member; and spring means engaged with said valve body and said valve core, said spring means biasing said valve core into a closed position wherein said sealing member on said self-aligning valve seat member engages said second sealing surface of said valve body thereby prohibiting fluid flow through said valve, said valve core being slidable generally within said valve body to an open position wherein said sealing member on said self-aligning valve seat member disengages from said second sealing surface of said valve body thereby allowing fluid flow through said valve.

\* \* \* \* \*