

(21) Application No: 2006383.0

(22) Date of Filing: 30.04.2020

(71) Applicant(s):
Creo Medical Limited
Riverside Court, Beaufort Park Way, CHEPSTOW,
NP16 5UH, United Kingdom

(72) Inventor(s):
Christopher Paul Hancock
George Christian Ullrich
David Webb
Louis Turner
George Hodgkins
Shaun Preston
Simon Meadowcroft

(74) Agent and/or Address for Service:
Mewburn Ellis LLP
Aurora Building, Counterslip, Bristol, BS1 6BX,
United Kingdom

(51) INT CL:
A61L 2/14 (2006.01) **A61L 2/26** (2006.01)
H05H 1/46 (2006.01)

(56) Documents Cited:
GB 2574365 A **GB 2562110 A**
GB 2520197 A

(58) Field of Search:
INT CL **A61L, H05H**
Other: **WPI, EPODOC**

(54) Title of the Invention: **Sterilisation apparatus for producing plasma and hydroxyl radicals**
Abstract Title: **Sterilisation device for generating a flow of hydroxyl radicals**

(57) A sterilisation device for generating a flow of hydroxyl radicals comprising: a housing defining a water mist fluid flow path between an inlet for receiving water mist and an outlet for directing a flow of hydroxyl radicals towards a region to be sterilised; an energy delivery tip 205 configured to produce a thermal or non-thermal plasma; a coaxial transmission line 206 arranged to convey radiofrequency (RF) and/or microwave frequency electromagnetic (EM) energy; and a gas conduit 224 in the housing and arranged to deliver gas to the energy delivery tip 205. The energy delivery tip 205 comprises: a first electrode 214 electrically connected to an inner conductor 208 of the coaxial transmission line 206; and a second electrode 216 electrically connected to an outer conductor 210 of the coaxial transmission line 206. The second electrode 216 defines an internal volume of the energy delivery tip 205, wherein the first electrode 214 extends longitudinally within the internal volume. The first electrode 214 and second electrode 216 are configured to strike a plasma in the gas delivered to the energy delivery tip 205 and direct the plasma into the water mist fluid flow path to form hydroxyl radicals therein.




FIG. 2




FIG. 1





FIG. 3



4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
8

**STERILISATION APPARATUS FOR PRODUCING PLASMA AND HYDROXYL
RADICALS**

FIELD OF THE INVENTION

5

The invention relates to sterilisation systems suitable for clinical use, e.g. on the human body, medical apparatuses, or hospital bed spaces. For example, the invention may provide a system that can be used to destroy or treat certain bacteria and/or viruses associated with the human or animal biological system and/or the surrounding environment. This invention is particularly useful for sterilising or decontaminating enclosed or partially enclosed spaces.

10

15

BACKGROUND TO THE INVENTION

Bacteria are single-celled organisms that are found almost everywhere, exist in large numbers and are capable of dividing and multiplying rapidly. Most bacteria are harmless, but there are three harmful groups; namely: cocci, spirilla, and bacilla. The cocci bacteria are round cells, the spirilla bacteria are coil-shaped cells, and the bacilli bacteria are rod-shaped. The harmful bacteria cause diseases such as tetanus and typhoid.

20

25

Viruses can only live and multiply by taking over other cells, i.e. they cannot survive on their own. Viruses cause diseases such as colds, flu, mumps and AIDS. Viruses may be transferred through person-to-person contact, or through contact with region that is contaminated with respiratory droplets or other virus-carrying bodily fluids from an infected person.

30

Fungal spores and tiny organisms called protozoa can cause illness.

35

Sterilisation is an act or process that destroys or eliminates all form of life, especially micro-organisms. During the process of plasma sterilisation, active agents are produced. These active agents are high intensity ultraviolet photons and free radicals, which are atoms or assemblies of atoms with chemically unpaired electrons. An attractive feature of plasma sterilisation is that it is possible to achieve sterilisation at relatively low temperatures, such as

40

body temperature. Plasma sterilisation also has the benefit that it is safe to the operator and the patient.

Plasma typically contains charged electrons and ions as well as chemically active species, such as ozone, nitrous oxides, and hydroxyl radicals. Hydroxyl radicals are far more effective at oxidizing pollutants in the air than ozone and are several times more germicidal and fungicidal than chlorine, which makes them a very interesting candidate for destroying bacteria or viruses and for performing effective decontamination of objects contained within enclosed spaces, e.g. objects or items associated with a hospital environment.

OH radicals held within a "macromolecule" of water (e.g. a droplet within a mist or fog) are stable for several seconds and they are 1000 times more effective than conventional disinfectants at comparable concentrations.

An article by Bai et al titled "Experimental studies on elimination of microbial contamination by hydroxyl radicals produced by strong ionisation discharge" (Plasma Science and Technology, vol. 10, no. 4, August 2008) considers the use of OH radicals produced by strong ionisation discharges to eliminate microbial contamination. In this study, the sterilisation effect on *E. coli* and *B. subtilis* is considered. The bacteria suspension with a concentration of 10^7 cfu/ml (cfu = colony forming unit) was prepared and a micropipette was used to transfer 10 μ l of the bacteria in fluid form onto 12 mm $\times$ 12 mm sterile stainless steel plates. The bacteria fluid was spread evenly on the plates and allowed to dry for 90 minutes. The plates were then put into a sterile glass dish and OH radicals with a constant concentration were sprayed onto the plates. The outcomes from this experimental study were:

1. OH radicals can be used to cause irreversible damage to cells and ultimately kill them;

2. The threshold potential for eliminating micro-organisms is ten thousandths of the disinfectants used at home or abroad;

3. The biochemical reaction with OH is a free radical reaction and the biochemical reaction time for eliminating micro-organisms is about 1 second, which meets the need for rapid elimination of microbial contamination, and the lethal

time is about one thousandth of that for current domestic and international disinfectants;

4. The lethal density of OH is about one thousandths of the spray density for other disinfectants - this will be helpful for eliminating microbial contamination efficiently and rapidly in large spaces, e.g. bed-space areas; and

5. The OH mist or fog drops oxidize the bacteria into CO₂, H₂O and micro-inorganic salts. The remaining OH will also decompose into H₂O and O₂, thus this method will eliminate microbial contamination without pollution.

WO 2009/060214 discloses sterilisation apparatus arranged controllably to generate and emit hydroxyl radicals. The apparatus includes an applicator which receives RF or microwave energy, gas and water mist in a hydroxyl radical generating region. The impedance at the hydroxyl radical generating region is controlled to be high to promote creation of an ionisation discharge which in turn generates hydroxyl radicals when water mist is present. The applicator may be a coaxial assembly or waveguide. A dynamic tuning mechanism e.g. integrated in the applicator may control the impedance at the hydroxyl radical generating region. The delivery means for the mist, gas and/or energy can be integrated with each other.

SUMMARY OF THE INVENTION

At its most general, the invention provides a sterilisation device arranged to generate and deflect a thermal or non-thermal plasma into a flow of water mist in order to provide a stream containing hydroxyl radicals. The stream may be directed on to a surface or object to perform sterilisation.

According to the invention, there is provided a sterilisation device for generating a flow of hydroxyl radicals, the sterilisation device comprising: a housing defining a water mist fluid flow path between an inlet for receiving water mist and an outlet for directing a flow of hydroxyl radicals towards a region to be sterilised; an energy delivery tip configured to produce a thermal or non-thermal plasma; a coaxial transmission line mounted in the housing and arranged to convey radiofrequency (RF) and/or microwave frequency electromagnetic (EM) energy to the energy delivery

tip; and a gas conduit mounted in the housing and arranged to deliver gas to the energy delivery tip, wherein the coaxial transmission line comprises an inner conductor, an outer conductor, and a dielectric material separating the inner conductor from the outer conductor, wherein the energy delivery tip extends from a distal end of the coaxial transmission line, and wherein the energy delivery tip comprises: a first electrode electrically connected to the inner conductor of the coaxial transmission line; and a second electrode electrically connected to the outer conductor of the coaxial transmission line, wherein the second electrode is configured to define an internal volume of the energy delivery tip, wherein the first electrode extends longitudinally within the internal volume, wherein the first electrode and second electrode are configured to: strike a plasma in the gas delivered to the energy delivery tip, and direct the plasma into the water mist fluid flow path to form hydroxyl radicals therein.

In use, the sterilisation device is configured to produce a plasma, which is directed into a flow path of water mist to produce hydroxyl radicals for sterilisation. The device may also be capable of use in the absence of the water mist, where sterilisation is performed by the plasma alone.

The plasma may be directed by the first electrode and second electrode in a longitudinal direction parallel with an axis of the coaxial transmission line. The water mist flow path may intersect the plasma as it exits the energy delivery tip. Alternatively, the plasma may be deflected by the first electrode and second electrode in a transverse direction that intersects a longitudinally directed water mist fluid flow path. These arrangements facilitate a longitudinally directed water mist fluid flow path, which is useful for providing a directable sterilisation beam.

The device may be a handheld unit. For example, the housing may be a portable unit, e.g. comprising a handle or grip. Providing a handheld unit may facilitate directing the flow of hydroxyl radicals to sterilise any surface or object as required.

The energy delivery tip advantageously defines a bipolar (e.g. coaxial) structure to produce a high electric field from received RF and/or microwave frequency energy in the internal

volume to strike and sustain a thermal or non-thermal plasma in the gas present in the volume. For example, a short pulse (e.g. having a duration of 10 ms or less, e.g. between 1 ms and 10 ms) of RF energy may be used to strike the plasma. A longer microwave pulse may be used to sustain the plasma.

However, it may also be possible to strike the plasma using the microwave frequency energy, e.g. by using a microwave resonator or an impedance transformer, i.e. a quarter wave transformer that transforms a low voltage to a higher voltage to strike plasma using a higher impedance transmission line that is a quarter wave (or an odd multiple thereof) long at the frequency of operation. This high impedance line may be switched in to strike plasma and switched out (i.e. to return to a lower impedance line) once the plasma has been struck and it is required to sustain plasma. A power PIN or varactor diode may be preferably used to switch between the two states, although it may be possible to use a co-axial or waveguide switch.

Alternatively, the energy delivery tip may be configured to strike and sustain plasma using only microwave energy through the provision of two quarter wavelength impedance transformed at the distal end of the coaxial transmission line. A first quarter wavelength transformer is configured to reduce the impedance of the coaxial transmission line, e.g. from 50 Ω to a target impedance (e.g. 25 Ω or the like). Once struck, the plasma in the internal volume will present a lower impedance, and hence the transformation can assist with power delivery into the struck plasma in order to sustain it.

A second (distalmost) quarter wavelength transformer is then provided with a much higher impedance, e.g. 200 Ω or more. The second quarter wavelength transformer operates to transform the lower impedance at the distal end of the first transformer to a much higher distal impedance, e.g. of 1600 Ω . Assuming a lossless line and an input microwave power of 100 W, a voltage of 400 V is achievable at the distal end of the second quarter wavelength transformer. The dimensions of the first and quarter wavelength transformers can be configured to provide a distal voltage capable of striking a plasma.

Preferably, the energy delivery tip is located within the housing. The first electrode and second electrode may define an exit from the internal volume, wherein the exit is located

at or in the outlet. The first electrode may be an elongate element extending in the longitudinal direction. It may be straight, or may be provided as another shape. For example, in some embodiments the first electrode may be helical.

5 Optionally, the first electrode may be formed of a portion of the inner conductor that extends beyond a distal end of the outer conductor.

The energy delivery tip may be open at its distal end to form the opening for directing plasma out of the energy
10 delivery tip. In such embodiments, the plasma is directed out of the energy delivery tip in a longitudinal direction. Alternatively, the energy delivery tip may comprise a conductive cap mounted on the first electrode at a distal end of the internal volume, the conductive cap being spaced from a
15 distal end of the second electrode to define the outlet for directing plasma out of the internal volume and into the fluid flow path, wherein plasma is directed radially outwards of the energy delivery tip at into the fluid flow path. For example, the fluid flow path may be formed coaxially with the energy
20 delivery tip. The conductive cap may ensure that plasma is efficiently produced and helps to direct substantially all of the plasma into the fluid flow path to maximised production of hydroxyl radicals. The conductive cap effectively acts as an extension of the first electrode for generation or plasma.

25 Advantageously, the fluid flow path tapers towards the outlet. In this way, the velocity of hydroxyl radicals may be increased, such that the radicals are more effectively projected towards a surface or object which is to be sterilised. In some embodiments, particularly where the energy
30 delivery tip is located at or about the outlet, tapering of the flow path in this way ensures that substantially all of the water mist passes through a plasma to maximise the production of hydroxyl radicals.

Preferably, the energy delivery tip further comprises an
35 insulating cap mounted at a distal end of the coaxial transmission line to isolate the coaxial transmission line from the internal volume, and wherein the gas conduit is in fluid communication with the internal volume via a flow path formed between the insulating cap and the second electrode.
40 The insulating cap may be mounted within the second electrode, e.g. to define a proximal end of the internal volume. The

flow path may comprise a plurality of openings in the second electrode that permit gas flow around the insulating cap. The plurality of openings may be regularly spaced to facilitate a uniform flow of gas into the internal volume.

5 The insulating cap may help to ensure that plasma is generated in a distal part of the energy delivery tip, and may also help to direct generated plasma out of the energy delivery tip. In some embodiments, the insulating cap may have a chamfered distal end in the region of an opening through the
10 second electrode. This may help to increase velocity of gas along the flow path the second electrode, aiding throughput of gas and direction of plasma out of the distal end of the energy delivery tip.

 The second electrode may be a cylinder. The plurality of
15 openings may each comprise a longitudinal notch in the cylinder. For example, a proximal end of the second electrode may be castellated to provide the plurality of openings.

 The energy delivery tip may comprise an insulating dielectric material located between the first electrode and
20 the second electrode in the internal volume. The dielectric material may be a piece of quartz, or other similar low loss material. Preferably the dielectric material is provided as a cylinder to sit within the second electrode. The dielectric material causes an increase in the electric field in the gas-
25 filled gap beside the insulating dielectric material which aids the production of plasma. In addition, the dielectric material reduces the size of the internal volume of the energy delivery tip, which increases the flow rate of gas therethrough and so plasma is projected further from the
30 energy delivery tip. This may be particularly advantageous in embodiments where plasma is directed out of the tip longitudinally, and/or where the device is configured to sterilisation using plasma only.

 According to a second aspect of the invention there is
35 provided a sterilisation apparatus comprising a sterilisation device according to the first aspect, a mist generator, a gas supply, and a generator for supplying radiofrequency (RF) and/or microwave frequency electromagnetic (EM) energy to the handheld sterilisation device. RF EM energy may be for
40 striking the plasma, and may be received as a high voltage pulse. The microwave EM energy may be for sustaining the

plasma, i.e. delivering power into the plasma to maintain the state of ionisation. This may also be received as a pulse. The plasma may be struck repeatedly in a manner to produce a quasi-continuous beam of plasma.

5 The mist generator may comprise either an ultrasonic transducer or a heating element. In this way, the mist generator may supply a mist (e.g. moisture or fog) to the handheld sterilisation device for the production of hydroxyl radicals from water. As a water mist is provided, the
10 apparatus does not need to use any chemical cleaning agents, and so no harmful by-products result from sterilisation using the present apparatus.

 Preferably the gas supply is a supply of argon gas. However, any other suitable gas may be chosen, e.g. carbon
15 dioxide, helium, nitrogen, a mixture of air and any one of these gases, for example 10% air/90% helium.

 Advantageously, the generator may be powered by a battery, such that the generator is portable. Preferably the mist generator and the gas supply are also portable such that
20 a user may easily operate the sterilisation apparatus, and sterilisation can be easily performed in any necessary environment.

 Herein, the term "inner" means radially closer to the centre (e.g. axis) of the coaxial transmission line, energy
25 delivery tip, and/or applicator. The term "outer" means radially further from the centre (axis) of the coaxial transmission line, energy delivery tip, and/or applicator.

 The term "conductive" is used here to mean electrically conductive, unless the context dictates otherwise.

30 Herein, the terms "proximal" and "distal" refers to the ends of the applicator. In use, the proximal end is closer to a generator for providing the RF and/or microwave energy, whereas the distal end is further from the generator.

 In this specification "microwave" may be used broadly to
35 indicated a frequency range of 400 MHz to 100 GHz, but preferably in the range 1 GHz to 60 GHz. Specific frequencies that have been considered are: 915 MHz, 2.45 GHz, 3.3 GHz, 5.8 GHz, 10 GHz, 14.5 GHz, and 25 GHz. In contrast, this specification uses "radiofrequency" or "RF" to indicate a
40 frequency range that is at least three orders of magnitude lower, e.g. up to 300 MHz, preferably 10 kHz to 1MHz, and most

preferably 400 kHz. The microwave frequency may be adjusted to enable the microwave energy delivered to be optimised. For example, an energy delivery tip may be designed to operate at a certain frequency (e.g. 900 MHz), but in use the most efficient frequency may be different (e.g. 866 MHz).

BRIEF DESCRIPTION OF THE DRAWINGS

Features of the invention are now explained in the detailed description of examples of the invention given below with reference to the accompanying drawings, in which:

Fig. 1 is a schematic diagram of a sterilisation apparatus according to an embodiment of the present invention;

Fig. 2 is a diagram of an applicator;

Fig. 3 is a cross-sectional view of the applicator shown in Fig. 2; and

Fig. 4 is a cross-sectional view of a second applicator.

DETAILED DESCRIPTION; FURTHER OPTIONS AND PREFERENCES

This invention relates to a device for performing sterilisation using hydroxyl radicals that are generated by creating a plasma in the presence of water mist.

Fig. 1 is a schematic diagram of a sterilisation apparatus 100 which is an embodiment of the present invention. The apparatus 100 is capable of generating hydroxyl (OH) radicals in order to sterilise a surface or an area. For example, the apparatus 100 may be used to sterilise medical apparatuses or hospital bed spaces.

The apparatus 100 comprises a generator 102 which able to controllably deliver radiofrequency (RF) and/or microwave energy to an applicator 104. The generator may be of type disclosed in WO 2012/076844, for example. The generator 102 is connected to the applicator 104 by a coaxial cable 106. The coaxial cable 106 comprises an inner conductor, an outer conductor and a dielectric material separating the inner conductor from the outer conductor. The coaxial cable 106 may couple energy into the applicator 104 through a QMA connector or the like. In some examples, the generator 102 may be arranged to monitor reflected signals (i.e. reflected power) received back from the applicator 104 in order to determine an

appropriate signal to be conveyed to the applicator 104. The radiofrequency and/or microwave energy is utilised at the applicator 104 in order to strike and sustain a thermal or non-thermal plasma in order to generate hydroxyl radicals in a manner which is explained in more detail below. In some examples, the thermal or non-thermal plasma may be used directly to sterilise surfaces.

The apparatus 100 further comprises a mist generator 108, which is arranged to deliver water mist (e.g. moisture or fog) to the applicator 104. The mist generator 108 may generate a mist by means of an ultrasonic transducer, for example. Alternatively, the mist generator 108 may be arranged to heat water to generate steam or mist to be passed to the applicator 104. The mist is supplied to the applicator 104 in order to generate hydroxyl radicals by a process which will be explained in more detail below. By using mist generator 108 in this way the apparatus 100 can be used to sterilise surfaces or objects without the use of any cleaning chemicals, reducing costs associated with sterilisation and allowing sterilisation to be performed when cleaning chemicals are in short supply. The use of hydroxyl radicals for sterilisation also ensures that there are no harmful by-products.

The mist generator 108 may include a pump or other fluid driving unit to cause generated mist to flow towards the applicator 104.

A gas supply 110 is connected to the applicator 104 to supply gas for forming a plasma which is used to generate hydroxyl radicals in a manner which will be explained below. The gas supply 110 may be a supply of any suitably inert gas for formation of a non-thermal or thermal plasma, for example argon, helium, nitrogen, carbon dioxide or a combination thereof. The gas supply 110 may be configured to allow adjustment of the flow rate of gas which is delivered to the applicator 104. The gas supply can supply between 1.5 and 10 litres of gas per minute, for example.

It may not be essential to provide an independent driving unit for mist flow. Instead, the mist may naturally diffuse towards the applicator. The mist may be entrained by a flow of gas, which in turn will accelerate the diffusion rate of the mist.

The flow rate of gas may be in the range 1.5 to 15 litres/minute, preferably between 2 and 6 litres/minute. The mist generator 108 may be arranged to generate sufficient mist for the mist to form at least 2% by volume of the combined gas/mist stream. The flow rate of the gas may be controlled to reach a desired proportion of gas and mist in the combined stream.

In some embodiments of the invention it is envisaged that the generator 102, the mist generator 108 and the gas supply 110 may each be portable, and the applicator 104 may be a handheld applicator such that the present invention provides an effective sterilisation apparatus which is easily transportable by a user.

The applicator 104 is shown in more detail in Figs. 2 to 4 below. To sterilise a surface, a plasma is created in the applicator 104 by applying energy from the generator 102 to the gas delivered from the gas supply 110. For example, RF energy may be used to strike a plasma and microwave energy may be used to sustain the plasma. For example, plasma may be generated as disclosed in WO 2009/060213. Simultaneous with the generation of plasma, water mist from the mist generator 108 is passed through a housing of the applicator 104 along a fluid flow path which passes through the plasma in order to produce a spray 112 of hydroxyl radicals which pass out of the applicator 104 to be directed at a surface or into an area for sterilisation. Examples of hydroxyl radical generation in this manner are disclosed in WO 2009/060214, for example.

Fig. 2 shows a schematic view of a first applicator 200 which may be used in an embodiment of the present invention. In particular, Fig. 2 shows detail regarding an energy delivery tip of the applicator 200. A cross-sectional view showing the applicator more generally is shown in Fig. 3.

The applicator 200 may be produced at any suitable scale. For example, the applicator may be sized to be gripped by a human hand. Alternatively, a larger version suitable for mounted on a stand may be manufactured. In use, the stream of plasma and/or OH radicals emitted by the applicator may be directed into a volume to be sterilized, e.g. the inside of a vehicle (e.g. ambulance) or a hospital bed or surgical suite.

The applicator 200 comprises a generally elongate housing 202, which contains components required to generate hydroxyl

radicals which are directed out of a distal outlet 204 towards a surface or object to be sterilised. In particularly preferred embodiments the applicator 200 may be handheld by a user to manually pass the applicator 200 over the surface or object.

Within the housing 202, the applicator 200 comprises an energy delivery structure that comprises a coaxial transmission line 206 that has an energy delivery tip 205 at a distal end thereof. A proximal end of coaxial transmission line 206 terminates in a QMA connector 207 or the like provided such that RF and/or microwave energy may be introduced to the energy delivery structure from a generator, e.g. via a cable as discussed above in relation to Fig. 1.

The coaxial transmission line 206 comprises an inner conductor 208, an outer conductor 210 and a dielectric material 212 separating the inner conductor 208 and the outer conductor 210. The coaxial transmission line 206 lies along a longitudinal axis of the housing 202.

The energy delivery tip 205 comprises a first electrode 214 electrically connected to the inner conductor 208, a second electrode 216 electrically connected to the outer conductor 210, and a conductive end cap 218, which is spaced away from the distal end of the second electrode 216 to define a gap 220. In this embodiment, the second electrode 216 is provided as a hollow cylinder which is open at each end, and the first electrode 214 is positioned generally along the longitudinal axis of the second electrode 216. An annular space is thereby defined between the first electrode 214 and the second electrode 216.

The first electrode 214 may be formed by an extension of the inner conductor 208 of the coaxial transmission line 206. The first electrode 214 is preferably straight, though in some examples the first electrode 214 may be provided in other shapes. For example, the first electrode 214 may be a helical electrode.

The conductive end cap 218 is a disc of conductive material (e.g. copper, silver, gold or plated steel) that is electrically connected to the first electrode 214 and shaped to lie over the mouth of the opening to the second electrode 216. The conductive end cap 218 is displaced from the distal end of the second electrode 216 in the longitudinal direction

to form the gap 220. The gap 220 is smaller than the radial separation of the first electrode 214 and second electrode 216, i.e. the radial distance between the outer surface of the first electrode 214 and the inner surface of the hollow cylinder that forms the second electrode 216. For example, the gap 220 between the end cap 218 and the second electrode 216 may have a length in the longitudinal direction of around 0.5 mm.

The first electrode 214, second electrode 216 and conductive end cap 218 are configured such that, when energy (e.g. an RF signal) is supplied to the coaxial transmission line 206, a high voltage condition is set up in and around the gap 220. The input signal may be control to cause the voltage to be high enough at the gap 220 to strike a plasma in gas flowing through or past an outer surface of the probe tip 205.

The effect of the geometry of the end cap 218 is to create a plasma generation region within the probe tip 205 at its distal end. Thermal or non-thermal plasma may be struck and sustain in this region through suitable delivery of RF and microwave energy through the coaxial transmission line 206 as is known.

As discussed below, in this embodiment the gas from which the plasma is formed is supplied to the annular space formed between the first electrode 214 and the second electrode 216. The gas flows through the probe tip 205 in the longitudinal direction. At the plasma generation region, the gas or plasma is diverted by the end cap 218 in a radial direction to intersect with a flow path 226 of water mist, as described below.

Within the second electrode 216, positioned at the distal end of the coaxial transmission line 206, is a generally cylindrical ceramic cap 222, which may extend for around 2 mm in the distal direction beyond the end of the dielectric material 212. In some embodiments, the first electrode 214 may be connected to the inner conductor 208 of the coaxial transmission line 206 by a conductive element which extends through the ceramic cap 222.

A gas conduit 224 is formed around the coaxial transmission line 206 in order to deliver gas to the energy delivery tip. At a proximal end of the applicator 200 the gas conduit 224 comprises a connector 225 to receive gas from the

gas supply 110. Gas is able to flow from the gas conduit 224 to within the second electrode 216 through castellations or apertures 217 which are formed in the proximal end of the second electrode 216. It may be desirable to have a plurality of castellations or apertures spaced regularly around the circumference of the second electrode 216 so that the flow of gas into the energy delivery tip is substantially uniform around the longitudinal axis.

Around the gas conduit 224, a fluid flow path 226 is formed in the applicator housing 202 to direct water mist from an inlet 227 to the outlet 204. As shown in Fig. 2, the fluid flow path 226 generally tapers in a distal direction towards the outlet 204. This serves the dual function of bringing the water mist into contact with the plasma being emitted from the gap 220 and to increase the flow rate of the mist. The plasma causes generation of hydroxyl radicals in the water mist, which are then ejected through the outlet 204 as a directable flow or spray.

In use, the gas supply 110 is operated to pass gas into the applicator 200 and through the gas conduit 224. The ceramic cap 222 has a chamfered distal face to encourage gas flowing from the gas conduit 224 into the second electrode 216 to pass between the first electrode 214 and the second electrode 216, where a thermal or non-thermal plasma is struck. For example, a plasma may be struck using RF energy, and sustained using microwave energy. Of course, it is envisaged that in some embodiments either RF or microwave energy may be used to strike and sustain the plasma. The power supplied to sustain the plasma may be controlled to maintain the plasma in a preferred state, e.g. as a non-thermal plasma.

At the same time as the plasma is produced, the mist generator 108 passes gas into the applicator 200 to provide a flow of water mist along the fluid flow path 226. The plasma passes out of the second electrode 216 through the gap 220, which forms a circumferential outlet for directing plasma into the fluid flow path 226 of water mist passing through the applicator 200. The plasma is shown in Fig. 3 by arrows 229. As the water mist passes through the plasma, the water molecules are ionised to produce hydroxyl radicals which pass

through the outlet 204 and towards a surface or object to be sterilised.

Fig. 4 shows a cross-sectional view of a second applicator 300 which may be used in an embodiment of the invention. In particular, the applicator 300 is adapted such that it may be used to sterilise surfaces or objects using hydroxyl radicals or using a thermal or non-thermal plasma which is emitted from the applicator 300. Features of the second applicator 300 which correspond with the first applicator 200 have been given the same reference numerals, and are not described again.

The applicator 300 comprises an energy delivery tip 305 connected to the distal end of a coaxial transmission line 206. The energy delivery tip 305 is configured to produce a thermal or non-thermal plasma which passes through the outlet 204 of the applicator 300. In this way, the applicator 300 may be used for sterilisation using just plasma when a gas supply, such as gas supply 110, is activated, or may be operable to produce hydroxyl radicals when the gas supply and a mist generator, such as mist generator 108, are both activated.

The energy delivery tip 305 comprises a first electrode 302 connected to the inner conductor 208 of the coaxial transmission line 206. In some embodiments, the first electrode 302 may be a continuation of the inner conductor 208. A second electrode 304 is connected to the outer conductor 210 of the coaxial transmission line 206. In this embodiment, the second electrode 304 is provided as a hollow cylinder which is open at each end, and the first electrode 302 is positioned generally along the longitudinal axis of the second electrode 304. In the embodiment shown, the first electrode 302 has a length of 20 mm, and the distal end of the first electrode 302 is 2 mm from the distal end of the second electrode 304. The spacing between the first electrode 302 and the second electrode 304 in the radial direction is approximately 1.3 mm. The first electrode 302 and the second electrode 304 are arranged to define an annular region 308 therebetween for receiving gas from a gas inlet 310, wherein a gas conduit is formed from the gas inlet, through the second electrode 304 and into the annular region 308 between the first electrode 302 and the second electrode 304.

At a distal end of the energy delivery tip 305 a quartz tube 312 is positioned within the annular region 308, with a gap between the quartz tube 312 and the first electrode 302 through which gas is able to flow. For example, the quartz tube 312 may have a length of 12.35 mm, and may be positioned such that the distal end of the quartz tube 312 is coterminous with the distal end of the second electrode 304. By positioning the quartz tube 312 in this way, the electric field in the gas-filled gap between the first electrode 302 and the second electrode 304 is increased to facilitate a plasma strike. The region within the quartz tube 312 is thus a plasma generation region.

At a proximal end of the energy delivery tip, an insulating element is provided to separate the coaxial transmission line 206 and the plasma generation region. The insulating element in this example comprises a ceramic cap 314 which sits around a proximal region of the first electrode 302. There is a gap between the cap 314 and the second electrode 304 in order to provide a conduit for gas to flow into the energy delivery tip from the inlet 310. For example, the cap 314 may have a length of 8 mm and an outer diameter of approximately 4.3 mm. The cap 314 is provide to prevent striking of the plasma at the proximal end of the energy delivery tip. In some examples the distal end of the cap 314 may be chamfered to encourage gas to flow between the quartz tube 312 and the first electrode 302, where the plasma is struck.

A distal end of the second electrode 304 is open to form an outlet for plasma generated within the energy delivery tip. In this way, plasma is directed in a longitudinal direction out of the energy delivery tip and towards the outlet 204 of the applicator 300. This is shown in Fig. 4 as a plume 316 of plasma which projects outwardly from the outlet 204 where it may be directed onto a surface or an object by a user for sterilisation.

The applicator 300 may be used in either a first mode for sterilisation using hydroxyl radicals, or a second mode for sterilisation using plasma.

In a first mode, the gas supply 110 is operated to pass gas into the applicator 300 via the inlet 310. The gas passes into the region between the first electrode 302 and the quartz

tube 312 where a plasma is struck. For example, a plasma may be struck using RF energy, and sustained using microwave energy. Of course, it is envisaged that in some embodiments either RF or microwave energy may be used to strike and sustain the plasma. At the same time as the plasma is produced, the mist generator 108 passes water mist into the applicator 300 via a mist inlet 318 to provide a flow of water mist along the fluid flow path 226. The plasma passes out of the second electrode 216 in a longitudinal direction, directing plasma into the fluid flow path 226 of water mist passing through the outlet 204. As the water mist passes through the plasma plume 316, the water molecules are ionised to produce hydroxyl radicals which pass through the outlet 204 and towards a surface or object to be sterilised.

The second mode comprises the same steps as the first mode, but a water mist is not supplied to the applicator 300, such that only a thermal or a non-thermal plasma is produced as plume 316 directed out of the outlet 204. The plume 316 of plasma may be passed directly over surfaces by a user for sterilisation.

The features disclosed in the foregoing description, or in the following claims, or in the accompanying drawings, expressed in their specific forms or in terms of a means for performing the disclosed function, or a method or process for obtaining the disclosed results, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

While the invention has been described in conjunction with the exemplary embodiments described above, many equivalent modifications and variations will be apparent to those skilled in the art when given this disclosure. Accordingly, the exemplary embodiments of the invention set forth above are considered to be illustrative and not limiting. Various changes to the described embodiments may be made without departing from the spirit and scope of the invention.

For the avoidance of any doubt, any theoretical explanations provided herein are provided for the purposes of improving the understanding of a reader. The inventors do not wish to be bound by any of these theoretical explanations.

Throughout this specification, including the claims which follow, unless the context requires otherwise, the words "have", "comprise", and "include", and variations such as "having", "comprises", "comprising", and "including" will be understood to imply the inclusion of a stated integer or step or group of integers or steps but not the exclusion of any other integer or step or group of integers or steps.

It must be noted that, as used in the specification and the appended claims, the singular forms "a," "an," and "the" include plural referents unless the context clearly dictates otherwise. Ranges may be expressed herein as from "about" one particular value, and/or to "about" another particular value. When such a range is expressed, another embodiment includes from the one particular value and/or to the other particular value. Similarly, when values are expressed as approximations, by the use of the antecedent "about," it will be understood that the particular value forms another embodiment. The term "about" in relation to a numerical value is optional and means, for example, +/- 10%.

The words "preferred" and "preferably" are used herein refer to embodiments of the invention that may provide certain benefits under some circumstances. It is to be appreciated, however, that other embodiments may also be preferred under the same or different circumstances. The recitation of one or more preferred embodiments therefore does not mean or imply that other embodiments are not useful, and is not intended to exclude other embodiments from the scope of the disclosure, or from the scope of the claims.

CLAIMS

1. A sterilisation device for generating a flow of hydroxyl radicals, the sterilisation device comprising:

5 a housing defining a water mist fluid flow path between an inlet for receiving water mist and an outlet for directing a flow of hydroxyl radicals towards a region to be sterilised;

an energy delivery tip configured to produce a thermal or non-thermal plasma;

10 a coaxial transmission line mounted in the housing and arranged to convey radiofrequency (RF) and/or microwave frequency electromagnetic (EM) energy to the energy delivery tip; and

15 a gas conduit mounted in the housing and arranged to deliver gas to the energy delivery tip,

wherein the coaxial transmission line comprises an inner conductor, an outer conductor, and a dielectric material separating the inner conductor from the outer conductor,

20 wherein the energy delivery tip extends from a distal end of the coaxial transmission line, and

wherein the energy delivery tip comprises:

a first electrode electrically connected to the inner conductor of the coaxial transmission line; and

25 a second electrode electrically connected to the outer conductor of the coaxial transmission line, wherein the second electrode is configured to define an internal volume of the energy delivery tip, wherein the first electrode extends longitudinally within the internal volume,

30 wherein the first electrode and second electrode are configured to:

strike a plasma in the gas delivered to the energy delivery tip, and

35 direct the plasma into the water mist fluid flow path to form hydroxyl radicals therein.

2. A sterilisation device according to claim 1, wherein the energy delivery tip is located within the housing.

40 3. A sterilisation device according to claim 2, wherein the first electrode and second electrode define an exit from

the internal volume, wherein the exit is located at or in the outlet.

5 4. A sterilisation device according to any preceding claim, wherein the first electrode is formed from a length of the inner conductor that extends beyond a distal end of the outer conductor.

10 5. A sterilisation device according to any preceding claim, wherein the first electrode comprises a conductive end cap mounted beyond a distal end of the second electrode, the conductive end cap being configured to deflect the plasma transversely into the water mist fluid flow path.

15 6. A sterilisation device according to any preceding claim, wherein the water mist fluid flow path tapers towards the outlet.

20 7. A sterilisation device according to any preceding claim, wherein the energy delivery tip further comprises an insulating cap mounted at a distal end of the coaxial transmission line to isolate the coaxial transmission line from the internal volume, and

25 wherein the gas conduit includes a fluid pathway formed between the insulating cap and the second electrode.

30 8. A sterilisation device according to claim 7, wherein the insulating cap is mounted within the second electrode, and wherein the fluid pathway comprises a plurality of openings in the second electrode that permit gas flow around the insulating cap.

35 9. A sterilisation device according to claim 8, wherein the second electrode is a cylinder, and the plurality of openings each comprise a notch in the cylinder.

40 10. A sterilisation device according to claim 9, wherein a proximal end of the second electrode is castellated to provide the plurality of openings.

11. A sterilisation device according to any preceding claim, wherein the energy delivery tip comprises an insulating dielectric material located between the first electrode and the second electrode in the internal volume.

5

12. A sterilisation device according to claim 11, wherein the dielectric material is quartz.

10

13. A sterilisation device according to any preceding claim, wherein the housing is configured as a handheld unit.

14. A sterilisation apparatus comprising:
a sterilisation device according to any one of claims 1 to 13;

15

a mist generator;
a gas supply; and
a generator for supplying radiofrequency (RF) and/or microwave frequency electromagnetic energy to the sterilisation device.

20

15. A sterilisation apparatus according to claim 14, wherein the mist generator comprises either:
an ultrasonic transducer, or
a heating element.

25

16. A sterilisation apparatus according to claim 14 or claim 15, wherein the gas supply is a supply of argon gas.

30

17. A sterilisation apparatus according to any one of claims 14 to 16, wherein the generator is powered by a battery.



Application No: GB2006383.0

Examiner: Helen Yard

Claims searched: 1-17

Date of search: 29 October 2020

Patents Act 1977: Search Report under Section 17

Documents considered to be relevant:

Category	Relevant to claims	Identity of document and passage or figure of particular relevance
X	1-17	GB 2574365 A (CREO MEDICAL LTD) See especially page 3 line 40 - page 4 line 9, page 11 lines 13-30, figures 2-4 and claims
A	-	GB 2520197 A (CREO MEDICAL LTD)
A	-	GB 2562110 A (CREO MEDICAL LTD)

Categories:

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.

Field of Search:

Search of GB, EP, WO & US patent documents classified in the following areas of the UKC^X :

Worldwide search of patent documents classified in the following areas of the IPC

The following online and other databases have been used in the preparation of this search report

International Classification:

Subclass	Subgroup	Valid From
A61L	0002/14	01/01/2006
A61L	0002/26	01/01/2006
H05H	0001/46	01/01/2006