



(11) **EP 2 225 974 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
08.09.2010 Bulletin 2010/36

(51) Int Cl.:
A47J 31/36^(2006.01) **A47J 31/54^(2006.01)**
F24H 1/00^(2006.01)

(21) Application number: **10163040.8**

(22) Date of filing: **01.10.2008**

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HR HU IE IS IT LI LT LU LV MC MT NL NO PL PT
RO SE SI SK TR
Designated Extension States:
AL BA MK RS

(30) Priority: **04.10.2007 EP 07117853**
22.04.2008 EP 08154918
22.05.2008 EP 08156704
30.09.2008 PCT/EP2008/063092

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
08804952.3 / 2 211 670

(71) Applicant: **Nestec S.A.**
1800 Vevey (CH)

(72) Inventors:
• **Etter, Stefan**
3122, Kehrsatz (CH)
• **Gaudenz, Urs**
8620, Wetzikon (CH)

- **Gavillet, Gilles**
1670, Ursy (CH)
- **Hodel, Thomas**
6332, Hagendorn (CH)
- **Kollep, Alexandre**
1095, LUTRY (CH)
- **Möri, Peter**
3272, WALPERSWIL (CH)
- **Moser, Renzo**
Gümmenen, 3205 (CH)
- **Preisig, Peter**
9100, Herisau (CH)
- **Schwab, Robin**
8057, Zürich (CH)

(74) Representative: **Schnyder, Frank Simon**
Avenue Nestlé 55
1800 Vevey (CH)

Remarks:

This application was filed on 18-05-2010 as a
divisional application to the application mentioned
under INID code 62.

(54) **Heating device with an integrated thermoblock for a beverage preparation machine**

(57) An in-line heating device (1,2,3,4) for a liquid food or beverage preparation machine in which liquid is circulated through the heating device and then guided into a brewing chamber. This heating device comprises: a thermoblock with a metal mass (1) that incorporates an inlet, an outlet and a heating chamber extending therebetween to form a passage for guiding said liquid circulating through said mass, the mass being arranged to accumulate heat and to supply heat to the liquid; and one or more electric components (60,70,75) that are rigidly secured onto or into the thermoblock and that are connected to a printed circuit board (4) and/or a flex-print (4') arranged to control the thermoblock. The electric components are rigidly connected to the printed circuit board and/or flex-print, in particular via rigid connector pins or blades or rigid plug and socket members.




FIG. 1

Description

Field of the Invention

[0001] The present invention concerns a heating device with an integrated thermoblock for the heating of a liquid in a liquid food or a beverage preparation machine.

Background Art

[0002] Liquid food and beverage preparation machines have been known for a number of years.

[0003] For instance, US 5,836,236 discloses a coffee brewer and hot water dispenser having a brew water tank with a preheater and a brew boiler for boiling preheated water and a hot water tank with a hot water heater. The tanks are heated in sequence, only one heater being energized at a time. The various heaters are connected to an electronic controller for regulating the brew water, level and temperature is located underneath the tank and protected by a thermoplastic shield. The heaters are made of an electric resistance wire and are associated with a safety switch. The electronic interconnection within the brewer is achieved by a ribbon cable having individual wires bearing terminal connectors. US 2007/0044664 discloses an automatic coffee machine having a boiler into which cold water is pumped and then heated for brewing coffee. Connections boiler's heater, sensors, flow meter, pump to a control circuit are schematically disclosed. The boiler includes a pair of thermal fuses to cut off the heater in case of overheating. WO01/60221 discloses a boiler associated with a probe extending between a lower part and upper part of the boiler and having a capacitive sensor for sensing the level of water in the boiler, the capacitive sensor being directly welded onto a printed circuit board.

[0004] Different fields of technology may use heaters, flow meters and thermal sensors and fuses, e.g. to dispense a viscous fluid namely body lotion, as disclosed in WO 99/51947.

[0005] US 5,943,472 discloses a water circulation system between a water reservoir and a hot water or vapour distribution chamber of an espresso machine. The circulation system includes a valve, metallic heating tube and pump that are connected together and to the reservoir via different silicone hoses, which are joined using clamp-collars.

[0006] EP 1 646 305 discloses a beverage preparation machine with a heating device that heats circulating water which is then supplied to the inlet of a brewing unit. The brewing unit is arranged to pass heated water to a capsule containing a beverage ingredient for its brewing. The brewing unit has a chamber delimited by a first part and a second part movable relative to the first part and a guide for positioning a capsule in an intermediate position between the first and second parts before moving the first and second parts together from an open to a closed configuration of the brewing unit.

[0007] In-line heaters for heating circulating liquid, in particular water are also well known and are for example disclosed in CH 593 044, DE 103 22 034, DE 197 32 414, DE 197 37 694, EP 0 485 211, FR 2 799 630, US 4,242,568, US 4,595,131, US 5,019,690, US 5,392,694, US 5,943,472, US 6,393,967, US 6,889,598, US 7,286,752, WO 01/54551, US 2003/0066431 and WO 2004/006742.

[0008] More particularly, CH 593 044 and US 4,242,568 disclose a coffee machine with an inline thermoblock heater having a metal mass with resistive heating cable cast in the mass and with a duct for the circulation of water to be heated.

[0009] EP 0 485 211 discloses a heater for a water heater, shower, washing machine, dishwasher or kettle. The heater includes a vessel for heating liquid, and an electric heating element which is arranged to heat a portion of the vessel. The heating element incorporates a thick-film resistive heating circuit with a thermal fuse included in the thick-film. The document further discloses a triac-type power regulator mounted directly on the heating element that acts as a heat sinker for this triac. Also disclosed is the presence of a thermistor, a temperature sensor, formed on the thick film, a thermal fuse, a flow control valve to continuously adjust the flow rate through the heater, a flow control and a temperature control. These electrical components are connected to a control unit that can be remote or formed as part of the dielectric layer of the thick film at a location close to the inlet pipe where the heater's metal substrate is kept cool by incoming cold water. Similar ideas are disclosed in DE 103 22 034, DE 197 32 414 and DE 197 37 694. Inline tubular heaters for beverage preparation devices are disclosed in WO 01/54551, WO 2004/006742 and US 7,286,752.

[0010] US 6,889,598 discloses a beverage device containing a liquid and having an operating apparatus for heating, cooling, agitating, whipping, pumping or frothing the liquid or grinding an ingredient, the operating apparatus being powered via an electronic switch such as a triac that is cooled by being in heat passing relationship with the liquid so as to evacuate the heat produced by the switch to the liquid, in particular via the bottom of a liquid heating tank made of steel or aluminium, and optionally with a radiator.

[0011] Moreover, US 5,019,690 discloses a boiling water dispenser that has a resistive heater powered via a triac switch connected via cables to a control module and mounted on the bottom of the dispenser's water reservoir to evacuate heat generated at the triac switch via the water.

[0012] US 4,595,131 discloses a beverage preparation machine with a water heating reservoir that is electrically connected to a printed circuit board via a series of cables leading to a thermostatically controlled heater and a thermistor probe in the reservoir. EP 1 610 596 discloses a heat evacuation system for a printed circuit board that includes layers of thermally highly conductive material extending to a thermally conductive bar located

at and along an edge of the printed circuit board for dissipation of heat generated by the printed circuit board.

[0013] FR 2 799 630 discloses an espresso machine having a cold water reservoir connected to a brewing unit via a pump and a thermoblock. The thermoblock includes a temperature sensor and an electric heater. The temperature sensor and the heater are connected to a printed circuit board with a controller, electric power being passed to the heater via a triac located on the printed circuit board and controlled by the controller.

[0014] EP 0 387 515 discloses an aircraft coffee maker having a fluid circuit connectable to an external water supply via a rear water supply connector. The fluid circuit includes the water supply connector, a rear inline heater and a top coffee brew nozzle that are in fluid communication via flexible tubing. The heater has three successive heatertubes, each with a central and elongated heating element, and inlet and outlet flared connectors for connecting the flexible tubing thereon. The heater further includes a first temperature sensor, a backup temperature sensor and a water sensor. The heating elements and sensors are all electrically connected via wires. The machine further includes an upper front user-interface with a printed circuit board with a number of wires and an electronic box with a heat sinker at the back of the machine.

[0015] US 2003/0066431 discloses a coffee machine with a fluid circuit made of several tubularly interconnected fluid modules including a water reservoir followed by a pump and then an in-line heater, water delivered by the heater is passed via a connection tube to a separate diverter and thereafter into a pod brewing unit. The inline heater is made of a heating tube inbetween a pair of cast aluminium bars, each bar containing a discrete heating resistor. A thermal cut-off, i.e. a one-time fusible link, and a thermistor, i.e. a thermal sensor, are clipped on the aluminium bars. The heating tube, the bars with the heating resistors, the thermal cut-off and the thermistor are enclosed within a heater housing through which water inlet and outlet fittings extend for connecting the heating tube into the fluid circuit of the coffee machine. The coffee machine further comprises a controller that appears to be mechanically assembled the housing of the heater by what seems to be a prismatic member. This controller is said to be "operably connected" various parts of the beverage machine, namely to the buttons, pump motor, pump sensor, heating resistor, thermal cut-off, thermistor, actuator sensor, pod sensor, reservoir sensor, diverter sensor, etc...

Summary of the Invention

[0016] A preferred object of the present invention is to simplify and improve the incorporation of the heating function in a liquid food or beverage preparation machine to facilitate and permit an increased automation of the assembly of the machine, reduce the manufacturing operations and costs and increase the reliability of the ma-

chine.

[0017] This object is in particular achieved by providing a heating device that integrates electrical and optionally fluid connections without requiring any flexible and deformable cable or tubes, for guiding current or liquid, to connect the heating function to other functional units of the liquid food or beverage preparation machine, or at least to limit the number of such flexible and deformable connections.

[0018] Therefore, the present invention relates to an inline heating device for a liquid food or beverage preparation machine. In such a machine, liquid is circulated, for instance from a liquid reservoir via a pump, through this heating device. Typically, the liquid that is circulated through the heating device is water. From the heating device, the heated liquid is guided into a machine's brewing chamber in which an ingredient may be brewed. The brewing chamber may include a capsule or pod housing, e.g. receiver, for housing an ingredient supplied within a capsule or pod into the brewing chamber.

[0019] For instance, the brewing chamber is arranged to contain a food or beverage ingredient, such as powder soup, ground coffee or tea optionally in a capsule or a pod. The brewing chamber may have an upstream part into which hot liquid is injected for brewing the food or beverage ingredient contained in the chamber and a downstream part leading into an outlet for guiding the liquid food or beverage produced by brewing.

[0020] Thermoblocks are typically in-line heaters through which a liquid is circulated for heating. They comprise a heating chamber, such as one or more ducts, in particular made of steel, extending through a (massive) mass of metal, in particular made of aluminium, iron and/or another metal or an alloy, that has a high thermal capacity for accumulating heat energy and a high thermal conductivity for the transfer the required amount of the accumulated heat to liquid circulating therethrough whenever needed. Instead of a distinct duct, the thermoblock's duct may be a through passage that is machined or otherwise formed in the duct's body, e.g. formed during a casting step of the thermoblock's mass. When the thermoblock's mass is made of aluminium, it is preferred, for health considerations, to provide a separate duct, for example of steel, to avoid contact between circulating liquid and aluminium. The block's mass can be made of one or several assembled parts around the duct. Thermoblocks usually include one or more resistive heating elements, for instance discrete or integrated resistors, that convert electrical energy into heating energy. Such resistive heating elements are typically in or on the thermoblock's mass at a distance of more than 1 mm, in particular 2 to 50 mm or 5 to 30 mm, from the duct. The heat is supplied to the thermoblock's mass and via the mass to the circulating liquid. The heating elements may be cast or loused into the metal mass or fixed against the surface of the metal mass. The duct(s) may have a helicoidal or another arrangement along the thermoblock to maximise its/their length and heat transfer through the

[0021] The heating device of the invention comprises: a thermoblock with a metal mass that incorporates an inlet, an outlet and a heating chamber extending therebetween, the mass being arranged to accumulate heat and to supply heat to the liquid; and one or more electric components that are rigidly secured onto or into the thermoblock and that are connected to a printed circuit board (PCB) and/or a flex-print arranged to control such thermoblock and optionally further functions of the liquid food or beverage preparation machine. Such electric components may include sensors, thermal fuses and/or electric power components, in particular temperature sensors, flow meters, resistor heaters, ammeters and electric power regulators.

[0022] In accordance with the invention, one or more of these electric components are rigidly connected to the printed circuit board and/or flex-print (or flexible circuit), in particular via rigid connector pins or blades or rigid plug and socket members.

[0023] To reduce the number of assembly operations, in particular human interventions during the manufacturing process, the number of flexible, deformable, electric cable connections are reduced. In particular, the electric components can be rigidly connected to this printed circuit board or flex-print, for instance via rigid connector pins or blades or rigid plug and socket members. Possibly, the electric components are present the form of integrated components on a printed circuit board or flex-print that is secured to the thermoblock and comes with these electric components into contact with the thermoblock's metal mass. In such a way, the electric components, in particular those which come into contact with the liquid circulation system such as the heating resistor(s), can be mounted automatically on the printed circuit board or the flex-print, and then the board or flex-print with its electric components is assembled (for instance clipped or glued) automatically onto the liquid circulation system without using any flexible, deformable electric connectors (e.g. cables) between the board or flex-print and the liquid circulation system. Alternatively, the electric components may be automatically mounted in a first step at dedicated locations of the liquid circulation system and then, in a second step, the printed circuit board or flex-print is assembled, for instance via an appropriate connector, to the electric components. It is also possible to assemble by welding the electric components to the liquid circulation system, in particular to the thermoblock and/or to the printed circuit board or flex-print. As mentioned, it is possible to provide some of these electric components as integrated components in the printed circuit board or flex-print, such as a heating resistive film formed on the surface of a printed circuit board or flex-print and applied directly against the surface of the thermoblock's metal mass.

[0024] In one embodiment, such an electric component is secured in a cavity of the thermoblock's metal mass. Optionally, the component is secured in the cavity by means of a biased spring element in the cavity or the

cavity forms a socket for a plug comprising the component. Electric components may also be cast into the metal mass or glued into or onto the metal mass, or attached by any other suitable means together with the metal mass, e.g. screwing, force fitting, welding, etc...

[0025] Such electric component may include a power component, such as a resistor heater and/or a power switch, which is rigidly connected via a rigid electric power pin and a rigid power connector that has a socket for receiving the rigid electric pin. The rigid connector can be resilient, in particular made of one or more spring blades, to allow small displacements of the socket for self-positioning the socket around the pin and to secure electric contact between the pin and the connector.

[0026] The printed circuit board may be contained in a thermal and electric insulating housing, such as a plastic housing, that is mechanically connected to the thermoblock, in particular via snaps. Preferably, the housing is substantially impervious to protect the board against liquids and vapours in the machine. The printed circuit board may have one or more openings for the passage of the electrical connectors for connecting to the printed circuit board such electric components that are rigidly secured on or in the metal mass.

[0027] The flex-print may be secured, typically glued, to a surface of the thermoblock, in particular to its metal mass. The flex-print can have: an inner side that faces the thermoblock or metal mass and that incorporates a resistor heater in the form of a heating foil or film; and an outer side to which one or more electric components are optionally rigidly secured. Alternatively, the flex-print may incorporate on the inner side one or more electric components, in particular discrete components, such as resistor heaters, sensors and/or power switches, e.g. triacs, that are rigidly secured into and/or onto the metal mass, and/or one or more components on the other side of the flex-print, for example a controller, a clock element and an interface connector for other electric devices of the liquid food or beverage preparation machines, such as a pump, electro-valve, user interface, level detector in a liquid reservoir or used ingredient collector, etc...

[0028] The electric components may be discrete components and/or integrated components, for instance formed directly into the flex-print and secured with the flex-print directly onto the thermoblock or its metal mass. Typically, thermal fuses, heating resistors and temperature sensors may be formed in flex-print technology.

[0029] Generally speaking, the printed circuit board as well as the flex-print can be arranged to control the thermoblock and optionally further functions in a liquid food or beverage preparation machine, of the type mentioned above by way of example.

[0030] The heating chamber in the metal mass is usually elongated, e.g. forms a duct, along a direction of flow of liquid through the mass. The heating chamber may comprise an upper flow portion followed by a down-coming flow portion, for example portions of a generally helical duct which extend helically along horizontal or non-

vertical inclined axis. Such upper low and down-coming flow portions may have a narrowed cross-section for promoting an increased velocity of liquid therealong to inhibit an accumulation of bubbles in such an upper flow portion by pushing them down the down-coming flow portion by the flow of liquid with increased velocity. In this configuration, the elongated chamber is arranged so that the size of its cross-section changes along the chamber, to increase the flow velocity in areas, usually upper areas, which might otherwise serve to capture bubbles, in particular vapour bubbles. The increased liquid velocity in these areas "washes" the bubbles down and away from these areas with the fast flow of liquid in these areas. To avoid overheating in such areas with reduced cross-section, the heating power may be reduced on the corresponding parts of the heater, for instance, by adjusting the resistive means on these parts.

[0031] Another aspect of the invention relates to a liquid food or beverage preparation machine. This machine comprises: a brewing chamber for brewing a food or beverage ingredient by circulating heated liquid there-through; and an in-line heating device with a thermoblock having a metal mass, as described above, for heating and supplying circulating liquid to the brewing chamber. The brewing chamber may be a capsule or pod housing for receiving an ingredient supplied within a capsule or pod into the brewing chamber.

[0032] Typically, the metal mass' inlet, outlet and heating chamber form together a rigid passage, in particular a rigid free-flow passage, for guiding the liquid circulating through the mass.

[0033] The thermoblock itself may incorporate an upstream part of the brewing chamber, the upstream part being formed by or rigidly anchored in the metal mass so that the rigid passage, in particular the rigid free-flow passage, of the metal mass extends into the brewing chamber. Furthermore, the machine usually includes a downstream part having a liquid food or beverage outlet and cooperating with the upstream part to form the brewing chamber. The downstream part and the upstream part may be movable apart and movable together for the supply into the brewing chamber and the evacuation from the brewing chamber of said ingredient. For instance, the upstream part and the metal mass are fixed, the downstream part being movable to and from the upstream part. Alternatively, the upstream part and the metal mass can be movable en bloc to and from the downstream part, the downstream part being fixed or movable in said machine.

[0034] Hence, the heating device of the invention may be used in connection with brewing chambers of the type disclosed in EP 1 646 305 or in EP 07117853.7 (NO8405).

[0035] A further aspect of the invention relates to a liquid food of beverage preparation machine, in particular as described above. The machine comprises: an electric supply circuit connectable to an electric power source; a heater powered by the electric supply circuit; and a ther-

mal fuse device in thermal communication with the heater and associated with the electric supply circuit. The fuse device is arranged to interrupt the electric supply circuit from the power source when the heater exceeds a temperature limit.

[0036] In accordance with the invention, the thermal fuse device is reversible and comprises a switch for automatically interrupting the electric supply circuit when the heater exceeds this temperature limit. The switch is operable by a user to close the electric supply circuit when the heater has a temperature that has returned below said temperature limit. Typically, the fuse device comprises an actuator that is arranged to push out a pin, rod or piston against the user switch when this temperature limit is exceeded by the heater so as to actuate the user switch and open the circuit.

[0037] This beverage or liquid food machine may include any of the above disclosed features or combination of features.

[0038] The fuse device may have an actuator which comprises a thermo-mechanical component that is in thermal communication with the heater and that mechanically actuates the user switch to open the electric supply circuit when the heater exceeds the temperature limit. The thermo mechanical component comprises in particular a shape memory element or a bimetal element.

[0039] The fuse device can include a safety electric temperature sensor in thermal communication with the heater and an electromechanical actuator that actuates the user switch to open the electric supply circuit when the safety sensor is exposed to a temperature generated by the heater which exceeds the temperature limit.

[0040] In one embodiment, the beverage or liquid food machine has a printed circuit board with a control circuit for controlling the heater and optionally further functions of the machine, such as a pump or an electric interface, the printed circuit board further including a safety circuit that is electrically separated on the printed circuit board from the control circuit, the safety circuit being connected to the safety sensor, in particular rigidly connected to the safety sensor, and arranged to control the electromechanical actuator.

[0041] At least part of the fuse device, in particular the actuator, electromechanical or thermo-mechanical actuator, the user switch and/or, when present, the safety sensor, may be rigidly connected to a printed circuit board of the liquid food or beverage machine, optionally on a part that is electrically insulated from an ordinary control unit of the machine, e.g. a unit for controlling the usual operations of the machine such as beverage or liquid food dispensing, self-cleaning, user-interface, etc... Hence, assembly and integration and safety of the fuse device into the liquid food and beverage machine is improved.

[0042] Yet another aspect of the invention relates to a liquid food of beverage preparation machine, in particular as above. The machine comprises a fluid arrangement and a printed circuit board, in particular a printed circuit

board bearing a control unit for controlling one or more functions of the fluid arrangement. Typically the functions may involve the use of a pump or a heater, such as the above discussed thermoblock, as well as sensors, detectors and a user-interface for a user-control of the fluid arrangement.

[0043] This printed circuit board is enclosed within a substantially impervious housing to protect the printed circuit board from fluid and/or vapor emissions from the fluid arrangement.

[0044] This beverage or liquid food machine may include any of the above disclosed features or combination of features.

[0045] In yet a further aspect of the invention, a printed circuit board or flex-print for a beverage preparation machine, for instance as described above, is rigidly connected to a flow meter, in particular a magnetic flow meter. The flow meter may comprise: a magnetic field detector, such as a hall sensor, that is incorporated into the printed circuit board or flex-print and a rotatable magnetic helix or turbine which is located within a duct or pipe that is arranged for circulating liquid therein and that is rigidly secured to the printed circuit board or flex-print.

[0046] By avoiding the use of flexible, deformable cables, the number of operations during the assembly process of a liquid food and beverage preparation machine is reduced, in particular the number of human interventions is reduced. Hence, the manufacturing and assembly costs are correspondingly reduced as well as the risks of failure due to human error. By avoiding flexible and deformable cable connections, automation of the assembly may be increased.

Brief Description of the Drawings

[0047] The invention will now be described with reference to the schematic drawings, wherein:

- Figure 1 shows a heating device incorporating a thermoblock and a printed circuit board in its housing according to the invention;
- Figures 2 and 3 show further details of the same printed circuit board in its housing;
- Figure 4 shows a printed circuit board with a flow meter in accordance with the invention;
- Figures 5 and 6 show the assembly of an electric power component to a metal mass of a thermoblock and to a printed circuit board in accordance with the invention;
- Figures 7 to 9 show the assembly of a sensor to a metal mass of a thermoblock and to a printed circuit board in accordance with the invention;
- Figure 10 shows an electric power connection be-

tween a power component in the metal mass and a printed circuit board of a thermoblock in accordance with the invention;

- 5 - Figures 11a and 11b illustrate a deflection according to a first direction of the power connection shown in Figure 10;
- Figures 12a and 12b illustrate a deflection according to a second direction of the power connection shown in Figure 10; and
- 10 - Figure 13 shows a heating device with a thermoblock and a flex-print circuit in accordance with the invention.
- 15 - Figures 14 and 15 schematically illustrate two embodiments of the invention of an electric circuit of a beverage machine with a user-reversible safety fuse in accordance with the invention.
- 20

Detailed description

[0048] Figure 1 shows an exploded view of a heating device of a liquid food or beverage preparation machine, in which liquid is circulated through a thermoblock and then guided into a brewing chamber for brewing a food or beverage ingredient supplied into the brewing chamber. For instance, a beverage ingredient is supplied to the machine in prepackaged form, for example contained in a capsule or in a pod. Typically, this type of liquid food or beverage machine is suitable to prepare coffee, tea and/or other hot beverages or even soups and like food preparations. The pressure of the liquid circulated to the brewing chamber may for instance reach about 10 to 20 atm.

[0049] The heating device incorporates a thermoblock and a printed circuit board according to the invention. Figures 2 and 3 show further details of the printed circuit board 4 in its housing 3 of the heating device of Fig. 1.

[0050] The heating device shown in Figures 1 to 3 has a thermoblock with an aluminium metal mass 1 and a functional block 2 including a thermal and electrically insulating plastic housing 3 containing a printed circuit board 4.

[0051] Metal mass 1 incorporates a water inlet, a water outlet and a water heating duct extending therebetween to form a rigid free-flow passage (not shown) for guiding water circulating from a water reservoir via a pump through metal mass 1.

[0052] As mentioned above, the heating duct may comprise an upper flow portion followed by a down-coming flow portion, for example portions of a generally helical duct which extends along a horizontal or non-vertical inclined axis. Such upper flow and down-coming flow portions may have a narrowed cross-section for promoting an increased velocity of water therealong to inhibit an

accumulation of bubbles in such upper flow portion by pushing them down the down-coming flow portion by the flow of water with increased velocity. In this configuration, the duct is arranged so that the size of its cross-section changes along the chamber, to increase the flow velocity in areas, usually upper areas, which might otherwise serve to capture bubbles, in particular vapour bubbles. The increased liquid velocity in these areas "washes" all possible bubbles away from these areas with the fast flow of liquid in these areas. To avoid overheating in such areas with reduced cross-section, the heating power may be reduced on the corresponding parts of the heater, for instance, by adjusting the resistive means on these parts.

[0053] In a variation, this duct has a reduced cross-section along its entire length to provide a sufficient velocity of the water flow for flushing possible vapour bubbles formed therein during heating.

[0054] Metal mass 1 of thermoblock further includes an opening 1b which forms or rigidly anchors an upstream part of the brewing chamber (not shown) so that the rigid passage of metal mass 1 extends into the brewing chamber. The liquid food or beverage preparation machine also comprises a downstream part (not shown) having a liquid food or beverage outlet and cooperating with the upstream part to form the brewing chamber, the downstream part and the upstream part can be movable apart and movable together for the supply into the brewing chamber and the evacuation from the brewing chamber of the ingredient.

[0055] Typically, the upstream part of the brewing chamber integrated into the thermoblock, will be fixed in the liquid food or beverage preparation machine and the downstream part of the brewing chamber will be movable. The brewing chamber may have a generally horizontal orientation, i.e. such a configuration and orientation that the water flows through the food or beverage ingredient in the brewing chamber along a generally horizontal direction, and the upstream part and/or downstream part may be movable in the same or in the opposite direction of the water flow in the chamber. Embodiments of such a thermoblock and brewing chamber are for example disclosed in EP 07117853.7 (NO8405), the content of which is hereby incorporated by way of reference.

[0056] Functional block 2 is secured to metal mass 1 via snaps 3a of housing 3 that cooperate with corresponding recesses 1a in the surface of metal mass 1 when housing 3 is assembled to metal mass 1 in the direction of arrow 3'.

[0057] The two part housing 3 of functional block 2 encloses printed circuit board 4 on all sides, in particular in a substantially impervious manner so as to protect board 4 against liquid and vapours in the machine. The two parts of housing 3 may be assembled by screws 3b or any other appropriate assembly means, such as rivets, gluing, welding, etc... Functional block 2 includes a user interface with a master switch 2a and two control switches 2b that are connected via housing 3 to printed circuit

board 4. It is of course possible to use more elaborated user interfaces including screens or touch screens. Printed circuit board 4 includes power connectors 80 for supplying electric heating power to metal mass 1 via power pins 11 extending through corresponding openings in housing 3, further electrical connectors 4a for one or more further electric devices in the liquid food or beverage preparation machine, such as a user interface, pump, fan, valve, liquid cooling element, etc... as required, and a connector 4b to the mains for the central electric power supply.

[0058] The thermoblock includes electric components, namely a temperature sensor 70 connected to plug member 52, thermal fuses 75, a power switch in the form of a triac 60 in a cavity the opening of which is formed between protruding walls 102 and a heating resistor (not shown) with connector pins 11, that are rigidly secured into metal mass 1 and rigidly connected to printed circuit board 4, as will be explained in greater details below in connection with Figures 5 to 12b. Furthermore, printed circuit board 4 is electrically connected via a rigid connector or cable 91 to a hall sensor 90 of a flow meter that is located on the water circuit of the beverage preparation machine, typically between a pump and a water or other liquid source such as a water or liquid reservoir, or between a pump and a heating device, or within the heating device.

[0059] Moreover, printed circuit board 4 may carry a micro-controller or processor and possibly a quartz clock for controlling the intensity of current passed to resistive heating element based on the flow rate of the circulating water measured with the flow meter and the temperature of the heated water measured with the temperature sensor. To increase the accuracy of the temperature control, one or more temperature sensors may be incorporated into metal mass 1 and/or into the brewing chamber and/or upstream the metal mass 1 or at its water inlet. The controller or processor may also control further functions of the liquid food or beverage preparation machine, such as a pump, a liquid level detector in a water supply reservoir, a valve, a user interface, a power management arrangement, an automatic beverage ingredient supplier such as an integrated coffee grinder or an automatic supplier of ingredient capsules or pods, etc...

[0060] Figure 4 illustrates another embodiment according to the invention of a flow meter 95 for a liquid food or beverage preparation machine according to the invention. Flow meter 95 includes a hall sensor 90' that is incorporated onto printed circuit board 4 as an integrated component of the printed circuit board 4 or as a discrete component rigidly mounted or connected thereto, typically by welding. Flow meter 95 is also integrated in the water circulation circuit 5 and is connected to a water incoming pipe 5' and a water outgoing pipe 5" and to the printed circuit board 4 via hall sensor 90'. Water pipes 5', 5" may be flexible, e.g. made of silicon, or rigid to facilitate automatic assembly. Flow meter 95 includes a internal magnetic helix or rotor (not shown) through

which water is circulated. The water flow drives within flow meter 95 the magnetic helix or rotor in rotation at an angular speed that is proportional to the velocity of the flow of water thereby causing a corresponding rotation of the magnetic field generated by the magnetic helix or rotor, which is detected by hall sensor 90' and converted into a corresponding electric signal on printed circuit board 4.

[0061] By providing flow meter 95 with hall sensor 90' directly on printed circuit board 4, the corresponding manufacturing steps of the liquid food or beverage preparation machine do not require human intervention, less components, in particular no separate connector link, in particular no electric cable, and thus reduces the production costs of the assembly of the liquid food or beverage preparation machine as well as its reliability since fewer parts are involved and the human factor is also reduced.

[0062] During use, a liquid to be heated is circulated, for instance by using a pump, via flow meter 90, 90', 91, 95 and then freely through the inlet of metal mass 1, through the heating duct and through the outlet of mass 1 into brewing chamber for brewing the ingredient contained therein. The controller on printed circuit board 4 is arranged to control triac 60 for adjusting the heating current passed via power pins 11 to heating resistor in metal mass 1, based on measures of the liquid flow by means of flow-meter 90, 90', 91, 95 and of the temperature of the heated liquid by means of temperature sensor 70 connected to plug member 52.

[0063] Figures 5 and 6, in which the same numeric references designate then same elements, illustrate in greater detail the rigid assembly of a discrete power component in the form of a triac 60 to metal mass 1 and to a printed circuit board 4 according to the invention. Whereas Figure 5 shows the assembly in an exploded perspective view, Figure 6 discloses the assembly in cross-section.

[0064] Metal mass 1, a part of which is shown in Figures 5 and 6, has a recess 101 for receiving power component 60. Recess 101, the opening of which is formed between protruding walls 102, is associated with a spring element 103, for example in the shape of a spring leaf, assembled to metal mass 1, e.g. via a screw 104. Other spring and assembly systems may of course be used, for example, the spring leaf may be integral with metal mass 1 or welded thereto so as to reduce the number of parts. Spring element 103 urges power component 60 against walls 102 of recess 101 in metal mass 1 when component 60 is inserted into recess 101, to secure component 60 in mass 1 and provide an optimal contact between mass 1 and component 60.

[0065] Power component 60 has one or more rigid electrical connector pins 61, for instance three pins for the triac shown in Figures 5 and 6, which are rigidly connected to printed circuit board 4. Furthermore, power component 60 is covered with an optional cap 62, e.g. made of silicon, that may assist fixation of the power component 60 in recess 101, as well as an optional non con-

ductive sleeve 63 around its connector pins 61 which spaces the main body of power component 60 from printed circuit board 4 and protect pins 61 against the environment. Moreover, cap 62 and sleeve 63 provide an electric insulation around power component 60.

[0066] Hence, metal mass 1 serves as a heat sinker for power component 60 by evacuating, via mass 1 and optionally via the water circulating through mass 1, heat generated by the power component during use. For this purpose, mass 1 is configured and made of a metal, such as aluminium or steel, that allows optimal evacuation of heat from the power component along the heat evacuation path through mass 1.

[0067] Power component 60 may be a switch or regulating element, e.g. a triac as mentioned above, for adjusting the required electric power that is supplied to the resistive means, e.g. a heating resistor, for generating the desired heat in metal mass 1 in order to heat the circulating water to the appropriate temperature.

[0068] Figures 7 to 9, in which the same numeric references designate the same element, illustrate the rigid assembly of a discrete electronic component 70 into metal mass 1 and to a printed circuit board 4. This electronic component may be a sensor such as a temperature sensor, a flow meter, a thermal fuse or another similar component, such as an ammeter for providing a feedback of the current passed through the resistive heating means, e.g. heating resistor. For the purpose of illustration, a thermal sensor 70 for the control of heating electric current passed to the heating resistor via pins 11 and adjustment of the heat generated in metal mass 1 is disclosed. Thermal sensor 70 may for example be located at the inlet or outlet of metal mass 1 or thereinbetween. Several thermal sensors may be used to allow a more precise control of the heating of the water passed via metal mass 1.

[0069] Metal mass 1, a part of which is shown in Figures 7 to 9, has a recess 111 for receiving the electronic component 70. Recess 111 is formed between protruding walls 112 and extends below the surface of metal mass 1.

[0070] Sensor 70 has a connector socket 71 through which a sensor element 72 is joined to electric flat connectors 73 on the opposite side of socket 71. The sensor's connection pins 73 are brought into contact with flat connector pins 51, one of which is shown in Figure 8, of printed circuit board 4. Pins 51 extend through a plug member 52 of board 4 into socket 71 for contacting the corresponding connection pins 73 of sensor 70. When connector socket 71 is urged between walls 112 of body 1, sensor element 72 is located in recess 111 of metal mass 1. As shown in Figure 2, plug member 52 extends through housing 3 via a corresponding opening. Alternatively, plug member 52 may be integral with housing 3 and electrically connected to printed circuit board 4.

[0071] When sensor 70 is a temperature sensor, the electric characteristics of sensor element 72 will depend on the temperature in recess 111, which will be used for evaluating the temperature of metal mass 1 at this loca-

tion and optionally also the temperature of water circulating in metal mass 1 in an indirect evaluation process.

[0072] Sensor element 72 may for instance be an NTC (negative temperature coefficient) resistor or a PTC (positive temperature coefficient) resistor.

[0073] Such a sensor configuration permits reliably measuring the temperature in the corresponding location of the heater, fast reaction (low inertia) and provides an excellent and reliable electric contact system.

[0074] Sensor 70 may be preassembled into socket 71, for instance made of thermoplastic material, and assembled into metal mass 1 and to printed circuit board 4 in a fully automatic process. Sensor 70 may be glued into metal mass 1 using for example an epoxy compound. The preassembled sensor 70 may then be connected by pressing the socket's flat connectors 73 into connection slots of socket 71 in such a way as to be connected to sensor element 72. Printed circuit board 4 is then mounted with housing 3 onto socket 70 via plug 52 and connector pins 51.

[0075] It follows that the assembly of thermoblock with metal mass 1 and printed circuit board 4 does not require handling any flexible parts and thus the assembly can be carried out automatically without the need of any human intervention. Furthermore, the assembly of sensor 70 itself only requires low cost components. Hence, the assembly of sensor 70 on metal mass 1 and its connection to printed circuit board 4 leads to significant cost savings.

[0076] Figure 10 is a perspective view in an xyz orthogonal referential, as indicated by the corresponding arrows associated with Figures 10 to 12b, of a self-positioning rigid electric power connector 80 for connecting a heating resistor to a printed circuit board 4 and for carrying electric heating current thereto or therefrom. Figures 11a and 11b on the one hand, and Figures 12a and 12b on the other hand, schematically show the self-positioning of power connector 80 in the y direction and the x direction, respectively.

[0077] Power connector 80 is typically metal-based, and may in particular contain steel, aluminium and/or copper alloys that provide sufficient electric conductivity, mechanical resistance and resilience.

[0078] Power connector 80 extends between a pair of flat feet 81 for connection to a printed circuit board 4. Each foot 81 is connected to a bottom part of a flat generally upright spring member 82. The upper parts of the upright spring blades 82 are connected together via a transverse spring member 83 that comprises a flat central horizontal part 84 inbetween a pair of inclined intermediate parts 85,85'. Upright members 82, intermediate part 84 and inclined parts 85,85' of transverse member 83 are in a general M arrangement on the pair of feet 81. Transverse member 83 further includes a socket 86 with a through-passage for securing therethrough an electric connector pin 11 extending from metal mass 1.

[0079] In Figures 11a, 11b, 12a and 12b, in which the same numeric references designate the same elements, a power connector 80 is schematically shown assembled

via a power pin 11 to a heating resistor (not shown) in metal mass 1. Power pin 11 extends upright from the surface of metal mass 11 and is secured in the through-passage of socket 86 of transverse member 83. To simplify the illustration, housing 3, as shown in Figures 1 to 3, extending between printed circuit board 4 and metal mass 1, is not shown in Figures 11a to 12b.

[0080] Feet 81 of power connector 80 are electrically connected and secured onto printed circuit board 4, for instance by rivets or welding 81' or any other suitable assembly means. Metal mass 1 faces printed circuit board 4 so that power pin 11 extends through corresponding holes in housing 3 and through board 4 via a through-opening 55 in board 4 to the other side of board 4 and is then secured in through-passage 86 of power connector 80. Continuous electrical connection between power pin 11 and transverse member 83 may be achieved by force-fitting or welding pin 11 in through-passage 86.

[0081] Power connector 80 allows for small positioning displacements of through-passage 86 in the x direction and y direction, with reference to the xyz referential associated with Figs. 10 to 12b. Different directions of displacements are provided by the different orientations, in particular perpendicular orientations, of the resilient spring blade members 82,83, which permit displacements along corresponding directions.

[0082] Figures 11a and 11b, on the one hand, and Figures 12a and 12b, on the other hand, show a displacement of the connector's socket 86 assembled to power pin 11 along the y direction and the x direction respectively. Displacement of socket 86 in the x and y directions is achieved by a small flexion of upright spring blades 82 and a small flexion of inclined intermediate parts 85,85', respectively.

[0083] Figures 11a and 12a show power pin 11 extending right through the middle of through-opening 55, and through the through-passage of socket 86 which all extend along substantially the same axis. In this configuration, power pin 11 is positioned in line with power connector 80 which is thus not subjected to any displacement flexion stress in its upright spring blades 82 and inclined intermediate parts 85,85'.

[0084] In contrast, Figures 11b and 12b show power pin 11 extending eccentrically through through-opening 55. Through-passage of socket 86 aligned to power pin 11 is equally eccentric with respect to through-opening 55. In this case, printed circuit board 4 is not perfectly aligned with power pin 11 of the heater and power connector 80 self-adapts the position of its through-passage in socket 86 to match precisely the position of pin 11 by flexion of its upright spring blades 82 in the x direction, as shown in Figure 12b, or by flexion of its transverse spring member 83 in the y direction, as shown in Figure 11b. In order to facilitate insertion of power pin 11 into through-passage of socket 86, the lower part 86' of socket 86 has a generally funnel-like or frustoconical shape that is arranged to receive a generally conical upper end of

power pin 11.

[0085] The displacement of socket 86 to adapt to the position of power pin 11 may result from discrepancies, e.g. manufacturing tolerance or different temperature-related dilatation mechanisms, between the relative positioning of a pair of power connectors 80 on printed circuit board 4 with respect to the relative positioning of a corresponding pair of power pins 11 on the metal mass. Furthermore, the relative position of other electrical components that are rigidly connected to the printed circuit board and fixed parts of the beverage preparation machine, in particular the metal mass, for example temperature sensors and power regulator or switches, e.g. like the ones shown in Figures 5 to 9, may induce displacements at the level of the power connection.

[0086] During use, the passage of current from and back to printed circuit board 4 via first power connector 80, first power pin 11, the heating resistor (not shown) in metal mass 1, the second power pin 11, the second power connector 80, is controlled by a power switch or regulator, e.g. a triac 60, for instance as illustrated in Figures 5 and 6.

[0087] Figures 11a and 11b also illustrate how an error of relative positioning of feet 81 and inclined parts 85,85' on printed circuit board 4 is managed by power connector 80. As shown, feet 81 and thus inclined parts 85,85' are not perfectly aligned in the x direction but slightly off-set one to another. This off-set is however fully compensated by a corresponding resilient deflection of transverse member 83 without causing excessive stress in printed circuit board 4 or in power connector 80. Likewise, if the spacing between the two anchorage locations on printed circuit board 4 for anchoring feet 81 are greater or shorter than the spacing between feet 81 when the power connector is in a relaxed state, then a corresponding resilient deflection of members 82 can absorb such a spacing difference without excessive or detrimental stress in power connector 80 or printed circuit board 4.

[0088] Tests have shown that in the case of an M-shaped power connector of the type shown in Figures 10 to 12b having an overall width and height above the feet of about 1.3 cm x 1 cm, made of bent blade-type conductive metal spring portions that have a cross-section of about 3 mm x 0.2 mm or 0.3 mm, the positioning offset that can be tolerated and compensated in all directions while maintaining good electrical and mechanical contacts for currents above 10 amps and temperatures around 80°C, may be in the range of 3 to 8%, in particular about 5%, or 0.25 to 0.7 mm, typically around 0.4 mm.

[0089] Hence, with such power connectors allowing small displacements in one or more directions of its connection part 86 relative to its base 81 for connection to a printed circuit board 4, small position tolerances of pre-assembled or preformed heating element connectors can be compensated and still provide a good electrical contact performance under high current and elevated temperature conditions.

[0090] Therefore, with such a power connector 80 that

self-positions its socket 86 on connector pins 11, it is possible to provide a cableless precise and continuous contact for high electrical currents, in particular between a resistive heating means on a heater and the power supply at printed circuit board 4. The absence of flexible power cables increases the integration, facilitates the manufacturing automation level of the device and reduces its production costs as well as its reliability by reducing the human factor.

[0091] Figure 13 illustrates a variation of the heating device in accordance with the invention which includes a flex-print 4' instead of a printed circuit board.

[0092] Flex-print 4' is bonded, in particular glued, to the surface of a metal mass 1 of a thermoblock. Flex-print 4' has: an inner side applied to metal mass 1 that incorporates a resistor heater in the form of a heating foil or film. The outer side of flex-print 4' carries one or more electric components 60,75' that are rigidly secured to the outer slide. Flex-print 4' may also incorporate on its inner side one or more electric components. The electric components may be integrated components or discrete components, such as resistor heaters, sensors and/or power switches, e.g. triacs, that are secured into and/or onto the metal mass, and/or one or more components on the outer side of the flex-print, for example a controller.

[0093] As illustrate in Figure 13, flex-print 4' is rigidly connected to a thermal fuse 75' and to a triac 60. Since the inner surface of flex-print 4' matches the surface of metal mass 1, triac 60 on the outer surface of flex-print 4' is in thermal communication with metal mass 1 via flex-print 4' so that heat generated by triac 60 during use can be well evacuated via metal mass 1 and optionally via the water circulating in mass 1. In a variation, a triac and/or other electric components, such as thermal sensors, may be rigidly connected to the inner side of flex-print to improve thermal communication between the triac and the metal mass.

[0094] Flex-print 4' is connected to functional block 2 into housing 3 via arm 4" for data and power connection. Via arm 4" flex-print 4' may be connected to a printed circuit board, for instance in housing 3, and/or to further electric devices, such as a user interface or a main switch 2a. The thermoblock with its metal mass 1 is also rigidly connected to functional block 2, for instance by means of snaps, screws, rivets, etc...

[0095] Figures 14 and 15, in which the same numeric references designate generally the same elements, schematically disclose two alternative embodiments of a beverage or liquid food machine with a user-reversible fuse device. !

[0096] The machine according to the invention has an electric supply circuit 57 that is connectable to a power source (not shown), such as the mains or an equivalent power source. Supply circuit 57 is connected to a printed circuit board (PCB) 4 which bears the machine's control unit, e.g. a micro-controller, memory device, various interfaces to the various parts of the machine that require automatic control, such as a user-interface, a pump, a

heater 1, sensors 60,70, etc... Supply circuit 57 has a main switch 205,205' allowing a user to switch on and off the beverage or liquid food machine.

[0097] In-line heater 1 has a water inlet 1' connected to a water source, in particular via a pump (not shown), and a downstream cavity 1b delimiting an upper part of a brewing unit arranged to receive a pre-packaged beverage ingredient such as a coffee or tea capsule and to cooperate with a beverage or liquid food outlet member or assembly (not shown).

[0098] Advantageously main switch 205,205' is mechanically mounted onto PCB 4 to facilitate assembly and increase integration of the system.

[0099] Furthermore, the machine includes a thermal fuse device 200 that has a switch 205 on circuit 57 and an actuator 201,201' arranged to disconnect circuit 57 by actuating switch 205 when heater 1 has a temperature that exceeds a temperature limit, e.g. a temperature limit in the range of 120°C to 180°C, in particular 140°C to 160°C, indicative of a malfunction of heater 1 or of its control unit 4.

[0100] Thermal fuse device 200 is user reversible. Upon safety disconnection of circuit 57 by fuse device 200, switch 205 may be operated by a user to reconnect circuit 57 and re-establish electric powering of PCB 4. Hence, if thermal fuse device 200 goes off improperly or if heater 1 merely has an accidental one time overheat condition, the liquid food or beverage machine of the invention does not need to be returned for servicing in order to replace the fuse device, unlike existing beverage or liquid food machines fitted with one-time thermal fuses.

[0101] Fuse device 200 has an actuator 201,201' that is arranged to push out a pin, rod or piston 202 against the user switch, e.g. a switch of the push-button type, when said temperature limit is exceeded by the heater so as to actuate the user switch and open circuit 57.

[0102] The embodiment shown in Fig. 14 has a fuse device 200 with an actuator 201 including a pin 202 movable along the direction of arrow 202' and a thermo-mechanical component mounted onto heater 1 and in thermal communication therewith. The thermo-mechanical component may be any arrangement suitable to convert the passage of a temperature level into a mechanical action or displacement, such as an element made of a shape memory alloy that remembers its shape, or a bi-metallic strip element.

[0103] Hence, when heater 1 exceeds the temperature limit, the thermo-mechanical component of actuator 201 is activated and will urge pin 202 against user switch 205. This will disconnect the electric parts of the machine from the power supply connected to circuit 57. When the heater's temperature drops below the temperature limit, the thermo-mechanical component will return back into its normal state and pin 202 will either follow the thermo-mechanical component or may be pushed back into its normal position by a user who actuates switch 205 to re-establish the power connection of the machine.

[0104] In the embodiment shown in Figure 14, the user

switch 205 cooperating with the thermal fuse may also serve as a main switch that may be operated independently of any over-heat situation in order to ordinarily switch on and off the beverage or liquid food machine.

[0105] Conversely, in the embodiment shown in Figure 15, the user switch 205 cooperating with the thermal fuse is a dedicated switch separate from the main switch 205'.

[0106] Fuse device 200 comprises a safety electric temperature sensor 203 mechanically mounted against heater 1 and in thermal communication therewith. Furthermore, to simplify assembly and further integrate the electric components of the machine, temperature sensor 203 is rigidly connected to PCB 50 in a similar manner as discussed above. In a less preferred embodiment, such a temperature sensor may also be connected by other means to the PCB, in particular in a partly or entirely flexible manner.

[0107] Temperature sensor 203 monitors the temperature of heater 1. Temperature sensor 203 is associated with a control means that controls the electrical powering of actuator 201' via its connection circuit 204 depending on the measured temperature. For instance, the control means includes a power switch, e.g. a transistor, on connection circuit 204 connected to temperature sensor 203.

[0108] Advantageously, the temperature sensor 203, the power switch associated therewith, user switches 205 and even actuator 201' are rigidly mounted onto PCB 4. Preferably these components are mounted on a section 41 of PCB 4 that is electrically insulated from the ordinary control unit of the beverage and liquid food machine on PCB 4. Hence, by having substantially all the electronic and electrical parts on the same PCB 4 but arranged in two distinct electrical circuits, mechanical assembly of the components is facilitated and the safety of the machine is increased.

Claims

1. A liquid food or beverage preparation machine comprising a fluid arrangement and a printed circuit board (4), in particular a printed circuit board bearing a control unit for controlling one or more functions of the fluid arrangement, said printed circuit board (4) being enclosed within a substantially impervious housing (3) to protect the printed circuit board from fluid and/or vapor emissions from the fluid arrangement.
2. The machine of claim 1, wherein the printed circuit board is rigidly connected to a flow meter, in particular a magnetic flow meter.
3. The machine of claim 2, wherein the flow meter comprises: a magnetic field detector, such as a hall sensor, that is incorporated into the printed circuit board or flex-print and a rotatable magnetic helix or turbine which is located within a duct or pipe that is arranged

for circulating liquid therein and that is rigidly secured to the printed circuit board or flex print.

4. The machine of any preceding claim, which comprises a heating device (1,2,3,4) having:

- a thermoblock with a metal mass (1) that incorporates an inlet, an outlet and a heating chamber extending therebetween to form a passage for guiding said liquid circulating through said mass, the mass being arranged to accumulate heat and to supply heat to said liquid; and
- one or more electric components, such as sensors (70), thermal fuses (75) and/or electric power components (60), that are rigidly secured onto or into the thermoblock and that are connected to the printed circuit board (4) arranged to control said thermoblock and optionally further functions of said liquid food or beverage preparation machine,

wherein said one or more electric components are rigidly connected to said printed circuit board, in particular via rigid connector pins (11,51,61,73) or blades or rigid plug (11,51) and socket (80,71) members.

5. The machine of claim 4, wherein one or more electric components are secured on or in the metal mass and are selected from temperature sensors, thermal fuses, flow meters, resistor heaters, ammeters and electric power regulators.
6. The machine of claim 4 or 5, wherein an electric component is secured in a cavity of the metal mass, optionally the component being secured by means of a biased spring element in the cavity or the cavity forming a socket for a plug comprising the component.
7. The machine of any one of claims 4 to 6, wherein said one or more electric components comprise a power component, such as a resistor heater and/or a power switch, which is rigidly connected via a rigid electric power pin and a rigid power connector that has a socket for receiving the rigid electric pin, the rigid connector being resilient, in particular made of one or more spring blades, to allow displacements of the socket for self-positioning the socket around the pin and to secure electric contact between the pin and the connector.
8. The machine of any one of claims 4 to 7, wherein the printed circuit board is contained in an impervious and/or thermal and electric insulating housing, such as a plastic housing, that is mechanically connected to the thermoblock, in particular via snaps, and that has one or more openings for the passage of elec-

trical connectors for connecting to the printed circuit board to said one or more electric components that are rigidly secured on or in the thermoblock.

9. The machine of any one of claims 4 to 8, wherein said printed circuit board is arranged to control the thermoblock and optionally further functions, such as a pump or an electric interface, of a liquid food or beverage preparation machine.
10. The machine of any one of claims 4 to 9, wherein the heating chamber in the metal mass is elongated along a direction of flow of liquid through the mass, the heating chamber comprising optionally an upper flow portion followed by a down-coming flow portion that have a narrowed cross-section for promoting an increased velocity of liquid along the upper and the down-coming flow portions to inhibit an accumulation of bubbles in the upper flow portion.
11. The machine of any one of claims 4 to 10, wherein the metal mass' inlet, outlet and heating chamber form together a rigid passage, in particular a rigid free-flow passage, for guiding said liquid circulating through said mass.
12. The machine of any one of claims 4 to 10, wherein the thermoblock comprises an upstream part of the brewing chamber, the upstream part being formed by or rigidly anchored in said metal mass so that the rigid passage of the metal mass extends into the brewing chamber.
13. The machine of claim 12, which comprises a downstream part having a liquid food or beverage outlet and cooperating with the upstream part to form the brewing chamber, the downstream part and the upstream part being optionally movable apart and movable together for the supply into the brewing chamber and the evacuation from the brewing chamber of said ingredient.
14. The machine of claim 13, in which: the upstream part and the metal mass are fixed, the downstream part being movable to and from the upstream part; or the upstream part and the metal mass are movable en bloc to and from the downstream part, the downstream part being fixed or movable.
15. The machine of any preceding claim, which comprises:
- an electric supply circuit (57) connectable to an electric power source;
 - a heater (1) powered by the electric supply circuit; and
 - a thermal fuse device (200) in thermal communication with the heater and associated with the

electric supply circuit, the fuse device being arranged to interrupt the electric supply circuit from said power source when the heater exceeds a temperature limit,

5

wherein the thermal fuse device (200) is reversible and comprises a switch (205) for automatically interrupting the electric supply circuit when the heater exceeds said temperature limit, the switch being operable by a user to close the electric supply circuit when the heater has a temperature that has returned below said temperature limit, the fuse device comprising in particular an actuator (201) that is arranged to push out a pin, rod or piston (202) against the user switch when said temperature limit is exceeded by the heater so as to actuate the user switch and open the circuit (57).

10

15

20

25

30

35

40

45

50

55





FIG. 1









FIG. 3








FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11a




FIG. 11b




FIG. 12a




FIG. 12b




FIG. 13

FIG 14





FIG 15



REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 5836236 A [0003]
- US 20070044664 A [0003]
- WO 0160221 A [0003]
- WO 9951947 A [0004]
- US 5943472 A [0005] [0007]
- EP 1646305 A [0006] [0034]
- CH 593044 [0007] [0008]
- DE 10322034 [0007] [0009]
- DE 19732414 [0007] [0009]
- DE 19737694 [0007] [0009]
- EP 0485211 A [0007] [0009]
- FR 2799630 [0007] [0013]
- US 4242568 A [0007] [0008]
- US 4595131 A [0007] [0012]
- US 5019690 A [0007] [0011]
- US 5392694 A [0007]
- US 6393967 B [0007]
- US 6889598 B [0007] [0010]
- US 7286752 B [0007] [0009]
- WO 0154551 A [0007] [0009]
- US 20030066431 A [0007] [0015]
- WO 2004006742 A [0007] [0009]
- EP 1610596 A [0012]
- EP 0387515 A [0014]
- EP 07117853 A [0034] [0055]

一种用于液体食物或饮料制备机器的直列加热装置(1, 2, 3, 4), 液体在该机器中经该加热装置循环并且然后被引导到冲煮室中。该加热装置包括: 带金属块状物(1)的热块, 该金属块状物结合了进口、出口和在它们之间延伸的加热室以形成用于引导经所述块状物循环的所述液体的通道, 该块状物设置成积聚热量并向液体供给热量; 以及一个或多个电气构件(60, 70, 75), 其刚性固定在热块上或其中并连接至设置成控制热块的印刷电路板(4)和/或挠性印刷电路板(4')。电气构件特别是经由刚性连接器插销或叶片或刚性插头和插座部件刚性连接至该印刷电路板和/或挠性印刷电路板。