



(51) International Patent Classification:

G06F 11/00 (2006.01)

G06F 17/00 (2019.01)

(21) International Application Number:

PCT/US2019/037343

(22) International Filing Date:

14 June 2019 (14.06.2019)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

62/685,690

15 June 2018 (15.06.2018)

US

(71) Applicant: BELL AND HOWELL, LLC [US/US]; 3791

South Alston Avenue, Durham, NC 27713 (US).

(72) Inventors: MIDDELBERG, Neal J.; 6022 Splitrock Trail,

Apex, NC 27539 (US). PAUL, Mark Gerard; 5124 For-

est Garden Lane, Raleigh, NC 27606 (US). ADCOCK,

Craig S.; 4101 Gallatree Lane, Raleigh, NC 27616 (US).

JOHNSON, Richard; 7616 Troy Stone Dr., Fuquay Vari-

na, NC 27526 (US).

(74) Agent: WILSON, Jeffrey L.; Jenkins, Wilson, Taylor &

Hunt, P.A., 3015 Carrington Mill Boulevard, Suite 550,

Morrisville, NC 27560 (US).

(81) Designated States (unless otherwise indicated, for every

kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every

kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

(54) Title: SECURE STORAGE AND RETRIEVAL SYSTEMS AND METHODS




FIG. 4

(57) Abstract: A secure storage and retrieval system has a vault with a frame, one or more platters rotatably mounted about the frame, storage bins arranged radially about each of the one or more platters, and mounting surfaces arranged about a perimeter of the vault; and at least one user terminal connected to the vault at one of the mounting surfaces of the vault, the at least one user terminal including an elevator system that vertically moves the plurality of storage bins between any of the one or more platters and an opening formed through an outer shell of the user terminal.

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

SECURE STORAGE AND RETRIEVAL SYSTEMS AND METHODS

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims the benefit of, and claims priority to, U.S. Provisional Patent Application Serial No. 62/685,690, which was filed on June 15, 2018, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

[0002] Pharmacies often fill prescriptions for patients who are not physically present at the pharmacy for immediate receipt of the prescription medication. In some instances, a prescription for one or more prescribed medications may be remotely submitted to a pharmacy by doctors electronically (e.g., via the Internet or an electronic facsimile service) or telephonically (e.g., using a facsimile service or actually calling the pharmacy) so that the pharmacy can fill the prescription and have the prescribed medications ready to dispense to the patient or caregiver upon their arrival at the pharmacy. In some other instances (e.g., when a prescribed medication is of a particular class of medications), a patient or caregiver may need to bring a physical prescription for one or more prescribed medications to the pharmacy to be filled, but returning later rather than waiting at the pharmacy while the prescription is filled. A pharmacy may also have standing prescription orders on file, requiring ongoing refills of prescriptions, as needed, over a period of time. Patients may order refills by calling the pharmacy, by accessing the pharmacy's automated interactive voice response (IVR) telephone system, by accessing the pharmacy's website, or by using any number of mobile device applications. In some instances, refills may even be triggered automatically by the pharmacy computer system.

[0003] Storage systems are often used to store prescriptions until patients arrive. Such systems may be referred to as pharmacy "will call" systems. A common will call system is simply an array of shelves behind the pharmacy counter where prescriptions are placed so pharmacy staff can access them when patients arrive. Another such will call system is an array of plastic bags that are filled with the medications and hung from one of a plurality of horizontal rods within the pharmacy.

The patient or caregiver to receive the prescribed medication from the pharmacy is typically given notice that the prescribed medication is available by, for example, a phone call, a short message service (SMS) text message, email, or even a notification on a mobile device associated with the patient or caregiver designated as the recipient of the prescribed medication. The patient or caregiver must then arrive at the pharmacy during normal business hours, show proper identification (where necessary) or provide other authentication information (e.g., birth date of the patient), present any prescription insurance coverage that may apply, pay for the prescribed medication, and then receive the designated medication. In some cases, e.g., first time prescriptions, the pharmacist may be required (e.g., by state or federal law) to discuss the medication with the customer, or the customer may want to review their prescription with the pharmacist to understand what interactions are possible with other medications being taken by the patient. Regardless of the reason for this pharmacist consultation, it will need to occur during normal business hours. Busy pharmacies typically have a large number of prescription items in will call. Unfortunately, when there are a large number of prescriptions in will call, time is spent searching for the prescriptions needed to dispense to a patient, thus wasting staff time and increasing patient wait time.

[0004] Many such will call systems are readily accessible by anyone physically behind the pharmacy counter, thus introducing the potential for errors and even intentional drug diversion (i.e., theft). For example, prescriptions are sometimes given to the wrong patient due to human error (e.g., misreading a label or otherwise selecting the wrong prescription). There is also a greater risk of theft by pharmacy staff or others if physical access to the will call system is not securely managed.

[0005] Thus, there is a need for an improved system of prescription medication storage and retrieval that mitigates risks of human error, theft, or tampering, while also decreasing retrieval time.

SUMMARY

[0006] This summary lists several embodiments of the presently disclosed subject matter, and in many cases lists variations and permutations of these embodiments. This summary is merely exemplary of the numerous and varied embodiments. Mention of one or more representative features of a given embodiment is likewise

exemplary. Such an embodiment can typically exist with or without the feature(s) mentioned; likewise, those features can be applied to other embodiments of the presently disclosed subject matter, whether listed in this summary or not. To avoid excessive repetition, this Summary does not list or suggest all possible combinations of such features.

[0007] According to a first aspect, a secure storage and retrieval system is provided, the system comprising: a vault comprising a frame; one or more platters mounted about the frame to be independently rotatable about the frame; a plurality of storage bins arranged radially about each of the one or more platters; and a plurality of mounting surfaces arranged about a perimeter of the vault; the system comprising at least one user terminal connected to the vault at one of the mounting surfaces of the vault, the at least one user terminal comprising an elevator system configured to vertically move the plurality of storage bins between any of the one or more platters and an opening formed through an outer shell of the user terminal.

[0008] In some embodiments of the system, the frame comprises a base, an upper portion, a lower portion, and a plurality of inner vertical struts extending between and connecting the upper portion to the lower portion.

[0009] In some embodiments of the system, the frame is devoid of a central axle.

[0010] In some embodiments of the system, the base comprises at least two parallel axial slots on an underside of the base, such that the frame is movable by a pallet jack, a fork truck, or other transport device.

[0011] In some embodiments of the system, the plurality of inner vertical struts comprises at least three inner vertical struts.

[0012] In some embodiments of the system, the frame has a cross-sectional profile in a shape of a polygon and a number of the plurality of mounting surfaces is equivalent to a number of sides of the polygon.

[0013] In some embodiments of the system, the inner vertical struts are spaced apart from each other by an angle of approximately 60° relative to the longitudinal axis of the frame.

[0014] In some embodiments, the system comprises, for each of the platters, a plurality of rollers rotatably attached to the inner vertical struts to support the platter and maintain a gap between an inner edge of the platters and the inner vertical struts.

[0015] In some embodiments of the system, the at least one user terminal comprises at least one user interface device for determining an identity of a user authorized to retrieve one or more items stored in one of the storage bins within the vault.

[0016] In some embodiments of the system, the one or more platters comprises a plurality of platters.

[0017] In some embodiments, the system comprises a rapid retrieval and storage (RRS) terminal attached to the vault at one of the mounting surfaces of the vault, the RRS terminal comprising: an outer shell; an opening formed through the outer shell to allow items to pass through the opening into and/or out of the vault; and a door that is movably arranged within the opening between an open position and a closed position; wherein the opening is at a height of one of the platters, designated as an RRS platter.

[0018] In some embodiments of the system, the RRS terminal is separated from the at least one user terminal by a physical barrier.

[0019] In some embodiments of the system, only the RRS platter can be accessed through the opening of the RRS terminal

[0020] In some embodiments of the system, the RRS terminal comprises an inventory control device configured to detect and/or verify one or more items passing through the opening of the RRS terminal; and the system is configured to advance the RRS platter, such that a second empty storage bin on the RRS platter is accessible through the opening of the RRS terminal, after an item has been deposited into a first empty storage bin on the RRS platter.

[0021] In some embodiments of the system, the at least one user terminal comprises a plurality of user terminals that support simultaneous user induction and retrieval of items within the vault; and the plurality of user terminals are configured to replace occupied storage bins on the RRS platter with empty storage bins from another of the platters as empty storage bins are filled by a user at the RRS terminal.

[0022] In some embodiments of the system, the system is configured to optimize an arrangement of storage bins within the vault, prior to items being loaded onto the RRS platter at the RRS terminal, by removing occupied storage bins from the RRS platter and arranging empty storage bins about the RRS terminal in a consecutive manner.

[0023] In some embodiments of the system, the RRS terminal comprises one or more user interface devices configured to authenticate an identity of a user at the RRS and/or to scan an item to obtain information about the item before an item is loaded into one of the storage bins at the RRS terminal and/or after an item is removed from one of the storage bins at the RRS terminal. In some such embodiments, the method comprises validating an association (e.g., regarding information obtained regarding the item(s)) to a bin identification number.

[0024] In some embodiments, the system comprises, for each of the platters, a drive motor configured to engage with one of the platters to rotate the one of the platters about the frame.

[0025] In some embodiments of the system, the system is configured to measure an amount of backlash between each drive motor and a corresponding one of the platters with which each drive motor rotatably engages, the amount of backlash being determined by, for each platter, rotating the platter in a first direction, stopping the platter, rotating the platter in a second direction, measuring a time between torque spikes detected by the drive motor, and adjusting a motion profile of the drive motor to account for the amount of backlash measured.

[0026] In some embodiments of the system, the at least one user terminal comprises a trolley system that is movable along a length of an elevator shaft of the elevator system and is configured to remove one of the storage bins from any of the platters, deposit one of the storage bins on any of the platters, and transport one of the storage bins vertically along the elevator shaft to be accessible through the opening of the user terminal.

[0027] In some embodiments of the system, the trolley system comprises a base that is movable along the length of the elevator shaft but fixedly arranged in a plane substantially perpendicular to the elevator shaft; and an extension platform that can be extended, relative to the base, towards the platters in a radially inward direction of the platters; wherein the extension platform is configured to engage with one of the storage bins to transfer the storage bin onto or off of the extension platform.

[0028] In some embodiments of the system, the extension platform comprises a slot along a length of the extension platform.

[0029] In some embodiments of the system, the storage bins comprise a rib and a track, the rib being configured to pass within the slot of the extension platform, such

that the track and a bottom of the storage bin are on opposite sides of the extension platform relative to a plane defined by an upper surface of the extension platform.

[0030] In some embodiments of the system, the track of the storage bins comprises a plurality of gear teeth; a bin pinion gear comprising a plurality of gear teeth is arranged on the extension platform in a position that, when the extension platform is in a deployed position extended relative to the base, the gear teeth of the bin pinion gear are adjacent to, and mesh with, the gear teeth of the track; and the bin pinion gear is rotatable in a first direction, in which the storage bin is removed from the platter and drawn onto the extension platform, and a second direction, in which the storage bin is ejected from the extension platform and deposited onto the platter.

[0031] In some embodiments of the system, the extension platform and the bin pinion gear are driven substantially simultaneously.

[0032] In some embodiments of the system, a first of the platters is located in a refrigerated region of the vault so that items stored on the first platter are maintained at a lower temperature than items stored on other platters within the vault.

[0033] In some embodiments of the system, each platter comprises a plurality of bin slots formed around the outer circumference thereof, the bin slots comprising a bin tab comprising opposing elastically deformable pincers; each storage bin comprises a rib connected to a bottom surface of the storage bin, a track connected to the rib in a position spaced apart from the bottom surface of the storage bin, and a bump arranged at, or adjacent to, an end of the rib; and the bump has a shape that can be removably retained within a region of the bin tab to prevent the bin slots from being dislodged from the bin slots other than by the storage bins being removed by a trolley system of the at least one user terminal.

[0034] In some embodiments, the system comprises one or more of: a secure cart configured to securely transport and load a plurality of items from a restricted access area to the vault; a locker pod attached to the vault, the locker pod comprising a plurality of lockers that are directly accessible by a user from a position outside of the vault; a high capacity pod attached to the vault and configured to receive storage bins from the vault for storage in the high capacity pod and/or to transfer storage bins to the vault to be accessible at one of the user terminals; a power pod attached to the vault and configured to provide redundant power to the system; and an automated storage and retrieval system (ASRS) attached to the vault

and comprising a plurality of storage areas internal to the ASRS that are accessible only via a portal external to and separate from the vault.

[0035] In some embodiments of the system, the at least one user terminal comprises an imaging device configured to measure a distance between two fiducial markings on the one or more platters to align the one or more platters with at least one user terminal.

[0036] In some embodiments, the system comprises an automated item-dispensing system operably connected to the vault at a mounting surface of the vault, the automated item-dispensing system being configured to transfer items to the vault for fully automated loading of the items within the vault.

[0037] In some embodiments of the system, the user terminal comprises a touchscreen configured to receive input from a user at the user terminal.

[0038] In some embodiments of the system, the user terminal comprises a touchscreen to sync and receive input from a personal electronic device (PED) of the user at the user terminal.

[0039] In some embodiments of the system, the system is configured to optimize positions of the storage bins within the vault to minimize a processing time for storage and retrieval of one or more items within the vault.

[0040] In some embodiments of the system, the at least one user terminal is configured to display a targeted message to a recipient present at one of the at least one user terminals after authenticating an identity of the recipient.

[0041] In some embodiments of the system, the system is configured to retrieve supply chain pedigree data and display the supply chain pedigree data to a recipient at one of the at least one user terminals.

[0042] In some embodiments, the system comprises a buffer system with a plurality of intermediate storage areas configured to hold and sequentially deposit one or more items into storage bins, which are configured for storage within the vault.

[0043] In some embodiments of the system, the buffer system comprises a belt rotatably movable about at least two spindles, the belt having a plurality of paddles arranged thereon extending away from an outer surface thereof, and the plurality of intermediate storage areas being defined by a space between adjacent paddles in a direction of the length of the belt.

[0044] In some embodiments of the system, the belt is configured to rotate such that any items in each of the intermediate storage areas are sequentially deposited into a storage bin for storage within the vault.

[0045] In some embodiments of the system, the buffer system is configured such that the belt is rotatable in a stepped manner, such that items in only a single intermediate storage area are deposited into a bin for storage within the vault.

[0046] In some embodiments of the system, the buffer system comprises a housing with at least one opening formed therein to allow for depositing items within only one of the intermediate storage areas at a time.

[0047] In some embodiments of the system, the buffer system comprises a scanner configured to detect information regarding the items being deposited into the intermediate storage areas.

[0048] In some embodiments of the system, the information comprises one or more of item identity authentication information, recipient identity information, and/or supply chain information.

[0049] In some embodiments of the system, the buffer system is configured such that the belt advances by a distance equivalent to a length of one intermediate storage area after the scanner or the sensor detects that an item has passed through the opening into one of the intermediate storage areas.

[0050] In some embodiments of the system, the buffer system comprises a sensor configured to detect when the item is deposited into one of the intermediate storage areas through the opening in the housing.

[0051] In some embodiments of the system, the buffer system is configured such that the belt advances by a distance equivalent to a length of one intermediate storage area after the scanner or the sensor detects that an item has passed through the opening into one of the intermediate storage areas.

[0052] In some embodiments of the system, the buffer system is configured to generate an error when the scanner or the sensor detects that an item has been deposited into an intermediate storage area without the information about the item having been detected.

[0053] In some embodiments of the system, advancing the belt by one intermediate storage area deposits items contained in at least one intermediate storage area to be transferred into a bin for storage within the vault.

[0054] In some embodiments of the system, the bin into which the at least one intermediate storage area deposits its contents is not accessible by a user at a user terminal.

[0055] In some embodiments, the system comprises an automated item-dispensing system operably connected to the buffer system and configured to transfer items to the buffer system for fully automated loading of the items within the vault.

[0056] In some embodiments of the system, the system is configured to transmit information remotely to diagnose and troubleshoot malfunctions detected by the system. In some such embodiments, the information may be transmitted to a remote location for diagnosis and corrective action to be determined by a human operator at the remote location, the corrective action being transmitted to the system for the corrective action to be performed without the human operator needing to be physically present at, or have physical access to, the system.

[0057] According to a second aspect, a method for storing and distributing at least one item within a secure storage and retrieval system is provided, the method comprising: providing a vault comprising a frame (e.g., a frame without a central axle), one or more platters mounted about the frame to be independently rotatable about the frame, a plurality of storage bins arranged radially about each of the one or more platters, and a plurality of mounting surfaces arranged about a perimeter of the vault; identifying a designated storage bin of a plurality of storage bins on a designated platter of the one or more platters within the vault, the designated storage bin containing one or more items associated with the user at the user terminal; removing the designated storage bin from the designated platter and transporting the designated storage bin adjacent to an opening formed through an outer shell of the user terminal; opening a door at the user terminal, such that the one or more items within the designated storage bin are accessible to the user through the opening; closing the door after a predetermined amount of time and/or after detecting that the one or more items were removed from the designated storage bin by the user; transporting the designated storage bin adjacent to one of the one or more platters within the vault; and depositing the designated storage bin onto the one of the one or more of platters within the vault.

[0058] In some embodiments of the method, the frame comprises a base, an upper portion, a lower portion, and a plurality of inner vertical struts extending between and connecting the upper portion to the lower portion.

[0059] In some embodiments of the method, the frame is devoid of a central axle.

[0060] In some embodiments of the method, the base comprises at least two parallel axial slots on an underside of the base, such that the frame is movable by a pallet jack, a fork truck, or other transport device.

[0061] In some embodiments of the method, the plurality of inner vertical struts comprises at least three inner vertical struts.

[0062] In some embodiments of the method, the frame has a cross-sectional profile in a shape of a polygon and a number of the plurality of inner vertical struts is equivalent to a number of sides of the polygon.

[0063] In some embodiments of the method, the inner vertical struts are spaced apart from each other by an angle of approximately 60° relative to the longitudinal axis of the frame.

[0064] In some embodiments, the method comprises rotatably attaching, for each of the platters, a plurality of rollers to the inner vertical struts to support the platter and maintain a gap between an inner edge of the platters and the inner vertical struts.

[0065] In some embodiments, the method comprises authenticating an identity of a user at a user terminal connected to the vault at one of the mounting surfaces of the vault.

[0066] In some embodiments of the method, the one or more platters comprises a plurality of platters.

[0067] In some embodiments, the method comprises attaching a rapid retrieval and storage (RRS) terminal to the vault at one of the mounting surfaces of the vault, the RRS terminal comprising: an outer shell; an opening formed through the outer shell to allow items to pass through the opening into and/or out of the vault; and a door that is movably arranged within the opening between an open position and a closed position; wherein the opening is at a height of one of the platters, designated as an RRS platter.

[0068] In some embodiments of the method, the RRS terminal is separated from the at least one user terminal by a physical barrier.

[0069] In some embodiments of the method, only the RRS platter can be accessed through the opening of the RRS terminal

[0070] In some embodiments, the method comprises: detecting, using an inventory control device of the RRS terminal, one or more items passing through the opening of the RRS terminal; and advancing, after an item has been deposited into a first empty storage bin on the RRS platter, the RRS platter, such that a second empty storage bin on the RRS platter is accessible through the opening of the RRS terminal.

[0071] In some embodiments of the method, the at least one user terminal comprises a plurality of user terminals that support simultaneous user induction and retrieval of items within the vault, the method comprising replacing, using the plurality of user terminals, occupied storage bins on the RRS platter with empty storage bins from another of the platters as empty storage bins are filled by a user at the RRS terminal.

[0072] In some embodiments, the method comprises optimizing an arrangement of storage bins within the vault, prior to items being loaded onto the RRS platter at the RRS terminal, by removing occupied storage bins from the RRS platter and arranging empty storage bins about the RRS terminal in a consecutive manner.

[0073] In some embodiments, the method comprises: authenticating, using one or more user interface devices of the RRS terminal, an identity of a user at the RRS; and/or scanning an item to obtain information about the item before an item is loaded into one of the storage bins at the RRS terminal and/or after an item is removed from one of the storage bins at the RRS terminal. In some such embodiments, the method comprises validating an association (e.g., regarding information obtained regarding the item(s)) to a bin identification number.

[0074] In some embodiments, the method comprises, for each of the platters, a drive motor that engages with one of the platters to rotate the one of the platters about the frame.

[0075] In some embodiments, the method comprises measuring an amount of backlash between each drive motor and a corresponding one of the platters with which each drive motor rotatably engages, the amount of backlash being determined by, for each platter, rotating the platter in a first direction, stopping the platter, rotating the platter in a second direction, measuring a time between torque spikes

detected by the drive motor, and adjusting a motion profile of the drive motor to account for the amount of backlash measured.

[0076] In some embodiments of the method, the at least one user terminal comprises a trolley system that is movable along a length of an elevator shaft of the elevator system and is configured to remove one of the storage bins from any of the platters, deposit one of the storage bins on any of the platters, and transport one of the storage bins vertically along the elevator shaft to be accessible through the opening of the user terminal.

[0077] In some embodiments of the method, the trolley system comprises: a base that is movable along the length of the elevator shaft but fixedly arranged in a plane substantially perpendicular to the elevator shaft; and an extension platform that can be extended, relative to the base, towards the platters in a radially inward direction of the platters; wherein the extension platform is configured to engage with one of the storage bins to transfer the storage bin onto or off of the extension platform.

[0078] In some embodiments of the method, the extension platform comprises a slot along a length of the extension platform.

[0079] In some embodiments of the method, the storage bins comprise a rib and a track, the method comprising inserting the rib within the slot of the extension platform, such that the track and a bottom of the storage bin are on opposite sides of the extension platform relative to a plane defined by an upper surface of the extension platform.

[0080] In some embodiments of the method, the track of the storage bins comprises a plurality of gear teeth; a bin pinion gear comprising a plurality of gear teeth is arranged on the extension platform in a position that, when the extension platform is in a deployed position extended relative to the base, the gear teeth of the bin pinion gear are adjacent to, and mesh with, the gear teeth of the track; and the bin pinion gear is rotatable in a first direction, in which the storage bin is removed from the platter and drawn onto the extension platform, and a second direction, in which the storage bin is ejected from the extension platform and deposited onto the platter.

[0081] In some embodiments of the method, the extension platform and the bin pinion gear are driven substantially simultaneously.

[0082] In some embodiments of the method, a first of the platters is located in a refrigerated region of the vault so that items stored on the first platter are maintained at a lower temperature than items stored on other platters within the vault.

[0083] In some embodiments of the method, each platter comprises a plurality of bin slots formed around the outer circumference thereof, the bin slots comprising a bin tab comprising opposing elastically deformable pincers; each storage bin comprises a rib connected to a bottom surface of the storage bin, a track connected to the rib in a position spaced apart from the bottom surface of the storage bin, and a bump arranged at, or adjacent to, an end of the rib; and the bump has a shape that can be removably retained within a region of the bin tab to prevent the bin slots from being dislodged from the bin slots other than by the storage bins being removed by a trolley system of the at least one user terminal.

[0084] In some embodiments, the method comprises one or more of: providing a secure cart configured to securely transport and load a plurality of items from a restricted access area to the vault; a locker pod attached to the vault, the locker pod comprising a plurality of lockers that are directly accessible by a user from a position outside of the vault; attaching a high capacity storage pod to the vault to receive storage bins from the vault for storage in the high capacity pod and/or to transfer storage bins to the vault to be accessible at one of the user terminals; attaching a power pod to the vault to provide redundant power to the system; and attaching an automated storage and retrieval system (ASRS) to the vault, the ASRS comprising a plurality of storage areas internal to the ASRS that are accessible only via a portal external to and separate from the vault.

[0085] In some embodiments of the method, the at least one user terminal comprises an imaging device configured to measure a distance between two fiducial markings on the one or more platters to align the one or more platters with at least one user terminal.

[0086] In some embodiments, the method comprises operably connecting an automated item-dispensing system to the vault at a mounting surface of the vault to transfer items to the vault for fully automated loading of the items within the vault.

[0087] In some embodiments of the method, the user terminal comprises a touchscreen to receive input from a user at the user terminal.

[0088] In some embodiments of the method, the user terminal comprises a touchscreen to sync and receive input from a personal electronic device (PED) of the user at the user terminal.

[0089] In some embodiments, the method comprises optimizing positions of the storage bins within the vault to minimize a processing time for storage and retrieval of one or more items within the vault.

[0090] In some embodiments, the method comprises displaying, on a display of the at least one user terminal, a targeted message to a recipient present at one of the at least one user terminals after authenticating an identity of the recipient.

[0091] In some embodiments, the method comprises retrieving supply chain pedigree data and displaying the supply chain pedigree data to a recipient at one of the at least one user terminals.

[0092] In some embodiments, the method comprises providing a buffer system with a plurality of intermediate storage areas to hold and sequentially deposit one or more items into storage bins for storage within the vault.

[0093] In some embodiments of the method, the buffer system comprises a belt rotatably movable about at least two spindles, the belt having a plurality of paddles arranged thereon extending away from an outer surface thereof, and the plurality of intermediate storage areas being defined by a space between adjacent paddles in a direction of the length of the belt.

[0094] In some embodiments, the method comprises rotating the belt such that any items in each of the intermediate storage areas are sequentially deposited into a storage bin for storage within the vault.

[0095] In some embodiments of the method, the belt is rotatable in a stepped manner, such that items in only a single intermediate storage area are deposited into a bin for storage within the vault.

[0096] In some embodiments of the method, the buffer system comprises a housing with at least one opening formed therein, the method comprising depositing items within only one of the intermediate storage areas at a time.

[0097] In some embodiments of the method, the buffer system comprises a scanner, the method comprising detecting, using the scanner of the buffer system, information regarding the items being deposited into the intermediate storage areas.

[0098] In some embodiments of the method, the information comprises one or more of item identity authentication information, recipient identity information, and/or supply chain information.

[0099] In some embodiments, the method comprises advancing the belt by a distance equivalent to a length of one intermediate storage area after the scanner or the sensor detects that an item has passed through the opening into one of the intermediate storage areas.

[0100] In some embodiments of the method, the buffer system comprises a sensor, the method comprising detecting, using the sensor, when the item is deposited into one of the intermediate storage areas through the opening in the housing.

[0101] In some embodiments, the method comprises advancing the belt by a distance equivalent to a length of one intermediate storage area after the scanner or the sensor detects that an item has passed through the opening into one of the intermediate storage areas.

[0102] In some embodiments, the method comprises generating, at the buffer system and/or in the system, an error when the scanner or the sensor detects that an item has been deposited into an intermediate storage area without the information about the item having been detected.

[0103] In some embodiments of the method, advancing the belt by one intermediate storage area deposits items contained in at least one intermediate storage area to be transferred into a bin for storage within the vault.

[0104] In some embodiments of the method, the bin into which the at least one intermediate storage area deposits its contents is not accessible by a user at a user terminal.

[0105] In some embodiments, the method comprises operably connecting an automated item-dispensing system to the buffer system to transfer items to the buffer system for fully automated loading of the items within the vault.

[0106] In some embodiments, the method comprises: rotating the designated platter on which the designated storage bin is located so that the designated storage bin is aligned with a trolley system of the user terminal; and extending an extension platform of the trolley system such that the designated storage bin can be transferred onto the extension platform.

[0107] In some embodiments of the method, the at least one item is a uniquely identified item.

[0108] In some embodiments, the method comprises transmitting information remotely to diagnose and troubleshoot malfunctions detected by the system. In some such embodiments, the information may be transmitted to a remote location for diagnosis and corrective action to be determined by a human operator at the remote location, the corrective action being transmitted to the system for the corrective action to be performed without the human operator needing to be physically present at, or have physical access to, the system.

[0109] In another aspect, a secure storage and retrieval system is provided, the system comprising: a vault comprising a frame that is devoid of a central axle and has a cross-sectional profile in a shape of a polygon and a number of the plurality of mounting surfaces being equivalent to a number of sides of the polygon; one or more platters mounted about the frame to be independently rotatable about the frame; a plurality of storage bins arranged radially about each of the one or more platters; and a plurality of mounting surfaces arranged about a perimeter of the vault; the system comprising at least one user terminal connected to the vault at one of the mounting surfaces of the vault, the at least one user terminal comprising an elevator system configured to vertically move the plurality of storage bins between any of the one or more platters and an opening formed through an outer shell of the user terminal.

[0110] The methods and systems disclosed herein can be combined in any combination and/or sub-combination, adding elements from other systems and/or sub-systems or steps from other methods and/or sub-methods, as the case may be, and/or omitting elements from other systems and/or sub-systems or steps from other methods and/or sub-methods without limitation. Nothing disclosed herein shall be interpreted as limiting in any way the combinations in which the features, structures, steps, *etc.* may be organized, described, and/or claimed in this or any related applications.

BRIEF DESCRIPTION OF THE DRAWINGS

[0111] The presently disclosed subject matter can be better understood by referring to the following figures. The components in the figures are not necessarily to scale, emphasis instead being placed upon illustrating the principles of the

presently disclosed subject matter (often schematically). In the figures, like reference numerals designate corresponding parts throughout the different views. A further understanding of the presently disclosed subject matter can be obtained by reference to an embodiment set forth in the illustrations of the accompanying drawings. Although the illustrated embodiment is merely exemplary of systems for carrying out the presently disclosed subject matter, both the organization and method of operation of the presently disclosed subject matter, in general, together with further objectives and advantages thereof, can be more easily understood by reference to the drawings and the following description. The drawings are not intended to limit the scope of this presently disclosed subject matter, which is set forth with particularity in the claims as appended or as subsequently amended, but merely to clarify and exemplify the presently disclosed subject matter.

[0112] Like numbers refer to like elements throughout. In the figures, the thickness of certain lines, layers, components, elements or features can be exaggerated for clarity. Where used, broken lines illustrate optional features or operations unless specified otherwise.

[0113] For a more complete understanding of the presently disclosed subject matter, reference is now made to the drawings submitted herewith.

[0114] FIG. 1 is a perspective view of an example embodiment of a secure storage and retrieval system.

[0115] FIG. 2 is a perspective view of the secure storage and retrieval system of FIG. 1.

[0116] FIG. 3 is a top view of the secure storage and retrieval system of FIG. 1.

[0117] FIG. 4 is a partial internal sectional view of the secure storage and retrieval system of FIG. 1.

[0118] FIG. 5 is an internal view of a portion of a user terminal of the secure storage and retrieval system of FIG. 1.

[0119] FIG. 6 is a partial internal sectional view of the secure storage and retrieval system of FIG. 1.

[0120] FIG. 7 is an isolated top view of an example embodiment of a platter with a plurality of storage bins arrayed thereabout.

[0121] FIG. 8 is a sectional view of an example embodiment of a secure storage and retrieval system, showing internal components of the user terminal.

[0122] FIGS. 9A and 9B are isolated side views of an example embodiment of a secure storage and retrieval system.

[0123] FIG. 10 is an internal perspective view of the platters of an example embodiment of a secure storage and retrieval system.

[0124] FIG. 11 is an internal view of a further example embodiment of a secure storage and retrieval system.

[0125] FIG. 12 is a perspective internal view of an example embodiment of a secure storage and retrieval system.

[0126] FIG. 13 is a perspective internal view of an example embodiment of a secure storage and retrieval system.

[0127] FIGS. 14-16 are isolated, perspective views of a user terminal of an example embodiment of a secure storage and retrieval system.

[0128] FIGS. 17 and 18 are isolated, perspective views of an example embodiment of a rapid retrieval and storage (RRS) terminal of a secure storage and retrieval system.

[0129] FIGS. 19 and 20 are isolated, perspective views of an example embodiment of a power pod of a secure storage and retrieval system.

[0130] FIG. 21 is a perspective illustration of an example embodiment of a secure storage and retrieval system.

[0131] FIG. 22 is a perspective illustration of an example embodiment of a secure storage and retrieval system.

[0132] FIG. 23 is a perspective illustration of an example embodiment of a secure storage and retrieval system and environment.

[0133] FIG. 24 is a schematic perspective illustration of an example embodiment of a buffer system used for induction of a series of items into any of the secure storage and retrieval systems disclosed herein.

[0134] FIG. 25 is a schematic front view of the example embodiment of the buffer system shown in FIG. 34.

[0135] FIG. 26 is a schematic illustration of an example embodiment of a secure storage and retrieval system.

[0136] FIGS. 27 and 28 are side and isolated views of an example embodiment of a storage bin for use in a secure storage and retrieval system.

[0137] FIGS. 29-31 are respective perspective views of an example embodiment of a trolley system for use in a secure storage and retrieval system.

[0138] FIG. 32 is a schematic illustration of an example embodiment of a secure storage and retrieval system.

DETAILED DESCRIPTION

[0139] The presently disclosed subject matter now will be described more fully hereinafter, in which some, but not all embodiments of the presently disclosed subject matter are described. Indeed, the disclosed subject matter can be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will satisfy applicable legal requirements.

[0140] The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the presently disclosed subject matter.

[0141] While the following terms are believed to be well understood by one of ordinary skill in the art, the following definitions are set forth to facilitate explanation of the presently disclosed subject matter.

[0142] All technical and scientific terms used herein, unless otherwise defined below, are intended to have the same meaning as commonly understood by one of ordinary skill in the art. References to techniques employed herein are intended to refer to the techniques as commonly understood in the art, including variations on those techniques or substitutions of equivalent techniques that would be apparent to one skilled in the art. While the following terms are believed to be well understood by one of ordinary skill in the art, the following definitions are set forth to facilitate explanation of the presently disclosed subject matter.

[0143] In describing the presently disclosed subject matter, it will be understood that a number of techniques and steps are disclosed. Each of these has individual benefit and each can also be used in conjunction with one or more, or in some cases all, of the other disclosed techniques.

[0144] Accordingly, for the sake of clarity, this description will refrain from repeating every possible combination of the individual steps in an unnecessary fashion. Nevertheless, the specification and claims should be read with the understanding that such combinations are entirely within the scope of the present disclosure and the claims.

[0145] All publications, patent applications, patents and other references cited herein are incorporated by reference in their entireties for the teachings relevant to the sentence and/or paragraph in which the reference is presented.

[0146] Following long-standing patent law convention, the terms “a”, “an”, and “the” refer to “one or more” when used in this application, including the claims. Thus, for example, reference to “an element” includes a plurality of such elements, and so forth.

[0147] Unless otherwise indicated, all numbers expressing quantities of ingredients, reaction conditions, and so forth used in the specification and claims are to be understood as being modified in all instances by the term “about”. Accordingly, unless indicated to the contrary, the numerical parameters set forth in this specification and attached claims are approximations that can vary depending upon the desired properties sought to be obtained by the presently disclosed subject matter.

[0148] As used herein, the term “about,” when referring to a value or to an amount of a composition, mass, weight, temperature, time, volume, concentration, percentage, etc., is meant to encompass variations of in some embodiments $\pm 20\%$, in some embodiments $\pm 10\%$, in some embodiments $\pm 5\%$, in some embodiments $\pm 1\%$, in some embodiments $\pm 0.5\%$, and in some embodiments $\pm 0.1\%$ from the specified amount, as such variations are appropriate to perform the disclosed methods or employ the disclosed compositions.

[0149] The term “comprising”, which is synonymous with “including” “containing” or “characterized by” is inclusive or open-ended and does not exclude additional, unrecited elements or method steps. “Comprising” is a term of art used in claim language which means that the named elements are essential, but other elements can be added and still form a construct within the scope of the claim.

[0150] As used herein, the phrase “consisting of” excludes any element, step, or ingredient not specified in the claim. When the phrase “consists of” appears in a clause of the body of a claim, rather than immediately following the preamble, it limits only the element set forth in that clause; other elements are not excluded from the claim as a whole.

[0151] As used herein, the phrase “consisting essentially of” limits the scope of a claim to the specified materials or steps, plus those that do not materially affect the basic and novel characteristic(s) of the claimed subject matter.

[0152] With respect to the terms “comprising”, “consisting of”, and “consisting essentially of”, where one of these three terms is used herein, the presently disclosed and claimed subject matter can include the use of either of the other two terms.

[0153] As used herein, the term “and/or” when used in the context of a listing of entities, refers to the entities being present singly or in combination. Thus, for example, the phrase “A, B, C, and/or D” includes A, B, C, and D individually, but also includes any and all combinations and subcombinations of A, B, C, and D.

[0154] As used herein, the term “substantially,” when referring to a value, an activity, or to an amount of a composition, mass, weight, temperature, time, volume, concentration, percentage, etc., is meant to encompass variations of in some embodiments $\pm 40\%$, in some embodiments $\pm 30\%$, in some embodiments $\pm 20\%$, in some embodiments $\pm 10\%$, in some embodiments $\pm 5\%$, in some embodiments $\pm 1\%$, in some embodiments $\pm 0.5\%$, and in some embodiments $\pm 0.1\%$ from the specified amount, as such variations are appropriate to perform the disclosed methods or employ the disclosed apparatuses and devices.

[0155] Referring to FIGS. 1-32, example embodiments of a secure storage and retrieval system, generally designated **1000**, are shown. As shown in this embodiment, the system **1000** comprises a central vault **200** that has a generally hexagonally-shaped (e.g., when viewed along the longitudinal axis of the vault **200** and/or from vertically above the vault **200**) external enclosure about which one or modules can be operably attached to, and interface with, the vault **200**, for example, to allow for the insertion and/or removal of items, whether directly or indirectly, from within the vault **200** by a user, which can be, for example, a retail employee, a customer, and the like, present at the system **1000**. While, in the example embodiment shown, the vault **200** comprises a generally hexagonally-shaped external enclosure, the vault **200** may have any suitably shaped external shape, profile, cross-section, etc., including, for example, circular, ovular, elliptical, triangular, square, rectangular, pentagonal, heptagonal, octagonal, nonagonal, decagonal, and the like (e.g., including cross-sectional shapes having more than 10 sides, surfaces, faces, etc.).

[0156] In the example embodiments shown, the system **1000** comprises a vault **200**, in which a plurality of platters **210** are arranged, each of the platters **210** having a plurality of storage bins **300**, which contain one or more items, arranged radially

about a respective one of the platters **210**. The system **1000** further comprises a plurality of sub-systems that can be removably and securely attached to an outer surface of the vault **200** to, for example, control operation of the system **1000**, provide power to the system **1000**, remove and/or input items and/or storage bins **300** within the vault **200**, and the like. The sub-systems can comprise any of (e.g., a plurality of one or more of) a user terminal **100**, a rapid retrieval and storage (RRS) terminal **700**, a power pod **800**, a buffer input device **900**, a storage locker enclosure **1100**, a locker pod **1200**, a high capacity pod **1300**, and/or a secure transfer device **1400**.

[0157] In the example embodiment shown in FIGS. 1-20, the system **1000** comprises a vault **200**, a plurality of (e.g., two) user terminals **100**, an RRS terminal **700**, and a power pod **800**, the user terminals **100**, the RRS terminal **700**, and the power pod **800** being arranged radially about and mounted (e.g., lockingly) to the vault **200**. FIGS. 21-24 show further example embodiments of the system **1000**, in which the RRS terminal **700** is physically segregated (e.g., by a barrier and/or in a restricted access area) from the user terminal(s) **100**. The embodiment shown in FIG. 25 shows an example embodiment in which the RRS terminal **700** is connected with a buffer input device **900**. FIG. 26 shows another example embodiment of the system **1000**, in which the system **1000** comprises a vault **200**, to which are connected a plurality of (e.g., two) user terminals **100**, a power pod **800**, a storage locker enclosure **1100**, a locker pod **1200**, and a high capacity pod **1300**. FIGS. 27 and 28 show various aspects of an example embodiment of a storage bin **300** suitable for use in one or all of the example embodiments of the system **1000** disclosed herein. FIGS. 29-31 show various aspects of an example embodiment of a trolley system **180** that transports storage bins **300** (e.g., individually) within a user terminal **100** between a platter **210** within the vault **200** and a door **110** of the user terminal **100**, where the contents of the storage bin **300** on the trolley system **180** are accessible by a user physically present at the user terminal **100**. FIG. 32 shows another example embodiment of the system **1000**, in which the system **1000** comprises a vault **200**, to which are connected a plurality of (e.g., two) user terminals **100**, a power pod **800**, a locker pod **1200**, and a high capacity pod **1300**, and a secure transfer device **1400**, which can be an enclosed cart that transports items within the interior thereof and can securely engage with and/or be mounted to an external surface of the vault **200**, a user terminal **100**, an RRS terminal **700**, a

storage locker enclosure **1100**, a locker pod **1200**, and/or a high capacity pod **1300** to transfer the items from within the secure transfer device **1400** into the vault **200**.

[0158] While the system **1000** can be operable with one or more (e.g., only a single or a plurality of) user terminals **100**, the system **1000** comprises, in a majority of the embodiments shown, a plurality of (e.g., two) user terminals **100** that are arrayed around and connected over a mounting surface of the vault **200**, at which one or more hinges **204** are attached to the vault **200** to pivotably connect the sub-systems, such as the user terminals **100**, to the vault **200** in a substantially sealing and tamper-proof manner. The user terminals **100** can be installed adjacent each other or spaced apart by, for example, a power pod **800** and/or one or more cover panels **201**.

[0159] In the example embodiment shown in FIGS. 1-20 and 26-32, the vault **200** comprises an internal frame **250** on which a plurality of platters, generally designated **210** are vertically arranged to accommodate a plurality of items and/or a plurality of storage bins **300** of a height less than a vertical distance between adjacent platters **210**. The pitch between adjacent platters **210** can be varied to accommodate taller storage bins **300** at a higher pitch (e.g., greater distance between adjacent platters **210**) and shorter storage bins **300** at a smaller pitch (e.g., smaller distance between adjacent platters **210**). As shown, each user terminal **100** comprises a retrieval portal comprising a door **110** configured to receive one of the plurality of storage bins **300** such that a user at the user terminal **100** can remove the contents stored therein.

[0160] The plurality of platters **210** can be rotatably supported and spaced apart a vertical distance corresponding to a height dimension of one or more storage bins **300** placed thereon. The frame **250** comprises a base **260**, to which at least two guide channels **262** are attached on an underside of the base **260** (e.g., on a surface of the base **260** oriented towards the floor). The guide channels **262** can be formed from one or more plates of, for example, a sheet metal material, and attached to a bottom surface of the base **260**. The guide channels **262** are spaced apart a predetermined distance to allow for engagement of the vault **200** by, for example, a pallet jack, fork truck, or other suitable moving device for positioning the system **1000** at a designated position within the retail store assembly of the remaining components of the system.

[0161] The base **260** as shown has a hexagonal shape, but other shapes are contemplated as well. The base **260** has axially-aligned guide channels **262** (e.g.,

slots) formed to allow for longitudinal members of a fork truck, pallet jack, etc. to pass between the guide channels **262** to lift and move the frame **250** and/or the entire system **1000**. The central region of the frame **250**, defined in this example embodiment as being radially between the inner vertical struts **252** and the outer vertical door latch bars **258** and vertically between the upper and lower portions of the frame **250**, formed, respectively, by the perimeter supports **254** and the ribs **256**, is substantially vacant to accommodate other components of the system **1000** therein when the system **1000** is in an assembled state. As such, in the embodiment shown, the system **1000** operates without a center rotary axle, the bins **300** instead rotating around a static frame **250** within the vault **200** of the system **1000**. Stated somewhat differently, the platters **210** are rotatable about a central axis of the frame **250**, but the platters **210** are not actually connected to the central axis about which they rotate.

[0162] The frame **250** has ribs **256** at the upper and lower vertical surfaces of the frame **250**. The ribs **256** extend radially away from a central hub to interconnect a plurality of perimeter supports **254** that, together, form generally hexagonally-shaped upper and lower surfaces of the frame **250**. The shape of the upper and lower surfaces of the frame **250** generally correspond to the shape (e.g., the outer contour and/or cross-section) of the vault **200**, so an octagonally-shaped vault **200** may have, for example, octagonally-shaped upper and lower portions of the frame **250**. These generally hexagonally-shaped upper and lower surfaces of the frame **250** are vertically connected together by a plurality of inner vertical struts **252**, which can be arranged about and/or at the outer perimeter of the frame **250** and/or radially at a position spaced apart from the outer perimeter of the frame **250**, which are connected by struts to a plurality of longitudinal ribs that extend vertically from a base to at least a height of the upper central portions.

[0163] The polygonal (e.g., hexagonal, in the embodiment shown) cross-sectional shape of the vault **200** is advantageous, in that it allows for a plurality of generally circular-shaped platters to be arranged vertically therein, with the sides of the polygon both approximating the contours of the platters within the vault **200** and also providing a suitable number of substantially planar sides to which various subsystems (e.g., **100**, **700**, **800**, **900**, **1100**, **1200**, **1300**, **1400**) or cover panels **201** can be provided, thereby fully enclosing the interior of the vault **200** and securing the contents stored therein on the platters **210**. The substantially circular shape of the

outer perimeter of the platters **210** is advantageous in that this shape allows for a maximum density of storage bins **300** to be arranged thereon while also minimizing the required diameter of the external enclosure of the vault **200** to allow the platters **210** to rotate about a longitudinal axis of the vault **200**, which is substantially coaxial to the height direction of the vault **200**. The inner-workings of the vault **200** will be discussed further hereinbelow regarding the illustrations thereof in FIGS. 1-20.

[0164] As configured with one or more subsystems (e.g., **100**, **700**, **800**, **900**, **1100**, **1200**, **1300**, **1400**) and/or cover panels **201** attached thereto, the vault **200** comprises a substantially solid and/or enclosed exterior surface about the external perimeter surface thereof. In some embodiments, one or more translucent window sections can be provided in this outer wall (e.g., in a cover panel **201**) to allow for viewing the internal structures within the vault **200**. In some such embodiments, the window sections can have a same contour as that of the outer wall, such that the shape of the outer wall of the vault **200** is not substantially altered by the window section. In some other such embodiments, the window sections can have a substantially flat viewing area that is either recessed within, at least partially, the outer wall, and/or may protrude from, at least partially, the outer wall of the vault. In some embodiments, such as those where the cover panels **201** have a generally planar profile, the window sections can be coplanar with the external surface of the cover panels **201**.

[0165] The outer corners and/or vertices where the perimeter supports **254** intersect in the upper and lower portions of the frame **250** are, in the embodiment shown, substantially vertically coaxially aligned (e.g., in the direction parallel to the longitudinal axis of the vault **200**). Such vertically aligned corners and/or vertices are connected together by one of a plurality of outer vertical door latch bars **258** attached between vertically aligned corners and/or vertices of the upper and lower portions of the frame **250**. In the embodiment shown, the inner vertical struts **252** are radially spaced apart from (e.g., in a radially inward direction) the outer vertical door latch bars **258**, defining a platter channel radially therebetween, in which a plurality of platters **210** are vertically arranged and/or supported thereby.

[0166] In the embodiment shown, each of the outer vertical door latch bars **258** is offset from a corresponding one of the inner vertical struts **252** in the angular, or circumferential, direction of the vault **200**, such that a plane through the longitudinal axis of the vault **200** would not pass through both an inner vertical strut **252** and an

outer vertical door latch bars **258**. This arrangement is advantageous because it allows for a first portion of the mass and/or weight of each platter **210** to be supported by a corresponding platter support ring **268** that can be supported by either the inner vertical struts **252** and/or the outer vertical door latch bars **258**, with a second portion of the mass and/or weight of the platters **210** being supported by the inner vertical struts **252**. As such, in the embodiment shown, each platter **210** is supported, at least partially, by a corresponding platter support ring **268**. This arrangement is further advantageous in that it permits the points at which the platter support ring **268** is connected to the frame **250** to be staggered in the angular, or circumferential, direction from the points at which the platters **210** are connected (e.g., directly and/or via one or more rollers) to the inner vertical struts **252**, thereby providing additional structural rigidity to the platters **210** by staggering the support points in the angular, or circumferential, direction. Furthermore, this angularly staggered region of the inner vertical struts **252** and the outer vertical door latch bars **258** allows for the outer vertical door latch bars **258** to be spaced at angular, circumferential, or radial positions of the frame **250** to define the attachment positions where the subsystems can be attached so as to not interfere with, or otherwise prevent proper operation of, for example, the internal components (e.g., elevator system **150** and trolley system **180**) of the user terminals **100** attached about the vault **200**.

[0167] The platter support ring **268** noted herein is provided at a position radially outward from the radial position where the vertical rollers **216** are connected to the inner vertical struts **252**. In the embodiment shown, the platter support ring **268** is connected to, and supported by, six radially positioned brackets that are secured (e.g., bolted) to the inner vertical struts **252**. Each platter support ring **268** is, in the example embodiment shown, a substantially continuous and/or uninterrupted ring structure on which a corresponding one of the platters **210** is vertically supported to prevent excessive vertical deflection of the platters **210** at positions thereof that are radially outwardly positioned from the vertical rollers **216**. The platters **210** have bearings **234** (e.g., roller bearings or any other suitable type of rotatable element capable of providing relative motion of each platter **210** over a corresponding one of the platter support rings **268**) positioned at a same radial position at which the platter support ring **268** is arranged, such that the bearings **234** rest on and rollably engage with the platter support ring **268** to provide vertical support to the platters **210** to

prevent undesired vertical deflections thereof. In the embodiment shown, the bearings **234** are spaced circumferentially about the platters **210** to be positioned between every other storage bin **300**, however any suitable number and position of bearings **234** may be selected based on the number of storage bins **300** and the maximum weight that can be supported by each storage bin **300**. In some embodiments, the platter support ring **268** can be of a segmented construction having individual ring segments that engage with each other (e.g., concentrically passing within, in some cases to lockingly engage with each other) to form the substantially continuous and uninterrupted platter support ring **268**. The platter support rings **268** can be connected to (e.g., by radially-oriented arms) the inner vertical struts **252** and/or the outer vertical door latch bars **258**. In embodiments where the platter support ring **268** is connected to, and supported by, both the inner vertical struts **252** and the outer vertical door latch bars **258**, the angular positions at which the platter support ring **268** is connected to each inner vertical strut **252** can be angularly and/or circumferentially staggered and/or offset from the angular position at which the platter support ring **268** is connected to each outer vertical door latch bars **258**. It should be noted that the outer vertical door latch bars **258** can be omitted in some embodiments where, for example, no subsystems are to be attached to the vault **200**.

[0168] The platters **210** are assembled from a plurality of platter segments (e.g., **210A-D**) that are joined together (e.g., by mechanical retention features molded into the platter segments and/or threadable fasteners that fixedly engage with and secure adjacent platter segments together) at respective platter seams, such that the platters can be installed between the vertical rollers **216** without requiring the removal of the vertical rollers **216** from the inner vertical struts **252** for installation of the platters **210** within the vault **200**. The platters **210** are rotatably connected to the inner vertical struts **252** of the frame **250** and are vertically supported at each vertical support strut **252** by a corresponding vertical roller **216** on which the platter **210** is supported at an inner radial support channel **214**. In some embodiments, each platter **210** is held (e.g., rollably clamped) between pairs substantially vertically aligned vertical rollers **216** in the form of wheels attached to the inner vertical struts **252** of the frame **250**. The vertical rollers **216** thereby provide a first support surface by which the platters **210** are connected to, and vertically supported by, the inner vertical struts **252**.

[0169] In some embodiments, the inner radial support channel **214** may be provided with a high-friction material on one or more side thereof, including, for example, rubber, silicone, and the like. In some other embodiments, either in addition to or in lieu of the high-friction material, a friction-increasing surface treatment may be applied over at least a portion of the inner radial support channel **214**; examples of such friction-increasing surface treatments include knurling, slotting (e.g., to create a washboard-like surface), hatching, and the like. In some embodiments, one or more of the vertical rollers **216** can be a driven roller, which is configured to interface with the inner radial support channel **214** of the platter **210** (e.g., in the form of a rack-and-pinion arrangement) in order to substantially eliminate slippage between the platter and the vertical rollers **216** to ensure radial positional fidelity of the platters **210** within the vault **200** and, in some embodiments, allow for the omission of a position detection system, since the angular position of each platter **210** within the vault **200** will be fixed as a function of the number of rotations of the vertical rollers **216** and/or of the drive motor **240**. By knowing the number of rotations of the vertical rollers **216** and/or of the drive motor **240**, as well as the effective diameter(s) thereof, the angular position of the platter **210** can be calculated continuously on a real-time basis.

[0170] The radial position of each of the platters **210** is maintained in a position spaced apart substantially uniformly from the inner vertical struts **252** by a plurality of horizontal rollers **218** that are each respectively mounted to a corresponding one of the inner vertical struts **252**. The horizontal rollers **218** engage against an inner edge **212** of one of the platters **210** and are positioned about the inner vertical struts **252** to define a substantially circular contact surface that prevents any eccentricities of the platter **210**, whether caused by the shape or movement of the platter **210**, as it rotates about the frame **250** that would cause the platter to otherwise make contact with one or more of the inner vertical struts **252** and/or for the platter **210** to become disengaged from the one or more vertical rollers **216**.

[0171] For each platter, at least one drive motor **242** is rigidly attached to one of the inner vertical struts **252** of the frame **250**, such that each at least one drive motor **242** is statically positioned within the vault **200**. The platter **210** has a plurality of geared teeth that are oriented to face radially inwards to define an inner radial gear **220**. The drive motor **242** comprises a plurality of complementarily-shaped gear teeth in the form of a pinion gear, such that the engagement of the drive motor **242**

with the inner radial gear **220** is in the form of a rack-and-pinion interface. Since the drive motors **242** remain stationary during operation, this advantageously precludes any tangling or twisting of wiring (e.g., about a central axis). Each drive motor **242** is capable of rotating a corresponding one of the platters **210** either clockwise or counterclockwise, depending on the direction of rotation of the platter **210** being rotated. The geared interface between each drive motor **242** and the inner radial gear **220** of a corresponding one of each of the platters **210** is therefore capable of providing precise positional control without allowing the platter **210** to slip relative to the drive motor **242**. A positional encoder (e.g., a rotary positional encoder) is provided, for example, in the drive motor **242**. In some embodiments, the drive motor **242** is a stepper motor that is configured to turn by a predetermined number of steps, or parts thereof, upon receiving a command. In some embodiments, the drive motor **242** turns in whole steps.

[0172] In some embodiments, a post (e.g., a vertically-oriented post) is provided on each platter **210** in a position such that, when the post passes through, by, adjacent to, *etc.* a sensor (e.g., a non-contact sensor), the precise angular position of the platter **210** within the vault **200** can be determined. The position where the post is detected by the sensor can be defined as the home position of the platter **210**. The home positions for the elevator systems **150**, trolley systems **180**, doors **110**, **710**, and the like are determined by monitoring a current consumption used during the movement thereof. Accordingly, to positionally register these devices in a “home” position, it is advantageous to drive these devices against a stop, monitor for a current spike or increase, such that the device is in the home position when the current spike is detected.

[0173] Since each platter **210** has at least one drive motor **242** associated and/or engaged therewith, each of the platters **210** is capable of rotary movement about the frame **250** independent of the movement of any of the other platters **210** within the system **1000**. As such, each of the platters **210** is movable about the frame **250** independent of the other platters **210** within the vault **200**. In some embodiments, the geared interface between the platters **210** and the corresponding drive motor **242** can be replaced with a substantially flat surface having a high-friction material coated on at least an outer circumference thereof to prevent and/or minimize an amount of slippage between the platter **210** and the drive motor **242**. In some embodiments, a plurality of drive motors **242** can be provided, which can be arranged on the same or

different inner vertical struts **252** of the frame **250**. In such embodiments having a high-friction material interface, the contact surface between the platter **210** and the drive motor **242** can be in a substantially horizontal plane, a substantially vertical plane, an inclined plane, or any other suitable interface surface. In the embodiment shown, seven (7) platters **210** are provided for the system **1000** to form the seven (7) arrays of storage bins **300** described elsewhere herein.

[0174] In the example embodiment shown, each platter **210** has a plurality of bin slots **226**, advantageously one for each storage bin **300**, arranged about an outer perimeter of each platter **210**, advantageously in a uniform spacing about the perimeter thereof so that the storage bins **300** are spaced substantially uniformly about the platter **210** in the circumferential direction. The bin slots **226** are circumferentially spaced apart from each other by a dimension larger than a width of the storage bins **300** to ensure that the storage bins **300** are physically separated from each other and held in a fixed position on the platter **210**. In some embodiments, bin slot dividers may be provided between one or more adjacent bin slots **226** to physically separate (e.g., as a barrier) adjacent storage bins **300** from each other. In such embodiments, the bin slot dividers may be arranged circumferentially about the platter **210** and terminate between the inner edge **212** of the platter **210** (e.g., radially outward from the surface on which the inner radial gear **220** is formed) to define a gap over which the vertical roller(s) **216** pass through as the platter **210** is rotated about the frame **250** by the drive motor **242**. As noted elsewhere herein, one or more of the platters **210** within the vault can be refrigerated/chilled to maintain a lower temperature for the items stored thereon than for the items stored on other platters **210** within the same vault **200**.

[0175] The bin slots **226** extend radially inwards from the outer perimeter of the platter **210**. The storage bins **300** have, on the bottom surface thereof, a track **330** that is connected to, and spaced apart from the bottom **320** of the storage bin **300** by, a connecting rib **332**. As such, the bottom **320**, the rib **332**, and the track **300** form a generally I-shaped cross-sectional profile. The rib **332** is arranged along the length of the storage bin **300** (e.g., in the direction from the back **306** to the front **308**) and has a height corresponding to at least a thickness of the platter **210**, such that the track **330** extends underneath the platter **210** in the manner of opposing flanges to vertically secure the storage bin **300** to the platter **210** when the rib **332** and, accordingly, the storage bin **300** are engaged within one of the bin slots **226** of

the platter **210**. In some embodiments, the bin slot **226** may have a thickness (e.g., measured in the vertical direction) that is less than a thickness of the entire platter **210**, allowing for the height of the rib **232** to be less than a height of the entire platter **210**. Such an arrangement is further advantageous because it is then possible for the track **330** to pass between the retaining flanges **227** of the bin slot **226** and the platter support ring **268**, thereby allowing the platter support ring **268** to be positioned further radially outwardly (e.g., at a radial position greater than half of a length of a storage bin **300**) underneath the platter **210** and storage bins **300**. The bin slots **226** advantageously have a widened portion at the outer perimeter of the platter **210** to account for minor misalignments between the platter **210** and the storage bin **300**.

[0176] The inner perimeter formed by the inner vertical struts **252** of the frame **250** is surrounded by a plurality of circularly arranged storage bins **300**, which are engaged with, and supported by, the platters **210**. In this example embodiment, the storage bins **300** have an inner edge (e.g., a back edge **306**, which is nearest the inner support struts **252**) that is taller than an outer circumferential edge (e.g., a front edge **308**), with the sides **310** extending therebetween and forming an opening above the front edge **308** to allow objects to be placed in and/or retrieved from the storage bins **300**. In some embodiments, the sides **310** can taper between the back edge **306** and the front edge **308**, such that the front edge **308** is wider than the back edge **306**. In some embodiments, the storage bins **300** have a substantially open top surface. In some other embodiments, the storage bins **300** have a partially or entirely closed top surface. As shown, there are seven (7) radially arranged arrays of storage bins **300** in a vertically stacked arrangement. Each of the radially arranged arrays of storage bins **300** is attached to, and supported by, one of the platters **210** supported by the frame **250**.

[0177] The storage bins **300** and platter segments can be formed from any suitable material, including, for example, plastic, composite, and/or metallic materials. The storage bins **300** and platter segments can be formed using any suitable manufacturing technique, including casting, milling, stamping, injection molding, additive manufacturing, and the like. In some examples, the storage bins **300** and platter segments may be injection molded from a plastic material. In other embodiments, storage bins **300** and platter segments may comprise a plastic, composite, metallic, and/or ferromagnetic material. In some embodiments, each

storage bin **300** has a unique identifier (e.g., a barcode, QR code, NFC chip, RFID chip, *etc.*) formed or attached thereon. This unique identifier is associated with only that particular storage bin **300**. In some such embodiments, this unique identifier is scanned (e.g., by imaging device **172**) each and/or every time that that an item is transported to the opening **112**, **712** of a user terminal **100** or an RRS terminal **700**, thereby positively identifying the storage bin **300** as or prior to the items being removed from, or deposited in, the storage bins **300**.

[0178] In some embodiments, at least one assembly tab is provided on at least one edge of the platter sections for assembly with adjacent platter sections. Ribs and other stiffening members can be formed in the top and/or bottom surfaces of the platter segments to provide enhanced structural rigidity. A plurality of holes **232** are formed through the thickness of the platters **210** to reduce a mass thereof without compromising structural rigidity of the platters **210** beyond a design threshold, thereby allowing for the use of smaller motors due to the reduced moments of inertia and/or rotation in such platters **210** having holes **232** formed therein.

[0179] In some embodiments, as shown at least in FIGS. 10 and 29-31, the storage bins **300** can be retained and/or locked in place on the platter **210** by a locking feature (e.g., bump **336** formed in at a radially internal end of the rib **332**). The bin slots **226** comprise, at a radially inner portion thereof, a bin tab **228** that comprises a pair of opposing retaining members that engage about the bump **336**, which can be in the form of a post, protuberance, or other feature that can be removably retained within the bin tab **228**. The bin tab **228** comprises opposing pincers that are spaced apart and capable of elastic deformation to allow the bump **336** to move between the bin tab **228**, while still providing a retention force to prevent the storage bin **300** from being dislodged from the platter **210** during, for example, transit or normal operation of the system **1000**. Thus, a force may be imparted (e.g., by the trolley system **180** of a user terminal **100**) to the storage bin **300** that is of a sufficient magnitude to overcome the force necessary to elastically spread apart the pincers of the bin tab **228** to allow for the bump **336** of a storage bin **300** to be engaged in, or removed from, the bin tab **228**, depending on whether the storage bin **300** is being placed on, or removed from, the platter **210** by the system **1000**. In the embodiment shown, the bump **336** has substantially a same perimeter shape as an inner perimeter shape of the bin tabs **228**.

[0180] A surface is provided on the front surface of the bin, on which an optically-scannable code can be affixed. In some embodiments, a wireless transmitter can be embedded within this surface, or within any other suitable portion of the bin. This code and/or wireless transmitter can allow for enhanced inventory analysis of the vault if any data integrity issues arise that causes the locations of one or more bins within the vault to become corrupted and/or unknown (e.g., due to a loss of power). Because the contents of each bin can be stored remotely from the vault (e.g., in a cloud storage system), during an inventory analysis the platters can be rotated, the identity of each of the bins can be detected and recorded (e.g., by scanning the code or wireless transmitter) by one or more suitable scanners located within the vault, and the contents of each of the bins (as well as the intended recipient for the contents of each bin) can be determined by the system by cross-referencing the identity of each bin with the data for the contents of each bin that can be stored remotely. Accordingly, the contents of the vault can be inventoried without requiring removal of the contents of the vault, thereby dramatically increasing operational recovery time of the system upon a system error.

[0181] During insertion of the storage bin **300** from the platter, the platter **210** is rotated to a position such that the rib **332** of the storage bin **300** is aligned (e.g., radially) with the bin slot **226**. The trolley system **180** then extends in the radial direction towards the platter.

[0182] Due to the presence of the multiple user terminals **100**, multiple platters **210**, and multiple storage bins **300** arranged on or about each of the multiple platters **210**, the system **1000** disclosed herein is capable of redundant operation. For example, if a drive motor **242** fails, the storage bins **300** stored on the other platters **210** remain accessible for retrieval by the user terminals **100**. Similarly, if an elevator system **150** of one of a plurality of user terminals **100** fails, the other user terminal(s) **100** remain operational. This redundancy reduces downtime for the system **1000**.

[0183] FIG. 7 shows a top plan view of an example embodiment of a plurality of storage bins **300** arranged on a platter **210**. Each of the plurality of storage bins **300** are arranged at regular intervals radially about the center of the platter **210**, each storage bin **300** being offset by an angle (e.g., θ) from an adjacent storage bin **300**. In the embodiment shown, the storage bins **300** have a substantially rectangular footprint (e.g., as defined by bottom **320**). In some embodiments, the storage bins **320** can have a profile that tapers in the radially inward direction, such that the back

(e.g., **306**) is narrower than the front (e.g., **308**). Smaller (e.g., narrower) storage bins **300** may be used to increase a storage density within the vault **200**, when it is anticipated that the items to be stored therein will be of a certain size. Additionally, storage bins **300** on one or more of the platters **210** may have a different size from storage bins **300** stored on a different platter **210**. In some embodiments, because the position of each of the storage bins **300** can be monitored by the system **1000** (e.g., by a controller of an inventory tracking system), storage bins **300** on a same platter **210** may have different dimensions from each other (e.g., by assembling platter segments having different spacings between adjacent bin slots **226**). Using the positional calibration method, the system **1000** can automatically detect a spacing between adjacent bin slots **226** when platter segments having different pitches between adjacent bin slots **226** are assembled into a same platter or, in some embodiments, when a platter segment or entire platter **210** is replaced with a platter segment or other platter having a different pitch between adjacent bin slots **226**. The differently sized storage bins **300** on a same platter **210** may be interspersed amongst each other or, in some embodiments, may be segregated from each other, so that at least a first continuous portion of a first platter **210** has storage bins **300** of a same first size, while at least a second continuous portion of the first platter **210** has storage bins **300** of a same second size, which can be the larger and/or smaller in one or more dimensional directions (e.g., height, length, width, etc.).

[0001] Referring to FIGS. 14-16, further aspects of an example embodiment of the user terminal **100** are shown therein. The user terminal **100** has an outer shell **102** that is mounted to an external surface of the vault **200** by hinges **104**, such that the user terminal **100** can pivot about the hinge **104** to reveal the interior of the vault **200** during assembly, maintenance, troubleshooting, and the like. During normal operation, the user terminal **100** is secured to the vault **200** and cannot be opened to access the interior of the vault **200**. A shelf **114** is provided on an external surface of the outer shell **102** of the user terminal **100**. The user terminal **100** comprises one or more user interface devices **120**, a display **122**, an elevator system, generally designated **150**, and an outer housing **102** that is rigidly connected (e.g., by a pivoting hinge) to the vault **200** at one of the mounting surfaces of the vault **200**. In some embodiments, the display **122** and some aspects of the user interface devices **120** can be combined into a single display screen or unit with touchscreen

functionality. In some embodiments, the user interface devices **120** can comprise a wireless communication device (e.g., Bluetooth®, WiFi, RFID, etc.) that can receive an input from a mobile computing device (e.g., a smartphone or a tablet computer) of a user present at the user terminal **100** for identity authentication purposes. As such, the identity of the user can be verified by, for example, scanning an image on the mobile computing device at a user interface device **120** or by positioning the mobile computing device adjacent a user interface device, allowing the user's identity to be authenticated without the user having to physically contact the system **1000**, thereby improving hygiene. In some embodiments, one of the one or more user interface devices **120** comprises a barcode reader or an NFC reader configured to read and/or detect information from a badge associated with, and carried on the person of, an authorized user (e.g., a retail employee). For systems **1000** in which higher degrees of recipient identity authentication is needed (e.g., for those systems **1000** intended for prescription medication storage and retrieval), other types of recipient authentication devices (see, e.g., **126**) can be provided at one or more of the user terminals **100**, including, for example, manual input keypads or keyboards, optical scanners (e.g., for reading bar codes), fingerprint readers, facial recognition imaging devices, retinal scanners, microphones for voice recognition, and the like.

[0184] In some embodiments, at least one of the user terminals **100** may be physically separated in an access-restricted location that is accessible, during normal operation of the system **1000**, by only authorized users, such as a licensed pharmacist, licensed pharmacy technician, or other authorized retail personnel. Such a restricted-access terminal can be either a user terminal **100**, which may be substantially identical to any of the other user terminals **100** of the system **1000**, or a rapid retrieval and storage (RRS) terminal **700**, without deviating from the scope of the subject matter disclosed herein. The RRS terminal **700** will be discussed further herein regarding FIGS. 17 and 18.

[0185] Each user terminal **100** comprises a vertically mobile elevator system **150** that transports a designated one of the plurality of storage bins **300** from one of a plurality of platters **210** arranged within the vault **200** to a door **110** in the exterior of the user terminal **100**, where the contents thereof are accessible to a user whose identity has been sufficiently authenticated by the system **1000** to authorize retrieval of the items (e.g., medications) stored in the designated storage bin **300**. The elevator system **150** has an elevator shaft **154** that is rigidly attached within the

interior of the user terminal **100** in a substantially static position, such that, other than translatory deflections and vibrations, the position of the elevator shaft **154** within the user terminal **100** is fixed. In the embodiment shown, the elevator shaft **154** is oriented substantially vertically (e.g., substantially co-aligned with the gravity vector) within a cavity formed through the height of the user terminal **100**. In some other embodiments, the shaft may be inclined with respect to the vertical direction. A trolley system **180** is attached to the elevator shaft **154**, such that the vertical position of the trolley system **180** changes as it moves along the length of the elevator shaft **154**. The elevator system **150** and the trolley system **180** are capable of accessing any of the platters **210** within the vault **200**.

[0186] A plurality of storage bins **300** are located on each platter **210**. An elevator system **150** is provided within each user terminal **100**. The elevator system is located adjacent to, and radially outward from, the platters **210** and each of the plurality of storage bins **300**, respectively, as the platter(s) **210** rotate about the frame **250**. The elevator system **150** comprises a trolley system **180** that is vertically movable within an interior of the user terminal **100** along an elevator shaft by an elevator motor **152**. In the example embodiment shown, the track **330** comprises a geared interface comprising a plurality of teeth **334** and the secondary bin pinion gear **194** comprises a driven rotatable pinion gear having a plurality of teeth that are complementarily shaped to the teeth **334** of the track **330**.

[0187] The trolley system **180** comprises a base **182** that is attached to the elevator shaft **154**. The base **182** is vertically mobile along the length of the elevator shaft **154**, but is otherwise positionally fixed to, and moves in a direction coaxial to the length of, the elevator shaft **154**. As such, the base does not move, relative to the elevator shaft **154** in the directions defined by the plane defined by, for example, one of the platters **210**, the base **260**, one of the platter support rings **268**, and the like, this plane being substantially orthogonally oriented relative to the length direction of the elevator shaft **154**. The trolley system **180** is moved along the length of the elevator shaft **154** by an elevator motor **152** which drives, based on commands from a controller of the system **1000**, the trolley system **180** therealong. An extension platform **190** is displaceably attached to the base **182** and is extendable, relative to the base **182**, in the radial direction of the platter **210** between a transport position, in which the extension **190** is entirely spaced radially apart from the platters **210** and/or storage bins **300** stored thereon, and a deployed position, in which the extension **190**

is moved towards the platter **210** in the radial direction of the platter **210** to either deposit a storage bin **300** onto a platter **210** or to engage with and retrieve a storage bin **300** from a platter **210**.

[0188] The trolley system **180** comprises, attached on opposite ends of the base **182** in the direction of movement of the extension platform **190**, stop plates **181A**, **181B** that limit a distance by which the extension platform **190** can move relative to the base **182**. A track **184** is connected on a surface of the base **182** adjacent the extension platform **190**. A drive motor **188** is rigidly connected to the extension platform **190** and has a drive pinion **186** having teeth that engage with (e.g., mesh with) complementary teeth formed in the track **184**. An alignment feature **197** is attached to, or at least associated with, the base **182** and extends in a direction substantially parallel to the direction in which the extension platform **190** moves, relative to the base between the retracted position and the deployed position, along the track **184**. In the embodiment shown, the alignment feature **197** has two rods that are arranged substantially in parallel to each other in the radial direction of the platters **210**. An extension base plate **193** comprises holes through which the alignment feature **197** passes to ensure that the extension platform **190** remains properly aligned (e.g., in the radial direction of the platters **210** and/or along the track **184**). As the drive pinion **186** is rotated by the drive motor **188**, the extension platform **190** moves in the direction of rotation of the drive pinion **186** relative to the track **184** between the stop plates **181A**, **181B**.

[0189] The extension platform **190** comprises a slot **192** through an upper surface thereof. In the embodiment shown, the slot **192** passes along substantially the entire length of the extension platform **190** (e.g., in the radial direction of the platters **210**), thereby essentially bifurcating the extension platform **190**. The outer stop plate **181B** comprises a tab that is aligned with the slot **192** to stop a movement of a storage bin **300** along the slot **192**. A bin motor **196** is connected to the extension platform **190** and extends through a side thereof to drive a rotary motion of the primary bin pinion gear **195**, which comprises a plurality of gear teeth that engage with (e.g., mesh with) gear teeth on a secondary bin pinion gear **194**, which is rotatably attached on a shaft between sides of the extension platform **190** in the form of an idler gear. The bin motor **196** drives a rotary movement of the primary bin pinion gear **195** in either a clockwise or counterclockwise direction, which causes a corresponding rotary motion of the secondary bin pinion gear **194**. In the embodiment shown, neither the primary

bin pinion gear **195** or the secondary bin pinion gear **194** are in contact with the track **184**. The secondary bin pinion gear is positioned underneath the slot **192** at a radially inward position on the extension platform. As such, when the extension platform **190** is moved to the extended position, the secondary bin pinion gear **194** is adjacent to, in contact with, and/or in a position to engage (e.g., mesh) with the teeth **334** of the track **330** of the storage bin **300** positioned adjacent (e.g., radially inwardly from) the extension platform **190**.

[0190] Once a transaction has been completed (e.g., when a designated period of time has elapsed, the user is no longer detected at the user terminal **100**, and/or the user terminates the session), the trolley system **180** then moves to a designated height corresponding to the platter **210** onto which the storage bin **300** is to be deposited. The extension **190**, as well as the storage bin **300** retained thereon, is then moved, relative to the base **182**, from the transport position to the deployed position and the pinion gear is rotated in a direction such that the storage bin **300** is driven off of the extension **190** and onto the designated platter **210**. The location (e.g., the location of the platter **210** and the bin slot **226** on the platter **210**) at which the storage bin **300** is deposited is recorded by the system **1000** (e.g., at a controller and/or in a database) for inventory control and tracking purposes. In some embodiments, all items that are stored within the vault **200** are scanned electronically by the system **1000** (e.g., via a barcode scanner or other suitable scanning device, for example, as described elsewhere herein) such that the location of each item can be precisely tracked within the vault **200** during operation of the system **1000**.

[0191] To retrieve a storage bin **300** from a designated position within the vault **200**, the extension platform **190** is moved into the deployed position, the drive motor **188** is energized to rotate the drive pinion **186** along the track and move the extension platform **190** into the deployed position, the bin motor **196** is energized to turn the primary bin pinion gear **195**, the secondary bin pinion gear **194** engages with the teeth **334** of the track **330** and spins in a corresponding direction to draw the storage bin **300** onto and/or over the extension platform **190**, such that the rib **332** passes along the length of the slot **192**, with the bottom **320** of the storage bin **300** being on an opposite side of the extension platform **190** from the track **330** of the storage bin **300**, thereby captively securing the storage bin **300** to the extension

platform **190**. While the secondary bin pinion gear **194** spins, the storage bin **300** is drawn over the extension platform **190**.

[0192] In some embodiments, the bin motor **196** is energized for a specified window of time during the transfer of the storage bin **300** onto the extension platform **190**. In some other embodiments, a position sensor is provided adjacent the tab of the outer stop plate **181B** to detect when the storage bin **300** is sufficiently engaged with the extension platform **190** and/or entirely disengaged from the platter **210** from which the storage bin **300** was removed, at which point a signal is transmitted (e.g., from a controller, based on a signal from the position sensor) to de-energize the bin motor **196**. In some other embodiments, the current (i) consumed by the bin motor **196** can be monitored (e.g., by a current sensor) and the bin motor **196** can be de-energized upon the occurrence of a current spike, corresponding to the storage bin **300** being driven in contact with the tab of the outer stop plate **181B** and being incapable of being driven further in that direction. In such embodiments, the output from the current sensor can be filtered and/or processed requiring the current measured to be above a threshold, whether instantaneously or for a predetermined amount of time.

[0193] When the secondary bin pinion gear **194** is engaged with and moving the storage bin **300** onto the extension platform **190**, the extension platform **190** can be moved along the base **182** to the transport position, such that the storage bin **300** on the extension platform **190** can be moved along the elevator shaft **154** to be accessible through the door **110** at the user terminal **100**. In some embodiments, the extension platform **190** does not move (e.g., remains stationary) while the storage bin **300** is being moved onto or off of the extension platform **190** (e.g., while the secondary bin pinion gear **194** is in motion and/or while the bin motor **196** is energized). In some embodiments, the extension platform **190** moves along the base **182** (e.g., to the transport position or the deployed position) at a same time as the storage bin **300** is drawn onto the extension platform **190** by the rotation of the secondary bin pinion gear **194**.

[0194] The process to deposit a storage bin **300** onto a platter **210** at a designated location is generally the reverse of that described hereinabove. Specifically, trolley system **180** moves along the elevator shaft **154** to a height at which a designated platter **210** is located within the vault **200**. When at the designated height, the drive motor **188** is energized to rotate the drive pinion **186**

along the track and move the extension platform **190** into the deployed position, the bin motor **196** is energized to turn the primary bin pinion gear **195**, the secondary bin pinion gear **194** engages with the teeth **334** of the track **330** and spins in a corresponding direction to eject (e.g., move in a radial inward direction of the platter **210**) the storage bin **300** onto and/or over the platter **210**, such that the rib **332** passes along the length of the bin slot **226** of the platter **210**, with the bottom **320** of the storage bin **300** being on an opposite side of the platter **210** from the track **330** of the storage bin **300**, thereby captively securing the storage bin **300** to the platter **210**. While the secondary bin pinion gear **194** spins, the storage bin **300** is ejected from the extension platform **190**. As the storage bin **300** is transferred radially into the platter **210**, the bump **336** of the storage bin **300** passes through the bin tabs **228** at the radially inner end of the bin slot **226**.

[0195] In some embodiments, the bin motor **196** is energized for a specified window of time during the transfer of the storage bin **300** onto the platter **210**. In some other embodiments, a position sensor is provided adjacent the bin tabs **228** of the platter **210** to detect when the storage bin **300** is sufficiently engaged with the platter **210** and/or entirely disengaged from the extension platform **190** from which the storage bin **300** was removed, at which point a signal is transmitted (e.g., from a controller, based on a signal from the position sensor) to de-energize the bin motor **196**. In some other embodiments, the current (i) consumed by the bin motor **196** can be monitored (e.g., by a current sensor) and the bin motor **196** can be de-energized upon the occurrence of a current spike, corresponding to the bump **336** of the storage bin **300** being driven in contact with the bin tabs **228** and/or the radially inner surface of the bin slot **226**, such that the storage bin **300** is incapable of being driven further in that direction. In such embodiments, the output from the current sensor can be filtered and/or processed requiring the current measured to be above a threshold, whether instantaneously or for a predetermined amount of time.

[0196] When the secondary bin pinion gear **194** is engaged with and moving the storage bin **300** off of the extension platform **190**, the extension platform **190** can be moved along the base **182** to the deployed position, such that the storage bin **300** on the extension platform **190** can be transferred onto the platter **210** while the extension platform **190** extends towards the platter **210**. In some embodiments, the extension platform **190** does not move (e.g., remains stationary) while the storage bin **300** is being moved onto or off of the extension platform **190** (e.g., while the

secondary bin pinion gear **194** is in motion and/or while the bin motor **196** is energized). In some embodiments, the extension platform **190** moves along the base **182** (e.g., to the transport position or the deployed position) at a same time as the storage bin **300** is ejected from the extension platform **190** by the rotation of the secondary bin pinion gear **194**.

[0197] In the embodiment shown in FIGS. 15-19, the user terminal **100** is configured such that the elevator system **150** and the display **122**, as well as any user interface devices **120** and other assorted controllers and computing equipment, are arranged laterally beside each other, thereby obviating the need for a further actuator mechanism to transfer the storage bin **300** from the elevator system **150** to the door **110**. In such embodiments, the storage bin **300** being accessed by the user at the user terminal **300** does not extend beyond the boundaries of the movement path of the trolley system **180** vertically along the elevator shaft **154** within the user terminal **100**. As such, the depth of the user terminal **100** and the overall footprint of the system **1000** can be further reduced.

[0198] In some embodiments, a shroud **158** may be provided over at least a portion of the vertically mobile components of the elevator system **150**, moving vertically along with the trolley system **180** as the trolley system **180** moves to vertically transport storage bins **300** between the platters **210** and the door **110** of the user terminal **100**. This shroud **158** may be of a sufficiently robust design and be dimensioned so as to prevent unauthorized access to items stored in other storage bins **300** adjacent to the door **110** that might otherwise be possible by, for example, a user manually reaching through the door **110** beyond the designated storage bin **300** to illicitly retrieve other items within manual reach of the user within the vault **200**. As such, the shroud **158** may have a size, allowing for manufacturing and installation tolerances, that is substantially the same size as the radially inner wall of the storage bins **300**. Thus, since the storage bin **300** is positively engaged with the guide feature(s) and the secondary bin pinion gear **194** of the extension platform **190** to prevent a positional disturbance of the storage bin **300**, such a shroud **158** would be configured to prevent unauthorized access to other storage bins **300** within the vault **200** by those who are retrieving another item from a designated storage bin **300**.

[0199] When a user is identified, the location of the storage bin associated with the user's order is determined and the trolley system **180** is moved along the

elevator shaft **154** to be at substantially the same height as the platter **210** on which the storage bin **300** containing the items designated for retrieval by the user at the user terminal **100** is located. Before, while, or after the trolley system **180** moves vertically along the elevator shaft **154** to attain the same height as the designated platter **210**, the platter **210** on which the designated storage bin **300** is located is rotated such that the designated storage bin **300** is substantially centered on, and aligned with, the extension platform **190** of the trolley system **180**. The extension platform **190** is then extended, relative to the base **182**, from the transport position to the deployed position. The designated storage bin **300** is then engaged (e.g., by the teeth **334** of the track **330**) by the secondary bin pinion gear **194** of the extension platform **190**. When actuated, the secondary bin pinion gear **194** of the extension platform **190** moves the designated storage bin **300** from the platter **210** onto the extension platform **190**, which can have guidance and alignment features (e.g., **197**) formed in or attached thereto. The extension platform **190** then moves from the deployed position to the transport position and the trolley system **180**, with the storage bin **300** positioned thereon and/or attached thereto, moves along the length of the elevator shaft **154** to be vertically aligned with the door **110** of the user terminal **100**. Once the storage bin **300** is aligned with the door **110**, the door is opened so that the contents within the designated storage bin **300** are accessible by the user at the user terminal **100** through the door **110**. Since the storage bin is positively retained (e.g., within slot **192** formed on an upper surface of the extension platform **190**, about which the track **330** of the storage bin **300** is engaged) on the extension platform **190** when the door **110** of the user terminal **100** is opened, the storage bin **300** is prevented from being removed through the door **110**. In some embodiments, the door **110** may be smaller in one or more dimensions than the outer dimensions of the storage bin **300**.

[0200] A method of dynamically aligning, in an automated manner, the trolley system **180** of one or more of (e.g., each of) the user terminals **100**, to the platter **210** in the horizontal direction (e.g., in the direction tangent to the outer perimeter of the platter **210** adjacent the elevator system **150**) and vertical directions using an imaging device **172** (e.g., a camera) is provided. There may be variation in the relative locations of the trolley system **180** and the platter **210** due to, for example, manufacturing tolerances. These tolerances are what the method is provided to provide a suitable positional correction. In some embodiments, there are marks on

the platter support ring **268**, platter **210**, and/or storage bin **300** that are of a precise dimension, such that they can be used for distance calibration and positional accuracy between the trolley system **180** and the storage bin **300** and/or the platter **210**. In some embodiments, the location of the imaging device **172** to the slot formed in the trolley system **180** and/or in the platter **210** is precise in the horizontal direction by approximately 0.5 millimeters (mm). In some embodiments, the location of the mounting bolt by which the platter support ring **268** is connected to the frame **250** (e.g., on the platter side) is precise in the horizontal direction by approximately 0.5 mm. In some embodiments, guide bumps may be formed on the platters **210** to ensure the position of the storage bin **300** relative to the platter **210** in the circumferential direction does not vary by more than approximately 0.5 mm when seated.

[0201] Positional encoders may be provided on the frame **250** and/or one or more of (e.g., all of) the platters **210** to determine a rotary position of the platter **210** within the system **1000**. While the positional encoders can be any substantially positionally fixed fiducial marking and can be detected by any suitable mechanism, including, for example, static images detected by one or more imaging devices, magnets detected by one or more magnetic sensors, and the like, in the example embodiment shown, a plurality of (e.g., two) alignment slots **236** are formed in a repeatable pattern (e.g., having one set of slots **236** for or associated with each storage bin **300**) about the outer perimeter of the platters **210** in a position that is visible to the imaging device **172** within or associated with, for example, the user terminal **100** and/or the RRS terminal **700**.

[0202] The method may be initiated at any storage bin location on any platter **210**. The platter **210** being positionally calibrated is stopped and the imaging device **172** captures an image having a known pixel density value, measured in pixels per inch (PPI), and calculates a number of pixels between the fiducials (e.g., alignment slots **236**) in the captured image. In some embodiments, the image number of pixels between the fiducials may be too large or too small, in which case the platter **210** is rotated by some distance corresponding to a ratio of the measured number of pixels and the correct number of pixels, and a second image is captured. This second image is analyzed to determine the number of pixels between the fiducials. If the correct number of pixels is detected, the calibration method terminates. If the incorrect number of pixels is detected, the process is repeated by iteratively rotating

the platter relative to the imaging device **172** until the correct number of pixels is measured, then the calibration method is terminated.

[0203] In some embodiments, the mounting bolt, which connects the platter support ring **268** to the bracket that connects the platter support ring **268** to the inner vertical strut **252**, in the image is identified and the horizontal distance (e.g., in the X-Y plane that is coplanar to the plane defined by the platter **210**) is calculated from a fixed reference in the image. These values are then entered into an offset table for the trolley system **180** at that location (e.g., including the user terminal **100** location, platter **210**, and storage bin **300**). The horizontal (e.g., X-Y) position of the storage bin **300** relative to the mounting bolt is also determined and/or calculated. These positional values are then added to the distance calculated from the fixed reference in the image to obtain the final offset values. In some embodiments, the angular and vertical distances from the imaging device will be referenced to the mounting bolt. In some embodiments, a vertical post on the trolley system **180** may be used for the fixed reference. It is anticipated that such a positional calibration method may be repeated for all of the storage bin locations within the vault **200** during manufacture of the system **1000**. This calibration method may be performed again after transport and installation of the system **1000** to a final installation location. In some embodiments, the calibration method may also be performed as part of a service call or a certification routine. If, during normal operation, a jam is detected at a particular storage bin location, in which the trolley system **180** cannot properly engage with and/or deposit a designated storage bin **300** on or to a platter **210**, this calibration method can be performed automatically, for example, after a fixed number of attempts to engage the storage bin **300** or to deposit the storage bin **300** onto the platter **210**.

[0204] In some embodiments, the system **1000** is able to determine, monitor, and/or account for backlash between geared interfaces (e.g., between the drive motor **242** and the inner radial gear **200**). Due to manufacturing tolerances during assembly, the amount of backlash between geared interfaces may differ between nominally identical systems **1000**. In order to detect and account for the backlash unique to each system, each platter **210** is rotated in a first circumferential direction and then stopped. Next, the platter **210** is rotated in a second circumferential direction, opposite the first circumferential direction. While the platter **210** is being monitored in the first and second directions, the torque of the drive motor **242** is

monitored and analyzed, with the time between the peaks in the monitored torque values being proportional to the amount of backlash at a particular geared interface. Because of manufacturing tolerances, it is necessary to perform this analysis at each of the geared interfaces within the system **100** (e.g., for each platter **210**). With the amount of backlash of each geared interface known, the particular backlash value for the interface between each drive motor **242** and each platter **210** can be programmed into the motion profile of each respective drive motor **242** to improve positional accuracy during normal operation (e.g., between instances of calibration).

[0205] As noted elsewhere herein, at least one of the user terminals **100** (e.g., including RRS terminal **700**), which can be referred to herein as a “controlled access terminal,” can be physically separated from the other user terminals **100**, for example, behind a counter, wall, or other physical partition or barrier. Because of the limited-access nature of such a controlled access terminal (e.g., a user terminal **100** or an RRS terminal **700**), it is contemplated that different authentication devices could be provided at the controlled access terminal than is utilized at the other user terminal(s) **100**. For example, a controlled access terminal may be equipped with a facial scanning device, such as may require prior mapping of a user’s facial contours that might otherwise be too time-consuming for typical users (e.g., customers, patients, caregivers, *etc.*) at the user terminal **100** to successfully register or enroll in, but which might also enable quicker and more secure identity authentication of an authorized user (e.g., pre-registered personnel) by the system **1000**. Other examples of such advanced authentication techniques can include, by way of example and not limitation, retinal scanning, voice recognition, gait analysis, and the like. The use of such rapid authentication biometric features would advantageously reduce the amount of time required by retail personnel, who have limited amounts of time to fulfill a given number of orders (e.g., for prescription medications), to operate the system **1000**.

[0206] Additionally, the system **1000** may be configured to remain logged in while an authorized user are located at the system **1000**, but to automatically logout when the system **1000** is no longer capable of authenticating the pharmacy employee via facial recognition. As such, it is envisioned that when the pharmacy employee looks away from the system **1000** for a prolonged period of time (e.g., more than 5, 10, 15, or 30 seconds) or physically moves away from the system **1000**, the system **1000** will logout the pharmacy employee automatically, so as to prevent unauthorized

access to the system **1000** using the credentials of such an authorized user by unauthorized users. Similarly, a presence sensor can be provided to automatically detect when an authorized user is present at the system **1000** and automatically logout of the session whenever the presence sensor can no longer detect the authorized user at the system **1000**. Such a presence sensor should have a refresh time of a short enough duration that it is not possible for an authorized user to move away from the system **1000** and a new user (e.g., an unauthorized user) to move into position at the controlled access terminal to continue the session illicitly. In one embodiment, the presence sensor could be a pressure-sensing mat adjacent the controlled access terminal, on which an authorized user must stand while using the system **1000**, such that the authorized user will be logged out when they are no longer physically standing in front of the system **1000**.

[0207] An example embodiment of an RRS terminal **700** is shown in FIG. 17. The RRS terminal **700** has an outer shell **702** that is mounted to an external surface of the vault **200** by hinges **704**, such that the RRS terminal **700** can pivot about the hinge **704** to reveal the interior of the vault **200** during assembly, maintenance, troubleshooting, and the like. During normal operation, the RRS terminal **700** is secured to the vault **200** and cannot be opened to access the interior of the vault **200**. A shelf **714** is provided on an external surface of the outer shell **702** of the RRS terminal **700**. The RRS terminal **700** comprises a display **722**, which in some embodiments is a touchscreen configured to accept user inputs via touching the surface of the display **722**. In some embodiments, physical buttons may be arranged around the display **722** to manipulate information and/or input data into the system **1000** at the RRS terminal **700**.

[0208] The RRS terminal **700** has, protruding from the external surface of the outer shell **702**, a user interface device **730**, which can be, for example, a wireless communication device (e.g., Bluetooth®, WiFi, RFID, etc.) that can receive an input from a mobile computing device (e.g., a smartphone or a tablet computer) of an authorized user present at the RRS terminal **700**. In some such embodiments, the wireless communication device is a near-field communication (NFC) receiver and/or transceiver that can authenticate an authorized user using, for example, a suitable card. The use of NFC technology is merely an example and any suitable near-field communication and/or detection protocol could be implemented. In some embodiments, the user interface device **700** can be one or more of manual input

keypads or keyboards, optical scanners (e.g., for reading bar codes), fingerprint readers, facial recognition imaging devices, retinal scanners, microphones for voice recognition, and the like. In some embodiments, it is advantageous for the user interface device **730** to comprise a plurality of user interface devices, at least one of which is a bar code reader, line scanner, QR code (e.g., a barcode having information encoded in two dimensions) scanner, or the like, such that items can be scanned in using a bar code reader, line scanner, or QR code scanner.

[0209] The RRS terminal **700** comprises a door **710** which is automatically closed unless an authorized user is authenticated at the RRS terminal and the session has not been terminated, ended, *etc.* The door **710** can be actuated in any suitable manner, but in the embodiment shown, the door **710** is actuated in the vertical direction by a linkage connected to the bottom edge of the door **710**, which may be opaque, translucent, transparent, and made of any suitably durable material. The outer shell **702** has an opening formed therein that the door **710** is configured to block when in the closed position. When the door **710** is in the closed position, the opening **712** is closed and the interior of the vault **200** cannot be accessed through the RRS terminal **700**. When the door **710** is in the open position, the opening is not obstructed, blocked, *etc.* and items within the vault **200** adjacent the RRS terminal **700** can be accessed through the opening. An inventory control device **770** is provided adjacent to (e.g., above) the door **710** in a position such that the movement of one or more items through the opening **712** when the door **710** is in the open position can be detected and the platter **210** can be rotatably advanced such that another vacant storage bin **300** on the platter **210** can be presented to the authorized user through the opening **712** for the authorized user to a further item (or items) into this storage bin **300**. In some embodiments, the item(s) are scanned at the user interface device(s) **120** (e.g., a barcode on the item(s) is scanned by a barcode scanner) prior to being loaded in the storage bin **300** through the opening **712**. As such, the storage bins **300** do not need to be removed from the RRS platter **210** in order for items to be loaded into a storage bin **300** through the opening **712** at the RRS terminal **700** when the door **710** is in the open position. In some embodiments, the item(s) will be scanned by the authorized user (e.g., at the user interface device(s) **730** and the item(s) will then be deposited directly into the storage bin **300** accessible through the opening **712**.

[0210] This process of scanning items, loading them into a storage bin **300**, and advancing the platter **210** is repeated until all of the items to be loaded by the authorized user at that time are loaded or until there are no vacant storage bins **300** on the platter **210** adjacent to the door **710** of the RRS terminal **700**. In order to increase throughput at the RRS terminal **700** by minimizing the number of components that must be moved or manipulated between when items can be loaded into subsequently presented storage bins **300**, the RRS terminal **700** does not have an elevator system (e.g., **150**). By eliminating the motion of the elevator system **150** and the trolley system **180**, only the RRS platter **210** and the door **710** are cycled (e.g., rotated and/or opened/closed, respectively) between when items are deposited into the vault **200**. In some embodiments, the cycle time will improve by about a factor of three or more. As such, items can only be loaded onto a single platter **210** within the vault **200** via the RRS terminal **700**. This single platter **210** is the platter **210** installed within the vault at a same, or substantially similar, height as the opening **712** such that the contents of storage bins **300** positioned thereon are accessible through the opening **712**. This particular platter can be referred to herein as the “RRS platter.”

[0211] In some embodiments, the capacity of the RRS platter **210** can be augmented artificially. The following examples can be combined in any combination. In some embodiments, the system **1000** may have a set of instructions that specify that all of the storage bins **300** on the RRS platter **210** are to be kept empty, with no storage bins **300** with items stored therein being deposited on the RRS platter **210**. As such, an authorized user at the RRS terminal will have an entire platter **210** of empty storage bins **300** into which items can be loaded sequentially within the vault **200**, thereby minimizing downtime and increasing throughput of items being loaded into the vault **200** at the RRS terminal **700**.

[0212] In some embodiments, the elevator systems **150** of the other user terminals **100** can be used to remove storage bins **300** from the RRS platter after they have been filled and to deposit these storage bins onto another platter **210** within the vault **200**, with the vacant slot on the RRS platter **210** being filled with an empty storage bin **300** from another platter **210**. This allows for the storage bins **300** of the RRS platter **210** to be removed and replaced with empty storage bins **300**, thereby artificially augmenting the capacity of storage bins **300** on the RRS platter. In some embodiments, it may be possible for this process to be repeated until all of the

storage bins **300** on every platter **210** in the vault **200** is filled. In some embodiments, it may not be possible to relocate storage bins **300** as rapidly as they are loaded at the RRS terminal **700**, in which case the RRS platter **210** will eventually reach capacity even if other storage bins **300** within the vault **200** are empty. In some embodiments, each the other user terminals **100** must be idle in order to relocate storage bins **300** from the RRS platter **210**. In some embodiments, the storage bins **300** are removed from the RRS platter **210** by a first user terminal **100** and empty storage bins are inserted on the RRS platter **210** by a second user terminal. It can be advantageous for not all of the platters **210** within the vault **200** to have storage bins **300** installed therein to allow for improved manipulation of storage bins **300** within the vault **200**, as a user terminal **100** cannot, in some embodiments, remove a storage bin **300** and simultaneously deposit a storage bin from a same bin slot **226** on a same platter **210**. In some embodiments where the RRS terminal becomes full, the system **1000** is configured to relocate, using the other user terminals **100** as described elsewhere herein, the occupied storage bins **300** from the RRS platter and, when a sufficient number of occupied storage bins **300** on the RRS platter **210** have been replaced with empty storage bins **300**, send a notification (e.g., a push notification or SMS to the authorized user's portable mobile device, emit a sound, send an email, *etc.*) to the authorized user that the RRS platter is sufficiently vacant to resume loading items within the vault **200**.

[0213] In some embodiments, the system **1000** is configured to alert a user at the RRS terminal **700** of any storage bins **300** whose contents have not been retrieved for longer than a prescribed time period, so that a notification can be generated and presented to an operator (e.g., a pharmacist or pharmacy technician at the RRS terminal **700**) so that the contents thereof can be removed and placed back into inventory or destroyed. In some such embodiments, the storage bins **300** having such expired or returned items designated to be removed from the vault **200** can be loaded onto the RRS platter **210** in a predetermined (e.g., sequential) pattern, such that the authorized user can remove the expired or returned items from these designated storage bins **300** through the opening **712** prior to loading further items into the storage bins **300** on the RRS platter **210** via the opening **712**. The inventory control device **770** is thus capable of detecting items both being removed and inserted into the vault **200** via the opening **712**. In some embodiments, expired or returned items can be removed from a storage bin **300** and a different item (e.g., for

a different customer) can be loaded into the same storage bin **300**, such that items are removed from the vault **200** and inducted into the vault **200** in an alternating pattern, therefore necessitating the RRS platter **210** to move only after an expired or returned item has been removed from a storage bin **300** and replaced with a new item for a different customer.

[0214] In some such embodiments, the system **1000** may be configured to charge customers a restocking or destruction fee for failure to retrieve the item(s) within a given delivery period of time. In some embodiments, the system **1000** can be configured to have one or more of the platters **210** physically separated within the vault **200** from the other platters **210** such that a temperature of the designated platter **210** can be maintained (e.g., refrigerated) without requiring temperature control of all of the platters **210** within the vault **200**. In some embodiments, an inventory control device **170** (e.g., an imaging device or a proximity device) is provided at each user terminal **100** to determine whether the item(s) have been removed from the storage bin **300** using image recognition software, such as by comparing the image recorded by the inventory control device **170** against an image of an empty storage bin **300**. In some embodiments, a space optimization algorithm can be implemented so that vacant storage bins **300** are stored consecutively on a same platter **210** at a same level at which the door **710** of the RRS terminal **700** is located. Furthermore, in some embodiments, when an elevator system **150** or even a single user terminal **100** is not being utilized, the system **1000** can be configured to move storage bins **300** to a more optimal location within the system according to the space optimization algorithm.

[0215] The power pod, generally designated **800**, is shown in FIGS. 19 and 20. The power pod **800** has an outer shell **802** that is mounted to an external surface of the vault **200** by hinges **804**, such that the power pod **800** can pivot about the hinge **804** to reveal the interior of the vault **200** during assembly, maintenance, troubleshooting, and the like. During normal operation, the power pod **800** is secured to the vault **200** and cannot be opened to access the interior of the vault **200**. One or more shelves (e.g., **450**) can be provided on an external surface of the outer shell **802** of the power pod **800** for the display of items that may be of interest to users at the system **1000**. The power pod comprises a controller **810**, which can be redundant (e.g., in a same or different physical housing within the power pod **800**) and allow continued operation of the system **1000** upon failure of a single controller

810. The power pod **800** further comprises an auxiliary power source **820**, in the form of an uninterruptible power supply (or source), which is able to provide power to the system **1000** in the event of a power outage. In some embodiments, the auxiliary power sources **820** are sized to allow continued operation of the system **1000** for a predetermined length of time. In some such embodiments, this predetermined length of time may be the amount of time necessary to provide an organized shutdown or to go into a standby mode, thereby obviating the need for recalibration of the system **1000** upon the power being returned to the system **1000**. The auxiliary power sources **820** can be any suitable number and can comprise any suitable power storage medium, including, for example, batteries and/or supercapacitors.

[0216] As can be seen in FIGS. 21 and 22, in which further example embodiments of the system **1000** are shown, in which the outer perimeter of the vault **200** has a generally arcuate and/or circular shape, at least portions of the outer circumference of the vault **200** can be provided with one or more shelves **450**, which can be used to support items placed thereon. Such shelves **450** may also be included on one or more of the cover panels **201**, having any suitable profile and length of extension away from the outer surface of the cover panel **201** to which such shelves **450** may be attached. Such shelves **450** may also be included on one or more power pod **800**, having any suitable profile and length of extension away from the outer surface of the power pod **800** to which such shelves **450** may be attached. In some embodiments, such as where the system **1000** is installed within a retail space, such shelves **450** can be used to display products that the retailer may wish to give added visibility in the vicinity of the store near the system **1000**. In some embodiments, advertising can be positioned above, on, and/or adjacent to the shelves **450**. In Some embodiments, the shelves **450** can be replaced such that some, all, or substantially all of an exterior of a cover panel **210** has an advertisement located thereon.

[0217] In some embodiments, targeted messages can be presented by the system **1000**, as disclosed in co-pending U.S. Pat. App. Ser. No. 15/850,657, filed December 21, 2017, and International Pat. App. No. PCT/US2017/067874, filed December 21, 2017, the disclosures of which are incorporated herein in their entirety.

[0218] For example, where the system **1000** is being utilized for the storage and retrieval of prescription medications, other over-the-counter (OTC) medications may

be arranged on or about one or more of the shelves. Similarly, during seasonal periods where cold and flu viral infections are prevalent, an array of palliative care items (e.g., facial tissue, nasal spray, humidifiers, and the like) for such infections may be displayed on such shelves **450**. These shelves **450** can extend entirely around the vault **450** (e.g., interlocking with shelves **450** of an adjacent cover panel **201** to form a continuous shelving surface) between adjacent user terminals **100**, as shown in FIGS. 21 and 22. In some embodiments, the shelves **450** extend over only a partial circumferential distance between adjacent user terminals **100**. In some embodiments, in which only a single user terminal **100** is connected to the vault **200**, such shelves **450** can extend circumferentially around a portion of the outer wall of the vault **200**, or around an entire perimeter of the vault **200** from one side of the single user terminal **100** to another side of the same user terminal **100**.

[0219] FIGS. 24 and 25 show an example embodiment of a buffer input device, generally designated **900**, for rapidly depositing items for storage and retrieval in the vault **200** (e.g., via user terminal **100** or the RRS terminal **700**) of any of the embodiments of the systems **1000** disclosed herein, without the user depositing such items having to wait for each storage bin **300** to be retrieved from a position within the vault **200**, made accessible at the user terminal (e.g., the user terminal **100** or the RRS terminal **700**), deposited in the vault **200** at a designated location (e.g., one of the platters **210**), and then another storage bin **300** be retrieved, for a next deposit of an item within the vault **200**. According to this embodiment, a plurality of intermediate storage areas **912** are provided within the buffer system **900**, each of the plurality of intermediate storage areas **912** being sequentially accessible by the user at the controlled access terminal (e.g., RRS terminal **700**) for depositing one or more items therein before an adjacent intermediate storage area **912** is made accessible. In this embodiment, the buffer system **900** has a substantially solid housing **902** (which can be entirely translucent, opaque, or a combination thereof) enclosing the buffer system **900**.

[0220] The housing **902** has an opening, generally designated **930**, formed through a surface thereof. A single opening **930** in the housing **902** is shown, yet a plurality of openings **930** can be provided. While other embodiments will be understood based on the scope of the disclosure herein, in the example embodiment shown the buffer system **900** comprises a belt **916** rotatably connected between and around two rotatable spindles **918**. The housing **902** has a plurality of paddles **926**

attached to an outer surface thereof, the space between the paddles **926** defining the dimensions of the intermediate storage areas **912**, and the inner surface of the belt **916** having a surface configured to minimize slippage with respect to the two rotatable spindles **918**. In some embodiments, each of the inner surface of the belt **916** and the outer surface of the spindles **918** can have a friction-enhancing coating (e.g., rubber, silicone, etc.). In some other embodiments, the belt **916** and the spindles **918** can engage with each other with a geared interface, with each of the belt **916** and the spindles **918** having a plurality of teeth that engage (e.g., mesh) with each other to prevent slippage between the belt **916** and either of the spindles **918** as the belt **916** is rotatably driven about the spindles **918**. In some embodiments, the belt **916** has a width that is wide enough such that a gap between the walls of the housing **902** and the belt **916** will not cause malfunctions or damage to the items being transported on the belt **916** within the housing **902**. The housing **902** of the buffer system **900** may have a same or a different external contour (e.g., planar, curved, arcuate, etc.) from the outer contour of the vault **200** and/or a user terminal **100**.

[0221] One or more scanners **924** (e.g., optical, RFID, NFC, Bluetooth®, etc.) can be mounted (e.g., fixedly or removably) to the housing **902** at a position adjacent to the opening **930** formed in the housing **902**, through which items are deposited to enter into one of the intermediate storage areas **912** of the buffer system **900** disclosed herein. In some embodiments, a sensor **932** can be provided to detect when an item passes through the opening **930**, such that the belt **916** can be advanced about the spindles **918** by a predetermined number (e.g., one) of positions such that the next intermediate storage area **912** is then located underneath the opening **930** in the housing **902**. In some embodiments, the sensor **932** is provided adjacent to, or within, the opening **930**. In some embodiments, the sensor **932** is a line scanner, laser scanner, or the like that can detect when the signal transmitted therefrom is interrupted by an item passing through the opening **930**. In some embodiments, the sensor **932** is integrated into a scanner **924**. In some embodiments, the functionality of the sensor **932** can be integrated within the one or more scanners **924** to reduce an overall number of devices of the buffer system **900**. In some embodiments, an actuatable flap **934** may be provided to close off (e.g., cover) the opening **930** in the housing **902**, such that items cannot accidentally be placed into an intermediate storage area **912**. In some embodiments, the flap **934**

can be locked unless/until it is actuated (e.g., after unlocking) once an item has been detected and successfully scanned by the scanner **924**. As such, if the system **1000** is unable to detect the item, or any pertinent information about the item (e.g., recipient name and/or address information, payment status, authentication/verification of the item, historical tracking data for the item, etc.), the flap **934** may remain in the closed position so that an insufficiently identified item cannot pass through the opening **930** into the housing **902** of the buffer system **900**.

[0222] The belt **916** may be rotatable in either direction, but in the embodiment shown the belt **916** is rotatable about the spindles **918** in a counterclockwise direction, as shown in FIGS. 24 and 25. The system **1000** and the buffer system **900** are interconnected for communication of items and/or information therebetween. As such, since the system **1000** knows when a storage bin **300** is properly located within the designated receiving position for the buffer system **900**, the system **1000** may request an item in a next of the intermediate storage areas **912** be deposited into the awaiting storage bin **300**. Upon receipt of this signal, the belt **916** is rotated to advance by a distance equivalent to a length of an intermediate storage area **912** (e.g., a distance between adjacent paddles **926** on the belt **916**). During this movement of the belt **916**, a lead paddle **926** of the next intermediate storage area **912** moves such that the item held therein can be transferred (e.g., by gravity) into the awaiting storage bin **300** and an empty intermediate storage area **912** becomes aligned with the opening **930** in the housing **902**.

[0223] Any number of paddles **926** may be provided along the belt **916**, which can have any suitable length to create any desired number of effective intermediate storage areas **912**. As such, because the buffer system **900** can advantageously have items detected, registered, and deposited therein at a much more rapid rate than is possible for a retrieval/depositing of a single storage bin **300** within the vault **200** (e.g., at a user terminal **100**), a user at a controlled access terminal equipped with such a buffer system **900** can rapidly input a number of items to fill all of the intermediate storage areas **912** and the buffer system **900** can input the items into storage bins **300** for the vault **200** at the user terminal **100** without requiring the user to wait at the system **1000**, as would otherwise be necessary without the buffer system **900**, such that the user only needs to return to induct further items once all of, or at least a majority of, the items within the buffer system **900** have been deposited in the vault **200** to deposit a further plurality of items within the buffer

system **900**, thereby increasing operational efficiency of users tasked with stocking the system **1000**.

[0224] In some embodiments, the buffer system **900** may be configured to reverse the rotation of the belt **916**; this can be advantageous where a user returns to the buffer system **900** but a small number of items have not yet been processed (e.g., transferred into the vault **200**). As such, rather than waiting or leaving/returning after only a short time, the user may reverse (e.g., manually or automatically) the rotation of the belt **916** such that a vacant intermediate storage area **912** adjacent to the last occupied intermediate storage area **912** is located underneath the opening **930**. At this point, the user can continue depositing items in each of the intermediate storage areas **912** until each of the intermediate storage areas **912** between the depositing position (e.g., adjacent to the storage bin **300** at the user terminal **100**) and the input position (e.g., underneath the opening **930**) are occupied, thereby freeing the user to resume other activities whilst the items are automatically transferred sequentially into adjacent storage bins **300** for storage within the vault **200**. This prevents the user from having to wait, or otherwise operate at a reduced rate, while items already in the queue are processed according to the operational speed of the system **1000** until all of the previously-deposited items in the first batch of items are stored within the vault **200**.

[0225] In some other embodiments, the buffer system **900** may be attached to the vault **200** and/or integrated within the system **1000** without being attached to an otherwise user-accessible user terminal **100**. As such, the buffer system **900** may be configured as a separate and discrete input into the vault **200** that is separate from any other user terminals **100** or RRS terminal(s) **700**, so that all user terminals **100** and RRS terminals **700** can remain operable for item retrieval (and/or depositing, as appropriate based on the permissions of a given user) while items are deposited within the vault **200** by the buffer system **900**. In some such embodiments, the storage bin **300** transported for filling at the buffer system **900** may not be directly accessible by a user present at the buffer system **900**. Similarly, there may be different, reduced, or omitted user inputs and displays at the buffer system **900** from those described relative to the user terminals **100** elsewhere herein.

[0226] In some embodiments, a user display (e.g., a light, a plurality of lights, a display screen, etc.) can be provided on the buffer system **900** to indicate the status of the buffer system **900** (e.g., the number of items in queue, an error status, an

estimated time of completion, etc.). In some embodiments, a user input device (e.g., a button, a keyboard, etc.) may be provided for use with the buffer system **900** (e.g., to advance the belt **916** manually, to stop/start operation of the buffer system **900**, etc.). In some embodiments, the user display and user input device may be incorporated into a single device, such as, for example, a control panel, a touchscreen, a tablet computer, and the like. In some embodiments, an auditory device (e.g., a speaker) can be provided on the buffer system **900**, on the system **1000**, or even remotely connected (e.g., wirelessly, via Bluetooth®) to alert a user that the buffer system **900** has completed processing all of the items and the queue (and all of the intermediate storage areas **912**) is empty and ready to accept new items for transfer and storage within the vault **200**. In some embodiments, the buffer system **900** may have a controller to achieve the functions described hereinabove. In some embodiments, the controller of the buffer system **900** is the same as, or integrated with, the controller of the system **1000**. The controller may be connected to a wireless transceiver capable of wirelessly communication with a personal electronic device (PED, e.g., a smartphone, tablet computer, or other wearable device, including a smart watch) associated with a user authorized to access the buffer system **900**. When the buffer system **900** is ready to accept new items, the controller may transmit a notification to the PED of the user to alert the user as to the status of the buffer system **900**. In some embodiments, such alerts can also include error messages, messages indicating an estimated and/or updated estimated time of completion, and the like. Such alerts may also be disabled by a user based on a user's individual preferences.

[0227] In some embodiments, the housing **902** may have more than one opening **930**, each of which can be retractable (e.g., automatically or manually), through which a plurality of intermediate storage areas **912** may be accessible without requiring a movement of the intermediate storage areas **912** within the housing **902**. In some embodiments, such a buffer system **900** may be provided in a position such that, rather than items being held within the intermediate storage areas **912** being deposited into a storage bin **300** within the user terminal **100** of the RRS terminal **700**, items deposited into the intermediate storage areas **912** may be deposited into a common receptacle (e.g., a container large enough that it would not require frequent emptying, depending on the size and volume of items being deposited therein). This would be very advantageous in, for example, a pharmacy installation

where users may have expired or otherwise unneeded medications, prescribed or over-the-counter (OTC), which the customer needs to dispose of safely. In such embodiments, a sensor **932** may be used to detect when one or more items are deposited through the opening **930** in the housing **902** without the need for any further verification of the contents of the items being deposited or the persons making such deposits. In some such embodiments, the housing **902** may have a retractable flap **934** that is either automatically or manually opened.

[0228] In some other embodiments, the buffer system **900** can have a series of containers that are connected together (e.g., by a belt **916**) and are configured to transport items deposited therein to a storage bin **300** to be stored in the vault **200**. In some such embodiments, the containers can be configured to tip over in a controlled manner such that the contents thereof would be emptied into an awaiting storage bin **300**. Similarly, the containers could have a releasable bottom panel that would allow, when the container is aligned with the storage bin **300**, the items stored in the container to drop vertically out of the container and into the awaiting storage bin **300**.

[0229] In some embodiments, the buffer system **900** may be spaced apart from the location of the storage bin **300**, such that a further conveyor (e.g., a slide or a secondary driven belt) would be used to connect the output of the buffer system **900** with the awaiting storage bin **300**.

[0230] In some embodiments, the input (e.g., at the opening **930**) of the buffer system **900** can be operably connected to an automated item-dispensing system, for example an automated pharmaceutical prescription-fulfilling system that is configured to fill orders for a predetermined number of commonly-prescribed medications and transport these (e.g., on a conveyor belt, a slide, etc.) to the buffer system **900** for fully automated loading of the items within the vault **200**. In some other embodiments, such an automated item-dispensing system can be connected to one of the mounting surfaces of the vault **200** so as to deposit the automatically generated items directly into an empty storage bin **300** within the vault **200**.

[0231] In some embodiments, due to the configuration of having multiple platters **210** within the vault **200**, it is possible for the system **1000** to retrieve a first storage bin **300** associated with a first recipient at a first user terminal **100** simultaneously while also retrieving a second storage bin **300** associated with a second recipient at a second user terminal **100**; in some such embodiments it may not be possible for

the system **1000** to always make such simultaneous retrievals of storage bins **300** when the storage bins **300** designated for retrieval at the different user terminals **100** are stored on a same platter **210**. However, in such embodiments, the system **1000** may rotate the platter **210** in question so the first storage bin **300** is aligned with the elevator platform of the first user terminal **100**, transfer the first storage bin **300** onto the elevator platform of the first user terminal **100**, then rotate the platter **210** in question such that the second storage bin **300** is aligned with the elevator platform of the second user terminal **100**, transfer the second storage bin **300** onto the elevator platform of the second user terminal **100**, then rotate the platter **210** such that the nearest vacant slot thereon is aligned with the elevator platform of whichever user terminal **100** signals a completed transaction first; at this point, the system **1000** could return to normal operation. In some such embodiments, the controlled access terminal (e.g., a designated one of the user terminals **100** and/or an RRS terminal **700**) may be operated simultaneously while one or more (e.g., all) of the other user terminals **100** are in use by persons authorized to retrieve items from one or more of the storage bins **300** stored within the vault **200**. In such instances, because the system **1000** knows which of the platters **210** are currently being accessed as part of the retrieval process at the one or more user terminals **100**, the automated item-dispensing system may assign the items being inducted at the RRS terminal **700** to a storage bin **300** located on a platter **210** that is not currently being utilized. As noted hereinabove, each platter **210** may be accessed for induction or retrieval of items at each user terminal **100** substantially simultaneously, with a delay in response times of the system **1000** ranging from the imperceptibly short to a period of time required to rotate the platter **210** sufficiently so that an empty location on the platter **210** is aligned with a trolley system **180** positioned to place or remove a storage bin **300** onto/from the platter **210**.

[0232] In some embodiments, the displays **122** at one or more (e.g., each) of the user terminals **100** may be configured to show targeted messages that are customized based on a user profile and/or information about the merchandise being retrieved from the system **1000** by the user and/or caregiver. In some embodiments, one or more of the user terminals **100** may be ADA (American's with Disabilities Act) compliant, such that the system can be used by all, regardless of any physical disabilities. Because the terminals and systems herein can utilize one or more user interface, there can be direct marketing to a customer, such as targeted marketing or

messaging that can, for example, be specific or particular to a customer based upon material being processed or picked up. For example, there could be an advertisement for what is on the shelf next to the portal, or even more direct advertisement, reward points, etc. that are directly tied to the specific customer account information.

[0233] FIG. 26 shows an example embodiment of a system **1000** with increased storage capacity.

[0234] Examples of systems **1000** having one or more such restricted-access terminals are shown in the embodiments of FIGS. 21-23, each of which show how the RRS terminal **700** is physically segregated from access by unauthorized persons by one or more physical barriers, with the physical barrier(s) being arranged such that the vault **200** itself can be used as a portion of the physical barrier.

[0235] In FIG. 21, the physical barrier is a plurality of wall segments **410** that extend from the sides of the vault **200**; while only wall segments **410** are shown herein, these wall segments **410** can be of any length, can be part of, and/or coincident with, existing physical barriers (e.g., pre-existing walls) at a location where the system **1000** is installed, and, in some instances, can extend from the vault **200** at any angle, including, for example, from between and including 90° and 180°.

[0236] FIG. 22 shows an embodiment where the physical barrier comprises a retail sales installation, such as a retail pharmacy counter where prescriptions can be dropped off for fulfillment, fulfilled prescription medications can be picked up, and pharmacist consultations may be carried out. In the embodiment shown, the system **1000** is physically integrated within the retail pharmacy counter, with the added advantage that the system **1000** serves as a further barrier to the pharmacist consultation area for enhanced privacy to those seeking pharmacist consultations.

[0237] In the embodiment shown in FIG. 33, a drive-through embodiment is shown, where the system **1000** has only two user terminals **100**, which are physically separated from each other by an external wall **430** of a building, in which one of the user terminals **100** is installed so that patients or caregivers are able to retrieve their medications while remaining in a vehicle; the RRS terminal **700** is thus located inside the building and the vault **200** is installed at a position adjacent to the physical barrier.

[0238] In any of the embodiments in which the vault **200** is integrated in, or otherwise attached to, a physical barrier, the outer shape of the vault **200** may be

modified to be any suitable shape. Each of the embodiments shown herein can be configured for outdoor installations, including having the ability to maintain a designated internal temperature within the vault **200** for embodiments where temperature-sensitive items are stored therein.

[0239] When the system **1000** is being loaded (e.g., at the RRS terminal **700**), the system **1000** may be configured to determine and assign, based on the dimensions of the item(s) to be stored therein, an appropriately sized storage bin **300**.

[0240] The system **1000** is further configured, in some embodiments, with one or more internal presence detectors that detect whether a storage bin **300** is occupied or vacant. These can be affixed to the underside of one or more of the platters **210** and/or on the upper surface of the vault **200**, such that the contents of the storage bins **300** can be detected passively as the platters **210** rotate about the frame **250**. In some other embodiments, the platters **210** may have individual force sensors configured to determine a weight of each of the storage bins **300** and determine occupancy thereof by comparing the measured weight against a reference empty weight of each storage bin **300**.

[0241] In some embodiments, the system **1000** is configured to, either by leaving at least one position on one or more platters **100** vacant or by utilizing the elevator systems **150** of at least two user terminals **100**, “defragment” the storage bins **300** during times that the system **1000** is idle, or at least two user terminals **100** are idle. This “defragmentation” refers to re-organizing the contents of the storage bins **300** within the vault **200**, including moving storage bins **300** such that occupied storage bins **300** are grouped together (e.g., on a same platter **210**). In some embodiments, occupied storage bins **300** could be moved to be adjacent to the user terminals **100**, while vacant storage bins **300** could be moved to be closer to the RRS terminal **700**. In some other embodiments, storage bins **300** could be reorganized such that all storage bins **300** on a designated platter **210** are vacant to minimize the likelihood of storage bins **300** on a same platter **210** needing to be accessed by more than one user terminal **100**. In some other embodiments, more recently occupied storage bins **300** could be located at a position closer to one of the user terminals **100** (e.g., on a platter **210** that is vertically closer to the user terminal **100**), while those storage bins **300** that have been occupied for a longer period of time being stored at a more remote location within the vault **200**, as these may be less likely to be accessed.

[0242] In some embodiments, the system **1000** is able to retrieve supply chain pedigree data (e.g., tracking information of the items being delivered to the user) throughout the supply chain, including, for example, from the point of origin of the merchandise (e.g., the original manufacturer). It is understood that the Electronic Product Code Information Services (EPCIS) portion of the Drug Supply Chain Security Act (DSCSA) is to be implemented by 2023. Once implemented, all retail pharmacies will comply with the standards set forth therein. In order for a pharmacy to accept a medication for distribution, the pharmacy must be able to verify the integrity of the supply chain for each medication, tracing the provenance of the medication all the way to the original manufacturer. As such, this data provides consumers and/or retailers (e.g., pharmacies) a verified supply chain pedigree at the time of deposit or retrieval of the merchandise into/from the vault **200**, depending on where this verification process is requested in the process or workflow. Additionally, this verification data can be interpreted from its core base machine language (e.g., an XML language) and converted to a graphical timeline that can be understood by a layperson.

[0243] In some embodiments, the system **1000** is configured to determine and, in some such embodiments, display a certification regarding the authenticity and tracking of each of the items stored within the vault **200**. In instances where the vault **200** is used for the storage of prescription medications, this information can include all pertinent supply chain data, including all steps between the medication leaving the manufacturer and its arrival (and detection/scanning) at the system **1000**. In some embodiments, this certified authentication information can be displayed to a user at the display **122** at a user terminal **100** upon and/or during retrieval of the item from within the vault **200**. In some such embodiments, the items themselves may be uniquely serialized to enable this end-to-end supply chain tracking. The certified authentication information can be accessed remotely by the system **1000** (e.g., through the Internet). The systems and methods herein can therefore access and use any data, such as data from the serialization process for medications or other items, and particularly including data such as the EPCIS data. These features can be automated with the systems and methods such as disclosed herein and are advantageous for processing, storage and dispensing or distribution of items, such as medications particularly.

[0244] In some embodiments, the system **1000** is configured for communication and/or payment between the retailer and the customer prior to the arrival of the customer at the store and at the user terminal **100** of the system **1000**. This feature allows for secure (e.g., encrypted, as necessary) communication to the end consumer when the item(s) ordered is ready for retrieval at one (e.g., any) of the user terminals **100**. This feature further allows for payment arrangements to be made between the retailer and the user, including allowing users to pre-pay or, in the instance of a retail pharmacy installation, input insurance information or allow for a request to be made to discuss the prescription with a licensed pharmacist.

[0245] The system **1000** is configured at the user terminal(s) **100** to accept payment (e.g., by one of the user interface devices **120**, which can comprise a card swipe terminal) for the item(s) stored within the vault **200**, preferably prior to the storage bin **300** being presented to the user at the user terminal **100** for retrieval of the item(s) stored therein. Payment can be made with either a pre-paid account, credit or debit card, cash, cryptocurrency, and the like. Any insurance contributions may be pre-arranged and will be automatically factored into the transaction. The user terminal **100** comprises a secured door **110**, which controls access to the storage bin **300** on the trolley system **180**. This secured door **110** remains closed and/or locked until identification, payment, and/or any security checks have been verified by the user, either remotely on a user device or using one or more of the user interface devices **120** and/or authentication devices **126**. If there is a discrepancy, or a reason the customer does not want the item(s), the transaction can be cancelled, and the item(s) returned to the vault **200**. In such instances, the system **1000** is configured to send a notification of this refusal event automatically to a retail employee (e.g., a pharmacist) so that the items can be removed from the vault **200** promptly.

[0246] In some embodiments, the system **1000** can be configured to accept returned items as well, in effect reversing the operation of the user terminals **100**, wherein the item(s) being returned will be deposited in one or more storage bins **300** at one of the generally accessible user terminals **100**, with the returned items being removable only by authorized users (e.g., authorized retail employees) at, for example, a restricted-access user terminal **100**, or RRS terminal **700**. In some embodiments, such returned items can be automatically deposited into a secure receptacle by the system **1000**, so that storage bins **300** within the vault **200** are not

occupied with defective/returned items instead of those to be delivered to the recipients.

[0247] In some embodiments, upon the items being deposited within the vault **200** and/or in the buffer system **900**, a notification may be sent (e.g., automatically) to an intended recipient for the items being deposited within the vault **200**. This notification can be sent to the intended recipient and/or his/her authorized caregiver via any suitable communication type, including, for example, e-mail, short messaging service (SMS) text messages, a dedicated mobile application for a smartphone, tablet computer, other computer, or wearable device, and the like. This notification can allow for payment arrangements to be made prior to retrieval, for a request to be made for a consultation with a pharmacist, for insurance information to be transmitted, and the like. In some instances, this notification can allow for a remote audio/visual consultation with a licensed pharmacist.

[0248] In embodiments where prescription medications are being stored/retrieved from the vault **200**, the types and number of identity authentication measures may change dynamically based on the medication classification of the medication being retrieved. For example, a class 2 medication may require more stringent identity standards than would be required for a class 3 medication. Additionally, the system **1000** may be configured to report, as necessary, to any governmental databases when and how much of a controlled substance (e.g., pseudoephedrine) is purchased and by whom (e.g., by scanning a valid government-issued identification card, such as a driver's license).

[0249] While the embodiments shown herein are directed towards the storage and retrieval of small items that require secure access control measures for their retrieval, such as prescription medications. In some embodiments, the system **1000** disclosed herein could be used for storage and retrieval of virtually any suitably-sized items, including, for example, low volume retail orders placed on a merchant's Internet retail website for later retrieval by a customer. Furthermore, the system **1000** shown could be reconfigured to use larger storage bins **300** for the storage and retrieval of the items stored therein, either with or without changing a shape and/or space between the internal platters **210** arranged within the vault **200**.

[0250] In some embodiments disclosed herein, the system **1000** is capable of being remotely accessed and one or more diagnostic programs may be executed during manufacturing, installation, and service of the system **1000**.

[0251] In some embodiments, it may be permissible for items for multiple people associated with each other (e.g., as a family) during pre-registration to be stored in a same storage bin **300** are retrieved by a single user who is authorized to pick up items for each such person.

[0252] In the example embodiment shown in FIG. 26, the system **1000** comprises a vault **200**, about which are arranged, mounted to, and/or connected to a plurality of user terminals **100**, a power pod **800**, a storage locker **1100**, a locker pod **1200**, and a high capacity pod **1300**.

[0253] The high capacity pod **1300** comprises a “satellite” storage area that is attached to the vault **200** to increase its capacity or, in some embodiments, to allow for variations in size of the storage bins **300** located therein or the temperature at which the items stored therein are stored. In some embodiments, the storage bins within the high capacity pod **1300** are the same as the storage bins **300** used in the vault **200**, allowing for the storage bins **300** to be transferred between the vault **200** and the high capacity pod **1300** relatively easily. In other embodiments, the storage bins **300** or storage areas within the high capacity storage pod **1300** can be of a different shape and/or size from the storage bins **300** in the vault **200**, allowing for more items of different sizes and shapes to be stored within the system **1000**. The high capacity pod **1300** attaches to the frame **250** of the vault **200** in a manner substantially similar to the attachment of the user terminal **100**, the RRS terminal **700**, and the power pod **800** to the vault **200**. Items stored within the high capacity pod **1300** are transferred into the vault **200** and are accessed through one of the user terminals **100** and the RRS terminals **700**. In some embodiments, items within the high capacity pod **1300** can be removed directly from the high capacity pod **1300**.

[0254] The locker pod **1200** is a storage device that can be configured to handle variably sized items therein. Such items can include, for example, items that will not fit or otherwise cannot be securely stored in the storage bins **300**. In some embodiments, all or a portion of the locker pod **1200** can be refrigerated or heated, so as to have a different temperature from the ambient temperature external to the vault **200** and/or within the vault **200** itself. The locker pod **1200** comprises a plurality of cubbies or enclosures of one or more sizes that are loaded and unloaded from an external side of the vault **200**, via individually accessible locker doors. As such, items within the locker pod **1200** would be accessible to users external to the vault **200**.

while other items can be removed from the vault **200** via the user terminal(s) **100** simultaneously.

[0255] The storage locker **1100** is connected to the vault **200** at an external surface thereof. The storage locker **1100** is an automated storage and retrieval system (ASRS) and, instead of individual external doors for each of the lockers contained therein, the storage locker **1100** comprises central access points of portal doors for induction and retrieval of items therein. There may be one or a plurality of portal doors through which items can be inducted and/or retrieved. Items stored in the storage locker could, but need not in all embodiments, be routed through the vault **200** to be accessed by a user. As such, items within the storage locker **1100** would be accessible to users external to the vault **200** while other items can be removed from the vault **200** via the user terminal(s) **100** simultaneously. In some embodiments, all or a portion of the storage locker **1100** can be refrigerated or heated, so as to have a different temperature from the ambient temperature external to the vault **200** and/or within the vault **200** itself.

[0256] In the example embodiment shown in FIG. 31, the system comprises an access port on the vault to which a secure cart **1400** can be removably coupled. The secure cart **1400** allows items to be securely transported from an access control area (e.g., a pharmacy) to be loaded within the vault **200**. In some embodiments, an identification number is assigned to the secure cart **1400** to establish the child-parent relationship between the items within the secure cart **1400** and the secure cart **1400** itself. This identification number is unique and will be recognized by the system **1000** and all information associated with the contents of the secure cart **1400** will be transferred to the system **1000** such that, if any of the items indicated as being present in the secure cart **1400** is missing, the appropriate security measures can be taken. In some embodiments, the items within the secure cart **1400** will be scanned both when being loaded into the secure cart **1400** and scanned again upon being transferred into the vault **200**. This same process can be used when expired or returned items are to be removed from the vault **200** and loaded into the secure cart **1400**, such that the items are scanned when removed from the vault **200** and scanned again when loaded into the secure cart **1400**.

[0257] While the subject matter has been described herein with reference to specific aspects, features, and illustrative embodiments, it will be appreciated that the utility of the subject matter is not thus limited, but rather extends to and

encompasses numerous other variations, modifications and alternative embodiments, as will suggest themselves to those of ordinary skill in the field of the present subject matter, based on the disclosure herein.

[0258] Various combinations and sub-combinations of the structures and features described herein are contemplated and will be apparent to a skilled person having knowledge of this disclosure. Any of the various features and elements as disclosed herein can be combined with one or more other disclosed features and elements unless indicated to the contrary herein. Correspondingly, the subject matter as hereinafter claimed is intended to be broadly construed and interpreted, as including all such variations, modifications and alternative embodiments, within its scope and including equivalents of the claims.

[0259] The methods and systems disclosed herein can be combined in any combination and/or sub-combination, adding elements from other systems and/or sub-systems or steps from other methods and/or sub-methods, as the case may be, and/or omitting elements from other systems and/or sub-systems or steps from other methods and/or sub-methods without limitation. Nothing disclosed herein shall be interpreted as limiting in any way the combinations in which the features, structures, steps, *etc.* may be organized, described, and/or claimed in this or any related applications.

CLAIMS

1. A secure storage and retrieval system comprising:
a vault comprising:
a frame;
one or more platters mounted about the frame to be independently rotatable about the frame;
a plurality of storage bins arranged radially about each of the one or more platters; and
a plurality of mounting surfaces arranged about a perimeter of the vault; and
at least one user terminal connected to the vault at one of the mounting surfaces of the vault, the at least one user terminal comprising an elevator system configured to vertically move the plurality of storage bins between any of the one or more platters and an opening formed through an outer shell of the user terminal.
2. The system of claim 1, wherein the frame comprises a base, an upper portion, a lower portion, and a plurality of inner vertical struts extending between and connecting the upper portion to the lower portion.
3. The system of claim 2, wherein the frame is devoid of a central axle.
4. The system of claim 2, wherein the base comprises at least two parallel axial slots on an underside of the base, such that the frame is movable by a pallet jack, a fork truck, or other transport device.
5. The system of claim 2, wherein the plurality of inner vertical struts comprises at least three inner vertical struts.
6. The system of claim 2, wherein the frame has a cross-sectional profile in a shape of a polygon and a number of the plurality of mounting surfaces is equivalent to a number of sides of the polygon.

7. The system of claim 6, wherein the inner vertical struts are spaced apart from each other by an angle of approximately 60° relative to the longitudinal axis of the frame.
8. The system of claim 2, comprising, for each of the platters, a plurality of rollers rotatably attached to the inner vertical struts to support the platter and maintain a gap between an inner edge of the platters and the inner vertical struts.
9. The system of claim 1, wherein the at least one user terminal comprises at least one user interface device for determining an identity of a user authorized to retrieve one or more items stored in one of the storage bins within the vault.
10. The system of claim 1, wherein the one or more platters comprises a plurality of platters.
11. The system of claim 10, comprising a rapid retrieval and storage (RRS) terminal attached to the vault at one of the mounting surfaces of the vault, the RRS terminal comprising:
- an outer shell;
 - an opening formed through the outer shell to allow items to pass through the opening into and/or out of the vault; and
 - a door that is movably arranged within the opening between an open position and a closed position;
- wherein the opening is at a height of one of the platters, designated as an RRS platter.
12. The system of claim 11, wherein the RRS terminal is separated from the at least one user terminal by a physical barrier.
13. The system of claim 12, wherein only the RRS platter can be accessed through the opening of the RRS terminal
14. The system of claim 11, wherein:

the RRS terminal comprises an inventory control device configured to detect and/or verify one or more items passing through the opening of the RRS terminal; and

the system is configured to advance the RRS platter, such that a second empty storage bin on the RRS platter is accessible through the opening of the RRS terminal, after an item has been deposited into a first empty storage bin on the RRS platter.

15. The system of claim 14, wherein:

the at least one user terminal comprises a plurality of user terminals that support simultaneous user induction and retrieval of items within the vault; and

the plurality of user terminals are configured to replace occupied storage bins on the RRS platter with empty storage bins from another of the platters as empty storage bins are filled by a user at the RRS terminal.

16. The system of claim 11, wherein the system is configured to optimize an arrangement of storage bins within the vault, prior to items being loaded onto the RRS platter at the RRS terminal, by removing occupied storage bins from the RRS platter and arranging empty storage bins about the RRS terminal in a consecutive manner.

17. The system of claim 11, wherein the RRS terminal comprises one or more user interface devices configured to authenticate an identity of a user at the RRS and/or to scan an item to obtain information about the item before an item is loaded into one of the storage bins at the RRS terminal and/or after an item is removed from one of the storage bins at the RRS terminal and validating an association to a bin identification number.

18. The system of claim 10, comprising, for each of the platters, a drive motor configured to engage with one of the platters to rotate the one of the platters about the frame.

19. The system of claim 18, wherein the system is configured to measure an amount of backlash between each drive motor and a corresponding one of the

platters with which each drive motor rotatably engages, the amount of backlash being determined by, for each platter, rotating the platter in a first direction, stopping the platter, rotating the platter in a second direction, measuring a time between torque spikes detected by the drive motor, and adjusting a motion profile of the drive motor to account for the amount of backlash measured.

20. The system of claim 18, wherein the at least one user terminal comprises a trolley system that is movable along a length of an elevator shaft of the elevator system and is configured to remove one of the storage bins from any of the platters, deposit one of the storage bins on any of the platters, and transport one of the storage bins vertically along the elevator shaft to be accessible through the opening of the user terminal.

21. The system of claim 20, wherein the trolley system comprises:

- a base that is movable along the length of the elevator shaft but fixedly arranged in a plane substantially perpendicular to the elevator shaft; and

- an extension platform that can be extended, relative to the base, towards the platters in a radially inward direction of the platters;

- wherein the extension platform is configured to engage with one of the storage bins to transfer the storage bin onto or off of the extension platform.

22. The system of claim 21, wherein the extension platform comprises a slot along a length of the extension platform.

23. The system of claim 22, wherein the storage bins comprise a rib and a track, the rib being configured to pass within the slot of the extension platform, such that the track and a bottom of the storage bin are on opposite sides of the extension platform relative to a plane defined by an upper surface of the extension platform.

24. The system of claim 23, wherein:

- the track of the storage bins comprises a plurality of gear teeth;

- a bin pinion gear comprising a plurality of gear teeth is arranged on the extension platform in a position that, when the extension platform is in a deployed

position extended relative to the base, the gear teeth of the bin pinion gear are adjacent to, and mesh with, the gear teeth of the track; and

the bin pinion gear is rotatable in a first direction, in which the storage bin is removed from the platter and drawn onto the extension platform, and a second direction, in which the storage bin is ejected from the extension platform and deposited onto the platter.

25. The system of claim 24, wherein the extension platform and the bin pinion gear are driven substantially simultaneously.

26. The system of claim 10, wherein a first of the platters is located in a refrigerated region of the vault so that items stored on the first platter are maintained at a lower temperature than items stored on other platters within the vault.

27. The system of claim 10, wherein:

each platter comprises a plurality of bin slots formed around the outer circumference thereof, the bin slots comprising a bin tab comprising opposing elastically deformable pincers;

each storage bin comprises a rib connected to a bottom surface of the storage bin, a track connected to the rib in a position spaced apart from the bottom surface of the storage bin, and a bump arranged at, or adjacent to, an end of the rib; and

the bump has a shape that can be removably retained within a region of the bin tab to prevent the bin slots from being dislodged from the bin slots other than by the storage bins being removed by a trolley system of the at least one user terminal.

28. The system of claim 1, comprising one or more of:

a secure cart configured to securely transport and load a plurality of items from a restricted access area to the vault;

a locker pod attached to the vault, the locker pod comprising a plurality of lockers that are directly accessible by a user from a position outside of the vault;

a high capacity pod attached to the vault and configured to receive storage bins from the vault for storage in the high capacity pod and/or to transfer storage bins to the vault to be accessible at one of the user terminals;

a power pod attached to the vault and configured to provide redundant power to the system; and

an automated storage and retrieval system (ASRS) attached to the vault and comprising a plurality of storage areas internal to the ASRS that are accessible only via a portal external to and separate from the vault.

29. The system of claim 1, wherein the at least one user terminal comprises an imaging device configured to measure a distance between two fiducial markings on the one or more platters to align the one or more platters with at least one user terminal.

30. The system of claim 1, comprising an automated item-dispensing system operably connected to the vault at a mounting surface of the vault, the automated item-dispensing system being configured to transfer items to the vault for fully automated loading of the items within the vault.

31. The system of claim 1, wherein the user terminal comprises a touchscreen configured to receive input from a user at the user terminal.

32. The system of claim 1, wherein the user terminal comprises a touchscreen to sync and receive input from a personal electronic device (PED) of the user at the user terminal.

33. The system of claim 1, wherein the system is configured to optimize positions of the storage bins within the vault to minimize a processing time for storage and retrieval of one or more items within the vault.

34. The system of claim 1, wherein the at least one user terminal is configured to display a targeted message to a recipient present at one of the at least one user terminals after authenticating an identity of the recipient.

35. The system of claim 1, wherein the system is configured to retrieve supply chain pedigree data and display the supply chain pedigree data to a recipient at one of the at least one user terminals.

36. The system of claim 1, comprising a buffer system with a plurality of intermediate storage areas configured to hold and sequentially deposit one or more items into storage bins, which are configured for storage within the vault.

37. The system of claim 36, wherein the buffer system comprises a belt rotatably movable about at least two spindles, the belt having a plurality of paddles arranged thereon extending away from an outer surface thereof, and the plurality of intermediate storage areas being defined by a space between adjacent paddles in a direction of the length of the belt.

38. The system of claim 37, wherein the belt is configured to rotate such that any items in each of the intermediate storage areas are sequentially deposited into a storage bin for storage within the vault.

39. The system of claim 37, wherein the buffer system is configured such that the belt is rotatable in a stepped manner, such that items in only a single intermediate storage area are deposited into a bin for storage within the vault.

40. The system of claim 37, wherein the buffer system comprises a housing with at least one opening formed therein to allow for depositing items within only one of the intermediate storage areas at a time.

41. The system of claim 40, wherein the buffer system comprises a scanner configured to detect information regarding the items being deposited into the intermediate storage areas.

42. The system of claim 41, wherein the information comprises one or more of item identity authentication information, recipient identity information, and/or supply chain information.

43. The system of claim 41, wherein the buffer system is configured such that the belt advances by a distance equivalent to a length of one intermediate storage area

after the scanner or the sensor detects that an item has passed through the opening into one of the intermediate storage areas.

44. The system of claim 40, wherein the buffer system comprises a sensor configured to detect when the item is deposited into one of the intermediate storage areas through the opening in the housing.

45. The system of claims 44, wherein the buffer system is configured such that the belt advances by a distance equivalent to a length of one intermediate storage area after the scanner or the sensor detects that an item has passed through the opening into one of the intermediate storage areas.

46. The system of claim 45, wherein the buffer system is configured to generate an error when the scanner or the sensor detects that an item has been deposited into an intermediate storage area without the information about the item having been detected.

47. The system of claim 37, wherein advancing the belt by one intermediate storage area deposits items contained in at least one intermediate storage area to be transferred into a bin for storage within the vault.

48. The system of claim 47, wherein the bin into which the at least one intermediate storage area deposits its contents is not accessible by a user at a user terminal.

49. The system of claim 37, comprising an automated item-dispensing system operably connected to the buffer system and configured to transfer items to the buffer system for fully automated loading of the items within the vault.

50. The system of claim 1, wherein the system is configured to transmit information remotely to diagnose and troubleshoot malfunctions detected by the system.

51. A method for storing and distributing at least one item within a secure storage and retrieval system, the method comprising:

providing a vault comprising a frame, one or more platters mounted about the frame to be independently rotatable about the frame, a plurality of storage bins arranged radially about each of the one or more platters, and a plurality of mounting surfaces arranged about a perimeter of the vault;

identifying a designated storage bin of a plurality of storage bins on a designated platter of the one or more platters within the vault, the designated storage bin containing one or more items associated with the user at the user terminal;

removing the designated storage bin from the designated platter and transporting the designated storage bin adjacent to an opening formed through an outer shell of the user terminal;

opening a door at the user terminal, such that the one or more items within the designated storage bin are accessible to the user through the opening;

closing the door after a predetermined amount of time and/or after detecting that the one or more items were removed from the designated storage bin by the user;

transporting the designated storage bin adjacent to one of the one or more platters within the vault; and

depositing the designated storage bin onto the one of the one or more of platters within the vault.

52. The method of claim 51, wherein the frame comprises a base, an upper portion, a lower portion, and a plurality of inner vertical struts extending between and connecting the upper portion to the lower portion.

53. The method of claim 52, wherein the frame is devoid of a central axle.

54. The method of claim 52, wherein the base comprises at least two parallel axial slots on an underside of the base, such that the frame is movable by a pallet jack, a fork truck, or other transport device.

55. The method of claim 52, wherein the plurality of inner vertical struts comprises at least three inner vertical struts.

56. The method of claim 52, wherein the frame has a cross-sectional profile in a shape of a polygon and a number of the plurality of inner vertical struts is equivalent to a number of sides of the polygon.

57. The method of claim 56, wherein the inner vertical struts are spaced apart from each other by an angle of approximately 60° relative to the longitudinal axis of the frame.

58. The method of claim 52, comprising rotatably attaching, for each of the platters, a plurality of rollers to the inner vertical struts to support the platter and maintain a gap between an inner edge of the platters and the inner vertical struts.

59. The method of claim 51, comprising authenticating an identity of a user at a user terminal connected to the vault at one of the mounting surfaces of the vault.

60. The method of claim 51, wherein the one or more platters comprises a plurality of platters.

61. The method of claim 60, comprising attaching a rapid retrieval and storage (RRS) terminal to the vault at one of the mounting surfaces of the vault, the RRS terminal comprising:

- an outer shell;

- an opening formed through the outer shell to allow items to pass through the opening into and/or out of the vault; and

- a door that is movably arranged within the opening between an open position and a closed position;

- wherein the opening is at a height of one of the platters, designated as an RRS platter.

62. The method of claim 61, wherein the RRS terminal is separated from the at least one user terminal by a physical barrier.

63. The method of claim 62, wherein only the RRS platter can be accessed through the opening of the RRS terminal

64. The method of claim 61, comprising:

detecting, using an inventory control device of the RRS terminal, one or more items passing through the opening of the RRS terminal; and

advancing, after an item has been deposited into a first empty storage bin on the RRS platter, the RRS platter, such that a second empty storage bin on the RRS platter is accessible through the opening of the RRS terminal.

65. The method of claim 64, wherein the at least one user terminal comprises a plurality of user terminals that support simultaneous user induction and retrieval of items within the vault, the method comprising replacing, using the plurality of user terminals, occupied storage bins on the RRS platter with empty storage bins from another of the platters as empty storage bins are filled by a user at the RRS terminal.

66. The method of claim 61, comprising optimizing an arrangement of storage bins within the vault, prior to items being loaded onto the RRS platter at the RRS terminal, by removing occupied storage bins from the RRS platter and arranging empty storage bins about the RRS terminal in a consecutive manner.

67. The method of claim 61, comprising:

authenticating, using one or more user interface devices of the RRS terminal, an identity of a user at the RRS; and/or

scanning an item to obtain information about the item before an item is loaded into one of the storage bins at the RRS terminal and/or after an item is removed from one of the storage bins at the RRS terminal and validating an association to a bin identification number.

68. The method of claim 60, comprising, for each of the platters, a drive motor that engages with one of the platters to rotate the one of the platters about the frame.

69. The method of claim 68, comprising measuring an amount of backlash between each drive motor and a corresponding one of the platters with which each

drive motor rotatably engages, the amount of backlash being determined by, for each platter, rotating the platter in a first direction, stopping the platter, rotating the platter in a second direction, measuring a time between torque spikes detected by the drive motor, and adjusting a motion profile of the drive motor to account for the amount of backlash measured.

70. The method of claim 68, wherein the at least one user terminal comprises a trolley system that is movable along a length of an elevator shaft of the elevator system and is configured to remove one of the storage bins from any of the platters, deposit one of the storage bins on any of the platters, and transport one of the storage bins vertically along the elevator shaft to be accessible through the opening of the user terminal.

71. The method of claim 70, wherein the trolley system comprises:

- a base that is movable along the length of the elevator shaft but fixedly arranged in a plane substantially perpendicular to the elevator shaft; and

- an extension platform that can be extended, relative to the base, towards the platters in a radially inward direction of the platters;

- wherein the extension platform is configured to engage with one of the storage bins to transfer the storage bin onto or off of the extension platform.

72. The method of claim 71, wherein the extension platform comprises a slot along a length of the extension platform.

73. The method of claim 72, wherein the storage bins comprise a rib and a track, the method comprising inserting the rib within the slot of the extension platform, such that the track and a bottom of the storage bin are on opposite sides of the extension platform relative to a plane defined by an upper surface of the extension platform.

74. The method of claim 73, wherein:

- the track of the storage bins comprises a plurality of gear teeth;

- a bin pinion gear comprising a plurality of gear teeth is arranged on the extension platform in a position that, when the extension platform is in a deployed

position extended relative to the base, the gear teeth of the bin pinion gear are adjacent to, and mesh with, the gear teeth of the track; and

the bin pinion gear is rotatable in a first direction, in which the storage bin is removed from the platter and drawn onto the extension platform, and a second direction, in which the storage bin is ejected from the extension platform and deposited onto the platter.

75. The method of claim 74, wherein the extension platform and the bin pinion gear are driven substantially simultaneously.

76. The method of claim 60, wherein a first of the platters is located in a refrigerated region of the vault so that items stored on the first platter are maintained at a lower temperature than items stored on other platters within the vault.

77. The method of claim 60, wherein:

each platter comprises a plurality of bin slots formed around the outer circumference thereof, the bin slots comprising a bin tab comprising opposing elastically deformable pincers;

each storage bin comprises a rib connected to a bottom surface of the storage bin, a track connected to the rib in a position spaced apart from the bottom surface of the storage bin, and a bump arranged at, or adjacent to, an end of the rib; and

the bump has a shape that can be removably retained within a region of the bin tab to prevent the bin slots from being dislodged from the bin slots other than by the storage bins being removed by a trolley system of the at least one user terminal.

78. The method of claim 51, comprising one or more of:

providing a secure cart configured to securely transport and load a plurality of items from a restricted access area to the vault;

a locker pod attached to the vault, the locker pod comprising a plurality of lockers that are directly accessible by a user from a position outside of the vault;

attaching a high capacity storage pod to the vault to receive storage bins from the vault for storage in the high capacity pod and/or to transfer storage bins to the vault to be accessible at one of the user terminals;

attaching a power pod to the vault to provide redundant power to the system;
and

attaching an automated storage and retrieval system (ASRS) to the vault, the ASRS comprising a plurality of storage areas internal to the ASRS that are accessible only via a portal external to and separate from the vault.

79. The method of claim 51, wherein the at least one user terminal comprises an imaging device configured to measure a distance between two fiducial markings on the one or more platters to align the one or more platters with at least one user terminal.

80. The method of claim 51, comprising operably connecting an automated item-dispensing system to the vault at a mounting surface of the vault to transfer items to the vault for fully automated loading of the items within the vault.

81. The method of claim 51, wherein the user terminal comprises a touchscreen to receive input from a user at the user terminal.

82. The method of claim 51, wherein the user terminal comprises a touchscreen to sync and receive input from a personal electronic device (PED) of the user at the user terminal.

83. The method of claim 51, comprising optimizing positions of the storage bins within the vault to minimize a processing time for storage and retrieval of one or more items within the vault.

84. The method of claim 51, comprising displaying, on a display of the at least one user terminal, a targeted message to a recipient present at one of the at least one user terminals after authenticating an identity of the recipient.

85. The method of claim 51, comprising retrieving supply chain pedigree data and displaying the supply chain pedigree data to a recipient at one of the at least one user terminals.

86. The method of claim 51, comprising providing a buffer system with a plurality of intermediate storage areas to hold and sequentially deposit one or more items into storage bins for storage within the vault.

87. The method of claim 86, wherein the buffer system comprises a belt rotatably movable about at least two spindles, the belt having a plurality of paddles arranged thereon extending away from an outer surface thereof, and the plurality of intermediate storage areas being defined by a space between adjacent paddles in a direction of the length of the belt.

88. The method of claim 87, comprising rotating the belt such that any items in each of the intermediate storage areas are sequentially deposited into a storage bin for storage within the vault.

89. The method of claim 87, wherein the belt is rotatable in a stepped manner, such that items in only a single intermediate storage area are deposited into a bin for storage within the vault.

90. The method of claim 87, wherein the buffer system comprises a housing with at least one opening formed therein, the method comprising depositing items within only one of the intermediate storage areas at a time.

91. The method of claim 90, wherein the buffer system comprises a scanner, the method comprising detecting, using the scanner of the buffer system, information regarding the items being deposited into the intermediate storage areas.

92. The method of claim 91, wherein the information comprises one or more of item identity authentication information, recipient identity information, and/or supply chain information.

93. The method of claim 91, comprising advancing the belt by a distance equivalent to a length of one intermediate storage area after the scanner or the sensor detects that an item has passed through the opening into one of the intermediate storage areas.

94. The method of claim 90, wherein the buffer system comprises a sensor, the method comprising detecting, using the sensor, when the item is deposited into one of the intermediate storage areas through the opening in the housing.

95. The method of claims 94, comprising advancing the belt by a distance equivalent to a length of one intermediate storage area after the scanner or the sensor detects that an item has passed through the opening into one of the intermediate storage areas.

96. The method of claim 95, comprising generating, at the buffer system and/or in the system, an error when the scanner or the sensor detects that an item has been deposited into an intermediate storage area without the information about the item having been detected.

97. The method of claim 87, wherein advancing the belt by one intermediate storage area deposits items contained in at least one intermediate storage area to be transferred into a bin for storage within the vault.

98. The method of claim 97, wherein the bin into which the at least one intermediate storage area deposits its contents is not accessible by a user at a user terminal.

99. The method of claim 87, comprising operably connecting an automated item-dispensing system to the buffer system to transfer items to the buffer system for fully automated loading of the items within the vault.

100. The method of claim 51, comprising:

rotating the designated platter on which the designated storage bin is located so that the designated storage bin is aligned with a trolley system of the user terminal; and

extending an extension platform of the trolley system such that the designated storage bin can be transferred onto the extension platform.

101. The method of claim 51, wherein the at least one item is a uniquely identified item.

102. The method of claim 51, comprising transmitting information remotely to diagnose and troubleshoot malfunctions detected by the system.

1/32




FIG. 1

2/32




FIG. 2

3/32




FIG. 3

4/32





FIG. 4



6/32




FIG. 6




FIG. 7







FIG. 8

9/32





11/32




FIG. 11

12/32




FIG. 12

13/32





FIG. 13

14/32



15/32




FIG. 15




FIG. 16

17/32




FIG. 17




FIG. 18





FIG. 19

20/32



21/32






FIG. 21








FIG. 24

25/32




FIG. 25




FIG. 26

27/32




FIG. 27




FIG. 28

29/32




FIG. 29

30/32




FIG. 30

31/32




FIG. 31




FIG. 32

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2019/037343

A. CLASSIFICATION OF SUBJECT MATTER
INV. G06F11/00 G06F17/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
G06F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EP0-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2013/253700 A1 (CARSON BRADLEY E [US] ET AL) 26 September 2013 (2013-09-26) the whole document -----	1-102
A	US 2014/361076 A1 (IANTORNO PAT R [US] ET AL) 11 December 2014 (2014-12-11) the whole document -----	1-102
A	US 2014/021253 A1 (CARSON BRADLEY E [US] ET AL) 23 January 2014 (2014-01-23) the whole document -----	1-102
A	US 8 628 289 B1 (BENEDICT CHARLES E [US] ET AL) 14 January 2014 (2014-01-14) the whole document -----	1-102

☐

Further documents are listed in the continuation of Box C.

☒

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

24 September 2019

Date of mailing of the international search report

07/10/2019

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Lutz, Andreas

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2019/037343

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2013253700 A1	26-09-2013	CA 2810338 A1	26-09-2013
		US 2013253700 A1	26-09-2013
US 2014361076 A1	11-12-2014	US 2014361076 A1	11-12-2014
		US 2017242977 A1	24-08-2017
		WO 2014197855 A1	11-12-2014
US 2014021253 A1	23-01-2014	CA 2820895 A1	23-01-2014
		CA 2820902 A1	23-01-2014
		US 2014021253 A1	23-01-2014
		US 2014025545 A1	23-01-2014
US 8628289 B1	14-01-2014	NONE	