


(No Model.)

S. F. BROWN.
BAG HOLDER.

No. 501,820.

Patented July 18, 1893.



WITNESSES:

F. L. Ourand
J. L. Loomis

INVENTOR:

Seabury F. Brown
James C. Brown & Co.
Attorneys

UNITED STATES PATENT OFFICE.

SEABURY F. BROWN, OF CUYLER, NEW YORK.

BAG-HOLDER.

SPECIFICATION forming part of Letters Patent No. 501,820, dated July 18, 1893.

Application filed February 13, 1893. Serial No. 462,141. (No model.)

To all whom it may concern:

Be it known that I, SEABURY F. BROWN, a citizen of the United States, and a resident of Cuyler, in the county of Cortland and State of New York, have invented certain new and useful Improvements in Bag-Holders; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to
10 which it appertains to make and use the same, reference being had to the accompanying drawings, which form a part of this specification.

My invention relates to improvements in
15 bag-holders of that class or description in which a bag may be suspended and its mouth held open while being filled.

The object of the invention is to provide an improved construction of same, whereby
20 I secure important advantages with respect to simplicity and efficiency in operation.

The invention consists in the novel construction and combination of parts, herein after fully described and claimed.

25 In the accompanying drawings: Figure 1 is a perspective view of a bag-holder constructed in accordance with my invention. Fig. 2 is a side elevation of the same; Fig. 3 is a detail sectional view.

30 In the said drawings the reference numeral 1 designates two uprights or standards mounted upon the base pieces 2, and braced by the lower end cross-piece 3, and intermediate cross-piece 4. The upper ends of these standards are made cylindrical to receive the
35 vertically sliding collars 5, provided with downwardly depending spring-arms 6, the free ends of which are provided with studs 12, which engage with recesses 13 in the standards, and serve to retain said collars in any
40 position to which they may be adjusted upon

said standards. These collars are provided or formed with lugs 7 to which are pivoted arms 8, secured to a rim 9, provided with a series of hooks or prongs 10, to support the
45 bag. This rim it will be seen is made of a single strip of metal with a curved front and straight back.

The operation is as follows: The collars 5 are adjusted upon the standards 1, according
50 to the height of the bag to be filled, and are held in place thereon by means of the spring-arms 6, which press against said standards. The upper edge of the bag to be filled, is then engaged with the prongs 10, which will sus-
55 pend the same and hold the mouth thereof distended, so that the bag can be readily filled. When the bag has been filled, the edge thereof is disengaged from the hooks or prongs and the rim is then thrown upward
60 and backward, turning upon the pivots of the arms 8, so as to be out of the way and allow the filled bag to be removed.

Having thus described my invention, what
I claim is—

65 In a bag-holder the combination with the standards having their upper ends made cylindrical, of the vertically movable collars provided with downwardly depending spring-arms bearing against said standards, the arms
70 pivoted to said collars, and the rim to which said arms are secured, made of a single piece of metal with curved front and straight back, and provided with prongs or hooks, substantially as and for the purpose specified.
75

In testimony that I claim the foregoing as my own I have hereunto affixed my signature in presence of two witnesses.

SEABURY F. BROWN.

Witnesses:

C. N. KNAPP,
ERNEST WOODWARD.