

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 December 2009 (03.12.2009)

(10) International Publication Number
WO 2009/146244 A1

- (51) **International Patent Classification:**
H04N 7/173 (2006.01)
- (21) **International Application Number:**
PCT/US2009/043389
- (22) **International Filing Date:**
8 May 2009 (08.05.2009)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**
12/128,096 28 May 2008 (28.05.2008) US
- (71) **Applicant (for all designated States except US):** SONY
COMPUTER ENTERTAINMENT AMERICA INC.
[US/US]; 919 East Hillsdale Boulevard, 2nd Floor, Foster
City, CA 94404 (US).
- (72) **Inventor; and**
- (75) **Inventor/Applicant (for US only):** ZALEWSKI, Gary
M. [US/US]; 919 East Hillsdale Boulevard, 2nd Floor,
Foster City, CA 94404 (US).
- (74) **Agent:** ISENBERG, Joshua D.; JDI PATENT, 809 Cor-
porate Way, Fremont, CA 94539 (US).

- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report (Art. 21(3))

(54) **Title:** INTEGRATION OF CONTROL DATA INTO DIGITAL BROADCAST CONTENT FOR ACCESS TO ANCILLARY INFORMATION




FIG. 3

(57) **Abstract:** Ancillary information associated with one or more images embedded in a digital broadcast data stream may be accessed by a digital broadcast receiving device. The device may include a receiver unit, a processor, and a memory. The processor may execute program instructions to access the ancillary information. Control data may be associated with one or more visual components of one or more video images. The control data and images may be combined into a digital broadcast data stream. The device may receive the images and control data. The images may be presented on a display device. The receiving device may use the control data to present or store a perceptible indication that ancillary information is associated with the visual components in conjunction with presenting the images. The device may use the control data to present or store the ancillary information in response to an input signal.

WO 2009/146244 A1

INTEGRATION OF CONTROL DATA INTO DIGITAL BROADCAST CONTENT FOR
ACCESS TO ANCILLARY INFORMATION

PRIORITY CLAIM

This application claims the benefit of priority of commonly
5 assigned U.S. Patent Application 12/128,096, filed May 28,
2008, the entire disclosures of which are incorporated herein
by reference.

FIELD OF THE INVENTION

Embodiments of this invention are related to digital
10 broadcasting and more specifically to updating data for
services usable in conjunction with a digital broadcast
signal.

BACKGROUND OF THE INVENTION

Since broadcast television was introduced in the 1930s,
15 television stations and networks have been paid to advertise
products and services in conjunction with scheduled
programming. Such advertising is often in the form of
commercials that are broadcast during breaks in program
content. A common problem with such commercials from the
20 point of view of the viewer is that they interrupt the
programming that the viewer would like to watch. Another
problem with commercials from the point of view of the
advertiser is that it is difficult to track the effectiveness
of a given ad in encouraging a given viewer to purchase
25 something advertised in a commercial.

A further problem has been the development of the digital
video recorders (DVR), which allows a viewer to "fast-forward"
through commercials and thereby avoid their impact entirely.
Many DVR systems also allow a viewer to "pause" or "rewind" a
30 television program. This feature is commonly used by DVR
users when television viewing is interrupted, e.g., by a
telephone call. Some viewers may use a DVR to pause or even
rewind a program to get a closer look at something shown in
the course of a broadcast.

35 To enhance revenue streams for broadcasters and to make
advertising less intrusive to viewers, some programs include

advertising in a form referred to herein as "product placement." In this type of advertising, a product, or the logo or trademark for the product, appears in a television program as part of the program. For example, a program may
5 show a character ostentatiously drinking from a can marked with the logo of a popular brand or soft drink or driving a particular make and model of automobile, with the manufacturer's trademark prominently displayed. Although these advertisements are less intrusive than conventional
10 television commercials, their impact on consumers may be lessened for this very reason.

A major change in the nature of television for both advertisers and consumers arose with the advent of digital television. Introduced in the late 1990s, digital television
15 (DTV) technology appealed to the television broadcasting business and consumer electronics industries as offering new consumer services and business opportunities that were impractical with previous analog television. Digital television is more flexible and efficient than analog
20 television. When properly used by broadcasters, digital television allows higher-quality images and sound and more programming choices than analog does. In DTV moving images and sound are sent and received by means of discrete (digital) signals, in contrast to the analog signals used by analog
25 television. Digital television includes, but is not limited to Digital Terrestrial Television (DTTV or DTT), which is an implementation of digital technology to provide a greater number of channels and/or better quality of picture and sound using aerial broadcasts to a conventional antenna (or aerial)
30 as opposed to a satellite dish or cable connection.

The development of digital television has lead to many changes in television broadcasting and related industries. Many countries have mandated a change from an analog television signal format to a new digital format. One example of such a
35 digital television broadcast standard was developed by the Advanced Television Systems Committee. With a conventional analog television broadcast, a video signal modulates a carrier wave signal that is broadcast by a transmission tower.

A television set contains a receiver that detects broadcast signals. The receiver includes a tuner that selects a particular channel according to its carrier frequency and a demodulator that extracts the video signal from the modulated carrier signal. With a digital television signal, the video signal is generated in a digital format or an analog video signal is converted to a digital format to produce a digital signal. The carrier wave is modulated according to the digital signal format, e.g., using vestigial sideband (VSB) modulation. This new format allows data for additional digital services to be broadcast along with a regular television signal. Examples of such services may include real time stock quotes, sports, weather and traffic updates and other services traditionally associated with delivery via two-way media, such as the internet, digital wireless services or cellular telephone services.

Digital broadcasting allows broadcasters to provide ancillary data or control data associated with program content. For example, some digital radio broadcast signals include data identifying program content, such as a program title or the name and/or artist of a song played over a digital broadcast. A digital radio receiver can display this information, e.g., on a text display. Some systems can even use this data to allow a user to download content. This type of two-way activity is relatively easy to implement in digital radio, which is essentially a one dimensional audio medium. However, the multi-dimensional audio-video nature of television makes such two-way activity problematic for digital television systems.

The delivery of digital services by a primarily one-way medium through digital broadcast presents certain challenges and problems. Providing a link between programming broadcast over digital television broadcast channels and data that is accessible on demand presents certain problems and opportunities heretofore unrecognized in the art.

It is within this context that embodiments of the present invention arise.

SUMMARY OF THE INVENTION

According to an embodiment of the present invention, a method for accessing ancillary information associated with one or more images embedded in a digital broadcast data stream may be implemented in a digital broadcast receiving device configured to receive programming and data over a plurality of digital broadcast channels. A digital television broadcast signal may be received by the receiving device. The digital broadcast signal may include data representing one or more video images and control data associated with one or more visual components of the one or more video images. The one or more video images may be presented on a video display device associated with the digital broadcast receiving device. The control data may be used to present a perceptible indication that ancillary information is associated with the one or more visual components in conjunction with presenting the one or more video images with the display device. The control data may also be used to present the ancillary information with the display device in response to an input signal.

In some embodiments, the input signal may be a signal from a remote control associated with the digital broadcast receiving device. In some embodiments, the ancillary information includes one or more advertisements.

In some embodiments, the control data may be associated with one or more objects depicted in one or more of the video images. The control data may alternatively be associated with a context associated with the one or more video images.

In some embodiments, the perceptible indication may be displayed with the display device while presenting the one or more video images.

In some embodiments, displaying the perceptible indication may include presenting information guiding a percipient to the ancillary information that is associated with the control data using the display device. In some embodiments, displaying the perceptible indication may include superposing the information guiding the percipient to the ancillary information over one or more of the video images. In some embodiments, the

information guiding the percipient to the ancillary information includes one or more links to one or more resources accessible via an electronic communications network. In some embodiments, the resources may be accessed via the one
5 or more links in response to the input signal.

In some embodiments, the information guiding the percipient to the ancillary information may include a video image identifying the one or more visual components. The image may include one or more links. Each link may be associated with
10 one or more of the visual components. Each link may be configured to provide access to the ancillary information associated with the corresponding visual component.

In some embodiments, displaying the perceptible indication may include pausing presentation of a program containing the one
15 or more video images at a particular video image in response to a pause signal. One or more visual components in that image may be highlighted in a manner perceptible to a percipient. One or more links to the ancillary information may be associated with the one or more visual components. In
20 such embodiments, the ancillary information associated with a particular visual component may be presented in response to a selection input.

In some embodiments, presenting the ancillary information may include storing the ancillary information in a memory
25 associated with the digital broadcast receiving device and/or display device. In other embodiments, presenting the ancillary information may include using the control data as an input to a search engine coupled to the digital broadcast receiving device and/or display device and conducting a search
30 with the search engine.

According to another embodiment of the invention, a digital broadcast receiving device may include a receiver unit, a processor coupled to the receiver unit and a memory coupled to the processor. The receiver unit may be configured to receive
35 programming and data over one or more digital broadcast channels. A set of processor readable instructions may be embodied in the memory for execution on the processor. The

instructions may be configured to implement the method described above.

In some embodiments, the digital broadcast receiving device may further comprise a video display device, which may be
5 operably coupled to the processor.

In some embodiments, the digital broadcast receiving device may further comprise a backchannel coupled to the processor. The backchannel may include a network interface coupled to an electronic communications network.

10 In some embodiments, the digital broadcast receiving device may further comprise a remote control configured to interoperate with the processor. In such a case the input signal referred to in the method above may be a signal from the remote control.

15 According to another embodiment, a digital broadcast data stream having control data associated with one or more images in a digital broadcast data stream may be provided according to an inventive method. According to the method control data may be associated with one or more visual components of one or
20 more video images. The control data may be configured facilitates access to ancillary data associated with the one or more visual components by a receiving device and/or display device usable with a digital broadcast signal generated from the digital broadcast data stream. The control data and the
25 video images may be combined into a digital broadcast data stream.

The control data may be configured as in the method described above. For example, according to some embodiments, the control data may be associated with one or more objects
30 depicted in one or more of the video images. According to other embodiments, the control data may be associated with a context of the one or more video images.

According to some embodiments, the digital broadcast data stream may be broadcast as a digital broadcast signal.

35 According to some embodiments, the control data may identify one or more hotspots associated with one or more video images.

Each hotspot may provide a link to ancillary information associated with the one or more visual components.

BRIEF DESCRIPTION OF THE DRAWINGS

The teachings of the present invention can be readily
5 understood by considering the following detailed description
in conjunction with the accompanying drawings, in which:

FIG. 1 is a schematic diagram illustrating a broadcast environment in which embodiments of the present invention may be employed.

10 FIG. 2 is a block diagram of a digital broadcast receiving device according to an embodiment of the present invention.

FIG. 3 is a flow diagram illustrating a method for accessing ancillary information associated with an image embedded in a digital broadcast data stream according to an embodiment of
15 the present invention.

FIG. 4 is a schematic diagram of a digital broadcast data stream that may be used in conjunction with embodiments of the present invention.

FIGS. 5A-5D illustrate examples of accessing ancillary
20 information associated with an image embedded in a digital broadcast data stream according to an embodiment of the present invention.

FIG. 6 is a block diagram illustrating method for providing a digital broadcast data stream having control data associated
25 with an image in a digital broadcast data stream according to an embodiment of the present invention.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

Although the following detailed description contains many specific details for the purposes of illustration, anyone of
30 ordinary skill in the art will appreciate that many variations and alterations to the following details are within the scope of the invention. Accordingly, examples of embodiments of the invention described below are set forth without any loss of generality to, and without imposing limitations upon, the
35 claimed invention.

Introduction

A digital television broadcast may include control data that allows a user to access ancillary information about visual components of one or more images in a program that is received
5 as part of a digital television broadcast.

FIG. 1 schematically illustrates a broadcast environment in which embodiments of the present invention may be employed. In such an environment broadcasters **102** receive or generate input data streams **101**. The input data streams **101** are
10 converted to digital broadcast data streams **103**, which are converted to a digital broadcast signal **105** for reception by digital broadcast receivers **110**. It is noted that for the sake of example, the two digital broadcast signals **105**, **106** are shown as being transmitted from different towers **104**.
15 This is not to be construed as a limitation upon any embodiment of the invention. Alternatively, the two digital broadcast signals **105**, **106** may originate from the same broadcast tower **104** and may be broadcast simultaneously, e.g., using frequency division multiplexing.

20 By way of example, a digital broadcast signal **105** may be a modulated radiation signal transmitted from a broadcast tower **104**, e.g., in the form of an over-the-air broadcast, such as by radiofrequency electromagnetic wave signal. It is noted that the digital broadcast signal **105** transmitted by a given
25 broadcast tower **104** may include multiple digital broadcast channels modulated at different carrier signal frequencies. Broadcast towers **104** associated with different broadcast units **102** may broadcast over different sets of frequencies. For example Broadcaster 1 may broadcast over a first set of
30 carrier frequencies $f_1 \dots f_m$ and Broadcaster N may broadcast over a different set of carrier frequencies $f'_1 \dots f'_j$. There may be some overlap between the two sets of carrier frequencies.

Furthermore, the digital broadcast signal **105** may be transmitted in a form other than an over-the-air broadcast.
35 Alternatively, embodiments of the invention may be used in conjunction with digital broadcasts transmitted over media such as cable (e.g., coaxial cable), optical fiber, or satellite transmission.

By way of example, the digital broadcast signal **105** may be configured in accordance with a digital broadcast standard. Examples of digital broadcast standards include, but are not limited to, the Digital Video Broadcasting (DVB) family of standards maintained in Europe and Australia, the Advanced Television Standards Committee (ATSC) family of standards developed for use in the United States and Canada, the Integrated Services Digital Broadcasting (ISDB) family of standards developed for use in Japan, Digital Multimedia Broadcasting (DMB) standard used in South Korea.

The DVB family of standards includes the DVB-S and DVB-S2 standards for satellite television, the DVB-T and DVB-T2 standards for terrestrial television, DVB-C for cable television and DVB-H for mobile television and other DVB standards which have been or may be developed. The ATSC family of standards includes the ATSC standard for terrestrial television broadcasts and the ATSC M/H standard for broadcasts to mobile and handheld devices. The ISDB family of standards includes the ISDB-S, ISDB-T, and ISDB-C standards, which were developed for satellite, terrestrial and cable television respectively.

By way of example, and not by way of limitation, the digital broadcast signal **105** may be configured according to the ATSC or ATSC-M/H standards. The ATSC standard is described in detail, e.g., in "ATSC Digital Television Standard Part 1 - Digital Television System" (A/53, Part 1:2007), "ATSC Digital Television Standard Part 2 - RF/Transmission System Characteristics" (A/53, Part 2:2007), and "ATSC Digital Television Standard Part 3 - Service Multiplex and Transport Subsystem Characteristics" (A/53, Part 3, 2007), the disclosures of all three of which are incorporated herein by reference. The ATSC Data Broadcast Standard is described, e.g., in (ATSC Recommended Practice: Implementation Guidelines for the ATSC Data Broadcast Standard (Doc. A/90)", which is incorporated herein by reference.

The input data stream **101** may include data streams from multiple sources. For example, within the broadcaster **102** data streams for different television program **107** may be made

up of audio, video and ancillary data streams. These data streams may be multiplexed to form a program data stream associated with a given program **107**. Multiple program data streams may be multiplexed with each other into the broadcast data stream **103**. The digital broadcast data stream **103** may include data representing one or more video images **I** and control data **CD** associated with one or more visual components of the one or more video images **I**.

As used herein, the term "visual component" refers to a visible portion of one or more video images that is associated with an object or context. Examples of objects include persons or things depicted within a video image. Examples of contexts include concepts, persons or things having an association with a person or thing depicted in a video image. For example, a manufacturer of a product may be associated with a product or logo depicted in a video image even though the manufacturer is not depicted.

Furthermore, one or more data service data streams **108** for broadcast data services $s_1 \dots s_x$ not specifically associated with a given program **107** may be overlaid (e.g., multiplexed) with the program data streams $P_1 \dots P_n$ into the broadcast data stream **103**.

The data streams **101** that make up digital broadcast data stream **103** may be subject to data transforms, such as source coding and compression. As used herein, "source coding and compression" refers to bit rate reduction methods, also known as data compression, appropriate for application to the video, audio, and ancillary digital data streams. The term "ancillary data" includes control data, conditional access control data, and data associated with the program audio and video services, such as closed captioning. "Ancillary data" can also refer to independent program services. The broadcast unit **102** may include a coder configured to minimize the number of bits needed to represent the audio and video information. If configured according to the ATSC standard, the broadcast unit **102** may employ the MPEG-2 video stream syntax for the coding of video and the Digital Audio Compression (AC-3) Standard for the coding of audio.

The broadcast unit **102** may also subject the digital broadcast data stream **103** to service and multiplex transport operations. As used herein, "service multiplex and transport" refers to the means of dividing the digital data stream into "packets" of information, the means of uniquely identifying each packet or packet type, and the appropriate methods of multiplexing video data stream packets, audio data stream packets, and ancillary data stream packets into a single data stream. By way of example, and not by way of limitation, digital broadcast unit **102** may employ the MPEG-2 transport stream syntax for the packetization and multiplexing of video, audio, and data signals for digital broadcasting systems. Such packetization and multiplexing is described e.g., ISO/IEC 13818- 1:2000 (E), International Standard, Information technology - Generic coding of moving pictures and associated audio information: systems", which is incorporated herein by reference.

The digital broadcast data stream **103** may be converted to a digital broadcast signal **105** through processes referred to as channel coding and modulation. The channel coder takes the data bit stream encoded in the digital broadcast data stream **103** and adds additional information that can be used by a receiving device **110** to reconstruct the data from the received signal which, due to transmission impairments, may not accurately represent the transmitted signal. A modulation subsystem (or physical layer) uses the digital data stream information to modulate the transmitted signal. By way of example and not by way of limitation, the ATSC standard, the modulation subsystem offers two modes. Both modes are based on vestigial sideband modulation. One mode is a terrestrial broadcast mode known as 8-VSB. The other mode is a high data rate mode known as 16-VSB.

A digital broadcast receiving device **110** receives the digital broadcast signal **105** and extracts the digital broadcast data stream **103** including the images **I** and control data **CD** encoded within the digital broadcast signal **105**. By way of example, and not by way of limitation, the digital broadcast receiving device **110** may include a digital receiver **111**, a processor

114, a memory **115**, a display **117** and a data storage device **118**. The digital broadcast receiving device **110** may be any type of device capable of receiving and utilizing the digital broadcast signal **105**. By way of example, the digital
5 broadcast receiving device **110** may be a digital television set, digital radio receiver, personal computer, laptop computer, a mobile or handheld device such as a cellular telephone, mobile internet device or mobile digital television receiver. Furthermore, the term digital broadcast receiving
10 device encompasses "digital media receivers", GPS devices, game consoles, portable game devices, home, mobile or device security systems, and any combination thereof and including other devices for which the present invention may be coupled to provide command and control.

15 The digital receiver **111** may include one or more tuners **112** and a decoder **113**. The tuner(s) **112** may be coupled to an antenna **119** that receives the digital broadcast signal **105**. The tuner **112** selects one or more particular frequencies from among the various signals that are picked up by the antenna
20 **119**. The tuner **112** and decoder **113** may extract data and generate audio and video signals from the digital broadcast signal **105**. By way of example the tuner **112** and decoder **113** may provide the following functions: demodulation, transport stream demultiplexing, decompression, error correction,
25 analog-to-digital conversion, AV synchronization and media reformatting to fit the specific type of display **117** optimally.

As used herein, demodulation refers to the process of transforming the received digital broadcast signal **105** into a
30 usable signal from which data may be extracted and/or from which quality images and sound may be produced.

Transport Stream Demultiplexing may be implemented, e.g., where multiple digital signals are combined and then transmitted from one antenna source to create over the air
35 broadcasts. In such a case, the decoder **113** may decode the digital broadcast data stream **103** and convert it to a suitable form for display of a particular program of the audio and/or video components with the display **117** or for extraction of a

broadcast service data stream **108** from the digital broadcast data stream **103**. The decoder **113** may implement decompression if the digital broadcast data stream **103** contains data in compressed form. The tuner **112** may decompress such data,
5 e.g., by unpacking compressed packets of digital data to their original size.

The decoder **113** may also implement Error Correction to make sure that any data that is missing from the received digital broadcast signal **105** can be corrected. For instance, sometimes
10 interference or a poor-quality signal will cause the loss of data information that the tuner **112** receives. In such cases, the decoder **112** may perform a number of checks and repair data so that a signal can be viewed on a TV set or data may be utilized by the processor **114**.

15 The decoder **113** may implement AV Synchronization to coordinate audio and video signals being displayed on the display **117** in proper time. AV synchronization ensures that the audio does not lag behind the video that is being displayed on the display **117** or vice versa, so that both audio and video are in
20 sync. Media reformatting allows the display **117** to properly display video images using the data extracted from the digital broadcast signal. Media reformatting is important since the formatting of images on TV sets may differ significantly according to the technology employed. For example, some
25 televisions utilize an interlaced picture, whereas others utilize a progressive-scan picture.

The video images **I** may be displayed on the video display **117**. By way of example, the display **117** may be any suitable video and/or audio-visual display usable with the digital broadcast
30 signal **105**. By way of example, and not by way of limitation, the display **117** may include a video monitor, such as a cathode ray tube (CRT), plasma display, liquid crystal display (LCD) or organic light-emitting diode (OLED) display. In addition, the display **117** may include one or more devices for generating
35 audio, e.g., one or more speakers.

The processor **114** may be programmed with instructions **SW** that use the control data **CD** to present a perceptible indication

that ancillary information is associated with one or more visual components of the images **I** in conjunction with presenting the images on the display device **117**. The instructions **SW** may use the control data **CD** to present the ancillary information with the display device in response to an input signal.

As used herein, the term "ancillary information" includes information about a visual component of a video image other than the visual depiction of the component within the image. Such ancillary information may include, but is not limited to information identifying visual component, information providing a history of a real object or concept represented by the visual component, advertisements of products or services associated with the object or concept represented by the visual component.

The receiving device **110** may also implement a backchannel **120** that allows information to be sent from the device to a broadcast unit **102** or a data center affiliated with the broadcast unit. The back channel **120** may be implemented through a digital broadcast signal transmitted from the device **110**, e.g., via the antenna **119**. Alternatively, the backchannel **120** may be implemented through some other mode of communication such as wireless telephony (e.g., cellular), wireless internet, cable, optical fiber and the like. The back channel **120** may be used to retrieve selected ancillary information **122** from a remote source **124**.

The receiving device **110** may also include a data storage device **118** for non-volatile storage of data, such as selected ancillary information **122**. Examples of data storage devices include hard disk drives, flash memories, compact disk (CD) drives, digital video disk (DVD) drives, tape drives, and the like.

The processor **114** may execute software program instructions that facilitate the above-referenced functions. In addition, the processor **114** may execute program instructions $SW_1 \dots SW_p$ for various digital broadcast data services. Data for these data services may be updated as part of the digital broadcast data

stream **103** that is carried by the digital broadcast signal **105**. The program instructions **SW** may operate on different portions of control data **CD₁...CD_p**, for different groups of related video images within the digital broadcast data stream

5 **103**. These different portions of control data **CD₁...CD_p** may be extracted from the digital broadcast signal **105** and stored, e.g., in the memory **115** or in the data storage **118**.

The selection of ancillary information **122** may be filtered from a geographic perspective based on device position

10 information. To facilitate such functionality, the receiving device **110** may optionally include a position location system **116**, such as a GPS receiver. For example, in the case of a mobile or hand-held device, GPS data may be used to filter weather and traffic updates and limit downloads to those that

15 are relevant to the area in which the device is presently located. In some embodiments, the function of the position location system **116** may be implemented by one of the tuners **112** in conjunction with software running on the processor **114**. The position location signal may originate from one or more of

20 the towers **104**.

By way of example, a digital broadcast receiving device **200** may be configured to implement scheduled updating according to an embodiment of the present invention as shown in FIG. 1. By way of example, and without loss of generality, the receiving

25 device **200** may be implemented as part of a digital television set, personal computer, video game console, personal digital assistant, mobile or handheld device such as a cellular phone or personal digital assistant, portable email device and the like, or other digital device. The device **200** may include a

30 central processing unit (CPU) **205** and a memory **206** coupled to the CPU **205**. The CPU **205** may be configured to run software applications and, optionally, an operating system. Some embodiments of the present invention may take advantage of certain types of processor architecture in which the CPU **205**

35 includes a main processor **205A** and one or more auxiliary processors **205B**. Each auxiliary processor may have its own associated local data storage. One example, among others of such a processor architecture is a Cell Processor. An example

of a Cell Processor architecture is described in detail, e.g.,
in Cell Broadband Engine Architecture, copyright International
Business Machines Corporation, Sony Computer Entertainment
Incorporated, Toshiba Corporation August 8, 2005 a copy of
5 which may be downloaded at <http://cell.scei.co.jp/>, the entire
contents of which are incorporated herein by reference.

The memory **206** may store applications and data for use by the
CPU **205**. The memory **206** may be in the form of an integrated
circuit, e.g., RAM, DRAM, ROM, and the like). A computer
10 program **201** may be stored in the memory **206** in the form of
instructions that can be executed on the processor **205**. By
way of example, the program **201** may include instructions that
when executed by the processor cause implement a method for
accessing ancillary information embedded in a digital
15 broadcast data stream. The memory **206** may also store Control
data **202** extracted from a received digital broadcast signal.
The control data **202** may be used to selectively access
ancillary information **203**, which may also be stored in the
memory **206**. The memory may also store instructions for
20 implementing a search engine **204**, e.g., by executing the
search engine instructions with the CPU **205**. The search
engine **204** may be configured, e.g., by suitable programming,
to search for particular ancillary information **203** using
selected control data **202**.

25 The receiving device **200** may also include well-known support
functions **210**, such as input/output (I/O) elements **211**, power
supplies (P/S) **212**, a clock (CLK) **213** and cache **214**. The
device **200** may further include a fast data storage device **215**
such as a hard disk drive that provides non-volatile storage
30 for applications and data. The fast storage device **215** may be
used for temporary or long-term storage of files **216** retrieved
from a slower data storage device. By way of example, the
storage device **215** may be a fixed disk drive, removable disk
drive, flash memory device, tape drive. Alternatively,
35 storage device **215** may be, e.g., a CD-ROM, DVD-ROM, Blu-ray,
HD-DVD, UMD, or other optical storage devices. Files **216** from
a slower storage device may be temporarily stored in a faster

storage device in a hardware cache for quick loading into the memory **206**.

The device **200** may include a digital broadcast receiver **238** which may be coupled to an antenna **241**. One or more digital
5 broadcast tuners **242** may receive digital broadcast signals picked up by the antenna **241**. The receiver **238** may further include a decoder **244**, which may implement the functions described above.

One or more user input devices **220** may be used to communicate
10 user inputs from one or more users to the system **200**. By way of example, one or more of the user input devices **220** may be coupled to the client device **200** via the I/O elements **211**. Examples of suitable input device **220** include keyboards, mice, joysticks, touch pads, touch screens, remote control units,
15 light pens, still or video cameras, and/or microphones.

The client device **200** may include a network interface **225** to facilitate communication via an electronic communications network **227**. The network interface **225** may be configured to
20 implement wired or wireless communication over local area networks and wide area networks such as the Internet. The system **200** may send and receive data and/or requests for files via one or more message packets **226** over the network **227**.

The system **200** may further comprise a graphics subsystem **230**, which may include a graphics processing unit (GPU) **235** and
25 graphics memory **240**. The graphics memory **240** may include a display memory (e.g., a frame buffer) used for storing pixel data for each pixel of an output image. The graphics memory **240** may be integrated in the same device as the GPU **235**, connected as a separate device with GPU **235**, and/or
30 implemented within the memory **206**. Pixel data may be provided to the graphics memory **240** directly from the CPU **205**. Alternatively, the graphics unit may receive video signal data extracted from a digital broadcast signal from the decoder
244. Alternatively, the CPU **205** may provide the GPU **235** with
35 data and/or instructions defining the desired output images, from which the GPU **235** may generate the pixel data of one or

more output images. The data and/or instructions defining the desired output images may be stored in memory **206** and/or graphics memory **240**. In an embodiment, the GPU **235** may be configured (e.g., by suitable programming or hardware
5 configuration) with 3D rendering capabilities for generating pixel data for output images from instructions and data defining the geometry, lighting, shading, texturing, motion, and/or camera parameters for a scene. The GPU **235** may further include one or more programmable execution units capable of
10 executing shader programs.

The graphics subsystem **230** may periodically output pixel data for an image from the graphics memory **240** to be displayed on a video display device **250**. The video display device **250** may be any device capable of displaying visual information in
15 response to a signal from the device **200**, including CRT, LCD, plasma, and OLED displays that can display text, numerals, graphical symbols or images. The digital broadcast receiving device **200** may provide the display device **250** with a display driving signal in analog or digital form, depending on the
20 type of display device. In addition, the display **250** may include one or more audio speakers that produce audible or otherwise detectable sounds. To facilitate generation of such sounds, the client device **200** may further include an audio processor **255** adapted to generate analog or digital audio
25 output from instructions and/or data provided by the CPU **205**, memory **206**, and/or storage **215**.

The receiving device **200** may optionally include a position location device **270**. Such a device may be based on any suitable technology capable of providing information on the
30 geographic location of a device. Examples of existing technology include global positioning satellite (GPS) technology, inertial guidance technology, and the like. Information from such devices may be used in digital broadcast data applications such as navigation for mobile or hand-held
35 devices.

The components of the device **200**, including the CPU **205**, memory **206**, support functions **210**, data storage devices **215**,

user input devices **220**, network interface **225**, graphics unit **230**, audio processor **255** and position location device **270** may be operably connected to each other via one or more data buses **260**. These components may be implemented in hardware,
5 software or firmware or some combination of two or more of these.

By way of example, and not by way of limitation, the program **201** may locate and present ancillary information in accordance with a method **300** depicted in the flow diagram of FIG. 3. As
10 indicated at **302** the receiving device **200** may receive a digital television broadcast signal **301**. The digital broadcast signal **301** includes coded data representing one or more video images **303** and control data **305** associated with one or more visual components of the images **303**. The decoder **244**
15 may convert the coded control image data **303** into image data usable by the graphics subsystem **230** and display **250**. The decoder **244** may similarly convert the coded control data **305** to control data **202** usable by the program **201** and CPU **205**.

By way of example, the broadcast signal may be configured as
20 depicted in FIG. 4. Specifically, a digital broadcast signal **400** may include data representing one or more video frame groups **402**, **404**, **406**. Each frame group may have a group header **408** and a plurality of video frames **F**. The frames **F₁...F_n**, within the frame groups **402**, **404**, **406** may be related to each
25 other within some context. For example, the frames within a given frame group may be part of particular, scene, shot or sequence of scenes or shots. The scenes or shots may be related by virtue of containing the same characters or objects or may be related to each other in terms of where they occur
30 in the course of the plot of a particular program or episode.

In some embodiments, the control data associated with a corresponding video frame group may be included in the group header for that frame group. By way of example a group header **408** may be associated with a frame group **402** containing data
35 for video frames **F₁**, **F₂** and **F₃**. By way of example the group header **408** may be a data packet containing the control data in some coded form that may be utilized by the program **201**.

Examples of suitable control data include, but are not limited to, information identifying the particular broadcast channel, sub-channel, program or frame group with which the control data is associated. Furthermore, the control data may
5 identify particular visual components within the frames **F₁**, **F₂**, **F₃**, that make up the frame group **402**. In addition, the control data may identify a location of ancillary information associated with one or more visual components of the frames **F**.

By way of example, program **201** may include a network protocol
10 stack that may be used to facilitate communication over the network **227**. The control data in the header **408** may include mark-up language code (e.g., HTML, XML and the like) that provides a universal resource locator (URL) for network resource (e.g., a website) from which ancillary information
15 may be obtained. Alternatively, the control data in the header **408** may include text descriptors that may be used as inputs to the search engine **204**.

As indicated at **304**, the video images corresponding to the image data **303** may be presented, e.g., using the display
20 device **250**. As indicated at **306**, the program **201** may use the control data **202** to present a perceptible indication that ancillary information is associated with the one or more visual components in conjunction with presenting the one or more video images with the display device. For example, as
25 shown in FIG. 5A, the display **250** may display a symbol **502** that is associated with the presence of ancillary information associated with a video image **504** (or group of such images) that is concurrently displayed. The presence of a symbol notifies a percipient **506** of the availability of the ancillary
30 information. For the purposes of this disclosure, a percipient is one whose senses are stimulated by an output from the display device **250**.

In some embodiments, the program **201** may optionally be configured to present guiding information that directs the
35 percipient **506** to the ancillary information, as indicated at **308**. As indicated at **310**, the program **201** may use the control data **202** to present or store the ancillary information in

response to an input signal **309**. By way of example, and not by way of limitation, the control data **305** associated with the image **504** may include a URL for a web page associated with a frame group that includes the image **504**. The web page may
5 display the ancillary information in any suitable form. For example, the ancillary information may be in the form of links to various sources of information related to the visual components of the image **504**. Such links may be grouped according to their association with a particular visual
10 component of the image **504**. Such links may be activated, e.g., through a signal from the interface **220**.

For example, the user interface **220** may be in the form of a remote control of a type commonly used with a television set or DVR. The interface **220** may include a pause button **221** and
15 one or more control buttons **223** which may include arrow buttons and numbered buttons. The percipient **506** may see something of interest in the image **504**. In such a case, the percipient **506** may activate the pause button **221** to freeze the display of the program of which the image **504** is a part.
20 Ancillary information **203** may be presented by the display **250** or stored in the memory **206** or storage **215** in response to a signal initiated by the percipient's activation of the pause button **221** or by a signal generated in response to activation of one or more of the control buttons **223** or some combination
25 of both.

The program **201** may use the control data **202** to access ancillary information **203** residing in the memory **206** or storage **215** or remote ancillary information residing on one or more servers **229** coupled to the network **227**. The program **201**
30 may utilize one or more portions of the control data **202** as input to a search engine **204** resident in memory **206** or may access a remote search engine server **228** via the network interface **226** and the network **227** for this purpose. By way of example, the control data **202** may include text descriptors
35 associated with visual components of the video images as inputs to the search engine **204** or the search engine server **229**.

There are a number of ways in which guiding information or ancillary information may be presented. For example, suppose that the image **504** depicts an automobile **510**, a soft drink can **512**, a laptop computer **514**, an actor **516** portraying a character and wearing clothes **518** and shoes **520**. Upon receipt of the signal from the interface **220**, the program **201** may use the control data **202** associated with the image **504** to cause the display **250** to present a menu **530**, as shown in FIG. 5B containing listings **510B**, **512B**, **514B** and **516B** for the automobile **510**, soft drink can **512**, laptop **514** and actor **516**. Each of these listings may provide ancillary information (e.g., in the form of text or images) or guiding information associated with ancillary information. Guiding information may be in the form of links to information resident in the memory **206**, storage **215** or at the remote server **229**. In the example depicted in FIG. 5B a particular listing may be selected, e.g., using left-right or up-down arrow keys on the interface **220**. A given link within a listing may be activated by pressing a numbered control button on the interface **220** corresponding to a number listed next to the link.

By way of example, listing **510B** for the automobile **510** may include links to web pages describing the history of the particular make and model of automobile, an advertisement for a dealership that sells that particular make or model, or for a dealership that sells the tire depicted on the automobile **510**. The listing **512B** for the soft drink can **512** may include links to the web page of the soft drink company, an advertisement for the soft drink or a coupon for the soft drink. The listing **514B** for the laptop computer **514** may include a links to websites for the laptop manufacturer or dealer, reviews of the particular brand of laptop depicted or technical help for the laptop. The listing **516B** for the actor **516** may include links to information regarding either the actor or the character portrayed or information regarding the clothes **518** or shoes **520** that the actor is wearing in the image **504**.

In some embodiments, information guiding the percipient to the ancillary information may be superposed over one or more of the video images presented by the display. For example, as shown in FIG. 5C, a program may be paused at a particular

5 frame **505**, in response to a signal from the input device **220** that is generated when the pause button **221** is activated. The program **201** may highlight certain visual components within the image in a manner perceptible to a percipient **506** if those components have ancillary information associated with them.

10 Highlighted regions of a video image that are associated with ancillary data are sometimes referred to herein as "hotspots". By way of example, and not by way of limitation, as shown in FIG. 5C, portions of the image **504** containing the automobile **510**, soft drink can **512**, laptop **514**, and actor **516** may be

15 surrounded by dashed polygons **510'**, **512'**, **514'** and **516'**, that mark the boundaries of hotspots. In addition, the actor's clothes **518** and shoes **520** may be shaded to stand out from the rest of the image **504**, thereby identifying these regions as hotspots.

20 Digital links to the ancillary information associated with these visual components may be associated with the corresponding portions of the image **504** that mark the hotspots. The ancillary information associated with a particular visual component may be presented in response to a

25 selection input. For example, the input device may include selection buttons that can be used to select the particular image portion. Alternatively, the display device **250** may include a touch screen on which the image **504** is displayed. In such a case, a particular highlighted portion of the image

30 **504** may be selected by touching the corresponding region of the touch screen on which it is presented. The information guiding the percipient to the ancillary information (or the ancillary information itself) may be presented in the form of "bubble text" **522** that appears next to the corresponding

35 portion of the image **504**. The "bubble text" **522** may include one or more links **524** to resources containing the ancillary information.

In some embodiments, ancillary information (or guiding information) may be stored for later review. For example, ancillary information retrieved from the remote source **229** may be stored in the memory **206** or the storage device **215**. In
5 some implementations of this embodiment, stored ancillary information (or guiding information) may be subsequently retrieved. By way of example, and not by way of limitation, FIG. 5D illustrates an example of a presentation of saved guiding information **540** presented on the display device **250**.
10 In this example, the guiding information is in the form of a plurality of menu lists **542**. Each menu list may correspond to a particular program or episode of a particular program. The lists may be broken down by frame group, with each list corresponding to a different frame group. The program **201** may
15 generate the lists as the percipient **506** selects ancillary information or guiding information to be saved. The lists **542** may include links to the ancillary information (or guiding information) for the frame group. For example, selecting the link marked group 1A may cause the program **201** to present a
20 menu, such as the menu **530** depicted in FIG. 5B.

According to another embodiment of the present invention a digital broadcast data stream may be provided as illustrated with respect to FIG. 6. According to a method **600**, video
25 control data **602** may be associated with one or more images **604** in a digital broadcast data stream **608**. By way of example, the control data may be associated with one or more visual components of one or more video images using an editor **606**.
By way of example, the editor may introduce time-varying
30 sensitive regions into portions of one or more video images. Examples of techniques for introducing such sensitive regions are described, e.g., in "Time-Varying Sensitive Regions in Dynamic Multimedia Objects: a Pragmatic Approach to Content-Based Retrieval from Video" by Victoria Burrill, Thomas Kirste
35 and Jochen Weiss, Information and Software Technology 1994, Volume 36, Number 4, the entire contents of which are incorporated herein by reference.

The digital broadcast data stream **608** may be coupled to a digital broadcasting unit **610**, which converts the digital broadcast data stream **608** to a digital broadcast signal **612**. The broadcasting unit **610** may be any system commonly used to
5 convert data to a format suitable for broadcast according to a digital broadcasting standard, such as the ATSC standard. The broadcasting unit may include a transmitter and broadcast tower with an antenna for transmitting the signal **612** over the airwaves. Alternatively, the broadcast signal **612** may be
10 transmitted to a separate transmitting unit for this purpose.

The control data **602** may be configured to facilitate access to ancillary data associated with the visual components when the digital broadcast signal **612** is received and/or the video images **604** are displayed, as discussed above. By way of
15 example, the control data **602** may be associated with one or more objects depicted in one or more of the video images or a context of the one or more video images. The control data **602** may identify one or more hotspots associated with one or more of the video images **604**. Each hotspot may provide a link to
20 ancillary information associated with one or more visual components in the hotspot. The control data **602** may be configured to cause a display device to present guiding information, as discussed above.

While the above is a complete description of the preferred
25 embodiment of the present invention, it is possible to use various alternatives, modifications and equivalents. Therefore, the scope of the present invention should be determined not with reference to the above description but should, instead, be determined with reference to the appended
30 claims, along with their full scope of equivalents. Any feature described herein, whether preferred or not, may be combined with any other feature described herein, whether preferred or not. In the claims that follow, the indefinite article "A", or "An" refers to a quantity of one or more of
35 the item following the article, except where expressly stated otherwise. The appended claims are not to be interpreted as including means-plus-function limitations, unless such a limitation is explicitly recited in a given claim using the

phrase "means for".

WHAT IS CLAIMED IS:

- 1 1. In a digital broadcast receiving device configured to
2 receive programming and data over a plurality of digital
3 broadcast channels, a method for accessing ancillary
4 information associated with one or more images embedded in a
5 digital broadcast data stream, the method comprising:
6 a) receiving a digital television broadcast signal, wherein
7 the digital broadcast signal includes data representing one
8 or more video images and control data associated with one or
9 more visual components of the one or more video images;
10 b) presenting the one or more video images on a video
11 display device associated with the digital broadcast
12 receiving device;
13 c) using the control data to present or store a perceptible
14 indication that ancillary information is associated with the
15 one or more visual components in conjunction with presenting
16 the one or more video images with the display device; and
17 d) using the control data to present or store the ancillary
18 information with the display device in response to an input
19 signal.
- 1 2. The method of claim 1, wherein the control data is
2 associated with one or more objects depicted in one or more
3 of the video images.
- 1 3. The method of claim 1 wherein the control data is associated
2 with a context associated with the one or more video images.
- 1 4. The method of claim 1 wherein c) includes displaying the
2 perceptible indication with the display device while
3 presenting the one or more video images.
- 1 5. The method of claim 1 wherein c) includes presenting
2 information guiding a percipient to the ancillary
3 information associated with the control data using the
4 display device.

- 1 6. The method of claim 5 wherein c) includes superposing the
2 information guiding the percipient to the ancillary
3 information over one or more of the video images.
- 1 7. The method of claim 5 wherein the information guiding the
2 percipient to the ancillary information includes one or more
3 links to one or more resources accessible via an electronic
4 communications network.
- 1 8. The method of claim 7 wherein d) includes accessing the one
2 or more resources via the one or more links in response to
3 the input signal.
- 1 9. The method of claim 5 wherein the information guiding the
2 percipient to the ancillary information includes a video
3 image identifying the one or more visual components, wherein
4 the image includes one or more links, each link being
5 associated with one or more of the visual components,
6 wherein each link is configured to provide access to the
7 ancillary information associated with the corresponding
8 visual component.
- 1 10. The method of claim 1 wherein c) includes pausing
2 presentation of a program containing the one or more video
3 images at a particular image of the one or more video images
4 in response to a pause signal, highlighting the one or more
5 visual components in a manner perceptible to a percipient,
6 and associating one or more links to the ancillary
7 information associated with the one or more visual
8 components.
- 1 11. The method of claim 10 wherein d) includes presenting the
2 ancillary information associated with a particular visual
3 component of the one or more visual components in response
4 to a selection input.
- 1 12. The method of claim 1 wherein d) includes storing the
2 ancillary information in a memory associated with the
3 digital broadcast receiving device and/or display device.

1 13. The method of claim 1 wherein d) includes using the
2 control data as an input to a search engine coupled to the
3 digital broadcast receiving device and/or display device and
4 conducting a search with the search engine.

1 14. The method of claim 1 wherein the input signal is a
2 signal from a remote control associated with the digital
3 broadcast receiving device.

1 15. The method of claim 1 wherein the ancillary information
2 includes one or more advertisements.

1 16. A digital broadcast receiving device, comprising:
2 a receiver unit configured to receive programming and data
3 over one or more digital broadcast channels,
4 a processor coupled to the receiver unit;
5 a memory coupled to the processor;
6 a set of processor readable instructions embodied in the
7 memory for execution on the processor, the instructions
8 being configured to implement a method for accessing control
9 data associated with one or more images embedded in a
10 digital broadcast data stream, the method comprising:
11 a) receiving a digital television broadcast signal, wherein
12 the digital broadcast signal includes data representing one
13 or more video images and control data associated with one or
14 more visual components of the one or more video images;
15 b) presenting the one or more video images on a video
16 display device associated with the digital broadcast
17 receiving device;
18 c) using the control data to present or store a perceptible
19 indication that ancillary information is associated with the
20 one or more visual components in conjunction with presenting
21 the one or more video images with the display device; and
22 d) using the control data to present or store the ancillary
23 information with the display device in response to an input
24 signal.

1 17. The device of claim 16, further comprising the video
2 display device, wherein the video display device is operably
3 coupled to the processor.

1 18. The device of claim 16, further comprising a backchannel
2 coupled to the processor.

1 19. The device of claim 18, wherein the backchannel comprises
2 a network interface coupled to an electronic communications
3 network.

1 20. The device of claim 16 wherein c) includes displaying the
2 perceptible indication with the display device while
3 presenting the one or more video images.

1 21. The device of claim 16 wherein c) includes presenting
2 information guiding a percipient to the ancillary
3 information associated with the control data using the
4 display device.

1 22. The device of claim 21 wherein c) includes superposing
2 the information guiding a percipient to ancillary
3 information over one or more of the video images.

1 23. The device of claim 21 wherein the information guiding
2 the percipient to the ancillary information is in the form
3 of one or more links to one or more resources accessible via
4 an electronic communications network.

1 24. The device of claim 23 wherein the one or more links are
2 configured to access the one or more resources in response
3 to the input signal.

1 25. The device of claim 21 wherein the information guiding
2 the percipient to the ancillary information includes a video
3 image identifying the one or more visual components, wherein
4 the image includes one or more links, each hot link being
5 associated with one or more of the visual components,
6 wherein each hot link is configured to provide access to the
7 ancillary information associated with the corresponding
8 visual component.

1 26. The device of claim 16 wherein c) includes pausing
2 presentation of a program containing the one or more video
3 images at a particular image of the one or more video images
4 in response to a pause signal, highlighting the one or more
5 visual components in a manner perceptible to a percipient,
6 and associating one or more links to the ancillary
7 information associated with the one or more visual
8 components.

1 27. The device of claim 26 wherein d) includes presenting the
2 ancillary information associated with a particular visual
3 component of the one or more visual components in response
4 to a selection input.

1 28. The device of claim 16 wherein d) includes storing the
2 ancillary information in the memory.

1 29. The device of claim 16, further comprising a search
2 engine coupled to the digital broadcast receiving device
3 and/or a display device that is interoperable with the
4 digital broadcast receiving device, wherein e) includes
5 using the control data as an input to the search engine
6 coupled and conducting a search with the search engine.

1 30. The device of claim 16, further comprising a remote
2 control configured to interoperate with the processor,
3 wherein the input signal is a signal from the remote
4 control.

1 31. A method for providing a digital broadcast data stream
2 having control data associated with one or more images in a
3 digital broadcast data stream, the method comprising:
4 a) associating control data with one or more visual
5 components of one or more video images, wherein the control
6 data facilitates access to ancillary data associated with
7 the one or more visual components by a receiving device
8 and/or display device usable with a digital broadcast signal
9 generated from the digital broadcast data stream;
10 b) combining the control data and the video images into a
11 digital broadcast data stream.

1 32. The method of claim 31, wherein the control data is
2 associated with one or more objects depicted in one or more
3 of the video images.

1 33. The method of claim 31 wherein the control data is
2 associated with a context of the one or more video images.

1 34. The method of claim 31, further comprising c)
2 broadcasting the digital broadcast data stream as a digital
3 broadcast signal.

1 35. The method of claim 31 wherein the control data
2 identifies one or more hotspots associated with one or more
3 video images, wherein each hotspot provides a link to
4 ancillary information associated with the one or more visual
5 components.

1 36. The method of claim 31 wherein the control data is
2 configured to cause the display device to present
3 information guiding a percipient to the ancillary
4 information associated with the control data.

1 37. The method of claim 36 wherein the control data is
2 configured to superpose the information guiding the
3 percipient to the ancillary information over one or more of
4 the video images.

1 38. The method of claim 36 wherein the information guiding
2 the percipient to the ancillary information includes a video
3 image identifying the one or more visual components, wherein
4 the image includes one or more links, each hot link being
5 associated with one or more of the visual components,
6 wherein each hot link is configured to provide access to the
7 ancillary information associated with the corresponding
8 visual component.

1 39. The method of claim 31 the control data is configured to
2 pause presentation of a program containing the one or more
3 video images at a particular image of the one or more video
4 images in response to a pause signal, highlight the one or

5 more visual components in a manner perceptible to a
6 percipient, and associate one or more links to the ancillary
7 information associated with the one or more visual
8 components.

1 40. The method of claim 39 wherein the control data is
2 configured to present the ancillary information associated
3 with a particular visual component of the one or more visual
4 components in response to a selection input.

1 41. The method of claim 31 wherein the control data includes
2 input for a search engine.

1 42. The method of claim 31 wherein the ancillary information
2 includes one or more advertisements.

1 43. The method of claim 31 wherein the control data is
2 configured to cause the display to present a perceptible
3 indication that ancillary information is associated with the
4 one or more visual components in conjunction with presenting
5 the one or more video images with the display device

1 44. The method of claim 43 wherein the control data is
2 configured to cause the display to present the perceptible
3 indication while presenting the one or more video images.

1 45. The method of claim 31 wherein the control data is
2 configured to cause the display device to present
3 information guiding a percipient to the ancillary
4 information associated with the control data.

1 46. The method of claim 45 wherein the control data is
2 configured to cause the display device to superpose the
3 information guiding the percipient to the ancillary
4 information over one or more of the video images.

1 47. The method of claim 45 wherein the information guiding
2 the percipient to the ancillary information includes one or
3 more links to one or more resources accessible via an
4 electronic communications network.

1 48. The method of claim 47 wherein the one or more links are
2 configured to be activated in response to the input signal.

1 49. The method of claim 45 wherein the information guiding
2 the percipient to the ancillary information includes a video
3 image identifying the one or more visual components, wherein
4 the image includes one or more links, each hot link being
5 associated with one or more of the visual components,
6 wherein each hot link is configured to provide access to the
7 ancillary information associated with the corresponding
8 visual component.




FIG. 1




FIG. 2

3/6




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B

5/6




FIG. 5C




FIG. 5D

6/6




FIG. 6

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2009/043389

A. CLASSIFICATION OF SUBJECT MATTER IPC(8) - H04N 7/173 (2009.01) USPC - 725/43 According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC(8) - H04N 7/173 (2009.01) USPC - 725/43 Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) Google Patents; PatBase		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X — Y Y Y Y Y	US 2002/0129366 A1 (SCHEIN et al) 12 September 2002 (12.09.2002) entire document US 2003/0005441 A1 (INOUE) 02 January 2003 (02.01.03) entire document US 2001/0013123 A1 (FREEMAN et al) 09 August 2001 (09.08.2001) entire document US 2002/0174438 A1 (CLEARY et al) 21 November 2002 (21.11.2002) entire document US 2004/0194149 A1 (KESSLER) 30 September 2004 (30.09.2004) entire document	1-5, 7-9, 12-17, 20, 21, 23-25, 28-30 — 6, 10, 11, 18, 19, 22, 26, 27, 31-49 6, 22, 37, 46 18, 19 10, 11, 26, 27, 39, 40 31-49
<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input type="checkbox"/>		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
Date of the actual completion of the international search 17 June 2009		Date of mailing of the international search report <p align="center" style="font-size: 1.2em;">01 JUL 2009</p>
Name and mailing address of the ISA/US Mail Stop PCT, Attn: ISA/US, Commissioner for Patents P.O. Box 1450, Alexandria, Virginia 22313-1450 Facsimile No. 571-273-3201		Authorized officer: Blaine R. Copenheaver PCT Helpdesk: 571-272-4300 PCT OSP: 571-272-7774