



US 20110270449A1

(19) **United States**

(12) **Patent Application Publication**
Nickerson et al.

(10) **Pub. No.: US 2011/0270449 A1**

(43) **Pub. Date: Nov. 3, 2011**

(54) **MODULAR AND EXPANDABLE IRRIGATION CONTROLLER**

(60) Provisional application No. 60/532,498, filed on Dec. 23, 2003, provisional application No. 60/418,894, filed on Oct. 15, 2002.

(75) Inventors: **Harvey J. Nickerson**, San Diego, CA (US); **Russel D. Leatherman**, Albion, IN (US); **Andrew M. Nguyen**, San Diego, CA (US); **Susan E. Basch**, San Diego, CA (US); **Sergio R. Perez Araujo**, San Diego, CA (US); **Jose Macias Galarza**, Tijuana (MX); **Bill Merkt**, San Diego, CA (US); **Adam A. Dunford**, Chula Vista, CA (US)

(73) Assignee: **RAIN BIRD CORPORATION**, Azusa, CA (US)

(21) Appl. No.: **13/182,418**

(22) Filed: **Jul. 13, 2011**

Related U.S. Application Data

(63) Continuation of application No. 12/204,747, filed on Sep. 4, 2008, now Pat. No. 7,996,115, which is a continuation of application No. 11/022,179, filed on Dec. 23, 2004, now Pat. No. 7,444,207, which is a continuation-in-part of application No. 10/687,352, filed on Oct. 15, 2003, now Pat. No. 7,257,465.


Publication Classification

(51) **Int. Cl.**
G05D 7/06 (2006.01)

(52) **U.S. Cl.** **700/284**

(57) **ABSTRACT**

Described herein are several embodiments relating to modular irrigation controllers. In many implementations, the irrigation controllers are modular in that various functional components of the irrigation controller are implemented in removable modules that when inserted into position within the controller, expand the capabilities of the controller. Also described are various different types of expansion modules that may be coupled to the modular controller, having as variety of functions and features, as well as related methods of use and configuration of these modules in the controller. In one implementation, an expansion module is provided that includes a microcontroller capable of sending and receiving data communications to and from a main microcontroller of the controller that executed irrigation programs, the data communications relating to an irrigation program.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 8




FIG. 7




FIG. 9




FIG. 11

RIBBON CABLE 49
INTERFACE PIN ASSIGNMENTS

NOT CONNECTED	○	○	NOT CONNECTED
ENUM-FREQ	○	○	SMB-DO
12V-UNREG-RTN	○	○	SMB-DI
12V-UNREG-RTN	○	○	REMOTE-DI
REMOTE-DO	○	○	I-SENSE-OUT
MV _n	○	○	MV2 _n
BM-LED _n -OUT	○	○	SENSOR-FTR
BM-STATUS	○	○	SENSOR2-FTR
NOT CONNECTED	○	○	NOT CONNECTED
AC-FUSE	○	○	AC-FUSE
AC-FUSE-S	○	○	NOT CONNECTED
AC-COM	○	○	AC-COM

FIG. 12




FIG. 13




FIG. 14

EXPANSION MODULE CIRCUITRY
66




FIG. 15

CONTROL PANEL CIRCUITRY

31




FIG. 16

FIG. 17





FIG. 18






FIG. 19




FIG. 21

FIG. 20

EXTERNAL HOUSING EXPANSION PORT 62
PIN ASSIGNMENTS

ENUM-FREQ	○
SBM-DO	○
SBM-DI	○
I-SENSE-OUT	○
AC-FUSE	○
AC-FUSE	○
AC-FUSE-S	○
AC-FUSE-S	○
AC-COM	○
AC-COM	○

FIG. 22




FIG. 23A




FIG. 23B

IRRIGATION CONTROLLER CONTROLLER 10 MODULE ENUMERATION PROCESS





FIG. 24

LCD 24
PIN ASSIGNMENTS


V5	○
V4	○
V3	○
V2	○
V1	○
C2-	○
C2+	○
C1+	○
C1-	○
C3+	○
Vout	○
Vss	○
Vdd	○
D7	○
D6	○
D5	○
D4	○
D3	○
D2	○
D1	○
D0	○
RDn	○
WRn	○
A0	○
RESn	○
Cs1n	○

FIG. 25



COMMUNICATIONS INTERFACE PORT 34a
PIN ASSIGNMENTS

FIG. 26



SOCKET APPLICATION PROGRAMMING INTERFACE

FIG. 27




FIG. 28




FIG. 29




FIG. 30

ENUMERATION PINS - DIODE ARRANGEMENTS




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35

Troubleshooting

1 - Confirm Programs
2 - Test All Valves

1 2

FIG. 36

Select "1"

Confirm Programming

1 - Review Program
2 - Program Run Time
3 - Valve Run Time

1 2 3 Back

FIG. 37

Select "1"

PGM A

Watering Start Times

1	1:00am	6	12:00pm
2	4:30am	7	3:45pm
3	5:30am	8	5:30pm
4	7:00am		
5	9:00am		

Back Next

FIG. 38A

Select "Next"




FIG. 38B




FIG. 39A

Select "Next"

Or:




FIG. 39B

Or:




FIG. 39C

Or:




FIG. 39D

Or:




FIG. 39E

PGM A			
Watering Days			
Mon	ON	Sat	ON
Tue	ON	Sun	OFF
Wed	ON		
Thur	OFF		
Fri	ON		
		Back	Next

FIG. 40

Select "Next"

PGM A Run Times	
Valve	HH : MM
01	0 : 22
02	0 : 27
03	0 : 22
04	0 : 25
05	0 : 19
+	-
	Back
	Next

FIG. 41

Select "Next"

PGM A	
Seasonal Adjust	
115%	
	Back
	Next

FIG. 42

Select "Next"

Rain Delay
2
Days Remaining
Back Next

FIG. 43

Select "Next"

Calendar Day Off
Jan 1 On
Day
+ - Back Next

FIG. 44

Select "Next"

PGM A Valve Delay
0 : 01 : 06
Hrs Min Sec
Back Next

FIG. 45

Select "Next"

Cycle + Soak Valve	Minutes	
	Cycle	Soak
01	10	15
02	15	10
03	5	5
04	10	7
05	14	7
+ -	Back	Next

FIG. 46A

Select "Next"

Press "+" or "-" will scroll through all valves if they are programmed, for example, press "+" once:

Cycle + Soak Valve	Minutes	
	Cycle	Soak
02	15	10
03	5	5
04	5	5
05	14	7
06	9	5
+ -	Back	Next

FIG. 46B

Press "+" again:

Cycle + Soak Valve	Minutes	
	Cycle	Soak
03	5	5
04	5	5
05	14	7
06	9	5
07	5	6
+ -	Back	Next

FIG. 46C

Keep on pressing "+", the display will scroll to the last entry:

Cycle + Soak Valve		Minutes Cycle	Soak
08		18	12
+	-	Back	Next

FIG. 46D

Master Valve or Pump			
1 Off			
Valve			
+	-	Back	Next

FIG. 47

Select "Next"

Press "+" or "-" will scroll through all "Off" valves.

Sensor Override			
1 On			
Valve			
+	-	Back	Next

FIG. 48

Select "Next"

Press "+" or "-" will scroll through all valves settings if they are programmed for "Sensor Override"

PGM A
Total Run Time
Hrs Min
0 : 40

Back

FIG. 49

Valve Run Times
Per Watering Day
Valve **01** HH:MM
PGM A 0:04
PGM B 0:06
PGM C 0:04
PGM D 0:00

+ - Back

FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 56




FIG. 56A





FIG. 57






FIG. 61




FIG. 62







FIG. 63



SMART MODULE
226

FIG. 65






FIG. 68




FIG. 69

MODULAR AND EXPANDABLE IRRIGATION CONTROLLER

[0001] This application is a continuation of U.S. application Ser. No. 12/204,747, filed Sep. 4, 2008 (Docket No. 8473-92163), which is a continuation of U.S. application Ser. No. 11/022,179, filed Dec. 23, 2004 (Docket No. 8473-81858), now U.S. Pat. No. 7,444,207 which claims the benefit of U.S. Provisional Application No. 60/532,498, filed Dec. 23, 2003 (Docket No. 45067-RB). U.S. application Ser. No. 11/022,179 is also a continuation-in-part of U.S. application Ser. No. 10/687,352, filed Oct. 15, 2003 (Docket No. 8473-82887), now U.S. Pat. No. 7,257,465, which claims the benefit of U.S. Provisional Application No. 60/418,894, filed Oct. 15, 2002 (Docket No. RB-40990). All of these applications are incorporated herein by reference.

FIELD OF INVENTION

[0002] This invention relates to an irrigation controller for controlling the operation of an irrigation system. In particular, this invention relates to a modular irrigation controller with expandable features.

BACKGROUND OF THE INVENTION

[0003] Modular irrigation controllers use optional modules that can be added to the controller to increase the number of irrigation stations that may be controlled by the controller. For example, U.S. Pat. No. 5,956,248 No. (William et al.) provides an irrigation controller having a housing that encloses a microprocessor that stores and executes watering programs, and includes station modules that can be added within the housing to increase the number of irrigation stations controlled. Additionally, U.S. Pat. No. 5,262,936 (Faris et al.) provides a controller having a base unit for actuating a predetermined minimum number of irrigation stations. External station expansion modules can be added to the base unit for increasing the number of irrigation stations controlled by the controller. Also described are optional pump modules and accessory timer modules that behave the same as the station modules in that they provide an electrical output signal to a pump or to an accessory (such as a light), instead of to an irrigation station. However, the expansion modules in these patents simply act as additional station outputs (e.g., a conduit extension of the logic inside the controller and only include driver circuitry responsive to commands from the base unit) and do not provide any additional functionality or intelligence. In order to add functionality to these controllers apart from adding additional station outputs (e.g., to control additional stations or accessories), a user would have to purchase another irrigation controller configured with the desired functionality.

[0004] There exists, therefore, a need for an improved irrigation controller with a flexible and expandable architecture modular design, along with an enhanced communications to the modules that will provide enough flexibility for further additions to an irrigation system, not only to include additional output stations, but also to upgrade to new features and capabilities of expansion and re-configuration.

BRIEF SUMMARY OF THE INVENTION

[0005] Several embodiments of the present invention answer the above and other needs by providing an irrigation

controller with flexible and expandable capabilities for controlling the operation of an irrigation system. In accordance with some several embodiments, the irrigation controller includes a base unit with a removable and programmable control panel and a bus for communicating with a plurality of removable modules capable of performing a variety of functions and expanding the capacity of the irrigation controller beyond the physical limitations of its housing. Also provided are various expansion modules having additionally functionality and related methods and features for use in the modular irrigation controllers described herein as well as in other irrigation control systems.

[0006] In one embodiment, the invention may be characterized as a modular irrigation controller comprising: a housing; a control unit within the housing, the control unit including a first microcontroller for executing stored irrigation programs; a first expansion module removably mounted within the housing and electrically coupled to the first microcontroller, the first expansion module including driver circuitry for actuating irrigation valves in accordance with control signals received from the first microcontroller; and a second expansion module removably mounted within the housing and electrically coupled to the first microcontroller, the second expansion module including a second microcontroller capable of sending and receiving data communications to and from the first microcontroller, the data communications relating to an irrigation program.

[0007] In another embodiment, the invention may be characterized as a modular irrigation controller comprising: a housing; a control unit within the housing, the control unit including a main microcontroller for executing stored irrigation programs; a plurality of expansion module mounting locations within the housing configured to removably receive expansion modules, each expansion module mounting location electrically coupled to the main microcontroller; and a first expansion module removably mounted to a first expansion module mounting location and electrically coupled to the main microcontroller, the first expansion module including a first microcontroller, the first microcontroller configured to operate with the main microcontroller and provide additional functionality not present in the capabilities of the main microcontroller.

[0008] In yet another embodiment, the invention may be characterized as an expansion module for a modular irrigation controller comprising: a housing; an electrical connector configured to removably connect to one of a plurality of expansion module mounting locations of a modular irrigation controller; and a microcontroller within the housing and coupled to the electrical connector, the microcontroller configured to operate with a control unit of the modular irrigation controller and provide additional control functionality not present in the capabilities of the control unit.

[0009] In another embodiment, the invention may be characterized as a modular irrigation controller comprising: a housing; a control unit within the housing, the control unit including a first microcontroller for executing stored irrigation programs; a plurality of expansion module mounting locations within the housing configured to removably receive expansion modules, each expansion module mounting location electrically coupled to the first microcontroller; an expansion module removably mounted to a first expansion module mounting location and electrically coupled to the first microcontroller, the expansion module including a second microcontroller, the second microcontroller configured to operate with the first microcontroller; wherein the first microcontrol-

ler is configured to send data corresponding to the stored irrigation programs to the second microcontroller upon request by the second microcontroller.

[0010] In yet another embodiment, the invention may be characterized as a modular irrigation controller comprising: a housing; a control unit within the housing, the control unit including a main microcontroller for executing stored irrigation programs; a plurality of expansion module mounting locations within the housing configured to removably receive expansion modules, each expansion mounting location electrically coupled to the main microcontroller; a first expansion module configured to be removably and non-sequentially connected to any one of the plurality of expansion module mounting locations, the first expansion module having a first microcontroller and including driver circuitry for actuating irrigation valves in accordance with control signals received from the main microcontroller, wherein the first microcontroller is configured to allow the first expansion module to be removably and non-sequentially connected to any one of the plurality of expansion module mounting locations.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The above and other aspects, features and advantages of several embodiments of the present invention will be more apparent from the following more particular description thereof, presented in conjunction with the following drawings.

[0012] FIG. 1 is a three dimensional view of the irrigation controller according to one embodiment of the present invention.

[0013] FIG. 2 is a front view of the open irrigation controller of FIG. 1 showing the control panel user interface and inside view of the door.

[0014] FIG. 3 is a three dimensional view of the open irrigation controller of FIG. 2 with the control panel also swung open, showing the backplane and its connection to the control panel through the ribbon cable.

[0015] FIG. 4 is a front view of the open irrigation controller of FIG. 2 showing the back of the control panel and the interior of the rear housing and having a portion of the control panel cut away to show a larger portion of the base module receptacle and having a portion of the backplane cover cut away to show the backplane circuitry underneath the backplane cover.

[0016] FIG. 5 is a three dimensional view of the irrigation controller of FIGS. 1-5 showing the base module and the expansion modules installed and the control panel detached.

[0017] FIG. 6 is an enlarged front view of the open controller of FIGS. 1-5 with the door cut away, control panel removed and showing the interior of the rear housing with the base module and the expansion modules installed.

[0018] FIG. 7 is an enlarged plan view of the base module.

[0019] FIG. 8 is an enlarged plan view of the expansion module.

[0020] FIG. 9 is three dimensional view of a base module showing the module latch buttons and the module interface connector.

[0021] FIG. 10 is a block diagram of one embodiment of the irrigation controller of FIGS. 1-7.

[0022] FIG. 11 is a block diagram of one embodiment of the control panel.

[0023] FIG. 12 is an illustration of one embodiment of the interface pin assignments for the ribbon cable connection between the control panel and the backplane circuitry.

[0024] FIG. 13 is a schematic diagram of one embodiment of the base module circuit.

[0025] FIG. 14 is a schematic diagram of one embodiment of an expansion module functioning as a station output module.

[0026] FIG. 15 is a schematic diagram of one embodiment of the control panel circuit.

[0027] FIG. 16 is a schematic diagram of one embodiment of the backplane circuit.

[0028] FIG. 17 is a block diagram of one embodiment of an expansion module functioning as an input module.

[0029] FIG. 18 is a block diagram of one embodiment of an expansion module functioning as a smart expansion module.

[0030] FIG. 19 is a block diagram showing the logical interaction of an expansion module functioning as a user interface extensible (configurable) module in accordance with one embodiment of the invention.

[0031] FIG. 20 is an illustration of one embodiment of the pinout assignments of the base module connector.

[0032] FIG. 21 is an illustration of one embodiment of the pinout assignments of the expansion module connector.

[0033] FIG. 22 is an illustration of one embodiment of the pinout configuration of the external expansion housing connector.

[0034] FIG. 23A illustrates the annular ring molded onto the control panel 30, running around the rotary switch post (not shown) and forming a barrier against water in accordance with one embodiment of the invention.

[0035] FIG. 23B is a cut away view of the annular ring of FIG. 23A taken at section A-A of FIG. 23A according to one embodiment.

[0036] FIG. 24 is a flow chart illustrating the module enumeration process in accordance with one embodiment of the invention.

[0037] FIG. 25 is an illustration of one embodiment of the pinout assignments for the liquid crystal display of the control panel.

[0038] FIG. 26 is an illustration of one embodiment of the pinout assignments for the external communications interface port.

[0039] FIG. 27 is an illustration of the socket application programming interface in accordance with one embodiment of the invention.

[0040] FIG. 28 is an illustration of the challenge/authenticate model in accordance with an embodiment of the invention.

[0041] FIG. 29 is an illustration of one embodiment of the module enumeration pin timing.

[0042] FIG. 30 is an illustration of generation of A0-A6 by a microcontroller in accordance with one embodiment of the invention.

[0043] FIG. 31 is an illustration of enumeration pins—diode arrangement in accordance with one embodiment of the invention.

[0044] FIG. 32 is a block diagram of one embodiment of an expansion module functioning as an interface extension smart module.

[0045] FIG. 33 is a block diagram of one embodiment of an expansion module functioning as a smart expansion module without any station inputs or outputs.

[0046] FIG. 34 is a block diagram of one embodiment of an expansion module functioning as a smart expansion module and including a display and a user input key.

[0047] FIG. 35 is one embodiment of a display screen sequence in which a user can select a user group, which then alters the display screen and programming sequence.

[0048] FIGS. 36-50 provide several embodiments of display screens for display on the LCD of user interface of the controller in accordance with one embodiment of the invention.

[0049] FIG. 51 is a three dimensional view of the open expansion housing showing the backplane and its expansion modules in accordance with one embodiment of the invention.

[0050] FIG. 52 is a perspective view of an enclosed housing or cabinet within which the new and improved irrigation controller according to another embodiment of the invention is contained.

[0051] FIG. 53 is a perspective view of the irrigation controller housing of FIG. 52, showing the housing door in an open position to reveal the control panel of the controller base unit.

[0052] FIG. 54 is a perspective view of the irrigation controller housing of FIG. 52 showing the base unit control panel in an open position and showing a base module and an expansion module mounted within the housing.

[0053] FIG. 55 is an expanded perspective view somewhat similar to FIG. 54, but showing the base module and the expansion module removed from the housing and having one additional expansion module and a smart module installed therein, and showing the control panel detached from the housing.

[0054] FIG. 56 is a front plan view of the controller housing with the door open and the with the base module locked in and two expansion modules and the Smart module placed on the insertion rail guides and with a portion of the backplane cover cut away to show the bay and the backplane circuitry underneath the backplane cover.

[0055] FIG. 56A is a fragmentary sectional view taken substantially along the line A-A of FIG. 5.

[0056] FIG. 57 is a front view of the open controller with the control panel opened to 180 degrees showing its back and revealing the interior of the base unit with all modules removed and with a portion of the backplane cover cut away to show the backplane circuit board underneath the backplane cover.

[0057] FIG. 58 is an enlarged plan view of the base module.

[0058] FIG. 59 is a perspective view, partially in cut-away section, of the expansion module, and showing the locking lever and the terminal blocks, and having a portion of the expansion module cut away to show the finger contacts connector.

[0059] FIG. 60 is an enlarged plan view of the smart module.

[0060] FIG. 61 is an exploded perspective view of a module, herein an expansion module, showing the module basic component parts.

[0061] FIG. 62 is a block diagram of the irrigation controller of the invention.

[0062] FIG. 63 is a schematic diagram of the base module circuit.

[0063] FIG. 64 is a schematic diagram of the expansion module circuit.

[0064] FIG. 65 is a schematic diagram of one form of the smart module circuit.

[0065] FIG. 66 is a block diagram representation of the expansion module indicating the configuration of the pins.

[0066] FIG. 67 is a block diagram representation of the smart module indicating the configuration of the pins.

[0067] FIG. 68 is a schematic diagram of the backplane circuit board circuit.

[0068] FIG. 69 is a schematic diagram of the control panel circuit.

[0069] Corresponding reference characters indicate corresponding components throughout the several views of the drawings. Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help to improve understanding of various embodiments of the present invention. Also, common but well-understood elements that are useful or necessary in a commercially feasible embodiment are often not depicted in order to facilitate a less obstructed view of these various embodiments of the present invention.

DETAILED DESCRIPTION

[0070] The following description is not to be taken in a limiting sense, but is made merely for the purpose of describing the general principles of exemplary embodiments. The scope of the invention should be determined with reference to the claims.

[0071] Described herein are several embodiments relating to irrigation controllers for controlling irrigation stations. In many embodiments, the irrigation controllers are modular in that various functional components of the irrigation controller are implemented in removable modules that when inserted into position within the controller provide certain functionality. Accordingly, the embodiments described herein cover various functionalities, features and methods useful in such modular controllers; however, many embodiments apply to irrigation controllers generally. The following specification describes several embodiments of the invention in the context of two example modular controller implementations. For example, many embodiments of the invention are described in one or both of a modular controller as illustrated variously in FIGS. 1-51 and a modular controller as variously illustrated in FIGS. 52-69.

[0072] Referring to the modular controller design, such as variously illustrated in FIGS. 1-51, one embodiment of the invention, designated as irrigation controller 10, is generally illustrated in FIG. 1. According to several embodiments herein, the controller 10 is a modular irrigation controller that has an expandable architecture. As shown, the expandable architecture irrigation controller 10 is installed in a water-resistant controller housing 20 indicated in FIG. 2. When the unit is installed on site, typically on a wall or the like, through mounting holes 42, indicated in FIGS. 4 and 6, valve control wires and power wires 79 run through a wiring access hole(s) 41 at the bottom and the back of the rear housing 40 as seen in FIG. 5. Also provided are additional wiring access holes 41a and 41b in the event additional wires need access into the housing 20. This innovative irrigation controller 10 having an expandable architecture modular design allows for economical expansion as well as easy installation and addition of capabilities and features not found in other irrigation controllers.

[0073] The controller housing 20, formed of plastic or other suitable material, is designed to withstand various environmental conditions. In one form, the controller housing 20 includes rear housing 40 and door 16 that enclose the electri-

cal components housed within the housing 20. In one embodiment, the housing 20 encloses the base unit 50, the base module 55 and a plurality of expansion modules 65 to protect their electronic components and connections. As described further throughout this specification, in preferred form, a plurality of different types of expansion modules 65 are provided that may be removably inserted in any one of one or more locations within the controller 10. Thus, in many embodiments, a controller 10 is provided with different types of expansion modules having different functionality with the same controller. Additionally, in many embodiments, expansion modules used as station outputs may have a different number of station outputs and be inserted in any one of one or more locations within the controller.

[0074] The base unit 50, shown in FIG. 3 and FIG. 4, carries out basic irrigation functions and also performs other advanced functions. The base unit 50 is comprised of the control panel 30 (also referred to generically as the main control unit or the control unit) and the controller housing 20 as further indicated in FIG. 2 and accommodates the backplane 45 which is indicated in FIG. 3. The backplane 45 provides backplane circuitry 46 (one embodiment of which is illustrated in FIG. 16) to provide electrical interconnections between various components and modules to be housed within the housing 20.

[0075] The door 16 pivotally swings open from a closed position to an open position as seen in FIG. 2 to reveal the removable and programmable control panel 30 that includes a user interface 21 to enter and maintain an irrigation schedule and to display controller status and other functions. The door 16 contains an opening or hole 18 to provide direct viewing of the illuminating status indicator 28 on the control panel 30 when the door 16 is closed. The door 16 has a lock 17 to restrict access to the base unit 50.

[0076] Looking at FIG. 4, a battery compartment 37 is provided to accommodate the battery of the control panel 30. The storage posts 37a used for storage of a battery connector, also visible in FIG. 3, are recessed to facilitate flat placement of the control panel 30 on a table during programming, when the control panel 30 is detached from the base unit 50. Also provided is an optional station wiring guide 29 that may be adhered to an interior surface of the control panel 30 to provide easy identification of the various station modules.

[0077] The reset button 36 on the back of the control panel 30 consists of a right-angle mounted switch component (not shown) on the front side of the control panel circuitry 31 for easy and cost effective manufacturing and can be discretely actuated by a pencil or a screwdriver for hardware reset. The reset button 36 serves to restart the control panel microcontroller 32 from a potential lock-up condition possibly caused by electrical disturbances.

[0078] Indicated in FIG. 4, the communication wire retention channel 38 conveniently restrains and directs the communications cables (not shown) to the external communication interface 34a (see FIG. 10) while the external communication interface panel 34 is closed and the electronic components are protected against environmental damage.

[0079] Importantly, it is an objective of several embodiments of the invention to have the control panel 30 modular and removable from the controller housing 20 and the base unit 50, as seen in FIG. 5. Advantageously, the control panel 30 can be programmed with irrigation schedules by a user while detached from the rest of the base unit 50. A pin and socket mechanism 35, plus a ribbon cable 49 connection to

the backplane circuitry 46 of the back plane 45 permits the control panel 30 to be removed from the base unit 50. To provide power so that the control panel 30 can be removed and programmed independent of an outside power source, a battery (not shown) is provided in the recessed battery compartment 37, seen in FIG. 4, at the back of the control panel 30. This further provides additional flexibility and economic advantage in that, for example, a damaged control panel can quickly be changed and replaced with a new control panel without the need to replace the entire base unit 50. It is noted that while in many embodiments, the control unit or control panel 30 is modular and removable, in other embodiments, the control unit is integral to the controller housing and not intended to be removable.

[0080] Now looking at FIG. 11, located within the control panel 30, the control panel circuitry 31 includes the main microcontroller 32 that communicates with base module 55 through base module signal lines 39a extending through the backplane circuitry 46 and the pins of a base module connector 44. The main microcontroller 32 also communicates with the expansion modules 65 through a communication bus 39 extending through the backplane circuitry 46 and the pins of the module connectors 47 (shown in FIG. 4) to control the irrigation functions as defined in the irrigation program as well as the other functions contained in expansion modules 65. Depending on the implementation, the bus 39 may be a serial or parallel bus. In preferred form, the communication bus is a multi-drop serial bus and is described further below. It is also noted that as used throughout this specification, the term "microcontroller" refers to an electrical device that minimally includes a processor logic (e.g., one or more microprocessors), memory (e.g., one or more memory devices), and inputs and outputs and is configured to execute instructions based on information stored in memory either within the microcontroller or external to the microcontroller. Microcontrollers as used herein also include any necessary timers and/or clocks.

[0081] It is also an object of several embodiments of the invention to have the communications interface port 34a, as part of the control panel circuitry 31, connecting to a plurality of modular cartridges (not shown) facilitating a communications link via a plurality of media such as a radio modem, a telephone modem, wireless networks, hard-wired or fiber optic systems, etc. interfacing to a plurality of computers and networks. Such a communications link allows the irrigation controller 10 to intercommunicate for various commands including those for irrigation, for the update of the firmware 33a without the removal of any electronic components from the irrigation controller 10, and for the uploading and downloading of irrigation schedules. Also, the schedules that the user has entered at the control panel 30 may be extracted and sent to a central control system via the communications interface 34. In one example, the communications interface port 34a uses a dual-sided 2x5-pin edge card type with pin assignments illustrated in FIG. 26.

[0082] The main microcontroller 32 gathers information or commands from the user interface 21, processes them and sends the commands to the base module 55 via control signals and to the expansion modules 65 via the communication bus 39 to drive the valves. As illustrated in FIG. 10, the control panel microcontroller 32 also has the ability to interface with other external peripherals including expansion modules 65, external expansion housing(s) 80 including additional expansion modules 65, and the external communications interface

34a. The expansion modules **65** are provided in many different forms including an expansion module that provides additional station outputs to control additional irrigation valves, an expansion module that provides outputs to devices other than to additional irrigation stations, an expansion module that provides inputs to the main microcontroller **32** (e.g., in the form of external conditions provided by sensors), a smart expansion module that provides additional functionality not originally found in the main microcontroller **32** as originally configured, and interface extension smart expansion modules that provide functionality to direct the main microcontroller to provide a user interface extension to the expansion module so that the expansion module can performed its additional functionality.

[0083] In many embodiments, the main microcontroller **32** and the communication bus **39** have an architecture that allows the main microcontroller of the main control panel **30** to work together with the expansion modules **65** in order to implement the functionality of the irrigation controller **10**. For example, in preferred form, one or more of the expansion modules **65** include their own microcontroller, e.g., microcontrollers **66a** as seen in FIGS. **14**, **17** and **18**. In smart expansion modules, the microcontrollers **66a** of the expansion modules are configured to communicate with and share data with the main microcontroller. The main microcontroller is configured to be able to accept additional expansion modules and work together with them. For example, the main microcontroller is configured to be able to transmit data, parameters or variables which correspond to or are a part of one or more irrigation programs stored by the main microcontroller, in response to requests from the expansion module (s) **65** for such data, parameters and variables. Additionally, the main microcontroller **32** is configured to accept and store changes or updates to parameters, variables or one or more irrigation programs as provided by an expansion module. For example, in one embodiment, an expansion module **65** receives a copy of a stored irrigation program from the main microcontroller **32**, adjusts the program based on the functionality of the expansion module **65** and sends the updated irrigation program to the main microcontroller to replace the existing irrigation program. Advantageously, such architecture allows an irrigation controller to be designed while allowing for expansion modules to be designed to add additional functionality to the capabilities of the irrigation controller. The additional functionalities may not even be known at the time of the manufacture of the irrigation controller **10** and the control panel **30**; however, since the main microcontroller is configured to share its data and accept data and control signaling from an expansion module, the capabilities of the irrigation controller may be expanded without requiring that a user purchase a new irrigation controller. Instead, the user would simply purchase a new expansion module **65** having the desired functionality. Accordingly, additional functionality can be provided to the irrigation controller **10** through the use of some types of expansion modules **65** without requiring that any firmware or software in the main microcontroller **32** be added, changed or replaced.

[0084] Generally, this type of coordinated operation between the main microcontroller **32** of the control panel **30** and the various expansion modules **65** is provided through the configuration of the main microcontroller **32** to be able to operate together with expansion modules of unknown functionality and its ability to share data with the expansion modules **65** and ability to act in response to data and commands

from the expansion module. Additionally, a communication link and protocol are provided that allow data flow between the main microcontroller **32** and the various expansion modules **65**. Further details and description are provided throughout this specification.

[0085] The main microcontroller **32** is also capable of directly monitoring other inputs such as the valve solenoid current, the presence of the base module **55**, sensor inputs (e.g. rain and flow), and the AC line frequency. In addition to the user interface **21**, the main microcontroller **32** is able to accept commands through the remote control port **63**, shown in FIG. **4**, and an external communication interface **34a**, illustrated in FIG. **10**.

[0086] Importantly, it is an objective of several embodiments of the invention to provide a communication link between the main microcontroller **32** and the distributed microcontrollers **66a** of the expansion modules **65**, seen in FIG. **14**. In one embodiment, the communication protocol uses a physical layer based on a 9-bit capable Universal Synchronous Asynchronous Receiver Transmitter (USART). This provides an addressing mechanism internal to the USART that avoids continuously interrupting the distributed microcontrollers **66a**. The USART utilizes a serial protocol on the module communication bus **39** that has a plurality of data in and data out pins as well as an optional serial clock pin. The transmission of data from the main microcontroller occurs on the data out pin (e.g., SMB-DO of FIG. **12**) and the reception occurs on the data in pin (e.g., SMB-DI of FIG. **12**). A serial clock is used in the case of synchronous data communication only. In the case of asynchronous communication, the serial clock pin is not used. In various forms, the communication protocol for communications on the bus **39** works with asynchronous data communication or with synchronous data communications when a serial clock is provided. However, the irrigation controller **10** takes the technology a step further by programming the microcontrollers **66a** of the expansion modules to configure their serial data out pins to be in high impedance mode until they are addressed. For example, in one embodiment, the main microcontroller **32** always drives its data out pin actively as it is the only device driving this signal. When individually addressed, each distributed microcontroller **66a** of the expansion modules **65** re-configures its serial transmit data out pin (e.g., SMB-DI of FIG. **21**) on-the-fly to drive the data bus **39** and transmit data on this pin. Consequently, several embodiments offer a communications protocol that can be extended and modified with minimum impact on the rest of the system. The bus **39** could be expanded to virtually any length and the expansion modules could be located remotely from the irrigation controller **10** either independently or located in an external expansion housing(s) **80**. It is noted that the USART is a well known communication protocol. Accordingly, the communication bus is a multi-drop bus structure in that all expansion modules **65** are coupled to the same bus **39** and each pulls any communications intended for it from the bus through the addressing mechanism of the USART. In preferred form, the bus **39** comprises a serial data bus; however, it is understood that in other embodiments, the bus **39** has a parallel line structure.

[0087] Interconnect communication busses in existing modular irrigation controllers use a master/slave architecture. For example, the controller of U.S. Pat. No. 5,748,466 (McGivern et al.) employs a query/response model with the main microcontroller making a query to the module and expecting a response from it to ascertain the number of stations installed

in the irrigation controller. Such a query/response relationship of the controller and modules results in unnecessary overhead and bandwidth usage on the interconnecting bus, becoming a limiting factor in expansion capability. Several embodiments of the invention solve this problem by having the expansion module 65 self-detect its installation and announce its presence to the main microcontroller 32. Generally, the microcontroller 66a of the expansion modules is configured to detect when it is connected to the connector 47 of the backplane 45. Once this determination is made, the microcontroller 66a causes a message to be transmitted to the main microcontroller via the communication bus 39 announcing that the expansion module has been installed. The microcontroller 66a waits for an acknowledge message back from the main microcontroller 32. If no acknowledge is received, the microcontroller 66a sends additional messages to the main microcontroller 32 until the main microcontroller 32 acknowledges the presence of the expansion module 65. Therefore, since the expansion modules are configured to self detect their installation in the controller 10, the main microcontroller 32 does not need to query the expansion modules 65. This results in saved overhead and bandwidth usage allowing the irrigation controller 10 to self-configure and provide for more overall expansion capacity with less demand on the main microcontroller 32.

[0088] It is an object of several embodiments to make the programming of a watering schedule into the irrigation controller 10 free of historical challenges that users have been facing with the prior art irrigation controllers. One embodiment solves the problem of difficult entry and incorrect setup of a watering schedule into existing controllers through the incorporation of a water wizard for easy setup, programming and use. The water wizard allows the irrigation controller 10 to confirm automatically that a watering schedule entered by the user is consistent and logical and guides the user through the programming steps necessary to setup the irrigation controller 10 and program a watering schedule into it. This intelligent water wizard is based on the main microcontroller 32 built into the irrigation controller 10. The water wizard guides the user through a series of logical steps, asking only for the needed information in an intuitive form and subsequently creating a schedule to satisfy the needed irrigation. For example, the water wizard asks if the irrigation is for lawn, trees or shrubs. Then it asks what the soil type is. And then it inquires about the Sun exposure. The water wizard would ask for a specific zone or watering time as necessary to complete the irrigation schedule. This union of native human language with the logic of an irrigation controller has been unprecedented in the art of inventing irrigation controllers.

[0089] It is a further object of other embodiments to include a novel water-conserving feature in which the user interface 21 provides 'program review' and 'total run time' features. Using the program review feature, the controller 10 displays to the user, e.g., on the LCD 24 (generically referred to as a display 24), a listing of all stations and watering times on a single display screen or series of displays screens that a user may scroll through. Advantageously, the user does not have to manipulate the rotary dial 22 or navigate complex menus in order to separately view irrigation settings or the irrigation program for various stations.

[0090] FIGS. 36-48 provide display screens generated for display on the LCD 24 that provides program review features in accordance with an embodiment of the invention. In the following display screens, text provides the information

while the bottom edge of the screen indicates which soft key 25 should be pressed to select a function or go forward or backwards through the display screen sequence. FIG. 36 illustrates the main display that allows the user to review programmed information for troubleshooting or other purposes. For example, the display of FIG. 36 allows the user to select the soft key below "1" to select option 1—confirm programs, while soft key below "2" selects option 2—test all valves. Selecting option "1" prompts the display screen of FIG. 37 to be displayed. This display screen allows the user to select between three options: 1—program review, 2—program run time, and 3—valve run time. In accordance with one embodiment, selecting option 1 enters the user into the program review display sequence of FIGS. 38A through 48 in which the user can review the programmed status of all stations and their watering times.

[0091] In response to selecting option 1 in the display screen of FIG. 37, the display screen of FIG. 38A is displayed. This screen displays the watering start times for all valves 1, 2, . . . , 8. It is noted that if no start times are programmed, the display screen of FIG. 38B is displayed instead of the screen of FIG. 38A. Furthermore, it is noted that this display screen and the other displays screens of FIGS. 38A through 48 illustrate the status of program A. To view the status of programs B, C, etc., the user simply moves the program selector switch 27 to the appropriate program.

[0092] Selecting the soft key corresponding to "next" in the screens of FIG. 38A or 38B results in the display screen of one of FIG. 39A, 39B, 39C, 39D or 39E providing the watering day cycle for the selected program to be displayed depending on whether the watering day cycle is cyclical, custom, odd, odd 31, or even. Selecting the "next" option in any of the displays of FIGS. 39A-39E displays the display screen of FIG. 40, which then provides the watering days (based on the watering day cycle). Selecting the "next" option in the display of FIG. 40 displays the display screen of FIG. 41, which then provides the run times for each valve. The soft keys corresponding to "+" and "-" allow the user to scroll through more valves not fitting on one the single display screen. Selecting the "next" option in the display of FIG. 41 displays the display screen of FIG. 42, which then provides the amount of seasonal adjust (e.g., 115%). If there is no seasonal adjust present (e.g., the value is 100%), the display screen of FIG. 42 is skipped. Selecting the "next" option in the display of FIG. 42 (or FIG. 41 if FIG. 42 is skipped) displays the display screen of FIG. 43, which then provides the number of rain delay days remaining. Again, if there are no rain delays days remaining, this display screen is skipped. Selecting the "next" option in the display of FIG. 43 (of FIGS. 41, 42 if there is a skipped display) displays the display screen of FIG. 44, which then provides the status (e.g., either "on" or a programmed "off" day) for each calendar day. The "+" and "-" allow the user to scroll through subsequent and previous days while indicating the status for that day. Selecting the "next" option in the display of FIG. 44 displays the display screen of FIG. 45, which then provides any programmed valve delays. Selecting the "next" option in the display of FIG. 45 displays the display screen of FIG. 46A, which then provides cycle and soak times for all valves. In the illustrated embodiment, since all valves will not fit on the same display screen, the "+" and "-" soft keys allow the user to scroll through the valves. For example, pressing the "+" key once advances the list to the display screen of FIG. 46B to reveal valve 06 and remove valve 01. Likewise, pressing the "+" soft key further, further advances

the display to the display of FIG. 46C and eventually to the display of FIG. 46D. Selecting the “next” option in any of the displays of FIGS. 46A-46D displays the display screen of FIG. 47, which then provides the status of the master valve or pump for valve 01. Again, the user may press the “+” and “-” soft keys to scroll through more valves. Selecting the “next” option in the display of FIG. 47 displays the display screen of FIG. 48, which then provides the status of a sensor override (e.g., overriding the rain sensor) for each valve. The user can use the “+” and “-” soft keys to scroll through more valves. The display screens of FIGS. 36 through 48 provide one embodiment of a program review feature in the display menus that allows a user to easily review the entire program for any program A, B, C, etc., and switch between the same display information for different programs easily (by using the program selector switch 27) in a simple intuitive manner. This is in contrast to known controllers that require a user to traverse through extensive programming menu systems to retrieve the same information.

[0093] FIGS. 49 and 50 illustrate one embodiment of a screen display provided by the user interface 21 to display ‘total run time’ features. For example, selecting the option “2” in the display of FIG. 37 displays the display screen of FIG. 49, which then provides the total run time for the program representing the total watering time per day for that program. Alternatively, selecting option “3” in the display of FIG. 37 displays the display screen of FIG. 50 which provides the total run time per watering day per valve to be displayed on the LCD 24 of the user interface 21. These total run time display screens allow contractors, water auditors and homeowners to see exactly how much irrigation will occur per day based on the controller’s settings. The total run time calculations include many factors including watering time, cycle and soak settings and the effects of seasonal adjust. It assumes there is no interference from a stacking effect, rain sensor, central control, or user intervention. Such calculations and ease in retrieving them through the user interface represents a significant advance in the user interface for irrigation controllers.

[0094] One advantage of the various program review user interface display screens, such as shown in FIGS. 36-50, is that this interface only allows the user to “review” the programs and parameters. In this interface, the user can not make changes to the program as the user is trying to review the program. This user interface solves a problem encountered in many controllers in which while attempting to review a given program or parameter, a user accidentally makes changes to the program (since when viewing program information in such controllers, the user has entered programming interface displays and menus).

[0095] Irrigation controllers are being provided with more and more features, buttons, labels and ever thickening manuals while trying to provide the user with more feedback and while supposedly simplifying the user interface, but ultimately adding to the complexity. Several embodiments answer the user interface complexity problem in the field of art, by pushing the complexity into the internal computer program logic of the irrigation controller 10. Basically, the user is asked about the watering or typical conditions or constraints existing on the landscape. The irrigation controller 10 configures itself in terms of the overall watering needs and objectives. This “Intelligent Use of Water”™ concept relieves the user of having to know detailed information about

station run times, optimum watering time of the day, start times, number of start times, etc.

[0096] In one embodiment, the irrigation controller 10 intelligently stores and recalls module programming and configuration information in order to eliminate the need to reprogram the controller or expansion module when expansion modules are changed. For example, information unique to each expansion module is stored in a configuration data table residing in the non-volatile storage device (EEPROM) 32a of the main microcontroller 32 (see FIG. 11). As an alternate embodiment, this same configuration data could be stored in the flash memory 33. This configuration data typically represents data that is specific to the expansion module 65. For example, the configuration data may include: what type of module the expansion module is (e.g., whether it is a station expansion module, an input module, a decoder module, etc.); how many station outputs are provided by the expansion module; how many and what type of inputs are provided by the expansion module; in the event the expansion module receives inputs from sensor devices, what type of sensor devices the expansion module is coupled to (e.g., moisture, rain, wind sensors), etc. This configuration data is transferred to the main microcontroller 32 from the microcontroller 66a of the expansion module 65 over the bus 39. This data is then stored in the non-volatile configuration data table. When the configuration data needs to be installed into a new replacement module, the data is recalled from the non-volatile memory and transferred to the module over the bus 39.

[0097] When a given expansion module 65 is removed and replaced by an identical expansion module (or a different module with similar function), all configuration data and programming related to the expansion module removed is retained by the controller 10 and is applied to the replacement expansion module. In one embodiment, the module location and module’s electronic SKU (stock keeping unit) number are used to track if a “new” module in a module mounting location 45b can accept the data. Once the newly installed expansion module 65 announces its presence to the main microcontroller 32 of the control unit, the configuration data table is scanned to verify that the same type of modules are mounted in the controller housing. If there is a match, the newly installed expansion module is passed the programming and configuration data already existing in the non-volatile memory 32a (or 33) eliminating the need for the user to reprogram the expansion module configuration or irrigation schedule. In the event there is not match, then the main microcontroller 32 determines that the newly installed expansion module is not identical to the removed module or is not intended to be a replacement for the removed expansion module, and the stored configuration data may be deleted or overwritten with new configuration data if the memory is needed.

[0098] Irrigation controllers are growing in complexity with each generation. According to several embodiments, the use of a Real Time Operating System (RTOS) in the main microcontroller 32 of the irrigation controller 10 simplifies and makes the operation of the microcontroller 32 more robust. It allows for a more complex program to be developed that is more robust and of higher quality in a shorter amount of time. In preferred form, the controller 10 employs the real time operating system (RTOS) to allow separate program sections to communicate between themselves in a well-defined fashion. Since each piece of program runs independently in its own context, it is easier to write and read the

supporting software as well as to troubleshoot software bugs during the development stage and have a bug-free software running in the irrigation controller 10.

[0099] The microcontroller 32 of the main control unit or control panel 30 houses non-volatile memory backup (EEPROM) 32a, shown in FIG. 11, which is used to store and maintain, while the power is off, information provided as input, via the user interface (UI) 21, remote control port 63 or the communications interface 34. This non-volatile memory backup 32a on the main microcontroller 32 maintains the watering schedule details, module data and other system parameters upon line power outage.

[0100] Also shown in FIG. 11, the firmware 33a for the irrigation controller 10 is stored in the flash memory 33. This flash memory allows the firmware 33a to be updated in the field without the need to replace the main microcontroller 32, by using an expansion module 65c, referred to as a re-flash module (one example of which is illustrated and described further in connection with FIG. 32) or through the communications interface 34a without the need to replace any physical component on the controller 10.

[0101] One of the objectives of another embodiment is to customize the user interface 21 according to the needs of the different user groups such as the contractors or the commercial users and novice users who lack experience in programming controllers. One embodiment solves the problem of having to design/redesign an irrigation controller according to the changing interface demands of the different user groups such as a classic contractor, a modern contractor, a novice user, etc., by offering a simple menu of user groups. The user simply makes a selection based on what user group they belong to and the overall user interface 21 changes with display driven menus tailored exclusively for that specific user group. For example, according to one embodiment, the user is able to specify in a user interface display settings display screen what type of group the user/programmer of the irrigation controller belongs to: a modern contractor (a contractor who is accustomed to modern methods to program an irrigation controller), a classic contractor (a contractor who is accustomed to a traditional method of programming an irrigation controller), or a novice (a user not familiar with the programming of an irrigation controller). Once the user selects which group the user belongs to, the user interface (i.e., the display screens and programming sequence) are presented to the user accordingly. Thus, the programming process the user must navigate to program the controller will vary depending on which group the user selects. One embodiment is illustrated in FIG. 35, which presents a programming setup display screen 130 offering the user to select whether the user is an advanced user, such as a contractor (option 1) or a beginner (option 2). Once the user selects which group the user belongs to, the display screens and programming sequence changes. For example, if the user is advanced, display screen sequence 131 is followed, while if the user is a beginner, display screen sequence 132 is followed.

[0102] As seen in FIG. 2, the user interface (UI) 21 consists of a rotary dial 22 for programming, a plurality of indicators 23, a liquid crystal display (LCD) 24 (generically referred to as a display), a status indicator 28 (e.g., a visual and/or audible alarm) to alert the user to a status condition, the unlabeled soft keys 25, a sensor switch 26, and a program selector switch 27. In one embodiment, the status indicator 28 indicates the status of the functionality of the control panel 30. For example, when flashing, the status indicator indicates

to the user a fault condition in the controller 10, while when the indicator is constantly illuminated, this indicates that the controller has suspended irrigation, e.g., due to a rain sensor. In preferred form, the status indicator 28 comprises a visual indicator, such as a light emitting device, e.g., a light emitting diode (LED), that visibly indicates a status of the controller. In preferred form, the opening or hole 18 formed in the door 16 is aligned with the status indicator so that the status indicator is visible from the exterior of the controller housing while the door is closed. In other words, the user does not have to open the controller housing in order to determine that there is a fault. In other embodiments, the status indicator 28 comprises an audible alarm, e.g., a sound emitting device, e.g., a small speaker, that emits an audible sound to indicate the status (e.g., fault condition or normal operation) of the controller. In another embodiment, the status indicator 28 is both a visual indicator and an audible indicator of a status of the controller 10.

[0103] Shown in FIGS. 23A and 23B, an annular ring 19, molded onto the control panel 30, runs around the rotary switch post (not shown) and forms a barrier against water entry into the controller 10. This protects the internal circuitry from water damage. In the illustrated form, the annular ring 19 is a raised wall, rib or barrier that extends perpendicularly from the surface of the control panel 30 and annularly about a recess 81b within which is formed a hole 81a that is provided to allow a post to connect the rotary dial 22 to the switching components within the controller 10. The annular ring 19 is designed to fit underneath the lip 82 or edge of the rotary dial 22. In use, with the control panel oriented such that the surface of the control panel is vertical (in the orientation of FIGS. 1-4), any water that seeps underneath the lip 82 of the rotary dial 22 contacts the raised surface of the annular ring 19 and is directed around the outer perimeter of the annular ring 19 and away from the recess 81b and hole 81a. Thus, the annular ring 19 provides additional protection from water entering the interior of the control panel 30.

[0104] The unlabeled soft keys 25 (also shown in FIG. 2) are used interactively with the commands that appear on the LCD 24. This approach places the label for each key 25 on the LCD 24 rather than on the keys themselves, allowing the label to change as appropriate, making the irrigation controller 10 easier to use and eliminating the need to create a different button for each label needed.

[0105] Existing irrigation controllers are limited to small, simple LCD segmented displays with limited language capability and limited graphic capability. It is a further objective of several embodiments to enhance the user experience through a display that can support a plurality of graphics and different alphabetical characters of different languages. To this end, the irrigation controller 10 employs a graphical display controlled by the control panel microcontroller 32 accommodating a superior language and graphics support with more lines of information displayed on the LCD 24 having the pinout configuration as illustrated in FIG. 25. This pinout provides 8 bits of data (D0-D7) to the LCD 24. As seen in FIG. 11, in one embodiment, the firmware 33a which implements multiple alphabets, languages, font sizes and graphics facilitates the offering of the alphabets of multiple languages for display by the irrigation controller 10. This solution involves a specialized and innovative set of graphics routines that enable the multiple alphabets and text strings to be stored in memory 33 or 32a and written to the display 24 with limited RAM resource demand on the main microcontroller 32. In preferred

form, this innovative firmware graphic routines treat each language's alphabet as a collection of bitmap characters. As each character is displayed on the screen, the individual dots on the screen are made dark or light to form that character. This results in a single character stored in the firmware controlling up to several hundred individual dots that represent the character on LCD 24. This is done through a 'look-up process' where the single character indexes into the bitmap collection stored in the firmware. A similar method is used for storing pictures and icons, where a single character stored in EEPROM 32a is used to translate into up to thousands of dots on the screen by looking-up the stored graphic bitmap based on the single character. This results in minimized memory usage which is crucial for the high volume manufacturing of the irrigation controller 10 at a low cost.

[0106] In several embodiments, the user is allowed to select which language to view the display screens in. Known controllers are configured to display screens in a single language (e.g., English). However, since the controller stores display screens in multiple languages, the user can select a given language or change the display screen language. The language selection is stored in non-volatile memory (e.g., EEPROM 32a) so that the setting is saved for use after a power outage occurs. For example, the user simply navigates (through the rotary switch 22, the display screen menus and soft keys 25) to a language select screen to select the language of choice. Additionally, the language of initial display may be set when shipping the product, if for example, the controller will be shipped to a specific country having a commonly accepted language. The user will have the ability to change this language, but at least the initial language will be in the most common language of that country.

[0107] While the user interface 21 in accordance with some embodiments of the invention utilizes different fonts to emphasize certain details to the user, different portions of the display 24 can be flashing to emphasize certain other details. A plurality of graphic icons is also employed as part of the emphasis mechanism of the user interface 21.

[0108] Now returning to FIG. 4, located within the rear housing 40, the backplane circuitry 46 is used primarily as an interconnection between the various modular components (e.g., the modules 55, 65) and the control panel circuitry 31 (one example of which is illustrated in FIG. 15). The backplane circuitry 46 (one example of which is illustrated in FIG. 16) is also used to connect with the remote control unit (not shown here) via remote connection port 63 as well as the external expansion housings 80 via external expansion housing connector 62 whose pin configuration is illustrated in FIG. 22. The backplane circuitry 46 additionally accommodates two terminal blocks 60a, shown in FIG. 4, connecting the 24 VAC supply voltage to the controller 10 and one grounding terminal block 60b which is used for grounding to provide electrical surge protection.

[0109] The backplane circuitry 46 provides a valve test through a single-position screw terminal 64, also shown in FIG. 4. The valve test connection terminal 64 is provided with a 24 VAC supply voltage.

[0110] The backplane 45 also includes a base module mounting location 45a and a plurality of expansion module mounting locations 45b. Each mounting location 45a and 45b provides a location on the backplane where a module can be mounted thereto. The base module mounting location 45a includes a connector 44 that includes pins or contacts electrically coupled to the backplane circuitry 46. Each expansion

module mounting location 45b also includes a connector 47 that includes pins or contacts electrically coupled to the backplane circuitry 46. In operation, the base module 55 is mounted within the housing 20 at the base module mounting location 45a of the backplane 45, and the expansion module (s) 65 are mounted within the housing 20 at corresponding expansion module mounting locations 45b of the backplane 45.

[0111] As seen in FIG. 3, the backplane circuitry 46 is connected to the control panel circuitry 31 via a ribbon cable assembly 49. The connector layout and assigned signals for the ribbon cable 49 are illustrated in FIG. 12.

[0112] According to several embodiments of the invention, mechanisms are provided to ensure that modules installed into the controller are compatible with the controller 10 and that these modules 65 were built by an authorized manufacturer. In one embodiment, each module 65 contains a predetermined textual message, e.g., a textual message that is copyright protected, that is transmitted by the module 65 over the bus 39 to the main microcontroller 32. The main microcontroller 32 expects to receive a valid textual message (e.g., the copyright message) from every module 65. If it does not receive such a message, the main microcontroller 32 will treat that specific module as rogue and ignore it. According to a second embodiment, both the modules 65 and the main microcontroller 32 contain a challenge/authenticate mechanism. This allows for a "mutual authentication" scheme that can be initiated by either the main microcontroller 32 or the expansion module microcontroller 66a. As shown in FIG. 28, in one form where the main microcontroller 32 initiates the authentication procedure (Step 90), the main microcontroller 32 will generate a random number (Step 91), pass this random number to the module 65 as a challenge (Step 92, which can be generically expressed as transmitting an authentication request to the expansion module 65), and also process this random number (Step 93) through a secret authentication algorithm contained inside the main microcontroller 32. The module 65 will receive this random number and also process this same random number (Step 94) through an identical secret authentication algorithm contained inside the module's microcontroller 66a. The module's microcontroller 66a will send the result (Step 95) from the secret authentication algorithm as a reply to the main microcontroller 32. Based on the response from the expansion module, the main microcontroller 32 will determine if the expansion module is an authorized expansion module. For example, the main microcontroller 32 will compare the result it computed internally with the result provided by the module (Step 96). If the results match, then this indicates to the main microcontroller 32 that the module does indeed know the secret authentication algorithm and therefore must be a valid module built by an authorized manufacturer (Step 97). The main microcontroller 32 will then continue to interact and communicate with that module 65. If the result does not match, the expansion module is not authorized to operate with the main microcontroller and a rogue alert will issue (Step 98). The controller 10 is also able to display a message on the LCD 24 to indicate that a rogue module has been detected.

[0113] Expansion modules 65 would also like to have assurance that they are installed in a controller 10 that has also been built by an authorized manufacturer. In this embodiment, the module 65 issues a challenge to the main microcontroller 32 (Step 100), as shown in FIG. 28. The module 65 will generate a random number (Step 101), pass this random

number to the main microcontroller 32 as a challenge (Step 102, which can be generically expressed as transmitting an authentication request to the main microcontroller 32), and also process this random number (Step 103) through a secret authentication algorithm contained inside the module 65. The main microcontroller 32 will receive this random number and also process this same random number (Step 104) through an identical secret authentication algorithm contained inside the main microcontroller 32. The main microcontroller 32 will send the result from the secret authentication algorithm as a reply to the module 65 (Step 105). Based on the response from the main microcontroller, the module 65 will determine if the main microcontroller is an authorized control unit. For example, the module 65 will then compare the result it computed internally with the result provided by the main microcontroller 32 (Step 106). If the results match, then this indicates to the module 65 that the controller 10 does indeed know the secret authentication algorithm and therefore must be a valid controller built by an authorized manufacturer (Step 107). The module 65 will then continue to interact and communicate with the controller. If there is no match, then the main microcontroller of the control unit is not authorized to operate with the expansion module and a rogue alert will issue (Step 108).

[0114] In preferred embodiments, the confidentiality of these transfers (steps 92, 95, 102, 105) is maintained by encrypting the data sent over the communication bus 39.

[0115] With an expandable architecture, it is possible that users could attempt to keep adding modules without limits. This may make it difficult to distinguish different products with different capacities in the market. A further object of some embodiments of the invention is to limit the number of modules, the number of each type of module, the number of external expansion housings, or any combination thereof. To that end, a mechanism exists in the firmware 33a such that if the user attempts to exceed the imposed limits, the irrigation controller 10 advises the user that a limit has been reached. Also, the controller 10 refuses to operate any modules that exceed the limit. For example, in one embodiment, a limit of the number of modules (or a limit of the number of certain types of modules that is allowed to be attached to the controller (including all expansion housings) is stored in the memory of the microcontroller (e.g., firmware 33 or the EEPROM 32a). When a module is enumerated, the main microcontroller checks to see if there are stored any limits. If there are, beyond the limit, the main microcontroller will not enumerate the additional modules or operate therewith. Additionally, the main microcontroller will send or cause an error message to be displayed to the user indicating that the user has exceeded the maximum number of modules (or maximum number of modules of a given type of module).

[0116] As indicated in FIGS. 7 and 8, each module contains a module status indicator 56a, e.g., a light emitting diode (LED), that is activated either by the module 55, 65 itself or by the main microcontroller 32. This module status indicator 56a is utilized to report status information, error conditions, correct operation or other functions to the user. To distinguish different status values, the indicator 56a utilizes a combination of different colors, changing illumination pattern extending from steady to various blinks and/or uses a combination of blinking and colors. It will be obvious to those skilled in the art that this status indicator 56a could be any alternate type of electro-illumination element. In other embodiments, the sta-

tus indicator comprises a sound emitting device, such as a small speaker driven by the microcontroller of the module.

[0117] An alternate embodiment of a module status indicator 56a to communicate the module status is using a display screen, such as an LCD directly on the module, that is operated by the microcontroller 66a of the modules 55, 65. See, for example, the diagram of FIG. 34. This display screen will display module status and fault conditions through text and/or graphical elements. The modules can also have an LCD or other numeric, alpha-numeric, or graphical display to convey more information than a simple lighted indicator (such as an LED). The display would be used to convey module-specific or module-related information such as status, setup, or operational readings. This could be, for example, evapotranspiration data, the real-time status of alarm inputs, or the activation or enabling of features. This would allow the end user to more efficiently and better use the module and the product as a whole. In another embodiment, the module 55, 65 itself includes a user input device, such as a keypad or other data entry or manipulation method. The microcontroller 55, 65 of the module 55, 65 is configured to accept inputs based on user interaction with the user input device and information displayed on a display screen located on the module. See, for example, the diagram of FIG. 34. For example, in the case of a decoder module, this would make the module very flexible and autonomous. This could also serve to decrease the burden placed on the control panel microcontroller 32.

[0118] As illustrated in the embodiment of FIG. 10, the irrigation controller 10 can easily be expanded in capacity beyond the physical size of the controller housing 20 by the addition of external expansion housings 80 (see the expansion housing of FIG. 51) that are chained together and function as one controller, operated by a single control panel 30. In preferred form, the external expansion housing 80 expands the communication bus 39 from the main microcontroller 32 to allow more modules 55 and/or 65. In an alternate embodiment, the external expansion housings 80 are linked to one another with a power line, wherein the power line carries both power and data between the main microcontroller 32 and the external expansion housings 80. Other alternate embodiments utilize fiberoptics, wireless links or infrared links to transfer data between the main microcontroller 32 and the external expansion housings 80. In one form, the backplane circuitry 46 interfaces to the external expansion housing 80 through a 1×10 pin-header connector 62 shown in FIG. 4. The connector 62 pinout and assigned signals are shown in FIG. 22. The external expansion housing interface connector 62a (see FIG. 10) allows coupling of the external expansion housing to the bus 39. The connector 62b facilitates the attachment of a further external expansion housing 80 serving to extend the bus 39 so that multiple external expansion housings can be daisy-chained together. Any module, except for the base module 55, can be in any position in the main body housing 20 or in any of the external expansion housings 80. Referring to FIG. 51, one embodiment of the expansion housing is similar to the housing 20 in that it has a rear housing 40a and a door 16a, lock 17 and hole 18. The cable connecting to the connector 62 of the backplane of the housing 20 couples at the other end to the connector 62a of the backplane 45 of the expansion housing. Advantageously, the expansion housing allows additional expansion modules 65 to be coupled to the main microcontroller of the controller 10.

[0119] Shown in detail in FIGS. 7 and 9, the base module 55 is a non-intelligent unit which is used to drive the master

valves, the module status indicator **56a** and to carry rain sensor input signals from the rain sensors to the main microcontroller **32**. As seen in FIG. 9, the base module **55** accommodates a connector **57** (e.g., a 2×5-pin header connector) to interface with the connector **44** coupled to the backplane circuitry **46**. The base module **55** includes circuitry **56** (one example of which is illustrated in FIG. 13), a plurality of wire output terminals **58** and the module status indicator **56a** (in this case, an LED). In preferred embodiments, the controller **10** cannot function to control irrigation operations without the base module **55** mounted in the controller housing **20**. As seen in FIG. 13, the base module circuitry **56** includes the base module pinout **69**, driver circuitry **70** for the master valve, a sensor input circuit **71**, surge protection circuitry **72**, and the output terminals **58**. The connector pinout **69** and the assigned signals are illustrated in FIG. 20. It is noted that as used throughout this application, the term “driver circuitry” in connection with actuating or activating an irrigation valve generally refers to any combination of electrical circuitry to cause an appropriate actuating signal to be delivered or deliverable to the irrigation valve. For example, in one embodiment, the driver circuitry includes drivers and output switches (such as triacs or relays). Additionally, the driver circuitry may vary depending on the type of irrigation valve that the circuitry is to drive (e.g., whether the valve is a latching or non-latching solenoid activated irrigation valve).

[0120] In one embodiment, a mechanism exists whereby the accidental installation of the base module **55** in any of the expansion module mounting locations **45b** or the accidental installation of an expansion module **65** in the base module mounting location **45a** is mechanically prevented. In one form, this mechanism utilizes the ‘polarity key feature’ in which the base module connector **57** is turned 180 degrees in the opposite direction from the placement of the expansion module connector **67**. This connector polarity key feature is also reflected on the corresponding pins of connectors **44** and **47** of backplane circuitry **46** that couple and interconnect with the base module connector **57** and the expansion module connector **67** respectively. This mechanism prevents the base module **55** from properly mating if there is an attempt to mount the base module into one of the expansion module mounting locations **45b** and also prevents the expansion module **65** from properly mating if there is an attempt to mount an expansion module to the base module mounting location **45a**.

[0121] Additionally, as seen best in FIG. 4, the connectors **44**, **47** are located off-center within the respective mounting locations **45a**, **45b**, such that even if the module were turned 180 degrees, it would be physically prevented from connecting into the mounting location. For example, guideposts **59a** formed on the back of the modules **55**, **65** are designed to fit within guide holes **59b** of the mounting locations **45a** and **45b**. As seen in FIG. 4, the vertical spacing between the guide holes on the left and right sides of the mounting locations **45a**, **45b** varies, such that if the module were turned 180 degrees, it could not mate into the mounting location. Additionally, in some embodiments, the male/female connectors are switched on the base module **55** and the expansion modules **65**. For example, in one embodiment, the connector **47** on the expansion module mounting location **45b** is a male connector while the corresponding connector **57** on the expansion module **65** is a female connector. In order to prevent the base module and the expansion modules from getting mixed, the connector **44** on the base module mounting location **45a** is a female con-

connector while the corresponding connector **57** on the base module **55** is a male connector.

[0122] Seen in FIGS. 7 and 8, the module identification strip **55a** located on the module tops provide easy identification of modules **55**, **65** while eliminating the need to manufacture different covers for different module types. These identification strips may be color-coded and/or contain labeling text and/or icons.

[0123] FIG. 8 illustrates an expansion module **65**, which can be configured as having a variety functions depending on the type of module. For example, the expansion module(s) **65** can be employed for expansion to increase the number of irrigation stations as well as to expand the functionality of the irrigation controller **10**. Such expansion module(s) **65** used for output are intelligent units driving a plurality of output stations. Referring to FIG. 14, when employed for output, the expansion module circuitry **66** of the expansion output module **65** includes a power regulator **73**, a “common” electrical connection for station output terminals **74**, an independent microcontroller **66a** which communicates with the main irrigation microcontroller **32**, a current sensor circuit **75**, valve-driver circuitry **76** and surge protection circuitry **77** as shown in FIG. 14. It is noted that as used throughout this application, the term “driver circuitry” in connection with actuating or activating an irrigation valve generally refers to any combination of electrical circuitry to cause an appropriate actuating signal to be delivered or deliverable to the irrigation valve. For example, in one embodiment, the driver circuitry includes drivers and output switches (such as triacs or relays). Additionally, the driver circuitry may vary depending on the type of irrigation valve that the circuitry is to drive (e.g., whether the valve is a latching or non-latching solenoid activated irrigation valve).

[0124] The expansion modules **65** interface with the backplane circuitry **46** through the connector **47** (e.g., a 2×5-pin header connector) indicated in FIG. 4. The expansion module pinout **78** and the assigned signals for the connectors **47** and **57** are illustrated in FIGS. 14 and 21. The expansion module (s) **65** can be used at any connector **47** of any expansion module mounting location **45b**, except for the one connector **44** at the base module mounting location **45a** allocated to the base module **55**. It is noted that due to the communication bus structure and communication protocol, expansion modules are allowed to be placed in any expansion module mounting location in any order, coupled with the fact that the main microcontroller **32** is configured to not expect modules **65** to be connected in any specific order in the expansion module mounting locations **45b**.

[0125] In addition to station output expansion modules **65**, each module connector **47** can also accept other types of input/output modules that will work together with the main microcontroller. In one example, an expansion input module **65a** can include a plurality of inputs **67** coupled to the microcontroller **66a** such as one providing sensor inputs with an architecture that is illustrated in FIG. 17. This type of module **65a** identifies itself (e.g., once the module detects its installation) to the main irrigation microcontroller **32** as an input module type so that the main microcontroller **32** can store configuration data and interact appropriately with the expansion module. Depending on its configuration as dictated by the firmware **33b**, the microcontroller **66a** either passes the input data to the main control unit via the bus **39** or processes the input data in some way prior to passing the data to the control unit. The irrigation controller **10** can then use these

inputs as conditional qualifiers to alter the way it runs an irrigation schedule or program.

[0126] The architecture for an expansion module type known as a smart expansion module **65b** is shown in FIG. 18. This type of module may contain any combination of input and/or output signals (e.g., station output signals to actuate additional irrigation valves or other output signals). The signals are not only restricted to irrigation applications but may also consist of data signals, communication signals, etc. The microcontroller **66a** inside the smart expansion module **65b** is programmed to perform a specific set of tasks dependant on the overall function of the expansion module. A smart expansion module **65b** is also unique in that it can interact with the main irrigation microcontroller **32** by sharing internal data. A unique aspect of several embodiments is that the communication methods, messages and protocols between the microcontroller **66a** of the smart expansion module **65b** and the main irrigation microcontroller of the main control unit or control panel **30** allow either microcontroller **66a**, **32** to access data, variables, and constants contained in the other's memory space. For example, the microcontroller **66a** can request and receive irrigation program related data (or the irrigation program itself), make changes to it in accordance with its programmed functionality, and return the irrigation program-related data to the main microcontroller **32**. The main microcontroller **32** is designed such that it can respond to requests for data and information from the smart expansion module **65b** as well as accept commands from the smart expansion module **65b**. This allows a smart expansion module **65b** to observe intricate details occurring inside the main microcontroller, and also allows the smart expansion module to affect how the main microcontroller **32** behaves by changing data in the main microcontroller's memory space. In this manner, the installation of a smart expansion module **65b** to the irrigation controller **10** can dramatically change the overall behavior of the system. Advantageously, this allows the controller **10** to have a significant upgrade of features and capability just by installing a smart expansion module **65b** and not having to replace any existing electronics or code in the irrigation controller **10** itself. It is noted that in preferred embodiments, there is a two way communication of irrigation program-related data between the main control unit and the expansion module **65b**. This two way data communication is the type of communication that can alter the operation of the main microcontroller **32** or otherwise alter the stored irrigation programs of the main microcontroller **32**.

[0127] In the diagram of FIG. 18, the smart expansion module **65b** includes inputs **67** and outputs **83** (which in some embodiments includes station output terminals **58**), coupled to the microcontroller **66a**, which communicates with the control unit or control panel **30** via the bus **39**. The module **65b** also includes module firmware **33b** to operate the microcontroller **66a** and additional module memory **68**.

[0128] One example of a smart expansion module **65b** is an evapotranspiration (ET) module that receives ET data at an input **67** and may optionally include one or more station outputs **67**. The microcontroller **66a** requests and receives an irrigation program from the main microcontroller **32**, alters the program in accordance with the decision making programmed into the module **65b** based on received ET data and returns the irrigation program with altered parameters to the memory of the main microcontroller **32**. The main microcontroller **32** is configured to receive the replacement irrigation program, store it and execute it. In this manner, the expand-

able and open architecture of the main control unit or control panel **30** together with the addition of the smart expansion module **65b** provides additional functionality (e.g., the ability to adjust schedules based on ET data) to the irrigation controller that was not present in the originally designed and configured control panel **30**, without any firmware updates or other changes to the control panel. According to this architecture, the main microcontroller does not need to know in advance the types of possible smart expansion modules **65b** that it could operate together with, it simply shares its data with other modules of unknown functionality and responds to commands and executes adjusted schedules provided by these modules **65b**. Advantageously, the user does not need to purchase a new control panel to upgrade to functions not provided by the control panel, the user simply purchases a smart expansion module **65b** that provides the desired functionality.

[0129] Moreover, in other embodiments, a variation of smart expansion modules defined as interface extension smart modules **65c** is provided which also has the ability to interact with the user interface **21** of the control panel **30**. The interactions between the user and the interface extension module **65c** are shown in FIG. 19. For example, the interface extension module has the ability to send control signaling to the main microcontroller **32** of the control panel **30** to cause textual and graphical information to be displayed on the LCD display **24**. It performs this by sending special messages containing the information to display to the main irrigation microcontroller **32**. The main microcontroller, which is directly connected to the LCD driver electronics, then places that information on the LCD for the user to see. For full interaction with the user, the main microcontroller **32** can also monitor any pressings of the soft keys **25** and will forward that information to the interface extension smart module. The interface extension smart module **65c** is also illustrated in the diagram of FIG. 18 with the module firmware **33b** specific to the functionality of the module **65c**. In addition, all of the other front panel (main control unit) controls, switches **26** and **27** and the rotary dial **22**, are also able to be monitored in the same way by the interface extension smart module. In this manner, the interface extension module **65c** is able to display menus and other information to the user, and then monitor the user's selections with the soft keys. The interface extension smart module is able to create a user interface and entry interaction that does not exist in the firmware **33a** of the controller **10**, without changing or upgrading any firmware operating the main microcontroller **32**. For example, in an interface extension module **65c** including ET functionality (such as the smart expansion module **65b** described above), the interface extension smart module **65c** can generate specific types of displays and prompts for user input, e.g., to configure the ET adjustment processes. The main microcontroller **32** would cause these displays to be displayed on the LCD **24** and monitor the user responses on the soft keys **25**, and finally forward the user response to the display screen or menu provided by the interface extension smart module **65c**. Advantageously, this provides an easy way for the user to access and/or configure a smart expansion module using the main control panel **30**.

[0130] One embodiment of an interface extension smart module **65d** is illustrated in FIG. 32. This embodiment is similar to the embodiment of FIG. 18, but does not have any inputs **67** or outputs **83**. Also illustrated are functional features stored in the firmware **33b** and/or memory **68** of the

interface extension module **65d**. For example, functionality to implement a display driver (through the main microcontroller), to monitor the user inputs of soft keys **25** (through the main microcontroller), additional menu displays and menus (to be sent to the main microcontroller for display) and any additional fonts for the display menus is stored in the firmware **33b** and/or the memory **68**.

[0131] Another variation of a smart expansion module **65e** is illustrated in FIG. **33**. In this embodiment, the expansion module **65e** does not provide terminal inputs or outputs and adds functionality not present in the main microcontroller **32**. For example, functionality of the module **65e** is stored in the firmware **33b** and in the microcontroller **66a**. Additionally, like the other modules **65**, **65a**, **65b**, **65c** and **65d**, the expansion module **65e** can be interchangeably and removably inserted into any module mounting location **45b**. In one embodiment, the expansion module **65e** comprises a re-flash module, which stores new firmware (in memory **68**) to replace the existing firmware **33** in the control panel **30**. When this re-flash module is inserted into the controller, the microcontroller **66a** initiates the process of loading the new firmware into the control panel **30** (after, of course, the control panel has authenticated the expansion module **65e**). In other embodiments, the expansion module **65e** adds functionality to the irrigation controller that does not require inputs or outputs. In an alternative embodiment, a re-flash expansion module is provided that does not require a microcontroller, and where the memory storing the new firmware in the module is directly coupled to the electrical connector **57** of the module. Upon installation, the main microcontroller of control unit extracts the new firmware from the memory and the memory is allowed to directly transmit a copy of the firmware to the main microcontroller without the need for a microcontroller. In this way, the functionality of the controller is updated (to include ET adjustment capabilities) without changing any code or firmware in the control panel **30**.

[0132] Another variation of a smart expansion module **65f** is illustrated in FIG. **34**. In this embodiment, the expansion module **65f** includes one or both of a display **88** and a user input device **89**, such as one or more keys, buttons, knobs, or any other type of device to allow a user to input information to the module. Although the module **65f** is illustrated without terminal inputs or outputs, some variations of this module **65f** include inputs and outputs. The display **88** minimally acts as a status indicator to indicate to the user a status of the operation of the module **65f**. Additionally, the display functions to provide an additional user interface as might be required in order for the user to program and implement the functionality of the expansion smart module **65f**. Additionally, the input device(s) **89** provides a way for the user to enter data or otherwise program or configure the module **65f**. The firmware **33b** allows the microcontroller **66a** to drive the display and interpret user interactions with the input device(s) **89**.

[0133] In one embodiment, once the rotary dial **22** is turned to the "Smart Module" setting, the LCD **24** provides a list of the installed smart expansion modules (and smart expansion modules having interface extension capabilities), e.g., modules **65b**, **65c**, **65d**, **65e**, **65f**. When this list appears, thanks to their built-in intelligence, these type of expansion modules have the ability to report their name and capabilities. Through the data received from the expansion modules **65** during the enumeration process (i.e., the process of the expansion modules **65** self detecting their installation and reporting their presence, type and configuration information to the main

microcontroller), the main microcontroller **32** knows what module mounting locations have modules **65** in them so it knows how many modules belong on this list. Once the user selects the expansion module **65** which he/she wants to program from the list, by using the soft keys **25**, the smart features are activated and the selected interface extension module **65c** takes control of the controller display (e.g., LCD **24**) and provides the user interface screens to the main microcontroller for display. The availability of an "exit" option on the menus created by the interface extension module **65c** allows exiting from the 'user interface extensibility' mode, bringing back the list of smart expansion modules to the LCD **24**.

[0134] Various expansion modules **65** and particularly smart expansion modules may be added to the controller to perform a variety of functions that expand the capabilities of the irrigation controller **10** beyond its basic irrigation functions. Other examples of functional expansion modules not specifically described above that may be added to the controller include: a latching solenoid module that sends a DC pulse along a wire to a latching solenoid operated valve; a wireless module having a wireless transmitter (radio, optical, etc.) that sends a wireless signal to a receiver at a self powered valve; a feature module containing an extra feature such as cycle and soak, etc., not present in the original controller; an alarm module for communicating fault conditions to a homeowner, an alarm company or alike; an lighting module that provides a low voltage output signal to outdoor lighting system (similar to an irrigation output, but intended to operate lights); a fertigation module connecting an automatic fertilization system and allowing the irrigation controller **210** to automate fertilization; a communication module connecting the controller **10** to other communication channels and/or networks including the internet, etc.

[0135] Referring next to FIG. **24**, a flow chart is shown that illustrates one embodiment of the module enumeration process. Enumeration generally involves the process of each expansion module **65** determining its location in the controller backplane **45**, and reporting this information and other details about the module to the main microcontroller. Initially, the modular controller is in normal operational mode (**110**), executing one or more irrigation programs or waiting to be programmed by a user. Many embodiments of the invention allow expansion modules **65** to be inserted and removed during operation of the controller **10** without having to power down the controller **10** or control panel **30**. Since the main microcontroller **32** does not query for new modules, when a new expansion module is mounted to an expansion module mounting location **45b**, the new module **65** detects its presence, determines which mounting location it is in, and announces its presence (along with its type or functionality, and the number of output stations it includes) (Step **111**). Typically, the expansion module **65** waits until the communication bus is quiet and sends a signal, such as an announce message to the main microcontroller. It is noted that in some embodiments, rather than sending a message (containing some data) to announce its presence, the expansion module sends or causes an electrical signal to be output to the main microcontroller, the characteristics of the signal or simply, its presence at the microcontroller, serve as an announcement of the expansion module. The control unit receives the signal (e.g., announce packet or message) from the expansion module and decides if it is a newly installed module (Step **112**). If so, it adds the module **65** to a tracking list so that the main

microcontroller 32 knows which modules 65 are present. The control unit will then respond to acknowledge the new expansion module 65 (not shown). Since the module 65 expects to receive a response from the controller, if the module 65 does not receive an acknowledge packet or message back from the main microcontroller 32 of the control unit, the module, it will assume that a data collision has occurred, and it will wait a period of time (either random or fixed duration), and make another announcement attempt. In one embodiment, the module performs a pseudo-random back off and retransmits the announce message (Step 113). That is, the module 65 waits and retries sending the message. Once acknowledged, the main microcontroller 32 will initiate a two-way challenge/authentication with the module (such as described with reference to FIG. 28). Additionally, the expansion module 65 provides any additional information (Step 114) needed to the main microcontroller 32. Alternatively, the microcontroller 32 requests any required information from the expansion module. In accordance with several embodiments, the main microcontroller 32 then stores any configuration data for the expansion module in memory (Step 115). At this point, the controller (e.g., the main control unit/control panel 30 or the main microcontroller 32) knows what type of expansion module is connected. In preferred form, configuration data includes data or parameters that is user defined and is not specific to the characteristics of a given expansion module itself, but is data that is learned or programmed in the use of the expansion module. For example, in one form, configuration data for an input expansion module may include the types of sensor inputs that the input expansion module is coupled to. That is, the configuration data could include the fact that a given input expansion module is coupled to a moisture sensor (as opposed to a rain sensor or other type of input) or the number of inputs/outputs that are connected. These details are useful to the main microcontroller, but not evident in the characteristics or functional capabilities of the expansion module itself (such as how many inputs or outputs the expansion module has, which is evident in the characteristics of the expansion module). Thus, configuration data can be user defined in use of the expansion module at the installation.

[0136] In normal operation, the main microcontroller 32 continuously sends refreshing signals on a periodic basis to each connected module to confirm that the module is still connected. For its part, the expansion module 65, replies to these refresh signals to let the controller know that it is still connected. If during operation, a given expansion module 65 is unplugged from the backplane, the main microcontroller 32 will stop receiving responses to the refresh signaling sent by the main microcontroller (Step 117). The microcontroller 32 then increments its retry counter (Step 118), and sends additional refresh signals until a response has still not been received from the expansion module after a maximum number of retry attempts (Step 119). At this point, the main microcontroller assumes that the expansion module has been removed and de-enumerates the expansion module (Step 120). In other words, the expansion module is removed from the list of enumerated modules 65. In preferred embodiments, the configuration data (including user defined configuration data) stored in memory is retained until another expansion module is mounted into the location of the removed module. In the event the new module (following steps 111-114) is a replacement module identical in nature to the recently removed module, the same configuration data is used for the replacement module. Advantageously, a module replacing an

expansion module does not need to be reconfigured. That is, it can use the already learned or programmed configuration data as the previous module it is replacing. In one embodiment, upon the enumeration of a replacement expansion module, a copy of the configuration data stored in the memory of the control unit is transmitted to the expansion module and stored in the expansion module as well, since some configuration data may relate to a programmed or user defined parameter of the control unit as it relates to its interaction with the expansion module.

[0137] Speaking of the module enumeration, one preferred embodiment for a module to determine its position within a plurality of expansion module mounting locations 45b is to have pulse code modulated (PCM) coded pulses sent to each connector 47. This ensures a robust digital signal for the expansion modules to use in determining which mounting location they are attached to and requires only a single signal pin at the module connector 57. The PCM pattern delivered is unique for each connector 47. The expansion module 65 sees this PCM pattern and determines which mounting location it is attached to since it knows what PCM coded signals match with which mounting location 45b. FIGS. 29-31 show the details of the PCM signal sent to the expansion modules 65. The PCM signal 85 has a frame SYNC marker to allow the module 65 to know that a PCM stream is about to arrive. In this embodiment, the SYNC marker consists of a pulsed duty cycle of 60% low ("6t" in FIG. 29) followed by a 40% high ("4t" in FIG. 29). The module microcontroller 66a can either use an interrupt to detect the falling edge of the SYNC marker, or use rapid polling to detect it. Each data bit in the PCM signal 85 is then sent using a duty cycle of 25% low followed by 75% high to represent a logic '0' or a duty cycle of 75% low followed by 25% high to represent a logic '1'. A total of 7 bits are sent allowing for a total of 2 to the power of 7=128 modules 65. This PCM technique requires only one data line versus the normal seven data lines required to represent 128 unique module addresses. Anyone skilled in the art will easily realize that changing the number of bits, the duty cycle of either the bits or SYNC marker, using an alternate style of SYNC marker, or eliminating the SYNC marker altogether, are obvious alternate embodiments. One embodiment of the technique for generating these PCM signals is using a digital device, such as a microcontroller (e.g., microcontroller 32) or other logic device that will generate a series of pulse streams as shown in FIG. 30. At each module connector 47, a combination of low-cost diodes, as shown in FIG. 31, is then used to mix these pulse streams to create a unique PCM slot identifier for each module. The diode arrangement technique is cost-effective when there are a large number of module mounting locations (e.g., more than four in the housing 20 or provided through expansion housings(s) 80) as it requires less pins from the pulse stream generator than the number of slots. If the digital device generating the PCM codes has sufficient pins, this device could directly generate the signal waveforms as shown in FIG. 31, eliminating the diodes. Other obvious embodiments, to anyone skilled in the art, will be to use a different form of serial data transmission other than PCM. The advantage of this embodiment is the use of a unique digitally encoded identifier signal for each module 65 consisting of fewer signal lines per module connector 47 than would normally be required to represent the total number of module connectors in a modular irrigation controller.

[0138] In another preferred embodiment for the expansion module to determine its location to report back the main

microcontroller **32**, each module mounting location **45b** is identified by the combination of two input signals. One is an analog signal and the other is a frequency signal. The analog signal is used to identify the module mounting location of a single module within a group of expansion modules (GOM) and the frequency signal is used to identify what group of expansion modules such module belongs to, for example, the irrigation controller **10** is considered as the first group of modules (GOM1), whereas groups of expansion modules in additional expansion housing(s) **80** would be considered in another group of expansion modules. For example, the first external expansion housing **80** which is daisy-chained to the irrigation controller **10** is considered the second group of module (GOM2). And if there is another external expansion housing **80** which is coupled to the first external expansion housing, it is considered to be the third group of module (GOM3), and so on. When used in combination, the analog and frequency signals give a unique identifying address to each module in the system. The analog signal is a voltage divider network may be formed in the backplane circuitry **46** and is formed by 1% resistors that are connected in series. Each module mounting location **45b** will be assigned to a pre-determined voltage signal which is between the logic ground and VCC. (For example: In this case, there are four different voltages for four different module mounting locations **45b**. Module mounting location **1** will be assigned to 0.5V, module mounting location **2** will be assigned to 1V, module mounting location **3** will be assigned to 1.5V, and module mounting location **4** will be assigned to 2V). This same voltage divider network will also be applied to the backplane circuitry of any external expansion housing **80**. In order to distinguish between groups of modules (which expansion housing), the frequency signal is initially generated by the main microcontroller **32** of the irrigation controller **10**. This signal will be divided by $2n$ ($n=1, 2, \dots$) by a frequency divider circuit in the external expansion housing **80** that is daisy-chained to the irrigation controller **10**. It will continuously be divided by another $2n$ by a subsequent frequency divider circuit in the second external expansion housing **80** if connected. In one embodiment, the frequency divider circuit is a simple flip-flop or frequency counter device that will be embedded in the external expansion housing **80**. In operation, the expansion modules **65** store a table of what voltages and frequencies corresponds to what module mounting location of what housing (either the main controller housing **20** or an expansion housing **80**).

[0139] A further preferred embodiment for the expansion module to determine its location to report back the main microcontroller **32** uses a low cost module microcontroller, a resistor and a capacitor to physically locate the expansion module to its physical module mounting location. In operation, each connector **47** has a single dedicated pin (e.g., ENUM-RCX) that has a single dedicated resistor (e.g., see resistor **86** in FIG. **16**) connected to ground or circuit reference. The value of these resistors **86** is different on the backplane circuitry **46** for each module mounting location **45b**. Typically, there might be from four to twelve module mounting locations in an enclosure (although only 4 are illustrated in FIGS. **3-6**). However, this technique is not limited to that range. The resistor value might be assigned as powers of two, such as 1,000 Ohms, 2,000 Ohms, 4,000 Ohms, etc. or some other range and step size in value. On the circuitry **66** of the expansion module **65**, there is a single capacitor (see capacitor **87** of FIG. **14**) connected to the same corresponding pin

(e.g., ENUM-RC) and this capacitor **87** is connected to a reference voltage, such as supply voltage, circuit reference or ground, or some other voltage. The junction of the capacitor **87** and the resistor **86** is also connected to the input pin (e.g., AIN0 of FIG. **14**) of the module microcontroller **66a**. When the expansion module is installed into a module mounting location **45b**, a circuit is closed including the resistor **86** which charges the capacitor **87** to some voltage. This could be performed by configuring this processor pin as an output pin and driving it to the processor supply voltage. Upon charging the capacitor, the module microcontroller then configures the pin to be an input or sensing pin and allows the capacitor **87** to discharge through the resistor **86** that is located on the backplane circuitry **46** and then measure the time it takes to discharge the capacitor **87**. The capacitor values are the same on all plug-in modules. Therefore, since the resistor values are different depending on which mounting location it is coupled to, the time constant is different for every mounting location **45b** because the resistor located on the backplane circuitry **46** forms a resistive-capacitive (RC) time constant with the module capacitor **87**. The microcontroller measures the amount of time required to discharge this RC circuit, and based on the values measured compared to a stored table of known values corresponding to each mounting location **46b**, determines which module mounting location **45b** that expansion module **65** has been installed into. This measurement could be made by a general purpose timer/counter, or program cycle-counter in the software of the microcontroller, and could use an analog comparator input such as is found on many microcontrollers to increase the accuracy of the measurement. The module mounting location, once detected, is reported by the expansion module **65** to the main microcontroller **32**. As a result, the user can see and know which station numbers, valves or other devices are associated with the expansion module. In alternative embodiments, rather than measuring the time to discharge, the time to charge is instead measured and will achieve the same result.

[0140] In preferred embodiments, since the main microcontroller **32** has an open architecture configured to work with and share data with expansion modules **65**, the main microcontroller **32** can make sure the expansion module **65** or the external expansion housing **80** to which it is communicating is "legitimate". Before establishing a normal communication activity, the main microcontroller **32** and the module microcontroller **66a** conduct an authentication scheme. In one embodiment, this is accomplished by exchanging challenge codes and response codes. For example, as described above with reference to FIG. **28**, this "mutual authentication" scheme can be initiated by either the main microcontroller **32** or the expansion module microcontroller **66a**. In the preferred embodiment, the main microcontroller **32** sends a random value (challenge) to the module microcontroller **66a**. The module microcontroller **66a**, then processes this value by passing it through its secret authentication algorithm. The resulting value (response) is sent back to the main microcontroller **32**. The main microcontroller **32** processes the challenge value through the identical secret authentication algorithm. The response value coming from the module microcontroller **66a** is compared to the value expected by the main microcontroller **32**. If these values match, the module is recognized to be "legitimate" by the microcontroller **32** and the irrigation controller **10** resumes its normal operation. If the values do not match, the main microcontroller **32** displays a "rogue device" alert on LCD **24**.

[0141] Historically, dealing with a large number of heavy gauge wires extending from the irrigation controller to each station on the site has been an issue of intense labor, rising cost and wire mapping complexity especially in large sites such as golf courses and cemeteries. In one embodiment, this problem is solved by introducing a special type of expansion output module, namely a 'decoder module', plugged into an expansion module mounting location **45b** of the irrigation controller **10** which will require just a single wire pair to connect to plurality of decoder enabled station valves on the site. This greatly minimizes the wiring requirements by having just a single pair of wires be connected to the controller. Stand-alone specialty controllers that work with decoder valves exist in the irrigation industry. However, one embodiment of the invention provides this decoder functionality in an expansion module to a modular controller that can also operate with other types of regular station expansion modules **65**, input expansion modules **65a**, and smart expansion modules **65b**, **65c**, **65d**, **65e**, **65f** that co-exist with the decoder type outputs. In addition, the use of smart expansion modules in combination with a decoder output module allows the smart expansion modules **65b** and **65c** to control the decoder outputs of a decoder module in a powerful manner not possible with any other controllers in the industry. The components of the decoder module are similar to the components found in FIG. **18**; however, they may not include any inputs **67**. The decoder module includes at least one output signal **83** (a decoder output) that sends signaling to actuate selectable ones of a plurality of decoder-based valves each coupled to the single wire pair coupled to the output signal **83**. Additionally, the decoder module may have multiple decoder outputs to independently control multiple sets of decoder-based irrigation valves. In accordance with the execution of an irrigation program, the microcontroller indicates to the microcontroller **66a** of the decoder module which irrigation valves are to be actuated, and the microcontroller **66a** of the decoder module sends the appropriate signaling to its output terminals to address and actuate the desired valve(s).

[0142] Each expansion module **65** (and likewise modules **65a**, **65b**, **65c**, **65d**, **65e**, **65f**) contains an independent microcontroller **66a** and communicates with the main irrigation microcontroller **32** to report its capability to the controller **10**. In the presently preferred embodiment, the microcontroller **66a** of the expansion module **65** is an ATMEGA8L-8AC microcontroller. The controller **10** then adjusts its operation accordingly based on the module capability. For example, if a new expansion module is detected with a 4-station capacity, then the controller **10** will add only an increment of 4 stations to the 'total available' in the programming menus. This flexibility of employing a plurality of expansion modules **65** provides operational and economic advantages to the contractor who no longer has to stock, install and learn to operate completely different controllers for different types of applications. By allowing different expansion module types to be mixed on a single controller, modular controllers in accordance with several embodiments of the invention provide the contractor with virtually infinite flexibility to tailor controller outputs to the unique set of needs of each individual site. For example, a site may have two or three valve locations that are difficult to access. The contractor could add wireless output module(s) to the controller and install wireless valves in these locations, while using lower cost AC output modules and standard solenoids for the other valves in the system.

[0143] It is common for prior art irrigation controllers to detect a short circuit caused by a mis-wired or a malfunctioning valve and suspend the watering. Those controllers typically assigned the responsibility of reading the short condition and alleviating the problem to the main microcontroller which is typically housed within the control panel. However, this responsibility of the main microcontroller introduces additional burden on the communication path, causing a delay in corrective action before undesirable effects take place. It is an object of another embodiment of the invention to move the short circuit and over-current detection (mis-wired or malfunctioning valve might have short circuit preventing the normal operation) out of the control panel **30** and into the expansion modules **65**, thus bypassing the bottleneck of the bus **39** and the main circuitry **31** (shown in FIG. **15**), and having the ability to detect and take action within milliseconds. This is made possible due to the fact that the module microcontroller **66a** has enough processing power and it is connected directly with the valve actuator (not shown). The module **65** takes immediate action, and then at its leisure, notifies the main circuitry **31**. The main circuitry **31** does its traditional job of sorting out the error conditions and displaying the status to the user. When the module **65** detects this short or over-current condition, it turns the valve off before any damage is done. The user will also be notified of the problem. In one embodiment, the short circuit and over current detection is implemented in the form of a current sensor circuit in the modules **65**. For example, the current sensor circuit **75** (illustrated in FIG. **14**) detects changes in the current from the AC-FUSE-S signal from the backplane circuitry and provides inputs to the microcontroller **66a** so that the microcontroller **66a** in the expansion module **65** can determine if there is a short circuit or over current condition. Again, since this determination occurs within the expansion module, irrigation may be immediately stopped in the event of a short circuit or over current condition without having to wait for the control panel **30** to make such termination.

[0144] As best seen in embodiment illustrated in FIGS. **7** and **8**, the terminals **58** of the base module **55** and the expansion modules **65** comprise snap-in wire terminals that are known in the art of electrical connection. These terminals **58** provide the necessary connection points **58a** to the valve outputs. In preferred form, there are two connection points **58a** for each terminal **58** on expansion modules **65** and one connection point **58a** for each terminal **58** on base module **55** with wire sizes up to 12 AWG. For each connection point **58a** (or pair of connection points **58a**) a wire release feature **58b** is provided which when pushed, allows the wires to be released from the corresponding connection point **58a**.

[0145] Seen clearly in FIG. **4**, the module mounting locations **45a** and **45b** accommodate docking and the electrical coupling of the modules **55** and **65** to the backplane **45**. The base module mounting location **45a** is reserved for the base module **55** and the expansion module mounting locations **45b** are for the expansion modules **65**. The backplane connectors **44** and **47** include pins that carry power and data signals. In one embodiment, these connectors **44** are reverse polarized from contacts **47** through the physical contact housing in order to prevent module **55** and modules **65** from being interchangeable. In preferred form, the connection of these pins from the modules **65** to the backplane **45** is designed to function in accordance with the industry standard term "hotswappable". In addition to this 'hotswapping' feature, any expansion module **65** can be installed in any receptacle,

allowing maximum flexibility for the user. This provided in part by the common bus structure (all expansion modules communicate using the same bus structure) and communication protocol as well as that the microcontroller 32 is configured to not expect modules 65 to be inserted in any particular mounting location or order. This is in contrast to known modular controllers in which the data line structure through the modules requires that modules be inserted in a specific order. Additionally, this is further allowed in that the main microcontroller 32 is configured to expect that a new module can appear and disappear at any time. For example, the main microcontroller automatically receives an announce message when a new module appears and constantly checks to verify that attached modules remain attached. Furthermore, the communication protocol can be asynchronous so that the main microcontroller 32 and the modules 65 can asynchronously communicate. As a result, several embodiments of the invention allow the user to remove or install modules without the need to power down and restart the controller 10. This feature is novel in the irrigation industry as other modular irrigation controllers must first have their power removed before any module can be removed or inserted. To accomplish “hotswapping”, the contacts in the connector 47 are arranged in a manner whereby the power signals establish a circuit connection at either end of the row of contact pins in FIG. 21 (e.g., AC-COM and AC-FUSE are located at either end of the pin configuration) at the same time or before the connection of the data lines (e.g., SMB-DO and SMB-DI) in the center of the connector 47, which are contacted into the mating connector 57 of module 65. This is done to prevent the possible non-orthogonal insertion of the modules from damaging module circuitry. In this manner, the module’s microcontroller power will have contacted before any voltage appears on the data lines. This “hotswapping” feature also allows the module to detect and indicate to the user that the module is not fully engaged mechanically. This condition could be caused by the user not fully applying pressure to the module to engage latch mechanism 59c, or by some other reason which prevented the module from fully engaging. The module, having gotten power from one set of pins at either end of the contacts 47, would be able to detect if the data pins in the center of receptacle were fully engaged and able to communicate with control panel 30. In the case where pin engagement was not made, the module 65 would communicate the problem through the use of the status indicator 56a, (e.g., an LED) so that the user could then reseal the module 65 to provide for full insertion.

[0146] The prior art irrigation controllers have certain disadvantages in regards to the placement of the modules. One such controller by a competitor requires modules to be installed in a specific order. In contrast, modular controllers in accordance with several embodiments of the invention eliminate the need to move an existing module, renumber irrigation zones or disconnect and reconnect valve wires when adding a module to the irrigation controller 10. It is a further object of several embodiments of the invention to allow expansion modules 65 of any output station size capacity to be placed on any receptacle 45b in any order. This is allowed in many embodiments because the modules 65 report their station output capability to the main microcontroller 32, which is configured to accept any number of station outputs, including decoder station outputs. The microcontroller 32 is also configured not to be confused if there is a gap in sequential modules as installed.

[0147] A latching mechanism between the modules 55 or 65 and the backplane cover 43 facilitates the secure, firm and reliable connection of modules 55 or 65 to the backplane circuitry 46. The module 55 or 65 is placed perpendicularly onto the module mounting location 45a or 45b, seen in FIG. 4, on the backplane cover 43. To install the module, the four guideposts 59a in the form of tapered posts on the bottom of the module 55 or 65 are matched into the guide holes 59b located on the backplane cover 43 and the module is pressed into the module mounting location 45a/45b (FIG. 4). The mating guideposts 59a provide alignment to prevent improper insertion of the modules 55 or 65 as well as provide initial alignment for the interconnect between the module 55 or 65 and the backplane circuitry 46 and also allows for “flat on table” storage of modules, preventing damage to the connectors 44 and 47. Releasing the module latching buttons 59 accessible through an opening in the side of the module allows the button latch mechanism 59c (also referred to as a latch having a ledge formed at one end) to expand underneath the backplane cover 43 through the holes 59d causing the module 55 or 65 to be held firmly in place. A “snap” or “click” sound is heard from the module latching buttons 59 when the module 55/65 is fully installed. The module 55 or 65 is released by pressing the two module latching buttons 59 on opposing sides of the module 55 or 65 and pulling the module perpendicularly away from the backplane cover 43.

[0148] Each module 55 and 65 has a status indicator 56a, e.g., a light emitting diode (LED), that illuminates to indicate correct installation of the module 55 or 65, or that the module 55 or 65 is active during valve or other operation. In some embodiments, the status indicator 56a is a sound emitting device.

[0149] To facilitate power consumption reduction, the microcontroller in modules 65 can go to sleep and be awakened by a command or signal from the control panel microcontroller 32. In some embodiments, the controller 10 also incorporates a power supply feature that enhances the component reliability while providing higher power output through a new method based on a modified form of pass regulator topology. The pass regulator transistor, instead of always being on, is switched to on and off modes using available line frequency. The advantage yielded with this approach is the increased system efficiency at no additional cost.

[0150] The backplane circuitry 46 holds the remote connector 63 and the ground terminal blocks 60b, the power terminals blocks 60a, base module connector 44 for the base module mounting location 45a and the connectors 47 for four additional expansion module mounting locations for expansion modules 65. In the illustrated embodiment, no station outputs are found on the backplane circuitry 46, although it is understood that in some embodiments, station outputs may be implemented in the backplane circuitry 46.

[0151] In one embodiment, the remote connector 63, indicated in FIG. 4, provides the means to connect a wireless receiver to the irrigation controller 10. A person equipped with the wireless control has now the means to manually activate irrigation valves, modify the irrigation schedule or the behavior of any additional tasks that the irrigation controller 10 is capable of performing. The remote connection ports found on prior art irrigation controllers are typically placed on the back of the front panel. This type of installation requires cumbersome wiring and wire routing, often times causing the tangling of wires behind the front panel hinge,

making the unit different to close. The preferred embodiment keeps the remote connection port **63** and the wire (not shown) on the backplane **45** contained within the rear housing **40** only, eliminating any complicated wiring and wire routing.

[0152] The prior art irrigation controllers have invented ad hoc or proprietary bus methodologies to solve communication problems. However, the software and firmware used for communications in such prior controllers is often not extensively tested, documented, or reliable, and is often inflexible thus offering few expandability options. Modular controllers in accordance with several embodiments of the invention incorporate, in a unique manner, the time-proven robust Transmission Control Protocol/Internet Protocol (TCP/IP) computer communication protocol for use on the controller's internal communication bus **39**. The use of such a powerful protocol in a modular irrigation controller has never been undertaken in the industry. This preferred method, using TCP/IP, allows for superior flexibility for internal communications between the main microcontroller **32** and other microcontrollers **66a** located in the irrigation controller **10**. It also offers easier and greater communication with external control networks and larger networks. As illustrated in FIG. **27**, a Socket Application Programming Interface allows the main program of the main microcontroller **32**, which operates the irrigation controller, to pass data from the main microprocessor **32** to expansion modules **65** via a User Datagram Protocol (UDP). The physical layer of this TCP/IP-driven communication protocol is a 9-bit serial port and takes advantage of the Serial Line Internet Protocol (SLIP). While the preferred embodiment utilizes the aforementioned physical layer means, the networking software is not hardware specific and can be adapted to many other physical layer methods such as RS232, RS485, or a parallel bus to move data.

[0153] One embodiment incorporates a very compact and efficient TCP/IP protocol stack so that it may fit in the small memory space of the module's microcontroller **66a** thus keeping the cost of the module's microcontroller **66a** as low as possible to create a cost-effective product. Traditionally, the use of a TCP/IP protocol would not be considered viable in a product of this nature. To keep the memory requirements as low as possible, the invention utilizes the UDP flavor of the TCP/IP protocol. The use of TCP/IP protocols within the modular controller allows utilizing the powerful addressing and routing features inherent in the TCP/IP protocol. The control panel **30** and each expansion module **65** are treated as separate internal network devices, each with a uniquely assigned IP address (Internet Protocol address).

[0154] To communicate within a larger network of a centralized system, this embodiment has an external communication interface **34a**. In preferred form, this communication interface also uses a TCP/IP protocol to communicate with the main microprocessor **32**. Thus, the controller **10** has the ability to be connected to an external network and assigned a unique IP address (dynamic or static) and be fully controlled over the Internet or other network. By using the TCP/IP protocol, each expansion module **65** (including input modules **65a**, smart expansion modules **65a**, **65b**, **65c**, **65d**, **65e**, **65f**) can communicate with either the main microprocessor **32** or an external computer located on a private or public network. In return, the external computer can interact directly with every expansion module **65** as the main microprocessor **32** will act as a TCP/IP router directing the data to the correct module. In the preferred embodiment, the external communication interface **34a** incorporates a phone line modem using

Point-to-Point Protocol (PPP). It will be obvious to those skilled in the art, that the communication interface could alternately be an Ethernet interface, wireless interface, etc. Optionally, Internet email may be used to send messages back to the main microcontroller. In addition, a Hypertext Markup Language (HTML) web server can be optionally installed to make communications easier. This way, the irrigation controller can be updated with the latest input data, such as weather and environmental conditions, by email or by direct sending of UDP packets to the controller.

[0155] The following description provides more details regarding many of the pinout configurations of various electrical components of the modular controller **10** in accordance with several embodiments of the invention. Each pinout configuration comprises a plurality of pins of an electrical connector interface designed to couple to a corresponding interface having the same pin assignments. In one embodiment, the pinout assignments for the ribbon cable **49** interface between the control panel **30** and the backplane circuitry **36** as illustrated in FIG. **12** is as follows:

NOT CONNECTED ENUM-FREQ	there is no electrical connection to this pin a frequency timing signal used by the enumeration process in the expansion modules to determine in which mounting location the expansion module is located
12 V-UNREG-RTN	current return connection for 12 volt unregulated power source for the remote control
12 V-UNREG-RTN	current return connection for 12 volt unregulated power source for the remote control
REMOTE-DO MVn	data output signal for remote control output for primary master valve solenoid
BM-LEDn-OUT	base module LED driver signal
BM-STATUS	installed status indicator for base module
NOT CONNECTED	there is no electrical connection to this pin
AC-FUSE	24 vac power source, fuse protected
AC-FUSE-S	24 vac power source with current sensing
AC-COM	24 vac power common line
NOT CONNECTED	there is no electrical connection to this pin
SMB-DO	data output for serial module bus
SMB-DI	data input for serial module bus
REMOTE-DI	data input signal for remote control
I-SENSE-OUT	current sensing signal
MV2n	output for secondary master valve solenoid
SENSOR-FTR	filtered input for external sensor #1
SENSOR2-FTR	filtered input for external sensor #2
NOT CONNECTED	there is no electrical connection to this pin
AC-FUSE	24 vac power source, fuse protected
NOT CONNECTED	there is no electrical connection to this pin
AC-COM	24 vac power common line

[0156] In one embodiment, the pinout assignments **69** for the base module connector interface between the connector **57** of the base module **55** and the connector **44** of the backplane circuitry **36** as illustrated in FIG. **20** is as follows:

MVn	output for primary master valve solenoid
BM-LEDn	base module LED driver signal
BM-STATUS	installed status indicator for base module
AC-FUSE	24 vac power source, fuse protected
AC-COM	24 vac power common line
MV2n	output for secondary master valve solenoid
SENSOR-FTR	filtered input for external sensor #1
SENSOR2-FTR	filtered input for external sensor #2
AC-FUSE-S	24 vac power source with current sensing
AC-COM	24 vac power common line

[0157] In one embodiment, the pinout assignments 78 for the expansion module connector interface between the connector 57 of the expansion module 65 and the connector 47 of the backplane circuitry 36 as illustrated in FIG. 21 is as follows:

AC-COM	24 vac power common line
ENUM-FREQ	a frequency timing signal used by the enumeration process in the expansion module to determine in which mounting location the expansion module is located
AC-FUSE-S	24 vac power source with current sensing
SMB-DI	data input for serial module bus
AC-FUSE	24 vac power source, fuse protected
AC-FUSE (alternatively I-SENSE-OUT)	24 vac power source, fuse protected (alternatively, current sensing signal)
SMB-DO	data output for serial module bus
AC-FUSE-S	24 vac power source with current sensing
ENUM-RC	a resistor connection from the backplane used by the enumeration process in the expansion module to determine in which mounting location the expansion module is located
AC-COM	24 vac power common line

[0158] In one embodiment, the pinout assignments for the external expansion port 62 connector interface to an expansion housing 80 as illustrated in FIG. 22 is as follows:

ENUM-FREQ	a frequency timing signal used by the enumeration process in the expansion module to determine in which mounting location the expansion module is located
SMB-DO	data output for serial module bus
SMB-DI	data input for serial module bus
I-SENSE-OUT	current sensing signal
AC-FUSE	24 vac power source, fuse protected
AC-FUSE	24 vac power source, fuse protected
AC-FUSE-S	24 vac power source with current sensing
AC-FUSE-S	24 vac power source with current sensing
AC-COM	24 vac power common line
AC-COM	24 vac power common line

[0159] In one embodiment, the pinout assignments for the interface to the LCD 24 of the user interface 21 as illustrated in FIG. 25 is as follows:

V5	voltage #5 for the LCD display
V4	voltage #4 for the LCD display
V3	voltage #3 for the LCD display
V2	voltage #2 for the LCD display
V1	voltage #1 for the LCD display
C2-	external capacitor connection
C2+	external capacitor connection
C1+	external capacitor connection
C1-	external capacitor connection
C3+	external capacitor connection
VOUT	voltage for the LCD display
VSS	power source for the LCD display
VDD	power common for the LCD display
D7	data bit 7-most significant bit
D6	data bit 6
D5	data bit 5
D4	data bit 4
D3	data bit 3
D2	data bit 2
D1	data bit 1

-continued

D0	data bit 0-least significant bit
RDn	read strobe signal
WRn	write strobe signal
A0	low order address signal
RESn	display reset signal
CS1n	chip select, enable signal
VSS	power source for the LCD display
VDD	power common for the LCD display

[0160] In one embodiment, the pinout assignments for the communications interface port 34a as illustrated in FIG. 26 is as follows:

1-	there is no electrical connection to this pin
2-RESET	reset signal to the main processor
3-RxD	communication interface serial data input signal
4-	there is no electrical connection to this pin
5-GND	circuit common for data, clock, and reset signals
6-AC-FUSE	24 vac power source, fuse protected
7-TxD	communication interface serial data output signal
8-	there is no electrical connection to this pin
9-ISP-CLK-IN	timing clock for programming of processor flash memory
10-AC-COM	24 vac power common line

[0161] Next, while referring to FIGS. 52-69, a modular controller in accordance with several other embodiments of the invention, generally designated at 210, is illustrated in FIG. 52. As shown, the expandable architecture modular irrigation controller 210 of this embodiment is installed in a water-resistant controller housing or cabinet 212 having a generally box-shaped appearance with a front cover door 216 and a rear main cabinet portion 214, the front cover door being attached to the rear cabinet portion by a hinge 262 that permits the front cover door to be opened for access to the inside of the rear cabinet, as best seen in FIG. 53. When the unit is installed on site, typically on a wall or the like through a key hole mount 213, power wires 218 and valve control wires (not shown here) run through wiring access holes 217 in the bottom of the controller housing 212, as seen in FIG. 54. The new and improved irrigation controller 210 having an expandable architecture modular design allows for easy and economical expansion of the controller capabilities not found in other controllers.

[0162] The controller housing 212, preferably formed of plastic or other suitable material, is designed to withstand various environmental conditions, and houses a base unit 224, a base module 221, expansion modules 222 and smart modules 226 (also referred to as smart expansion modules). To releasably retain the cabinet door 16 in the closed position, the door edge opposite the hinge 262 includes a laterally inwardly projecting lip 266 that releasably mates with an opening 270 formed in a tab 268 projecting forwardly from the front edge of the rear cabinet portion 214. Upon release of the lip 266 from the opening 270, the cabinet door 216 pivotally swings open about the hinge 262 to reveal a removable and programmable control panel 220 that includes a user interface to enter and maintain an irrigation schedule. The cabinet door 216 contains a window 272 to which is mounted a light pipe 247. The light pipe 247 is positioned on the

cabinet door 216 to provide direct viewing of a light emitting diode (led) alarm indicator 246 when the cabinet door 216 is closed.

[0163] The base unit 224 carries out basic irrigation functions and also performs other advanced functions, and comprises the control panel 220 that is removably attached to the front of the rear cabinet portion 214, and a back plane circuit board 251 (see FIGS. 54 and 56) permanently housed in the rear cabinet portion and having circuitry for connection to the base module 221, expansion modules 222 and smart modules 226. The control panel 220 is pivotally coupled to the rear cabinet 214 and swings open to provide access to the interior within which various electronic components, including the backplane circuit board 251 are located. Terminal blocks on the back plane circuit board 251, designated 231a-231e in FIG. 57, provide an interface to the power supply line 218, an earth ground line and various sensor input lines (not shown here).

[0164] It is an object of one embodiment of the present invention to have an easy and intuitive user interface to enter and modify a plurality of irrigation schedules for an irrigation system. As seen in FIG. 53, the front surface of the control panel 220 includes various operational controls and indicators 229 that assist a user in interfacing with and programming the controller and the irrigation system. In this instance, a liquid crystal display (LCD) 236 provides a visual output of information to the user such as when operating the programming functions, among other tasks. An LED Alarm Indicator 246 seen in FIG. 53 illuminates when a faulty condition is detected, for example, at a station output in a standard expansion module 222, or a programming error in the control panel microcontroller 220c. Illumination of the LCD is visible through the window 272 in the cabinet door 216 when it is closed.

[0165] With reference to FIGS. 62 and 69, the control panel 220 has circuitry 220b (shown in FIG. 69) that includes a control panel microcontroller 220c that communicates with the backplane circuitry 251 to activate the irrigation functions as defined in an irrigation program as well as other functions as may be contained in the smart modules 226. The microcontroller 220c sends commands via the back plane circuitry 251 to the base module 221 and/or the expansion modules 222 to activate irrigation valves according to a pre-programmed schedule or via a manually initiated irrigation cycle. In the presently preferred embodiment, the microcontroller 220c of the control panel circuitry 220b employs a TMP87CM20F microcontroller manufactured by Toshiba, and is powered by a 5 VDC power supply. A non-volatile memory backup (EEPROM) 44 maintains the watering schedule upon line power outages.

[0166] As best seen in FIG. 68, the back plane circuitry 251 herein includes 13 active input stations (station 12 is not active) that communicate with the microcontroller 220c of the control panel 220. In this instance, the stations include four station inputs for actuating valves, a master valve station, a rain sensor station, a ground line station, four communications stations, an AC-com station, and an AC-fuse station. The information conveyed from the control panel 220 to the back plane circuitry 251 is then distributed to individual output bays 219 (see FIG. 56) into which one or more irrigation function control modules 221, 222, and 226 have been inserted. As shown in FIG. 68, the base plane circuitry 251 includes an output connection, "module 0", that communicates information to the base module 221; two output con-

nections, "module 1" and "module 2", for bays 219 that can receive expansion modules 222; and an output connection for a smart module 226, "module 3." As will become more apparent hereinafter, not only can an expansion module 222 be used in place of a smart module 226 in the station designated "module 3," but expansion modules can be used in any of the bays 219, with the sole exception of "module 0" which is reserved for the base module 221.

[0167] The control panel 220 can be removed from the controller 210, as seen in FIG. 55, for remote stand-alone programming by the user. In this connection, the control panel 220 is pivotally attached to the front edge of the rear housing portion 214 through a pair of hinge pins 232 that are releasably received in holes 274 formed in tabs 276 projecting forwardly from the rear housing portion. The tabs 276 are sufficiently flexible to permit the pins to be released for removal of the control panel 220, but are sufficiently rigid to retain and support the control panel on the rear housing.

[0168] A detachable ribbon cable 228 removably connects the control panel 220 to the backplane circuitry 251 so as to permit the control panel 220 to be completely removed from the base unit 224. To provide power so that the control panel 220 can be removed and programmed independent of an outside power source, a battery (not shown) is provided in a recess 234 in the control panel 220. This further provides additional flexibility in that, for example, a damaged control panel can quickly be changed and replaced with a new control panel without the need to replace the entire base unit 224. This feature also lets the user enter program information before installing the controller at a job site. In this instance, the battery is retained by a cantilever-type spring biasing element 235 that frictionally presses against the side of the battery to hold it in position. The battery is easily removed via a finger access hole 235b located in the spring biasing element 235 which allows the user to simply insert a finger, pull up on the spring element slightly to release the frictional contact, and remove the battery from the recess 234 shown in FIG. 55. The spring biasing element 235 allows the battery to be retained and/or replaced without the use of any tools, such as screws, and retains the battery without additional parts, such as a latch or a swinging door. This results in less cost for manufacturing due to lack of additional parts (screws, doors, etc.), this also results in an easy, single-handed removal and insertion of the battery.

[0169] A reset button 225 is located at the back of the control panel 220 as seen in FIG. 56. The reset button 225 serves to restart the control panel microcontroller 220c from a potential lock-up condition possibly caused by electrical disturbances. A "remote" connector 239, also indicated in FIG. 56, provides the means to connect a wireless receiver to the irrigation controller 210, and a wire retention channel 239b is provided to direct and restrain the remote connection cables (not shown). An authorized person equipped with the wireless control now has the means to manually activate irrigation valves, modify the irrigation schedule or the behavior of any additional tasks the irrigation controller is capable of performing.

[0170] The base unit 224 relies on the insertion of the base module 221 to be capable of activating any irrigation stations. The base unit 224 does not have sufficient capability by itself to control an irrigation station, as there are no driver or output switches for irrigation stations within the base unit 224. Instead, drivers and switching means are located in the base module 221 and the expansion modules 222. It is an object of

several embodiments of the present invention to achieve flexibility and cost savings. For example, a damaged component such as a microcontroller or station switch in a prior art base unit would require that the entire base unit be replaced. In one embodiment, a damaged component in the base module 221, the expansion module 222 or the smart module 226 requires only that the damaged module be swapped out and replaced on-site by a new module in much less time than is needed to install a new base unit and at significant cost savings. The expandable architecture allows the user to choose from a variety of expansion modules 222 that can include standard irrigation modules for carrying out watering schedules or smart modules 226 for carrying out additional functions.

[0171] Moreover, as shown in FIGS. 58-61, each module 221, 222, and 226 is relatively simple in construction and incorporates similar basic components. As seen in FIG. 61 which depicts the structure of an expansion module 222, but which is also representative of the structures of each of the base and smart modules 221 and 226, the module includes a housing 280 comprising a lower portion 282 and an upper portion 284 which mate together to encase and protect the module circuit board 286, and herein are held together by a screw 288. Rotatably attached to the top of the upper module housing 284 is a rotary locking lever 252 that function to securely hold and retain the module in position when installed into the controller 210. The locking lever 252 has a downwardly projecting pin 281 that is snap fit through a cylindrical sleeve 283 formed in the upper module housing 284 to pivotally attach the locking lever to the upper module housing, and includes an upwardly projecting locking tab 285 that functions to lock the module in its operative position. As best seen from the expansion modules 222 and the smart module 226 in FIG. 56, when the locking lever 252 is in one rotary position, herein the left rotary position, the locking lever is “unlocked” while when the lever is in the counterclockwise rotary position to the right such as shown for the base module 221, the lever is in the “locked” position as shown in FIG. 56A in detail. To frictionally retain the locking lever 252 in the “locked” and “unlocked” rotary positions, the underside of the locking lever has a small downwardly projecting nipple (not shown) that snap fits into corresponding recesses or dimples 287 in the upper module housing 284.

[0172] As shown in FIG. 57, module insertion paths 237A-237D lead to individual bays 219 that accommodate docking and electrically coupling of the expansion modules 222 and smart module 226 with the back plane circuit board 251. In this instance, path 237A is reserved for the base module 221 and paths 237B and 237C are for expansion modules 222 and path 237D is for either another expansion module, or the smart module 226. Each of the modules, 221, 222, and 226 electrically couples and interconnects with the backplane circuitry 251 via sets of conventional spring finger contacts 245 indicated in FIGS. 59 and 61 that electrically couple with complementary sets of conventional electrical contact pins 245A of the backplane circuitry 51 (see FIG. 56). Each module also includes output terminals 223, 227, and 226, herein in the form of conductive screws, to which output wires to irrigation components such as valves and solenoids can be attached in a conventional manner.

[0173] In this connection, the electrical contact pins 245A of the back plane circuitry 251 are grouped in sets corresponding to the location of each bay 219 into which a module can be positioned. Herein, as seen in FIGS. 56 and 57, the electrical contact pin sets 245A for each bay 219 are carried

on generally rectangular shaped tongues 251A formed as part of the back plain circuit board 251, and slide into complementary slots 245B (see FIG. 56A) in the front end of the housing 280 to make electrical contact with the corresponding set of spring finger contacts 245. It should be apparent that additional modules could be accommodated by the addition of an expanded base unit 224 and its back plane 251 and number of bays 219. To secure and retain the Base module 221, the expansion module(s) 222 and the smart module(s) 226 to the base unit 224, and to releasably retain the modules in position, the module insertion paths 237A-237D are partially covered by the backplane cover 250 as seen in FIG. 57, such that the modules can be slid into the module insertion paths 237A-237D and into the bays 219 to be coupled to the backplane circuit board 251, as best shown in FIG. 56.

[0174] To properly position and guide the modules 221, 222, and 226 into the bays 219, each module includes longitudinal recesses (not shown) formed along the bottom of the lower module housing 282 that can mate with upstanding guide rails 230 formed on the bottom wall of the rear cabinet portion as seen in FIG. 57. Once the module is inserted into the bay 219, the user indexes the locking lever 252 from the unlocked to the locked position. In this instance, as best seen in FIG. 56A, the backplane cover 250 has a downwardly projecting wall 250A extending along the length of the forward edge, and which has openings 290 corresponding to the locations of the insertion paths 237A-237D, and through which the locking tabs 285 of the modules can move when the module locking lever 252 is in the “unlocked” position. When a module is fully inserted into one of the insertion paths 237A-237D, the locking lever 252 is then rotated counterclockwise which causes the locking tab 285 to move out of alignment with the opening 290 and into abutting engagement with the rear side of the wall 250A adjacent the opening. With the tab 285 abutting the wall 250A, the module is securely locked in position, and cannot be pulled out of the controller unless the locking lever 252 is first rotated to align the locking tab with the opening 290.

[0175] The base module 221 is responsible for the carrying out basic irrigation functions, such as turning on or off irrigation system valves (not shown here) which control the flow of water to the irrigation stations for the preset programmed duration. The presently preferred circuitry for the base module 221 is illustrated in FIG. 63. As can be seen, the base module circuit 221 includes a bus interface having input connections from the back plane circuit board 251 for controlling a master valve and four individual station valves, and incorporates surge protection circuitry for lightning protection. Valve test circuitry is also provided to allow the user to assess the condition of the system. As best seen in FIG. 58, the base module 221 includes a number of conductive screws that serve as output terminals 223 for connecting the module to irrigation station valves. Herein, the base module 221 includes a plurality of station output terminals 223D-223G (preferably four station output terminals), a ‘hot post’ terminal 223A (VT) to test the valves during installation, a terminal 223B for a master valve (MV) and a terminal 223C for a common wire terminal (COM).

[0176] The expansion modules 222, which are generally identical to each other, enable a user to quickly and easily expand the capabilities of the controller 210 functions without requiring the purchase of a new base unit 224. Each of the expansion modules 222 includes three station output terminals 227, herein in the form of conductive screws, as seen in

FIG. 59, to which output wires to irrigation components such as valves and solenoids can be attached.

[0177] Each expansion module 222 includes a microcontroller 222*b* (see FIG. 64) capable of communicating with the microcontroller 220*c* of the base unit 224. By using a microcontroller in the expansion module 222, the number of connections required is reduced, as well as space and cost. As illustrated in the circuit diagram of FIG. 64, the microcontroller 222*b* is capable of communicating with the control panel microcontroller 220*c* and controls the drivers and switches for the output stations. In the presently preferred embodiment, the microcontroller 222*b* employed in the expansion module is an Atmel AT-TINY 12L-4 microcontroller that provides communication to the base unit 224, thereby substantially reducing the number of connections between the module and the base unit 224 while at the same time handling the 'drivers' to the output stations. The basic irrigation controller 210 in accordance with one embodiment of the invention has no irrigation stations, but separate modules can be added later for a determined location, and to provide possible upgrade for a future improvement to the initial installation.

[0178] The microcontroller 222*b* in the expansion module 222 and the microcontroller 220*c* in the base unit 224 are mutually dependent upon each other in order to operate. The communication between the control panel microcontroller 220*c* and the expansion modules 222 takes place through an asynchronous serial communication line, namely, COMM_X. During the communication, data bits are transmitted in 100 microsecond intervals. In order to obtain a consistent time reference for data reception, bit marks are set at 100 microseconds. Due to the fact that the control panel microcontroller 220*c* and the modules 221 and 222 are running asynchronously, each running on a separate clock, a bit jitter of 8.4 microseconds, worst-case, could be realized. To guarantee the bit jitter not exceeding 8.4 microseconds, it is necessary that the control panel microcontroller 220*c* disables any interrupts associated with any other interrupt functions, such as key actuation by a user, and only service the communication task at hand. Other functions and operations should not be affected adversely since the communication sequence lasts only for approximately half a millisecond per module.

[0179] Preferably, the communication protocol consists of a negative start bit, 3 data bits, and an active low acknowledge. The recognition of the start bit by the module prompts the module to read the station status bits near the center of each 100 us bit mark. Upon completion of the status bits by the control panel microcontroller 220*c*, the control panel microcontroller releases the serial communication line and allows the module to acknowledge data reception by pulling down the serial communication line.

[0180] The microcontroller 222*b* in the expansion module 222 looks at the received data which contains information about which irrigation stations attached to this module should be activated or deactivated. In preferred form, the microcontroller 222*b* receives three consecutive messages with identical information before it actually makes a change to the irrigation station outputs. This provides a robust communication implementation whereby the irrigation stations do not erratically turn on or off under noisy data conditions.

[0181] The control panel microcontroller 220*c* sends irrigation station data to every expansion module 222 through the backplane circuitry 251 on a one second interval, thereby insuring that each microcontroller 222*b* in each expansion

module 222 is refreshed with irrigation station data every one second. The microcontroller 222*b* in the expansion module 222 also includes a timeout mechanism. A timer inside the microcontroller 222*b* and an interrupt service routine in the microcontroller firmware is used to create a repetitive internal clock tick every few hundred microseconds, which in turn, increments a counter to keep track of seconds. This clock tick and counter is used to measure the interval time gap since the last valid communication packet received by the module microcontroller 222*b* from the control panel microcontroller 220*c*. If this time interval gap exceeds five seconds, the microcontroller 222*b* in the expansion module decides that a fatal communication failure has occurred and the microcontroller 222*b* deactivates all irrigation station outputs connected to itself.

[0182] Each time that the control panel microcontroller 220*c* sends irrigation station data to an expansion module 222, the microcontroller 222*b* in the expansion module 222 will respond with an acknowledge bit. This acknowledge bit is transmitted by the microcontroller 222*b* immediately after the receipt of the station status bits in the serial communication. If the control panel microcontroller 220*c* does not receive an acknowledge bit, this is an indication that a module is not installed in that specific path 237A-237D of the bay 219. After communicating with each connector in the bay 219, the control panel microcontroller 220*c* will know which paths have modules installed and which do not. The firmware of the control panel microcontroller 220*c* will correlate this information to determine which irrigation stations are effectively available to the irrigation program. If a user attempts to program an irrigation station that is not present, the firmware will alert the user by displaying a message such as "No Module".

[0183] The spring finger contacts 245 of the expansion modules 222 mate with complementary contact pin sets 245*a* formed in the backplane circuitry 251, for example as is shown in FIG. 59. The backplane contact pins 245*a* carry power and data signals, and are arranged as sets in a manner whereby the power signals establish a circuit connection prior to the data lines when the module is inserted into the bay. In this manner, the module's microcontroller power will have stabilized before any voltage appears on the data lines. Stabilizing the power of the module's microcontroller before voltage is applied to the data lines prevents the microcontroller in the module from latching up or overloading its current ratings on its input/output pins. This allows the module to be removed from and inserted into the bay 219 without the need to first remove power from the remainder of the controller 210. Many embodiments of the modular controller 210 are novel in the industry as other modular irrigation controllers using microprocessors in their modules must first have their power removed before any modules can be removed or inserted. In addition, the firmware in the control panel microcontroller 220*c* is able to handle the dynamic appearance and disappearance of irrigation stations without the need to restart or reboot the firmware. This is made possible by having the firmware continuously verify if a module that corresponds to each irrigation station is installed. For stations that are detected as being not available, the firmware prohibits the user from enabling that station. In addition, it alerts the user that the station is unavailable by displaying a message such as "No Module".

[0184] As shown in FIGS. 64 and 66, the set of spring finger contacts 245 for coupling the expansion modules 222 to the

corresponding set of connector pins **245A** of the back plane **251** herein include two AC power line connections, an earth ground line connection, and a data communication signal line connection. The corresponding pin-out of the back plane circuit **251** is illustrated in FIGS. **66** and **68** and the corresponding signals are as follows: 1—EARTH GROUND, 2—AC COM, 3—AC HOT, and 4—COMM-1 (or 2 or 3 depending on which bay **19** the module is positioned in and indicated in FIG. **64** as “COMM X”).

[**0185**] The communication between the control panel microcontroller **220c** and each of the expansion modules **222** and the smart modules **226** takes place through a serial communication line so that the particular module insertion path **237A-237D** into which an expansion or smart module is inserted makes no difference. Thus, if an expansion module in insertion path **237B** malfunctions and needs to be replaced, the removal of that module will have no effect on the operation of the remaining modules in insertion paths **237C** and/or **237D**.

[**0186**] If the control panel circuit **220b**, illustrated in FIG. **69**, detects the presence of one or more expansion modules **222**, the control panel microcontroller **220c** assigns a default identity to each module and queries the module to identify its functionality. Once in communication, the expansion modules **222** work in concert with the control panel microcontroller **220c** to carry out the programmed functions. For example, the expansion modules **222** can inform the base unit **224** of various conditions, such as temperature, humidity, rain gauge readings, moisture of the ground, etc. the base unit **224** also contains the basic irrigation schedules and is programmed to adjust irrigation schedules based on data received from the expansion modules **222**. Although the expansion modules **222** enable the base unit **224** to change to permit advanced functions such as adjusting for weather conditions, neither the expansion modules **222** nor the base Unit **224** can adjust or change themselves.

[**0187**] Various smart modules **226** may be used to perform a variety of functions that expand the capabilities of the irrigation controller **210** beyond its basic irrigation functions. In this instance the smart module circuit shown in FIG. **65** includes a microcontroller **222c** that is of the same type as that employed in the expansion modules **222**. This and other types of microcontrollers can be employed in the smart modules **222**, and which could be used, for example, to perform such functions as being a latching solenoid module sending a DC pulse along a wire to a solenoid, a wireless module sending a signal to a valve, a decoder module interpreting a command from the controller **210** that indicates when a valve should turn on/off, an input module accepting inputs from sensors and providing information to the controller **210** about environmental condition, weather, etc., a feature module containing an extra feature such as cycle and soak, etc., an alarming module communicating fault conditions to a homeowner, an alarm company or alike, a fertigation module connecting an automatic fertilization system and allowing the irrigation controller **210** to automate fertilization, an evapotranspiration module receiving evapotranspiration data or weather conditions and allowing the controller **210** to adjust irrigation accordingly, a communication module connecting the controller **210** to other communication channels and/or networks including the internet, etc.

[**0188**] Like the expansion modules **222**, the smart modules **226** have a set of conventional spring finger contacts **245** that mate with a corresponding set of conventional connector pins

245A of the backplane circuitry **251**. In this instance, as best seen in FIGS. **65** and **67**, each smart module **226** includes an earth ground connection, two AC power line connections, and two data communication signal connections. As shown in FIGS. **67** and **68**, the complementary set of connector pins **245A** of the back plane circuit **251** for the smart module **226** (referred to as “Module 3” in FIG. **68**) have pin-outs for the corresponding signals are as follows: 1—EARTH GROUND, 2—AC COM, 3—AC HOT, 4—COMM-X, and 5—COMM-4

[**0189**] The smart modules **226** use a dedicated line, herein designated COMM4, to communicate their presence and identity to the control panel microcontroller **220c**. This COMM4 connection is provided in the right-most slot **230D** of the base unit **224**, so that a module inserted therein has access to this additional communication signal. Smart modules **226** can also utilize the asynchronous serial communication line, COMMX, in a similar manner to the expansion modules **222**. In addition, if a Smart module **226** requires extended two-way communications with the base unit **224**, it can achieve that through a software-based communications protocol programmed into the microprocessor of the smart module **226** and that of the base unit **224**. Moreover, if desired, the backplane circuit board **251** can be modified to include additional bays **219** for receiving additional smart modules **226** simply by adding bays with a COMM-4 communication line for two-way communication with the control panel microcontroller **220c** and/or by adding COMM-4 lines to one or more of the bays **219** in which expansion modules **222** are mounted.

[**0190**] Notably, the expandable architecture modular design allows the communication between the smart modules **226** and the base unit **224** such that all smart functions are carried out in the smart modules **226** rather than the base unit **224**. The smart modules **226**, herein having circuitry as shown in FIG. **65**, allow the abilities of the base unit **224** to be upgraded to include new and different functions without requiring the replacement of the base unit **224**. For example, the smart modules **226** provide flexibility by allowing the base unit **224** to interface with an outside user, such as a home security company, to alert the outside user if a sprinkler is not working. The smart modules **226** may be programmed so as to provide an alert that there is a bad solenoid because a valve did not activate. In the case of automatic fertilization, the smart modules **226** could interface with a, homeowner, gardener, etc. to provide an update on conditions.

[**0191**] To guard against the failure of the control panel microcontroller **220c**, a mechanism is in place that allows both the expansion modules **222** and the smart modules **226** to be aware of such failures. The control panel microcontroller **220c** communicates with the modules on a frequent basis. This allows a module to detect the loss of communication. In effect, this action is similar to that of a watchdog timer. While the control panel microcontroller **220c** is active, the expansion modules **222** execute the commands as received in real time from the control panel microcontroller **220c**. However, should there be a communication gap greater than expected, the expansion modules' microcontrollers **222b** interpret this as a control panel microcontroller **220c** failure and immediately shut down any watering activities or other functions until the watchdog conditions have been properly restored. For each command sent to the expansion modules **222**, the expansion modules **222** respond with an acknowledgment. Absence of this acknowledgment informs the control panel

microcontroller 220c that the module has suffered a hardware or software failure. Notably, it makes no difference into which bay 219 an expansion module 222 is positioned, nor to which of the output terminals 227 irrigation station wires are connected. The microcontroller 220c of the control panel 220 monitors the bays 219 for the presence or absence of expansion modules 222, and cooperates with the microcontrollers 222b of the expansion modules to send control signals only to those irrigation stations detected. In this manner, there is no requirement that any particular bay 219 include an expansion module 226, thus allowing the user to add or remove modules in random order, even while the controller 210 is on and active.

[0192] In addition to the normal irrigation program set, labeled A, B & C and stored in non-volatile EEPROM 44, the Controller 210 also contains a contractor's default program set. This contractor's default program set is stored at a separate location in non-volatile EEPROM 44 than the active program set. Irrigation programs for A, B & C are entered through the User Interface 229. A menu choice is available to store this set of irrigation programs into the EEPROM 44 as a contractor's default program set. Thereafter, the user may make changes to the programs A, B & C without concern about making irrigation program mistakes since there is a backup copy. In addition, a knowledgeable irrigation expert can enter a set of programs and store them as the contractor's default program set. A menu choice is available to recall the contractor's default program set from the EEPROM 44 and replace the normal irrigation program set A, B & C. This allows the user to quickly and easily restore a known working irrigation schedule. Other irrigation controllers in the industry have a set of factory defaults with fixed program settings that a user may recall, but do not have the ability to store and recall a set of irrigation programs customized for each individual site.

[0193] Generally, the contractor default program set is a program set that has been modified relative to the factory default, typically by a contractor during installation and is preferably site specific. In one embodiment, the contractor saves this customized program as a set recallable default program. Thus, if a user modifies the program that was input by the contractor, the user has the ability to recall the contractor default if the user is not happy with the changes made. In a prior art controller, the user could recall only the factory default and would have to re-program the controller just to get it back to the customized state the contractor had set up. By having the ability to recall this customized contractor default program, the user can easily go back to the customized state of the program, which was set up for the installation. Generically, the contractor default program may be referred to as modified default program, which is specifically not a factory default. Additional memory space is provided to be able to store both the factory default and the contractor's default in addition to the active program set.

[0194] In other embodiments, a contractor/user may set a contractor default program, save it, then make further changes to the contractor default so that the active program is the modified contractor default program. Then, the user instructs the controller to recall the stored contractor default program after a set period of time (days, hours, etc.). In operation, the controller executes the active program for a set period of time (e.g., 30 days), then the controller automatically stops using the active program and reverts back to the stored contractor default program. This feature may be useful

in situations where the new grass is being planted and this new grass has initial watering needs until the grass takes root and becomes established in the soil. At this later point in time, the watering needs of the grass will have changed. In this example, the contractor will modify the factory default to generate a set of programs that will match the watering needs of the grass after 30 days once the grass has fully grown in. The contractor saves this program set as the contractor default, then modifies these programs further to generate an active program that will meet the current watering needs of the grass and sets the expiration of the active program for 30 days. After 30 days, the controller stops using the active program and recalls the contractor default to use as the active program (while continuing to save the contractor default to be recalled in the event a user modifies the active program and is not satisfied with the modified program). Advantageously, this embodiment allows more flexibility in the programming of the controller and greater ease to a user, who knows that a set of programs customized to the installation may be recalled, as opposed to being able to only recall a factory default which is not site specific.

[0195] While the invention herein disclosed has been described by means of specific embodiments, examples and applications thereof, numerous modifications and variations could be made thereto by those skilled in the art without departing from the scope of the invention set forth in the claims.

What is claimed is:

1. A modular irrigation controller comprising:
 - a housing;
 - a control unit within the housing, the control unit including
 - a first microcontroller for executing stored irrigation programs;
 - a first expansion module removably mounted within the housing and electrically coupled to the first microcontroller, the first expansion module including driver circuitry for actuating irrigation valves in accordance with control signals received from the first microcontroller; and
 - a second expansion module removably mounted within the housing and electrically coupled to the first microcontroller, the second expansion module including a second microcontroller configured to send and receive data communications to and from the first microcontroller, the data communications relating to an irrigation program.
2. The modular irrigation controller of claim 1 wherein the control unit and the second expansion module share data relating to the irrigation program.
3. The modular irrigation controller of claim 1 wherein the first microcontroller is configured to monitor user manipulation of user inputs of the modular irrigation controller and transmit one or more signals providing indications of the user manipulation to the second microcontroller.
4. The modular irrigation controller of claim 1 wherein the one or more data value, variable and/or constant are stored in a first memory associated with the first microcontroller.
5. The modular irrigation controller of claim 1 wherein the data communications relating to the irrigation program include at least a portion of the irrigation program.
6. The modular irrigation controller of claim 1 wherein the first expansion module and the second expansion module are contained entirely within the housing of the modular irrigation controller.

7. The modular irrigation controller of claim 1 further comprising:

a plurality of expansion module mounting locations within the housing and configured to removably receive expansion modules, each expansion mounting location electrically coupled to the first microcontroller,

wherein the first expansion module is coupled to a first one of the expansion module mounting locations and the second expansion module is coupled to a second one of the expansion module mounting locations, and

wherein the first microcontroller is configured to operate with the first expansion module and the second expansion module if the first expansion module was alternatively coupled to the second one of the expansion module mounting locations and the second expansion module was alternatively coupled to the first one of the expansion module mounting locations.

8. A modular irrigation controller comprising:

a housing:

a control unit within the housing, the control unit including a main microcontroller for executing stored irrigation programs;

a plurality of expansion module mounting locations within the housing configured to removably receive expansion modules, each expansion mounting location electrically coupled to the main microcontroller; and

a first expansion module removably mounted to a first expansion module mounting location and electrically coupled to the main microcontroller, the first expansion module including a first microcontroller, the first microcontroller configured to operate with the main microcontroller and provide additional functionality not present in the capabilities of the main microcontroller.

9. The modular irrigation controller of claim 8 further comprising:

a second expansion module removably mounted to a second expansion module mounting location and electrically coupled to the main microcontroller, the second expansion module including driver circuitry for actuating irrigation valves in accordance with control signals received from the main microcontroller.

10. The modular irrigation controller of claim 8 wherein the first expansion module includes driver circuitry for actuating irrigation valves in accordance with control signals received from the main microcontroller.

11. The modular irrigation controller of claim 8 wherein the main microcontroller is programmed to be able to perform a first set of functionality, wherein the first microcontroller is programmed to operate with the main microcontroller, wherein the additional functionality is not included in the first set of functionality, such that the modular irrigation controller can perform the first set of functionality and the additional functionality.

12. The modular irrigation controller of claim 11 wherein the first set of functionality includes the ability to control driver circuitry of one or more expansion modules removably coupled to one or more expansion module mounting locations, the driver circuitry for actuating irrigation valves in accordance with control signals received from the main microcontroller.

13. The modular irrigation controller of claim 11 wherein the additional functionality comprises one or more functions selected from a group consisting of: adjust irrigation based on the evapotranspiration (ET) data; provide a direct current

(DC) pulse to a latching solenoid; transmit a wireless signal; provide a cycle and soak feature; and communicate a fault condition.

14. The modular irrigation controller of claim 8 wherein the first expansion module includes an input to receive data, wherein the additional functionality includes processing the data.

15. The modular irrigation controller of claim 8 wherein the first expansion module is contained entirely within the housing of the modular irrigation controller.

16. The modular irrigation controller of claim 8 wherein the main microcontroller is configured to alternatively function with a second expansion module removably mounted to the first expansion module mounting location, the second expansion module including driver circuitry for actuating irrigation valves in accordance with control signals received from the main microcontroller.

17. An expansion module for a modular irrigation controller comprising:

a housing;

an electrical connector configured to removably connect to one of a plurality of expansion module mounting locations of a modular irrigation controller; and

a microcontroller within the housing and coupled to the electrical connector, the microcontroller configured to operate with a control unit of the modular irrigation controller and provide additional control functionality not present in the capabilities of the control unit.

18. The expansion module of claim 17 wherein the electrical connector is configured to removably connect to any one of the plurality of expansion module mounting locations of the modular irrigation controller.

19. The expansion module of claim 17 wherein the control unit is programmed to be able to perform a first set of functionality, wherein the microcontroller is programmed to operate with the control unit, wherein the additional control functionality is not included in the first set of functionality, such that the modular irrigation controller can perform the first set of functionality and the additional control functionality.

20. The expansion module of claim 19 wherein the first set of functionality includes the ability to control driver circuitry of one or more expansion modules removably coupled to one or more expansion module mounting locations, the driver circuitry for actuating irrigation valves in accordance with control signals received from the control unit.

21. The expansion module of claim 19 wherein the additional control functionality comprises one or more functions selected from a group consisting of: adjust irrigation based on the evapotranspiration (ET) data; provide a direct current (DC) pulse to a latching solenoid; transmit a wireless signal; provide a cycle and soak feature; and communicate a fault condition.

22. The expansion module of claim 17 further comprising an input coupled to the microcontroller and configured to receive data, wherein the additional functionality includes processing the data.

23. The expansion module of claim 17 wherein the housing of the expansion module is sized to be contained entirely within a controller housing of the modular irrigation controller.

24. The expansion module of claim 17 wherein the one of the plurality of expansion module mounting locations of the modular irrigation controller is configured to receive and the

modular irrigation controller is configured to alternatively function with a second expansion module removably mounted to the one of the plurality of expansion module mounting locations, the second expansion module including

driver circuitry for actuating irrigation valves in accordance with control signals received from the control unit.

* * * * *