

(12) PATENT
(19) AUSTRALIAN PATENT OFFICE

(11) Application No. **AU 199951798 B2**
(10) Patent No. **754937**

(54) Title
Pressure controlled pad

(51)⁶ International Patent Classification(s)
A47C 027/08

(21) Application No: **199951798** (22) Application Date: **1999 .07 .29**

(87) WIPO No: **WO00/06001**

(30) Priority Data

(31) Number (32) Date (33) Country
9816473 1998 .07 .30 GB

(43) Publication Date : **2000 .02 .21**

(43) Publication Journal Date : **2000 .04 .20**

(44) Accepted Journal Date : **2002 .11 .28**

(71) Applicant(s)
Huntleigh Technology PLC

(72) Inventor(s)
David Gillman Barber; David Mark Hampson

(74) Agent/Attorney
LORD and COMPANY, 4 Douro Place, WEST PERTH WA 6005

(56) Related Art
US 5074765
GB 2275986

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

51798/99

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : A47C 27/08	A1	(11) International Publication Number: WO 00/06001 (43) International Publication Date: 10 February 2000 (10.02.00)
(21) International Application Number: PCT/GB99/02502 (22) International Filing Date: 29 July 1999 (29.07.99) (30) Priority Data: 9816473.4 30 July 1998 (30.07.98) GB (71) Applicant (for all designated States except US): HUNTLEIGH TECHNOLOGY PLC [GB/GB]; Group IPR Dept., 310-312 Dallow Road, Luton, Bedfordshire LU1 1TD (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): BARBER, David, Gillman [GB/GB]; 14 Grosmont Place, Croesyceiliog, Cwmbran, Gwent NP44 2QX (GB), HAMPSON, David, Mark [GB/GB]; 34 Highfields, Llandaff, Cardiff CF5 2QB (GB). (74) Agent: THAKER, Shalini; Huntleigh Technology plc, Group IPR Dept., 310-312 Dallow Road, Luton, Bedfordshire LU1 1TD (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published With international search report.
(54) Title: PRESSURE CONTROLLED PAD (57) Abstract An inflatable seating pad (10) consists of a hand operated pump (12) integrated within the top surface to inflate the pad with air. The pad (10) has a shut-off connector (6) at one corner which locates and is connected to a pressure relief valve (8). In use, the pad (10) is inflated by pushing upon the hand operated pump (12) to over inflate the pad. The shut-off connector (6) maintains the pressure in the pad (10). To set the pressure to a desired pressure the user actuates the pressure relief valve (pre-set to optimum pressure) to operate the shut-off connector (6) to allow air to exhaust through the pressure relief valve.		

PRESSURE CONTROLLED PAD

The present invention relates to a body support system, in particular to an inflatable support pad that
5 can be set to a desired pressure or firmness.

Such supports, for example, inflatable cushions are well known and are normally set to a desired pressure with the person supported thereon, by either connecting an external pump and gauge to an inflation port on the
10 cushion and sealing the port after inflation or using an external pump with a relief valve set to the required pressure.

The above methods have the disadvantage of having to use a meter gauge or pressure relief valve requiring
15 operator skill to set the desired pressure. Also, the body support systems using such pumps and gauges or relief valves would be very inconvenient and time consuming to set or change to a desired firmness in situ with the person supported thereon.

Accordingly, the present invention provides a
20 pressure controlled inflatable pad apparatus for supporting a body comprising an inflatable pad, a source of fluid to inflate the pad, a shut-off connector connecting the pad to exhaust through a pressure relief
25 valve, the pressure relief valve operating the shut-off connector to connect the pad to exhaust if the pad is over inflated until a predetermined pressure within the pad is reached.

The pressure relief valve is connected to the shut-
30 off connector on the inflatable pad and operates the shut-off connector by means of positive engagement. Therefore, when not actuated the pressure relief valve remains attached and integral with the inflatable pad making it readily available for the user. Further, since the

pressure relief valve only becomes part of the fluid circuit when actuated, the problems associated with such valves when continuously connected are avoided. Thus, there is no gradual leakage in the system due to imperfections in the seal surfaces of such valves. Also, user movement on the pad causing transient high pressures does not result in venting off by the pressure relief valve to a subsequent lower pressure than desired.

The valve is simple to operate when compared to existing systems that require external intervention to remove the valve or the pump, out of circuit.

Preferably, the fluid source is a hand operated pump integrated within the inflatable pad, which makes the inflatable pad a complete single unit body support system without requiring the external pumps with gauges/valves of existing systems. The system is thus a simple design providing a cost advantage over the existing systems, and moreover the carer or user has only one item to carry rather than ensure that the inflatable pad as well as the associated pump/gauges/valves are available.

According to another aspect of the invention, there is provided a pressure controlled inflatable pad apparatus for supporting a body comprising an inflatable seating pad, a hand operated pump located within the pad to inflate the pad, a shut-off connector connecting the pad to exhaust through a pressure relief valve, the pressure relief valve operating the shut-off connector to connect the pad to exhaust if the pad is over inflated until a predetermined pressure within the pad is reached.

According to a further aspect of the present invention there is provided a method of supporting a person on a uniform pressure support surface comprising the steps of inflating an inflatable pad by means of an integrated hand pump to an over inflate condition,

inserting the pad under the person supported thereon, actuating a pressure relief valve connected to a shut-off connector attached to the pad for a pre-determined time whereby the shut-off connector allows air to vent from the
5 pad through the pressure relief valve which is set to a pre-determined pressure.

A preferred embodiment of the present invention will now be described with reference to the accompanying drawings in which;

10 Figure 1 is a schematic view of an inflatable seating pad according to the present invention;

Figure 2 is a cross-sectional view of the pressure relief valve and the shut-off connector according to the present invention; and

15 Figure 3 is a cross-sectional view of the pressure relief valve actuating the shut-off connector.

Referring first to Figure 1, an inflatable seating pad 10 consists of a hand operated pump 12 integrated within the top surface to inflate the pad with air. The
20 pad 10 has a shut-off connector 6 at one corner which locates and is connected to a pressure relief valve 8.

As shown in Figure 2, the shut-off connector 6 consists of a shut-off valve 11 and the pressure relief valve 8 consists of a spring loaded valve closure, in this
25 case a ball 1 resting on a circular seating. Air will flow out of the valve 8 when the air pressure in the pad 10 is greater than the sealing pressure derived from the pre-loaded spring 2.

The relief pressure can be varied by adjusting the
30 pre-load on spring 2. The pre-load is adjusted by a screw threaded plunger 3 acting on the spring 2. The shaft of the plunger 3 includes a coin slot 4 to adjust the spring pre-load and hence the pre-set pressure for the pad 10.

The coin slot 4 allows for the plunger to be rotated

by the user or carer when needed to change the pre-set pressure, but cannot be inadvertently rotated by mistake.

The screw plunger 3 may have a graduated scale 5 around its circumference, to give an indication of the set pressure.

The pressure relief valve assembly 8 is adapted to clip into the connection profile 9 of the shut-off connector 6 on the pad 10.

The pressure relief valve has a locking groove 7 to locate and secure the valve onto the connection profile 9 of the shut-off connector 6. The locking groove 7 is of an increased length than the corresponding connection profile 9 so that upon insertion, the pressure relief valve 8 is held in place within the shut-off connector 6 but does not engage with the shut-off valve 11.

In use, the pad 10 is inflated by pushing upon the hand operated pump 12 several times, say ten, to over inflate the pad 10. The shut-off valve 11 within connector 6 maintains the pressure within the pad. To set the pressure to a predetermined optimum pressure for the user, the user when supported by the pad manually depresses the protruding end 13 of the pressure relief valve 8 which acts on the shut-off valve 11 to allow air to flow through the pressure relief valve to exhaust (see Figure 3).

When released, the spring in the shut-off valve 11 will seal off the connector 6, preventing any further air flow from the pad 10 through to the pressure relief valve 8. The pressure relief valve 8 may be thus activated by the user for a pre-determined time, typically ten seconds, to achieve the desired set pressure which is then maintained by the valve 11 in shut-off connector 6. The pressure relief valve 8 may be activated as and when required to re-set the pressure within the pad.

Although the preferred embodiment, as outlined above, refers to a seating pad the same principle according to the present invention may be used for similar body supports such as inflatable pads or mattresses for lying on, or other types of inflatable body supports such as inflatable compression garments, back or neck supports or the like within the scope of the present invention.

Claims:

1. A pressure controlled inflatable pad apparatus for supporting a body comprising an inflatable pad, a source of fluid to inflate the pad, a shut-off connector connecting the pad to exhaust through a pressure relief valve, the pressure relief valve operating the shut-off connector to connect the pad to exhaust if the pad is over inflated until a predetermined pressure within the pad is reached.
10 reached.
2. A pressure controlled inflatable pad apparatus as claimed in claim 1, wherein the pressure relief valve is connected to the shut-off connector on the inflatable pad and operates the shut-off connector by means of positive engagement
15
3. A pressure controlled inflatable pad apparatus as claimed in claims 1 or 2, wherein the fluid source is a hand operated pump integrated within the inflatable pad.
20
4. A pressure controlled inflatable pad apparatus for supporting a body comprising an inflatable seating pad, a hand operated pump located within the pad to inflate the pad, a shut-off connector connecting the pad to exhaust through a pressure relief valve, the pressure relief valve operating the shut-off connector to connect the pad to exhaust if the pad is over inflated until a predetermined pressure within the pad is reached.
25
5. A pressure controlled inflatable pad apparatus as claimed in claim 4, wherein the pressure relief valve is connected to the shut-off connector on the inflatable pad
30

and operates the shut-off connector by means of positive engagement.

6. A method of supporting a person on a uniform pressure support surface comprising the steps of inflating an inflatable pad by means of an integrated hand pump to an over inflate condition inserting the pad under the person supported thereon, actuating a pressure relief valve connected to a shut-off connector attached to the pad for a pre-determined time whereby the shut-off connector allows air to vent from the pad through the pressure relief valve which is set to a pre-determined pressure.

Fig.1.



