



US012083995B1

(12) **United States Patent**
Smith et al.

(10) **Patent No.:** **US 12,083,995 B1**
(45) **Date of Patent:** **Sep. 10, 2024**

(54) **POWER EXPORT SYSTEM FOR A MILITARY VEHICLE**

(56) **References Cited**

(71) Applicant: **Oshkosh Defense, LLC**, Oshkosh, WI (US)

(72) Inventors: **Chad Smith**, Omro, WI (US); **Nader Nasr**, Neenah, WI (US); **Rachell Harsh**, Oshkosh, WI (US); **Mike J. Bolton**, Oshkosh, WI (US); **Bradon Zeitler**, Oshkosh, WI (US); **Ryan Crabtree**, Oshkosh, WI (US)

(73) Assignee: **Oshkosh Defense, LLC**, Oshkosh, WI (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 160 days.

U.S. PATENT DOCUMENTS

2,612,964 A	10/1952	Dudley
5,081,365 A	1/1992	Field et al.
5,343,970 A	9/1994	Severinsky
5,713,424 A	2/1998	Christenson
5,720,589 A	2/1998	Christenson et al.
5,725,350 A	3/1998	Christenson
5,769,055 A	6/1998	Motose et al.
5,769,592 A	6/1998	Christenson
5,775,867 A	7/1998	Christenson
5,785,486 A	7/1998	McNeilus et al.
5,785,487 A	7/1998	McNeilus et al.
5,820,150 A	10/1998	Archer et al.
5,833,429 A	11/1998	McNeilus et al.
5,851,100 A	12/1998	Brandt
5,857,822 A	1/1999	Christenson
5,863,086 A	1/1999	Christenson
5,868,543 A	2/1999	McNeilus et al.

(Continued)

(21) Appl. No.: **17/886,672**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Aug. 12, 2022**

CN	102490584 A	6/2012
DE	10 2014 201 355 A1	7/2015

(Continued)

Related U.S. Application Data

(60) Provisional application No. 63/344,274, filed on May 20, 2022, provisional application No. 63/233,008, filed on Aug. 13, 2021.

Primary Examiner — Robert L Deberadinis

(74) *Attorney, Agent, or Firm* — Foley & Lardner LLP

(51) **Int. Cl.**
B60R 5/04 (2006.01)
H02K 11/33 (2016.01)


(57) **ABSTRACT**

(52) **U.S. Cl.**
CPC **B60R 5/04** (2013.01); **H02K 11/33** (2016.01); **B60L 2210/10** (2013.01)

A military vehicle includes a chassis, a cab mounted to the chassis and defining a rear wall, an engine mounted to the chassis, an electric machine coupled to the engine and generating electrical power when driven by the engine, an energy storage system receiving and storing electrical power from the generator, and power conversion hardware positioned between the energy storage system and the rear wall of the cab, the power conversion hardware including a DC-DC converter.

(58) **Field of Classification Search**
CPC B60R 5/04; H02K 11/33; B60L 2210/10
See application file for complete search history.

17 Claims, 57 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

5,885,049	A	3/1999	McNeilus et al.	9,533,631	B2	1/2017	Kamimura et al.
5,897,123	A	4/1999	Cherney et al.	9,580,960	B2	2/2017	Aiken et al.
6,083,138	A	7/2000	Aoyama et al.	9,580,962	B2	2/2017	Betz et al.
6,086,074	A	7/2000	Braun	9,650,032	B2	5/2017	Kotloski et al.
6,123,347	A	9/2000	Christenson	9,651,120	B2	5/2017	Morrow et al.
6,371,227	B2	4/2002	Bartlett	9,656,640	B1	5/2017	Verhoff et al.
6,372,378	B1	4/2002	Warner et al.	9,656,659	B2	5/2017	Shukla et al.
6,516,914	B1	2/2003	Andersen et al.	9,669,679	B2	6/2017	Zuleger et al.
6,561,718	B1	5/2003	Archer et al.	9,677,334	B2	6/2017	Aiken et al.
6,672,415	B1	1/2004	Tabata	9,688,112	B2	6/2017	Venton-Walters et al.
6,764,085	B1	7/2004	Anderson	9,707,869	B1	7/2017	Messina et al.
6,779,806	B1	8/2004	Breitbach et al.	9,732,846	B2	8/2017	Li et al.
6,832,148	B1	12/2004	Bennett et al.	9,764,613	B2	9/2017	Rowe et al.
6,883,815	B2	4/2005	Archer	9,765,841	B2	9/2017	Ellifson et al.
6,976,688	B2	12/2005	Archer et al.	9,809,080	B2	11/2017	Ellifson et al.
7,073,620	B2	7/2006	Braun et al.	9,821,789	B2	11/2017	Shukla et al.
7,207,582	B2	4/2007	Siebers et al.	9,849,871	B2	12/2017	Dunlap et al.
7,222,004	B2	5/2007	Anderson	9,890,024	B2	2/2018	Hao et al.
7,258,194	B2	8/2007	Braun et al.	9,908,520	B2	3/2018	Shukla et al.
7,277,782	B2	10/2007	Yakes et al.	9,944,145	B2	4/2018	Dillman et al.
7,302,320	B2	11/2007	Nasr et al.	9,970,515	B2	5/2018	Morrow et al.
7,331,586	B2	2/2008	Trinkner et al.	10,029,555	B2	7/2018	Kotloski et al.
7,357,203	B2	4/2008	Morrow et al.	10,029,556	B2	7/2018	Morrow et al.
7,379,797	B2	5/2008	Nasr et al.	10,030,737	B2	7/2018	Dillman et al.
7,439,711	B2	10/2008	Bolton	10,144,389	B2	12/2018	Archer et al.
7,472,914	B2	1/2009	Anderson et al.	10,160,438	B2	12/2018	Shukla et al.
7,521,814	B2	4/2009	Nasr	10,167,027	B2	1/2019	Perron et al.
7,770,506	B2	8/2010	Johnson et al.	10,221,055	B2	3/2019	Hao et al.
7,848,857	B2	12/2010	Nasr et al.	10,267,390	B2	4/2019	Morrow et al.
7,878,750	B2	2/2011	Zhou et al.	10,315,643	B2	6/2019	Shukla et al.
7,905,540	B2	3/2011	Kiley et al.	10,350,956	B2	7/2019	Dillman et al.
7,937,194	B2	5/2011	Nasr et al.	10,369,860	B2	8/2019	Ellifson et al.
8,000,850	B2	8/2011	Nasr et al.	10,384,668	B2	8/2019	Hilliard et al.
8,005,587	B2	8/2011	Tamor et al.	10,392,000	B2	8/2019	Shukla et al.
8,201,656	B2	6/2012	Archer et al.	10,392,056	B2	8/2019	Perron et al.
8,333,390	B2	12/2012	Linsmeier et al.	10,407,288	B2	9/2019	Hao et al.
8,337,352	B2	12/2012	Morrow et al.	10,421,332	B2	9/2019	Venton-Walters et al.
8,376,077	B2	2/2013	Venton-Walters	10,422,403	B2	9/2019	Ellifson et al.
8,459,619	B2	6/2013	Trinh et al.	10,434,995	B2	10/2019	Verhoff et al.
8,465,025	B2	6/2013	Venton-Walters et al.	10,435,026	B2	10/2019	Shively et al.
8,561,735	B2	10/2013	Morrow et al.	10,457,134	B2	10/2019	Morrow et al.
8,565,990	B2	10/2013	Ortmann et al.	10,458,182	B1	10/2019	Betz et al.
8,596,648	B2	12/2013	Venton-Walters et al.	10,463,900	B1	11/2019	Betz et al.
8,764,029	B2	7/2014	Venton-Walters et al.	10,464,389	B2	11/2019	Zuleger et al.
8,801,017	B2	8/2014	Ellifson et al.	10,486,689	B2	11/2019	Farrell et al.
8,801,393	B2	8/2014	Crabtree et al.	D869,332	S	12/2019	Gander et al.
8,833,324	B2	9/2014	O'Brien et al.	10,532,722	B1	1/2020	Betz et al.
8,834,319	B2	9/2014	Nefcy	10,611,203	B1	4/2020	Rositch et al.
8,839,902	B1	9/2014	Archer et al.	10,611,204	B1	4/2020	Zhang et al.
8,864,613	B2	10/2014	Morrow et al.	10,619,696	B2	4/2020	Dillman et al.
8,876,133	B2	11/2014	Ellifson	10,632,805	B1	4/2020	Rositch et al.
8,955,859	B1	2/2015	Richmond et al.	10,676,079	B1	6/2020	Bucknor et al.
8,955,880	B2	2/2015	Malcolm et al.	10,723,282	B2	7/2020	Perron et al.
8,991,834	B2	3/2015	Venton-Walters et al.	10,724,616	B2	7/2020	Katsura et al.
8,991,840	B2	3/2015	Zuleger et al.	10,752,075	B1	8/2020	Shukla et al.
9,016,703	B2	4/2015	Rowe et al.	10,759,251	B1	9/2020	Zuleger
9,045,014	B1	6/2015	Verhoff et al.	10,836,375	B2	11/2020	Kaufman et al.
9,074,656	B2	7/2015	Benz et al.	10,843,549	B2	11/2020	Morrow et al.
9,114,804	B1	8/2015	Shukla et al.	10,858,231	B2	12/2020	Holmes et al.
9,127,738	B2	9/2015	Ellifson et al.	10,934,145	B2	3/2021	Hao et al.
9,132,736	B1	9/2015	Shukla et al.	10,940,728	B2	3/2021	Rositch et al.
9,174,686	B1	11/2015	Messina et al.	10,953,939	B2	3/2021	Zuleger et al.
9,227,582	B2	1/2016	Katayama et al.	10,960,248	B2	3/2021	Betz et al.
9,291,230	B2	3/2016	Ellifson et al.	10,967,728	B2	4/2021	Kotloski et al.
9,302,129	B1	4/2016	Betz et al.	10,974,561	B2	4/2021	Dillman et al.
9,303,715	B2	4/2016	Dillman et al.	10,974,713	B2	4/2021	Shukla et al.
9,327,576	B2	5/2016	Ellifson	10,974,724	B1	4/2021	Shively et al.
9,328,986	B1	5/2016	Pennau et al.	10,981,538	B2	4/2021	Archer et al.
9,329,000	B1	5/2016	Richmond et al.	10,982,736	B2	4/2021	Steinberger et al.
9,376,102	B1	6/2016	Shukla et al.	10,988,132	B2	4/2021	Ayesh et al.
9,428,042	B2	8/2016	Morrow et al.	10,989,279	B2	4/2021	Morrow et al.
9,434,321	B2	9/2016	Perron et al.	11,001,135	B2	5/2021	Yakes et al.
9,440,523	B2	9/2016	Decker	11,007,863	B2	5/2021	Yakes et al.
9,452,750	B2	9/2016	Shukla et al.	11,027,606	B2	6/2021	Wildgrube et al.
9,492,695	B2	11/2016	Betz et al.	11,034,206	B2	6/2021	Zuleger
				11,046,142	B2	6/2021	Zhang et al.
				11,052,899	B2	7/2021	Shukla et al.
				11,097,617	B2	8/2021	Rocholl et al.
				11,110,977	B2	9/2021	Smith et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

11,111,120	B2	9/2021	Hao et al.	2017/0120899	A1	5/2017	Sugimoto et al.
11,135,890	B2	10/2021	Ellifson et al.	2017/0129475	A1	5/2017	Prakah-Asante et al.
11,136,187	B1	10/2021	Koga et al.	2017/0282737	A1	10/2017	Miller et al.
11,137,053	B2	10/2021	Steinberger et al.	2017/0297425	A1	10/2017	Wildgrube et al.
11,148,550	B2	10/2021	Rocholl et al.	2017/0355259	A1	12/2017	Borud et al.
11,161,403	B2	11/2021	Lo et al.	2017/0355373	A1	12/2017	Dalum
11,161,415	B1	11/2021	Koga et al.	2018/0001839	A1	1/2018	Perron et al.
11,161,483	B2	11/2021	Betz et al.	2018/0009431	A1	1/2018	Akuzawa
11,167,919	B1	11/2021	Koga et al.	2018/0050685	A1	2/2018	Atluri et al.
11,199,239	B2	12/2021	Dumitru et al.	2018/0050686	A1	2/2018	Atluri et al.
11,209,067	B2	12/2021	Ellifson et al.	2018/0162371	A1	6/2018	Colavincenzo et al.
11,230,278	B2	1/2022	Linsmeier et al.	2018/0170349	A1	6/2018	Jobson et al.
11,299,139	B2	4/2022	Shukla et al.	2018/0281772	A1	10/2018	Hilliard et al.
11,358,431	B2	6/2022	Hall et al.	2018/0304882	A1	10/2018	Koh et al.
11,376,943	B1	7/2022	Smith et al.	2018/0370373	A1	12/2018	Hooper et al.
11,376,958	B1	7/2022	Smith et al.	2019/0039407	A1	2/2019	Smith
11,376,990	B1	7/2022	Smith et al.	2019/0084395	A1	3/2019	Toyota et al.
11,377,089	B1	7/2022	Smith et al.	2019/0126759	A1	5/2019	Miller et al.
11,383,694	B1	7/2022	Smith et al.	2019/0129416	A1	5/2019	Upmanue et al.
11,420,522	B1	8/2022	Bernatchez	2019/0135107	A1	5/2019	Fortune et al.
11,498,409	B1	11/2022	Smith et al.	2019/0143957	A1	5/2019	Dalum et al.
11,498,426	B1	11/2022	Bernatchez	2019/0178350	A1	6/2019	Steinberger et al.
11,505,062	B1	11/2022	Smith et al.	2019/0202286	A1	7/2019	Natsume et al.
11,597,399	B1	3/2023	Smith et al.	2019/0276001	A1	9/2019	Kava et al.
11,608,050	B1	3/2023	Smith et al.	2019/0291711	A1	9/2019	Shukla et al.
2005/0080523	A1	4/2005	Bennett et al.	2019/0308669	A1	10/2019	Aitharaju et al.
2005/0109550	A1	5/2005	Buglione et al.	2019/0316650	A1	10/2019	Dillman et al.
2005/0113996	A1	5/2005	Pillar et al.	2019/0344838	A1	11/2019	Perron et al.
2005/0209747	A1	9/2005	Yakes et al.	2020/0001698	A1	1/2020	Jang et al.
2005/0256631	A1	11/2005	Cawthorne et al.	2020/0047740	A1	2/2020	Hoesl
2006/0173593	A1	8/2006	Anderson	2020/0056426	A1	2/2020	Betz et al.
2007/0021879	A1	1/2007	DelNero et al.	2020/0062071	A1	2/2020	Zuleger et al.
2007/0124037	A1	5/2007	Moran	2020/0108709	A1	4/2020	Kohler et al.
2007/0164552	A1	7/2007	Bauer et al.	2020/0117204	A1	4/2020	Lindemann et al.
2007/0186896	A1	8/2007	Carroll et al.	2020/0171907	A1	6/2020	Hall et al.
2007/0278856	A1	12/2007	Craig et al.	2020/0180440	A1	6/2020	Uchimura et al.
2008/0017426	A1	1/2008	Walters et al.	2020/0223276	A1	7/2020	Rositch et al.
2008/0020875	A1	1/2008	Serrels et al.	2020/0232533	A1	7/2020	Dillman et al.
2008/0149405	A1	6/2008	Hladun et al.	2020/0316816	A1	10/2020	Messina et al.
2008/0150350	A1	6/2008	Morrow et al.	2020/0317083	A1	10/2020	Messina et al.
2008/0234096	A1	9/2008	Joshi et al.	2020/0346547	A1	11/2020	Rocholl et al.
2008/0284118	A1	11/2008	Venton-Walters et al.	2020/0346556	A1	11/2020	Rocholl et al.
2009/0098976	A1	4/2009	Usoro et al.	2020/0384823	A1	12/2020	Shukla et al.
2009/0174158	A1	7/2009	Anderson et al.	2020/0384977	A1	12/2020	Higuchi et al.
2009/0192660	A1	7/2009	Tamor et al.	2020/0385977	A1	12/2020	Cooper et al.
2009/0287366	A1	11/2009	Davis et al.	2020/0386135	A1	12/2020	Kobayashi et al.
2009/0298646	A1	12/2009	Parsons	2021/0031649	A1	2/2021	Messina et al.
2009/0326750	A1	12/2009	Ang	2021/0031837	A1	2/2021	Schmidt
2010/0019538	A1	1/2010	Kiley et al.	2021/0070371	A1	3/2021	Ebisumoto et al.
2010/0049389	A1	2/2010	Ando	2021/0070375	A1	3/2021	Ebisumoto et al.
2010/0065001	A1	3/2010	Spicer et al.	2021/0070388	A1	3/2021	Matsuda
2010/0138089	A1	6/2010	James	2021/0107361	A1	4/2021	Linsmeier et al.
2010/0145562	A1	6/2010	Moran	2021/0122205	A1	4/2021	Shukla et al.
2011/0079978	A1	4/2011	Schreiner et al.	2021/0129757	A1	5/2021	Uken
2012/0225751	A1	9/2012	Andreae et al.	2021/0140517	A1	5/2021	Steinberger et al.
2012/0227394	A1	9/2012	Schweiher et al.	2021/0143663	A1	5/2021	Bolton
2012/0244979	A1	9/2012	Kruger	2021/0155063	A1	5/2021	Rositch et al.
2012/0266701	A1	10/2012	Yamada et al.	2021/0155218	A1	5/2021	Higuchi et al.
2012/0299544	A1*	11/2012	Prosser H02J 7/342 320/109	2021/0171137	A1	6/2021	Zuleger et al.
2012/0328454	A1	12/2012	Roby	2021/0173411	A1	6/2021	Rao et al.
2013/0218386	A1	8/2013	Fisker et al.	2021/0178890	A1	6/2021	Steinberger et al.
2014/0228168	A1	8/2014	Kaufman et al.	2021/0188069	A1	6/2021	Friedman
2014/0315064	A1	10/2014	Katayama et al.	2021/0188076	A1	6/2021	Morrow et al.
2015/0188104	A1	7/2015	Templeman et al.	2021/0213822	A1	7/2021	Ripley et al.
2015/0247559	A1	9/2015	Graves	2021/0213934	A1	7/2021	Higuchi et al.
2015/0336568	A1	11/2015	Porrás et al.	2021/0215493	A1	7/2021	Kapadia et al.
2016/0052382	A1	2/2016	Clark et al.	2021/0221190	A1	7/2021	Rowe
2016/0052420	A1	2/2016	Kim	2021/0221216	A1	7/2021	Yakes et al.
2016/0082951	A1	3/2016	Ohn et al.	2021/0231411	A1	7/2021	Grate et al.
2016/0185207	A1	6/2016	Gerschütz et al.	2021/0276450	A1	9/2021	Eshleman et al.
2017/0023947	A1	1/2017	McMillion	2021/0276643	A1	9/2021	Ellifson et al.
2017/0028912	A1	2/2017	Yang et al.	2021/0316588	A1	10/2021	Zhang et al.
2017/0028978	A1	2/2017	Dunlap et al.	2021/0318696	A1	10/2021	Koch
2017/0066431	A1	3/2017	Kim et al.	2021/0323436	A1	10/2021	Rocholl et al.
				2021/0323437	A1	10/2021	Rocholl et al.
				2021/0323438	A1	10/2021	Rocholl et al.
				2021/0327170	A1	10/2021	Rocholl et al.
				2021/0327237	A1	10/2021	Rocholl et al.
				2021/0339632	A1	11/2021	Rocholl et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS

U.S. PATENT DOCUMENTS

2021/0339648 A1 11/2021 Koga et al.
 2021/0354684 A1 11/2021 Healy et al.
 2021/0369515 A1 12/2021 Malcolm et al.
 2021/0380179 A1 12/2021 Smith et al.
 2021/0396293 A1 12/2021 Ellifson et al.
 2022/0001734 A1 1/2022 Tanaka et al.
 2022/0049647 A1 2/2022 Papaioannou et al.
 2022/0063660 A1 3/2022 Poulet et al.
 2022/0118845 A1 4/2022 Mu
 2022/0126878 A1 4/2022 Moustafa et al.
 2022/0268202 A1 8/2022 Pennazza et al.
 2022/0371456 A1 11/2022 Borud et al.
 2022/0379730 A1 12/2022 Bernatchez
 2023/0047110 A1 2/2023 Smith et al.
 2023/0057525 A1 2/2023 Smith et al.
 2023/0415555 A1 12/2023 Murphy et al.
 2024/0063470 A1 2/2024 Linsmeier et al.

DE 10 2016 204 936 A1 9/2017
 DE 10 2017 214 229 A1 2/2018
 DE 10 2018 002 650 A1 10/2019
 DE 10 2018 129 759 A1 5/2020
 DE 10 2021 100 131 A1 7/2021
 EP 1 995 482 A1 11/2008
 EP 3 678 074 A1 7/2020
 ES 2897461 T3 3/2022
 FR 2932556 A1 12/2009
 FR 3082298 A1 12/2019
 JP 2000-224710 A 8/2000
 JP 2007-022309 A 2/2007
 JP 2012-232714 A 11/2012
 WO WO-2005/071819 A1 4/2004
 WO WO-2012/139224 A1 10/2012
 WO WO-2019/116589 A1 6/2019
 WO WO-2020/097885 A1 5/2020

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11





FIG. 12






FIG. 14





FIG. 15






FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 26




FIG. 27




FIG. 29




FIG. 30




FIG. 32

FIG. 31




FIG. 33




FIG. 35

1600 →




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44A




FIG. 44B




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58

4800 →




FIG. 59




FIG. 60

4800




FIG. 61

1

**POWER EXPORT SYSTEM FOR A
MILITARY VEHICLE****CROSS REFERENCE TO RELATED
APPLICATIONS**

This application claims the benefit of and priority to (a) U.S. Provisional Patent Application No. 63/233,008, filed Aug. 13, 2021, and (b) U.S. Provisional Patent Application No. 63/344,274 filed May 20, 2022, both of which are incorporated herein by reference in their entireties.

BACKGROUND

Traditionally, military vehicles have been powered by internal combustion engines. However, such internal combustion engines and related systems can produce a significant amount of noise. Under certain circumstances, such as when in enemy territory and trying to remain discreet and unidentified, it may be advantageous to drive military vehicles and their associated subsystems with the engine off to mitigate the amount of noise being produced by the military vehicles, something that current military vehicles cannot provide.

SUMMARY

One embodiment relates to a military vehicle that includes a chassis, a cab mounted to the chassis and defining a rear wall, an engine mounted to the chassis, an electric machine coupled to the engine and generating electrical power when driven by the engine, an energy storage system receiving and storing electrical power from the generator, and power conversion hardware positioned between the energy storage system and the rear wall of the cab, the power conversion hardware including a DC-DC converter.

In some embodiments, the military vehicle further includes an export power panel including power inputs configured to receive electrical power for charging the energy storage system or powering vehicle components, and power outputs configured to provide electrical power from at least one of the energy storage system and the electric machine to loads remote from the vehicle. In some embodiments, the power input and the power outputs are configured to be arranged in a ring-bus system. In some embodiments, the export power panel is positioned in a passenger side stowage box located vertically above a rear wheel well of the vehicle.

Another embodiment relates to a military vehicle that includes a chassis, a cab mounted to the chassis and defining a rear wall, an engine mounted to the chassis, an electric machine coupled to the engine and generating electrical power when driven by the engine, an energy storage system receiving and storing electrical power from the generator, and an export power panel positioned in a passenger side stowage box located rearward of the rear wall, the export power panel including a power input configured to receive electrical power for charging the energy storage system or powering vehicle components, a power output configured to provide electrical power from at least one of the energy storage system and the electric machine to loads remote from the vehicle, a ring input configured to receive electrical power from a ring-bus system, and a ring output configured to provide electrical power to the ring-bus system.

Another embodiment relates to a military vehicle including a chassis, a cab mounted to the chassis and defining a rear wall, an engine mounted to the chassis, an electric

2

machine coupled to the engine and generating electrical power when driven by the engine, an energy storage system receiving and storing electrical power from the generator, power conversion hardware positioned between the energy storage system and the rear wall of the cab, the power conversion hardware including a DC-DC converter, the power conversion hardware positioned between the energy storage system and the rear wall of the cab, the power conversion hardware including a DC-DC converter, the power conversion hardware fastened to one of the energy storage system, the rear wall, or the chassis, an alternating current power system housed in a driver side stowage box located rearward of the rear wall of the cab and vertically above a driver side rear wheel well, a low voltage system mounted to a passenger wheel well below a topmost plane of a fender well, and an export power panel positioned in a passenger side stowage box located rearward of the rear wall, the export power panel including a power input configured to receive electrical power for charging the energy storage system or powering vehicle components, a power output configured to provide electrical power from at least one of the energy storage system and the electric machine to loads remote from the vehicle, a ring input configured to receive electrical power from a ring-bus system, and a ring output configured to provide electrical power to the ring-bus system.

This summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices or processes described herein will become apparent in the detailed description set forth herein, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a front perspective view of a vehicle, according to an exemplary embodiment.

FIG. 2 is a side view of the vehicle of FIG. 1, according to an exemplary embodiment.

FIG. 3 is a rear view of the vehicle of FIG. 1, according to an exemplary embodiment.

FIG. 4 is a perspective view of a chassis assembly of the vehicle of FIG. 1 including a passenger capsule, a front module, and a rear module, according to an exemplary embodiment.

FIG. 5 is a side view of the chassis assembly of FIG. 4, according to an exemplary embodiment.

FIG. 6 is a cross-sectional view of the passenger capsule of FIG. 4, according to an exemplary embodiment.

FIG. 7 is a detailed side view of a chassis assembly of the vehicle of FIG. 1, according to another exemplary embodiment.

FIG. 8 is a side view of a chassis assembly of the vehicle of FIG. 1, according to another exemplary embodiment.

FIG. 9 is a partially transparent side view of the vehicle of FIG. 1 having a driveline including an engine, an integrated motor/generator ("IMG"), a transmission, an energy storage system ("ESS"), and a front-end accessory drive ("FEAD"), according to an exemplary embodiment.

FIG. 10 is a cross-sectional side view of the driveline of FIG. 9 including the engine, the IMG, the transmission, the ESS, the FEAD, and a transaxle, according to an exemplary embodiment.

FIG. 11 is a detailed side view of the engine, the IMG, the transmission, and the FEAD of the driveline of FIG. 9, according to an exemplary embodiment.

FIG. 12 is an exploded view the IMG and the transmission of the driveline of FIG. 9, according to an exemplary embodiment.

FIG. 13 is a detailed cross-sectional side view of the IMG of the driveline of FIG. 9, according to an exemplary embodiment.

FIG. 14 is a detailed cross-sectional side view of the IMG of the driveline of FIG. 9, according to another exemplary embodiment.

FIG. 15 is a front perspective view of the FEAD of FIG. 9, according to an exemplary embodiment.

FIG. 16 is a front view of the FEAD of FIG. 15, according to an exemplary embodiment.

FIG. 17 is a schematic diagram of the FEAD of FIG. 15, according to an exemplary embodiment.

FIG. 18 is a schematic diagram of a sprag clutch of the FEAD of FIG. 15, according to an exemplary embodiment.

FIG. 19 is a schematic block diagram of the FEAD of FIG. 15 operably coupled with the ESS of FIGS. 9 and 10, according to an exemplary embodiment.

FIG. 20 is a schematic diagram of the FEAD of FIG. 9 without an electric motor/generator, according to another exemplary embodiment.

FIG. 21 is a schematic block diagram of the driveline of FIG. 9 including a power take-off (“PTO”) that is driven by the IMG and coupled to the FEAD, according to another exemplary embodiment.

FIG. 22 is a schematic diagram of the FEAD coupled to the PTO of the driveline of FIG. 21, according to an exemplary embodiment.

FIG. 23 is a schematic block diagram of the FEAD of FIG. 9 including an electric motor for each of the accessories thereof, according to another exemplary embodiment.

FIG. 24 is a schematic diagram of the ESS of FIG. 9, according to an exemplary embodiment.

FIG. 25 is a rear perspective view of the vehicle of FIG. 1 including the ESS of FIG. 24, according to an exemplary embodiment.

FIG. 26 is another rear perspective view of the vehicle of FIG. 25, according to an exemplary embodiment.

FIG. 27 is a rear view of the vehicle of FIG. 25 having a bed cavity, according to an exemplary embodiment.

FIG. 28 is a detailed perspective view of the bed cavity of FIG. 27, according to an exemplary embodiment.

FIG. 29 is another detailed perspective view of the bed cavity of FIG. 27, according to an exemplary embodiment.

FIG. 30 is a detailed perspective view of a rear portion of the vehicle of FIG. 25, according to an exemplary embodiment.

FIGS. 31 and 32 are various views of a portion of the vehicle of FIG. 1 including the ESS of FIG. 24, according to another exemplary embodiment.

FIG. 33 is a section view of the vehicle of FIG. 1 including the ESS of FIG. 24, according to another exemplary embodiment.

FIG. 34 is a perspective view of the vehicle of FIG. 8 including the ESS of FIG. 24, according to an exemplary embodiment.

FIG. 35 is a perspective view of the vehicle of FIG. 7 including the ESS of FIG. 24, according to an exemplary embodiment.

FIG. 36 is a section view of the vehicle of FIG. 1 including the ESS of FIG. 24, according to another exemplary embodiment.

FIG. 37 is a block diagram of a control system for the vehicle of FIG. 1, according to an exemplary embodiment.

FIG. 38 is a graph showing torque versus speed for an internal combustion engine and an electric motor, the graph including a maximum torque as defined by a transmission of the driveline of FIG. 9, according to an exemplary embodiment.

FIG. 39 is a block diagram of a controller of the control system of FIG. 37, according to an exemplary embodiment.

FIG. 40 is a partially transparent side view of the vehicle of FIG. 1 having a driveline including an engine, a transmission, a transaxle drive motor, and a gearbox, according to another exemplary embodiment.

FIG. 41 is a partially transparent side view of the vehicle of FIG. 1 having a driveline including an engine, a transmission, a drive motor, and a gearbox arranged in a rear engine power take-off arrangement, according to another exemplary embodiment.

FIG. 42 is a partially transparent side view of the vehicle of FIG. 1 having a driveline including an engine, a drive motor, a transmission, and a gearbox, according to another exemplary embodiment.

FIG. 43 is a left side view of the rear module of the vehicle of FIG. 1 including a power export system, according to another exemplary embodiment.

FIG. 44A is a right side view of the power export system of FIG. 43, according to an exemplary embodiment.

FIG. 44B is a rear perspective view of the power export system of FIG. 43, according to an exemplary embodiment.

FIG. 45 is a schematic view of a ring-bus system including the vehicle having the power export system of FIG. 43, according to an exemplary embodiment.

FIG. 46 is a flow chart of a method of operating the export power panel of the vehicle of FIG. 43, according to an exemplary embodiment.

FIG. 47 is a perspective view of the rear module of the vehicle of FIG. 1 including a power export system, according to another exemplary embodiment.

FIG. 48 is a perspective view of a transfer case of the power export system of FIG. 47, according to an exemplary embodiment.

FIG. 49 is a perspective view of the transfer case of FIG. 48, according to an exemplary embodiment.

FIG. 50 is a section view of the transfer case of FIG. 48, according to an exemplary embodiment.

FIG. 51 is a section view of the transfer case of FIG. 48, according to an exemplary embodiment.

FIG. 52 is a perspective view of a generator gear box of the power export system of FIG. 47, according to an exemplary embodiment.

FIG. 53 is a section view of the generator gear box of FIG. 52, according to an exemplary embodiment.

FIG. 54 is a front view of the power export system of FIG. 47, according to an exemplary embodiment.

FIG. 55 is a perspective view of a chassis of the vehicle of FIG. 1 including mounting brackets, according to an exemplary embodiment.

FIG. 56 is a perspective view of the mounting brackets of FIG. 55 including an enclosure, according to an exemplary embodiment.

FIG. 57 is a perspective view of the enclosure of FIG. 56 and an export power panel, according to an exemplary embodiment.

FIG. 58 is a perspective view of the power export system of FIG. 47, according to an exemplary embodiment.

FIG. 59 is a perspective view of a low voltage system of the power export system of FIG. 47, according to an exemplary embodiment.

5

FIG. 60 is a left side view of the power export system of FIG. 47 including a primary fuel tank and a stowage box, according to an exemplary embodiment.

FIG. 61 is a right side view of the power export system of FIG. 47 including a secondary fuel tank, according to an exemplary embodiment.

DETAILED DESCRIPTION

Before turning to the figures, which illustrate certain exemplary embodiments in detail, it should be understood that the present disclosure is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology used herein is for the purpose of description only and should not be regarded as limiting.

According to an exemplary embodiment, a vehicle of the present disclosure (e.g., a military vehicle, etc.) includes an electrified driveline. Specifically, the vehicle includes (i) a first driver including an internal combustion engine and (ii) a second driver including a motor/generator and a clutch. The clutch is positioned between the engine and the motor/generator. The engine can drive the driveline independently, the motor/generator can drive the driveline independently, and/or both the engine and the motor/generator can drive the driveline together. Such an electrified driveline arrangement facilitates operating the vehicle in variety of ways that current military vehicles are incapable of.

According to an exemplary embodiment, the vehicle of the present disclosure includes an engine and a FEAD. The FEAD can include a first belt and a second belt that are coupled with each other through a sprag clutch. The first belt is coupled with multiple accessories, which may include, but is not limited to, a fan, an air compressor, and an electric motor/generator. The second belt is coupled with an output of the engine and the sprag clutch. The sprag clutch is coupled with an additional accessory (e.g., a hydraulic pump). The FEAD is operable between an engine-driven mode and an electric-driven mode (e.g., an electrified mode). When the FEAD is operated in the engine-driven mode, the engine drives the second belt and the first belt (e.g., through the sprag clutch) and the accessories that are coupled with the sprag clutch and the first belt. When the FEAD is operated in the engine-driven mode, the electric motor/generator may be driven to generate electrical energy that can be stored in a battery or consumed by electric accessories of the vehicle. When the FEAD is operated in the electric-driven mode, the electric motor/generator drives the first belt and the accessories coupled with the first belt, and the additional accessory (e.g., the hydraulic pump) coupled with the sprag clutch. In the electric-driven mode, the electric motor/generator consumes electrical energy from the battery, and operates independently of operation of the engine.

In alternative embodiments, the FEAD does not include the electric motor/generator. In one such embodiment, the FEAD may instead be driven solely by the engine and the FEAD only operates according to an engine-driven mode. In another such embodiment, a PTO is positioned at an output of an IMG or a transmission of a driveline of the vehicle, and the PTO can be engaged while the IMG or the transmission drives the PTO. The PTO may transfer torque to the FEAD belt in place of the electric motor/generator to thereby drive the FEAD using an electrically-driven source. In still another such embodiment, one or more accessories, or all of the accessories, of the FEAD include a corresponding electric motor so that each of the accessories of the FEAD

6

having the corresponding electric motor can be independently operated relative to operation of the engine (if included), and relative to operation of each other.

According to an exemplary embodiment, the vehicle of the present disclosure includes an ESS with a large battery capable of providing electric vehicle propulsion. The ESS can be stored behind a cab within a bed cavity, behind a cab outside the bed cavity, above the rear wheel wells, between a floor and a belly deflector, above a floor within the cab, and/or below a false floor above the floor.

According to an exemplary embodiment, the vehicle of the present disclosure includes a control system. The control system includes a controller configured to operate the vehicle according to different modes. The modes include an engine mode, a dual-drive mode, an EV/silent mode, and/or an ultrasilent mode. In the engine mode, an engine of the vehicle drives the FEAD and tractive elements of the vehicle for transportation. In the dual-drive mode, both the engine and an IMG of the vehicle drive the tractive elements of the vehicle for transportation. In the EV/silent mode, the IMG drives the tractive elements of the vehicle for transportation with the engine shut off and an electric motor of the FEAD drives the FEAD. In the ultrasilent mode, the IMG drives the tractive elements of the vehicle for transportation with the engine shut off, the electric motor drives the FEAD, and a fan of the FEAD is disengaged to further reduce sound output of the vehicle during operation.

According to an exemplary embodiment, the vehicle of the present disclosure includes a driveline assembly that can be configured to operate in an (i) engine-only travel mode, (ii) an electric-motor-only travel mode, and/or (iii) a hybrid or dual-drive travel mode where each of the engine and an electric motor can be used to drive the vehicle. The vehicle includes an onboard energy storage system (e.g., a battery) that is configured to supply the electric drive motor with power to drive the vehicle for an extended period of time (e.g., 30 minutes) within the electric-motor-only mode or a "silent mode" or a "stealth mode." The driveline assembly is arranged so that the electric drive motor of the vehicle can be selectively clutched into one or more of a transaxle drive shaft, a transmission shaft, or a transaxle to supply torque to each of a front axle assembly and a rear axle assembly to drive the vehicle. During the silent or stealth mode, the engine can be decoupled from the transmission or the transaxle drive shaft, which allows the vehicle to drive entirely independent of the engine for a period of time. This type of operation can permit the vehicle to perform tasks discretely, which provides a significant advantage to military vehicles that may wish to travel undetected through enemy territory, for example.

Overall Vehicle

According to the exemplary embodiment shown in FIGS. 1-3, a machine, shown vehicle 10, is configured as a military vehicle. In the embodiment shown, the military vehicle is a joint light tactical vehicle ("JLTV"). In other embodiments, the military vehicle is another type of military vehicle (e.g., a medium tactical vehicle, a heavy tactical vehicle, etc.). In an alternative embodiment, the vehicle 10 is another type of vehicle other than a military vehicle. For example, the vehicle 10 may be a fire apparatus (e.g., a pumper fire truck, a rear-mount aerial ladder truck, a mid-mount aerial ladder truck, a quint fire truck, a tiller fire truck, an airport rescue fire fighting ("ARFF") truck, etc.), a refuse truck, a concrete mixer truck, a tow truck, an ambulance, a farming machine or vehicle, a construction machine or vehicle, and/or still another vehicle.

As shown in FIGS. 1-14, the vehicle 10 includes a chassis assembly, shown as hull and frame assembly 100, including a passenger cabin, shown as passenger capsule 200, a first module, shown as front module 300, a second module, shown as rear module 400; a plurality of axle assemblies (e.g., including axles, differentials, wheels, brakes, suspension components, etc.), shown as axle assemblies 500, coupled to the front module 300 and the rear module 400; and a first electrified driveline arrangement (e.g., a powertrain, a drivetrain, including an accessory drive, etc.), shown as driveline 600.

According to an exemplary embodiment, the passenger capsule 200 provides a robust and consistent level of protection by using overlaps to provide further protection at the door interfaces, component integration seams, and panel joints. The passenger capsule 200 may be manufactured from high hardness steel, commercially available aluminum alloys, ceramic-based SMART armor, and/or other suitable materials to provide a 360-degree modular protection system with two levels of underbody mine/improvised explosive device (“IED”) protection. The modular protection system provides protection against kinetic energy projectiles and fragmentation produced by IEDs and overhead artillery fire. The two levels of underbody protection may be made of an aluminum alloy configured to provide an optimum combination of yield strength and material elongation. Each protection level uses an optimized thickness of this aluminum alloy to defeat underbody mine and IED threats.

According to an exemplary embodiment, the passenger capsule 200 is a structural shell that forms a monocoque hull structure. Monocoque refers to a form of vehicle construction in which the vehicle body and chassis form a single unit. In some embodiments, the passenger capsule 200 includes a plurality of integrated armor mounting points configured to engage a supplemental armor kit (e.g., a “B-Kit,” etc.). According to the exemplary embodiment shown in FIGS. 1, 2, 4, 5, 9, and 10, the passenger capsule 200 accommodates four passengers in a two-by-two seating arrangement and has four doors mounted thereto. According to the alternative embodiment shown in FIG. 8, the passenger capsule 200 accommodates two passengers and has two doors mounted thereto.

As shown in FIGS. 4-6, the passenger capsule 200 includes a floor assembly, shown as floor assembly 202, having a pair of floor portions, shown as floor portions 204, laterally spaced apart and separated by a central tunnel, shown as structural tunnel 206, extending longitudinally along a centerline of the passenger capsule 200. According to an exemplary embodiment, for load purposes, the structural tunnel 206 replaces a frame or rail traditionally used in vehicle chassis. As shown in FIG. 6, the structural tunnel 206 (i) has an arcuately shaped cross-section that extends upward into an interior, shown as passenger compartment 218, of the passenger capsule 200 and (ii) defines a cavity or recessed space, shown as tunnel slot 208. The configuration of the structural tunnel 206 increases the distance between the ground and the passenger compartment 218 of the passenger capsule 200. Accordingly, the structural tunnel 206 may provide greater blast protection from IEDs located on the ground (e.g., because the IED has to travel a greater distance in order to penetrate the structural tunnel 206).

As shown in FIGS. 4-6, the passenger capsule 200 additionally includes a pair of side panels, shown as sidewalls 210, coupled to opposing lateral sides of the floor assembly 202; a top panel, shown as roof 212, coupled to the sidewalls 210 opposite the floor assembly 202; a front panel, shown as front wall 214, coupled to front ends of the floor assembly

202, the sidewalls 210, and the roof 212; and a rear panel, shown as rear wall 216, coupled to rear ends of the floor assembly 202, the sidewalls 210, and the roof 212. As shown in FIGS. 4 and 6, the floor assembly 202, the sidewalls 210, the roof 212, the front wall 214, and the rear wall 216 cooperatively define the passenger compartment 218.

As shown in FIG. 6, the passenger capsule 200 includes a belly deflector, shown as v-shaped belly deflector 220, coupled to bottom ends of the sidewalls 210 and across the bottom of the passenger capsule 200 beneath the floor assembly 202. According to an exemplary embodiment, the v-shaped belly deflector 220 is configured to mitigate and spread blast forces along the belly of the vehicle 10. As shown in FIG. 6, the v-shaped belly deflector 220 is spaced from the floor assembly 202 such that a space, shown as air gap 222, is formed between the floor portions 204 of the floor assembly 202 and the v-shaped belly deflector 220.

In some embodiments, the floor assembly 202, the sidewalls 210, the roof 212, the front wall 214, the rear wall 216, and the v-shaped belly deflector 220 are fabricated subassemblies that are bolted together to provide the passenger capsule 200. Such a modular approach to the passenger capsule 200 provides increased protection with the application of perimeter, roof, and underbody add on panels. The components of the passenger capsule 200 mitigate and attenuate blast effects, allow for upgrades, and facilitate maintenance and replacements.

As shown in FIGS. 4, 5, 7, 8, and 10, the front module 300 includes a first subframe assembly, shown as front subframe 310, and the rear module 400 includes a second subframe assembly, shown as rear subframe 410. The front subframe 310 includes a first plurality of frame members coupled to the floor assembly 202 and the front wall 214 of the passenger capsule 200 at a first plurality of interfaces. The rear subframe 410 includes a second plurality of frame members coupled to the floor assembly 202 and the rear wall 216 of the passenger capsule 200 at a second plurality of interfaces. Such interfaces may include, for example, a plurality of fasteners (e.g., bolts, rivets, etc.) extending through corresponding pads coupled to the front subframe 310, the rear subframe 410, and the passenger capsule 200. According to an exemplary embodiment, a front axle assembly of the axle assemblies 500 is coupled to the front subframe 310 and a rear axle assembly of the axle assemblies 500 is coupled to the rear subframe 410.

The front subframe 310 and the rear subframe 410 may be manufactured from high strength steels, high strength aluminum, or another suitable material. According to an exemplary embodiment, the front subframe 310 and the rear subframe 410 feature a tabbed, laser cut, bent, and welded design. In other embodiments, the front subframe 310 and the rear subframe 410 are manufactured from tubular members to form a space frame. The front subframe 310 and the rear subframe 410 may also include forged frame sections, rather than fabricated or cast frame sections, to mitigate the stress, strains, and impact loading imparted during operation of the vehicle 10. Aluminum castings may be used for various cross member components where the loading is compatible with such material properties.

The passenger capsule 200, the front subframe 310, and the rear subframe 410 are integrated into the hull and frame assembly 100 to efficiently carry chassis loading imparted during operation of the vehicle 10, during a lift event, during a blast event, or under still other conditions. During a blast event, conventional frame rails can capture the blast force, transferring the blast force into the vehicle 10 and the occupants thereof. The vehicle 10 replaces conventional

frame rails and instead includes the passenger capsule 200, the front module 300, and the rear module 400. According to an exemplary embodiment, the passenger capsule 200, the front module 300, and the rear module 400 vent blast gases (e.g., traveling upward after a tire triggers an IED), thereby reducing the blast force on the passenger capsule 200 and the occupants within passenger capsule 200. Traditional frame rails may also directly impact (e.g., contact, engage, hit, etc.) the floor of traditional military vehicles. The hull and frame assembly 100 does not include traditional frame rails extending along a length of the vehicle 10, thereby eliminating the ability for such frame rails to impact the floor assembly 202 of the passenger capsule 200.

As shown in FIGS. 1, 2, and 9, the front module 300 includes a body panel, shown as hood 320, supported by the front subframe 310. As shown in FIG. 9, the hood 320 partially surrounds components of the driveline 600 (e.g., an engine, a FEAD, radiators, etc.) of the vehicle 10. The hood 320 may be manufactured from a composite material (e.g., carbon fiber, fiberglass, a combination of fiberglass and carbon fiber, etc.) or a metal material (e.g., steel, aluminum, etc.). The hood 320 may be configured (e.g., shaped, etc.) to maximize vision while clearing under-hood components.

As shown in FIGS. 1-3, the rear module 400 includes a body assembly, shown as cargo body assembly 420, supported by the rear subframe 410. The cargo body assembly 420 includes a deck, shown as bed 430; a pair of wheel wells, shown as wheel wells 440, positioned along opposing lateral sides of the bed 430 and over the wheels of the rear axle assembly of the axle assemblies 500; and a pair of storage compartments, shown as stowage boxes 450, positioned along and on top of the wheel wells 440. As shown in FIG. 3, the bed 430, the wheel wells 440, and the stowage boxes 450 cooperatively define a compartment, shown as bed cavity 460.

In some embodiment, as shown in FIG. 7, the passenger capsule 200 includes a protrusion, shown as capsule extension 224, extending from a bottom portion of the rear wall 216 of the passenger capsule 200. According to an exemplary embodiment, the capsule extension 224 provides an extended wheelbase for the vehicle 10, which facilitates providing a cavity, shown as gap 226, between the rear wall 216 and the cargo body assembly 420 of the rear module 400. In some embodiments, as shown in FIG. 8, the capsule extension 224 replaces a rear portion (e.g., back seats, etc.) of the passenger capsule 200 and supports an extended cargo body assembly 420 (e.g., eliminating the gap 226 of FIG. 7 or maintaining the gap 226 of FIG. 7).

Driveline

As shown in FIGS. 9-36, the driveline 600 includes a first driver, shown as engine 610; a transmission device, shown as transmission 620; a first drive shaft, shown transaxle drive shaft 630, coupled to the transmission 620; a power splitter, shown as transaxle 640, coupled to the transaxle drive shaft 630 and the rear axle assembly 500; a second drive shaft, shown as front axle drive shaft 650, extending between the transaxle 640 and the front axle assembly 500 (e.g., a front differential thereof); a second driver, shown as IMG 700, positioned between the engine 610 and the transmission 620; an accessory drive assembly, shown as FEAD 800, positioned in front of the engine 610; and an on-board ESS, shown as ESS 1000.

As shown in FIGS. 9 and 10, the engine 610 and the FEAD 800 are positioned within the front module 300 and supported by the front subframe 310. The FEAD 800 may include an independent FEAD motor (e.g., motor/generator 822) and various belt driven-accessories and/or electrically-

operated accessories (e.g., a fan, a hydraulic pump, an air compressor, an air conditioning ("A/C") compressor, etc.). As shown in FIG. 10, the IMG 700 and the transmission 620 are positioned beneath the passenger capsule 200 within the tunnel slot 208 of the structural tunnel 206. The transaxle drive shaft 630 extends from the transmission 620 longitudinally along the structural tunnel 206 and within tunnel slot 208 to the transaxle 640. According to an exemplary embodiment, the transaxle 640 is positioned within the rear module 400 and supported by the rear subframe 410. As shown in FIG. 10, the front axle drive shaft 650 is positioned beneath the transaxle drive shaft 630 and outside of the tunnel slot 208 (e.g., between the transaxle drive shaft 630 and the v-shaped belly deflector 220).

According to various embodiments, the engine 610 is individually, the IMG 700 is individually, or both the engine 610 and the IMG 700 are cooperatively configured to provide power to the transmission 620 to drive the transmission 620 and, thereby, drive the transaxle drive shaft 630, the transaxle 640, the rear axle assembly 500, the front axle drive shaft 650, and the front axle assembly 500 to drive the vehicle 10. According to various embodiments, the FEAD 800 is configured to be selectively driven by the engine 610, by the FEAD motor, by the IMG 700, and/or electrically-operated. According to an exemplary embodiment, the ESS 1000 is configured to power various high-voltage components and low-voltage components of the vehicle 10 (e.g., the IMG 700, the FEAD motor, electrified FEAD accessories, cab displays, cab gauges, cab lights, external lights, etc.). According to various embodiments, except for electrical wiring, the components of the ESS 1000 (e.g., battery packs, inverters, power distribution components, power conversion hardware, etc.) are variously positioned about the vehicle 10 (e.g., within the rear module 400, under the passenger capsule 200, etc.), except proximate the engine 610 or within the tunnel slot 208 of the structural tunnel 206. Such positioning facilitates maintaining the components of the ESS 1000 at proper operating temperatures and away from high temperature zones proximate the engine 610 and/or within the tunnel slot 208 of the structural tunnel 206. In some embodiments (e.g., when the FEAD 800 includes the FEAD motor, when the engine 610 drives the FEAD, etc.), the FEAD motor and the IMG 700 are configured to selectively operate as generators to facilitate charging the ESS 1000 using power provided by the engine 610 while the vehicle 10 is stationary or moving.

Engine, Transmission, and Transaxle

According to an exemplary embodiment, the engine 610 is a compression-ignition internal combustion engine that utilizes diesel fuel. In other embodiments, the engine 610 is a spark-ignition engine that utilizes one of a variety of fuel types (e.g., gasoline, compressed natural gas, propane, etc.). The transmission may be a commercially available transmission. The transmission 620 may include a torque converter configured to improve efficiency and decrease heat loads. Lower transmission gear ratios combined with a low range of an integrated rear differential/transfer case provide optimal speed for slower speeds, while higher transmission gear ratios deliver convoy-speed fuel economy and speed on grade. According to an exemplary embodiment, the transmission 620 includes a driver selectable range selection.

The transaxle 640 is designed to reduce the weight of the vehicle 10. The weight of the transaxle 640 is minimized by integrating a transercase and a rear differential into a single unit, selecting an optimized gear configuration, and/or utilizing high strength structural aluminum housings. By integrating the transercase and the rear differential into the

transaxle **640** (thereby forming a singular unit), the connecting drive shaft and end yokes traditionally utilized to connect the transference and the rear differential have been eliminated. An integral neutral and front axle disconnect allows the vehicle **10** to be flat towed or front/rear lift and towed with minimal preparation (i.e., without removing the transaxle drive shaft **630** or the front axle drive shaft **650**). Specifically, the transaxle **640** includes an internal mechanical disconnect capability that allows the front axle assembly **500** and/or the rear axle assembly **500** to turn without rotating the transaxle **640** and the transmission **620**. A mechanical air solenoid over-ride is easily accessible from the interior and/or exterior of the vehicle **10**. Once actuated, no further vehicle preparation is needed. After the recovery operation is complete, the driveline **600** can be re-engaged by returning the air solenoid mechanical over-ride to the original position.

IMG

According to an exemplary embodiment, the IMG **700** is electrically coupled to the ESS **1000**, selectively mechanically coupled to the engine **610**, and mechanically coupled to the transmission **620**. The IMG **700** is configured to be mechanically driven by the engine **610** to selectively generate electricity for storage in the ESS **1000** and/or to power electrical components of the vehicle **10**. The IMG **700** is configured to receive electrical power from the ESS **1000** to facilitate driving the transmission **620** and, therefore, the axle assemblies **500** of the vehicle **10**. In some embodiments, the IMG **700** is configured to receive electrical power from the ESS **1000** to function as a starter for the engine **610**. Such starting capability can be performed while the vehicle **10** is stationary or while the vehicle **10** is moving. In some embodiments, the driveline **600** additionally or alternatively includes a backup or dedicated engine starter.

As shown in FIGS. **12-14**, the IMG **700** includes a housing, shown as IMG housing **710**, including a first portion, shown as backing plate **720**, coupled to the transmission **620**, and a second portion, shown as engine mount **730**, coupled to the engine **610**. The IMG **700** further includes an electromagnetic device, shown as motor/generator **740**, coupled to the backing plate **720**, and a clutch mechanism, shown as engine clutch **750**, coupled to the motor/generator **740** and selectively couplable to the engine **610**. The motor/generator **740** and the engine clutch **750** are, therefore, positioned between the backing plate **720** and the engine mount **730** and enclosed within the IMG housing **710** (e.g., a single unit).

According to an exemplary embodiment, the engine clutch **750** is controllable (e.g., disengaged, engaged, etc.) to facilitate (i) selectively mechanically coupling the engine **610** and the motor/generator **740** (e.g., to start the engine **610** with the motor/generator **740**, to drive the motor/generator **740** with the engine **610** to produce electricity, to drive the motor/generator **740** with the engine **610** to drive the transmission **620**, etc.) and (ii) selectively mechanically decoupling the engine **610** and the motor/generator **740** (e.g., to drive the motor/generator **740** with power from the ESS **1000** to drive the transmission **620**, the FEAD **800**, etc.). In an alternative embodiment, the IMG **700** does not include the engine clutch **750** such that the engine **610** is directly coupled to the motor/generator **740**.

As shown in FIGS. **12** and **13**, the motor/generator **740** and the engine clutch **750** are arranged in a stacked arrangement with the engine clutch **750** positioned within an interior chamber, shown as cavity **732**, of the engine mount **730**. As shown in FIG. **14**, the motor/generator **740** and the engine clutch **750** are arranged in an integrated arrangement

with the engine clutch **750** positioned within an interior chamber, shown as cavity **752**, of the motor/generator **740**. The integrated arrangement of the motor/generator **740** and the engine clutch **750** facilitates reducing the packaging size of the IMG **700**, which facilitates reducing the overall length of the driveline **600**.

According to an exemplary embodiment, the engine clutch **750** is a pneumatically-operated clutch that is (i) spring-biased towards engagement with the engine **610** to couple the engine **610** to the other components of the driveline **600** (e.g., the motor/generator **740**, the transmission **620**, etc.) and (ii) selectively disengaged using compressed air provided from an air compressor (e.g., included in the FEAD **800**, air compressor **808**, etc.) to decouple the engine **610** from the other components of the driveline **600**. Such a spring-biased and air-disengaged clutch ensures that the driveline **600** of the vehicle **10** is operational in the event of damage to the ESS **1000** or if a state-of-charge ("SoC") of the ESS **1000** falls below a minimum SoC threshold (e.g., 20% SoC). As an example, if the engine clutch **750** is disengaged and the motor/generator **740** is driving the vehicle **10**, the engine clutch **750** will auto-engage (i) if electrical power is lost due to the ESS **1000** being damaged or the FEAD motor is damaged (which will cause the air compressor of the FEAD **800** to stop providing compressed air to the engine clutch **750**) or (ii) if switching to an engine drive mode, which may include stopping the FEAD motor (e.g., in response to the SoC of the ESS **1000** falling below the minimum SoC threshold, which causes the air compressor of the FEAD **800** to stop providing compressed air to the engine clutch **750**). In the event of auto-engagement of the engine clutch **750**, the engine **610** (if already off) will be started by the inertial forces of the vehicle **10** (if moving), can be started by the motor/generator **740**, or can be started by the dedicated engine starter. Such auto-engagement, therefore, ensures that engine **610** is connected to the remainder of the driveline **600** to drive the vehicle **10** in the event of some malfunction in the electrical system or when transitioning from electric drive to engine drive. According to an exemplary embodiment, the components of the driveline **600** do not need to be stopped nor do component speeds need to be matched to switch between engine drive and electric drive.

FEAD

According to an exemplary embodiment, the FEAD **800** is configured to drive (e.g., provide mechanical energy to, provide torque to, provide rotational inertia to, etc.) various accessories of the vehicle **10**. As shown in FIGS. **15-17**, **19**, **22**, and **23**, the various accessories include a first accessory, shown as air compressor **808**, a second accessory, shown as fan **810**, a third accessory, shown as motor/generator **822**, a fourth accessory, shown as hydraulic pump **832**, and a fifth accessory, shown as air conditioning ("A/C") compressor **848**. In other embodiments, the FEAD **800** includes additional, fewer, or different accessories. According to an exemplary embodiment, the FEAD **800** is selectively transitionable between different configurations, modes, or states to change a drive source (e.g., to change which of multiple available primary movers, engines, internal combustion engines, electric motors, etc. drive various accessories of the vehicle **10**).

E-FEAD

According to the exemplary embodiment shown in FIGS. **15-19**, the FEAD **800** is configured as an electrified FEAD ("E-FEAD") having a dual-belt drive arrangement. The FEAD **800** can be selectively driven by either the engine **610** (e.g., in a first mode or state) or the motor/generator **822**

(e.g., in a second mode or state). Accordingly, the FEAD **800** and, therefore, the driving of the accessories can be transitioned between an electrified state or mode and an engine-driven state or mode. When the FEAD **800** is in the electrified state or mode, the FEAD **800** can operate independently of operation of the engine **610**. For example, when the FEAD **800** is in the electrified state, the FEAD **800** and accessories thereof can operate even when the engine **610** is off or in-operational, thereby operating independently of the engine **610**. In another example, when the FEAD **800** is in the electrified state, the FEAD **800** can operate to drive the accessories of the vehicle **10** while the engine **610** operates to drive other driveable elements or systems of the vehicle **10** such as the wheels of the axle assemblies **500**, thereby operating independently and simultaneously with operation of the engine **610**.

As shown in FIGS. **15-17**, the FEAD **800** includes a first belt (e.g., tensile member, chain, power transmitting band, pulley, etc.), shown as FEAD belt **804**, and a second belt (e.g., tensile member, chain, power transmitting band, pulley, etc.), shown as engine belt **806**. The engine belt **806** is coupled between an output shaft **858** of the engine **610** (e.g., at a front end of the engine **610**) and a one-way bearing or clutch, shown as sprag clutch **834**. The FEAD belt **804** is coupled with, and defines a power band circuit between, a shaft **820** of the motor/generator **822**, a drive member **812** of the air compressor **808** (e.g., an air compressor pulley or sheave), an outer race **852** of a fan clutch **856** of the fan **810**, a tensioning pulley **818**, a pulley **836** of the sprag clutch **834**, a first roller **824**, a second roller **826**, a third roller **828**, and a fourth roller **830** (e.g., roller pulleys). The FEAD belt **804** and the engine belt **806** can be V-belts or synchronous belts and are configured to drive or be driven by any of the coupled components, clutches, shafts, pulleys, rollers, gears, rotatable members, etc. of the FEAD **800** as described in detail herein.

The hydraulic pump **832** is configured to be driven (e.g., by providing a torque input at an input shaft **844** of the hydraulic pump **832** as shown in FIG. **18**) to pressurize a hydraulic fluid, according to an exemplary embodiment. The hydraulic fluid may be stored in a reservoir or tank, pressurized by the hydraulic pump **832**, and provided to different hydraulically driven accessories, accessory systems, hydraulic motors, hydraulic actuators, power steering systems, suspension systems, etc. of the vehicle **10**. The hydraulic pump **832** may be a component of a hydraulic circuit of the vehicle **10** that is used for different body operations or body systems of the vehicle **10**, or different chassis systems of the vehicle **10** that use hydraulic primary movers (e.g., hydraulic motors, hydraulic linear actuators, etc.). The hydraulic pump **832** can be any of a gear pump, a piston pump, a vane pump, a clutch pump, a dump pump, a refuse pump, etc. or any other hydraulic pump (e.g., clutched) that receives an input torque and pressurizes or drives a hydraulic fluid. In an exemplary embodiment, the hydraulic pump **832** pressurizes the hydraulic fluid for a power steering system and a suspension system of the vehicle **10**.

The air compressor **808** is configured to be driven (e.g., by providing a torque input at an input shaft **814** of the air compressor **808** such as by driving, with the FEAD belt **804**, the drive member **812** that is fixedly coupled with the input shaft **814**) to pressurize air or any other gas, according to an exemplary embodiment. The air may be pressurized and stored in an air tank (e.g., a tank, a reservoir, a pressure vessel, etc.) that is fluidly coupled with the air compressor **808**. For example, the air compressor **808** can be configured to operate to maintain a required pressure in the air tank for

different chassis operations or systems such as brakes. In an exemplary embodiment, the air compressor **808** is configured to pressurize air for air brakes of the vehicle **10** (e.g., drum brakes that include a brake chamber that is fluidly coupled with the air tank). The air compressor **808** is a component of a fluid circuit for providing pressurized air to different accessories or systems of the vehicle **10**, including but not limited to, air brakes of the axle assemblies **500**. In some embodiments, the air compressor **808** is configured to pressurize air for other chassis or body operations of the vehicle **10** (e.g., suspension components, etc.).

The fan **810** is configured to be driven (e.g., by providing a torque input, with the FEAD belt **804**, through the fan clutch **856** of the fan **810** when the fan clutch **856** is in an engaged state) to drive a rotor or impeller component of the fan **810**. The fan **810** is configured to drive an airflow through cooling components (e.g., an engine radiator, a transmission cooler, heat exchangers, a hydraulic cooler, an A/C condenser, a battery cooler, etc.) of the vehicle **10** to provide cooling for the engine **610** and various other systems (e.g., a hydraulic circuit, the transmission **620**, the ESS **1000**, etc.) of the vehicle **10**. The impeller component or assembly can be selectively engaged with the FEAD belt **804** through the fan clutch **856**. The fan clutch **856** may be an electric clutch that is selectively engaged or disengaged to thereby couple or de-couple the impeller component or assembly of the fan **810** with the FEAD belt **804**. The FEAD belt **804** couples with the outer race **852** of the fan clutch **856**, and the impeller assembly of the fan **810** is fixedly coupled with an inner race **854** of the fan clutch **856**. Engaging or disengaging the fan clutch **856** couples or decouples the inner race **854** with the outer race **852** of the fan clutch **856**. The fan clutch **856** can be transitioned between the engaged state and the disengaged state automatically based on a temperature of the engine **610** or other vehicle components, in response to a user input, in response to a control mode, etc.

As shown in FIGS. **15** and **16**, the tensioning pulley **818** is positioned along the FEAD belt **804** between the pulley **836** of the sprag clutch **834** and the fan **810**. In other embodiments, the tensioning pulley **818** is otherwise positioned along the FEAD belt **804**. The tensioning pulley **818** is adjustable (e.g., physically moveable, translatable, etc.) to increase or decrease a tension of the FEAD belt **804**. The tensioning pulley **818** can be adjusted by providing an input to an adjustment member **816** (e.g., lever, knob, etc.) to reposition (e.g., translate, etc.) the tensioning pulley **818**.

According to an exemplary embodiment, the motor/generator **822** is configured to function both as a motor and as a generator in different modes of the FEAD **800**. When the motor/generator **822** functions as a motor, the motor/generator **822** is configured to consume electrical energy from the ESS **1000** of the vehicle **10** and output a torque to the FEAD belt **804** through the shaft **820** of the motor/generator **822**. The FEAD belt **804** transfers the torque or mechanical energy to each of the fan **810**, the air compressor **808**, and the hydraulic pump **832** so that the motor/generator **822** functions as the primary mover of the FEAD **800** when activated, thereby electrifying the FEAD **800** and facilitating independent operation the FEAD **800** (i.e., operating independently of operation of the engine **610**). The FEAD belt **804** can be configured to drive the hydraulic pump **832** through the sprag clutch **834**, as described in greater detail below with reference to FIG. **18**.

The motor/generator **822** is also configured to function as a generator and be driven by the FEAD belt **804** when the engine **610** operates as the primary mover of the FEAD **800**.

The engine 610 is configured to drive the sprag clutch 834 through the engine belt 806, which thereby drives (i) the hydraulic pump 832 through the sprag clutch 834 and (ii) the FEAD belt 804 through the sprag clutch 834, and thereby the fan 810, the air compressor 808, and the motor/generator 822 through the pulley 836 of the sprag clutch 834. In some embodiments, the FEAD 800 can be transitioned between the engine-driven mode and the electrified mode by (i) selectively configuring the engine 610 to drive the engine belt 806 (e.g., by engaging a clutch of the engine 610 so that the engine outputs torque to the sprag clutch 834 via the engine belt 806, or by starting or stopping the engine 610) or (ii) activating the motor/generator 822 to drive the FEAD belt 804 (e.g., by providing electrical power to the motor/generator 822 to thereby cause the motor/generator 822 to function as an electric motor and drive the FEAD belt 804). When the engine 610 drives the FEAD 800 through the engine belt 806, the sprag clutch 834, and the FEAD belt 804, the motor/generator 822 may be driven through the shaft 820 and function as a generator (as necessary or continuously) to generate electrical energy based on the driving of the shaft 820 (e.g., now functioning as an input shaft) and provide the electrical energy to various electrical components of the vehicle 10 and/or to the ESS 1000 for storage.

As shown in FIGS. 15 and 16, the FEAD 800 includes a structural member, shown as frame 802, with which each of the motor/generator 822, the air compressor 808, the tensioning pulley 818, the hydraulic pump 832, the sprag clutch 834, the fan 810, and the roller pulleys 824-830 are coupled (e.g., translationally fixedly coupled). According to an exemplary embodiment, the frame 802 is coupled (e.g., mounted, secured, fixedly coupled, fastened, attached, etc.) to a front of the engine 610. In other embodiments, the frame 802 is coupled to the hull and frame assembly 100 (e.g., a portion of the front module 300).

As shown in FIG. 18, the sprag clutch 834 includes a first portion, shown as outer race 838, a second portion, shown as inner race 840, and one-way rotational elements, shown as sprags 862, positioned between the inner race 840 and the outer race 838. The sprags 862 are configured to (i) permit free rotation between the inner race 840 and the outer race 838 when the inner race 840 is rotated relative to the outer race 838 about a central axis 860 thereof (e.g., when the pulley 836, and therefore, the inner race 840 is driven by the motor/generator 822) and (ii) limit or jam when the outer race 838 is rotated relative to the inner race 840 about the central axis 860 (e.g., when the outer race 838 is driven by the engine 610 through the engine belt 806).

As shown in FIGS. 15 and 17, the engine belt 806 is coupled with the outer race 838 of the sprag clutch 834 so that when the engine 610 drives the engine belt 806, the outer race 838 locks with the inner race 840 and both the outer race 838 and the inner race 840 rotate in unison (e.g., due to the sprags 862 locking the inner race 840 with the outer race 838 or limiting relative rotation between the inner race 840 and the outer race 838). The pulley 836 of the sprag clutch 834 is fixedly coupled with the inner race 840 of the sprag clutch 834 (e.g., via a shaft 842) so that rotation of the inner race 840 drives the pulley 836 and the FEAD belt 804. The input shaft 844 of the hydraulic pump 832 is coupled (e.g., rotatably) with the inner race 840 of the sprag clutch 834 such that rotation of the inner race 840 (e.g., in unison with rotation of the outer race 838 when the engine 610 drives the outer race 838 and the inner race 840 in unison through the engine belt 806) also drives the hydraulic pump 832.

As shown in FIG. 18, the pulley 836 and, therefore, the FEAD belt 804 are coupled with the inner race 840 of the sprag clutch 834. When the motor/generator 822 of the FEAD 800 operates as the primary mover of the FEAD 800, the motor/generator 822 drives the FEAD belt 804 (thereby driving the air compressor 808 and/or the fan 810), which drives the pulley 836 and the inner race 840 to rotate relative to the outer race 838 of the sprag clutch 834, thereby also driving the hydraulic pump 832 without driving the outer race 838 and the engine belt 806. In this way, the sprag clutch 834 can function to facilitate driving the FEAD 800 with either the engine 610 or the motor/generator 822. When the motor/generator 822 drives the FEAD 800 and accessories thereof, the inner race 840 of the sprag clutch 834 rotates freely relative to the outer race 838. When the engine 610 drives the FEAD 800 and accessories thereof, the inner race 840 and the outer race 838 of the sprag clutch 834 have limited relative rotation to thereby transfer the torque from the engine 610 and the engine belt 806 to the FEAD 800 and accessories thereof.

It should be understood that while FIG. 18 shows the engine belt 806 being coupled with the outer race 838 of the sprag clutch 834, and the hydraulic pump 832 and the FEAD belt 804 being coupled with the inner race 840 of the sprag clutch 834, in other embodiments, the engine belt 806 is coupled with the inner race 840 of the sprag clutch 834 and the hydraulic pump 832 and the FEAD belt 804 are coupled with the outer race 838 of the sprag clutch 834.

As shown in FIG. 19, the FEAD 800 is operably or electrically coupled with the ESS 1000 so that the ESS 1000 can exchange electrical energy with electrical components of the FEAD 800. The FEAD 800 also includes the A/C compressor 848 and an electric motor 846 that is configured to drive the A/C compressor 848. The A/C compressor 848 and the electric motor 846 can operate independently of the engine 610 and the motor/generator 822 so that the A/C compressor 848 does not depend on operation, drive speed, or on/off status of the engine 610 or the motor/generator 822. The engine 610 or the motor/generator 822 are selectively configured to provide mechanical energy to drive the air compressor 808, the fan 810, or the hydraulic pump 832. When the engine 610 drives the air compressor 808, the fan 810, and the hydraulic pump 832, the engine 610 may also drive the motor/generator 822 so that the motor/generator 822 generates electrical energy. The motor/generator 822 is electrically coupled (e.g., via electrical wiring) with the ESS 1000 and provides generated electrical energy to the ESS 1000 for storage and discharge to other electrical components of the vehicle 10. When the motor/generator 822 operates to drive the FEAD 800 (e.g., in the electrified mode), the motor/generator 822 consumes electrical energy provided by the ESS 1000 (or more specifically batteries thereof) and uses the electrical energy to drive the accessories of the FEAD 800.

As shown in FIG. 19, the FEAD 800 includes a pump (e.g., an oil pump, a lubrication pump, etc.), shown as lubricant pump 850, that is configured to provide lubricant to the A/C compressor 848, the air compressor 808, the fan 810, and/or the hydraulic pump 832. In some embodiments, the lubricant pump 850 is a component in a fluid lubricant circuit that includes a reservoir for the lubricant, one or more filters to filter the lubricant, etc. In some embodiments, the lubricant pump 850 is configured to provide lubricant to the engine 610. The lubricant pump 850 may be selectively fluidly coupled with the accessories of the FEAD 800 (e.g., the A/C compressor 848, the air compressor 808, the fan 810, the hydraulic pump 832, etc.) or lubricant inlets (e.g.,

grease fittings) of the accessories of the FEAD 800 to provide lubricant (e.g., grease, liquid lubricant, oil-based lubricant, etc.) to reduce friction and reduce wear of the accessories of the FEAD 800. The lubricant fluid circuit including the lubricant pump 850 can include a valve and a branch (e.g., a tee) to selectively direct lubricant to the accessories of the FEAD 800 or moving parts of the accessories of the FEAD 800 as required, automatically, or in response to a user input. The lubricant pump 850 can include an electric motor that consumes electrical energy provided by the ESS 1000 to operate independently of operation of the engine 610 and/or the motor/generator 822 (e.g., operates when the engine 610 and/or the motor/generator 822 are in an off state, not operating to provide torque or generate electrical energy, etc.). The lubricant pump 850 is configured to receive return lubricant from any of the A/C compressor 848, the air compressor 808, the fan 810, the hydraulic pump 832, or the engine 610, and recirculate the return lubricant.

The A/C compressor 848 and the electric motor 846 are configured to operate independently of the engine 610 and the motor/generator 822 to provide A/C for occupants of the vehicle 10. The electric motor 846 operates by consuming electrical power provided by the ESS 1000 (or other batteries of the vehicle 10) and driving the A/C compressor 848. The A/C compressor 848 is configured to compress a refrigerant to pass the refrigerant through a heat exchanger for A/C. Advantageously, the A/C compressor 848 can be operated regardless of the mode of the FEAD 800 (e.g., if the FEAD 800 is being driven by the engine 610, if the FEAD 800 is being driven by the motor/generator 822, if the FEAD 800 is not being driven).

Engine-Only-Driven FEAD

According to the alternative embodiment shown in FIG. 20, the FEAD 800 does not include the motor/generator 822 and is instead driven solely by the engine 610 through the output shaft 858 of the engine 610 that is coupled with the engine belt 806, thereby driving the FEAD belt 804 through the sprag clutch 834. In such an embodiment, the FEAD 800 may not include the sprag clutch 834. The accessories of the FEAD 800 may, therefore, be directly coupled to the engine belt 806 or the sprag clutch 834 is replaced by two pulleys coupled together (e.g., the pulley 836 and a second pulley that replaces the outer race 838 and the inner race 840 of the sprag clutch 834).

IMG-Driven FEAD

According to the exemplary embodiment FIGS. 21 and 22, the FEAD 800 or accessories thereof can be driven by the IMG 700 of the driveline 600. As shown in FIG. 21, the driveline 600 includes the engine 610, the engine clutch 750, the IMG 700, and the transmission 620 where the IMG 700 includes a PTO, shown as PTO 870, configured to be driven by an output (e.g., a secondary output, etc.) of the IMG 700. The PTO 870 can be transitionable between an engaged state and a disengaged state. When the PTO 870 is in the engaged state, the PTO 870 can receive output torque from the IMG 700 and transfer the torque to an input pulley 872 of the FEAD 800 for driving the FEAD belt 804.

Accordingly, the input pulley 872 may replace the motor/generator 822 of the FEAD 800. The engine 610 may still be configured to drive the FEAD 800 and accessories of the FEAD 800 through the sprag clutch 834 and the engine belt 806 when the FEAD 800 is in the engine-driven mode. When the FEAD 800 is transitioned into the motor/driven or electrified mode, the IMG 700 can consume electrical energy (e.g., from the ESS 1000) and output torque to the PTO 870. The PTO 870 can be transitioned into the engaged state so that the PTO 870 receives the output torque from the

IMG 700 and transfers the output torque to the input pulley 872 of the FEAD 800. The input pulley 872 can be configured to drive the FEAD belt 804 similarly to the motor/generator 822 as described in greater detail above with reference to FIGS. 15-19.

Accordingly, the FEAD 800 shown in FIGS. 21 and 22 is transitionable between (i) an engine-driven mode where the FEAD 800 and accessories of the FEAD 800 are driven by the engine 610 and (ii) a motor/driven or electrified mode where the FEAD 800 and accessories of the FEAD 800 are driven by the IMG 700 of the driveline 600 (e.g., through the PTO 870). Transitioning between the engine-driven mode and the motor/driven mode can include (i) transitioning the PTO 870 between the engaged state and the disengaged state and/or (ii) transitioning the IMG 700 between operating as a motor and operating as a generator. Advantageously, driving the FEAD 800 in the motor/driven mode with the IMG 700 reduces the need for an additional motor/generator at the FEAD 800 (e.g., the motor/generator 822). When the FEAD 800 is driven by the IMG 700 through the PTO 870, the engine clutch 750 may be de-coupled from the engine 610 so that the IMG 700 operates independently of operation of the engine 610. In another embodiment, the PTO 870 is coupled to an output (e.g., a secondary output) of the transmission 620 and driven by the IMG 700 and/or the engine 610 to drive the FEAD 800.

Electrified Accessories

According to the exemplary embodiment shown in FIG. 23, each of the accessories of the FEAD 800 can be individually electrified. As shown in FIG. 23, the FEAD 800 additionally includes an electric motor 864 configured to drive the air compressor 808, an electric motor 866 configured to drive the fan 810, and an electric motor 868 configured to drive the hydraulic pump 832. Each of the electric motor 864, the electric motor 866, the electric motor 868, and the electric motor 846 is configured to consume electrical energy provided by the ESS 1000 to drive their corresponding accessories. Each of the electric motor 864, the electric motor 866, the electric motor 868, and the electric motor 846 can therefore be operated independently of each other and/or independently of the engine 610.

In the embodiment shown in FIG. 23 where each of the accessories is electrified, the engine 610 may be optional as a primary mover for the FEAD 800. If the engine 610 is not used by the FEAD 800 in such an embodiment, the engine 610 may still be provided as a component of the driveline 600 but is not used to provide a torque input to the FEAD 800. If the engine 610 is not used to provide a torque input to the FEAD 800, the engine belt 806, the FEAD belt 804, and the sprag clutch 834 are not used since each of the accessories are independently operated by their corresponding electric motors.

If the engine 610 is used to provide a torque input to the FEAD 800, the electric motor 864, the electric motor 866, and the electric motor 868 can function as motor/generators, and can be driven by the engine 610 to generate electrical energy and provide the electrical energy to the ESS 1000. In some embodiments, one or more of the air compressor 808, the fan 810, and the hydraulic pump 832 are not electrified, while one or more others of the air compressor 808, the fan 810, and the hydraulic pump 832 are electrified. For example, the hydraulic pump 832 and the air compressor 808 can both be electrified and independently operational (e.g., through operation of the electric motor 868 and the electric motor 864) while the fan 810 may be coupled with the engine 610 through the FEAD belt 804 or the engine belt 806 to be driven by the engine 610. Advantageously, pro-

viding the electric motors **864-868** facilitates independent operation of each of the air compressor **808**, the fan **810**, and the hydraulic pump **832** relative to operation of the engine **610**, and also relative to operation of each other. For example, the air compressor **808** can be operated independently, regardless of operation of any of the A/C compressor **848**, the engine **610**, the fan **810**, or the hydraulic pump **832**. Further, electrification of the accessories may facilitate distributing the accessories variously about the vehicle 10, providing improved component packaging.

Energy Storage System

Capacity, Operating Range, and Charging

As shown in FIG. 24, the ESS **1000** is electrically coupled to the IMG **700**. In some embodiments (e.g., embodiments where the FEAD **800** includes the motor/generator **822**), the ESS **1000** is also electrically coupled to the motor/generator **822** of the FEAD **800**. In an electric drive mode of operation, the ESS **1000** provides power to the IMG **700** to drive the transmission **620** and/or other components/systems of the vehicle 10 (e.g., to the motor/generator **822** to drive the FEAD **800**). In a charge mode of operation (e.g., during the engine mode), (i) the IMG **700** is driven by the engine **610** via the engine clutch **750** and electrical power may generated and provided to the ESS **1000** and/or (ii) the motor/generator **822** may be driven by the engine **610** and electrical power may be generated and provided to the ESS **1000**.

As shown in FIG. 24, the ESS **1000** includes a battery storage housing **1002**, a power connector **1004** supported by the battery storage housing **1002**, and a data connector **1006** supported by the battery storage housing **1002**. The power connector **1004** provides power communication between the ESS **1000**, the IMG **700**, and/or the motor/generator **822**. The data connector **1006** provides data communication between the ESS **1000**, the IMG **700**, and/or the motor/generator **822**. The ESS **1000** includes a number of batteries **1008**, each including a number of cells **1010**. The batteries **1008** are coupled together to provide an energy storage capacity of the ESS **1000**.

In some embodiments, the batteries **1008** are configured (e.g., structured, designed, etc.) to operate at 700 volts (“V”). In some embodiments, the batteries **1008** are configured to operate at 24 V. In some embodiments, the batteries **1008** are configured to operate at a voltage between 700 V and 24 V. In an exemplary embodiment, the batteries **1008** are configured to operate at 666 V nominal voltage with a 406 kW discharge power. In some embodiments, the ESS **1000** has an energy storage capacity of 30.6 kWh. In some embodiments, the ESS **1000** is configured to operate at ambient temperatures between -40 degrees Celsius and 80 degrees Celsius.

In some embodiments, the energy storage capacity is defined for a target load. The target load is defined by the vehicle 10 (e.g., weight, transmission design, suspension dynamics, etc.) and can be expressed as an average load in

kilowatts (“kW”). In some embodiments, the target load is defined by a specific vehicle and a specific use case. In some embodiments, the vehicle 10 is structured to provide a silent mobility mode where the systems and components the vehicle 10 are operated using energy from the ESS **1000** and the engine **610** is inactive. The silent mobility mode can define the energy storage capacity in part. In some embodiments, the target load is defined at the gross-vehicle-weight-rating (“GVWR”) of the vehicle 10. Table 1, reproduced below, depicts six use cases and associated target loads during the silent mobility mode.

In use case “Vehicle 1,” the target load is 68 kW average load and results in 22 minutes of run time and 13.5 miles of distance traveled. The energy storage capacity of “Vehicle 1” can be defined as 22 minutes of run time and/or 13.5 miles of distance traveled. In some embodiments, the target load of “Vehicle 1” is at least sixty-five kilowatts (65 kW). In some embodiments, the energy storage capacity of “Vehicle 1” can be defined as at least 20 minutes of run time and/or at least 13 miles of distance traveled.

In use case “Vehicle 2,” the target load is 53 kW average load and results in 29 minutes of run time and 6 miles of distance traveled. The energy storage capacity of “Vehicle 2” can be defined as 29 minutes of run time and/or 6 miles of distance traveled. In some embodiments, the target load of “Vehicle 2” is at least fifty kilowatts (50 kW). In some embodiments, the energy storage capacity of “Vehicle 2” can be defined as at least 29 minutes of run time and/or at least 6 miles of distance traveled.

In use case “Vehicle 3,” the target load is 40 kW average load and results in 38 minutes of run time and 14.5 miles of distance traveled. The energy storage capacity of “Vehicle 3” can be defined as 38 minutes of run time and/or 14.5 miles of distance traveled. In some embodiments, the target load of “Vehicle 3” is at least forty kilowatts (40 kW). In some embodiments, the energy storage capacity of “Vehicle 3” can be defined as at least 35 minutes of run time and/or at least 14 miles of distance traveled.

In use case “Idle,” the goal is to idle the vehicle 10 using the ESS **1000** without requiring activation of the engine **610** (e.g., operate all loads of the vehicle 10 using the ESS **1000**). The target load of the “Idle” use case is 17 kW average load and results in 90 minutes of run time. The energy storage capacity of “Idle” can be defined as 90 minutes of run time and/or 0 miles of distance traveled.

In use case “Fuel_Econ,” the goal is to maximize the distance traveled by the vehicle 10. The target load is 40 kW average load and results in 22 miles of distance traveled. The energy storage capacity of “Fuel_Econ” can be defined 22 miles of distance traveled.

In use case “25 mph,” the goal is to maximize a time of operation while moving the vehicle 10 at 25 mph over ground. The target load is 34 kW average load and results in 44 minutes of run time. The energy storage capacity of “25 mph” can be defined as 44 minutes of run time.

TABLE 1

	Use Case								
	Vehicle 1	Vehicle 2	Vehicle 3	Idle	Fuel_Econ	25 mph			
Target Load	68 kW	53 kW	40 kW	17 kW	40 kW	34 kW			
Criteria	Minutes	Miles	Minutes	Miles	Minutes	Miles	Minutes	Miles	Minutes
Result	22	13.5	29	6	38	14.5	90	22	44

In one example, the ESS **1000** includes batteries **1008** that provide 30.6 kWh of energy storage capacity and are capable of providing enough energy for a minimum pure electric vehicle (EV) drive operation (e.g., silent mobility mode) of at least 30 minutes at 25 mph (e.g., 30-35 min at 45 mph).

The battery storage housing **1002** and the batteries **1008** may have a weight of about 818.4 pounds. In some embodiments, the battery storage housing **1002** and batteries **1008** may have a weight of between about 600 pounds and about 1000 pounds. The battery storage housing **1002** may have dimensions of about 60.8 inches wide, about 29.5 inches tall, and about 8.5 inches thick. In some embodiments, the battery storage housing **1002** is shaped differently and defines different dimensions (e.g., dependent upon the positioning on the vehicle **10**, the desired battery capacity, weight loading requirements, etc.). For example, the battery storage housing **1002** may be between 40 and 80 inches wide, between 10 and 40 inches tall, and between 4 and 12 inches thick. In some embodiments, the battery storage housing **1002** is not structured as a single housing containing multiple batteries. In some embodiments, each battery **1008** or a subset of batteries **1008** may include battery storage housings **1002** that may be collocated on the vehicle **10** or distributed in multiple positions about the vehicle **10**.

The batteries **1008** are configured to be maintained at between a lower SoC limit and an upper SoC limit. In one embodiment, the lower SoC limit is 20% of the maximum SoC and the upper SoC limit is 93% of the maximum SoC. In some embodiments, the lower SoC limit is greater than or less than 20% (e.g., 5%, 10%, 15%, 25%, etc.). In some embodiments, the upper SoC limit may be greater than or less than 93% (e.g., 88%, 90%, 95%, etc.).

The ESS **1000** can include a charge controller **1012** structured to control the flow of electrical energy into the batteries **1008** using a charge profile. The charge profile instituted by the charge controller **1012** may be dependent on the battery **1008** chemistry and other considerations. In some embodiments, the energy storage capacity may be defined as the amount of energy available between the lower SoC limit and the upper SoC limit.

As shown in FIG. **25**, power conversion hardware **1014** (e.g., a DC/DC converter) is coupled to the rear module **400** and structured to convert DC power received from either the IMG **700**, the motor/generator **822**, and/or the ESS **1000** and convert the DC power to power usable by the vehicle systems (e.g., 12 V, 24 V, and/or 48 V). A power panel **1016** is also coupled to the rear module **400** and provides a charging plug **1018** that can be used for plugging the ESS **1000** into an external power station for charging. Additionally, the power panel **1016** can include external power output that receive cords, plugs, or other power connections configured to provide power to external components and systems. An AC power system **1020** includes inverters that convert (i) available DC power from the IMG **700**, the motor/generator **822**, and/or the ESS **1000** into AC power for consumption by components of the vehicle **10** and/or external systems and/or (ii) AC power from the IMG **700** and/or the motor/generator **82** into DC power for consumption by components of the vehicle **10** and/or external systems. In some embodiments, the charging plug **1018** is an external plug positioned above the rear, driver side wheel well of the rear module **400**.

The engine **610**, the IMG **700**, the motor/generator **822**, the charge controller **1012**, and the batteries **1008** are sized such that electrical power generation through engine drive of the IMG **700** and/or the motor/generator **822** of the FEAD

800 is greater than the power depletion through operation of the vehicle **10** in the silent mobility mode. In other words, the charge time through engine **610** generation of electrical power via the IMG **700** and/or the motor/generator **822** of the FEAD **800** is less than the depletion time in an electric vehicle drive mode (i.e., takes less time to charge than to deplete). The batteries **1008** can be charged in a first time by the motor generator (e.g., the motor generator **822** and/or the IMG **700**). The batteries **1008** are depleted in the silent mobility mode in a second time. The first time is less than the second time. In some embodiments, the vehicle **10** is structured to operate in any combination of engine **610** powered, IMG **700** powered, motor/generator **822** powered, engine **610** charging the ESS **1000**, etc. For example, a blended power mode can include propulsion of the vehicle **10** via both electrical power and engine generated power. The engine **610** can charge the ESS **1000** while the vehicle **10** is driving or stationary.

Between-the-Wheels Configuration

As shown in FIGS. **25-30**, the ESS **1000** is mounted in the bed cavity **460** of the rear module **400** adjacent the rear wall **216** of the passenger capsule **200** between the wheel wells **440**. A bracket **1024** supports the ESS **1000** in position and includes a protective plate **1026** that shields the ESS **1000** from impact. The protective plate **1026** may surround the ESS **1000** to provide protection from vulnerable directions. The bracket **1024** may include a vibration damping material disposed between the bracket **1024**, the protective plate **1026**, and the ESS **1000** to inhibit vibrational transfer between the hull and frame assembly **100** and the ESS **1000**. In some embodiments, the protective plate **1026** is formed from similar materials to the body or frame of the vehicle **10** to inhibit the intrusion of hostile fragments, blasts, or projectiles.

The bracket **1024** is mounted to the vehicle **10** with an upper isolator mount **1028** that is connected between the bracket **1024** and the passenger capsule **200**. In some embodiments, the upper isolator mount **1028** is generally centered on the bracket **1024** and connected to the rear wall **216** of the passenger capsule **200**. The upper isolator mount **1028** provides front-to-back vibration isolation relative to the passenger capsule **200**. In some embodiments, the upper isolator mount **1028** includes a spring damper shock system coupled between the bracket **1024** and the passenger capsule **200**. In some embodiments, the upper isolator mount **1028** includes a pneumatic damper or a hydraulic fluid damper. In some embodiments, the upper isolator mount **1028** is coupled between the bracket **1024** and another portion of the vehicle **10** and/or the hull and frame assembly **100**. In some embodiments, the upper isolator mount **1028** includes a plate **1032** rigidly coupled to the passenger capsule **200** (e.g., by welding, fastening, etc.) and a rod **1034** coupled to the plate **1032** with a spherical rod end. The rod **1034** is fastened to the bracket **1024** using a nut, a weld, or a captured end. In some embodiments, the ESS **1000** includes a plurality of the upper isolator mounts **1028**.

As shown in FIGS. **27-29**, a lower support **1036** is coupled to the bed **430**. For example, four legs **1038** are coupled to the bed **430** using fasteners. In some embodiments, more than four or less than four legs **1038** are included. In some embodiments, the lower support **1036** is welded to the bed **430** or formed as a part of the bed **430**. The lower support **1036** includes ESS mount structures in the form of recesses **1040** sized to receive lower isolator mounts **1042**. In some embodiments, the recesses **1040** are circular and the lower isolator mounts **1042** are secured using adhesive. In some embodiments, the recesses are square,

rectangular, oval, or another shape. In some embodiments, the lower isolator mounts **1042** are fastened to the recesses **1040**, captured within the recesses **1040**, or otherwise held in place between the bracket **1024** and the lower support **1036**. As shown in FIG. **29**, two lower isolator mounts **1042** are used to support the bracket **1024** on the lower support **1036**. In some embodiments, more than two or less than two lower isolator mounts **1042** are included. In some embodiments, the lower isolator mounts **1042** are rubber or another vibration attenuating material. In some embodiments, the bracket **1024** is adhered, fastened to, captured by, or otherwise directly coupled to the lower isolator mounts **1042**.

The upper isolator mount **1028** and the lower isolator mounts **1042** maintain the bracket **1024**, and thereby the ESS **1000**, in position relative to the passenger capsule **200** and the rear module **400** during use of the vehicle **10**. The ESS **1000** is positioned within the rear module **400**. The weight of the ESS **1000** is supported by the rear subframe **410**. The ESS **1000** is centered between the wheel wells **440** within the bed cavity **460** and supported on top of the bed **430**.

In some embodiments, the AC power system **1020** (e.g., a high voltage inverter) and power distribution components are positioned in or above driver side stowage box **450** above the rear, driver side wheel well **440** with cables running to through the tunnel slot **208** of the structural tunnel **206** to the IMG **700**, the motor/generator **822** of the FEAD **800**, and other high voltage components. The power conversion hardware **1014** (700V to 24V) is positioned in or above the passenger side stowage box **450** above the rear, passenger side wheel well **440** and cables run therefrom to low voltage components (e.g., cab electronics, etc.).

Over-the-Wheels Configuration

As shown in FIGS. **31** and **32**, an ESS **1044** is structured to be supported above the wheel wells **440** of the rear module **400**. In some embodiments, the ESS **1044** includes a first battery set **1046** positioned above a driver side wheel well **440** and/or a second battery set **1048** positioned above the passenger side wheel well **440**. Each of the first battery set **1046** and the second battery set **1048** can include multiple batteries **1008** or multiple battery cells and be sized as discussed above in the cumulative (i.e., both battery sets) to provide the desired energy storage capacity.

The weight of the ESS **1044** is supported by the rear subframe **410**. In some embodiments, the battery sets **1046**, **1048** do not occupy space directly above the bed **430** or within the bed cavity **460**. In some embodiments, the first battery set **1046** and/or the second battery set **1048** are additionally or alternatively positioned within the stowage boxes **450** above the wheel wells **440**.

In some embodiments, the first battery set **1046** and the second battery set **1048** each include a housing **1050** having a curved surface **1052** shaped to conform to the wheel wells **440**. The housing **1050** defines an internal volume sized to receive the batteries **1008**. In some embodiments, the housing **1050** defines a rear portion **1054** with a substantially rectangular cross-section that is sized to accommodate one or more batteries **1008**. In other words, the rear portion **1054** is positioned aft of the wheel well **440** and defines an area at least as big as a single battery **1008**.

In some embodiments, the first battery set **1046** and the second battery set **1048** are fastened to the wheel wells **440**. In some embodiments, the first battery set **1046** and the second battery set **1048** are formed as a part of the wheel wells **440** or the rear module **400** (e.g., the housing **1050** is formed as a part of the rear module **400**). In some embodiments, the first battery set **1046** and the second battery set

1048 are held to the rear module **400** using brackets, welds, isolator mounts, vibrational dampers, or other rigid connections.

Under Cab Configuration

As shown in FIG. **33**, an ESS **1056** includes a first battery set **1058** and/or a second battery set **1060** coupled to the floor portions **204** of the passenger capsule **200** and positioned laterally outside of the structural tunnel **206** and spaced above the v-shaped belly deflector **220** within the air gap **222**. Each of the first battery set **1058** and the second battery set **1060** includes a housing **1062** coupled to the floor portion **204** with isolator mounts **1064**. In some embodiments, the housings **1062** are coupled to the v-shaped belly deflector **220** via isolator mounts in addition to, or as a replacement for, the isolator mounts **1064**. In some embodiments, the housing **1062** includes a resilient bottom material to inhibit damage from impacts from below. For example, if the v-shaped belly deflector **220** is damaged, the housing **1062** can be structured to protect the ESS **1056** from damage. In some embodiments, the housing **1062** is formed from the same material as the v-shaped belly deflector **220**. In some embodiments, the housing **1062** has a shape corresponding to the air gap **222** to substantially fill the air gap **222** and maximize the amount of battery capacity of the ESS **1056** within the air gap **222**.

The weight of the ESS **1056** is carried by the hull and frame assembly **100** and/or the passenger capsule **200**. In some embodiments, the weight of the ESS **1056** is supported by the floor portion **204** of the passenger capsule **200**. Each of the first battery set **1058** and the second battery set **1060** can include multiple batteries **1008** or multiple battery cells and be sized as discussed above in the cumulative (i.e., both battery sets) to provide the desired energy storage capacity.

The position of the ESS **1056** below the floor portion **204** provides a low center of gravity. In some embodiments, the weight of the ESS **1056** is substantially all below the natural center of gravity of the vehicle **10** and the addition of the ESS **1056** lowers the center of gravity of the vehicle **10**. In some embodiments, the ESS **1056** extends longitudinally along the length of the passenger capsule **200** and provides fore-aft stability ballast.

Extended Wheelbase Configuration

As shown in FIGS. **34** and **35**, an ESS **1068** is mounted on the capsule extension **224** of the passenger capsule **200** in between the rear wall **216** of the passenger capsule **200** and in front of the cargo body assembly **420**. In some embodiments, a bracket **1070** supports the ESS **1068** in position and includes a protective plate **1072** that shields the ESS **1068** from impact. The protective plate **1072** may surround the ESS **1068** to provide protection from vulnerable directions (e.g., the rear and sides). The bracket **1070** may include a vibration damping material disposed between the bracket **1070**, the protective plate **1072**, and the ESS **1068** to inhibit vibrational transfer between the hull and frame assembly **100** and the ESS **1068**. In some embodiments, the protective plate **1072** is formed from, similar materials to the body or frame of the vehicle **10** to inhibit the intrusion of hostile fragments, blasts, or projectiles.

The bracket **1070** is mounted to the vehicle **10** with an upper isolator mount **1074** that is connected between the bracket **1070** and the passenger capsule **200**. In some embodiments, the upper isolator mount **1074** is generally centered on the bracket **1070** and connected to the rear wall **216** of the passenger capsule **200**. The upper isolator mount **1074** provides front-to-back vibration isolation relative to the passenger capsule **200**. In some embodiments, the upper isolator mount **1074** includes a spring damper shock system

coupled between the bracket **1070** and the passenger capsule **200**. In some embodiments, the upper isolator mount **1074** includes a pneumatic damper or a hydraulic fluid damper. In some embodiments, the upper isolator mount **1074** is coupled between the bracket **1070** and another portion of the vehicle **10** and/or the hull and frame assembly **100**. In some embodiments, the upper isolator mount **1074** includes a plate rigidly coupled to the passenger capsule **200** (e.g., by welding, fastening, etc.) and a rod coupled to the plate with a spherical rod end. The rod is fastened to the bracket **1070** using a nut, a weld, or a captured end. In some embodiments, the ESS **1068** includes a plurality of the upper isolator mounts **1074**.

A lower support **1076** is coupled to the capsule extension **224**. For example, four legs are coupled to the capsule extension **224** using fasteners. In some embodiments, more than four or less than four legs are included. In some embodiments, the lower support **1076** is welded to the capsule extension **224** or formed as a part of the capsule extension **224**. The lower support **1076** includes ESS mount structures in the form of recesses sized to receive lower isolator mounts **1078**. In some embodiments, the recesses are circular and the lower isolator mounts **1078** are secured therein using adhesive. In some embodiments, the recesses are square, rectangular, oval, or another shape. In some embodiments, the lower isolator mounts **1078** are fastened to the recesses, captured within the recesses, or otherwise held in place between the bracket **1070** and the lower support **1076**. In some embodiments, two lower isolator mounts **1078** are used to support the bracket **1070** on the lower support **1076**. In some embodiments, more than two or less than two lower isolator mounts **1078** are included. In some embodiments, the lower isolator mounts **1078** are rubber or another vibration attenuating material. In some embodiments, the bracket **1070** is adhered, fastened to, captured by, or otherwise directly coupled to the lower isolator mounts **1078**.

The upper isolator mount **1074** and the lower isolator mounts **1078** maintain the bracket **1070**, and thereby the ESS **1068**, in position relative to the passenger capsule **200** and the rear module **400**, and on the capsule extension **224** during use of the vehicle **10**. The ESS **1068** is positioned outside the rear module **400** (and the bed cavity **460** thereof) and is supported by the passenger capsule **200** and the hull and frame assembly **100**. The weight of the ESS **1068** is supported by the capsule extension **224**. The ESS **1068** may be centered between the wheel wells **440** or extend beyond the wheel wells **440**.

In some embodiments, the extended wheel base utilizing the capsule extension **224** provides a fifteen inch gap between rear wall **216** and the rear module **400**. In other words, the capsule extension **224** has a longitudinal length of at least fifteen inches. In some embodiments, the longitudinal length of the capsule extension **224** is less than or greater than fifteen inches. The longitudinal length of the capsule extension **224** accommodates the ESS **1068**. In other words, the thickness of the ESS **1068** is equal to or less than the longitudinal length of the capsule extension **224**.

The position of the ESS **1068** on the capsule extension **224** forward of the rear module **400** moves the center of gravity of the vehicle **10** toward to true center of the vehicle **10** and can improve handling characteristics of the vehicle **10** and overall vehicle stability. Additionally, the ESS **1068** is not positioned within the bed cavity **460** thereby providing a larger storage capacity of the rear module **400**.

False Floor Configuration

As shown in FIG. **36**, an ESS **1080** includes a first battery set **1082** and/or a second battery set **1084** coupled to the floor portions **204** of the passenger capsule **200** laterally outside of the structural tunnel **206** and spaced above the floor portions **204** and under a false floor **1086**. Each of the first battery set **1082** and the second battery set **1084** includes a housing **1088** coupled top the floor portion **204** with isolator mounts **1090**. In some embodiments, the housings **1088** are coupled to the false floor **1086** via isolator mounts in addition to, or as a replacement for, the isolator mounts **1090**. In some embodiments, the housing **1088** is formed from the same material as the v-shaped belly deflector **220** and/or the floor portion **204**.

The false floor **1086** includes a door or removable panel **1092** that provides access to the ESS **1080** from within the passenger compartment **218** of the passenger capsule **200**. In some embodiments, the removable panel **1092** is a plate that is fastened in place. In some embodiments, the removable panel **1092** is hingedly coupled to the false floor **1086**. In some embodiments, the removable panel **1092** is locked in place with a key.

The weight of the ESS **1080** is carried by the hull and frame assembly **100** and/or the passenger capsule **200**. In some embodiments, the weight of the ESS **1080** is supported by the floor portion **204** of the passenger capsule **200**. Each of the first battery set **1082** and the second battery set **1084** can include multiple batteries **1008** or multiple battery cells and be sized as discussed above in the cumulative (i.e., both battery sets) to provide the desired energy storage capacity.

The position of the ESS **1080** adjacent the floor portion **204** provides a low center of gravity. In some embodiments, the weight of the ESS **1080** is substantially all below the natural center of gravity of the vehicle **10** and the addition of the ESS **1080** lowers the center of gravity of the vehicle **10**. In some embodiments, the ESS **1080** extends longitudinally along the length of the passenger capsule **200** and provides fore-aft stability ballast.

In some embodiments, the ESS **1000**, the ESS **1044**, the ESS **1056**, the ESS **1068**, and/or the ESS **1080** are used in combination.

Controls

Referring to FIGS. **37-39**, the vehicle **10** can include a control system **1600** for controlling the vehicle **10** or systems of the vehicle **10** between and according to different modes of operation. In some embodiments, the vehicle **10** is operable in an engine mode, a dual-drive mode, an EV/silent mode, and/or an ultrasilent mode. The control system **1600** includes a controller **1602** configured to transition the vehicle **10** between the different modes. According to exemplary embodiment, the control system **1600** is configured to provide control signals to the driveline **600** (e.g., the engine **610**, the transmission **620**, the IMG **700**, the FEAD **800**, etc.) to transition the driveline **600** and the FEAD **800** between the different modes.

As shown in FIG. **37**, the control system **1600** includes the controller **1602**, an operator interface, shown as human machine interface (“HMI”) **1610**, the ESS **1000** (and/or sensors or controllers of the ESS **1000**), a temperature sensor **1612**, and an engine sensor **1614**. The ESS **1000** is configured to provide detected battery SoC of batteries or energy storage devices of the ESS **1000** to the controller **1602**. The engine sensor **1614** can be a sensor of the engine **610**, feedback from a controller of the engine **610**, etc. to provide current speed w of the engine **610** (e.g., revolutions per minute “RPM”) and/or current torque t of the engine **610**. The temperature sensor **1612** is configured to provide a detected, measured, or sensed temperature of the engine **610**.

and/or of other components of the vehicle 10 (e.g., the ESS 1000, the transmission 620, etc.) to the controller 1602. The HMI 1610 is configured to receive a user input and provide the user input to the controller 1602 (e.g., a selection of a specific mode). The controller 1602 is configured to use any of the battery SoC, the current speed w of the engine 610, the current torque t of the engine 610, the temperature of the engine 610 (or other components), and/or the user input to transition the vehicle 10 (e.g., the driveline 600 and the FEAD 800) between the different modes, and to operate the vehicle 10 (e.g., the driveline 600 and the FEAD 800) according to the different modes. The HMI 1610 can be positioned within the passenger compartment 218 of the passenger capsule 200 of the vehicle 10.

As shown in FIGS. 37 and 39, the controller 1602 includes a processing circuit 1604 including a processor 1606 and memory 1608. The processing circuit 1604 can be communicably connected to a communications interface such that the processing circuit 1604 and the various components thereof can send and receive data via the communications interface. The processor 1606 can be implemented as a general purpose processor, an application specific integrated circuit (“ASIC”), one or more field programmable gate arrays (“FPGAs”), a group of processing components, or other suitable electronic processing components.

The memory 1608 (e.g., memory, memory unit, storage device, etc.) can include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage, etc.) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present application. The memory 1608 can be or include volatile memory or non-volatile memory. The memory 1608 can include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present application. According to some embodiments, the memory 1608 is communicably connected to the processor 1606 via the processing circuit 1604 and includes computer code for executing (e.g., by the processing circuit 1604 and/or the processor 1606) one or more processes described herein.

As shown in FIG. 39, the memory 1608 includes an engine mode 1616, a dual-drive mode 1618, an EV/silent mode 1620, and an ultrasilent mode 1622, according to an exemplary embodiment. The processing circuit 1604 is configured to transition between the different modes and operate the vehicle 10 according to an active one of the engine mode 1616, the dual-drive mode 1618, the EV/silent mode 1620, or the ultrasilent mode 1622. The controller 1602 may transition between the modes in response to a user input, or at least partially automatically (e.g., based on sensor data). The controller 1602 generates engine control signals for the engine 610, the engine clutch 750, and/or the transmission 620, IMG control signals for the IMG 700, FEAD control signals for the FEAD 800 or controllable components thereof, and display data for the HMI 1610 according to the active one of the modes 1616-1622. The HMI 1610 can be or include any of a display screen, a touch screen, input buttons, levers, a steering wheel, a joystick, alert lights, alert speakers, etc., or any other component configured to facilitate input of data from the user to the controller 1602 or output of data from the controller 1602 to the HMI 1610.

Engine Mode

According to an exemplary embodiment, the control system 1600 is configured to operate the vehicle 10 according to the engine mode 1616. In some embodiments, the

controller 1602 transitions the vehicle 10 into the engine mode 1616 when a user input is received from the HMI 1610 to operate the vehicle 10 according to the engine mode 1616. In some embodiments, the engine mode 1616 is a default mode of operation of the vehicle 10.

When the vehicle 10 is operated by the controller 1602 according to the engine mode 1616, control signals are generated by the controller 1602 and provided to the driveline 600 so that the engine 610 operates to drive the driveline 600 through the IMG 700 and the transmission 620. The controller 1602 can also provide control signals to the IMG 700 so that the IMG 700 functions as a generator, is driven by the engine 610, and generates electrical energy that is provided to the ESS 1000 for storage, and/or provided to electrical components of the vehicle 10 for consumption. The engine 610 also drives the FEAD 800 in the engine mode 1616, according to some embodiments. In some embodiments, in the engine mode 1616, the controller 1602 is configured to provide control signals to the motor/generator 822 of the FEAD 800 such that the motor/generator 822 functions as a generator and is driven by the engine 610. The motor/generator 822 of the FEAD 800 generates electrical energy when driven by the engine 610 and provides the electrical energy to the ESS 1000 for storage and later use, and/or provides the electrical energy to electrical components of the vehicle 10 for consumption. In the engine mode 1616, the engine 610 may therefore drive the IMG 700, the FEAD 800, and/or the transmission 620. The engine 610 drives the axle assemblies 500 or tractive elements thereof by driving the transmission 620.

The engine 610 drives the FEAD 800 and the accessories of the FEAD 800 (e.g., the hydraulic pump 832, the air compressor 808, the fan 810, the motor/generator 822). The engine 610 may also selectively drive the fan 810 through selective engagement of the fan clutch 856. In some embodiments, the controller 1602 is configured to use the engine temperature from the temperature sensor 1612 to transition the fan clutch 856 between an engaged state and a disengaged state. For example, when the engine temperature exceeds a predetermined value, the controller 1602 may transition the fan clutch 856 into the engaged state so that the fan 810 is driven by the engine 610 to cool the engine 610 (and/or other components of the vehicle 10). When the engine temperature decreases below another predetermined temperature, the controller 1602 can generate control signals for the fan clutch 856 to transition the fan clutch 856 into the disengaged state. In some embodiments, the controller 1602 is configured to operate the HMI 1610 to provide an alert or display to the user that the fan clutch 856 is about to be actuated to the engaged state. In some embodiments, the controller 1602 operates the HMI 1610 to display a current status of the fan clutch 856.

Dual-Drive Mode

According to an exemplary embodiment, the controller 1602 is configured to transition the vehicle 10 into the dual-drive mode 1618 and operate the vehicle 10 according to the dual-drive mode 1618. In another embodiment, the controller 1602 does not include the dual-drive mode 1618. In the dual-drive mode 1618, both the engine 610 and the IMG 700 operate to provide torque to tractive elements of the vehicle 10 through the transmission 620. The engine 610 and the IMG 700 can both operate to provide a maximum torque to the transmission 620 as defined by specifications or ratings of the transmission 620. In the dual-drive mode 1618, the IMG 700 and the engine 610 cooperatively operate to drive the driveline 600.

As shown in FIG. 38, a graph 1700 illustrates a maximum allowable torque 1702, an electric motor torque speed curve 1704, and an engine torque speed curve 1706. The maximum allowable torque 1702 is defined by a rating or capability of the transmission 620. When the vehicle 10 is in the dual-drive mode 1618, the controller 1602 is configured to (i) monitor torque and speed of the engine 610 (e.g., as provided by the engine sensor 1614, a defined by a predetermined torque-speed curve for the engine 610, etc.) and (ii) determine, based on the maximum allowable torque 1702 (e.g., based on a comparison between the current torque of the engine 610 and the maximum allowable torque 1702), an additional amount of torque that can be supported by the transmission 620. If the transmission 620 can support additional torque, the controller 1602 is configured to operate the IMG 700 (e.g., by generating and providing control signals to the IMG 700) to provide additional torque to the transmission 620. In some embodiments, the controller 1602 is configured to operate the IMG 700 to provide additional torque so that a combined torque output by the IMG 700 and the engine 610 is equal to or less than the maximum allowable torque 1702 supported by the transmission 620.

The dual-drive mode 1618 can be similar to the engine mode 1616 but with the additional torque provided to the transmission 620 by the IMG 700 (e.g., with the IMG 700 operating as an electric motor). In some embodiments, the IMG 700 and the engine 610 both operate to provide combined torque to the transmission 620 at a same speed. In some embodiments, the speeds of the IMG 700 and the engine 610 are different.

Advantageously, the dual-drive mode 1618 can be used when the vehicle 10 climbs a hill, when the vehicle 10 is under enemy fire, etc. to provide enhanced acceleration and grade ability. In some embodiments, the dual-drive mode 1618 includes operating the engine 610 and the IMG 700 cooperatively to consistently (e.g., over time, or when the dual-drive mode 1618 is active) provide the maximum allowable torque 1702 to the transmission 620. In some embodiments, the controller 1602 is configured to transition the vehicle 10, or more specifically the driveline 600, into the dual-drive mode 1618 in response to a user input received via the HMI 1610. In some embodiments, the controller 1602 is configured to automatically transition the driveline 600 into the dual-drive mode 1618 in response to sensor data indicating a slope, tilt, roll, or angle of the vehicle 10 (e.g., to detect when the vehicle 10 is climbing a hill and additional or assisting torque from the IMG 700 may be advantageous).

Silent Mode

According to an exemplary embodiment, the controller 1602 includes the EV/silent mode 1620 and is configured to operate the driveline 600 according to the EV/silent mode 1620 in response to receiving a user input from the HMI 1610 to operate according to the EV/silent mode 1620. In the EV/silent mode 1620, the controller 1602 is configured to generate control signals for the engine 610 and provide the control signals to the engine 610 to shut off the engine 610. Advantageously, shutting off the engine 610 reduces a sound output of the vehicle 10 to facilitate substantially quieter operation of the vehicle 10. When the engine 610 is shut off, the driveline 600 (e.g., tractive elements of the axle assemblies 500) is driven by the IMG 700. The IMG 700 can function as an electric motor, consuming electrical energy from the ESS 1000 to drive the vehicle 10 (e.g., for transportation of the vehicle 10). Advantageously, shutting

off the engine 610 also reduces a thermal signature of the vehicle 10 to facilitate concealment or harder thermal detection of the vehicle 10.

In the EV/silent mode 1620, the FEAD 800 is driven by the motor/generator 822 as described in greater detail above with reference to FIGS. 15-19. Shutting off the engine 610, driving the transmission 620 with the IMG 700, and driving the FEAD 800 with the motor/generator 822 can reduce an operational sound level of the vehicle 10 (relative to the engine mode 1616) by a significant amount. By way of example, Applicant performed a drive-by test in the engine mode and the silent mode, which resulted in about a 25 decibels (dB) reduction in sound when switching from the engine mode to the silent mode. The fan 810 and fan clutch 856 can be operated based on the temperature received from the temperature sensor 1612 as described in greater detail above with reference to the engine mode 1616. In some embodiments, the controller 1602 is configured to monitor the battery SoC of the ESS 1000 to determine an amount of energy remaining and an estimated remaining runtime of the vehicle 10 in the EV/silent mode 1620. In some embodiments, when the SoC of the ESS 1000 reduces to or below a first threshold, the controller 1602 operates the HMI 1610 to provide a warning to the user regarding the SoC of the ESS 1000. In some embodiments, the controller 1602 is configured to monitor electrical energy consumption or a rate of energy consumption of the ESS 1000 during the EV/silent mode 1620 to determine an estimated amount of runtime remaining for the vehicle 10 in the EV/silent mode 1620. In some embodiments, when the SoC of the ESS 1000 reduces to a minimum allowable level (e.g., 20% SoC), the controller 1602 is configured to automatically transition the vehicle 10 into the engine mode 1616 (e.g., starting the engine 610 by engaging the engine clutch 750). In some embodiments, the controller 1602 is configured to operate the HMI 1610 to notify the user prior to transitioning into the engine mode 1616. In some embodiments, the user can provide an input to override the automatic transition into the engine mode 1616, or to transition the vehicle 10 into the ultrasilent mode 1622.

When the vehicle 10 is operated according to the EV/silent mode 1620, the vehicle 10 may be configured to operate for at least 30 minutes at a speed of at least 25 mph (e.g., 30-35 minutes at 45 mph). In some embodiments, when in the EV/silent mode 1620, the FEAD 800 and, therefore, the fan 810 are driven by the motor/generator 822, independently of a speed of the IMG 700 that is used to drive the vehicle 10 for transportation (e.g., the transmission 620). In some embodiments, operating the fan 810 independently of operation of the IMG 700 facilitates operating the fan 810 at a constant speed (e.g., 1400 RPM) regardless of a speed of the IMG 700 (which prevents sound fluctuations that would otherwise occur due to increasing and decreasing the fan speed). However, when the vehicle 10 is operated in the engine mode 1616 and the engine 610 drives the FEAD 800, the speed of the fan 810 may vary based on variations of the speed of the engine 610.

Ultra-Silent Mode

According to an exemplary embodiment, the controller 1602 includes the ultrasilent mode 1622 and is configured to operate the vehicle 10 according to the ultrasilent mode 1622. In another embodiment, the controller 1602 does not include the ultrasilent mode 1622. When the vehicle 10 is operated according to the ultrasilent mode 1622, the controller 1602 is configured to maintain or transition the engine 610 in an off state (e.g., to reduce sound output) and drive the driveline 600 by operating the IMG 700 (e.g., to provide

an output torque to the transmission 620). The ultrasilent mode 1622 can be similar to the EV/silent mode 1620 but with additional operations to further reduce sound output of the vehicle 10.

In some embodiments, the ultrasilent mode 1622 includes shutting off operation of the fan 810 by disengaging the fan clutch 856. Shutting off operation of the fan 810 by disengaging the fan clutch 856 can further reduce sound output of the vehicle 10. In some embodiments, during operation of the vehicle 10 in the ultrasilent mode 1622, automatic transitioning of the vehicle 10 into the engine mode 1616 (or more particularly, starting of the engine 610) is limited. In some embodiments, during operation of the vehicle 10 in the ultrasilent mode 1622, operation of the fan 810 of the FEAD 800, and activation of the engine 610 is limited, regardless of the temperature provided by the temperature sensor 1612, and the SoC of the batteries of the ESS 1000. In this way, the vehicle 10 can be operated in the ultrasilent mode 1622 even to the point of complete depletion of the ESS 1000. In some embodiments, the controller 1602 is configured to provide alerts, notifications, alarms, etc. to the user or operator of the vehicle 10 via the HMI 1610 to notify the operator that the batteries of the ESS 1000 are about to be depleted, that an overheat condition is proximate, etc. The operator may manually transition the vehicle 10 out of the ultrasilent mode 1622 (e.g., to start the engine 610 to charge the batteries of the ESS 1000 and/or to engage the fan 810 of the FEAD 800) as desired. Advantageously, operating the vehicle 10 according to the ultrasilent mode 1622 facilitates improved noise and thermal concealment of the vehicle 10.

Alternative Drivelines

According to the various embodiments shown in FIGS. 40-42 various other driveline arrangements for the driveline 600 (e.g., that do not include the IMG 700) can be incorporated into the vehicle 10 to enable multiple modes of vehicle travel. As discussed in detail below, a variety of alternative arrangements can provide the vehicle 10 with one or more of (i) an engine-only travel mode, (ii) an electric-motor only travel mode, and (iii) a hybrid or dual-drive travel mode where each of the engine 610 and an electric motor may variously function, depending on different traveling conditions (e.g., traveling downhill, uphill, below a threshold speed, above a threshold speed, etc.). In some examples, the driveline 600 can be arranged to operate the motor/generator 740 as a booster motor, such that each of the engine 610 and the motor/generator 740 simultaneously drive the transmission 620, and therefore the transaxle drive shaft 630 and the front axle drive shaft 650, providing a maximum output.

Electrified Transaxle

As shown in FIG. 40, the driveline 600 of the vehicle 10 includes a second electrified driveline arrangement replacing the IMG 700 with an electrified transaxle, shown as electrified transaxle assembly 2000. The electrified transaxle assembly 2000 is generally positioned within the rear module 400 (e.g., within the rear subframe 410), and is configured to supply rotational power to each of the rear axle and front axle assemblies 500 to drive the vehicle 10. The electrified transaxle assembly 2000 can be positioned opposite the engine 610 and transmission 620, and can be configured to selectively impart rotational motion to each of the transaxle drive shaft 630 and front axle drive shaft 650 to drive the vehicle 10.

The electrified transaxle assembly 2000 generally includes an electric drive motor 2010 and a gearbox 2020 positioned forward of and coupled to a driveshaft of the electric drive motor 2010. The gearbox 2020 can include one

or more gears that engage with the transaxle 640 (e.g., one or more gears thereof), which then imparts rotational motion from the electric drive motor 2010 into each of the rear axle and front axle assemblies 500 to drive the vehicle 10. In some examples, the transaxle 640 further includes a clutch assembly that can selectively decouple or disengage electric drive motor 2010 from the transaxle 640, such that the vehicle 10 can be driven by the engine 610 and independent of the electric drive motor 2010 in certain instances (e.g., to execute an engine drive operation mode). The transmission 620 may be shifted to a neutral gear to decouple the electrified transaxle assembly 2000 from the engine 610 such that the vehicle 10 can be driven by the electric drive motor 2010 and independent of the engine 610 in certain instances (e.g., to execute a silent drive operation mode). In some examples, the electric drive motor 2010 is configured similarly to the motor/generator 740 described above, such that the electric drive motor 2010 can be configured to both draw power from, and generate and provide power to the ESS 1000, depending on the mode the vehicle 10 is in.

Using the vehicle 10 and the electrified transaxle assembly 2000, each of the travel modes described above can be performed by the vehicle 10. For example, in the engine-only travel mode, the engine 610 can once again supply rotational power to the transmission 620, which in turn rotates the transaxle drive shaft 630. The transaxle drive shaft 630 can in turn drive the transaxle 640, which drive the rear axle assembly 500, as well as the front axle drive shaft 650 to drive the front axle assembly 500. In some examples, rotation of the transaxle 640 can be used to drive the electric drive motor 2010 to generate electricity, which can be supplied to the ESS 1000. For example, when the transaxle clutch assembly 2030 is engaged and a gear within the gearbox 2020 engages the transaxle 640, rotation of the transaxle 640 will transmit rotational force through the gearbox 2020 to the driveshaft of the electric drive motor 2010. If the electric drive motor 2010 is configured as a motor/generator 740, as described above, rotation of the drive shaft within an electric drive motor housing 2012 (which includes wound coils) will generate electricity. The electricity generated can then be supplied to or otherwise transferred to the ESS 1000 for subsequent use. In some examples, the electric drive motor 2010 includes a transformer and/or an inverter (or rectifier) that are used to condition and step down or step up the generated electrical power prior to being supplied back to the ESS 1000.

In examples where the electric drive motor 2010 is configured as a motor only (e.g., and is not configured to generate and/or supply electrical power to the ESS 1000), the electric drive motor 2010 can be decoupled from the transaxle 640 using the transaxle clutch assembly 2030. The transaxle clutch assembly 2030 can decouple or disengage one or more of the gears within the gearbox 2020 from the transaxle 640, which then allows the transaxle 640 to rotate without transmitting rotational power through the gearbox 2020 and/or to the electric drive motor 2010. In some examples, the gears within the gearbox 2020 remain in contact with the transaxle 640, but are disengaged with a gearbox shaft or countershaft so that the gears freely spin and do not transmit torque. Accordingly, in this arrangement, the engine 610 and transmission 620 power each of the transaxle drive shaft 630 and the front axle drive shaft 650 while the electric drive motor 2010 is inactive (e.g., no or limited power is supplied to the electric drive motor 2010).

If a silent or reduced fuel mode is selected, the driveline 600 of the vehicle 10 is reconfigured. First, the engine 610 can be turned off, which in turn halts the rotation of the

transmission 620. In some examples, the engine clutch 750 disengages the transmission 620, such that the transmission 620 is free to rotate independently (or nearly independently) of the drive shaft of the engine 610. Eliminating the rotation of the transmission 620 in turn ceases rotational power transmission from the transmission 620 to the transaxle drive shaft 630, which then stops (or slows) the vehicle 10 from moving.

With the engine 610 and transmission 620 disengaged from the electrified transaxle assembly 2000 of the driveline 600, the electrified transaxle assembly 2000 can be activated. First, the transaxle clutch assembly 2030 can engage the gearbox 2020. The gearbox 2020 then creates a rotational link between the transaxle 640 and the drive shaft of the electric drive motor 2010. With this coupling created, the ESS 1000 can supply electrical power to the electric drive motor 2010. In some examples, the ESS 1000 includes an inverter to convert stored DC electric power within the ESS 1000 to AC electric power that can be used by the electric drive motor 2010. Once activated, the electric drive motor 2010 rotates its drive shaft, which in turn imparts a torque to the transaxle 640. Because the transaxle 640 is coupled to the rear axle assembly 500, rotation of the transaxle 640 drives the rear wheels of the vehicle 10. Similarly, the rotation of the transaxle 640 transmits torque to the front axle drive shaft 650, which in turn drives the front axle assembly 500 to provide all-wheel (or four-wheel, in some embodiments) drive to the vehicle 10 in the silent or quieter electric-motor-only travel mode. In some examples, the ESS 1000 and electric drive motor 2010 can allow the vehicle 10 to travel in the silent or electric-motor-only mode for greater than 30 minutes at speeds of 25 miles per hour or higher. To accomplish these tasks, the electric drive motor 2010 can be configured to produce approximately 70 kW of continuous output power, with a peak output rating of 200 kW or more.

Similarly, hybrid modes of travel can be accomplished. For example, in some embodiments, the vehicle 10 operates in the electric-motor-only travel mode until a certain threshold traveling speed (e.g., 25 mph) is reached. When the threshold traveling speed is reached, the engine 610 can be activated and engaged with the transmission 620, while the electric drive motor 2010 can be deactivated and decoupled from the transaxle 640. In some examples, the engine 610 is activated upon the vehicle 10 reaching a first threshold speed (e.g., 25 mph) and the engine clutch 750 and/or transmission 620 are engaged to couple the engine 610 to the driveline 600 upon the vehicle 10 reaching a second threshold speed (e.g., 30 mph). In some examples, the driveline 600 transitions back to an electric-motor-only mode after the vehicle 10 has been traveling below the first threshold speed for a predetermined time period (e.g., 30 seconds, 60 seconds, 120 seconds, etc.). Using the above-described electrified transaxle assembly 2000 with the driveline 600, various different vehicle modes can be executed, including engine-only, electric-motor-only, and hybrid. As described above, different embodiments of the vehicle 10 can include an electric drive motor 2010 having a structure similar to the motor/generator 740, which allows for electricity to be generated and stored within the ESS 1000, for use in driving the electric drive motor 2010 at a later time.

Rear Engine PTO

As shown in FIG. 41, the driveline 600 of the vehicle 10 includes a third electrified driveline arrangement replacing the IMG 700 with a rear engine PTO (“REPTO”), shown as REPTO 2100. The REPTO 2100, like the electrified transaxle assembly 2000, includes an electric drive motor 2110 that can be selectively coupled with the transmission

620 using a gearbox 2120 and a REPTO clutch assembly 2130. The gearbox 2120 and the REPTO clutch assembly 2130 of the REPTO 2100 are positioned between the engine 610 and the transmission 620, and the electric drive motor 2110 is positioned within the tunnel slot 208 of the structural tunnel 206 of the passenger capsule 200. The electric drive motor 2110 is configured to supply rotational power the gearbox 2120 to drive the transmission 620 and, thereby, each of the rear axle and front axle assemblies 500 to drive the vehicle 10. Specifically, the REPTO 2100 can be configured to selectively impart rotational motion to each of the transaxle drive shaft 630 and the front axle drive shaft 650 through the transmission 620 and the transaxle 640 to drive the vehicle 10. Once again, the vehicle 10 can be configured to drive in each of the engine-only mode, the electric drive-motor-only mode, and a hybrid mode. In embodiments where the electric drive motor 2110 is configured like the motor/generator 740, the electric drive motor 2110 can generate and provide electrical power to the ESS 1000 for storage and subsequent use.

The electric drive motor 2110 of the REPTO 2100 is positioned behind the engine 610, and is configured to provide an alternative torque to the transmission 620 to drive the vehicle 10. As shown in FIG. 41, the electric drive motor 2110 includes a drive shaft 2112 that is driven by the electric drive motor 2110. The drive shaft 2112 extends forward, toward the engine 610 and parallel to the transaxle drive shaft 630. The drive shaft 2112 is coupled to (e.g., in a splined or geared engagement) with one or more gears within the gearbox 2120 positioned forward of the transmission 620 and behind the engine 610. The one or more gears within the gearbox 2120 can be selectively engaged with the transmission 620, such that rotation of the drive shaft 2112 rotates and transmits a torque to the transmission 620 and the transaxle drive shaft 630 to drive the vehicle 10. In some examples, the gearbox 2120 includes the REPTO clutch assembly 2130 that is configured to selectively engage the drive shaft 2112 with the transmission 620 to transmit torque from the electric drive motor 2110 through to the axle assemblies 500 to drive the vehicle 10. In other examples, the gearbox 2120 remains engaged with the drive shaft 2112 such that when the electric drive motor 2110 is inactive, torque is transferred from the engine 610, through the gearbox 2120, and to the drive shaft 2112, which rotates to generate electrical power that can be subsequently provided to the ESS 1000.

The REPTO 2100 is configured to provide the same multi-mode functionality as described above. For example, when the engine 610 is operating and the vehicle 10 is traveling at high speeds, the electric drive motor 2110 can be disengaged from the transmission 620 (e.g., through the REPTO clutch assembly 2130 disengagement), which in turn permits the transmission and/or gears within the gearbox 2120 to rotate without imparting a significant torque onto the drive shaft 2112 of the electric drive motor 2110. The torque produced by the engine 610 is supplied to the transmission 620, which then rotates the transaxle drive shaft 630 and transaxle 640. Rotation of the transaxle 640 in turn drives the front axle drive shaft 650, thereby transmitting torque to each of the front axle and rear axle assemblies 500 to drive the vehicle 10. In other examples, the electric drive motor 2110 remains clutched to the gearbox 2120 and the transmission 620, such that rotation of the engine 610 (e.g., the engine output shaft) rotates the drive shaft 2112, which in turn generates electricity within the coils of the electric drive motor 2110.

The REPTO 2100 is also configured to operate in a silent mode. To operate the REPTO 2100 in the silent mode, the engine 610 is decoupled from the transmission 620 (e.g., using a clutch assembly). The gearbox 2120 is then engaged with the transmission 620 (e.g., using the REPTO clutch assembly 2130) to create a mechanical linkage between the electric drive motor 2110 and the transaxle drive shaft 630. Then, the electric drive motor 2110 is activated. As discussed above, rotation of the electric drive motor 2110 rotates the transmission 620 shaft, which in turn rotates the transaxle 640 to drive each of the rear and front axle assemblies 500 using only electric power from the electric drive motor 2110. With the engine 610 deactivated, the vehicle 10 is able to drive in a "stealth mode" that makes the vehicle 10 more difficult to hear and less detectable by enemies. In some examples, the vehicle 10 is configured to transition between the stealth mode and the engine-only mode based upon traveling speed or remaining state of charge of the ESS 1000, for example. As discussed above, various different timing strategies can also be used to transition the vehicle 10 between driving modes during operation.

Motor/Gearbox

As shown in FIG. 42, the driveline 600 of the vehicle 10 includes a fourth electrified driveline arrangement replacing the IMG 700 with a motor and gearbox assembly, shown as an upper motor drive shaft and gearbox assembly 2200. The upper motor drive shaft and gearbox assembly 2200 includes a separate electric drive motor 2210 that can be selectively coupled with the transmission 620 and/or the transaxle drive shaft 630 using a gearbox 2220 and a rear clutch assembly 2230. As shown in FIG. 42, the electric drive motor 2210, the gearbox 2220, and the rear clutch assembly 2230 are each positioned within the tunnel slot 208 of the structural tunnel 206 of the passenger capsule 200 and behind the transmission 620. In some examples, the gearbox 2220 is positioned in-line with the transaxle drive shaft 630, which allows the electric drive motor 2210 to impart torque onto the transaxle drive shaft 630 to drive the vehicle 10 independently of the engine 610.

The electric drive motor 2210 includes a drive shaft 2212 that is engaged with one or more gears within the gearbox 2220. The drive shaft 2212 extends approximately parallel (e.g., +/-10 degrees) to the transaxle drive shaft 630, and is configured to drive each of the transaxle drive shaft 630, the transaxle 640, and the front axle drive shaft 650 when the vehicle 10 is operating in the silent or stealth mode. Like the electric drive motor 2010 and the electric drive motor 2110, the electric drive motor 2210 can be an asynchronous or induction AC electric motor that can be controlled using a variable frequency drive. The electric drive motor 2210 can be supplied with electricity from the ESS 1000, which can include an inverter to convert DC power stored within the ESS 1000 to AC power that can be used by the electric drive motor 2210.

The electric drive motor 2210 can also be configured as a motor/generator. Accordingly, when the vehicle 10 is in an engine-only drive mode, and the transaxle drive shaft 630 is being driven by the engine 610, torque can be transmitted to the drive shaft 2212 of the electric drive motor 2210 through the gearbox 2220. When the drive shaft 2212 is rotated within the housing 2214 of the electric drive motor 2210, AC electricity is generated. The generated electricity can be passed to a rectifier and/or one or more transformers to condition the generated electric power before being supplied back to the ESS 1000. In some examples, the electric drive motor 2210 is decoupled from the transaxle drive shaft 630

when the vehicle 10 is in the engine-only drive mode, such that rotation of the transaxle drive shaft 630 does not transmit a significant amount of torque through the gearbox 2220 and into the drive shaft 2212. The rear clutch assembly 2230 can selectively disengage one or more gears from the gearbox 2220, which in turn decouples the drive shaft 2212 from the transaxle drive shaft 630.

The upper motor drive shaft and gearbox assembly 2200 arrangement can also be used to perform any of the engine-only mode, electric-motor-only (e.g., stealth or silent) mode, or hybrid modes, as discussed above. In the engine-only mode, the electric drive motor 2210 is decoupled from the transaxle drive shaft 630 using the rear clutch assembly 2230. As indicated above, the rear clutch assembly 2230 can disengage one or more gears within the gearbox 2220 from a shaft or countershaft within the gearbox 2220, which allows the gear(s) to freely rotate relative to the shaft and/or the countershaft, such that limited torque is transmitted from the transaxle drive shaft 630 to the drive shaft 2212. Accordingly, the torque within the transaxle drive shaft 630 is transmitted to the transaxle 640 and the front axle drive shaft 650, and not to the drive shaft 2212.

The stealth or silent mode can be engaged by turning off the engine 610 and decoupling the drive shaft from the transmission 620. Then, the electric drive motor 2210 can be linked to the transaxle drive shaft 630 using the rear clutch assembly 2230, which engages one or more gears within the gearbox 2220 to the transaxle drive shaft 630. With the transaxle drive shaft linked to the electric drive motor 2210, the electric drive motor 2210 can be activated. Torque produced by the electric drive motor 2210 can then be transmitted through to the transaxle 640, to drive the rear axle assembly 500, and through to the front axle drive shaft 650, to drive the front axle assembly 500. The vehicle 10 can include a control system or engine control unit (ECU) 2240 that communicates between the various components of the driveline 600 to ensure appropriate timing between the different clutches and the electric drive motor 2210, which allows the vehicle to shift between engine-only and electric-motor-only modes while the vehicle 10 is operating.

Using the various above-described arrangements of the driveline 600, the vehicle 10 can transition between several driving modes, including a silent or "stealth" mode that allows the vehicle 10 to drive while producing a limited amount of noise and a limited thermal signature. A compact motor/generator can be incorporated to charge the ESS 1000, which enables extended electric-motor-only use. Different clutch mechanisms and couplings can be used to allow each of the engine 610 and electric motor (e.g., the IMG 700, the electric drive motor 2010, the electric drive motor 2110, the electric drive motor 2210, etc.) to drive the vehicle 10 independently of one another.

Export Power

Referring now to FIGS. 43-46, a power export system 4800 is positioned in the rear module 400 of the vehicle 10. The power export system 4800 includes the ESS 1000 and the AC power system 1020. The AC power system 1020 is housed in a driver side (e.g., left side) stowage box 450. In some embodiments, the driver side stowage box 450 is positioned vertically above and supported by a driver side wheel well 440. In some embodiments, the AC power system 1020 includes inverters that convert (i) available DC power from the IMG 700, the motor/generator 822, and/or the ESS 1000 into AC power for consumption by components of the vehicle 10 and/or external systems and/or (ii) AC power from the IMG 700 and/or the motor/generator 82 into DC power for consumption by components of the

vehicle 10 and/or external systems. The AC power system 1020 is controllable (e.g., by a control system or a controller) to provide a desired AC output for use on or off the vehicle 10. In some embodiments, the AC power system 1020 provides high voltage AC power and/or three-phase AC power.

The power export system 4800 also includes the power conversion hardware 1014 (e.g., a DC/DC converter). The power conversion hardware 1014 is structured to convert DC power received from either the IMG 700, the motor/generator 822, the ESS 1000, and/or an external power source (e.g., grid power, another vehicle 10, a generator set, etc.) and convert the DC power to power usable by the vehicle systems or off-vehicle systems (e.g., a light stand, a heater, an electric weapon, a laser, etc.). In some embodiments, the power conversion hardware 1014 converts available power to any of 12 V, 24 V, 48 V, 270 V, 280 V, 600 V, another high or low voltage output, or a combination of high voltage and low voltage outputs. In some embodiments, the power conversion hardware 1014 includes actuatable circuits that are controlled to provide a desired DC output. For example, the power conversion hardware 1014 can actuate in response to control commands received from a controller to provide the desired DC output including a desired voltage and/or a desired amperage. In some embodiments, the power conversion hardware 1014 provided power output for use on the vehicle 10, and power output for use off the vehicle 10 simultaneously.

In some embodiments, the power conversion hardware 1014 is positioned between the ESS 1000 and the rear wall 216 of the passenger capsule 200. In some embodiments, the power conversion hardware 1014 is supported on the capsule extension 224. For example, the power conversion hardware 1014 can be supported using brackets, vibration damping pucks, and structures similar to those discussed above with respect to the ESS 1000. In some embodiments, the power conversion hardware 1014 is supported on the rear wall 216 of the passenger capsule 200. For example, the power conversion hardware 1014 can be fastened to the rear wall 216 or supported by the rear wall 216 by vibration damping bosses or other structures. In some embodiments, the power conversion hardware 1014 is supported on the ESS 1000. For example, the power conversion hardware 1014 can be fastened to or supported by the bracket 1024 or another part of the ESS 1000. In some embodiments, the capsule extension 224 is eliminated and the power conversion hardware 1014 is supported between the wheel wells 440 in the bed cavity 460.

As shown in FIG. 44A, the power export system 4800 includes a low voltage system 4814 supported by the passenger side (e.g., the right side) wheel well 440, and an export power panel 4818 supported by a passenger side stowage box 450. The passenger side wheel well 440 includes a fender well 4804 that defines a generally downward surface providing space for the wheel 500. The fender well 4804 defines a topmost plane 4808 parallel to a ground plane that defines the topmost point of the fender well 4804. A fender plate 4812 is positioned toward the longitudinal centerline of the vehicle 10 relative to the fender well 4804 and defines a generally vertical surface. The low voltage system 4814 is mounted to the passenger side wheel well 440. In some embodiments, the low voltage system 4814 is mounted below the topmost plane 4808 of the fender well 4804. In some embodiments, the entire casing or housing of the low voltage system 4814 is positioned below the topmost plane 4808 of the fender well 4804. In some embodiments, the low voltage system 4814 is fastened, adhered, or other-

wise mounted to the fender well 4804. In some embodiments, the low voltage system 4814 is fastened, adhered, or otherwise mounted to the fender plate 4812. The low voltage system 4814 includes circuitry and control components that receive DC power from the power conversion hardware 1014 and converts the received DC to low voltage DC power for use throughout the vehicle 10 and for exporting low voltage DC power off the vehicle 10.

The export power panel 4818 of the power export system 4800 provides an interface for user input, power output, power input, and/or micro-grid integration. The export power panel 4818 includes an input panel 4822, an output panel 4826, a ring panel 4828, and an export power controller 4830.

The input panel 4822 includes a high voltage AC input 4822A, a low voltage AC input 4822B, a high voltage DC input 4822C, and a low voltage DC input 4822D. The inputs 4822A-D of the input panel 4822 are structured to accept electrical power from external sources (e.g., another vehicle 10, grid power, etc.) and power vehicle systems, the charge the ESS 1000, an electric weapon (e.g., a laser), or other electrical systems. In some embodiments, the inputs 4822A-D provide power to a charge controller (e.g., within the export power controller 4830) that converts power to the desired charging power for the ESS 1000. In some embodiments, the inputs 4822A-D provide power to the low voltage system 4814 and/or the power conversion hardware 1014 so that power received through the inputs 4822A-D can be used on the vehicle 10 or export for use off of the vehicle 10.

The output panel 4826 includes a high voltage AC output 4826A, a low voltage AC output 4826B, a high voltage DC output 4826C, and a low voltage DC output 4826D. The outputs 4826A-D of the output panel 4826 are structured to provide electrical power to systems off the vehicle 10. In some embodiments, electrical power is provided to the high voltage AC output 4826A and the low voltage AC output 4826B from the AC power system 1020. In some embodiments, electrical power is provided to the high voltage DC output 4826C from the power conversion hardware 1014. In some embodiments, electrical power is provided to the low voltage DC output 4826D from the low voltage system 4814. The output panel 4826 can be configured by the export power controller 4830 to provide desired power to devices and systems external to the vehicle 10. The output panel 4826 can be configured by the export power controller 4830 to provide desired power to electric components mounted to the vehicle 10 (e.g., providing high voltage AC and/or DC power to an electric weapon (e.g., a laser) mounted to the vehicle 10).

The ring panel 4828 provides an interface for the power export system 4800 and a micro-grid or ring bus system 4836. The ring panel 4828 includes a ring input 4828A structured to receive electrical power from the micro-grid or ring bus system 4836, and a ring output 4828B structured to provide electrical power to the micro-grid or ring bus system 4836.

The export power controller 4830 is structured to control the ESS 1000, the AC power system 1020, the power conversion hardware 1014, the low voltage system 4814, the input panel 4822, the output panel 4826, and the ring panel 4828 to provide desirable power input and output from the power export system 4800. The export power controller 4830 includes a user interface 4834 that can be mounted locally in the stowage compartment 450, or remotely (e.g., in the cab 200). The user interface 4834 allows a user to select which inputs 4822A-D, outputs 4826A-D, or ring connections 4828A-B will be used. In some embodiments,

the export power controller **4830** determines the input, output, and ring power needs automatically. For example, the export power controller **4830** may determine a desired output voltage, AC or DC, or other output characteristics automatically. In some embodiments, the user enters the desired voltage, AC or DC, and other parameters for export power operation via the user interface **4834**. In some embodiments, the user interface **4834** includes a CAN/daport located in the stowage box **450** and structured to provide functionality to the vehicle **10** such that charging/export power/general functionality/troubleshooting can be controlled via tether to an external controller.

As shown in FIG. **44B**, in some embodiments, the power export system **4800** of the vehicle **10** includes wireless power system **5100**. The wireless power system **5100** may be in addition to or replace one or more of the high voltage AC input **4822A** of the input panel, the high voltage DC input **4822C** of the input panel **4822**, the high voltage AC output **4826A** of the output panel **4826**, the high voltage DC output **4826C** of the output panel **4826**, the ring input **4828A** of the ring panel **4828**, and/or the ring output **4828B** of the ring panel **4828** (and, therefore, can perform the functions thereof that are described herein). According to the exemplary embodiment shown in FIG. **44B**, the wireless power system **5100** is integrated into the bed **430** of the rear module **400**. In some embodiments, the wireless power system **5100** is additionally or alternatively positioned elsewhere on or about the vehicle **10** (e.g., integrated into the front module **300**, disposed within or along a front grille and/or front bumper of the vehicle **10**, integrated into a side of the vehicle **10**, integrated into a side of the rear module **400**, integrated into a rear bumper of the vehicle **10**, etc.). As shown in FIG. **44B**, the wireless power system **5100** includes (i) a power transfer interface, shown as transfer pad **5102**, disposed within, along the top of, or underneath the bed **430** and (ii) one or more securing interfaces (e.g., clamps, fasteners, snap-lock interfaces, magnetic, twist-lock interfaces, etc.), shown as couplers **5104**, disposed along the bed **430** and about the periphery of the transfer pad **5102**. The couplers **5104** may be configured to interface with a coupling pad of an off-vehicle system (e.g., an electronic weapon, a laser system, a ring or micro-grid system, another vehicle, other electrified off-vehicle systems, etc.) to secure the coupling pad to the bed **430** above or in contact with the transfer pad **5102** to facilitate wirelessly exporting power off of the vehicle **10** to the off-vehicle system and/or importing power onto the vehicle **10** (e.g., to charge the ESS **1000**) through the engagement (e.g., direct engagement, indirect or spaced engagement, etc.) of the transfer pad **5102** of the vehicle **10** and the coupling pad of the off-vehicle system. In some embodiments, the transfer pad **5102** is configured to facilitate exporting and/or importing high voltage power (e.g., 240 V, 700 V, etc.) through wireless or non-contact power transfer. In such embodiments, the transfer pad **5102** may be configured as at least a 75 KW pad. Such a non-plug-based or non-contact-based system for exporting power from and/or importing power onto the vehicle **10** provides increased robustness and reliability of the power export system **4800** relative to a system that only has traditional input/output ports or connectors (e.g., due to the harsh use cases and environments that the vehicle **10** is designed to encounter that can cause traditional ports to experience rapid wear or frequent damage), as well as alleviate the need for operators of the vehicle **10** to have to physically make high voltage connections.

As shown in FIG. **45**, the vehicle **10** is a first vehicle **10a** integrated with the micro-grid or ring bus system **4836** that

also includes a second vehicle **10b**. The micro-grid or ring bus system **4836** can include one vehicle **10** or more than two vehicles **10a** and **10b**. The micro-grid or ring bus system **4836** includes loads **4838a-d** that include lights **4838a**, heaters **4838b**, a stationary electric weapon **4838c** (e.g., a laser, a sonic weapon, a radar etc.), and external electronics (e.g., computers, cooking systems, troop support systems, medical devices, etc.). In some embodiments, the micro-grid or ring bus system **4836** includes less than four loads **4838** or more than four loads **4838** as desired.

The vehicle **10** is structured to integrate with the micro-grid or ring bus system **4836** to provide power to the micro-grid or ring bus system **4836** via the ring output **4828A** to power the loads **4838**, or to receive power from the micro-grid or ring bus system **4836** via the ring input **4828B**. In some embodiments, multiple vehicles **10** can be connected together in the micro-grid or ring bus system **4836** to provide power to one or more vehicles **10**. For example, one vehicle **10** can include an electric weapon (e.g., a laser) and power can be provided from multiple other vehicles **10** via the micro-grid or ring bus system **4836** to provide power to the electric weapon. The export power controller **3830** can control the vehicle's **10** integration in the micro-grid or ring bus system **4836** and utilize the power available in the micro-grid or ring bus system **4836** to charge the ESS **1000**, or provide power to the micro-grid or ring bus system **4836** to power loads **4838** or other vehicles **10**. The user interface **3834** of the export power controller **4830** can be connected to the micro-grid or ring bus system **4836** so that vehicles **10** in the micro-grid or ring bus system **4836** can be controlled as primary and secondary assets in the micro-grid or ring bus system **4836**. For example, the first vehicle **10a** may be a primary control and the second vehicle **10b** is a secondary control and is controlled by the export controller **4830** of the first vehicle **10a**.

As shown in FIG. **46**, a method of exporting power **4842** includes selecting a power output at step **4846**. In some embodiments, the power output is selected automatically by the export power controller **4830** (e.g., via load sensors, a machine learning engine, etc.), by input from the user interface **4834** manually, via a primary control received from the micro-grid or ring bus system **4836**, or from another selector.

At step **4848**, the export power controller **3830** determines a desired output based on the selected power output. If the desired output is a DC output, the method continues to step **4850** and the DC requirements are determined including voltage requirements and/or other power parameters of a connected load (e.g., an on vehicle load, an off vehicle load, a micro-grid or ring bus system **4836** load **4838**, etc.).

At step **4854**, the export power controller **4830** determines if the desired output is high voltage or low voltage. If the desired output is high voltage, the method **4842** continues to step **4858** and the power conversion hardware **1014** is controlled to deliver the desired output to the high voltage DC output **4826C** in step **4862**.

If the desired output is low voltage, then the method **4842** continues to step **4866** and the power conversion hardware **1014** is controlled to output a preconditioned power to the low voltage system **4814**. In step **4870**, the low voltage system **4814** is controlled to condition the DC power for output to the low voltage DC output **4826D** in step **4874**.

If the desired output is determined to be AC at step **4848**, then the method **4842** proceeds to step **4878** and the AC requirements are determined including voltage requirements and/or other power parameters of a connected load (e.g., an

on vehicle load, an off vehicle load, a micro-grid or ring bus system 4836 load 4838, etc.).

At step 4882, the export power controller 4830 determines if the determined AC requirements should be powered by the ESS 1000 or the IMG 700 (or the motor/generator 822). If the determined AC requirements can be met from power provided by the ESS 1000, then the method 4842 continues to step 4886 and the AC power system 1020 is controlled to provide AC power to the high voltage AC output 4828A or the low voltage AC output 4828B. As discussed above, the AC power system 1020 can be controlled to provide either high voltage or low voltage AC power from the ESS 1000 at step 4890.

If the determines AC requirements require that the IMG 700 or the motor/generator 822 provide the AC output power, then the method 4842 continues to step 4894 and the export power controller 4830 determines if the AC requirements are for high voltage or for low voltage. If high voltage is required, then the method 4842 continues to step 4898 and a high speed engine command is sent from the export power controller 4830 to the engine control unit 2240 to operate the engine 610 at a high speed. With the engine 610 operating at high speed, high voltage AC power can be provided from the IMG 700 or the motor/generator 822 directly to the high voltage AC output 4826A at step 4902.

If low voltage is required, then the method 4842 continues to step 4908 and a low speed engine command is sent from the export power controller 4830 to the engine control unit 2240 to operate the engine 610 at a low speed. With the engine 610 operating at low speed, low voltage AC power can be provided from the IMG 700 or the motor generator 822 directly to the low voltage AC output 4826B at step 4912.

The power export system 4800 can be operated to provide multiple types of output power simultaneously. Additionally, electrical power can be provided to the output panel 4826 from the ESS 100, the IMG 700, the motor/generator 822, the micro-grid or ring bus system 4836, or any combination of those sources simultaneously.

Transfer Case and Vehicle Mounted Generator

Referring now to FIGS. 47-61, another embodiment of the power export system 4800 is shown and positioned in the rear module 400 of the vehicle 10. The power export system 4800 includes the ESS 1000. The power export system 4800 is positioned in the rear module 400 and includes a transfer case 4916 that receives power from the engine 610 and transfers power to the driveline 600 and also a generator gear box 4920 driving a generator 4924. The AC power system 1020 includes an inverter 4928, a high voltage power distribution unit (HV PDU) 4932, and an electronics cooling system 4934 are mounted in an enclosure 4936 supported on the chassis 410. The power export system 4800 also includes a low voltage power generation system 4940 structured to be powered mechanically by the engine 610 or electrically driven by electric motors powered by the generator 4924. The low voltage power generation system 4940 provides low voltage electrical power to pumps and fans on the vehicle 10. Generally, the power export system 4800 provides electrical power to the ESS 1000, onboard vehicle systems (e.g., motors, electrical weapons, etc.) or a large amount of electrical power that can be provided to another vehicle 10 or the micro-grid or ring bus system 4836 via an export power panel 4944 (see FIG. 57) that is similar to the export power panel 4818 discussed above.

Generally, the transfer case 4916 drives the high-power generator 4924 of the vehicle 10. One use of the power export system 4800 is to produce electrical power for a

weapon system. Other applications in defense and commercially can make use of the power export system 4800. The power export system 4800 allows higher power output than can be obtained with a typical transmission mounted PTO. The power export system 4800 takes power from the transfer case 4916 and can be used on the move or when the vehicle 10 is stationary. The power export system 4800 can also transfer power the other way by using the generator 4924 as a motor from stored energy (e.g., the ESS 1000) to provide power to the driveline 600 of the vehicle 10. This allow the vehicle 10 to be driven without use of the engine 610 in the silent mobility mode.

As shown in FIGS. 48 and 49, the transfer case 4916 includes a transfer case housing 4944, an input shaft 4948 that receives mechanical power from the engine 610, a generator clutch 4952 selectively coupling a generator transfer shaft 4954 to the input shaft 4948, an auxiliary lubricant pump 4956 driven by the input shaft 4948, a first driven shaft 4960 and a second driven shaft 4964 each driven by the input shaft 4948. A transfer case cover 4968 is fastened to the transfer case housing 4944 to seal the transfer case 4916. The first driven shaft 4960 and the second driven shaft 4964 can be used to power tractive elements (e.g., the wheels 500) or other components of the driveline 600.

As shown in FIG. 50, the clutch 4952 is electronically controlled and provides selective engagement of the generator transfer shaft 4954 with the input shaft 4948 via a gear train. The clutch 4952 includes a drive gear 4968 driven by the input shaft 4954 and rotatably mounted to the generation transfer shaft 4954, a mounting adapter 4972 including a bolt circle fastening the mounting adapter 4972 to the drive gear 4968, an armature 4976 fastened to the mounting adapter 4972, a rotor 4980 fixedly mounted to the generator transfer shaft 4954 for rotation therewith, and a coil 4984 mounted to the housing 4944. The coil 4984 can be energized to engage the rotor 4980 with the armature 4976 and couple the input shaft 4948 to the generator transfer shaft 4954 and therefore transfer mechanical power to the generator 4924 via the generator gearbox 4920. The clutch 4952 is electrically actuated and no hydraulic pump and/or hosing is required for actuation. The clutch 4952 also includes a clutch housing 4988 that is fastened to the transfer case housing 4944 and allows easy assembly and maintenance of the clutch 4952.

As shown in FIG. 51, the input shaft 4948 is selectively coupled to the first driven shaft 4960 by a drive clutch 4992. In some embodiments, the drive clutch 4992 is electrically actuated so that hydraulic pumps and hoses are not required for actuation. The auxiliary lubricant pump 4956 is electronically controlled (e.g., via CAN communication) and provides positive flow lubrication to the shafts, and bearings of the transfer case 4916. In some embodiments, an oil cooler is included to cool the lubricating oil pumped by the auxiliary lubricant pump 4956.

As shown in FIGS. 52 and 53, the generator gear box 4920 includes a generator gearbox housing 4996, a gearbox input shaft 5000 driven by the generator transfer shaft 4954, a flange 5004 engaged with the generator 4924, and a gear train 5008 driving a generator shaft 5012 of the generator 4924. A lubrication pump 5016 is driven by the gearbox input shaft 5000 and provides lubrication to the bearings, shafts, and gears of the generator gear box 4920. The generator gear box 4920 is arranged as a sealed gear box that utilizes seals 5020 to maintain oil in a closed loop. In some embodiments, the generator gear box 4920 includes the flange 5004 structured to mate with the generator 4924 in the form of an AF440 electric machine provided by Avid Tech-

nology limited. In some embodiments, the generator gear box 4920 provides a front motor mount for the generator 4924 thereby reducing the need for an additional mounting structure for securing the generator 4924. In some embodiments, the flange 5004 provides a sealing structure to the generator 4924.

As shown in FIG. 54, the generator 4924 includes a cable housing 5024 that directs phase cables (4/0 HV Cables) 5028 to face inward toward a longitudinal centerline of the vehicle 10. Directing the cables 5028 toward the center of the vehicle 10 allows easier cable routing to the inverter 4928 and protects the cables 5028 from the exterior of the vehicle 10. In some embodiments, the generator 4924 is a 5-Turn electric machine and produces significantly less current than the 4-Turn option, allowing the use of a single inverter 4928. One drawback the 5-Turn generator 4928 is that it creates more voltage per 1000 RPM than a 4-Turn electric machine. In some embodiments, the generator 4924 is a 4-Turn electric machine. In some embodiments, the power export system 4800 is voltage limited by the inverter 4928 for power-on-the-move. In some embodiments, the clutch 4952 on the transfer case 4916 will open if the engine 610 reaches an upper speed threshold (e.g., 1800 RPM in 6th gear). In some embodiments, the voltage output of the generator 4928 is dependent on the engine 610 speed as shown below in Table 2.

TABLE 2

Engine Speed	Total Gear Ratio	Generator Speed	Calculated Peak Voltage to Inverter
5th Gear			
1200	1.981	2377	452
1300	1.981	2575	489
1400	1.981	2773	527
1500	1.981	2971	565
1600	1.981	3169	602
1700	1.981	3368	640
1800	1.981	3566	677
1900	1.981	3764	715
2000	1.981	3962	753
2100	1.981	4160	790
6th Gear			
1200	2.254	2704	514
1300	2.254	2930	557
1400	2.254	3155	599
1500	2.254	3380	642
1600	2.254	3606	685
1700	2.254	3831	728
1800	2.254	4057	771
1900	2.254	4282	814
2000	2.254	4507	856
2100	2.254	4733	899

The inverter 4928, the HVPDU 4932, and the electronics cooling system 4934 are housed in the enclosure 4936. The inverter 4928 is supported on a shelf of the enclosure near the cable housing 5024 of the generator 4924 to minimize cable 5028 length. The HVPDU 4932 is positioned adjacent the top of the enclosure 4936 and an enclosure cover 5034 which is removable from the enclosure 4936 to provide access for maintenance (e.g., changing fuses etc.). In some embodiments, the HVPDU 4932 is tied to the export power panel 4818 and allows the input, output, and ring power integration of electric power with the power export system 4800. In some embodiments, a modular rail system is included so that extra components can be added to the power export system 4800 by adding an extra rail. A lid switch is

tied to a High Voltage Interlock Loop (HVIL) to disable power in/out of the HVPDU 4932 if the enclosure cover 5034 is removed.

The generator 4924 and the enclosure 4936 are supported on mounting brackets 5036 that are rigidly mounted to the chassis 410. Vibration dampers 5040 inhibit the transference of vibrations from the mounting brackets 5036 to the enclosure 4936 and the generator 4924 while holding the generator 4924 and the enclosure 4936 in place securely.

As shown in FIG. 56, in some embodiments, the enclosure 4936 is housed within or replaces a stowage compartment 450 discussed above. In some embodiments, the enclosure 4936 houses all high voltage components (e.g., the AC power system 1020, the power conversion hardware 1014, the HVPDU 4932, etc.) and the electronics cooling system 4934. Pre-assembly of the enclosure 4936 can improve the manufacturing process and a finished and populated or partially populated enclosure 4936 can then be installed on the vehicle 10. In some embodiments, component mounting sections of the enclosure 4936 are modular. For example, the inverter 4928 can be installable and removable as a modular unit. In some embodiments, the enclosure 4936 provides plenty of room for future components (e.g., high voltage DC-DC converters, high voltage-low voltage DC-DC converters, DC-AC Converters for 240 output, etc.). For example, the enclosure 4936 may include radar components or other cooling components other than the electronics cooling system 4934.

As shown in FIG. 57, the export power panel 4818 in the form of the export power panel 4944 can provide all the functionality of the export power panel 4818 discussed above. The export power panel 4944 is positioned relatively lower than the export power panel 4818 and includes power quick disconnects providing power outputs, power inputs, and ring connections.

As shown in FIG. 58, the electronic cooling system 4934 provides liquid cooling to the high voltage electronics components of the power export system 4800 and includes a coolant pump 5048, a radiator 5052, and a distribution manifold 5056. In some embodiments, the coolant pump 5048 is housed below the enclosure 4936 adjacent the export power panel 4944. In some embodiments, the radiator 5052 is housed in the enclosure 4936 adjacent an exterior of the vehicle 10 where airflow is plentiful. In some embodiments, the radiator 5052 is accessed via a swing away door or a swing open enclosure with the radiator mounted to the swing away portion. The distribution manifold 5056 is positioned to provide convenient hose routing to provide coolant from the manifold 5056 to the electronic components of the power export system 4800 in need of cooling.

As shown in FIG. 59, the low voltage power generation system 4940 structured to be powered mechanically by the engine 610 or electrically driven by electric motors powered by the generator 4924. In some embodiments, the low voltage power generation system 4940 includes two alternators are structured to provide power to the pumps and fans of the vehicle 10. In some embodiments, the low voltage power generation system 4940 includes a machined casing. In some embodiments, the low voltage power generation system 4940 includes a cast casing.

As shown in FIG. 60, the power export system 4800 includes a primary fuel tank 5060 mounted to the chassis 410 and supported above a stowage box 5064 on the driver side (e.g., the left side) of the vehicle 10. As shown in FIG. 61, a secondary fuel tank 5068 is mounted to the chassis 410 on the passenger side (e.g., the right side) of the vehicle 10. In some embodiments, the primary fuel tank 5060 and the

secondary fuel tank **5068** provide a fuel storage capacity of about one-hundred-sixty gallons. In some embodiments, the stowage box **5064** is eliminated and a larger fuel tank installed.

In some embodiments, the generator **4924** outputs up to 800 volts. The power export system **4800** can be used for weapons systems in support of (ISO) long range precision fires, rechargeable next generation squad weapons and integrated visual augmentation system (IVAS) **3.0** goggles ISO soldier lethality, and communication systems ISO Army networks, etc. The power export system **4800** provides a vehicle **10** fitted with a high-power generator option allowing the vehicle **10** to export large amounts of current to power a base, radio system, or have a laser fitted to the vehicle **10**. In some cases the drive through transfer case **4916** is arranged to drive the generator **4924** to produce 275+kW at 600 VDC while the vehicle **10** is in motion, or stationary.

In some embodiments, valuable space is consumed by trying to shoehorn a generator between the engine **610** and the transmission **620**. In some embodiments, a generator running at a diesel engine output speed does not produce power efficiently. In some embodiments, generators need higher RPM for higher power efficiency. Additionally, in some embodiments, heat generated by the engine **610** and the transmission **620** reduces the performance of motors/generators.

In some embodiments, a slim gear box bolts in-between the engine bell housing and the transmission freeing up the options for electric motor/generators by ratio speeding up the RPM, by shrinking the mass and size of the motor/generator, or allowing more power for the same mass and space occupied today. In some embodiments, the arrangement described herein enable better thermal management. In some embodiments, the gear box may be flat teeth or bevel-helical gearing depending on the end load packaging needs (e.g., inline with the transmission or perpendicular). In some embodiments, a high speed ratio of the slim gearbox reduces the size of an electric generator where speeds in the range of 6-12 k+RPM align with low cost automotive generators with low cost compared with large low speed generators.

As utilized herein, the terms “approximately,” “about,” “substantially,” and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the disclosure as recited in the appended claims.

It should be noted that the term “exemplary” and variations thereof, as used herein to describe various embodiments, are intended to indicate that such embodiments are possible examples, representations, or illustrations of possible embodiments (and such terms are not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

The term “coupled” and variations thereof, as used herein, means the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent or fixed) or moveable (e.g., removable or releasable). Such

joining may be achieved with the two members coupled directly to each other, with the two members coupled to each other using a separate intervening member and any additional intermediate members coupled with one another, or with the two members coupled to each other using an intervening member that is integrally formed as a single unitary body with one of the two members. If “coupled” or variations thereof are modified by an additional term (e.g., directly coupled), the generic definition of “coupled” provided above is modified by the plain language meaning of the additional term (e.g., “directly coupled” means the joining of two members without any separate intervening member), resulting in a narrower definition than the generic definition of “coupled” provided above. Such coupling may be mechanical, electrical, or fluidic.

References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below”) are merely used to describe the orientation of various elements in the figures. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

The hardware and data processing components used to implement the various processes, operations, illustrative logics, logical blocks, modules and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose single- or multi-chip processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, or, any conventional processor, controller, microcontroller, or state machine. A processor also may be implemented as a combination of computing devices, such as a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. In some embodiments, particular processes and methods may be performed by circuitry that is specific to a given function. The memory (e.g., memory, memory unit, storage device) may include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present disclosure. The memory may be or include volatile memory or non-volatile memory, and may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. According to an exemplary embodiment, the memory is communicably connected to the processor via a processing circuit and includes computer code for executing (e.g., by the processing circuit or the processor) the one or more processes described herein.

The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored

thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

Although the figures and description may illustrate a specific order of method steps, the order of such steps may differ from what is depicted and described, unless specified differently above. Also, two or more steps may be performed concurrently or with partial concurrence, unless specified differently above. Such variation may depend, for example, on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations of the described methods could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps, and decision steps.

It is important to note that the construction and arrangement of the vehicle 10 and the systems and components thereof (e.g., the hull and frame assembly 100, the driveline 600, IMG 700, the FEAD 800, the ESS 1000, the control system 1600, etc.) as shown in the various exemplary embodiments is illustrative only. Additionally, any element disclosed in one embodiment may be incorporated or utilized with any other embodiment disclosed herein.

The invention claimed is:

1. A military vehicle comprising:
 - a chassis;
 - a cab mounted to the chassis and defining a rear wall;
 - an engine mounted to the chassis;
 - an electric machine coupled to the engine and generating electrical power when driven by the engine;
 - an energy storage system receiving and storing electrical power from the electric machine;
 - power conversion hardware including a DC-DC converter; and
 - an export power panel including:
 - a power input configured to receive electrical power for charging the energy storage system or powering vehicle components; and
 - a power output configured to provide electrical power from at least one of the energy storage system or the electric machine to loads remote from the vehicle; wherein the power input and the power output are configured to be arranged in a ring-bus system.
2. The military vehicle of claim 1, wherein the export power panel is positioned in a passenger side stowage box located vertically above a rear wheel well of the military vehicle.
3. The military vehicle of claim 1, further comprising an alternating current power system housed in a driver side stowage box located rearward of the rear wall of the cab.

4. The military vehicle of claim 3, further comprising a driver side rear wheel well, wherein the driver side stowage box is located vertically above the driver side rear wheel well.

5. The military vehicle of claim 3, wherein the alternating current power system includes an inverter, and provides at least one of high voltage alternating current power or three-phase alternating current power.

6. The military vehicle of claim 1, further comprising:

- a wheel well including a fender well defining a topmost plane; and
- a low voltage system mounted to the wheel well below the topmost plane.

7. The military vehicle of claim 6, wherein the low voltage system receives power from the DC-DC converter and provides low voltage DC power.

8. The military vehicle of claim 6, wherein the wheel well is a passenger rear wheel well.

9. A military vehicle comprising:

- a chassis;
- a cab mounted to the chassis;
- an engine mounted to the chassis;
- an electric machine coupled to the engine and generating electrical power when driven by the engine;
- an energy storage system receiving and storing electrical power from the electric machine;
- power conversion hardware; and
- an export power panel including:
 - a power input configured to receive electrical power for charging the energy storage system or powering vehicle components;
 - a power output configured to provide electrical power from at least one of the energy storage system and the electric machine to loads remote from the vehicle;
 - a ring input configured to receive electrical power from a ring-bus system; and
 - a ring output configured to provide electrical power to the ring-bus system.

10. The military vehicle of claim 9, wherein the military vehicle is configured to provide electrical power to systems onboard the military vehicle, the power output, and the ring output simultaneously.

11. The military vehicle of claim 9, further comprising a controller configured to control the flow of electrical power between the electric machine, the energy storage system, the power conversion hardware, and the export power panel.

12. The military vehicle of claim 11, wherein the controller includes a user interface positioned in a passenger side stowage box located vertically above a rear wheel well of the military vehicle.

13. A military vehicle comprising:

- a chassis;
- a cab mounted to the chassis and defining a rear wall;
- an engine mounted to the chassis;
- an electric machine coupled to the engine and generating electrical power when driven by the engine;
- an energy storage system receiving and storing electrical power from the electric machine; and
- an export power panel positioned in a passenger side stowage box located rearward of the rear wall, the export power panel including:
 - a power input configured to receive electrical power for charging the energy storage system or powering vehicle components;

a power output configured to provide electrical power from at least one of the energy storage system and the electric machine to loads remote from the vehicle;

a ring input configured to receive electrical power from a ring-bus system; and

a ring output configured to provide electrical power to the ring-bus system.

14. The military vehicle of claim 13, further comprising: power conversion hardware positioned between the energy storage system and the rear wall of the cab, the power conversion hardware including a DC-DC converter, the power conversion hardware fastened to one of the energy storage system, the rear wall, or the chassis.

15. The military vehicle of claim 13, further comprising a controller configured to control the flow of electrical power between the electric machine, the energy storage system, the power conversion hardware, and the export power panel, the controller including a user interface positioned in a passenger side stowage box located vertically above a rear wheel well of the military vehicle.

16. A military vehicle comprising:

- a chassis;
- a cab mounted to the chassis and defining a rear wall;
- an engine mounted to the chassis;
- an electric machine coupled to the engine and generating electrical power when driven by the engine;
- an energy storage system receiving and storing electrical power from the electric machine;
- power conversion hardware positioned between the energy storage system and the rear wall of the cab, the power conversion hardware including a DC-DC converter, the power conversion hardware positioned between the energy storage system and the rear wall of

- the cab, the power conversion hardware including a DC-DC converter, the power conversion hardware fastened to one of the energy storage system, the rear wall, or the chassis;
- an alternating current power system housed in a driver side stowage box located rearward of the rear wall of the cab and vertically above a driver side rear wheel well;
- a low voltage system mounted to a passenger wheel well below a topmost plane of a fender well; and
- an export power panel positioned in a passenger side stowage box located rearward of the rear wall, the export power panel including:
 - a power input configured to receive electrical power for charging the energy storage system or powering vehicle components;
 - a power output configured to provide electrical power from at least one of the energy storage system and the electric machine to loads remote from the vehicle;
 - a ring input configured to receive electrical power from a ring-bus system; and
 - a ring output configured to provide electrical power to the ring-bus system.

17. The military vehicle of claim 16, wherein the power input provides electrical power to at least one of the power conversion hardware, the alternating current power system, the electrical machine, the energy storage system, or the ring output; and

wherein the power output receives electrical power from at least one of the power conversion hardware, the alternating current power system, the electrical machine, the energy storage system, or the ring input.

* * * * *