

(43) International Publication Date
12 November 2015 (12.11.2015)

(51) International Patent Classification:

H03F 1/02 (2006.01) H03F 3/217 (2006.01)
H03F 3/181 (2006.01)

(21) International Application Number:

PCT/US2015/029765

(22) International Filing Date:

7 May 2015 (07.05.2015)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/990,363	8 May 2014 (08.05.2014)	US
62/072,059	29 October 2014 (29.10.2014)	US
62/090,142	10 December 2014 (10.12.2014)	US
14/706,680	7 May 2015 (07.05.2015)	US

(71) Applicant: CIRRUS LOGIC, INC. [US/US]; 800 West Sixth Street, Austin, Texas 78701 (US).

(72) Inventors: AMADI, Christophe J.; 8905 Lomita Verde Crt, Austin, Texas 78749 (US). MARU, Siddharth; 3500 Greystone Drive #212, Austin, Texas 78731 (US). KING, Eric J.; 1050 Trail Head Circle, Dripping Springs, Texas 78620 (US).

(74) Agents: PREWITT, Brian K. et al.; Jackson Walker L.L.P., 100 Congress Avenue, Suite 1100, Austin, Texas 78701 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: SWITCHED MODE CONVERTER WITH LOW-VOLTAGE LINEAR MODE



(57) Abstract: A power converter may include a power inductor, a plurality of switches arranged to sequentially operate in a plurality of switch configurations, an output for producing the output voltage, wherein a first switch is coupled to a first output terminal of the output and a second switch is coupled to a second output terminal of the output, and a linear amplifier coupled to the output. The controller may be configured to, in a linear amplifier mode of the power stage, enable the linear amplifier to transfer electrical energy from an input source of the power stage to the load, and in at least one mode of the power stage other than the linear amplifier mode, sequentially apply switch configurations from the plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to transfer the electrical energy from the input source to the load.

SWITCHED MODE CONVERTER WITH LOW-VOLTAGE LINEAR MODE

RELATED APPLICATIONS

The present disclosure claims priority to United States Non-Provisional Patent Application Serial No. 14/706,680, filed May 7, 2015, United States Provisional Patent Application Serial No. 61/990,363, filed May 8, 2014, United States Provisional Patent Application Serial No. 62/072,059, filed October 29, 2014, United States Provisional Patent Application Serial No. 62/090,142, filed December 10, 2014 and each of which is incorporated by reference herein in its entirety.

The present disclosure is related to United States Application Serial No. 14/612,889 filed February 3, 2015, United States Application Serial No. 14/612,946 filed February 3, 2015, and United States Application Serial No. 14/612,734 filed February 3, 2015, each of which is incorporated by reference herein in its entirety.

FIELD OF DISCLOSURE

The present disclosure relates in general to circuits for audio devices, including without limitation personal audio devices such as wireless telephones and media players, and more specifically, to a switch mode amplifier for driving an audio transducer of an audio device.

BACKGROUND

Personal audio devices, including wireless telephones, such as mobile/cellular telephones, cordless telephones, mp3 players, and other consumer audio devices, are in widespread use. Such personal audio devices may include circuitry for driving a pair of headphones or one or more speakers. Such circuitry often includes a speaker driver including a power amplifier for driving an audio output signal to headphones or speakers.

One existing approach to driving an audio output signal is to employ a speaker driver, such as speaker driver 100 depicted in FIGURE 1. Speaker driver 100 may include an envelope-tracking boost converter 102 (e.g., a Class H amplifier) followed by a full-bridge output stage 104 (e.g., a Class D amplifier) which effectively operates as another converter stage. Boost converter 102 may include a power inductor 104, switches

106, 108, and a capacitor 110 arranged as shown. Full-bridge output stage 104 may include switches 112, 114, 116, and 118, inductors 120 and 124, and capacitors 122 and 126 as shown.

Speaker drivers such as speaker driver 100 suffer from numerous disadvantages. One disadvantage is that due to switching in output stage 104, such a speaker driver 100 may give rise to large amounts of radiated electromagnetic radiation, which may cause interference with other electromagnetic signals. Such radiated electromagnetic interference may be mitigated by LC filters formed using inductor 120 and capacitor 122 and inductor 124 and capacitor 126. However, such LC filters are often quite large in size, and coupling capacitors 122 and 124 to the terminals of the output transducer may have a negative impact on the power efficiency of speaker driver 100.

In addition, such architectures often do not handle large impulsive signals. To reduce power consumption, a power supply voltage V_{SUPPLY} may be varied in accordance with the output signal, such that V_{SUPPLY} may operate at lower voltage levels for lower output signal magnitudes. Thus, if a signal quickly increases, adequate time may not be present to increase voltage V_{SUPPLY} , thus leading to signal clipping unless a delay is placed in the signal path. However, adding a delay to a signal path may cause incompatibility with other types of audio circuits, such as adaptive noise cancellation circuits.

SUMMARY

In accordance with the teachings of the present disclosure, one or more disadvantages and problems associated with existing approaches to driving an audio output signal to an audio transducer may be reduced or eliminated.

In accordance with embodiments of the present disclosure, a system may include an impedance estimator configured to estimate an impedance of a load and generate a target current based at least on an input voltage and the impedance, a voltage feedback loop responsive to a difference between the input voltage and an output voltage of the load, and a current controller configured to, responsive to the voltage feedback loop, the impedance estimator, and the input voltage, generate an output current to the load.

In accordance with these and other embodiments of the present disclosure, a method may include estimating an impedance of a load and generating a target current based at least on an input voltage and the impedance. The method may also include generating a feedback voltage responsive to a difference between the input voltage and an output voltage of the load. The method may further include, responsive to the feedback voltage, estimated impedance of the load, and the input voltage, generating an output current to the load.

In accordance with these and other embodiments of the present disclosure, a switching power stage for producing an output voltage to a load may include a power converter and a controller. The power converter may include a power inductor, a plurality of switching, and an output. The plurality of switches may be arranged to sequentially operate in a plurality of switch configurations in accordance with a selected operational mode of the power converter, the selected operational mode selected from a plurality of operational modes. The output may produce the output voltage comprising a first output terminal and a second output terminal, wherein a first switch of the plurality of switches is coupled to the first output terminal and a second switch of the plurality of switches is coupled to the second output terminal. The plurality of operational modes may include a single-ended buck mode for switching a polarity of the output voltage in which: (i) during a charging phase of the power converter, at least one of the plurality of switches is activated such that the power inductor is coupled between a first terminal of a power source and a particular one of the first output terminal and the second output terminal; and (ii) during a transfer phase of the power converter, at least one of the plurality of switches is activated such that the power inductor is coupled between a second terminal of the power source and the particular one of the first output terminal and the second output terminal, wherein the output voltage comprises a differential voltage between the first output terminal and the second output terminal. The controller may be configured to sequentially apply switch configurations from the plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to transfer electrical energy from an input source of the power converter to the load in accordance with the selected operational mode.

In accordance with these and other embodiments of the present disclosure, a method for producing an output voltage to a load may include, in a power converter comprising a power inductor, a plurality of switches arranged to sequentially operate in a plurality of switch configurations in accordance with a selected operational mode of the power converter selected from a plurality of operational modes, and an output for producing the output voltage comprising a first output terminal and a second output terminal, wherein a first switch of the plurality of switches is coupled to the first output terminal and a second switch of the plurality of switches is coupled to the second output terminal, and sequentially applying a plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to operate the power converter in a single-ended buck mode for switching a polarity of the output voltage, such that: (i) during a charging phase of the power converter, at least one of the plurality of switches is activated such that the power inductor is coupled between a first terminal of a power source and a particular one of the first output terminal and the second output terminal; and (ii) during a transfer phase of the power converter, at least one of the plurality of switches is activated such that the power inductor is coupled between a second terminal of the power source and the particular one of the first output terminal and the second output terminal, wherein the output voltage comprises a differential voltage between the first output terminal and the second output terminal.

In accordance with these and other embodiments of the present disclosure, a switching power stage for producing an output voltage to a load may include a power converter comprising a power inductor and plurality of switches arranged to sequentially operate in a plurality of switch configurations and a controller. The controller may be configured to sequentially apply the plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to operate the power converter as a differential output converter to switch a polarity of the output voltage, such that: during a charging phase of the power converter, the power inductor is coupled between (i) one of a first terminal of a power source and a second terminal of the power source and (ii) one of a first terminal of an output load and a second terminal of the output load; and during a transfer phase of the power converter, at least one of the plurality of switches is activated in order to couple the power inductor between the second terminal of

the power source and one of the first terminal of the output load and the second terminal of the output load, wherein the output voltage comprises a differential voltage between the first terminal and the second terminal.

In accordance with these and other embodiments of the present disclosure, a method for producing an output voltage to a load may include, in a power converter comprising a power inductor, a plurality of switches arranged to sequentially operate in a plurality of switch configurations, sequentially applying a plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to operate the power converter as a differential output converter to switch a polarity of the output voltage, such that: during a charging phase of the power converter, the power inductor is coupled between (i) one of a first terminal of a power source and a second terminal of the power source and (ii) one of a first terminal of an output load and a second terminal of the output load; and during a transfer phase of the power converter, at least one of the plurality of switches is activated in order to couple the power inductor between the second terminal of the power source and one of the first terminal of the output load and the second terminal of the output load, wherein the output voltage comprises a differential voltage between the first terminal and the second terminal.

In accordance with these and other embodiments of the present disclosure, a power stage for producing an output voltage to a load may include a power converter and a controller. The power converter may include a power inductor, a plurality of switches arranged to sequentially operate in a plurality of switch configurations, an output for producing the output voltage comprising a first output terminal and a second output terminal, wherein a first switch of the plurality of switches is coupled to the first output terminal and a second switch of the plurality of switches is coupled to the second output terminal, and a linear amplifier coupled to the output. The controller may be configured to, in a linear amplifier mode of the power stage, enable the linear amplifier to transfer electrical energy from an input source of the power stage to the load, and in at least one mode of the power stage other than the linear amplifier mode, sequentially apply switch configurations from the plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to transfer electrical energy from the input source of the power converter to the load.

In accordance with these and other embodiments of the present disclosure, a method for producing an output voltage to a load may include in a power converter comprising a power inductor, a plurality of switches arranged to sequentially operate in a plurality of switch configurations, and an output for producing the output voltage comprising a first output terminal and a second output terminal, wherein a first switch of the plurality of switches is coupled to the first output terminal and a second switch of the plurality of switches is coupled to the second output terminal: (i) in a linear amplifier mode of the power stage, enabling a linear amplifier coupled to the output to transfer electrical energy from an input source of the power stage to the load; and (ii) in at least one mode of the power stage other than the linear amplifier mode, sequentially applying switch configurations from the plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to transfer electrical energy from the input source of the power converter to the load.

Technical advantages of the present disclosure may be readily apparent to one skilled in the art from the figures, description and claims included herein. The objects and advantages of the embodiments will be realized and achieved at least by the elements, features, and combinations particularly pointed out in the claims.

It is to be understood that both the foregoing general description and the following detailed description are examples and explanatory and are not restrictive of the claims set forth in this disclosure.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present embodiments and advantages thereof may be acquired by referring to the following description taken in conjunction with the accompanying drawings, in which like reference numbers indicate like features, and wherein:

FIGURE 1 illustrates an example speaker driver, as is known in the relevant art.

FIGURE 2 illustrates an example personal audio device, in accordance with embodiments of the present disclosure;

FIGURE 3 illustrates a block diagram of selected components of an example audio integrated circuit of a personal audio device, in accordance with embodiments of the present disclosure;

FIGURE 4 illustrates a block and circuit diagram of selected components of an example switched mode amplifier, in accordance with embodiments of the present disclosure;

FIGURE 5 illustrates a circuit diagram of selected components of another example power converter, in accordance with embodiments of the present disclosure;

FIGURE 6 illustrates a table setting forth switch configurations of the power converter of FIGURE 5 when operating in a single-ended boost mode, in accordance with embodiments of the present disclosure;

FIGURE 7 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a charging phase of a single-ended boost mode, in accordance with embodiments of the present disclosure;

FIGURE 8 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a discharge phase of a single-ended boost mode, in accordance with embodiments of the present disclosure;

FIGURE 9 illustrates a table setting forth switch configurations of the power converter of FIGURE 5 when operating in a differential-output buck-boost mode, in accordance with embodiments of the present disclosure;

FIGURE 10 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a charging phase of a differential-output buck-boost mode, in accordance with embodiments of the present disclosure;

FIGURE 11 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a discharge phase of a differential-output buck-boost mode, in accordance with embodiments of the present disclosure;

FIGURE 12 illustrates a table setting forth switch configurations of the power converter of FIGURE 5 when operating in a differential-output buck mode, in accordance with embodiments of the present disclosure;

FIGURE 13 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a charging phase of a differential-output buck mode, in accordance with embodiments of the present disclosure;

FIGURE 14 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in another charging phase of a differential-output buck mode, in accordance with embodiments of the present disclosure;

FIGURE 15 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a discharge phase of a differential-output buck mode, in accordance with embodiments of the present disclosure;

FIGURE 16 illustrates a table setting forth switch configurations of the power converter of FIGURE 5 when operating in a turn-around mode, in accordance with embodiments of the present disclosure;

FIGURE 17 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a charging phase of a differential-output turn-around mode, in accordance with embodiments of the present disclosure;

FIGURE 18 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in another charging phase of a differential-output turn-around mode, in accordance with embodiments of the present disclosure;

FIGURE 19 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a discharge phase of a differential-output turn-around mode, in accordance with embodiments of the present disclosure;

FIGURE 20 illustrates a table setting forth switch configurations of the power converter of FIGURE 5 when operating in a single-ended buck mode, in accordance with embodiments of the present disclosure;

FIGURE 21 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a charging phase of a single-ended buck mode, in accordance with embodiments of the present disclosure;

FIGURE 22 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in a discharge phase of a single-ended buck mode, in accordance with embodiments of the present disclosure;

FIGURE 23 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in another charging phase of a single-ended buck mode, in accordance with embodiments of the present disclosure;

FIGURE 24 illustrates an equivalent circuit diagram of selected components of the power converter of FIGURE 5 operating in another discharge phase of a single-ended buck mode, in accordance with embodiments of the present disclosure;

FIGURE 25 illustrates the power converter of FIGURE 5 including a linear amplifier implemented as a quadrant digital-to-analog converter, in accordance with embodiments of the present disclosure;

FIGURE 26 illustrates the power converter of FIGURE 5 including a linear amplifier implemented as a hemispherical digital-to-analog converter, in accordance with embodiments of the present disclosure;

FIGURE 27 illustrates a circuit diagram of selected components of another example power converter, in accordance with embodiments of the present disclosure;

FIGURE 28 illustrates a graph of an example output voltage having a sinusoidal waveform, the graph indicating example ranges for operation in the various operational modes of the power converter of FIGURE 5, in accordance with embodiments of the present disclosure;

FIGURE 29 illustrates a block diagram of selected components of an example loop filter, in accordance with embodiments of the present disclosure;

FIGURE 30 illustrates a block diagram of selected components of a power converter control, in accordance with embodiments of the present disclosure; and

FIGURE 31 illustrates a block and circuit diagram of selected components of an example switched mode amplifier including an impedance estimator, in accordance with embodiments of the present disclosure.

DETAILED DESCRIPTION

FIGURE 2 illustrates an example personal audio device 1, in accordance with embodiments of the present disclosure. FIGURE 2 depicts personal audio device 1 coupled to a headset 3 in the form of a pair of earbud speakers 8A and 8B. Headset 3 depicted in FIGURE 2 is merely an example, and it is understood that personal audio

device 1 may be used in connection with a variety of audio transducers, including without limitation, headphones, earbuds, in-ear earphones, and external speakers. A plug 4 may provide for connection of headset 3 to an electrical terminal of personal audio device 1. Personal audio device 1 may provide a display to a user and receive user input using a touch screen 2, or alternatively, a standard liquid crystal display (LCD) may be combined with various buttons, sliders, and/or dials disposed on the face and/or sides of personal audio device 1. As also shown in FIGURE 2, personal audio device 1 may include an audio integrated circuit (IC) 9 for generating an analog audio signal for transmission to headset 3 and/or another audio transducer.

FIGURE 3 illustrates a block diagram of selected components of an example audio IC 9 of a personal audio device, in accordance with embodiments of the present disclosure. As shown in FIGURE 3, a microcontroller core 18 may supply a digital audio input signal DIG_IN to a digital-to-analog converter (DAC) 14, which may convert the digital audio input signal to an analog signal V_{IN} . DAC 14 may supply analog signal V_{IN} to an amplifier 16 which may amplify or attenuate audio input signal V_{IN} to provide a differential audio output signal V_{OUT} , which may operate a speaker, headphone transducer, a line level signal output, and/or other suitable output. In some embodiments, DAC 14 may be an integral component of amplifier 16. A power supply 10 may provide the power supply rail inputs of amplifier 16. In some embodiments, power supply 10 may comprise a battery. Although FIGURES 2 and 3 contemplate that audio IC 9 resides in a personal audio device, systems and methods described herein may also be applied to electrical and electronic systems and devices other than a personal audio device, including audio systems for use in a computing device larger than a personal audio device, an automobile, a building, or other structure.

FIGURE 4 illustrates a block and circuit diagram of selected components of an example switched mode amplifier 20, in accordance with embodiments of the present disclosure. In some embodiments, switched mode amplifier 20 may implement all or a portion of amplifier 16 described with respect to FIGURE 3. As shown in FIGURE 4, switched mode amplifier 20 may comprise a loop filter 22, a converter controller 24, and a power converter 26.

Loop filter 22 may comprise any system, device, or apparatus configured to receive an input signal (e.g., audio input signal V_{IN} or a derivative thereof) and a feedback signal (e.g., audio output signal V_{OUT} , a derivative thereof, or other signal indicative of audio output signal V_{OUT}) and based on such input signal and feedback signal, generate a controller input signal to be communicated to converter controller 24. In some embodiments, such controller input signal may comprise a signal indicative of an integrated error between the input signal and the feedback signal, as is described in greater detail below with reference to FIGURES 6, 9 and 25. In other embodiments, such controller input signal may comprise a signal indicative of a target current signal to be driven as an output current I_{OUT} to a load coupled to the output terminals of power converter 26, as described in greater detail below with reference to FIGURES 26 and 27.

Converter controller 24 may comprise any system, device, or apparatus configured to, based on the controller input signal, sequentially select among operational modes of power converter 26 and based on a selected operational mode, communicate a plurality of control signals to power converter 26 to apply a switch configuration from a plurality of switch configurations of switches of power converter 26 to selectively activate or deactivate each of the plurality of switches in order to transfer electrical energy from a power supply V_{SUPPLY} to the load of switched-mode amplifier 20 in accordance with the selected operational mode. Examples of operational modes and switch configurations associated with each are described in greater detail elsewhere in this disclosure. Example implementations of converter controller 24 are also described in greater detail elsewhere in this disclosure. In addition, in some embodiments, converter controller 24 may control switches of a power converter 26 in order to regulate a common mode voltage of the output terminals of power converter 26 to the maximum of a first voltage associated with switched-mode amplifier 20 and a second voltage associated with switched-mode amplifier 20. In some embodiments, the first voltage may comprise one-half of the supply voltage V_{SUPPLY} . In these and other embodiments, the second voltage may comprise one-half of output voltage V_{OUT} , or another signal indicative of an expected voltage for output voltage V_{OUT} (e.g., input voltage signal V_{IN}).

Power converter 26 may receive at its input a voltage V_{SUPPLY} (e.g., provided by power supply 10) at its input, and may generate at its output audio output signal V_{OUT} .

Although not explicitly shown in FIGURE 3, in some embodiments, voltage V_{SUPPLY} may be received via input terminals including a positive input terminal and a negative input terminal which may be coupled to a ground voltage. As described in greater detail in this disclosure, power converter 26 may comprise a power inductor and a plurality of switches that are controlled by control signals received from converter controller 24 in order to convert voltage V_{SUPPLY} to audio output signal V_{OUT} , such that audio output signal V_{OUT} is a function of the input signal to loop filter 22. Examples of power converter 26 are described in greater detail elsewhere in this disclosure.

FIGURE 5 illustrates a circuit diagram of selected components of an example power converter 26, in accordance with embodiments of the present disclosure. In some embodiments, power converter 26 depicted in FIGURE 5 may implement all or a portion of power converter 26 described with respect to FIGURE 4. As shown in FIGURE 5, power converter 26 may receive at its input a voltage V_{SUPPLY} (e.g., provided by power supply 10) at input terminals, including a positive input terminal and a negative input terminal which may be coupled to a ground voltage, and may generate at its output a differential output voltage V_{OUT} . Power converter 26 may comprise a power inductor 62 and plurality of switches 51-60. Power inductor 62 may comprise any passive two-terminal electrical component which resists changes in electrical current passing through it and such that when electrical current flowing through it changes, a time-varying magnetic field induces a voltage in power inductor 62, in accordance with Faraday's law of electromagnetic induction, which opposes the change in current that created the magnetic field.

Each switch 51-60 may comprise any suitable device, system, or apparatus for making a connection in an electric circuit when the switch is enabled (e.g., closed or on) and breaking the connection when the switch is disabled (e.g., open or off) in response to a control signal received by the switch. For purposes of clarity and exposition, control signals for switches 51-60 (e.g., control signals communicated from converter controller 24) are not depicted although such control signals would be present to selectively enable and disable switches 51-60. In some embodiments, a switch 51-60 may comprise an n-type metal-oxide-semiconductor field-effect transistor. Switch 51 may be coupled between the positive input terminal and a first terminal of power inductor 62. Switch 52

may be coupled between a second terminal of power inductor 62 and ground. Switch 53 may be coupled between a positive terminal of the output of power converter 26 and a second terminal of power inductor 62. Switch 54 may be coupled between a negative terminal of the output of power converter 26 and the first terminal of power inductor 62. Switch 55 may be coupled between a negative terminal of the output of power converter 26 and the second terminal of power inductor 62. Switch 56 may be coupled between a positive terminal of the output of power converter 26 and the first terminal of power inductor 62. Switch 57 may be coupled between the ground voltage and the first terminal of power inductor 62. Switch 58 may be coupled between the negative terminal of the output of power converter 26 and the ground voltage. Switch 59 may be coupled between the positive terminal of the output of power converter 26 and the ground voltage. Switch 60 may be coupled between the positive input terminal and the second terminal of power inductor 62.

In addition to switches 51-60 and power inductor 62, power converter 26 may include a first output capacitor 66 coupled between the positive terminal of the output of power converter 26 and the ground voltage and a second output capacitor 68 coupled between the negative terminal of the output of power converter 26 and the ground voltage. Each output capacitor 66 and 68 may comprise a passive two-terminal electrical component used to store energy electrostatically in an electric field, and may generate a current in response to a time-varying voltage across the capacitor.

As shown in FIGURE 5, power converter 26 may in some embodiments comprise a linear amplifier 70. Functionality of power converter 26 is described in greater detail elsewhere in this disclosure for those embodiments including linear amplifier 70.

As described above, a power converter 26 may operate in a plurality of different operational modes, and may sequentially operate in a number of switch configurations under each operational mode. The plurality of modes may include, without limitation, a single-ended boost mode, a differential-output buck-boost mode, a differential-output buck mode, and a low-voltage mode.

Power converter 26 may operate in a single-ended boost mode when output voltage V_{OUT} has a magnitude significantly larger than the supply voltage V_{SUPPLY} (e.g., $|V_{OUT}| > V_{SUPPLY} = 2V$). FIGURE 6 illustrates a table setting forth switch configurations

of power converter 26 when operating in the single-ended boost mode, in accordance with embodiments of the present disclosure. As shown in FIGURE 6, when output voltage V_{OUT} is positive, and during a charging phase T1 of power converter 26, converter controller 24 may enable switches 51, 52, and 58 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 7. In such switch configuration, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and ground. When output voltage V_{OUT} is positive, and during a discharge phase T2 of power converter 26, converter controller 24 may enable switches 51, 53, and 58 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 8. In such switch configuration, power inductor 62 may be discharged, with charge transferred from the power supply (e.g., power supply 10) to the positive terminal of the output of power converter 26. Similarly, when output voltage V_{OUT} is negative, and during the charging phase T1 of power converter 26, converter controller 24 may enable switches 51, 52, and 59 of power converter 26, wherein in accordance with such switch configuration, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and ground. In addition, when output voltage V_{OUT} is negative, and during the discharge phase T2 of power converter 26, converter controller 24 may enable switches 51, 55, and 59 of power converter 26, wherein in accordance with such switch configuration, power inductor 62 may be discharged, with charge transferred from the power supply (e.g., power supply 10) to the negative terminal of the output of power converter 26.

Notably, in the boost configuration, one of either of the terminals of the output of power converter 26 remains grounded in order to provide for operation in the boost mode, thus allowing power converter 26 to act as a boost converter when in the boost mode.

In some embodiments, it may be desirable to operate in a continuous current mode (CCM) as opposed to a discontinuous current mode (DCM) when operating power converter 26 in the single-ended boost mode. This preference is because a CCM boost converter may have lower root-means-square (e.g., ripple) currents compared to a corresponding DCM boost converter.

For an input voltage signal V_I to loop filter 22, loop filter 22 may generate a target current signal I_{TGT} as the controller input signal which may be given by $I_{TGT} = V_I/R_{OUT}$,

where R_{OUT} is an impedance of a load at the output of power converter 26. A duration of charging phase T1 may be given by $T1 = D \times TT$, where D is a unitless variable given by $D = 1 - (V_{SUPPLY}/V_I)$ and TT is a switching period of power converter 26 which is the sum of the durations of the charging phase T1 and the transfer phase T2 (e.g., $TT = T1 + T2$). A change in power inductor current I_L occurring during charging phase T1 may be given by $\Delta I_L = T1 \times (V_{SUPPLY}/L)$ where L is an inductance of power inductor 62. A minimum inductor current I_{min} may be given by:

$$I_{min} = [2 \times TT \times I_{TGT} \times (V_{SUPPLY} - V_I)/L - \Delta I_L^2] / 2 \times \Delta I_L$$

and a peak current I_{pk} for inductor current I_L may be given as $I_{pk} = I_{min} + \Delta I_L$.

Power converter 26 may operate in a differential-output buck-boost mode when output voltage V_{OUT} has a magnitude lower than that for which the single-ended boost mode is appropriate (e.g., $|V_{OUT}| < V_{SUPPLY} + 2V$) but higher than a particular threshold magnitude (e.g., $|V_{OUT}| > 3V$) for which the duration of a charging phase T1 becomes too small to operate power converter 26 in a buck-boost mode. FIGURE 9 illustrates a table setting forth switch configurations of power converter 26 when operating in the differential-output buck-boost mode, in accordance with embodiments of the present disclosure. As shown in FIGURE 9, when output voltage V_{OUT} is positive, and during a charging phase T1 of power converter 26, converter controller 24 may enable switches 51 and 52 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 10. In such switch configuration, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and ground. When output voltage V_{OUT} is positive, and during a discharge phase T2 of power converter 26, converter controller 24 may enable switches 53 and 54 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 11. In such switch configuration, power inductor 62 may be discharged, with charge transferred from the negative terminal of the output of power converter 26 to the positive terminal of the output of power converter 26. Similarly, when output voltage V_{OUT} is negative, and during the charging phase T1 of power converter 26, converter controller 24 may enable switches 51 and 52 of power converter 26, wherein in accordance with such switch configuration, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and ground. In

addition, when output voltage V_{OUT} is negative, and during the discharge phase T2 of power converter 26, converter controller 24 may enable switches 55 and 56 of power converter 26, wherein in accordance with such switch configuration, power inductor 62 may be discharged, with charge transferred from the positive terminal of the output of power converter 26 to the negative terminal of the output of power converter 26.

Thus, in the differential-output buck-boost mode, power inductor 62 may be charged from V_{SUPPLY} to ground during charging phases T1, and in discharging phases T2, power inductor 62 may be coupled across the output terminals of a load at the output of power converter 26 in order to discharge power inductor 62 and create a differential output. Coupling power inductor 62 across the output terminals in a differential output fashion may lead to a greater charge differential between capacitors 66 and 68 than would be in a single-ended configuration (e.g., with one of the output terminals grounded). Thus, lower power inductor peak currents may be required to achieve the same output current.

Within the output voltage range of operation for the differential-output buck-boost mode, power converter 26 may operate in CCM for larger output voltages (e.g., $7V < V_{OUT} < V_{SUPPLY} + 2V$) and DCM for smaller output voltages (e.g., $3V < V_{OUT} < 7V$). In DCM, peak current I_{pk} of power inductor 62 may be given by:

$$I_{pk} = \sqrt{\frac{2 \times I_{TGT} \times V_{OUT} \times TT}{L}}$$

where TT is a switching period of power converter 26.

In CCM, a duration of charging phase T1 may be given by $T1 = D \times TT$, where D is a unitless variable given by $D = V_{OUT}/(V_{OUT} + V_{SUPPLY})$ and TT is a switching period of power converter 26 which is the sum of the durations of the charging phase T1 and the transfer phase T2 (e.g., $TT = T1 + T2$). A change in power inductor current I_L occurring during charging phase T1 may be given by $\Delta I_L = T1 \times (V_{SUPPLY}/L)$. A minimum inductor current I_{min} may be given by:

$$I_{min} = [I_{OUT} \times TT \times V_{OUT}/L - \Delta I_L^2/2] / \Delta I_L$$

and a peak current I_{pk} for inductor current I_L may be given as $I_{pk} = I_{min} + \Delta I_L$.

Power converter 26 may operate in a differential-output buck mode when output voltage V_{OUT} has a magnitude lower than that for which the duration of a charging phase

T1 becomes too small to operate power converter in a buck-boost mode (e.g., $|V_{OUT}| < 3V$) and a magnitude higher than for which the duration of a charging phase T1 becomes too small (e.g., $|V_{OUT}| > 1V$) to operate power converter 26 in a buck mode. FIGURE 12 illustrates a table setting forth switch configurations of power converter 26 when operating in the differential-output buck-boost mode, in accordance with embodiments of the present disclosure. As shown in FIGURE 12, in the differential-output buck mode, switch configurations may not only be based on the polarity of output voltage V_{OUT} , but also on whether the common-mode voltage of the positive output terminal and the negative output terminal of power converter 26 is to be increased or decreased to regulate the common-mode voltage at a desired level, as shown in the column with the heading “CM” in FIGURE 12. For example, in some embodiments, converter controller 24 may control switches of power converter 26 in order to regulate the common mode to a voltage associated with switched-mode amplifier 20. In some embodiments, the voltage may comprise one-half of the supply voltage V_{SUPPLY} .

As shown in FIGURE 12, during a charging phase T1 of power converter 26, when output voltage V_{OUT} is positive and the common-mode voltage of the output terminals is to be increased, converter controller 24 may enable switches 51 and 53 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 13. In such switch configuration, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and the positive terminal of the output of power converter 26, thus generating a positive output voltage V_{OUT} and increasing the common-mode voltage by increasing the electrical charge on capacitor 66. On the other hand, during a charging phase T1 of power converter 26, when output voltage V_{OUT} is positive and the common-mode voltage of the output terminals is to be decreased, converter controller 24 may enable switches 52 and 54 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 14. In such switch configuration, power inductor 62 may be charged via a current flowing between the negative terminal of the output of power converter 26 and ground, thus generating a positive output voltage V_{OUT} and decreasing common-mode voltage by decreasing the electrical charge on capacitor 68. During a discharge phase T2 of power converter 26, when target current I_{TGT} is positive and regardless of whether the

common-mode voltage of the output terminals is to be increased or decreased, converter controller 24 may enable switches 53 and 54 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 15. In such switch configuration, power inductor 62 may be discharged, with charge transferred from the negative terminal of the output of power converter 26 to the positive terminal of the output of power converter 26 in order to provide a positive output voltage V_{OUT} while maintaining the same common-mode voltage.

Similarly, during a charging phase T1 of power converter 26, when output voltage V_{OUT} is negative and the common-mode voltage of the output terminals is to be increased, converter controller 24 may enable switches 51 and 55 of power converter 26. In such switch configuration, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and the negative terminal of the output of power converter 26, thus generating a negative output voltage V_{OUT} and increasing the common-mode voltage by increasing the electrical charge on capacitor 68. On the other hand, during a charging phase T1 of power converter 26, when output voltage V_{OUT} is negative and the common-mode voltage of the output terminals is to be decreased, converter controller 24 may enable switches 52 and 56 of power converter 26. In such switch configuration, power inductor 62 may be charged via a current flowing between the positive terminal of the output of power converter 26 and ground, thus generating a negative output voltage V_{OUT} and decreasing common-mode voltage by decreasing the electrical charge on capacitor 66. During a discharge phase T2 of power converter 26, when output voltage V_{OUT} is negative and regardless of whether the common-mode voltage of the output terminals is to be increased or decreased, converter controller 24 may enable switches 55 and 56 of power converter 26. In such switch configuration, power inductor 62 may be discharged, with charge transferred from the positive terminal of the output of power converter 26 to the negative terminal of the output of power converter 26 in order to provide a negative output voltage V_{OUT} while maintaining the same common-mode voltage.

Thus, during charging phases T1, converter controller 24 may cause power converter 26 to couple a capacitor 66 or 68 to supply voltage V_{SUPPLY} or ground to increase or decrease the total amount of charge in capacitors 66 and 68 in order to

regulate common-mode voltage of the output terminals. On the other hand, discharge phases T2 of converter controller 24 may cause power converter 26 to couple a power inductor 62 across the output terminals, which may redistribute charge between capacitors 66 and 68. Accordingly, in the differential-output buck mode, power converter 26 uses common-mode voltage at the output to create differential output voltage V_{OUT} , as the duration of charging phase T1 may determine the common mode voltage and differential voltage V_{OUT} while the duration of discharge phase T2 may additionally determine the differential voltage V_{OUT} . As compared to other modes of operation, the differential-output buck mode provides for efficient charge transfer as charge is pushed to an output capacitor 66 or 68 during charging phase T1 and redistributed between output capacitors 66 and 68 during discharge phase T2. Because of such charge-transfer scheme, lower peak currents through power inductor 62 may be necessary to transfer charge as compared to other modes. Also, root-mean-square current through switch 51 may be reduced as it is not exercised as much as it is in other modes of operation, which may minimize power dissipation of switch 51. Common-mode voltage at the output terminals may also be well-controlled, as common-mode control is achieved by coupling an output capacitor 66 or 68 to supply voltage V_{SUPPLY} or ground through power inductor 62.

When operating in the differential-output buck mode, power converter 26 may typically operate in DCM, unless power inductor 62 has a very high inductance (e.g., greater than 500 nH). In DCM, peak current I_{pk} of power inductor 62 may be given by:

$$I_{pk} = \sqrt{\frac{2 \times I_{TCT} \times V_{OUT} \times (V_{SUPPLY} - V_{OUT}) \times TT}{L \times V_{SUPPLY}}}$$

where TT is a switching period of power converter 26.

In CCM, a duration of charging phase T1 may be given by $T1 = D \times TT$, where D is a unitless variable given by $D = V_{OUT}/(V_{OUT} + V_{SUPPLY})$ and TT is a switching period of power converter 26 which is the sum of the durations of the charging phase T1 and the transfer phase T2 (e.g., $TT = T1 + T2$). A change in power inductor current I_L occurring during charging phase T1 may be given by $\Delta I_L = T1 \times (V_{SUPPLY} - V_{OUT})/2L$. A minimum inductor current I_{min} may be given by:

$$I_{min} = [I_{OUT} \times TT \times (V_{SUPPLY} - V_{OUT}) \times TT/(L \times V_{SUPPLY}) - \Delta I_L^2/2] / \Delta I_L$$

and a peak current I_{pk} for inductor current I_L may be given as $I_{pk} = I_{min} + \Delta I_L$.

Power converter 26 may operate in a low-voltage mode in order to allow output voltage V_{OUT} to cross zero, as the differential-output buck mode and operational modes discussed above may not be capable of effectuating a polarity change in output voltage V_{OUT} . Accordingly, when output voltage V_{OUT} has a magnitude lower than a particular threshold (e.g., $|V_{OUT}| < 1V$), power converter 26 may operate in the low-voltage mode. As described below, the low-voltage mode may be implemented in one of a plurality of ways, including a single-ended buck mode and a linear amplifier mode.

Power converter 26 may transition to operation in a differential-output turn-around mode from the differential-output buck mode when, while operating in the differential-output buck mode, output voltage V_{OUT} has a polarity opposite that of a target voltage V_{TGT} for output voltage V_{OUT} wherein target voltage V_{TGT} corresponds to input signal INPUT. In such a situation, output voltage V_{OUT} may need to effectively change polarity in a quick fashion, which may not be possible using any of the operational modes described above. FIGURE 16 illustrates a table setting forth switch configurations of power converter 26 when operating in the differential-output turn-around mode, in accordance with embodiments of the present disclosure. As shown in FIGURE 16, in the differential-output turn-around mode, switch configurations may not only be based on the polarities of output voltage V_{OUT} and target voltage V_{TGT} , but also on whether the common-mode voltage of the positive output terminal and the negative output terminal of power converter 26 is to be increased or decreased to regulate the common-mode voltage at a desired level, as shown in the column with the heading “CM” in FIGURE 16. For example, in some embodiments, converter controller 24 may control switches of power converter 26 in order to regulate the common mode to a voltage associated with switched-mode amplifier 20. In some embodiments, the voltage may comprise one-half of the supply voltage V_{SUPPLY} .

As shown in FIGURE 16, during a charging phase T1 of power converter 26, when output voltage V_{OUT} is negative, target voltage V_{TGT} is positive (meaning output voltage V_{OUT} needs to switch from a negative to a positive polarity), and the common-mode voltage of the output terminals is to be increased, converter controller 24 may enable switches 51 and 53 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 17. In such switch configuration,

power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and the positive terminal of the output of power converter 26, thus generating an increasing output voltage V_{OUT} and increasing the common-mode voltage by increasing the electrical charge on capacitor 66. On the other hand, during a charging phase T1 of power converter 26, when output voltage V_{OUT} is negative, target voltage V_{TGT} is positive (meaning output voltage V_{OUT} needs to switch from a negative to a positive polarity), and the common-mode voltage of the output terminals is to be decreased, converter controller 24 may enable switches 52 and 54 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 18. In such switch configuration, power inductor 62 may be charged via a current flowing between the negative terminal of the output of power converter 26 and ground, thus generating an increasing output voltage V_{OUT} and decreasing common-mode voltage by decreasing the electrical charge on capacitor 68. During a discharge phase T2 of power converter 26, when output voltage V_{OUT} is negative, target voltage V_{TGT} is positive (meaning output voltage V_{OUT} needs to switch from a negative to a positive polarity), and regardless of whether the common-mode voltage of the output terminals is to be increased or decreased, converter controller 24 may enable switches 53 and 57 of power converter 26, with such switch configuration resulting in the equivalent circuit depicted in FIGURE 19. In such switch configuration, power inductor 62 may be discharged, with charge transferred from the ground to the positive terminal of the output of power converter 26 in order to provide an increasing output voltage V_{OUT} .

Similarly, during a charging phase T1 of power converter 26, when output voltage V_{OUT} is positive, target voltage V_{TGT} is negative (meaning output voltage V_{OUT} needs to switch from a positive to a negative polarity), and the common-mode voltage of the output terminals is to be increased, converter controller 24 may enable switches 51 and 55 of power converter 26. In such switch configuration, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and the negative terminal of the output of power converter 26, thus generating a decreasing output voltage V_{OUT} and increasing the common-mode voltage by increasing the electrical charge on capacitor 68. On the other hand, during a charging phase T1 of power converter 26, when output voltage V_{OUT} is positive, target voltage V_{TGT} is negative (meaning output voltage

V_{OUT} needs to switch from a positive to a negative polarity), and the common-mode voltage of the output terminals is to be decreased, converter controller 24 may enable switches 52 and 56 of power converter 26. In such switch configuration, power inductor 62 may be charged via a current flowing between the positive terminal of the output of power converter 26 and ground, thus generating a decreasing output voltage V_{OUT} and decreasing common-mode voltage by decreasing the electrical charge on capacitor 66. During a discharge phase T2 of power converter 26, voltage V_{OUT} is positive, target voltage V_{TGT} is negative (meaning output voltage V_{OUT} needs to switch from a positive to a negative polarity), and regardless of whether the common-mode voltage of the output terminals is to be increased or decreased, converter controller 24 may enable switches 55 and 57 of power converter 26. In such switch configuration, power inductor 62 may be discharged, with charge transferred from the ground to the negative terminal of the output of power converter 26 in order to provide a decreasing output voltage V_{OUT} .

Thus, during charging phases T1, converter controller 24 may cause power converter 26 to couple a capacitor 66 or 68 to supply voltage V_{SUPPLY} or ground to increase or decrease the total amount of charge in capacitors 66 and 68 in order to regulate common-mode voltage of the output terminals. On the other hand, discharge phases T2 of converter controller 24 may cause power converter 26 to couple a power inductor 62 between the ground and one of the output terminals, to increase or decrease output voltage V_{OUT} . Accordingly, in the differential-output turn-around mode, power converter 26 uses common-mode voltage at the output to create differential output voltage V_{OUT} , as the duration of charging phase T1 may determine the common mode voltage and differential voltage V_{OUT} while the duration of discharge phase T2 may additionally determine the differential voltage V_{OUT} .

FIGURE 20 illustrates a table setting forth switch configurations of power converter 26 when operating in the single-ended buck mode, in accordance with embodiments of the present disclosure. As shown in FIGURE 20, when target voltage V_{TGT} is positive and the common-mode voltage of the output terminals is to be increased, power converter 26 may have a charging phase T1 in which converter controller 24 enables switches 51 and 53 (as shown in the equivalent circuit depicted in FIGURE 21), followed immediately by a discharge phase T2 in which converter controller 24 enables

switches 54 and 60 of power converter 26 (as shown in the equivalent circuit depicted in FIGURE 22). In such charging phase T1, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and the positive terminal of the output of power converter 26, thus generating an increasing output voltage V_{OUT} and increasing the common-mode voltage by increasing the electrical charge on capacitor 66. In such discharge phase T2, power inductor 62 may be discharged, with charge transferred from the negative terminal of the output of power converter 26 to the power supply in order to provide an increasing output voltage V_{OUT} . Discharge phase T2 may have the effect of decreasing the common-mode voltage, but the net effect of charging phase T1 and discharge phase T2 may be an increase in common-mode voltage.

Also as shown in FIGURE 20, when target voltage V_{TGT} is positive and the common-mode voltage of the output terminals is to be decreased, power converter 26 may have a charging phase T1 in which converter controller 24 enables switches 52 and 54 (as shown in the equivalent circuit depicted in FIGURE 23), followed immediately by a discharge phase T2 in which converter controller 24 enables switches 53 and 57 of power converter 26 (as shown in the equivalent circuit depicted in FIGURE 24). In such charging phase T1, power inductor 62 may be charged via a current flowing between the negative terminal of the output of power converter 26 and ground, thus generating an increasing output voltage V_{OUT} and decreasing common-mode voltage by decreasing the electrical charge on capacitor 68. In such discharge phase T2, power inductor 62 may be discharged, with charge transferred from the ground to the positive terminal of the output of power converter 26 in order to provide an increasing output voltage V_{OUT} . Discharge phase T2 may have the effect of increasing the common-mode voltage, but the net effect of charging phase T1 and discharge phase T2 may be a decrease in common-mode voltage.

Similarly, when target voltage V_{TGT} is positive and the common-mode voltage of the output terminals is to be increased, power converter 26 may have a charging phase T1 in which converter controller 24 enables switches 51 and 55, followed immediately by a discharge phase T2 in which converter controller 24 enables switches 56 and 60 of power converter 26. In such charging phase T1, power inductor 62 may be charged via a current flowing between the power supply (e.g., power supply 10) and the negative terminal of

the output of power converter 26, thus generating a decreasing output voltage V_{OUT} and increasing the common-mode voltage by increasing the electrical charge on capacitor 68. In such discharge phase T2, power inductor 62 may be discharged, with charge transferred from the positive terminal of the output of power converter 26 to the power supply in order to provide a decreasing output voltage V_{OUT} . Discharge phase T2 may have the effect of decreasing the common-mode voltage, but the net effect of charging phase T1 and discharge phase T2 may be an increase in common-mode voltage.

On the other hand, when target voltage V_{TGT} is positive and the common-mode voltage of the output terminals is to be increased, power converter 26 may have a charging phase T1 in which converter controller 24 enables switches 52 and 56, followed immediately by a discharge phase T2 in which converter controller 24 enables switches 55 and 57 of power converter 26. In such charging phase T1, power inductor 62 may be charged via a current flowing between the positive terminal of the output of power converter 26 and ground, thus generating a decreasing output voltage V_{OUT} and decreasing common-mode voltage by decreasing the electrical charge on capacitor 66. In such discharge phase T2, power inductor 62 may be discharged, with charge transferred from the ground to the negative terminal of the output of power converter 26 in order to provide a decreasing output voltage V_{OUT} . Discharge phase T2 may have the effect of increasing the common-mode voltage, but the net effect of charging phase T1 and discharge phase T2 may be a decrease in common-mode voltage.

In the linear amplifier mode, linear amplifier 70 may receive a digital linear amplifier input signal from converter controller 24, loop filter 22, or elsewhere within switched mode amplifier 20. For example, in some embodiments, digital linear amplifier input signal may comprise an output of a quantizer of loop filter 22. To provide for fine resolution in the low-voltage mode of output voltages at magnitudes lower than the operational range of the differential-output buck mode, power converter 26 may operate in a linear amplifier mode, in which linear amplifier 70 of FIGURE 5, operating in effect as a digital-to-analog converter (DAC), may be used to convert the digital linear amplifier control signal (which may be indicative of a desired output current I_{OUT}) communicated from loop filter 22, converter controller 24, or elsewhere within switched mode amplifier into an analog current driven to a load coupled between output terminals of power

converter 26. Linear amplifier 70, which is shown as a current source in FIGURE 5, may comprise any system, device, or apparatus configured to generate a current in response to an input signal.

An example embodiment for linear amplifier 70 is depicted in FIGURE 25, in which linear amplifier 70 is embodied as a current-mode quadrant DAC having variable current sources 70A, 70B, 70C, and 70D. In the linear amplifier mode, when output voltage V_{OUT} is positive, current sources 70A and 70B may be enabled to deliver a current to a load at the output of power converter 26 with a magnitude to generate the desired positive output voltage V_{OUT} . Conversely, when output voltage V_{OUT} is negative, current sources 70C and 70D may be enabled to deliver a current to a load at the output of power converter 26 with a magnitude to generate the desired negative output voltage V_{OUT} .

Another example embodiment for linear amplifier 70 is shown in FIGURE 26, in which linear amplifier 70 is embodied as a current-mode hemispherical DAC having variable current sources 70E and 70F and switches 71A, 71B, 71C, and 71D. In the linear amplifier mode, when output voltage V_{OUT} is positive, switches 71A and 71B may be enabled (e.g., closed or on) and switches 71C and 71D may be disabled (e.g., open or off) to deliver a current to a load at the output of power converter 26 with a magnitude to generate the desired positive output voltage V_{OUT} . Conversely, when output voltage V_{OUT} is negative, switches 71C and 71D may be enabled (e.g., closed or on) and switches 71A and 71B may be disabled (e.g., open or off) to deliver a current to a load at the output of power converter 26 with a magnitude to generate the desired negative output voltage V_{OUT} .

In some embodiments, converter controller 24 may control switches of power converter 26 such that the switches perform synchronous rectification, wherein all switches of power converter 26 are controlled (e.g., disabled if inductor current I_L decrease to zero) in order to prevent inductor current I_L from decreasing below zero. In other embodiments, power converter 26 may include a diode (e.g., with anode terminal coupled to power inductor 62 and cathode terminal coupled to switches 53 and 55) in order to prevent inductor current I_L from decreasing below zero.

FIGURE 27 illustrates a circuit diagram of selected components of another example power converter 26A, in accordance with embodiments of the present disclosure. Power converter 26A may, in some embodiments, be used as an alternative to power converter 26 depicted in FIGURE 5, and may in many respects, be mathematically equivalent to power converter 26 depicted in FIGURE 5 and/or operate in a similar manner to power converter 26 depicted in FIGURE 5. As shown in FIGURE 27, power converter 26A may receive at its input a voltage V_{SUPPLY} (e.g., provided by power supply 10) at input terminals, including a positive input terminal and a negative input terminal which may be coupled to a ground voltage, and may generate at its output a differential output voltage V_{OUT} . Power converter 26A may comprise a power inductor 62A, and a plurality of switches 51A-58A. Although not shown in FIGURE 27, power converter 26A may also include across its output terminals a linear amplifier identical or similar to linear amplifier 70 of power amplifier 26. Power inductor 62A may comprise any passive two-terminal electrical component which resists changes in electrical current passing through it and such that when electrical current flowing through it changes, a time-varying magnetic field induces a voltage in power inductor 62A, in accordance with Faraday's law of electromagnetic induction, which opposes the change in current that created the magnetic field.

Each switch 51A-58A may comprise any suitable device, system, or apparatus for making a connection in an electric circuit when the switch is enabled (e.g., closed or on) and breaking the connection when the switch is disabled (e.g., open or off) in response to a control signal received by the switch. For purposes of clarity and exposition, control signals for switches 51A-58A (e.g., control signals communicated from converter controller 24) are not depicted although such control signals would be present to selectively enable and disable switches 51A-58A. In some embodiments, a switch 51A-58A may comprise an n-type metal-oxide-semiconductor field-effect transistor. Switch 51A may be coupled between the positive input terminal and a first terminal of power inductor 62A. Switch 52A may be coupled between the positive input terminal and a second terminal of power inductor 62A. Switch 53A may be coupled between the first terminal of power inductor 62A and the ground voltage. Switch 54A may be coupled between the second terminal of power inductor 62A and the ground voltage. Switch 55A

may be coupled between the first terminal of power inductor 62A and a negative terminal of the output of power converter 26A. Switch 56A may be coupled between the second terminal of power inductor 62A and a positive terminal of the output of power converter 26A. Switch 57A may be coupled between the negative terminal of the output of power converter 26A and the ground voltage. Switch 58A may be coupled between the positive terminal of the output of power converter 26A and the ground voltage.

In addition to switches 51A-58A and power inductor 62A, power converter 26A may include a first output capacitor 66A coupled between the positive terminal of the output of power converter 26A and the ground voltage and a second output capacitor 68A coupled between the negative terminal of the output of power converter 26A and the ground voltage. Each output capacitor 66A and 68A may comprise a passive two-terminal electrical component used to store energy electrostatically in an electric field, and may generate a current in response to a time-varying voltage across the capacitor.

FIGURE 28 illustrates a graph of an example output voltage V_{OUT} having a sinusoidal waveform, the graph indicating example ranges for operation in the various operational modes of power converter 26. Thus, for a full-scale sinusoidal signal, power converter 26 may sequentially operate in the low-voltage mode (e.g., single-ended buck, or linear amplifier mode), the differential-output buck mode, the differential output buck-boost mode, the single-ended boost mode, the differential output buck-boost mode, the differential-output buck mode, and the low-voltage mode (e.g., single-ended buck, or linear amplifier mode) for each half-cycle of output voltage V_{OUT} . Although not shown in FIGURE 28, in some embodiments, while operating in the differential-output buck mode, power converter 26 may switch to operation in the differential-output turn-around mode, in order to change a signal polarity of the output voltage V_{OUT} in response to a target voltage corresponding to input signal INPUT having an opposite polarity of output voltage V_{OUT} . In addition, in these and other embodiments, the low-voltage mode may employ the differential-output turn-around mode or a similar mode (e.g., instead of the single-ended buck or linear amplifier mode) in order to operate at lower voltage magnitudes and change the polarity of output voltage V_{OUT} .

FIGURE 29 illustrates a block diagram of selected components of an example loop filter 22, in accordance with embodiments of the present disclosure. In some

embodiments, loop filter 22 depicted in FIGURE 29 may implement all or a portion of loop filter 22 described with respect to FIGURE 4.

Loop filter 22 may comprise a delta-sigma filter or similar filter which may have the function of moving quantization errors outside the audio band. Loop filter 22 may include an input summer 73 for generating a difference between an input signal (e.g., an analog voltage signal V_{IN}) and a feedback signal (e.g., output voltage V_{OUT}), and one or more integrator stages 74, such that loop filter 22 operates as analog filter of an error signal equal to the difference between the input signal and the feedback signal, and generates, at the output of output summer 75 a filtered analog signal to analog-to-digital converter (ADC) 78 based on the input signal and the feedback signal. The inputs to output summer 75 may include the input signal as modified by a feed-forward gain coefficient K_F applied by a gain element 76, the outputs of individual integrator stages 74 as each is modified by a respective integrator gain coefficient $K_1, K_2, \dots, K_N$ applied by gain elements 76, and the output of a feedback digital-to-analog converter 80 as modified by a delay-compensation coefficient K_F applied by a gain element 76 in order to compensate for excess loop delay of loop filter 22.

ADC 78 may comprise any system, device, or apparatus for converting the analog output signal generated by loop filter 22 (e.g., the output of output summer 75) into an equivalent digital signal, which, in some embodiments, may represent a desired output voltage to be generated at the output of switched mode amplifier 20 (e.g., across the terminals labeled V_{OUT} in FIGURE 5). Such digital signal or a derivative thereof (e.g., a current signal based on the input signal) may be communicated to converter controller 24, such that converter controller 24 may control switches of power converter 26 in accordance with a selected mode corresponding to such quantized integrated error.

DAC 80 may comprise any suitable system, device, or apparatus configured to convert the digital signal into an equivalent analog feedback signal.

FIGURE 30 illustrates a block diagram of selected components of an example converter controller 24A, in accordance with embodiments of the present disclosure. In some embodiments, converter controller 24A depicted in FIGURE 30 may implement all or a portion of converter controller 24 described with respect to FIGURE 4. In the embodiments represented by FIGURE 30 the controller input signal received by converter

controller 24A is a target current signal I_{TGT} . As shown in FIGURE 30, converter controller 24A may implement an ADC 82, a mode determiner 84, a peak current computation block 86, a DAC 88, a peak current detector 90, a clock 92, a phase determiner 94, and a switch controller 96.

ADC 82 may comprise any system, device, or apparatus configured to convert analog output voltage V_{OUT} (or a derivative thereof) into an equivalent digital signal V_{OUT_DIG} .

Mode determiner 84 may comprise any system, device, or apparatus configured to select a mode of operation from a plurality of modes of operation (e.g., single-ended boost mode, differential-output buck-boost mode, differential-output buck mode, low-voltage mode, etc.) based on digital output voltage signal V_{OUT_DIG} (or another signal indicative of output voltage V_{OUT}) and/or a digital input voltage signal V_{L_DIG} indicative of input voltage V_{IN} . For example, mode determiner 82 may select the mode of operation based upon a voltage range of digital output voltage signal V_{OUT_DIG} , digital input voltage signal V_{L_DIG} , or a signal derivative or indicative thereof, such as analog feedback voltage V_{FB} described in greater detail below with respect to FIGURE 31 (e.g., select single-ended boost mode for $|V_{FB}| > 14V$, select differential-output buck-boost mode for $3V < |V_{FB}| < 14V$, select differential-output buck mode for $1V < |V_{FB}| < 3V$, and select the low-voltage mode for $|V_I| < 1V$).

Peak current computation block 86 may comprise any system, device, or apparatus configured to compute a peak current I_{pk} to be driven through power inductor 62 during a switching cycle of power converter 26. Such peak current I_{pk} may be calculated based on the selected mode of operation, digital output voltage signal V_{OUT_DIG} (or another signal indicative of output voltage V_{OUT}), supply voltage V_{SUPPLY} , output current I_{OUT} (or another signal indicative of output current I_{OUT}), and/or target current I_{TGT} in accordance with the various equations for peak current I_{pk} set forth above.

DAC 88 may comprise any system, device, or apparatus configured to convert a digital signal generated by peak current computation block 106 indicative of peak current I_{pk} into an equivalent analog peak current signal I_{pk} .

Peak current detector 90 may comprise any system, device, or apparatus configured to compare power inductor current I_L to the analog peak current signal I_{pk} and

generate an output signal indicative of the comparison, thus providing an indication for when power inductor current I_L has reached its desired peak current. Power inductor current I_L reaching its desired peak current may indicate the end of a charging phase T1 and beginning of a transfer phase T2 of power converter 26.

Clock 92 may comprise any system, device, or apparatus configured to generate a periodic timing signal indicative of an occurrence of or within a switching cycle of power converter 26. For example, a zero crossing, edge, or other characteristic of a waveform generated by clock 92 may indicate the beginning of a charging phase T1 of power converter 26.

Phase determiner 94 may comprise any system, device, or apparatus configured to, based on the outputs of peak current detector 90 and clock 92, determine which phase (e.g., charging phase T1 or discharge phase T2) power converter 26 is to operate.

Switch controller 96 may comprise any system, device, or apparatus configured to, based on the mode of operation, phase, polarity of digital input signal V_{L_DIG} (or another signal indicative of input voltage V_{IN} or output voltage V_{OUT}), and (for the differential-output buck mode of power converter 26) a common-mode voltage V_{CM} of the output terminals of power converter 26, generate switch control signals for controlling the switches of power converter 26.

Thus, during each switching cycle for converter controller 24A, converter controller 24A may select a mode of operation based on input voltage V_{IN} and output voltage V_{OUT} , calculate a peak current I_{pk} based on input voltage V_{IN} , output voltage V_{OUT} , target current signal I_{TGT} , and/or output current I_{OUT} , and use information regarding the selected mode and the phase of power converter 26 to select a switch configuration to control the switches of power converter 26. In alternative embodiments, rather than operating as a peak current system as depicted in FIGURE 28, converter controller 24 may operate as a time-based system based on measurements of supply voltage V_{SUPPLY} , output voltage V_{OUT} , and output current I_{OUT} .

Thus, in the various embodiments disclosed herein, the choice of sequence for switches of power converter 26 may be made consistent with a desired change in output voltage V_{OUT} . By repeatedly increasing and decreasing output voltage V_{OUT} in small steps, output voltage V_{OUT} may be made to follow, on average, the desired audio signal.

Accordingly, quantization error present in output voltage V_{OUT} may be moved outside the audio band in a manner similar to a delta-sigma modulator.

FIGURE 31 illustrates a block and circuit diagram of selected components of an example switched mode amplifier 20B including an impedance estimator 23, in accordance with embodiments of the present disclosure. In the embodiments represented by FIGURE 31, switched mode amplifier 20B may operate as voltage feedback loop (e.g., a delta-sigma modulator) responsive to input voltage V_I and output voltage V_{OUT} . Switched mode amplifier 20B may be similar to switched mode amplifier 20 of FIGURE 4, except that switched mode amplifier 20B may also include impedance estimator 23 and a current calculator 21 interfaced between loop filter 22 and converter controller 24, and a differential amplifier 25 and a current sensor 27. Loop filter 22, converter controller 24, and power converter 26 may respectively comprise any suitable loop filters, converter controllers, and power converters, including without limitation the various loop filters, converter controllers, and power converters disclosed herein. In the embodiments represented by FIGURE 31, loop filter 22 may receive an input voltage V_I as its input and generate, based on input voltage V_I and an analog voltage feedback signal V_{FB} , a target voltage signal V_{TGT} representative of a voltage to be applied as output voltage V_{OUT} .

Impedance estimator 23 may comprise any system, device, or apparatus for estimating an impedance of a load at the output of switched mode amplifier 20B (e.g., across the terminals labeled V_{OUT} in FIGURE 31). Impedance estimator 23 may estimate load impedance Z_{OUT} based on a measured output current I_{OUT} and analog voltage feedback signal V_{FB} (or other signal indicative of output voltage V_{OUT}), and applying Ohm's law to determine load impedance Z_{OUT} (e.g., $Z_{OUT} \approx V_{FB}/I_{OUT}$). In some embodiments, impedance estimator 23 may comprise or implement an adaptive filter (e.g., a least-mean-squares filter) configured to adaptively minimize a difference between target output voltage V_{TGT} of a load and an actual output voltage of the load (e.g., V_{OUT} , V_{FB}), wherein target output voltage V_{TGT} is equal to an output voltage expected from applying target current signal I_{TGT} to the load assuming no variance of a nominal impedance of the load, and the actual output voltage at the load is the output voltage of the load generated by applying the output current (e.g., I_{OUT}) to the load. In these and other embodiments, impedance estimator 23 may be configured to determine impedance

of a load at the output of switched-mode amplifier 20B as a function of a frequency of output voltage V_{OUT} and control target current signal I_{TGT} to compensate for variance of the impedance as a function of the frequency. In these and other embodiments, impedance estimator 23 may be configured to control target current signal I_{TGT} to compensate for variance of the impedance Z_{OUT} over time.

Current calculator 21 comprise any system, device, or apparatus for calculating a target current I_{TGT} to be applied to the output load of power converter 26 based on target output voltage V_{TGT} generated by loop filter 22 and estimated load impedance Z_{OUT} generated by impedance estimator 23, and applying Ohm's law to determine target current I_{TGT} (e.g., $I_{TGT} \approx V_{TGT}/Z_{OUT}$).

Differential amplifier 25 may comprise any system, device, or apparatus configured to receive at its input terminals differential output voltage V_{OUT} and generate analog voltage feedback signal V_{FB} indicative of differential output voltage V_{OUT} .

Current sensor 27 may comprise any system, device, or apparatus configured to sense output current I_{OUT} and generate a signal indicative of such sensed output current.

Thus, switched-mode amplifier 20B may comprise a system which includes an impedance estimator 23 configured to estimate an impedance of a load at the output of switched-mode amplifier 20B and a current calculator 21 configured to generate a target current I_{TGT} based at least on an input voltage V_I and the impedance. In some embodiments, current calculator 21 may be integral to impedance estimator 23 such that impedance estimator 23 includes both the functionality of impedance estimator 23 and current calculator 21 depicted on FIGURE 31. Such system may also include a voltage feedback loop (e.g., implemented by differential amplifier 25 and loop filter 22) responsive to a difference between the input voltage V_I and an output voltage of the load (represented by analog voltage feedback signal V_{FB}). Such system may also include a current controller (e.g., implemented by converter controller 24 and power converter 26) configured to, responsive to the voltage feedback loop, impedance estimator 23, and the input voltage V_I , generate an output current I_{OUT} to the load.

As used herein, absolute voltage values (e.g., 1V, 3V, 7V, 14V) are given merely as examples, and any other suitable voltages may be used to define ranges of operation of the various power converter modes described herein.

As used herein, when two or more elements are referred to as “coupled” to one another, such term indicates that such two or more elements are in electronic communication or mechanical communication, as applicable, whether connected indirectly or directly, with or without intervening elements.

This disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the exemplary embodiments herein that a person having ordinary skill in the art would comprehend. Similarly, where appropriate, the appended claims encompass all changes, substitutions, variations, alterations, and modifications to the exemplary embodiments herein that a person having ordinary skill in the art would comprehend. Moreover, reference in the appended claims to an apparatus or system or a component of an apparatus or system being adapted to, arranged to, capable of, configured to, enabled to, operable to, or operative to perform a particular function encompasses that apparatus, system, or component, whether or not it or that particular function is activated, turned on, or unlocked, as long as that apparatus, system, or component is so adapted, arranged, capable, configured, enabled, operable, or operative.

All examples and conditional language recited herein are intended for pedagogical objects to aid the reader in understanding the invention and the concepts contributed by the inventor to furthering the art, and are construed as being without limitation to such specifically recited examples and conditions. Although embodiments of the present inventions have been described in detail, it should be understood that various changes, substitutions, and alterations could be made hereto without departing from the spirit and scope of the disclosure.

WHAT IS CLAIMED IS:

1. A power stage for producing an output voltage to a load, comprising:
a power converter comprising:
a power inductor;
a plurality of switches arranged to sequentially operate in a plurality of switch configurations; and
an output for producing the output voltage comprising a first output terminal and a second output terminal, wherein a first switch of the plurality of switches is coupled to the first output terminal and a second switch of the plurality of switches is coupled to the second output terminal;
a linear amplifier coupled to the output; and
a controller configured to:
in a linear amplifier mode of the power stage, enable the linear amplifier to transfer electrical energy from an input source of the power stage to the load; and
in at least one mode of the power stage other than the linear amplifier mode, sequentially apply switch configurations from the plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to transfer electrical energy from the input source of the power stage to the load.
2. The power stage of Claim 1, further comprising at least one of a capacitor coupled to the first output terminal and a capacitor coupled to the second output terminal, and wherein the first switch is coupled between the power inductor and the first output terminal and the second switch is coupled between the power inductor and the second output terminal.
3. The power stage of Claim 1, the controller configured to, in the at least one mode of the power stage other than the linear amplifier mode, disable the linear amplifier.

4. The power stage of Claim 1, wherein the linear amplifier comprises a current-mode digital-to-analog converter configured to produce the output voltage as a function of an input signal.

5. The power stage of Claim 4, wherein the input signal is an audio signal.

6. The power stage of Claim 4, wherein the digital-to-analog converter comprises a quadrant digital-to-analog converter.

7. The power stage of Claim 4, wherein the digital-to-analog converter comprises a hemispherical digital-to-analog converter.

8. The power stage of Claim 1, the controller configured to operate the power converter in the linear amplifier mode and enable the linear amplifier when at least one of a magnitude of the output voltage and a magnitude of a target voltage of the output voltage is below a threshold magnitude.

9. The power stage of Claim 8, the controller configured to operate the power converter in the at least one mode of the power stage other than the linear amplifier mode and disable the linear amplifier when at least one of the magnitude of the output voltage and the magnitude of a target voltage of the output voltage is above the threshold magnitude.

10. The power stage of Claim 1, wherein the load is an acoustic transducer.

11. A method for producing an output voltage to a load, comprising:

in a power converter comprising a power inductor, a plurality of switches arranged to sequentially operate in a plurality of switch configurations, and an output for producing the output voltage comprising a first output terminal and a second output terminal, wherein a first switch of the plurality of switches is coupled to the first output terminal and a second switch of the plurality of switches is coupled to the second output terminal:

in a linear amplifier mode of a power stage, enabling a linear amplifier coupled to the output to transfer electrical energy from an input source of the power stage to the load; and

in at least one mode of the power stage other than the linear amplifier mode, sequentially applying switch configurations from the plurality of switch configurations to selectively activate or deactivate each of the plurality of switches in order to transfer electrical energy from the input source of the power stage to the load.

12. The method of Claim 11, wherein the power converter comprises at least one of a capacitor coupled to the first output terminal and a capacitor coupled to the second output terminal, and wherein the first switch is coupled between the power inductor and the first output terminal and the second switch is coupled between the power inductor and the second output terminal.

13. The method of Claim 11, further comprising, in the at least one mode of the power stage other than the linear amplifier mode, disabling the linear amplifier.

14. The method of Claim 11, wherein the linear amplifier comprises a current-mode digital-to-analog converter configured to produce the output voltage as a function of an input signal.

15. The method of Claim 14, wherein the input signal is an audio signal.

16. The method of Claim 14, wherein the digital-to-analog converter comprises a quadrant digital-to-analog converter.

17. The method of Claim 14, wherein the digital-to-analog converter comprises a hemispherical digital-to-analog converter.

18. The method of Claim 11, further comprising operating the power converter in the linear amplifier mode and enabling the linear amplifier when at least one of a magnitude of the output voltage and a magnitude of a target voltage of the output voltage is below a threshold magnitude.

19. The method of Claim 18, further comprising operating the power converter in the at least one mode of the power stage other than the linear amplifier mode and disabling the linear amplifier when at least one of the magnitude of the output voltage and the magnitude of a target voltage of the output voltage is above the threshold magnitude.

20. The method of Claim 11, wherein the load is an acoustic transducer.

1/15





FIG. 2

2/15




FIG. 3







FIG. 4



V_{OUT}	PHASE	SWITCH STATES									
+/-	T1/T2	51	52	53	54	55	56	57	58	59	60
+	T1	1	1	0	0	0	0	0	1	0	0
+	T2	1	0	1	0	0	0	0	1	0	0
-	T1	1	1	0	0	0	0	0	0	1	0
-	T2	1	0	0	0	1	0	0	0	1	0


FIG. 6






V_{OUT}	PHASE	SWITCH STATES									
		51	52	53	54	55	56	57	58	59	60
+	T1	1	1	0	0	0	0	0	0	0	0
+	T2	0	0	1	1	0	0	0	0	0	0
-	T1	1	1	0	0	0	0	0	0	0	0
-	T2	0	0	0	0	1	1	0	0	0	0

FIG. 9





V _{OUT}	CM	PHASE	SWITCH STATES									
			51	52	53	54	55	56	57	58	59	60
+	+	T1	1	0	1	0	0	0	0	0	0	0
+	+	T2	0	0	1	1	0	0	0	0	0	0
+	-	T1	0	1	0	1	0	0	0	0	0	0
+	-	T2	0	0	1	1	0	0	0	0	0	0
-	+	T1	1	0	0	0	1	0	0	0	0	0
-	+	T2	0	0	0	0	1	1	0	0	0	0
-	-	T1	0	1	0	0	0	1	0	0	0	0
-	-	T2	0	0	0	0	1	1	0	0	0	0

FIG. 12

6/15




FIG. 13




FIG. 14




FIG. 15

V_{TGT}	V_{OUT}	CM	PHASE	SWITCH STATES									
+/-	+/-	+/-	T1/T2	51	52	53	54	55	56	57	58	59	60
+	-	+	T1	1	0	1	0	0	0	0	0	0	0
+	-	+	T2	0	0	1	0	0	0	1	0	0	0
+	-	-	T1	0	1	0	1	0	0	0	0	0	0
+	-	-	T2	0	0	1	0	0	0	1	0	0	0
-	+	+	T1	1	0	0	0	1	0	0	0	0	0
-	+	+	T2	0	0	0	0	1	0	1	0	0	0
-	+	-	T1	0	1	0	0	0	1	0	0	0	0
-	+	-	T2	0	0	0	0	1	0	1	0	0	0

FIG. 16




FIG. 17




FIG. 18




FIG. 19

V_{TGT}	CM	PHASE	SWITCH STATES									
+/-	+/-	T1/T2	51	52	53	54	55	56	57	58	59	60
+	+	T1	1	0	1	0	0	0	0	0	0	0
		T2	0	0	0	1	0	0	0	0	0	1
+	-	T1	0	1	0	1	0	0	0	0	0	0
		T2	0	0	1	0	0	0	1	0	0	0
-	+	T1	1	0	0	0	1	0	0	0	0	0
		T2	0	0	0	0	0	1	0	0	0	1
-	-	T1	0	1	0	0	0	1	0	0	0	0
		T2	0	0	0	0	1	0	1	0	0	0

FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24

9/15





FIG. 25

10/15



11/15




FIG. 27




FIG. 28






FIG. 29

14/15



15/15



INTERNATIONAL SEARCH REPORT

International application No
PCT/US2015/029765

A. CLASSIFICATION OF SUBJECT MATTER

INV. H03F1/02 H03F3/181 H03F3/217
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H03F

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 2 395 657 A1 (HARMAN INT IND [US]) 14 December 2011 (2011-12-14) paragraph [0031] - paragraph [0037]; figures 2,3,5	1,3,5, 8-11,13, 15,18-20
A	----- US 2013/082771 A1 (DELANO CARY L [US]) 4 April 2013 (2013-04-04) the whole document	1-20
A	----- EP 2 709 272 A1 (NEC CORP [JP]) 19 March 2014 (2014-03-19) the whole document	1-20
A	----- US 2010/019844 A1 (METZGER JUERGEN [DE] ET AL) 28 January 2010 (2010-01-28) figure 2 ----- -/-	1,11



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

12 August 2015

Date of mailing of the international search report

19/08/2015

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Kurzbauer, Werner

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2015/029765

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 101 26 236 A1 (HARMAN BECKER AUTOMOTIVE SYS [DE]) 12 December 2002 (2002-12-12) the whole document -----	1-20

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2015/029765

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 2395657	A1	14-12-2011	CN	102386868 A		21-03-2012
			EP	2395657 A1		14-12-2011
			JP	5377579 B2		25-12-2013
			JP	2012005122 A		05-01-2012
			US	2011304400 A1		15-12-2011

US 2013082771	A1	04-04-2013	CN	103828231 A		28-05-2014
			EP	2761743 A1		06-08-2014
			JP	2014528666 A		27-10-2014
			US	2013082771 A1		04-04-2013
			WO	2013049212 A1		04-04-2013

EP 2709272	A1	19-03-2014	EP	2709272 A1		19-03-2014
			US	2015137886 A1		21-05-2015
			WO	2012157418 A1		22-11-2012

US 2010019844	A1	28-01-2010	DE	102008030576 B3		03-12-2009
			US	2010019844 A1		28-01-2010

DE 10126236	A1	12-12-2002	DE	10126236 A1		12-12-2002
			EP	1286454 A2		26-02-2003
			US	2003001547 A1		02-01-2003
