PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: WO 97/37490 (11) International Publication Number: A1 H04N 5/445 (43) International Publication Date: 9 October 1997 (09.10.97) PCT/US97/05228 (81) Designated States: AU, CA, CN, JP, KR, MX, US, European (21) International Application Number: patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). 31 March 1997 (31.03.97) (22) International Filing Date: **Published** (30) Priority Data: US With international search report. 08/630,428 3 April 1996 (03.04.96) (71) Applicant (for all designated States except US): HYUNDAI ELECTRONICS AMERICA, INC. [US/US]; 3101 North First Street, San Jose, CA 95134 (US). (72) Inventor; and (75) Inventor/Applicant (for US only): BEDARD, Karen [CA/US]; 2275 Glenkird Drive, San Jose, CA 95124 (US). (74) Agents: LANG, Dan, H. et al.; Townsend and Townsend and Crew L.L.P., 8th floor, Two Embarcadero Center, San Francisco, CA 94111-3834 (US).

(54) Title: BOOKMARKING TELEVISION PROGRAM AND CHANNEL SELECTIONS



(57) Abstract

A method and apparatus coupled to broadcast signals, such as television signals, and a television set (16) for displaying broadcast programs and channels. The apparatus displays broadcast programs on selected channels to a viewer, marks one or more of the programs in response to a first signal from the viewer, marks one or more of the channels in response to a second signal from the viewer, stores signals corresponding to the marked programs and channels; and sequentially displays the marked programs and channels in response to a third signal from the viewer. The apparatus displays a plurality of icons (51-58) on the screen, sequentially moves an icon cursor (42) from one icon to another icon in response to a first signal from a television viewer to point to one icon at a time, and displays text associated with the pointed icon only.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AL AM	Amenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Annema	FR	France	LU	Luxembourg	SN.	Senegal
	Australia	GA	Gabon	LV	Latvia	SZ`	Swaziland
AU AZ	Austrana Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
		GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BE	Belgium	GR	Greece	1,116	Republic of Macedonia	TR	Turkey
BF	Burkina Faso	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BG	Bulgaria	IE	rungary Ireland	MN	Mongolia	ÜA	Ukraine
ВJ	Benin		Ireiand Israel	MR	Mauritania	UG	Uganda
BR	Brazil	IL		MW	Malawi	US	United States of America
BY	Belarus	IS	Iceland	MX	Mexico	UZ	Uzbekistan
CA	Canada	IT	Italy			VN	Viet Nam
CF	Central African Republic	JP	Japan	NE	Niger	YU	
CG	Congo	KE	Kenya	NL	Netherlands	ZW	Yugoslavia Zimbabwe
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbaowe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

5

10

15

25

30

35

BOOKMARKING TELEVISION PROGRAM AND CHANNEL SELECTIONS

EXAMPLE FIGURES

The present application includes drawings showing iconographic and electronic program guide information displays on a television screen in accordance with the invention. A portion of the disclosure of this patent document contains material which is subject to copyright protection. The copyright owner has no objection to the facsimile reproduction by anyone of the patent document or the patent disclosure, as it appears in the Patent and Trademark Office patent file or records, but otherwise reserves all copyright rights whatsoever.

BACKGROUND OF THE INVENTION

This invention relates to the selection of broadcast signals and, more particularly, to the convenient selection of broadcast signals, such as television programs and channels, by a viewer.

Since the inception of television, the number of available channels has steadily increased. The inauguration of the UHF band for broadcast use, the development of the cable television infrastructure, and the introduction of readily available direct satellite reception have all increased the number of available channels and programs. Presently there are predictions that there will be hundreds of channels (and a corresponding increase in the number of programs) for individual markets in the United States by the end of this century. These broadcast signals may be television signals, or some other form of broadcast medium.

The proliferation of these channels and programs brings with it a greater variety of choices. However, the viewer's task is complicated by not only learning what programming is available at any particular time and on its

WO 97/37490 PCT/US97/05228

channel, but also of simply finding a program to watch. Many television viewers turn on a television set and flip through the channels to find a program which catches their interest. With ten channels, for example, the time to flip through the channels is short. However, with hundreds of available programs, the time required to view all the channels becomes undesirably long. Unless the viewer knows exactly what channel he or she wishes to see, channel flipping becomes the television entertainment itself.

SUMMARY OF THE INVENTION

The present invention overcomes or substantially mitigates some of these problems by providing for an apparatus which is coupled to broadcast signals, such as television signals, and a television set for displaying broadcast programs and channels on a screen of the television set and for a method of displaying broadcast signals, such as programs and channels, on a screen of the television set. The apparatus has means for displaying broadcast programs on selected channels to a viewer, means for marking one or more of the programs in response to a first signal from the viewer, means for marking one or more of the channels in response to a second signal from the viewer, means for storing signals corresponding to the marked programs and channels, and means for sequentially displaying the marked programs and channels in response to a third signal from the viewer.

The present invention also provides for an apparatus and a method for displaying broadcast information, such as television signals, on a screen of a television. The apparatus has means for displaying a plurality of icons on the screen; means for sequentially moving an icon cursor from one icon to another icon in response to a first signal from a television viewer to point to one icon at a time; and means for displaying text associated with the pointed icon only.

PCT/US97/05228 WO 97/37490

BRIEF DESCRIPTION OF THE DRAWINGS

3

The invention may be better understood by reference to the following detailed description in connection with the accompanying drawings.

Fig. 1A depicts an exemplary settop unit and television set suitable for implementing the present invention; Fig. 1B illustrates the general operation and organization of the internal circuitry of the settop unit of Fig. 1A;

Fig. 2 depicts an exemplary remote control unit suitable for use in conjunction with the settop unit and television set of Fig. 1A;

Figs. 3A-3B depicts a television display showing program and channel bookmarking icons respectively;

Figs. 4A-4K depicts television display images of exemplary programs and channels as a viewer bookmarks programs and channels in accordance with an embodiment of the present invention;

Figs. 5A-5C depicts recalled television display images of the bookmarked programs and channels of Figs. 4A-4K; and

Figs. 6A-6D illustrates the details and operation of an icon bar displayed in accordance with the present invention.

25

30

35

5

10

15

20

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

The present invention can perhaps be best understood in terms of a viewer with a television set 12 and a settop unit 16 in Fig. 1A and a remote control unit 10 in Fig. 1B.

As shown in Fig. 1A, the settop unit 12 is coupled to a broadcast medium (not shown) and to a broadcast signal input of a television set 16. The settop unit 12 operates to select a particular channel to be received and to display the programming of that channel through the television set 16. The settop unit 12 preferably includes an IR receiver 18 operative to receive remote control signals from a remote Thus a viewer may select a particular channel control unit. to be received by the commanding settop unit 12 via remote

control or by operating controls (not shown) on the settop unit 12. The settop unit 12 has circuitry to allow it to generate its own displays to show on the screen of the television 16 and to extract electronic program guide (EPG) information from externally received signals and storing the signals in an internal memory (not shown). Such electronic program guide information signals are sent over any broadcast bands, such as present UHF band, television cable and direct satellite broadcasts.

5

10

15

20

25

30

35

Fig. 1B represents the general operation and organization of the internal circuitry of the settop unit 12. The settop unit 12 includes a tuner/decoder 28, a control unit 21, a remote control receiver 23, an electronic program quide information extraction unit 25, a display generation unit 36, and a presentation circuit 38. The remote control receiver 23 is coupled to the IR receiver 18 and converts the received IR signals to electrical command signals which are input to the control unit 21. The control unit 21 coordinates the general operation of the settop unit 12. The control unit 21 preferably incorporates a microprocessor or microcontroller. One function of the control unit 21 is to generate a channel selection control signal to the tuner/decoder 28. tuner/decoder 28 receives the external broadcast video signal and isolates a desired channel in accordance with the channel selection control signal.

The program guide extraction unit 25 isolates the EPG information from the received signal. In one embodiment, this information is extracted from the blanking intervals of the currently selected channel. There are, of course, other ways that the EPG information could be multiplexed with video information to display. In an alternative embodiment, the tuner/decoder 28 may be shifted to a special electronic program guide information channel which transmits only EPG information.

The control unit 21 also directs the display generation unit 36 to generate electronic program displays and prompts responsive to the EPG information made available by the electronic program guide extraction unit 25 and further

WO 97/37490 PCT/US97/05228

5

responsive to user commands received via the remote control receiver 23. The control unit 21 also directs the display generation unit 36 to generate various displays and prompts, such as the icons described below, indicative of various functions. The functions pertinent to the present invention are described below. Electronic memory space is also included in the control unit 21 to hold various electrical signals in response to user commands and to guide the control unit 21 through its operations.

5

20

25

30

35

The presentation unit 36 combines the program guide display generated by the display generation unit 36 with the video signal received from the tuner/decoder 28 to produce a video signal for display. Certain prompts and displays may be superimposed over video programming of the selected channel.

Other displays may occupy the entire screen and thus substitute entirely for the selected channel.

Further details of the internal design of settop unit 12 should be apparent to those of skill in the art and is not further discussed herein. Any combination of hardware or software may be used to implement the functions of settop unit 12.

Of course, a separate settop unit is only one possible apparatus for implementing the present invention. For example, part, or all of the settop unit may be located within the television 16 itself or within an interactive television network coupled to the settop unit 12.

Fig. 2 depicts the exemplary remote control unit 10 operates with the settop unit 12 and television set 16 in Fig. 1A. Of course, the remote control unit 10 is not drawn to the same scale as the television set 16 of Fig. 1A. The remote control unit 10 includes a numeric keypad 13, volume controls 14, channel controls 15, vertical cursor arrow keys 17A and horizontal cursor arrow keys 17B, an Off/On switch 18, a TV button 20, a Guide button 22, a Select button 24, and an Options button 26. The Off/On switch 18 turns the settop unit 12 on and off. The numeric keypad 13 and/or channel controls 15 are used for channel selection. The volume controls 14 adjust volume of the television set 16. The TV button 20, the

6

Guide button 22, the Select button 24, and the Options button 26 are used in the selection of programs from EPG information signals. An example of such operations are explained in a copending patent application, U.S. Appln. No._____, entitled "ELECTRONIC PROGRAM GUIDE WITH ENHANCED PRESENTATION," filed November 10, 1995 by the present inventor and assigned to the present assignee, which application is incorporated by reference.

5

10

15

20

25

30

35

In accordance with the present invention, at any time while watching the television set 16, the viewer can "bookmark" programs or channels to which he or she wants to return quickly and/or at a later time. In the simplest form, the present invention operates like the "Recall" feature on many television sets today, which allows a viewer to toggle between the two most recently visited channels. In the present invention up to 32 channels (and programs), for example, may be marked and recalled. This allows the viewer to create a list of favorite channels to flip through when a viewing decision has not yet been made, or allows the viewer to track progress of certain programs while also watching something else.

The Bookmark feature toggles between three stages:
Mark Program, Mark Channel and Unmark. When the viewer is
watching an unmarked program which the viewer wishes to
"bookmark", the viewer simply presses the Select button 24 on
the remote control unit 10. A hollow checkmark icon 30 at the
top right of the screen as shown in Fig. 3A, which indicates
that the current program is marked. Of course, other icons
may be used. To avoid visual confusion the underlying
broadcast images are not shown in Figs. 3A and 3B. This
bookmark is remembered only as long as the program is running.
When the program ends, the bookmark is automatically removed.

If Select button 24 is pressed again on a marked program, the hollow checkmark changes to a filled checkmark icon as shown in Fig. 3B, which indicates that the channel, rather than the program, is marked. Again, other icons may be used to indicate this function. Marked channels are remembered permanently for the current viewer even after the

current viewing session terminates or after the television is turned off, until the viewer removes the bookmark.

If the viewer presses Select button 24 again, the channel bookmark icon 31 is removed and the icon disappears. As the user switches channels, the bookmark icon 30 or 31 is displayed only for a few seconds so as not to interfere with the broadcast image on the television set 16.

5

10

15

20

Signals to recall bookmarked programs and channels are stored in the settop unit 12. The bookmarked programs and channels are remembered even when the television set 16 is turned off. However, as stated above, marked programs are removed when these programs are over, as indicated by EPG signals being received by the settop unit 12.

The viewer can then sequentially flip through the bookmarked programs and channels, at any point in time during normal viewing, by using the Recall button 27 on the remote control unit 10. The viewer can still navigate through all the channels in order by using Channel Up and Channel Down buttons 15. If no programs or channels have been marked, the last channel visited is recalled by the settop unit 12 so that the television set 16 toggles between the last two visited channels when the viewer presses the Recall button 27 repeatedly.

Figs. 4A-4K illustrate the present invention as 25 might be used by the viewer. Each figure illustrates an exemplary broadcast image on the television set 16 as the viewer bookmarks programs and channels. Fig. 4A shows the image of the first channel. In Fig. 4B the Select button 24 has been pushed twice and the channel has been bookmarked. This is indicated by the shaded icon 33 in the upper righthand 30 corner of the television set 16. The channel is then changed by the different image in Fig. 4C. Fig. 4D indicates that the viewer has changed the channel again. Likewise, Fig. 4E indicates another channel. The viewer then bookmarks the 35 broadcast program by pressing the Select button 24 once. 4F shows the bookmarked program icon 34 in the upper righthand corner of the image. Figs. 4G and 4H indicate that the viewer has changed channels twice. A shaded bookmarked channel icon

WO 97/37490 8

5

10

15

20

25

30

35

35 in Fig. 4I indicates that the viewer has pushed the Select button 24 twice to select the channel shown by Fig. 4H. viewer then changes channels twice as shown by Figs. 4J and 4K.

The result is that, after changing among eight channels, the viewer has bookmarked two channels and one Upon pushing the Recall button 27, the settop unit 12 recalls the first bookmarked channel, as shown in Fig. 5A. Another push of the Recall button 27 brings the bookmarked program, as shown in Fig. 5B. A third push of the Recall button 27 brings the second bookmarked channel, as shown in Fig. 5C. As noted previously, the bookmarked program of Fig. 5B is recalled only if it is still being broadcast. program has ended by the time the viewer pushes the Recall button 27, the settop unit 12 recalls only the bookmarked channels.

It should be noted all of the television set images in the drawings have information on the television set 16. described above, the bookmarking of programs and channels and their recall can be performed while the settop unit 12 is in a simple broadcast reception mode. The screen of the television set 16 simply displays the broadcast image of the selected channel (and the transient program and channel bookmark The bookmarking of programs and channels and their recall can also be performed in other modes as well.

In the drawings of Figs. 3A-3B, 4A-4K and 5A-5C, the settop unit 12 is in an EPG display mode by which electronic program guide information may be obtained and displayed on the television set 16. In this mode an icon bar 40 and some electronic program guide information 41 is displayed. Figs. 3A and 3B, for example. In this mode and other EPG display modes, which are described in detail in the abovereferenced patent application, the viewer can view the schedules of broadcast programs and programs can also be selected for present and future viewing.

As one aspect of the present invention, the viewer can also bookmark programs and channels while in these EPG display modes by selecting these programs from the EPG

WO 97/37490 PCT/US97/05228

information. The programs may be broadcast in the future or at the time of the selection. Bookmarking a program is performed by moving an icon cursor 42 on the icon bar 40 over a Mark/Unmark icon 54. Pushing the Select button 24 then bookmarks the selected program for later recall (until the time for program's broadcast has expired).

5

10

15

20

25

30

35

As part of the present invention, the settop unit 12 generates icon bars for display on the television set 16 upon request by the viewer. An icon bar consists of a row of icons identifying functions that the viewer can perform in the context they are in. The viewer uses the <- and -> arrow buttons 17B on the remote control unit 10 to move the icon cursor box 42 from one icon to the next. A function is chosen by pressing the Select button 24 on the remote control unit 10 when the icon cursor box 42 is over the selected function. In the example shown in Figs. 6A-6C, the icon bar 40 has icons 51-52, which include the Mark/Unmark icon 54. In the three drawings the icon cursor 42 is moved to the left by pushing the left arrow button 17B.

The number of icons available are not limited to the size of the screen. The viewer may access more of the icons by moving the icon cursor box 42 to the far left or right of an icon bar. The icon cursor box 42 shows the viewer the appropriate left and right arrows when they are available. In addition, a partial icon is visible on the end of the bar to reinforce the fact that more functions lie in that direction. If there are no more icons to the left, for example, the icon cursor box 42 shows only a right arrow.

As shown in Figs. 6A-6D, the icon cursor box 42 is accompanied by a text bar 43 which describes the function of the icon on which icon cursor box 42 is placed. By providing text for only the icon the cursor is on, more choices can be provided than that by textual menus in the same amount of screen space. At the same time, the text bar 43 provides for a large text space for international translation of each function of the icon. The example shown in Fig. 5D shows a German phrase for a Record.

The use of icon bars, the icon cursor and the accompanying allow the viewer to easily create lists of identifiable viewers. For example, the icon bar 40 shown in Fig. 6A has a Viewer icon 53 which leads to further icon bars to identify the viewer from a list of viewer or to add a viewer. In the electronic program guide information 41 shown in Figs. 3A and 3B, for example, the viewer, "Bob," is identified. Once an "Add Viewer" function is selected, the arrow buttons 17A and 17B and the Select button 24 allow the name of the added viewer to be entered from an on-screen table of letters.

5

10

15

20

25

In accordance with the present invention, there is a separate list of bookmarked programs and channels for each identified viewer. Upon identifying himself or herself to the settop unit 12 through the remote control unit 10 as prompted by the displays on the television set 16, the viewer has personalized programs and channels which are bookmarked. Accordingly, each viewer need not waste time to flip through channels and programs which are undesirable to that viewer.

while the above is a complete description of the preferred embodiments of the invention, various alternatives, modifications and equivalents may be used. It should be evident that the present invention is equally applicable by making appropriate modifications to the embodiments described above. Therefore, the above description should not be taken as limiting the scope of the invention which is defined by the metes and bounds of the appended claims.

WO 97/37490 PCT/US97/05228

WHAT IS CLAIMED IS:

1. An apparatus coupled to broadcast signals and a
2 television set for displaying broadcast programs and channels
3 on a screen of said television set, said apparatus comprising
4 means for displaying broadcast programs on selected
5 channels to a viewer;

means for marking one or more of said programs in response to a first signal from said viewer;

means for marking one or more of said channels in response to a second signal from said viewer;

means for storing signals corresponding to said marked programs and channels; and

means for sequentially displaying said marked
programs and said channels in response to a third signal from
said viewer.

- 2. The apparatus of claim 1 wherein said apparatus is further coupled to broadcast electronic program guide information signals and wherein said storing means removes signals corresponding to a marked program responsive to said broadcast electronic program guide information signals indicative of a termination of said marked program.
- The apparatus of claim 1 further comprising
 means for displaying a first icon on said screen in response
 to said program marking means marking a program.
- 4. The apparatus of claim 1 further comprising means for displaying a second icon on said screen in response to said channel marking means marking a channel.
- 5. The apparatus of claim 1 further comprising means for unmarking a marked program or a marked channel in response to a fourth signal from said viewer.
- 6. The apparatus of claim 5 further comprising a remote control unit associated with said viewer, said remote

- 3 control unit having a first button and generating first,
- 4 second, or fourth signals as said first button is asserted
- 5 sequentially.
- 7. An apparatus for displaying broadcast signal
- 2 information on a screen of a television, said apparatus
- 3 comprising
- 4 means for displaying a plurality of icons on said
- 5 screen;
- means for sequentially moving an icon cursor from
- one icon to another icon in response to a first signal from a
- 8 television viewer to point to one icon at a time; and
- means for displaying text associated with said
- 10 pointed icon only.
 - 1 8. The apparatus of claim 7 wherein said icon
 - 2 displaying means further comprises means for arranging said
 - 3 plurality of icons in a horizontal bar on said screen.
 - 9. The apparatus of claim 8 wherein said text
 - 2 displaying means displays said text in a bar adjacent to said
 - 3 pointed icon.
 - 1 10. The apparatus of claim 9 wherein said text
 - displaying means displays said text bar below said pointed
 - 3 icon.
 - 1 11. The apparatus of claim 7 wherein in said text
 - 2 displaying apparatus displays said text indicative of a
 - g function associated with said pointed icon.
 - 1 12. A method for displaying broadcast programs and
 - channels on a television screen, said method comprising the
 - 3 steps of:
 - displaying on said television screen broadcast
 - 5 programs on selected channels to a television viewer;
 - 6 marking one or more of said programs in response to
 - 7 a first signal from said television viewer;

marking one or more of said channels in response to

- 9 a second signal from said television viewer;
- storing signals corresponding to said marked
- 11 programs and channels; and
- sequentially displaying said marked programs and
- channels on said television screen in response to a third
- 14 signal from said television viewer.
 - 1 13. The method of claim 12 wherein said storing
 - 2 step further comprises removing signals corresponding to a
 - 3 marked program responsive to broadcast electronic program
 - 4 quide information signals indicative of a termination of said
 - 5 program.
 - 1 14. The method of claim 12 wherein said program
 - 2 marking step further comprises displaying a first icon.
 - 1 15. The method of claim 12 wherein said channel
 - 2 marking step further comprises displaying a second icon.
 - 1 16. The method of claim 12 further comprising the
 - 2 step of unmarking a marked program or a marked channel in
 - 3 response to a fourth signal from said viewer.
 - 1 17. A method for displaying broadcast information
 - on a television screen, said method comprising the steps of:
 - displaying a plurality of icons on said screen;
 - 4 sequentially moving an icon cursor from one icon to
 - 5 another icon in response to signals from a television viewer
 - 6 to select one icon at a time; and
 - 7 displaying text associated with said selected icon
 - 8 only.
 - 1 18. The method of claim 17 wherein said icon
 - 2 displaying step comprises arranging said plurality of icons in
 - 3 a horizontal bar on said screen.

- The method of claim 18 wherein said text 1
- displaying step comprises displaying said text in a bar 2
- adjacent to said selected icon. 3
- The method of claim 19 wherein said text 20. 1
- displaying step comprises displaying said text in a bar below 2
- said selected icon. 3
- 21. The method of claim 17 wherein said icon cursor 1
- comprises a box about an icon to which said cursor has been 2
- 3 moved.
- 22. The method of claim 17 wherein in said text 1
- displaying step said text describes a function of said 2
- selected icon. 3
- 23. The method of claim 22 wherein said text is 1
- adjacent said selected icon. 2




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3A




FIG. 3B

3/8




FIG. 4A




FIG. 4B




FIG. 4C

4/8




FIG. 4D




FIG. 4E




FIG. 4F




FIG. 4G




FIG. 4H




FIG. 41




FIG. 4J




FIG. 4K

7/8




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D

INTERNATIONAL SEARCH REPORT

International application No. PCT/US97/05228

A. CLASSIFICATION OF SUBJECT MATTER IPC(6) :H04N 5/445 US CL :348/564, 569, 601 According to International Patent Classification (IPC) or to both national classification and IPC								
B. FIELDS SEARCHED								
Minimum documentation searched (classification system followed by classification symbols)								
U.S. : 348/563, 564, 569, 589, 600, 601, 906 IPC H04N 5/445, 5/50, 9/74, 9/76								
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched								
Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)								
C. DOCUMENTS CONSIDERED TO BE RELEVANT								
Category*	Citation of document, with indication, where a	ppropriate, of the relevant passages	Relevant to claim No.					
X,P	US 5,528,304 A (CHERRICK et a and accompanying text.	7-11 and 17-23						
	and descripting text.		1-6 and 12-16					
A,P	whole document.							
X,P	US 5,604,544 A (BERTRAM) 18 18 and accompanying text.	7, 11, 17, 22 and 23						
A,P	whole document.	1-6, 8-10, 12- 16 and 18-21						
A,P	US 5,596,373 A (WHITE et al) 21 and accompanying text.	1-23						
A,P	US 5,532,753 A (BUCHNER et document.	1-23						
Furth	ner documents are listed in the continuation of Box C	See patent family annex.						
"A" doc	ecial categories of cited documents: cument defining the general state of the art which is not considered be part of particular relevance	"T" later document published after the inte date and not in conflict with the applica principle or theory underlying the inve	tion but cited to understand the					
"E" ear	tier document published on or after the international filing date cument which may throw doubts on priority claim(s) or which is ad to establish the publication date of another citation or other	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone						
"O" document referring to an oral disclosure, use, exhibition or other means		"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art						
P doc	cument published prior to the international filing date but later than priority date claimed	*&* document member of the same patent family						
Date of the	actual completion of the international search	Date of mailing of the international search report						
Commission Box PCT Washington	nailing address of the ISA/US ner of Patents and Trademarks n. D.C. 20231	Authorized officer SHERRIE HSIA Telephone No. (703) 305-3900						