



(86) Date de dépôt PCT/PCT Filing Date: 2008/07/22
(87) Date publication PCT/PCT Publication Date: 2009/04/02
(85) Entrée phase nationale/National Entry: 2010/03/24
(86) N° demande PCT/PCT Application No.: US 2008/008883
(87) N° publication PCT/PCT Publication No.: 2009/042005
(30) Priorités/Priorities: 2007/09/27 (US60/975,693);
2008/06/25 (US12/146,129)

(51) Cl.Int./Int.Cl. *F23G 7/07* (2006.01),
F23J 15/02 (2006.01), *F23L 17/02* (2006.01)

(71) Demandeur/Applicant:
ARNOLD, JOHN G., JR., US


(72) Inventeurs/Inventors:
SMITH, JOSEPH D., US;
ARNOLD, JOHN G., JR., US

(74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : DISPOSITIF DE CHAPEAU ET DE FILTRE DE CONDUIT DE CHEMINEE POUR UN APPAREIL CHAUFFE
AU GAZ

(54) Title: EXHAUST FLUE CAP AND FILTER DEVICE FOR A GAS FIRED APPLIANCE

FIG. 2



(57) **Abrégé/Abstract:**

An exhaust flue cap and filter device (10) for a gas fired appliance in communication with an exhaust flue opening having an outer pipe (13) and a coaxial liner (14). The device includes a tubular cap (16) with an open lower end (18), an opposed open upper end (20), and a plurality of ventilation holes (22) wherein the cap is receivable over the flue opening. A removable top (24) is attached to and closes the open upper end of the tubular cap. A filter tray (40) having a smaller diameter than the tubular cap includes a ledge (44) extending radially inward from the tray. A removable catalytic converter filter insert (50) within the tubular cap is supported on the ledge.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
2 April 2009 (02.04.2009)

PCT

(10) International Publication Number
WO 2009/042005 A2

(51) International Patent Classification:

F23G 7/02 (2006.01) *F23J 15/02* (2006.01)
F23L 17/02 (2006.01) *F23G 7/07* (2006.01)

(21) International Application Number:

PCT/US2008/008883

(22) International Filing Date: 22 July 2008 (22.07.2008)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/975,693 27 September 2007 (27.09.2007) US
12/146,129 25 June 2008 (25.06.2008) US

(71) Applicant and

(72) Inventor: **ARNOLD, John, G., Jr.** [US/US]; 2621 East
33rd Street, Tulsa, OK 74105 (US).

(72) Inventor: **SMITH, Joseph, D.**; 7130 North 194th East
Avenue, Owasso, OK 74055 (US).

(74) Agent: **KACHIGIAN, Mark, G.**; Head, Johnson &
Kachigian, 228 West 17th Place, Tulsa, OK 74119 (US).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished upon receipt of that report*

(54) Title: EXHAUST FLUE CAP AND FILTER DEVICE FOR A GAS FIRED APPLIANCE

FIG. 2



(57) Abstract: An exhaust flue cap and filter device (10) for a gas fired appliance in communication with an exhaust flue opening having an outer pipe (13) and a coaxial liner (14). The device includes a tubular cap (16) with an open lower end (18), an opposed open upper end (20), and a plurality of ventilation holes (22) wherein the cap is receivable over the flue opening. A removable top (24) is attached to and closes the open upper end of the tubular cap. A filter tray (40) having a smaller diameter than the tubular cap includes a ledge (44) extending radially inward from the tray. A removable catalytic converter filter insert (50) within the tubular cap is supported on the ledge.

EXHAUST FLUE CAP AND FILTER DEVICE FOR A GAS FIRED APPLIANCE

BACKGROUND OF THE INVENTION

1. Field of the Invention.

The present invention is directed to an exhaust flue cap and filter device or appliance and a method of use for an exhaust flue opening of a gas fired appliance. In particular, the present invention is directed to an exhaust flue cap and filter device which will reduce
5 carbon monoxide and particulate emissions from the exhaust of a gas fired appliance.

2. Prior Art.

There are various types of known gas fired appliances that are used with buildings and residences. These include gas fired water heaters, gas fired boilers, gas fired fireplaces, gas logs fitted within fireplaces, gas fired air heating systems, gas fired clothes dryers, or
10 other apparatus that use gaseous hydrocarbon fuels such as natural gas or propane.

For the most part, gas fired appliances are relatively efficient and do not produce the extensive amount of soot or other emissions associated with wood burning fireplaces and stoves or with coal burning fireplaces or stoves. Even gas fired appliances, however, produce a certain amount of particulate emissions and carbon monoxide emissions.

15 It is advisable and required by laws, codes, or regulations in many applications to vent a gas fired appliance from the building or residence outside to the atmosphere. There are various types and configurations of known venting systems. One type of double wall flue exhaust is known as a Type B double wall gas vent system. A Type B vent system includes an outer cylindrical wall along with a coaxial and concentric inner liner spaced
20 from the outer wall.

Accordingly, the present invention is directed to an exhaust flue cap and filter appliance capable of reducing the carbon monoxide and particulate emissions from the exhaust of gas fired appliances.

The present invention is directed to an exhaust flue cap and filter device for a gas
5 fired appliance that can be installed with new building or residence construction or can be retro-fit to an existing flue opening.

The present invention is directed to an exhaust flue cap and filter device for a gas fired appliance that reduces carbon monoxide and particulate emissions through a removable and replaceable catalytic filter insert.

10 The present invention is directed to an exhaust flue cap and filter device that will reduce carbon monoxide and particulate emissions while not substantially reducing flow through the exhaust flue.

The present invention is directed to an exhaust flue cap and filter device that permits bypass of exhaust gases in the event of any blockage of the filter component of the device.

SUMMARY OF THE INVENTION

The present invention is directed to an exhaust flue cap and filter device for a gas fired appliance and to a process or method to reduce carbon monoxide and unburned hydrocarbon emissions from the exhaust of a gas fired appliance.

5 The exhaust flue cap and filter device includes a tubular cap having a diameter larger than the exhaust flue opening. The tubular cap includes an open lower end, an opposed upper end, and a plurality of ventilation slots or vents between the lower end and the opposed upper end.

A removable top is attached to and closes the open upper end of the tubular cap. The removable top may be secured by fasteners or other mechanism to the tubular cap. The
10 removable top may also include an optional outwardly extending rain flange to discourage rain or precipitation from entering the ventilation slots of the tubular cap.

A filter tray is suspended within the tubular cap and has a smaller diameter than the tubular cap. The filter tray may be suspended within the tubular cap by a series of standoffs. The filter tray has an open bottom and an open top and may include a downwardly and
15 outwardly extending flared skirt to discourage rain or precipitation from entering the exhaust vent pipe and also to encourage flue gas to pass through the filter tray.

The filter tray includes a ledge extending radially inward to act as a support or shoulder to hold a removable filter insert which is received into the filter tray. The filter insert is catalytically active.

20 The exhaust flue cap and filter device also includes a cylindrical inner collar having a slightly larger diameter than the exhaust flue opening so that the inner collar fits over the exhaust flue opening. The inner collar is suspended within the tubular cap such as by a series of standoffs or by another mechanism.

In order to use the exhaust flue cap and filter device of the present invention, exhaust gases from the gas fired appliance are passed through the exhaust flue opening into the tubular cap. Atmospheric air is also allowed and permitted to pass into the tubular cap from the open lower end. The exhaust gases and the atmospheric air in the tubular cap are
5 permitted to pass into and through the catalytic filter insert which is supported within the tubular cap. The exhaust gases are treated by the catalytic filter insert as they pass therethrough.

The treated exhaust gases which have passed through the filter insert pass from the tubular cap through a plurality of ventilation holes in the tubular cap to the atmosphere.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a side view of an exhaust flue cap and filter device for a gas fired appliance exhaust flue opening constructed in accordance with the present invention;

Figure 2 illustrates a sectional view cut through the center of the exhaust flue cap and filter device shown in Figure 1;

5 Figure 3 illustrates a top view of the exhaust flue cap and filter device shown in Figure 1 apart from the exhaust flue opening; and

Figure 4 illustrates an exploded view of the exhaust flue cap and filter device shown in Figures 1, 2 and 3 apart from the exhaust vent pipe flue opening.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments discussed herein are merely illustrative of specific manners in which to make and use the invention and are not to be interpreted as limiting the scope of the instant invention.

While the invention has been described with a certain degree of particularity, it is to be noted that many modifications may be made in the details of the invention's construction and the arrangement of its components without departing from the spirit and scope of this disclosure. It is understood that the invention is not limited to the embodiments set forth herein for purposes of exemplification.

Referring to the drawings in detail, Figure 1 illustrates a side or elevation view of a preferred embodiment of an exhaust flue cap and filter device 10 of the present invention. Figure 2 illustrates a sectional view cut through the center of the exhaust device 10 shown in Figure 1, and Figure 3 illustrates a top view of the exhaust flue cap and filter device 10 with the removable top taken off of the device for ease of viewing.

Figure 4 illustrates an exploded view of the exhaust flue cap and filter device 10 separated from an exhaust flue vent system 12 with portions cut-away for clarity.

The present invention operates with exhaust flue openings of various types and configurations. As best seen in Figures 1, 2 and 4, in one non-limiting embodiment, the exhaust flue cap and filter device 10 of the present invention may be utilized with a double wall exhaust system, such as a Type B double wall gas vent system which includes an outer cylindrical pipe 13 and a coaxial and concentric cylindrical liner 14 having a diameter smaller than the outer cylindrical pipe 13.

As best seen in Figure 2, the exhaust flue cap and filter device 10 includes a tubular cap 16 having a diameter larger than the outer pipe 13 so that at least a portion of the tubular cap 16 is receivable over the exhaust flue opening. In the present embodiment, the tubular cap 16 is cylindrical and concentric with the vent system 12.

5 The tubular cap 16, as best seen in Figures 2 and 4, includes an open lower end 18, an opposed open upper end 20, and a plurality of ventilation slots or vents 22 between the lower end 18 and the opposed upper end 20. Because the tubular cap 16 has an open lower end 18, atmospheric air is permitted to enter the tubular cap as shown by arrows 30 in Figure 2. The tubular cap 16 may be fabricated from flat sheet metal or other lightweight material.

10 The tubular cap 16 may be configured so that a cross-section of the chimney cap is in the form of an octagon, a hexagon, a square, a rectangle, an oval, a circle, or other configuration. The ventilation slots or vents 22 may be stamped or otherwise formed into the tubular cap 16. The ventilation slots or vents 22 may be in various patterns or configurations.

15 A removable top 24 is attached to and closes the open upper end 20 of the tubular cap 16. The removable top 24 is shown attached to the device 10 in Figures 1 and 2 and is shown exploded from the device in Figure 4. The removable top 24 may be secured by fasteners 26 or other mechanism to the tubular cap 16. The removable top 24 may likewise be fabricated from flat sheet metal or other lightweight material.

20 The removable cap may include an outwardly extending rain flange 28. The outwardly extending rain flange 28 has a larger diameter than the removable top 24 and the tubular cap 16 and acts as an overhang to discourage rain or precipitation from entering the ventilation slots 22.

A filter tray 40 is suspended within the tubular cap 16 and has a smaller diameter than the tubular cap 16. In one preferred embodiment, the filter tray 40 has an open bottom and an open top. As may be appreciated from Figures 2 and 4, the filter tray 40 includes a downwardly and outwardly extending flared skirt 42 which discourages rain and precipitation from entering the vent pipe and also encourages exhaust from the vent pipe to pass through the insert to be described.

The filter tray 40 includes a ledge 44 extending radially inward. The ledge 44 acts as a support or shoulder to hold a removable filter insert 50. In one configuration, the filter tray 40 is substantially cylindrical. The filter insert 50 is substantially cylindrical with a slightly smaller diameter than the filter tray 40 so that the filter insert 50 is received into and is supported by the filter tray.

In an alternate embodiment (not shown), the filter tray 40 may have a square cross-section (smaller than the cap 16) to accommodate a filter insert in the shape of a block.

The filter tray 40 may be suspended within the tubular cap 16 by a series of stand-offs 52 as best seen in Figure 3. The stand-offs 52 extend radially from the filter tray 40. The outwardly flared skirt 42 of the filter tray 40 encourages exhaust gases from the vent pipe 12 to pass through the filter insert 50.

Because the filter insert 50 and the filter tray 40 have a diameter less than the tubular cap, gases such as atmospheric air are permitted to enter the base of the tubular cap 16 and travel outside of the filter tray and filter insert 50 and pass above the filter tray and filter insert within the tubular cap. The atmospheric air assists in moving the exhaust gases up and through the tubular cap 16 and assists in catalytic conversion to be described. Also, in the event of blockage of the filter insert for any reason, both exhaust gases and atmospheric air may pass through the device without blockage.


The exhaust flue cap and filter device 10 also includes a cylindrical inner collar 54 having a slightly larger diameter than the exhaust flue opening outer pipe 12 as best seen in Figure 4. Accordingly, the inner collar 54 fits over the outer pipe 13 of the exhaust system. One or more stop tabs 48 (best seen in Figure 4) may extend from the inner collar 54 to stop
5 insertion of the inner collar once fully inserted. The inner collar 54 is suspended within the tubular cap 16 by a series of stand-offs 56 or by another mechanism.

The exhaust flue cap and filter device 10 may be installed by slipping the inner collar 54 over the exhaust flue vent system 12 until the stop tabs 48 abut the upper edge of the outer pipe 13. Thereafter the device 10 is secured to the outer pipe 13 thereto with fasteners
10 58.

The filter insert 50 may be removed and cleaned or may be replaced by removing the fasteners 26 in order to remove the removable top 24 from the tubular cap 16. Thereafter, it will be possible to access the filter insert 50 in order to remove it from the filter tray 40. A replacement filter insert may be installed in the tubular cap suspended by the filter tray 40.

15 The filter insert 50 may be fabricated from a number of materials in order to reduce carbon monoxide and particulate emissions from the exhaust of the gas fired appliance.

In one configuration, the filter insert 50 may be catalytically active in order to reduce carbon monoxide (CO) which escapes from the device 10. The catalytically active filter insert 50 may include a core or substrate and a washcoat including catalytically active
20 metals. The filter insert reduces unburned hydrocarbons and carbon monoxide by oxidizing them over a metal catalyst. This catalyst aids the reaction of the carbon monoxide (CO) and hydrocarbons with the remaining oxygen in the exhaust gas and with oxygen in the atmospheric air entering the tubular cap 16. For example:



The catalytically active converter may include a core or substrate material and a washcoat which is comprised of catalytically active metals. The washcoat is applied to the surface of the core or substrate material so that the washcoat comes into contact with exhaust gases passing from the gas fired appliance through the device 10.

5 The removable filter insert 50 may be comprised of a number of materials. In a first configuration, the filter insert 50 may be a wire screen or a series of wire screens with a washcoat including a precious metal catalyst. In one non-limiting example, the wire screen may have eighth inch (1/8") square openings.

10 In a second embodiment, the filter insert 50 may be comprised of a ceramic block monolith having a honeycomb structure with gas flow passages which are coated with a washcoat having a precious metal catalyst.

In a third embodiment, the filter insert 50 is comprised of a metal foam with between three to five pores per inch. The filter insert includes a washcoat having a precious metal catalyst.

15 In a fourth configuration, the filter insert may take the form of multiple ceramic discs which are coated with a washcoat having a precious metal catalyst. In each case, the washcoat may be alumina based.

In use, exhaust gases are passed from a gas fired appliance (not shown) through the exhaust vent system 12 flue opening into the tubular cap 16 so that exhaust gases mix with atmospheric air entering the open lower end of the tubular cap 16. The atmospheric air and exhaust gases pass into and through the catalytic filter insert 50 in the tray. The exhaust gases are treated by the catalytically active filter insert 50 which promotes oxidation in order to convert excess carbon monoxide (CO) into carbon dioxide (CO₂). The treated gases are thereafter permitted to move from the upper end of the tubular cap 16 through the vents to
25 the atmosphere.

A further objective of the present invention is to minimize pressure loss through the device 10. In testing of the exhaust flue cap and filter device 10 of the present invention, only a minimal pressure drop was observed as exhaust gases passed from the flue exhaust through the device.

5 Testing of the exhaust flue cap and filter device 10 of the present invention reveals a reduction of carbon monoxide emissions of from 20-40% but as high as 70% depending on operating conditions.

Whereas, the present invention has been described in relation to the drawings attached hereto, it should be understood that other and further modifications, apart from
10 those shown or suggested herein, may be made within the spirit and scope of this invention.

WHAT IS CLAIMED IS:

- 1 1. An exhaust flue cap and filter device (10) for a gas fired appliance in communication
2 with an exhaust flue opening having an outer pipe (13) and a coaxial liner (14), which device
3 comprises:
4 a tubular cap (16) with an open lower end (18), an opposed open upper end (20), and
5 a plurality of ventilation holes (22), said cap receivable over said exhaust flue opening;
6 a filter tray (40) having a smaller diameter than said tubular cap (16) and a ledge (44)
7 extending radially inward from said tray;
8 a removable top (24) attached to and closing said open upper end (20) of said tubular
9 cap (16);
10 a removable filter insert (50) within said tubular cap (16) supported on said ledge
11 (44); and
12 an inner collar (54) to engage said exhaust flue opening outer pipe (13).
- 1 2. An exhaust flue cap and filter device (10) as set forth in Claim 1 wherein said inner
2 collar (54) includes at least one stop tab (48) which engages said exhaust flue opening.
- 1 3. An exhaust flue cap and filter device (10) as set forth in Claim 1 wherein removable
2 top (24) is attached to said tubular cap by fasteners (26).
- 1 4. An exhaust flue cap and filter device (10) as set forth in Claim 1 wherein said
2 tubular cap and said removable top (24) are each fabricated from flat sheet metal.

1 5. An exhaust flue cap and filter device (10) as set forth in Claim 1 wherein said
2 removable top (24) includes an outwardly extending rain flange (28).

1 6. An exhaust flue cap and filter device (10) as set forth in Claim 1 wherein said tubular
2 cap (16) has a cross-section from the group consisting of an octagon, a hexagon, a square,
3 a rectangle, an oval, or a circle.

1 7. An exhaust flue cap and filter device (10) for a flue opening as set forth in Claim 1
2 wherein said filter insert (50) is a catalytically active converter.

1 8. An exhaust flue cap and filter device (10) for a flue opening as set forth in Claim 7
2 wherein said catalytically active converter includes a core or substrate and a washcoat
3 including catalytically active metals.

1 9. An exhaust flue cap and filter device (10) for a flue opening as set forth in Claim 8
2 wherein said core or substrate is a ceramic honeycomb structure with gas flow passages.

1 10. An exhaust flue cap and filter device (10) for a flue opening as set forth in Claim 8
2 wherein said core or substrate is at least one wire screen.

1 11. An exhaust flue cap and filter device (10) for a flue opening as set forth in Claim 8
2 wherein said core or substrate is a metal foam.

1 12. An exhaust flue cap and filter device (10) for a flue opening as set forth in Claim 8
2 wherein said washcoat and catalyst are applied to a surface of said core or substrate.

1 13. An exhaust flue cap and filter device (10) for a flue opening as set forth in Claim 1
2 wherein said filter tray (40) includes an outwardly flared skirt (42).

1 14. An exhaust flue cap and filter device (10) for a gas fired appliance in communication
2 with an exhaust flue opening having an outer pipe (13) and a coaxial liner (14), which device
3 comprises:

4 a tubular cap (16) fabricated from sheet metal with an open lower end (18) and an
5 open upper end (20);

6 a plurality of ventilation slots (22) in said tubular cap (16) to permit air flow
7 therethrough;

8 a removable top (24) attached to said open upper end (20) of said tubular cap by
9 fasteners (26);

10 a removable catalytic converter filter insert (50);

11 a filter tray (40) suspended within said tubular cap (24) with at least one ledge
12 support (44) extending from said cap to hold said filter insert (50) within said tubular cap
13 (24); and

14 an inner collar (54) suspended within said tubular cap (16) to receive said outer pipe
15 (13) of said exhaust flue opening.

1 15. An exhaust flue cap and filter device (10) as set forth in Claim 14 wherein said inner
2 collar (54) includes stop tabs (48) which engage said exhaust flue opening.

1 16. An exhaust flue cap and filter device (10) as set forth in Claim 14 wherein said
2 removable top (24) includes an outwardly extending rain flange (28).

1 17. An exhaust flue cap and filter device (10) as set forth in Claim 14 wherein said
2 tubular cap (16) has a cross-section in a form chosen from the group consisting of an
3 octagon, a hexagon, a square, a rectangle, an oval, or a circle.

1 18. A process to treat carbon monoxide and unburned hydrocarbon emissions from a gas
2 fired appliance in communication with an exhaust flue opening, which process comprises:
3 passing exhaust gases from said gas fired appliance through the exhaust flue opening
4 into a tubular cap (16) with an open lower end (18), an opposed upper end (20), and a
5 plurality of ventilation holes (22);
6 permitting atmospheric air to pass into said tubular cap (16) through said open lower
7 end (18);
8 permitting said exhaust gases and said atmospheric air in said tubular cap (16) to
9 pass into and through a catalytic filter insert (50) supported within said tubular cap (16);
10 treating said exhaust gases with said filter insert (50); and
11 permitting passage of said treated gases from within said removable top (24) through
12 a plurality of ventilation holes (22) in said removable top.

1 19. A process to treat emissions as set forth in Claim 18 wherein said filter insert (50)
2 is a catalytic converter and wherein said step of treating emissions includes promoting
3 oxidation with said catalytic converter.




FIG. 4






FIG. 2

