



US00RE48417E

(19) **United States**
(12) **Reissued Patent**
Marks et al.

(10) **Patent Number:** **US RE48,417 E**
(45) **Date of Reissued Patent:** **Feb. 2, 2021**

(54) **OBJECT DIRECTION USING VIDEO INPUT COMBINED WITH TILT ANGLE INFORMATION**

(71) Applicant: **Sony Interactive Entertainment Inc.,**
Tokyo (JP)

(72) Inventors: **Richard Marks,** Pleasanton, CA (US);
Gary M. Zalewski, Piedmont, CA (US)

(73) Assignee: **Sony Interactive Entertainment Inc.,**
Tokyo (JP)

(21) Appl. No.: **15/210,816**

(22) Filed: **Jul. 14, 2016**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **8,781,151**
Issued: **Jul. 15, 2014**
Appl. No.: **11/840,170**
Filed: **Aug. 16, 2007**

U.S. Applications:

(63) Continuation-in-part of application No. 11/536,559,
filed on Sep. 28, 2006, now Pat. No. 8,310,656.

(51) **Int. Cl.**
A63F 13/42 (2014.01)
A63F 13/211 (2014.01)
(Continued)

(52) **U.S. Cl.**
CPC **A63F 13/42** (2014.09); **A63F 13/211**
(2014.09); **A63F 13/213** (2014.09);
(Continued)

(58) **Field of Classification Search**
CPC **A63F 13/06**; **A63F 13/10**; **A63F 13/211**;
A63F 13/42; **A63F 2300/1006**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,270,564 A 9/1966 Evans
3,561,272 A 2/1971 Davis
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0353200 1/1990
EP 0652686 5/1995 H04R 1/40
(Continued)

OTHER PUBLICATIONS

ADXL202/ADXL210 Datasheet, Rev. B, Analog Devices, Inc.,
1999.*

(Continued)


Primary Examiner — Eric B. Kiss

(74) *Attorney, Agent, or Firm* — Penilla IP, APC

(57) **ABSTRACT**

A method for use in obtaining input data from an object includes capturing a live image of the object with an image capture device, receiving information related to a tilt angle of the object from one or more sensors other than the image capture device, using the information related to a tilt angle of the object to obtain at least one rotated reference image of the object, comparing the live image of the object with the rotated reference image of the object, and generating an indication in response to the live image matching the rotated reference image. An apparatus and a storage medium storing a computer program executable by a processor based system are also disclosed

43 Claims, 19 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

6,101,289	A	8/2000	Kellner	6,580,414	B1	6/2003	Wergen et al.	
6,102,803	A	8/2000	Takeda et al.	6,580,415	B1	6/2003	Kato et al.	
6,115,052	A	9/2000	Freeman et al.	6,587,573	B1	7/2003	Stam et al.	
6,134,346	A	10/2000	Berman et al.	6,587,835	B1	7/2003	Treyz et al.	
6,144,367	A	11/2000	Berstis	6,593,956	B1	7/2003	Potts et al.	
6,146,278	A	11/2000	Kobayashi	6,595,642	B2	7/2003	Wirth	
6,151,009	A	11/2000	Kanade et al.	6,597,342	B1	7/2003	Haruta	
6,157,368	A	12/2000	Fager	6,611,141	B1	8/2003	Schulz et al.	G01C 21/165
6,160,540	A	12/2000	Fishkin et al.					324/207.12
6,166,744	A	12/2000	Jaszlics et al.	6,621,938	B1	9/2003	Tanaka et al.	
6,173,059	B1	1/2001	Huang et al.	6,628,265	B2	9/2003	Hwang	
6,173,610	B1	1/2001	Pace	6,661,914	B2	12/2003	Dufour	
6,175,343	B1	1/2001	Mitchell et al.	6,668,244	B1	12/2003	Rourke et al.	
6,184,863	B1	2/2001	Sibert et al.	6,674,415	B2	1/2004	Nakamura et al.	
6,191,773	B1	2/2001	Maruno et al.	6,676,522	B2	1/2004	Rowe et al.	
6,195,104	B1	2/2001	Lyons	6,677,967	B2	1/2004	Swano et al.	
6,203,432	B1	3/2001	Roberts et al.	6,677,987	B1	1/2004	Girod	
6,215,898	B1	4/2001	Woodfill et al.	6,692,359	B1	2/2004	Williams et al.	
6,243,054	B1	6/2001	DeLuca	6,699,123	B2	3/2004	Matsuura et al.	
6,243,074	B1	6/2001	Fishkin et al.	6,709,108	B2	3/2004	Levine et al.	
6,243,491	B1	6/2001	Andersson	6,712,703	B2	3/2004	Miyamoto et al.	
6,259,431	B1	7/2001	Futatsugi et al.	6,720,949	B1	4/2004	Pryor et al.	
6,275,213	B1	8/2001	Tremblay et al.	6,727,988	B2	4/2004	Kim et al.	
6,281,930	B1	8/2001	Parker et al.	6,741,741	B2	5/2004	Farrell	
6,282,362	B1	8/2001	Murphy et al.	6,746,124	B2	6/2004	Fischer et al.	
6,295,064	B1	9/2001	Yamaguchi	6,747,632	B2	6/2004	Howard	
6,297,838	B1	10/2001	Chang et al.	6,749,510	B2	6/2004	Giobbi	
6,304,267	B1	10/2001	Sata	6,751,338	B1	6/2004	Wallack	
6,307,549	B1	10/2001	King et al.	6,753,849	B1	6/2004	Curran et al.	
6,307,568	B1	10/2001	Rom	6,766,036	B1	7/2004	Pryor	
6,323,839	B1	11/2001	Fukuda et al.	6,767,282	B2	7/2004	Matsuyama et al.	
6,323,942	B1	11/2001	Bamji	6,769,769	B2	8/2004	Podoleanu et al.	
6,324,296	B1	11/2001	McSheery	6,772,057	B2	8/2004	Breed et al.	
6,326,901	B1	12/2001	Gonzales	6,774,939	B1	8/2004	Peng	
6,327,073	B1	12/2001	Yahav et al.	6,785,329	B1	8/2004	Pan et al.	
6,331,911	B1	12/2001	Manassen et al.	6,789,967	B1	9/2004	Forester	
6,338,485	B1	1/2002	Huettinger	6,791,531	B1	9/2004	Johnston et al.	
6,346,929	B1	2/2002	Fukushima et al.	6,795,068	B1	9/2004	Marks	
6,351,661	B1	2/2002	Cosman	6,809,776	B1	10/2004	Simpson et al.	
6,352,516	B1	3/2002	Pozos et al.	6,811,491	B1	11/2004	Levenberg et al.	
6,371,849	B1	4/2002	Togami	6,819,318	B1	11/2004	Geng	
6,375,572	B1	4/2002	Masuyama	6,846,238	B2	1/2005	Wells	
6,392,644	B1	5/2002	Miyata et al.	6,847,311	B2	1/2005	Li	
6,393,142	B1	5/2002	Swain et al.	6,850,221	B1	2/2005	Tickle	
6,394,897	B1	5/2002	Togami	6,863,609	B2	3/2005	Okuda et al.	
6,400,374	B2	6/2002	Lanier	6,870,526	B2	3/2005	Zngfet et al.	
6,409,602	B1	6/2002	Wiltshire et al.	6,873,747	B2	3/2005	Askary	
6,411,392	B1	6/2002	Bender et al.	6,881,147	B2	4/2005	Naghi et al.	
6,411,744	B1	6/2002	Edwards	6,884,171	B2	4/2005	Eck et al.	
6,417,836	B1	7/2002	Kumar et al.	6,890,262	B2	5/2005	Oishi et al.	
6,441,745	B1	8/2002	Gates	6,912,464	B1 *	6/2005	Parker	G01C 21/005
6,441,825	B1	8/2002	Peters					701/500
6,450,820	B1	9/2002	Palsson et al.	6,917,688	B2	7/2005	Yu et al.	
6,473,516	B1	10/2002	Kawaguchi et al.	6,919,824	B2	7/2005	Lee	
6,489,946	B1	12/2002	Takeda et al.	6,924,787	B2	8/2005	Kramer et al.	
6,489,948	B1	12/2002	Lau	6,928,180	B2	8/2005	Stam et al.	
6,498,628	B2 *	12/2002	Iwamura	6,930,725	B1	8/2005	Hayashi	348/734
6,498,860	B1	12/2002	Sasaki et al.	6,931,125	B2	8/2005	Smallwood	
6,501,258	B1	12/2002	Levitt et al.	6,931,596	B2	8/2005	Gutta et al.	
6,504,535	B1	1/2003	Edmark	6,943,776	B2	9/2005	Ehrenburg	
6,513,160	B2	1/2003	Dureau	6,945,653	B2	9/2005	Kobori et al.	
6,515,669	B1	2/2003	Mohri	6,947,576	B2	9/2005	Stam et al.	
6,516,466	B1	2/2003	Jackson	6,951,515	B2	10/2005	Ohshima et al.	
6,519,359	B1	2/2003	Nafis et al.	6,952,198	B2	10/2005	Hansen	
6,533,420	B1	3/2003	Eichenlaub	6,965,362	B1	11/2005	Ishizuka	
6,542,927	B2	4/2003	Rhoads	6,970,183	B1	11/2005	Monroe	
6,544,124	B2	4/2003	Ireland et al.	6,990,639	B2	1/2006	Wilson	
6,545,661	B1	4/2003	Goschy et al.	7,006,009	B2	2/2006	Newman	
6,545,706	B1	4/2003	Edwards et al.	7,016,411	B2	3/2006	Azuma et al.	
6,546,153	B1	4/2003	Hoydal	7,016,532	B2	3/2006	Boncyk et al.	
6,556,704	B1	4/2003	Chen	7,023,475	B2	4/2006	Bean et al.	
6,559,813	B1	5/2003	DeLuca	7,030,856	B2	4/2006	Dawson et al.	
6,567,071	B1	5/2003	Curran et al.	7,039,199	B2	5/2006	Rui	
6,573,883	B1	6/2003	Bartlett	7,039,253	B2	5/2006	Matsuoka et al.	
6,577,748	B2	6/2003	Chang	7,042,440	B2	5/2006	Pryor et al.	
				7,043,056	B2	5/2006	Edwards et al.	
				7,054,452	B2	5/2006	Ukita	
				7,059,962	B2	6/2006	Watashiba	
				7,061,507	B1	6/2006	Tuomi et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

7,071,914	B1	7/2006	Marks	8,072,424	B2	12/2011	Liberty
7,084,887	B1	8/2006	Sato et al.	8,096,880	B2	1/2012	Jawad et al.
7,090,352	B2	8/2006	Kobor et al.	8,179,366	B2	5/2012	Richardson et al.
7,098,891	B1	8/2006	Pryor	8,310,656	B2	11/2012	Zalewski
7,102,615	B2	9/2006	Marks	8,313,380	B2	11/2012	Zalewski et al.
7,106,366	B2	9/2006	Parker et al.	8,570,378	B2	10/2013	Zalewski et al.
7,113,635	B2	9/2006	Robert et al.	2001/0011995	A1	3/2001	Hinckley et al.
7,116,330	B2	10/2006	Marshall et al.	2001/0024973	A1	9/2001	Meredith
7,116,342	B2	10/2006	Dengler et al.	2001/0056477	A1	12/2001	McTernan et al.
7,121,946	B2	10/2006	Paul et al.	2002/0010655	A1	1/2002	Kjallstrom
7,139,767	B1	11/2006	Taylor et al.	2002/0022519	A1	2/2002	Ogino
7,148,922	B2	12/2006	Shimada	2002/0023027	A1	2/2002	Simonds
7,156,311	B2	1/2007	Attia et al.	2002/0024500	A1	2/2002	Howard
7,158,118	B2	1/2007	Liberty	2002/0036617	A1	3/2002	Pryor
7,161,634	B2	1/2007	Long	2002/0041327	A1	4/2002	Hildreth et al.
7,164,413	B2	1/2007	Davis et al.	2002/0056114	A1	5/2002	Fillebrown et al.
7,168,042	B2	1/2007	Braun et al.	2002/0061739	A1	5/2002	Nakamura et al.
7,174,312	B2	2/2007	Harper et al.	2002/0071036	A1	6/2002	Gonzales et al.
7,182,691	B1	2/2007	Schena	2002/0072414	A1	6/2002	Stylinski et al.
7,183,929	B1	2/2007	Antebi et al.	2002/0075286	A1	6/2002	Yonezawa et al.
7,193,607	B2	3/2007	Moore et al.	2002/0083461	A1	6/2002	Hutcheson et al.
7,212,308	B2	5/2007	Morgan	2002/0085097	A1	7/2002	Colmenarez et al.
7,223,173	B2	5/2007	Masuyama et al.	2002/0089412	A1	7/2002	Heger et al.
7,224,384	B1	5/2007	Iddan et al.	2002/0094189	A1	7/2002	Navab et al.
7,227,526	B2	6/2007	Hildreth et al.	2002/0110273	A1	8/2002	Dufour
7,227,976	B1	6/2007	Jung et al.	2002/0126899	A1	9/2002	Farrell
7,233,316	B2	6/2007	Smith et al.	2002/0134151	A1	9/2002	Naruoka et al.
7,239,301	B2	7/2007	Liberty et al.	2002/0158873	A1	10/2002	Williamson
7,245,273	B2	7/2007	Eberl et al.	2002/0171622	A1	11/2002	Shen et al.
7,259,375	B2	8/2007	Tichit et al.	2002/0171625	A1	11/2002	Rothchild
7,260,221	B1	8/2007	Atsmon	2003/0014212	A1	1/2003	Ralston et al.
7,262,760	B2	8/2007	Liberty	2003/0020718	A1	1/2003	Marshall et al.
7,263,462	B2	8/2007	Funge et al.	2003/0022716	A1	1/2003	Park et al.
7,274,305	B1	9/2007	Lutrell	2003/0032466	A1	2/2003	Watashiba
7,283,679	B2	10/2007	Okada et al.	2003/0032484	A1	2/2003	Ohshima et al.
7,296,007	B1	11/2007	Funge et al.	2003/0034961	A1	2/2003	Kao
7,301,530	B2	11/2007	Lee et al.	2003/0038778	A1	2/2003	Noguera
7,301,547	B2	11/2007	Martins et al.	2003/0063065	A1	4/2003	Lee et al.
7,305,114	B2	12/2007	Wolff et al.	2003/0064712	A1	4/2003	Gaston et al.
7,339,580	B2	3/2008	Westerman et al.	2003/0073492	A1	4/2003	Tosaki et al.
7,346,387	B1	3/2008	Wachter et al.	2003/0092493	A1	5/2003	Shimizu et al.
7,352,358	B2	4/2008	Zalewski et al.	2003/0093591	A1	5/2003	Hohl
7,352,359	B2	4/2008	Zalewski et al.	2003/0096650	A1	5/2003	Eguchi et al.
7,364,297	B2	4/2008	Goldfain et al.	2003/0100363	A1	5/2003	Ali
7,379,559	B2	5/2008	Wallace et al.	2003/0128187	A1	6/2003	Strubbe
7,391,409	B2	6/2008	Zalewski et al.	2003/0123705	A1	7/2003	Stam et al.
7,414,611	B2	8/2008	Liberty	2003/0160862	A1	8/2003	Charlier et al.
7,432,910	B2	10/2008	Shahoian	2003/0169233	A1	9/2003	Hansen
7,436,887	B2	10/2008	Yeredor et al.	2003/0193572	A1	10/2003	Wilson et al.
7,446,650	B2	11/2008	Scholfield et al.	2003/0232649	A1	12/2003	Gizis et al.
7,489,298	B2	2/2009	Liberty et al.	2004/0001082	A1	1/2004	Said
7,489,299	B2	2/2009	Liberty et al.	2004/0017355	A1	1/2004	Shim
7,545,926	B2	6/2009	Mao	2004/0023736	A1	2/2004	Cardinale
7,555,157	B2	6/2009	Davidson et al.	2004/0029640	A1	2/2004	Masuyama et al.
7,558,432	B2	7/2009	Zaharia et al.	2004/0035925	A1	2/2004	Wu et al.
7,558,698	B2	7/2009	Funge et al.	2004/0046736	A1	3/2004	Pryor et al.
7,565,295	B1	7/2009	Hernandez-Rebollar	2004/0047464	A1	3/2004	Yu et al.
7,613,610	B1	11/2009	Zimmerman et al.	2004/0051680	A1*	3/2004	Azuma G03B 13/28 345/8
7,623,115	B2	11/2009	Marks	2004/0054512	A1	3/2004	Kim et al.
7,627,139	B2	12/2009	Marks et al.	2004/0063480	A1	4/2004	Wang
7,636,645	B1	12/2009	Yen et al.	2004/0063481	A1	4/2004	Wang
7,636,697	B1	12/2009	Dobson et al.	2004/0063502	A1	4/2004	Hussaini et al.
7,636,701	B2	12/2009	Funge et al.	2004/0070564	A1	4/2004	Dawson et al.
7,646,372	B2	1/2010	Marks et al.	2004/0070565	A1	4/2004	Nayar et al.
7,665,041	B2	2/2010	Wilson et al.	2004/0087366	A1	5/2004	Shum et al.
7,697,700	B2	4/2010	Mao	2004/0095327	A1	5/2004	Lo
7,721,231	B2	5/2010	Wilson	2004/0104891	A1	6/2004	Sacca et al.
7,737,944	B2	6/2010	Harrison et al.	2004/0140955	A1	7/2004	Metz
7,774,155	B2*	8/2010	Sato A63F 13/06 345/156	2004/0150728	A1	8/2004	Ogino
7,782,297	B2*	8/2010	Zalewski et al. 345/156	2004/0155962	A1	8/2004	Marks
7,826,641	B2	11/2010	Mandella et al.	2004/0174473	A1	9/2004	Cavanaugh et al.
7,843,429	B2	11/2010	Pryor	2004/0178576	A1	9/2004	Hillis et al.
7,850,526	B2*	12/2010	Zalewski et al. 463/36	2004/0180720	A1	9/2004	Nashi et al.
7,918,733	B2	4/2011	Zalewski et al.	2004/0189720	A1	9/2004	Wilson et al.
				2004/0204240	A1	10/2004	Barney
				2004/0207597	A1	10/2004	Marks
				2004/0213419	A1	10/2004	Varma et al.
				2004/0222970	A1	11/2004	Martinez et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2004/0227725 A1 11/2004 Calarco et al.
 2004/0239670 A1 12/2004 Marks
 2004/0240542 A1 12/2004 Yeredor et al.
 2004/0254017 A1 12/2004 Cheng
 2004/0266528 A1 12/2004 Wang
 2005/0009605 A1 1/2005 Rosenberg et al.
 2005/0026684 A1 2/2005 Sumi et al.
 2005/0037844 A1 2/2005 Shum et al.
 2005/0047611 A1 3/2005 Mao
 2005/0054457 A1 3/2005 Eyestone et al.
 2005/0059488 A1 3/2005 Larsen
 2005/0064936 A1 3/2005 Pryor
 2005/0075167 A1 4/2005 Beaulieu et al.
 2005/0085298 A1 4/2005 Woolston
 2005/0088369 A1 4/2005 Yoshioka
 2005/0102374 A1 5/2005 Moragne et al.
 2005/0105777 A1 5/2005 Kozlowski et al.
 2005/0117045 A1 6/2005 Abdellatif et al.
 2005/0157204 A1 7/2005 Marks
 2005/0162384 A1 7/2005 Yokoyama
 2005/0162385 A1 7/2005 Yokoyama
 2005/0174324 A1 8/2005 Liberty et al.
 2005/0181878 A1 8/2005 Danieli et al.
 2005/0198095 A1 9/2005 Du et al.
 2005/0215320 A1 9/2005 Koay et al.
 2005/0226431 A1 10/2005 Mao
 2005/0239548 A1 10/2005 Ueshima et al.
 2005/0282603 A1 12/2005 Parrott et al.
 2006/0025229 A1 2/2006 Mahajan et al.
 2006/0033713 A1 2/2006 Pryor
 2006/0035710 A1 2/2006 Festejo et al.
 2006/0038819 A1 2/2006 Festejo et al.
 2006/0126900 A1 6/2006 Mihara et al.
 2006/0139322 A1 6/2006 Marks
 2006/0143571 A1 6/2006 Chan
 2006/0166738 A1 7/2006 Eyestone et al.
 2006/0183546 A1 8/2006 Addington et al.
 2006/0204012 A1 9/2006 Marks
 2006/0227211 A1 10/2006 Kotake
 2006/0233389 A1 10/2006 Mao
 2006/0239471 A1 10/2006 Mao
 2006/0252474 A1 11/2006 Zalewski
 2006/0252475 A1 11/2006 Zalewski
 2006/0252477 A1 11/2006 Zalewski
 2006/0252541 A1 11/2006 Zalewski et al.
 2006/0252543 A1 11/2006 Van Noland et al.
 2006/0256081 A1 11/2006 Zalewski
 2006/0264258 A1 11/2006 Zalewski et al.
 2006/0264259 A1* 11/2006 Zalewski et al. 463/36
 2006/0264260 A1 11/2006 Zalewski
 2006/0269072 A1 11/2006 Mao
 2006/0269073 A1 11/2006 Mao
 2006/0274032 A1 12/2006 Mao et al.
 2006/0274911 A1 12/2006 Mao
 2006/0277571 A1 12/2006 Marks
 2006/0280312 A1 12/2006 Mao
 2006/0281550 A1 12/2006 Schena
 2006/0282873 A1 12/2006 Zalewski
 2006/0287084 A1 12/2006 Mao
 2006/0287085 A1 12/2006 Mao
 2006/0287086 A1 12/2006 Zalewski
 2006/0287087 A1 12/2006 Zalewski
 2007/0015558 A1 1/2007 Zalewski
 2007/0015559 A1 1/2007 Zalewski
 2007/0021208 A1 1/2007 Mao
 2007/0025562 A1 2/2007 Zalewski
 2007/0060336 A1 3/2007 Marks et al.
 2007/0061413 A1 3/2007 Larsen
 2007/0066394 A1 3/2007 Ikeda et al.
 2007/0072675 A1 3/2007 Hamano et al.
 2007/0120834 A1 5/2007 Boillot
 2007/0120996 A1 5/2007 Boillot
 2007/0260340 A1 11/2007 Mao et al.
 2007/0260517 A1 11/2007 Zalewski
 2007/0261077 A1 11/2007 Zalewski

2007/0270215 A1 11/2007 Miyamoto et al.
 2007/0270217 A1 11/2007 Rabin
 2007/0293317 A1 12/2007 Sato et al.
 2008/0056561 A1 3/2008 Sawachi
 2008/0070684 A1 3/2008 Haigh-Hutchinson
 2008/0091421 A1 4/2008 Gustavsson
 2008/0208613 A1 8/2008 Scibora
 2009/0010494 A1 1/2009 Bechtel et al.
 2009/0016642 A1 1/2009 Hart
 2009/0067291 A1 3/2009 Atsmon et al.
 2009/0118012 A1 5/2009 Sternberg
 2009/0221368 A1 9/2009 Yen et al.
 2009/0221374 A1 9/2009 Yen et al.
 2009/0288064 A1 11/2009 Yen et al.
 2010/0004896 A1 1/2010 Yen et al.
 2010/0137064 A1 6/2010 Shum et al.
 2011/0074669 A1 3/2011 Marks et al.
 2011/0077082 A1 3/2011 Marks et al.
 2011/0118021 A1 5/2011 Zalewski et al.

FOREIGN PATENT DOCUMENTS

EP 0750202 12/1996 G01S 17/00
 EP 0750202 5/1998
 EP 0867798 9/1998
 EP 0613294 10/1998
 EP 1098686 5/1999
 EP 1074934 2/2001
 EP 1176559 A2 1/2002
 EP 1180384 2/2002
 EP 1206950 5/2002
 EP 0652686 8/2002
 EP 1279425 1/2003
 EP 1306112 5/2003
 EP 0869458 7/2003
 EP 1335338 8/2003
 EP 1358918 11/2003
 EP 1402929 3/2004
 EP 1411461 4/2004
 EP 1435258 7/2004 A63F 13/04
 EP 1435258 9/2004
 EP 0835676 10/2004
 EP 0823683 7/2005
 EP 1553486 A1 7/2005
 EP 1489596 9/2006
 EP 1033882 9/2009
 EP 1449358 2/2011
 FR 2780176 6/1998
 FR 2814965 4/2002
 FR 2832892 4/2004
 GB 2206716 1/1989
 GB 2388418 A 3/2002
 GB 2376397 12/2002
 GB 2398691 A 8/2004
 JP 1138949 5/1989
 JP 1284897 11/1989
 JP 6-198075 A 7/1994
 JP 6102980 12/1994
 JP 9128141 5/1997
 JP 9185456 7/1997
 JP 9265346 10/1997
 JP 2000-123186 A 4/2000
 JP 2000-172431 6/2000 G06F 3/033
 JP 2000-259340 9/2000
 JP 2000/259856 9/2000
 JP 2000/350859 12/2000
 JP 2001-166676 6/2001 G09B 9/00
 JP 2001-170358 A 6/2001
 JP 2002-306846 A 10/2002
 JP 2002306846 10/2002
 JP 2002320773 11/2002
 JP 2002/369969 12/2002
 JP 2003-78779 A 3/2003
 JP 2003-126548 A 5/2003
 JP 2003135851 5/2003
 JP 2003-236244 A 8/2003
 JP 2004-145448 5/2004 G06T 17/40
 JP 2004-336740 A 11/2004
 JP 2005/046422 2/2005

(56)

References Cited

FOREIGN PATENT DOCUMENTS

JP	2006-509548 A	3/2006	
JP	2006-99468 A	4/2006	
JP	2011-045780	3/2011	
WO	88/05942	8/1988	
WO	98/48571	4/1997	
WO	99/35633	1/1999	
WO	99/26198	5/1999	
WO	99/26198	10/1999	
WO	WO 99/26198	10/1999	
WO	01/18563	3/2001	
WO	WO 02/27456	2/2002 G06F 3/00
WO	02/052496	7/2002	
WO	WO 3/079179	9/2003 G06F 3/033
WO	2004/041379 A2	5/2004	
WO	2004073814	9/2004	
WO	2004073815	9/2004	
WO	2005073838 A2	8/2005	
WO	2005/107911	11/2005	
WO	2005113086 A1	12/2005	
WO	2006/121896	11/2006	
WO	2007/095082	8/2007	
WO	2008056180 A2	5/2008	

OTHER PUBLICATIONS

USPTO; Office Action issued in U.S. Appl. No. 11/536,559; mailed Jun. 30, 2008; 8 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,034; mailed Aug. 4, 2008; 14 pages.

Patent Cooperation Treaty; "International Search Report" issued in PCT/US07/67367, which corresponds to U.S. Appl. Nos. 11/382,034; 11/382,037; 11/382,039; mailed Jun. 3, 2008; 2 pages.

Patent Cooperation Treaty; "Written Opinion of the International Searching Authority" issued in PCT/US07/67367, which corresponds to U.S. Appl. Nos. 11/382,034; 11/382,037; 11/382,039; mailed Jun. 3, 2008; 5 pages.

Patent Cooperation Treaty; "Notification Concerning Transmittal of the International Search Report and the Written Opinion of the International Searching Authority or the Declaration" issued in PCT/US07/67367, which corresponds to U.S. Appl. Nos. 11/382,034; 11/382,037; 11/382,039; mailed Jun. 3, 2008; 2 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,034; mailed Mar. 9, 2009; 28 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,037; mailed Oct. 2, 2008; 6 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,043; mailed Sep. 4, 2008; 15 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,043; mailed Feb. 9, 2009; 20 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,039; mailed Oct. 1, 2008; 6 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,259; mailed Sep. 15, 2008; 15 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,259; mailed Mar. 25, 2009; 17 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,258; mailed Sep. 17, 2008; 11 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,258; mailed Mar. 19, 2009; 14 pages.

Patent Cooperation Treaty; "International Search Report" issued in PCT/US07/67697, which corresponds to U.S. Pub. No. 2007/0015558A1; mailed Sep. 15, 2008; 3 pages.

Patent Cooperation Treaty; "Written Opinion of the International Searching Authority" issued in PCT/US07/67697, which corresponds to U.S. Pub. No. 2007/0015558A1; mailed Sep. 15, 2008; 7 pages.

Patent Cooperation Treaty; "Notification Concerning Transmittal of the International Search Report and the Written Opinion of the International Searching Authority or the Declaration" issued in

PCT/US07/67697, which corresponds to U.S. Pub. No. 2007/0015558A1; mailed Sep. 15, 2008; 1 page.

Patent Cooperation Treaty; "International Search Report" issued in PCT/US07/67961, which corresponds to U.S. Pub. No. 2006/0282873A1; mailed Sep. 16, 2008; 2 pages.

Patent Cooperation Treaty; "Written Opinion of the International Searching Authority" issued in PCT/US07/67961, which corresponds to U.S. Pub. No. 2006/0282873A1; mailed Sep. 16, 2008; 3 pages.

Patent Cooperation Treaty; "Notification Concerning Transmittal of the International Search Report and the Written Opinion of the International Searching Authority or the Declaration" issued in PCT/US07/67961, which corresponds to U.S. Pub. No. 2006/0282873A1; mailed Sep. 16, 2008; 1 page.

USPTO; Final Office Action issued in U.S. Appl. No. 11/536,559; mailed Sep. 15, 2008; 8 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/536,559; mailed Mar. 2, 2009; 8 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/624,637; mailed Oct. 1, 2008; 9 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,699; mailed Sep. 23, 2008; 11 pages.

Gary Zalewski; "Method and Apparatus for Tracking Three-Dimensional Movements of an Object Using a Depth Sensing Camera"; U.S. Appl. No. 12/262,044, filed Oct. 30, 2008; 76 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,250; mailed Jul. 22, 2008; 11 pages.

Patent Cooperation Treaty; "International Search Report" issued in PCT/US08/73196, which corresponds to U.S. Pub. No. 2008/0080789A1, U.S. Appl. No. 11/840,170; mailed Nov. 7, 2008; 2 pages.

Patent Cooperation Treaty; "Written Opinion of the International Searching Authority" issued in PCT/US08/73196, which corresponds to U.S. Pub. No. 2008/0080789A1, U.S. Appl. No. 11/840,170; mailed Nov. 7, 2008; 4 pages.

Patent Cooperation Treaty; "Notification Concerning Transmittal of the International Search Report and the Written Opinion of the International Searching Authority or the Declaration" issued in PCT/US08/73196, which corresponds to U.S. Pub. No. 2008/0080789A1, U.S. Appl. No. 11/840,170; mailed Nov. 7, 2008; 1 page.

USPTO; Office Action from U.S. Appl. No. 11/382,043; U.S. Pub. No. US-2006-0264260-A1; mailed Feb. 5, 2008; 16 pages.

USPTO; Office Action from U.S. Appl. No. 11/382,699; U.S. Pub. No. US-2007-0265075-A1; mailed Feb. 14, 2008; 15 pages.

USPTO; Office Action from U.S. Appl. No. 11/536,559; mailed Dec. 10, 2007; 6 pages.

Naturalpoint Inc., "NaturalPoint TrackIR, TrackIR Software Version 3.10 Manual", Old TrackIR Manual 3.10, posted on the Internet May 3, 2004, pp. 1-35.

Naturalpoint Inc., "NaturalPoint TrackIR, Users Manual version 4.0.020", TrackIR 3 :: TrackIR Manual 4.0.020, posted on the Internet Jan. 9, 2005, pp. 1-29.

Naturalpoint Inc., "Vector Expansion QuickStart Guide v2", posted on the Internet Jan. 11, 2005, 1 page.

Naturalpoint Inc., "NaturalPoint TrackIR, Users Manual version 4.1.028", TrackIR 4:Pro :: TrackIR Manual 4.1.028, posted on the Internet Nov. 15, 2005, pp. 1-30.

Naturalpoint Inc., "TrackClip PRO Quick Start Guide", posted on the Internet Dec. 12, 2006, 1 page.

Naturalpoint Inc., "TrackIR Newsletter", Newsletters from TrackIR website: <http://www.naturalpoint.com/trackir/04-community/newsletters/>, dated Jan. 2005 through Sep. 2006 (printed from the Internet Mar. 7, 2008), pp. 1-48.

Naturalpoint Inc., "TrackIR : head tracking view control immersion for flight racing and action simulator", Pages from TrackIR website: <http://www.naturalpoint.com/trackir/>, Copyright Jul. 2005 (printed from the Internet Mar. 7, 2008), pp. 1-59.

USPTO; Office Action issued in U.S. Appl. No. 11/382,034; mailed Nov. 13, 2009; 33 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,037; mailed Sep. 29, 2009; 7 pages.

(56)

References Cited

OTHER PUBLICATIONS

- USPTO; Advisory Action issued in U.S. Appl. No. 11/382,043; mailed Dec. 11, 2009; 4 pages.
- European Patent Office; "Extended European Search Report (including the Supplementary European Search Report and the European Search Opinion)" issued in European Application No. EP 07 76 1296 for PCT/US2007/067437; dated Nov. 30, 2009; 8 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/536,559; mailed Oct. 13, 2009; 8 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/536,559; mailed Feb. 26, 2010; 9 pages.
- USPTO; Notice of Allowance issued in U.S. Appl. No. 11/624,637 (Publication No. US 2008-027480 A1) ; mailed Jan. 29, 2010; 6 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,699; mailed Oct. 29, 2009; 11 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/551,197; mailed Mar. 18, 2010; 9 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,039; mailed Dec. 8, 2009; 8 pages.
- USPTO; Notice of Allowance and Fee(s) Due issued in U.S. Appl. No. 11/382,258; mailed Sep. 24, 2009; 7 pages.
- USPTO; Notice of Allowance and Fee(s) Due issued in U.S. Appl. No. 11/382,258; mailed Mar. 30, 2010; 4 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,034; mailed Jun. 16, 2010; 34 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,037; mailed Mar. 31, 2010; 8 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,043; mailed Jun. 23, 2010; 16 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,039; mailed Jun. 8, 2010; 8 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,251; mailed Jun. 21, 2010; 10 pages.
- USPTO; Advisory Action issued in U.S. Appl. No. 11/536,559; mailed Jun. 16, 2010; 3 pages.
- USPTO; Interview Summary issued in U.S. Appl. No. 11/624,637; mailed May 5, 2009; 2 pages.
- USPTO; Interview Summary issued in U.S. Appl. No. 11/382,699; mailed Mar. 29, 2010; 3 pages.
- USPTO; Interview Summary issued in U.S. Appl. No. 11/382,699; mailed Apr. 26, 2010; 3 pages.
- USPTO; Notice on Panel Decision issued in U.S. Appl. No. 11/382,699; mailed May 26, 2010; 2 pages.
- U.S. Appl. No. 11/838,823, filed Aug. 14, 2007, Benoist.
- U.S. Appl. No. 11/624,637, filed Jan. 18, 2007, Harrison.
- U.S. Appl. No. 11/551,682, filed Oct. 20, 2006, Mondesir.
- U.S. Appl. No. 11/551,197, filed Oct. 19, 2006, Mondesir.
- U.S. Appl. No. 11/536,559, filed Sep. 28, 2006, Zalewski.
- U.S. Appl. No. 11/382,699, filed May 10, 2006, Zalewski.
- U.S. Appl. No. 29/259,348, filed May 6, 2006, Zalewski.
- U.S. Appl. No. 29/259,349, filed May 6, 2006, Goto.
- U.S. Appl. No. 29/259,350, filed May 6, 2006, Zalewski.
- U.S. Appl. No. 60/798,031, filed May 6, 2006, Woodard.
- U.S. Appl. No. 11/381,727, filed May 4, 2006, Mao.
- U.S. Appl. No. 11/381,728, filed May 4, 2006, Mao.
- U.S. Appl. No. 11/381,729, filed May 4, 2006, Mao.
- U.S. Appl. No. 11/301,673, filed Dec. 12, 2005, Marks.
- U.S. Appl. No. 60/718,145, filed Sep. 15, 2005, Hernandez-Abrego.
- U.S. Appl. No. 60/678,413, filed May 5, 2005, Marks.
- U.S. Appl. No. 29/246,743, filed May 8, 2006.
- U.S. Appl. No. 29/246,744, filed May 8, 2006.
- U.S. Appl. No. 29/246,759, filed May 8, 2006.
- U.S. Appl. No. 29/246,762, filed May 8, 2006.
- U.S. Appl. No. 29/246,763, filed May 8, 2006.
- U.S. Appl. No. 29/246,764, filed May 8, 2006.
- U.S. Appl. No. 29/246,765, filed May 8, 2006.
- U.S. Appl. No. 29/246,766, filed May 8, 2006.
- U.S. Appl. No. 29/246,767, filed May 8, 2006.
- U.S. Appl. No. 29/246,768, filed May 8, 2006.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,043; mailed Aug. 21, 2009; 14 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/624,637; mailed Sep. 15, 2009; 11 pages.
- Nintendo; "Super Mario 64 Instruction Booklet"; released Jun. 1996; pp. 1-25 plus title pages (all included in the attached 14 page PDF).
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,037; mailed May 11, 2009; 6 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,039; mailed May 6, 2009; 7 pages.
- USPTO; Advisory Action issued in U.S. Appl. No. 11/382,259; mailed Jul. 7, 2009; 9 pages.
- USPTO; Advisory Action issued in U.S. Appl. No. 11/536,559; mailed Jan. 15, 2009; 3 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/624,637; mailed Apr. 6, 2009; 19 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/551,682; mailed May 26, 2009; 10 pages.
- USPTO; Advisory Action issued in U.S. Appl. No. 11/382,699; mailed Mar. 11, 2009; 3 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,699; mailed Apr. 24, 2009; 11 pages.
- USPTO; Advisory Action issued in U.S. Appl. No. 11/382,034; mailed Sep. 21, 2010; 4 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,034; mailed Dec. 23, 2010; 40 pages.
- USPTO; Notice of Allowance issued in U.S. Appl. No. 11/382,037; mailed Sep. 20, 2010; 11 pages.
- USPTO; Supplemental Notice of Allowability issued in U.S. Appl. No. 11/382,037; mailed Nov. 16, 2010; 5 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,043; mailed Oct. 22, 2010; 17 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,039; mailed Nov. 24, 2010; 9 pages.
- USPTO; Notice of Allowance issued in U.S. Appl. No. 11/536,559; mailed Aug. 25, 2010; 4 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/551,197; mailed Sep. 1, 2010; 10 pages.
- Korean Intellectual Property Office; "Notice of Preliminary Rejection" issued in Korean Patent Application No. 10-2009-706674; mailed Oct. 19, 2010; 8 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,699; mailed Aug. 17, 2010; 12 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,034; mailed Jun. 28, 2011; 43 pages.
- USPTO; Notice of Allowance issued in U.S. Appl. No. 11/382,037; mailed Feb. 3, 2011; 6 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,037; mailed May 26, 2011; 6 pages.
- USPTO; Advisory Action issued in U.S. Appl. No. 11/382,043; mailed Jan. 26, 2011; 3 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,043; mailed Apr. 13, 2011; 18 pages.
- USPTO; Supplemental Final Office Action issued in U.S. Appl. No. 11/382,043; mailed Apr. 21, 2011; 18 pages.
- USPTO; Advisory Action issued in U.S. Appl. No. 11/382,039; mailed Feb. 4, 2011; 3 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,039; mailed May 12, 2011; 10 pages.
- EPO; Extended Search Report issued in European Application No. 07797288.3; dated Feb. 21, 2011; 8 pages.
- USPTO; Office Action issued in U.S. Appl. No. 11/382,251; mailed Dec. 8, 2010; 12 pages.
- USPTO; Notice of Allowance issued in U.S. Appl. No. 11/536,559; mailed Jan. 31, 2011; 4 pages.
- USPTO; Notice of Allowance issued in U.S. Appl. No. 11/536,559; mailed May 12, 2011; 5 pages.
- State Intellectual Property Office, P.R. China; First Office Action in Chinese Patent Application No. 200880000845.3, mailed Dec. 21, 2010; 8 pages.
- USPTO; Final Office Action issued in U.S. Appl. No. 11/382,699; mailed Feb. 1, 2011; 12 pages.

(56)

References Cited

OTHER PUBLICATIONS

USPTO; Interview Summary issued in U.S. Appl. No. 11/382,699; mailed Apr. 13, 2011; 3 pages.

Bolt, R.A., "'Put-that-there': voice and gesture at the graphics interface", *Computer Graphics*, vol. 14, No. 3 (ACM SIGGRAPH Conference Proceedings) Jul. 1980, pp. 262-270.

Dewitt, Thomas and Edelstein, Phil, "Pantomation: A System for Position Tracking," *Proceedings of the 2nd Symposium on Small Computers in the Arts*, Oct. 1982, pp. 61-69.

Gvili, et al., "Depth Keying", *SPIE* vol. 5006 (2003), 2003 *SPIE-IS&T*, pp. 564-574 (031).

Hemmi, et al., "3-D Natural Interactive Interface-Using Marker Tracking from a Single View", Sep. 9, 1991, *Systems and Computers in Japan*.

Ephraim et al. "Speech Enhancement Using a Minimum Mean-Square Error Log-Spectral Amplitude Estimator", 1985, *IEEE*.

Ephraim et al. "Speech Enhancement Using a Minimum Mean-Square Error Short-Time Spectral Amplitude Estimator", 1984, *IEEE*.

Richardson et al. "Virtual Network Computing", 1998, *IEEE Internet Computing* vol. 2.

Wilson et al., "Audio-Video Array Source Localization for Intelligent Environments", 2002 *IEEE Dept. of Electrical Eng and Computer Science*, MIT, Cambridge, MA 02139.

Fiala, et al., "A Panoramic Video and Acoustic Beamforming Sensor for Videoconferencing", 2004 *IEEE, Computational Video Group, National Research Council, Ottawa, Canada KIA OR6*.

Kanade, et al., "A Stereo Machine for Video-rate Dense Depth Mapping and Its New Application" 1996, *CVPR 96, IEEE Computer Society Conference*, pp. 196-202 (022).

Nakamura, et al., "A Consideration on Reconstructing 3-D Model Using Object Views", 2004-01601-003, pp. 17-21, *Kokkaido University, Japan, nakamura@media.eng.hokudai.ac.jp*.

Nakagawa, et al., "A Collision Detection and Motion Image Synthesis Between a Background Image and a Foreground 3-Dimensional Object", *TVRSJ Bol.* 4, No. 2, pp. 425-430, 1999, Japan.

Nishida, et al., "A Method of Estimating Human Shapes by Fitting the Standard Human Model to Partial Measured Data", *D-11 vol. J84-D-11*, No. 7, pp. 1310-1318, Jul. 2001.

Mihara, et al., "A Realtime Vision-Based Interface Using Motion Processor and Applications to Robotics", vol. *J84-D-11*, No. 9, pp. 2070-2078, Jan. 9, 2001, Japan.

Klinker, et al., "Distributed User Tracking Concepts for Augmented Reality Applications", pp. 37-44, *Augmented Reality, 2000, IEEE and ACM Int'l Symposium*, Oct. 2000, XP010520308, ISBN: 0-7695-0846-4, Germany.

Jojic, et al., "Tracking Self-occluding Articulated Objects in Dense Disparity Maps", *Computer Vision, 1999, The Proceedings for the Seventh IEEE International Conference on Kerkyra, Greece Sep. 20-27, 1999, Los Alamitos, CA, US, IEEE Computer Society, US*, Sep. 20, 1999, pp. 123-130.

Fujitsu, "Internet Development of Emulators" Abstract, Mar. 1997, vol. 48, No. 2.

Lanier, Jaron, "Virtually there: three-dimensional tele-immersion may eventually bring the world to your desk", *Scientific American*, ISSN: 0036-8733, Year: 2001.

"The Tracking Cube: A Three-Dimensional Input Device", *IBM Technical Disclosure Bulletin*, Aug. 1, 1989, pp. 91-95, No. 3B, IBM Corp. New York, U.S.

K. B. Shimoga, et al., "Touch and Force Reflection for Telepresence Surgery". *Engineering in Medicine and Biology Opportunities of the IEEE*, Baltimore, MD, USA, Nov. 3, 1994, New York, New York, USA, pp. 1049-1050.

Iddan, et al., "3D Imaging in the Studio (And Elsewhere . . .)", *Proceedings of the SPIE, SPIE, Bellingham, VA, US*, vol. 4298, Jan. 24, 2001, pp. 48-55, XP008005351.

XP-002453974, "CFS and FS95/98/2000: How to Use the Trim Controls to Keep Your Aircraft Level", Aug. 10, 2007, <http://support.microsoft.com/?scid=kb%3Ben-us%3B175195&x=13&y=15>.

European Patent Office; App. No. 07251651.1; European Search Report mailed Oct. 18, 2007.

PCT; App. No. PCT/US06/61056; International Search Report and Written Opinion mailed Mar. 3, 2008.

PCT; App. No. PCT/US07/67004; International Search Report and Written Opinion of the International Searching Authority mailed Jul. 28, 2008.

U.S. Appl. No. 11/382,031; Office Action mailed Sep. 30, 2008.

U.S. Appl. No. 11/382,035; Office Action mailed Jul. 25, 2008.

U.S. Appl. No. 11/382,031; Office Action mailed Sep. 2, 2009.

U.S. Appl. No. 11/382,031; Final Office Action mailed Mar. 19, 2009.

U.S. Appl. No. 11/382,035; Office Action mailed May 27, 2009.

U.S. Appl. No. 11/382,035; Final Office Action mailed Jan. 7, 2009.

U.S. Appl. No. 11/382,250; Final Office Action mailed May 1, 2009.

U.S. Appl. No. 11/382,250; Office Action mailed Jan. 22, 2010.

U.S. Appl. No. 11/382,250; Notice of Allowance mailed Sep. 13, 2010.

U.S. Appl. No. 11/382,031; Notice of Allowance mailed Sep. 22, 2010.

Korean Patent Office; Korean App. No. 10-2008-7029704; Notice of Preliminary Rejection mailed Aug. 25, 2010.

Chinese Patent Office; China App. No. 200780016094; First Office Action mailed Aug. 16, 2010.

Korean Patent Office; Korean App. No. 10-2008-7029705; Notice of Preliminary Rejection mailed Aug. 25, 2010.

U.S. Appl. No. 11/382,032; Office Action mailed Sep. 25, 2009.

European Patent Office; App. No. EP 07760946.9; Extended European Search Report mailed Oct. 27, 2010.

Definition of "mount"—*Merriam-Webster Online Dictionary*; downloaded from the Internet <<http://www.M-w.com/dictionary/mountable>>, downloaded on Nov. 8, 2007.

CFS and FS95/98/2000: How to Use the Trim Controls to Keep Your Aircraft Level; downloaded from the Internet <<http://support.microsoft.com/?scid=kb%3Ben-us%3B175195&x=13&y=15>>; downloaded on Aug. 10, 2007.

Dietrich, F., "Real Time Animation Techniques with Microcomputers", *Pixel Creations, University of Michigan Press* 1982, 4 pages.

You, S., "Fusion of Vision and Gyro Tracking for Robust Augmented Reality Registration", *Proceedings IEEE Virtual Reality, 2001*, 8 pages.

USPTO, Final Office Action issued in U.S. Appl. No. 11/382,251 mailed May 25, 2011, 12 pages.

USPTO, Notice of Allowance issued U.S. Appl. No. 11/536,559 mailed Aug. 3, 2011, 5 pages.

USPTO, Notice of Allowance issued in U.S. Appl. No. 11/536,559 mailed Nov. 7, 2011, 5 pages.

USPTO, Office Action issued in U.S. Appl. No. 11/838,823 mailed Sep. 15, 2011, 7 pages.

USPTO, Office Action issued in U.S. Appl. No. 11/382,699 mailed Nov. 9, 2011, 11 pages.

USPTO, Office Action issued in U.S. Appl. No. 12/262,044 mailed Oct. 14, 2011, 10 pages.

USPTO, Office Action issued in U.S. Appl. No. 11/382,251 mailed Nov. 23, 2011, 11 pages.

USPTO, Final Office Action issued in U.S. Appl. No. 11/382,036 mailed Sep. 7, 2011, 26 pages.

Japanese Patent Office, Notification of Reasons for Refusal issued in Japanese Patent Application 2009-509960 dated Nov. 15, 2011, 8 pages.

USPTO, Final Office Action issued in U.S. Appl. No. 11/382,039 mailed Dec. 15, 2011, 7 pages.

USPTO, Final Office Action issued in U.S. Appl. No. 11/382,034 mailed Dec. 23, 2011, 47 pages.

USPTO, Office Action issued in U.S. Appl. No. 11/382,037 mailed Dec. 27, 2011, 5 pages.

Japanese Patent Office, Notification of Reasons for Refusal issued in Japanese Patent Application 2009-509977 dated Jan. 17, 2012, 10 pages.

USPTO, Final Office Action issued in U.S. Appl. No. 12/262,044 mailed Feb. 21, 2012, 9 pages.

USPTO, Notice of Allowance issued in U.S. Appl. No. 11/536,559 mailed Mar. 5, 2012, 5 pages.

(56)

References Cited

OTHER PUBLICATIONS

USPTO, Advisory Action issued in U.S. Appl. No. 11/382,039 mailed Mar. 14, 2012, 2 pages.

USPTO, Final Office Action issued in U.S. Appl. No. 11/838,823 mailed Mar. 28, 2012, 8 pages.

USPTO, Advisory Action issued in U.S. Appl. No. 11/382,039 mailed Mar. 29, 2012, 3 pages.

USPTO; Applicant-Initiated Interview Summary issued in U.S. Appl. No. 11/382,039 mailed Apr. 3, 2012, 3 pages.

USPTO; Advisory Action issued in U.S. Appl. No. 13/004,780, mailed Aug. 6, 2013, 3 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,699, mailed Jul. 25, 2013, 14 pages.

European Patent Office; "Extended European Search Report" issued in European Patent Application No. 12156402.5, dated Jul. 27, 2012, 11 pages.

European Patent Office; "Extended European Search Report" issued in European Patent Application No. 12156589.9, dated Aug. 2, 2012, 6 pages.

Japanese Patent Office; "Notification of Reasons for Refusal" issued in Japanese Patent Application No. 2012-057129, dated Dec. 3, 2013, 8 pages (includes English translation).

Japanese Patent Office; "Notification of Reasons for Refusal" issued in Japanese Patent Application No. 2012-057132, dated Dec. 3, 2013, 4 pages (includes English translation).

USPTO; Office Action issued in U.S. Appl. No. 13/004,780, mailed Dec. 16, 2013, 12 pages.

USPTO; Pending Unpublished U.S. Patent Application by inventor Zalewski, Gary M. et al.; U.S. Appl. No. 14/059,326, filed Oct. 21, 2013, and as amended by Preliminary Amendment filed Nov. 1, 2013; entitled "Method and Apparatus for Tracking Three-Dimensional Movements of an Object Using a Depth Sensing Camera"; 93 pages, which includes the specification, claims, abstract, and drawings as-filed Oct. 21, 2013, and Preliminary Amendment filed Nov. 1, 2013.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,699, mailed Dec. 27, 2012, 13 pages.

Japanese Patent Office; "Decision to Grant a Patent" issued in Japanese Patent Application No. 2009-509960, dated Jun. 11, 2013, 3 pages.

USPTO; Notice of Allowance issued in U.S. Appl. No. 12/262,044, mailed Jun. 21, 2013, 10 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 12/262,044, mailed Nov. 8, 2012, 10 pages.

USPTO; Pending Unpublished U.S. Patent Application by Zalewski, Gary M. et al.; U.S. Appl. No. 14/059,326, filed Oct. 21, 2013, entitled "Method and Apparatus For Tracking Three-Dimensional Movements of an Object Using a Depth Sensing Camera", 77 pages, which includes the application abstract, specification, claims, and drawings.

Japanese Patent Office; "Notification of Reasons for Refusal" issued in Japanese Patent Application No. 2012-120096, dated Jan. 7, 2014, 5 pages (includes English translation).

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,034, mailed Feb. 5, 2013, 44 pages.

Japanese Patent Office; Final Notification of Reasons for Refusal issued in Japanese Patent Application No. 2009-509977, mailed Aug. 14, 2012, 4 pages (includes English translation).

USPTO; Notice of Allowance issued in U.S. Appl. No. 11/382,039, mailed Aug. 29, 2013, 9 pages.

European Patent Office; "Communication pursuant to Rules 70(2) and 70a(2) EPC and reference to Rule 39(1) EPC" issued in European Patent Application No. 12156402.5, dated Sep. 3, 2012, 2 pages.

European Patent Office; "Communication pursuant to Rules 70(2) and 70a(2) EPC and reference to Rule 39(1) EPC" issued in European Patent Application No. 12156589.9, dated Sep. 10, 2012, 2 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,251, mailed Dec. 4, 2012, 12 pages.

USPTO, Advisory Action issued in U.S. Appl. No. 12/262,044 mailed Apr. 26, 2012, 3 pages.

European Patent Office; "Communication pursuant to Article 94(3) EPC" issued in European Patent Application No. 12156402.5; dated May 27, 2013, 5 pages.

European Patent Office; "Extended European Search Report" issued in corresponding European Patent Application No. 08797908.4, dated Jun. 22, 2012, 5 pages.

Japanese Patent Office; Notification of Reasons for Refusal issued in corresponding Japanese Patent Application No. 2010-515294, dated Jun. 26, 2012, 8 pages (includes English translation).

USPTO; Office Action issued in U.S. Appl. No. 11/382,699, mailed Jun. 5, 2012, 12 pages.

European Patent Office; "Communication pursuant to Rules 70(2) and 70a(2) EPC" issued in European Patent Application No. 08797908.4, dated Jul. 10, 2012, 1 page.

USPTO; Office Action issued in U.S. Appl. No. 11/382,034, mailed Jun. 26, 2012, 44 pages.

USPTO; Office Action issued in U.S. Appl. No. 13/004,780, mailed Jun. 27, 2012, 12 pages.

USPTO; Office Action issued in U.S. Appl. No. 12/262,044, mailed Jul. 10, 2012, 8 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 13/004,780, mailed May 10, 2013, 11 pages.

USPTO; Final Office Action issued in U.S. Appl. No. 11/382,251, mailed Jan. 14, 2014, 13 pages.

USPTO; Advisory Action issued in U.S. Appl. No. 12/262,044, mailed Feb. 19, 2013, 3 pages.

USPTO; Office Action issued in U.S. Appl. No. 11/382,699, mailed Apr. 17, 2013, 14 pages.

Japanese Patent Office; Notification of Reasons for Refusal issued in Japanese Patent Application No. 2009-509960, dated Jul. 31, 2012, 7 pages (includes English translation).

USPTO; Notice of Allowance issued in U.S. Appl. No. 11/536,559, mailed Jul. 30, 2012, 5 pages.

USPTO; Notice of Allowance issued in U.S. Appl. No. 11/382,037, mailed Aug. 7, 2012, 8 pages.

US 2002/0018582 A1, 02/2002, Hagiwara et al. (Withdrawn).

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1D




FIG. 1E






FIG. 2B




300

FIG. 3A




320

FIG. 3B



400
FIG. 4



500
FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11A




FIG. 11B




FIG. 12




FIG. 13A




FIG. 13B




FIG. 13C




FIG. 14





FIG. 15






FIG. 16

**OBJECT DIRECTION USING VIDEO INPUT
COMBINED WITH TILT ANGLE
INFORMATION**

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue; a claim printed with strikethrough indicates that the claim was canceled, disclaimed, or held invalid by a prior post-patent action or proceeding.

CROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a continuation-in-part (CIP) of U.S. patent application Ser. No. 11/536,559, filed on Sep. 28, 2006, entitled "MAPPING MOVEMENTS OF A HAND-HELD CONTROLLER TO THE TWO-DIMENSIONAL IMAGE PLANE OF A DISPLAY SCREEN", which is hereby incorporated by reference herein in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to computer entertainment systems, and more specifically to a user's manipulation of a controller for such computer entertainment systems.

2. Discussion of the Related Art

Computer entertainment systems typically include a hand-held controller, game controller, or other controller. A user or player uses the controller to send commands or other instructions to the entertainment system to control a video game or other simulation being played. For example, the controller may be provided with a manipulator which is operated by the user, such as a joy stick. The manipulated variable of the joy stick is converted from an analog value into a digital value, which is sent to the game machine main frame. The controller may also be provided with buttons that can be operated by the user.

It is with respect to these and other background information factors that the present invention has evolved.

SUMMARY OF THE INVENTION

One embodiment provides a method for use in obtaining input data from an object, comprising: capturing a live image of the object with an image capture device; receiving information related to a tilt angle of the object from one or more sensors other than the image capture device; using the information related to a tilt angle of the object to obtain at least one rotated reference image of the object; comparing the live image of the object with the rotated reference image of the object; and generating an indication in response to the live image matching the rotated reference image.

Another embodiment provides an apparatus for use in obtaining input data from an object, comprising: an image capture device configured to capture a live image of the object; and a processor based system configured to receive information related to a tilt angle of the object from one or more sensors other than the image capture device, use the information related to a tilt angle of the object to obtain at least one rotated reference image of the object, compare the live image of the object with the rotated reference image of the object, and generate an indication in response to the live image matching the rotated reference image.

Another embodiment provides a storage medium storing a computer program executable by a processor based system, the computer program causing the processor based system to execute steps comprising: receiving a captured live image of an object from an image capture device; receiving information related to a tilt angle of the object from one or more sensors other than the image capture device; using the information related to a tilt angle of the object to obtain at least one rotated reference image of the object; comparing the live image of the object with the rotated reference image of the object; and generating an indication in response to the live image matching the rotated reference image.

A better understanding of the features and advantages of various embodiments of the present invention will be obtained by reference to the following detailed description and accompanying drawings which set forth an illustrative embodiment in which principles of embodiments of the invention are utilized.

BRIEF DESCRIPTION OF THE DRAWINGS

The above and other aspects, features and advantages of embodiments of the present invention will be more apparent from the following more particular description thereof, presented in conjunction with the following drawings wherein:

FIG. 1A is a pictorial diagram illustrating a system that operates in accordance with an embodiment of the present invention;

FIG. 1B is a perspective view of a controller made in accordance with an embodiment of the present invention;

FIG. 1C is a perspective view of a controller made in accordance with an embodiment of the present invention;

FIG. 1D is a perspective view of a controller made in accordance with an embodiment of the present invention;

FIG. 1E is a perspective view of a controller made in accordance with some embodiments of the present invention;

FIG. 2A is a pictorial diagram illustrating a manner for determining position information for a controller in accordance with an embodiment of the present invention;

FIG. 2B is a planar view of an image plane illustrating a manner for determining position information for a controller in accordance with an embodiment of the present invention;

FIG. 3A is a flow diagram illustrating a method for use in obtaining information in accordance with an embodiment of the present invention;

FIG. 3B is a flow diagram illustrating a method for use in providing input to a system in accordance with an embodiment of the present invention;

FIG. 4 is a block diagram illustrating a system that may be used to run, implement and/or execute the methods and techniques shown and described herein in accordance with embodiments of the present invention;

FIG. 5 is a block diagram illustrating a processor that may be used to run, implement and/or execute the methods and techniques shown and described herein in accordance with embodiments of the present invention; and

FIGS. 6A, 6B, and 6C are pictorial diagrams illustrating a system that operates in accordance with another embodiment of the present invention;

FIG. 7 is a flow diagram illustrating a method for use in controlling a system in accordance with an embodiment of the present invention;

3

FIG. 8 is a pictorial diagram illustrating a system that operates in accordance with another embodiment of the present invention;

FIG. 9 is a block diagram illustrating a system that operates in accordance with another embodiment of the present invention;

FIG. 10 is a pictorial diagram illustrating a system that operates in accordance with another embodiment of the present invention;

FIGS. 11A and 11B are perspective diagrams illustrating controllers that may optionally be used in the described systems in accordance with embodiments of the present invention;

FIG. 12 is a block diagram of a system for mixing various control inputs according to an embodiment of the present invention;

FIG. 13A is a block diagram of a system according to an embodiment of the present invention;

FIG. 13B is a flow diagram of a method according to an embodiment of the present invention;

FIG. 13C is a flow diagram of a method according to an embodiment of the present invention;

FIG. 14 is a flow diagram illustrating a method for use in obtaining input data from an object in accordance with an embodiment of the present invention;

FIG. 15 is a block diagram illustrating some of the steps shown in FIG. 14 in accordance with an embodiment of the present invention; and

FIG. 16 is a block diagram illustrating a set of rotated reference images in accordance with an embodiment of the present invention.

DETAILED DESCRIPTION

The user or player of a video game typically holds the game controller with one or both hands in order to operate the buttons, joy stick, etc., located on the controller. Often times while playing the game the user will also move the entire controller itself around in the air as he or she simultaneously operates the buttons, joy stick, etc. Some users tend to get excited while playing the game and attempt to control actions or aspects of the game by moving the entire controller itself around in the air.

Various embodiments of the methods, apparatus, schemes and systems described herein provide for the detection, capture and tracking of the movements, motions and/or manipulations of the entire controller body itself by the user. The detected movements, motions and/or manipulations of the entire controller body by the user may be used as additional commands to control various aspects of the game or other simulation being played.

Detecting and tracking a user's manipulations of a game controller body may be implemented in different ways. For example, in some embodiments a camera peripheral can be used with the computer entertainment system to detect motions of the hand-held controller body and transfer them into actions in a game. The camera can be used to detect many different types of motions of the controller, such as for example up and down movements, twisting movements, side to side movements, jerking movements, wand-like motions, plunging motions, etc. Such motions may correspond to various commands such that the motions are transferred into actions in a game.

Detecting and tracking the user's manipulations of a game controller body can be used to implement many different types of games, simulations, etc., that allow the user to, for example, engage in a sword or lightsaber fight, use a wand

4

to trace the shape of items, engage in many different types of sporting events, engage in on-screen fights or other encounters, etc.

Referring to FIG. 1A, there is illustrated a system 100 that operates in accordance with an embodiment of the present invention. As illustrated, a computer entertainment system or console 102 uses a television or other video display 104 to display the images of the video game or other simulation thereon. The game or other simulation may be stored on a DVD, CD, flash memory, USB memory, or other memory media 106 that is inserted into the console 102. A user or player 108 manipulates a game controller 110 to control the video game or other simulation.

A camera or other video image capturing device 112 is positioned so that the controller 110 is within the camera's field of view 114. As illustrated, the camera 110 may be placed on the video display 104, but it should be well understood that the camera may be located elsewhere. By way of example, the camera 112 may comprise a camera peripheral device such as the commercially available Eye-Toy™ product. But it should be well understood that any type or brand of camera may be used, such as for example a web-cam camera, add-on USB camera, infrared (IR) capability camera, fast frame capture rate camera, etc.

In some embodiments, the camera or other image capturing device 112, as well as the image capture unit discussed below, may comprise a Z-camera or depth camera. Such a Z-camera or depth camera may, for example, provide or measure a depth of each pixel and/or determine the distance of a pixel from the camera. As such, any of the cameras or other image capturing devices described herein may, in some embodiments, comprise any type of three-dimensional camera.

During operation, the user 108 physically moves the controller 110 itself. That is, the user 108 physically moves the entire controller 110 around in the air. For example, the controller 110 may be moved in any direction by the user 108, such as up, down, to one side, to the other side, twisted, rolled, shaken, jerked, plunged, etc. These movements of the controller 110 itself may be detected and captured by the camera 112 by way of tracking through image analysis in a manner described below.

In general, the detected and captured movements of the controller 110 are used to generate position and orientation data for the controller 110. Because this data is gathered on an image frame-by-frame basis, the data can be used to calculate many physical aspects of the movement of the controller 110, such as for example its acceleration and velocity along any axis, its tilt, pitch, yaw, roll, as well as any telemetry points of the controller 110.

The ability to detect and track the movements of the controller 110 makes it possible to determine whether any predefined movements of the controller 110 are performed. That is, certain movement patterns or gestures of the controller 110 may be predefined and used as input commands for the game or other simulation. For example, a plunging downward gesture of the controller 110 may be defined as one command, a twisting gesture of the controller 110 may be defined as another command, a shaking gesture of the controller 110 may be defined as another command, and so on. In this way the manner in which the user 108 physically moves the controller 110 itself is used as another input for controlling the game, which provides a more stimulating and entertaining experience for the user. Examples of how movements of the controller 110 can be mapped to input commands for the game will be discussed below.

Referring to FIG. 1B, there is illustrated a more detailed view of the controller **110** that is made in accordance with an embodiment of the present invention. The controller **110** includes a body **111**. The body **111** is the part of the game controller **110** that one would hold by hand (or wear if it were a wearable game controller). An input device manipulable by a user is something such as, for example, a button or multiaxis control stick on the controller. One or more buttons may be disposed on the body **111**. The body may include a housing holdable by hand. The housing may include a handgrip graspable by hand. Thus, during operation when the user **108** physically moves the controller **110** itself, the user **108** physically moves the body **111** of the controller **110**. The user moves the body **111** around in the air, or in free-space.

The body **111** may have a forward section to be oriented towards a screen when a progress of a game controlled in accordance with the game controller is displayed upon the screen. At least one input device may be assembled with the body **111** with the input device manipulable by a user to register an input from the user.

One or more light-emitting diodes (LEDs) may be disposed on the body that are arranged in a geometric shape. Or, another type of photonically detectable (“PD”) element may be assembled with the body **111**. A position of the photonically detectable element may be within an image being recorded by an image capture device when the forward section is oriented at least generally towards the screen. The positions of the PD element at different points in time may be quantifiable at quantify movement of the body **111** in space.

In this embodiment, the controller **110** includes four light-emitting diodes (LEDs) **122**, **124**, **126**, **128**. As illustrated, the four LEDs **122**, **124**, **126**, **128** may be arranged in a substantially square or rectangular pattern and located on the bridge of the controller **110** between the R1 and L1 buttons. Thus, in this embodiment the geometric shape comprises a substantially square or rectangular pattern. The square or rectangular pattern formed by the four LEDs **122**, **124**, **126**, **128** will be referred to herein as the “bounding box” formed by the LEDs.

It should be well understood that the geometric shape may comprise many different shapes. For example, the geometric shape may comprise any linear or two-dimensional pattern. Although a linear array of LEDs is preferred, the LEDs may alternatively, be arranged in a rectangular pattern or an arcuate pattern to facilitate determination of an image plane of the LED array when analyzing an image of the LED pattern obtained by an image capture camera.

While the illustrated embodiment of the controller utilizes four LEDs, it should be well understood that other embodiments may utilize more than four LEDs or less than four LEDs. For example, three LEDs will work, and two LEDs will also work to provide tracking information. Even one LED can provide position information. Furthermore, the LEDs may be located on a different part of the controller **110**.

The LEDs may be positioned or disposed on the controller **110** in a variety of ways, including in a cluster, a line, a triangle, and/or other such configurations. One LED may be used or multiple LEDs can be used. In the case of multiple LEDs, in one configuration, the plane that is formed that intersects the LEDs may be tilted with respect to the orientation of the controller. The actual orientation of the controller may be determined by performing a transformation of data received in the image plane to determine the controller orientation. Additionally or alternatively, the

LEDs can be removable, attachable and/or detachable. For example, the LEDs can be included on a plate or separate casing that is detachable from the body **111**.

Referring to FIG. 1C, there is illustrated a view of the controller **110** that is made in accordance with an embodiment of the present invention. The controller **110** includes the body **111** and a cluster or array of LEDs **122**, **124**, **126** and **128**. As illustrated, the four LEDs **122**, **124**, **126**, **128** may be arranged in a substantially linear pattern and located on the bridge of the controller **110** between the R1 and L1 buttons. Thus, in this embodiment the geometric shape comprises a substantially linear pattern. Further in some embodiments, one or more of the LEDs can be implemented through infrared LEDs. For example, infrared LEDs can be paired with the visible LEDs. The visible LEDs can, for example, show a player ID. In some implementations, the LEDs may be surface mounted, with the infrared LEDs peeking through small windows that allow both visible LED and infrared LED transmission.

Referring to FIG. 1D, there is illustrated a view of the controller **110** that is made in accordance with an embodiment of the present invention. The controller **110** includes the body **111** and a communications interface and/or port **132**. The interface, in some embodiments, allows the controller to couple directly with a tracking device and/or the console **102**. The tracking devices at least in part can allow for the detection of movement of the controller **110**, by optical, audio and/or inertia. The interface **132** can be substantially any relevant communication interface, such as a universal serial bus (USB) interface, universal asynchronous receiver transmitter (UART), and/or other such relevant interface. The interface **132** can be positioned on the controller **110** in substantially any position. As illustrated, the interface **132** may be located on the bridge of the controller **110** between the R1 and L1 buttons.

Referring to FIG. 1E, there is depicted a perspective view of the controller **110** that is made in accordance with some embodiments of the present invention. The controller includes the body **111**, the R1 and L1 buttons, the one or more LEDs **122**, **124**, **126** and **128**, the interface **132** (e.g., a USB interface), and other relevant buttons, indicators and the like. The LEDs **122**, **124**, **126** and **128** are shown in the linear pattern, however, other patterns can be employed as described above and further below. Additionally in some implementations, the LEDs and/or interface **132** can be removable, attachable and/or detachable.

The four LEDs **122**, **124**, **126**, **128** produce four points or dots that are perceived by camera **112** (FIG. 1A). Because the camera **112** is looking at the player **108** with the controller **110** in his hands, the camera **112** is able to track the movement of the controller **110** by tracking the movement of the dots produced by the four LEDs **122**, **124**, **126**, **128** and the bounding box that they form.

Namely, as the user **108** twists and rotates the controller body **110** the projection of the four dots are cast on the image plane of the camera **112**'s outputs. Image analysis is used to track the user's manipulations of the controller and to determine controller position and orientation. Thus, the four LEDs **122**, **124**, **126**, **128** produce information regarding the body's movement. The positions of one or two controllers can be determined, or the relative movements of two controllers can be tracked.

FIG. 2A illustrates an example of how the bounding box is used to track the movements of the controller. Specifically, the controller, and thus the four LEDs **122**, **124**, **126**, **128**, are located within the field of view **114** of the camera **112**. The four LEDs **122**, **124**, **126**, **128** form a bounding box **202**

when the controller is in a first position. When the controller is moved to a second position the four LEDs **122**, **124**, **126**, **128** form a second bounding box **204**. In addition, when the controller is moved from the first to the second position, the intermediate positions of the bounding boxes are also captured, depending on the speed of the movement and the frame rate of the camera **112**.

The bounding boxes **202** and **204** formed by the four LEDs **122**, **124**, **126**, **128** are captured in the image plane of the camera **112**. FIG. 2B illustrates an example of the image plane **220** of the camera **112** showing the bounding boxes **202** and **204**. A physics analysis is performed to derive and determine the movements of the bounding box and how the rectangle of the bounding box deforms into different shapes based on the tilt, yaw, etc. of the controller. By projecting the bounding boxes on the image plane, the position, orientation, acceleration, velocity, etc., of the controller can be determined, which can in turn be used to track the user's manipulations of the game controller.

Referring to FIG. 3A, there is illustrated a method **300** for use in obtaining information from a controller in accordance with an embodiment of the present invention. The method **300** may be executed and performed by many different types of systems and devices, such as for example entertainment systems and consoles, computers, consumer electronics device, etc. An example of a system that may be used to perform the method **300** will be described below.

The method **300** begins in step **302** in which a projection of a geometric shape established on the controller is received on an image plane of a camera. This step may be performed as has already been described above.

In step **304** the movements and deformities in the projection of the geometric shape are analyzed. Namely, the four dots of the bounding box are tracked and analyzed. Field and frame analysis is performed on the image plane of the camera output to analyze the manipulation of the four reference points to determine position orientation, tilt, yaw, roll, etc. of the controller. In addition, acceleration of the controller can be tracked in any direction. Analysis of the frames of the image can give the acceleration along any axis. Telemetry points of the controller can also be computed. It can also be determined whether or not the controller is in a resting position or resting state, such as for example when the controller is in a neutral or steady state near the user's waist.

As the controller rolls the image translates in the plane. Changes in the width of the rectangle of the bounding box indicate the controller is rolling. As the yaw of the controller is adjusted, the width of the rectangle changes. Yaw maps to the width of the rectangle. Tilt of the controller influences the height of the rectangle.

For example, the bounding box **202** (FIG. 2B) indicates that the controller was initially positioned looking fairly straight ahead at the camera. The bounding box **204** indicates that the controller was then moved downward, rolled and turned to the user's left.

It is difficult to know which side of the "ground plane" the controller is positioned on because the image plane only sees a deformed rectangle. For example, this issue can occur if someone walks in front of and occludes the camera during a time when the user manipulates the controller and moves the controller to an equal distance on the other side of an axis horizon line. This may cause the bounding box to look the same in the image plane. This can also happen if the controller travels outside of the viewing region of the image capture device.

As such, a determination may need to be made as to whether the deformation is caused by positive or negative tilt or roll (positive and negative being related to up/down and left/right movements away from the steady state origin position). This can be solved by reading other telemetry from the controller or by strobing or modulating the LEDs to enable the video analyzer system to discriminate individual corners of the bounding box rectangle for tracking purposes. The LEDs may be strobed or modulated as an aid for discerning the different corners of the bounding box. Or, each LED may have its own frequency as an aid for discerning the different corners of the bounding box. By identifying each specific corner of a bounding region, i.e. each LED, it can be determined which side of a horizontal line the controller is on at any point in time. In this way problems associated with the controller passing through the camera plane can be handled.

Tracking the movements and rotations of the bounding box on the screen is based on a frame-by-frame analysis. The camera's output creates the frames of image data. The projection of the bounding box is captured in software. The movements of the controller across the frames is based on the translation of the box.

The use of a high frame rate provides the ability to accurately track acceleration and changes in acceleration of the movement of the controller. That is, by projecting the image on the plane at high rates, the delta movements of the controller can be tracked. This provides the ability to plot the acceleration, the points where the acceleration peaks out, the points where gravity zeros out, and the points of inflection. The points of inflection are the transition points where the controller stops and changes direction. All of this analysis is performed by analyzing the frames of the image and determining the position and deformation of the bounding box. By way of example, frame rates of 120 frames per second or higher may be used, but it should well understood that any frame rate may be used.

As will be discussed below, the history of previous frames may be mapped. This allows the previous telemetry of the controller to be looked at for determining certain parameters such as, for example, in tracking acceleration, velocity, and stopping points.

In step **306** (FIG. 3A) position information for the controller is determined based on the analysis of the movements and deformities in the projection of the geometric shape. By way of example, an image analyzer may be used to perform one or both of steps **304** and **306**. Namely, an image analyzer may be used to perform the analysis of the movements and deformations of the bounding boxes in the image plane of the camera. The output of the video camera may be coupled to the input of an image analyzer. An example of a system which may incorporate an image analyzer for implementing one or more of the methods, schemes and functions described herein will be discussed below.

The image analyzer monitors the bounding box formed by the reference LEDs as captured in the image plane of the camera. The image analyzer analyzes the position, rotation, horizontal and vertical deformation of the bounding box to determine the physical user manipulation of the controller, its position, roll, tilt and yaw coordinates. At the end of the image analysis the data may be output in the form of an output ID or the like. Such output IDs from the image analysis may include data such as the x, y, z coordinates, acceleration and velocity along any axis, that the controller is in a resting position or state, etc. Thus, at the end of image analysis the image analyzer can indicate where the controller is and whether a command is issued. And the image analyzer

may be pinged at any instant of time and it may provide position, orientation, last command, etc.

By way of example, the image analyzer may provide, but shall not be limited to providing the following outputs:

CONTROLLER POSITION (X, Y, Z coordinates);
 CONTROLLER ORIENTATION alpha, beta, gamma (ra-
 dians);
 CONTROLLER X-AXIS VELOCITY;
 CONTROLLER Y-AXIS VELOCITY;
 CONTROLLER Z-AXIS VELOCITY;
 CONTROLLER X-AXIS ACCELERATION;
 CONTROLLER Y-AXIS ACCELERATION;
 CONTROLLER Z-AXIS ACCELERATION;
 RESTING POSITION OF STEADY STATE Y/N (at
 waist as described, but may be defined as any position);
 TIME SINCE LAST STEADY STATE;
 LAST GESTURE RECOGNIZED;
 TIME LAST GESTURE RECOGNIZED; and
 INTERRUPT ZERO-ACCELERATION POINT
 REACHED.

Each of these outputs may be generated by analyzing the movements and deformations of the bounding box as described above. These outputs may be further processed in order to track the movement of the controller. Such tracking will allow certain movements of the controller to be recognized, which can then be used to trigger certain commands as described below. It should be well understood that many other outputs may be used in addition to or in replacement of the above-listed outputs.

Additional inputs to the image analyzer may optionally be provided. Such optional inputs may include but shall not be limited the following:

SET NOISE LEVEL (X, Y or Z AXIS) (this is a reference tolerance when analyzing jitter of hands in the game);
 SET SAMPLING RATE (how often frames of the camera
 are being taken in and analyzed);
 SET GEARING; and
 SET MAPPING CHAIN.

As mentioned above, the ability to detect and track the movements of the controller **110** makes it possible to determine whether any predefined movements of the controller **110** are performed. That is, certain movement patterns or gestures of the controller **110** may be mapped to input commands for the game or other simulation.

Referring to FIG. 3B, there is illustrated a method **320** for use in providing input to a system in accordance with an embodiment of the present invention. The method **320** begins in step **322** in which position information for a controller for the system is determined. This step may be performed using the methods and techniques described above.

In step **324**, the determined position information for the controller is compared with predetermined position information associated with commands. That is, any number of different movements, gestures or manipulations of the controller may be mapped to various commands. This allows different movements, gestures or manipulations of the controller to be mapped into game models. For example, moving the controller up may be mapped to one command, moving the controller down may be mapped to another command, and moving the controller in any other direction may be mapped to other commands.

Similarly, shaking the controller once may be mapped to one command, shaking the controller twice may be mapped to another command, and similarly, shaking the controller three, four, five, etc., times may be mapped to other commands. That is, various gestures may be established based on

shaking the controller a certain number of times. Still other gestures may be established based on shaking the controller up and down vigorously a certain number of times. Other movements of the controller such as twisting, rolling, etc., may be mapped to still other commands.

Thus, various different trajectories of the game controller may be mapped onto gestures, which trigger commands in the game. Each command is mapped to a predetermined movement of the controller. Such predetermined movements of the controller will have associated predetermined position information. In this embodiment the determined position information for the controller is compared with the predetermined position information to see if a command should be triggered.

By way of example, such mapping of gestures to game commands may be implemented as follows. The outputs of the image analyzer may be used to determine position and orientation information for the controller. The image analyzer may output various different IDs that are indicative of position and orientation of the controller. For example, one ID may be output for a steady state determination, another ID may be output to indicate shaking of the controller, and various other IDs may be output to indicate other orientations. Thus, the use of such IDs may be used to output whether the controller is in steady state or is moving. If the controller is in steady state, an ID may indicate how long the controller has been in steady state.

The determined position and orientation information for the controller may then be compared with predetermined position information associated with input commands for the game. If the determined position information matches the predetermined position information for a command, then the command is provided to the entertainment system. Again, various gestures such as pushing the controller up or down, twisting in a circle, right or left, twisting while pulling it up or down, rolling right or left, etc., may all be mapped to various commands.

When a new command or gesture is recognized the image analyzer may trigger an interrupt. The triggering of such an interrupt may be used as part of the process of providing the command to the entertainment system. The system may optionally be configured so that zero acceleration points in the axes, stop points, and/or other events also trigger interrupts.

In comparing the determined position and orientation information with the predetermined position information associated with input commands to see if there is a match, it may often be the case that there is not an exact match. This is because with movement of the controller in free-space it may be difficult to precisely recreate a predefined movement. Therefore, the predetermined position information associated with input commands may be defined in terms of ranges, tolerances, and/or thresholds that are considered to be close enough to the predetermined position information such as to activate the command. That is, commands may be defined in terms of the thresholds or ranges. Thus, in determining whether or not any commands or gestures have been identified, the system may check to see if the determined position and orientation information falls within a range of a gesture. Thus, the defined commands may have thresholds that can be looked at in determining whether or not to invoke the command.

Furthermore, in comparing the determined position and orientation information with the predetermined position information associated with input commands to see if there is a match, histories of previous frames may be saved or mapped. For example, the frame buffer may be monitored or

the system may otherwise keep running records of the history of the previous frames. The previous frames may be looked at to determine if any commands are met. The mapping of frame histories may allow the telemetry of the controller at a specific time to be determined to provide the position orientation in determining if a command is met.

Finally, in step 326 if the determined position information for the controller matches predetermined position information for a command, the command is provided to the system. Such command may be used to cause an event to occur or not occur in a video game or other simulation.

In other embodiments, the movements of a game controller may be mapped to game commands, such as for example in video game. With such a method, which may be used in video games or other simulations, position information for a controller that is being manipulated by a user is received. The position information is analyzed to determine whether a predetermined movement of the controller associated with a command has been performed. This analysis may be performed as described above. If the predetermined movement of the controller associated with a command has been performed, then the command is executed by the game. The execution of the command may cause a visual effect or the like to occur on the video display that the game is being displayed on.

While the discussion herein is directed to the use of LEDs on the controller for a game or other entertainment system, it should be well understood that the teachings provided herein may be applied to detect and track the movements of controllers for other types of systems, devices, consumer electronics, etc. That is, the LEDs of the game controller described above can be used to perform remote control functions for consumer electronics devices or any device. LEDs may be used on the controllers for many other types of systems and devices in order to detect and track the controllers so that such movements may be mapped to commands for those systems and device. Examples of such other types of systems and devices may include, but are not limited to, televisions, stereos, telephones, computers, home or office networks, hand-held computing or communication device, etc.

Furthermore, the teachings described herein may be applied to universal remote controls that have the ability to control several or many different devices. That is, such universal remote controls may include LEDs as described herein such that movements of the universal remote control body may be used as input commands for several or many different devices or systems.

Moreover, a game controller may have a universal remote function. For example, such may comprise a body having a forward section to be oriented towards a screen when a progress of a game controlled in accordance with the game controller is displayed upon the screen. At least one input device may be assembled with the body with the input device manipulable by a user to register an input from the user. A signal encoder may be included. An infrared signal transmitter operable to transmit an infrared signal over the air using a signal generated by the signal encoder may be included. The signal encoder may be programmable to encode the signal with a selected one of a plurality of signaling codes for reception by an electronic device having an infrared receiver and a signal decoder operable with the selected one signaling code.

Moreover, battery operated toys (including toys molded into a form and style of a branded game) can be formed having LEDs and form a tracked user manipulated body in the sensed environment.

In some embodiments the image analyzer can recognize a user or process audio authenticated gestures, etc. A user may be identified by an analyzer in the system through a gesture and a gesture may be specific to a user. Gestures may be recorded by users and stored in models. The recordation process may optionally store audio generated during recordation of a gesture. The sensed environment may be sampled into a multi-channel analyzer and processed. The processor may reference gesture models to determine and authenticate user identity or objects based on voice or acoustic patterns and to a high degree of accuracy and performance.

According to embodiments of the present invention, the methods and techniques described herein may be implemented as part of a signal processing apparatus 400, as depicted in FIG. 4. The apparatus 400 may include a processor 401 and a memory 402 (e.g., RAM, DRAM, ROM, and the like). In addition, the signal processing apparatus 400 may have multiple processors 401 if parallel processing is to be implemented. The memory 402 may include data and code configured as described above. The signal processing apparatus 400 comprises one example of a processor based system.

Specifically, the memory 402 may include signal data 406. The memory 402 may also contain calibration data 408, e.g., data representing one or more inverse eigenmatrices C^{-1} for one or more corresponding pre-calibrated listening zones obtained from calibration of a microphone array 422. By way of example the memory 402 may contain eigenmatrices for eighteen 20 degree sectors that encompass a microphone array 422.

The apparatus 400 may also include well-known support functions 410, such as input/output (I/O) elements 411, power supplies (P/S) 412, a clock (CLK) 413 and cache 414. The apparatus 400 may optionally include a mass storage device 415 such as a disk drive, CD-ROM drive, tape drive, or the like to store programs and/or data. For example, such storage device or storage medium may store one or more computer programs executable by the apparatus or other processor based system for causing the system to execute one or more steps of the methods and/or techniques described herein. The controller may also optionally include a display unit 416 and user interface unit 418 to facilitate interaction between the controller 400 and a user. The display unit 416 may be in the form of a cathode ray tube (CRT) or flat panel screen that displays text, numerals, graphical symbols or images. The user interface 418 may include a keyboard, mouse, joystick, light pen or other device. In addition, the user interface 418 may include a microphone, video camera or other signal transducing device to provide for direct capture of a signal to be analyzed. The processor 401, memory 402 and other components of the system 400 may exchange signals (e.g., code instructions and data) with each other via a system bus 420 as shown in FIG. 4.

The microphone array 422 may be coupled to the apparatus 400 through the I/O functions 411. The microphone array may include between about 2 and about 8 microphones, preferably about 4 microphones with neighboring microphones separated by a distance of less than about 4 centimeters, preferably between about 1 centimeter and about 2 centimeters. Preferably, the microphones in the array 422 are omni-directional microphones. An optional image capture unit 423 (e.g., a digital camera) may be coupled to the apparatus 400 through the I/O functions 411. One or more pointing actuators 425 that are mechanically coupled to the camera may exchange signals with the processor 401 via the I/O functions 411.

As mentioned above, in some embodiments, the optional image capture unit **423**, as well as any of the cameras described herein, may comprise any type of camera or sensor capable of detecting light emitting elements. For example, in some embodiments the optional image capture unit **423** may comprise a Z-camera or depth camera or some other type of three-dimensional camera. Such a Z-camera or depth camera may, for example, provide or measure a depth of each pixel and/or determine the distance of a pixel from the camera.

As used herein, the term I/O generally refers to any program, operation or device that transfers data to or from the system **400** and to or from a peripheral device. Every data transfer may be regarded as an output from one device and an input into another. Peripheral devices include input-only devices, such as keyboards and mouses, output-only devices, such as printers as well as devices such as a writable CD-ROM that can act as both an input and an output device. The term "peripheral device" includes external devices, such as a mouse, keyboard, printer, monitor, microphone, game controller, camera, external Zip drive or scanner as well as internal devices, such as a CD-ROM drive, CD-R drive or internal modem or other peripheral such as a flash memory reader/writer, hard drive.

In certain embodiments of the invention, the apparatus **400** may be a video game unit, which may include a joystick controller **430** coupled to the processor via the I/O functions **411** either through wires (e.g., a USB cable) or wirelessly. The joystick controller **430** may have analog joystick controls **431** and conventional buttons **433** that provide control signals commonly used during playing of video games. Such video games may be implemented as processor readable data and/or instructions which may be stored in the memory **402** or other processor readable medium such as one associated with the mass storage device **415**.

The joystick controls **431** may generally be configured so that moving a control stick left or right signals movement along the X axis, and moving it forward (up) or back (down) signals movement along the Y axis. In joysticks that are configured for three-dimensional movement, twisting the stick left (counter-clockwise) or right (clockwise) may signal movement along the Z axis. These three axis—X Y and Z—are often referred to as roll, pitch, and yaw, respectively, particularly in relation to an aircraft.

In addition to conventional features, the joystick controller **430** may include one or more inertial sensors **432**, which may provide position and/or orientation information to the processor **401** via an inertial signal. Orientation information may include angular information such as a tilt, roll or yaw of the joystick controller **430**. By way of example, the inertial sensors **432** may include any number and/or combination of accelerometers, gyroscopes or tilt sensors. In a preferred embodiment, the inertial sensors **432** include tilt sensors adapted to sense orientation of the joystick controller with respect to tilt and roll axes, a first accelerometer adapted to sense acceleration along a yaw axis and a second accelerometer adapted to sense angular acceleration with respect to the yaw axis. An accelerometer may be implemented, e.g., as a MEMS device including a mass mounted by one or more springs with sensors for sensing displacement of the mass relative to one or more directions. Signals from the sensors that are dependent on the displacement of the mass may be used to determine an acceleration of the joystick controller **430**. Such techniques may be implemented by program code instructions **404** which may be stored in the memory **402** and executed by the processor **401**.

By way of example an accelerometer suitable as the inertial sensor **432** may be a simple mass elastically coupled at three or four points to a frame, e.g., by springs. Pitch and roll axes lie in a plane that intersects the frame, which is mounted to the joystick controller **430**. As the frame (and the joystick controller **430**) rotates about pitch and roll axes the mass will displace under the influence of gravity and the springs will elongate or compress in a way that depends on the angle of pitch and/or roll. The displacement and of the mass can be sensed and converted to a signal that is dependent on the amount of pitch and/or roll. Angular acceleration about the yaw axis or linear acceleration along the yaw axis may also produce characteristic patterns of compression and/or elongation of the springs or motion of the mass that can be sensed and converted to signals that are dependent on the amount of angular or linear acceleration. Such an accelerometer device can measure tilt, roll angular acceleration about the yaw axis and linear acceleration along the yaw axis by tracking movement of the mass or compression and expansion forces of the springs. There are a number of different ways to track the position of the mass and/or the forces exerted on it, including resistive strain gauge material, photonic sensors, magnetic sensors, hall-effect devices, piezoelectric devices, capacitive sensors, and the like.

In addition, the joystick controller **430** may include one or more light sources **434**, such as light emitting diodes (LEDs). The light sources **434** may be used to distinguish one controller from the other. For example one or more LEDs can accomplish this by flashing or holding an LED pattern code. By way of example, 5 LEDs can be provided on the joystick controller **430** in a linear or two-dimensional pattern. Although a linear array of LEDs is preferred, the LEDs may alternatively, be arranged in a rectangular pattern or an arcuate pattern to facilitate determination of an image plane of the LED array when analyzing an image of the LED pattern obtained by the image capture unit **423**. Furthermore, the LED pattern codes may also be used to determine the positioning of the joystick controller **430** during game play. For instance, the LEDs can assist in identifying tilt, yaw and roll of the controllers. This detection pattern can assist in providing a better user/feel in games, such as aircraft flying games, etc. The image capture unit **423** may capture images containing the joystick controller **430** and light sources **434**. Analysis of such images can determine the location and/or orientation of the joystick controller. Such analysis may be implemented by program code instructions **404** stored in the memory **402** and executed by the processor **401**. To facilitate capture of images of the light sources **434** by the image capture unit **423**, the light sources **434** may be placed on two or more different sides of the joystick controller **430**, e.g., on the front and on the back (as shown in phantom). Such placement allows the image capture unit **423** to obtain images of the light sources **434** for different orientations of the joystick controller **430** depending on how the joystick controller **430** is held by a user.

In addition the light sources **434** may provide telemetry signals to the processor **401**, e.g., in pulse code, amplitude modulation or frequency modulation format. Such telemetry signals may indicate which joystick buttons are being pressed and/or how hard such buttons are being pressed. Telemetry signals may be encoded into the optical signal, e.g., by pulse coding, pulse width modulation, frequency modulation or light intensity (amplitude) modulation. The processor **401** may decode the telemetry signal from the optical signal and execute a game command in response to the decoded telemetry signal. Telemetry signals may be

decoded from analysis of images of the joystick controller **430** obtained by the image capture unit **423**. Alternatively, the apparatus **401** may include a separate optical sensor dedicated to receiving telemetry signals from the lights sources **434**. The use of LEDs in conjunction with determining an intensity amount in interfacing with a computer program is described, e.g., in commonly-owned U.S. patent application Ser. No. 11/429,414 filed May 4, 2006, to Richard L. Marks et al., entitled "USE OF COMPUTER IMAGE AND AUDIO PROCESSING IN DETERMINING AN INTENSITY AMOUNT WHEN INTERFACING WITH A COMPUTER PROGRAM", which is incorporated herein by reference in its entirety. In addition, analysis of images containing the light sources **434** may be used for both telemetry and determining the position and/or orientation of the joystick controller **430**. Such techniques may be implemented by program code instructions **404** which may be stored in the memory **402** and executed by the processor **401**.

The processor **401** may use the inertial signals from the inertial sensor **432** in conjunction with optical signals from light sources **434** detected by the image capture unit **423** and/or sound source location and characterization information from acoustic signals detected by the microphone array **422** to deduce information on the location and/or orientation of the joystick controller **430** and/or its user. For example, "acoustic radar" sound source location and characterization may be used in conjunction with the microphone array **422** to track a moving voice while motion of the joystick controller is independently tracked (through the inertial sensor **432** and or light sources **434**). Any number of different combinations of different modes of providing control signals to the processor **401** may be used in conjunction with embodiments of the present invention. Such techniques may be implemented by program code instructions **404** which may be stored in the memory **402** and executed by the processor **401**.

Signals from the inertial sensor **432** may provide part of a tracking information input and signals generated from the image capture unit **423** from tracking the one or more light sources **434** may provide another part of the tracking information input. By way of example, and without limitation, such "mixed mode" signals may be used in a football type video game in which a Quarterback pitches the ball to the right after a head fake head movement to the left. Specifically, a game player holding the controller **430** may turn his head to the left and make a sound while making a pitch movement swinging the controller out to the right like it was the football. The microphone array **420** in conjunction with "acoustic radar" program code can track the user's voice. The image capture unit **423** can track the motion of the user's head or track other commands that do not require sound or use of the controller. The sensor **432** may track the motion of the joystick controller (representing the football). The image capture unit **423** may also track the light sources **434** on the controller **430**. The user may release of the "ball" upon reaching a certain amount and/or direction of acceleration of the joystick controller **430** or upon a key command triggered by pressing a button on the joystick controller **430**.

In certain embodiments of the present invention, an inertial signal, e.g., from an accelerometer or gyroscope may be used to determine a location of the joystick controller **430**. Specifically, an acceleration signal from an accelerometer may be integrated once with respect to time to determine a change in velocity and the velocity may be integrated with respect to time to determine a change in position. If values

of the initial position and velocity at some time are known then the absolute position may be determined using these values and the changes in velocity and position. Although position determination using an inertial sensor may be made more quickly than using the image capture unit **423** and light sources **434** the inertial sensor **432** may be subject to a type of error known as "drift" in which errors that accumulate over time can lead to a discrepancy D between the position of the joystick **430** calculated from the inertial signal (shown in phantom) and the actual position of the joystick controller **430**. Embodiments of the present invention allow a number of ways to deal with such errors.

For example, the drift may be cancelled out manually by re-setting the initial position of the joystick controller **430** to be equal to the current calculated position. A user may use one or more of the buttons on the joystick controller **430** to trigger a command to re-set the initial position. Alternatively, image-based drift may be implemented by re-setting the current position to a position determined from an image obtained from the image capture unit **423** as a reference. Such image-based drift compensation may be implemented manually, e.g., when the user triggers one or more of the buttons on the joystick controller **430**. Alternatively, image-based drift compensation may be implemented automatically, e.g., at regular intervals of time or in response to game play. Such techniques may be implemented by program code instructions **404** which may be stored in the memory **402** and executed by the processor **401**.

In certain embodiments it may be desirable to compensate for spurious data in the inertial sensor signal. For example the signal from the inertial sensor **432** may be oversampled and a sliding average may be computed from the oversampled signal to remove spurious data from the inertial sensor signal. In some situations it may be desirable to oversample the signal and reject a high and/or low value from some subset of data points and compute the sliding average from the remaining data points. Furthermore, other data sampling and manipulation techniques may be used to adjust the signal from the inertial sensor to remove or reduce the significance of spurious data. The choice of technique may depend on the nature of the signal, computations to be performed with the signal, the nature of game play or some combination of two or more of these. Such techniques may be implemented by program code instructions **404** which may be stored in the memory **402** and executed by the processor **401**.

The processor **401** may perform digital signal processing on signal data **406** in response to the data **406** and program code instructions of a program **404** stored and retrieved by the memory **402** and executed by the processor module **401**. Code portions of the program **404** may conform to any one of a number of different programming languages such as Assembly, C++, JAVA or a number of other languages. The processor module **401** forms a general-purpose computer that becomes a specific purpose computer when executing programs such as the program code **404**. Although the program code **404** is described herein as being implemented in software and executed upon a general purpose computer, those skilled in the art will realize that the method of task management could alternatively be implemented using hardware such as an application specific integrated circuit (ASIC) or other hardware circuitry. As such, it should be understood that embodiments of the invention can be implemented, in whole or in part, in software, hardware or some combination of both.

In one embodiment, among others, the program code **404** may include a set of processor readable instructions that

implement any one or more of the methods and techniques described herein or some combination of two or more of such methods and techniques. For example, the program code 404 may be configured to implement the image analyzer function described herein. Or alternatively, the image analyzer function described herein may be implemented in hardware.

In the illustrated embodiment the image analyzer function described above is illustrated as the image analyzer 450. The image analyzer 450 may receive its input from a camera, such as for example the image capture unit 423 or the camera 112 (FIG. 1A). Thus, the output of the video camera 112 or the image capture unit 423 may be coupled to the input of the image analyzer 450. The output of the image analyzer 450 may be provided to the system of the apparatus 400. This way, either commands themselves or information needed to see if a command or gesture has been recognized is provided to the apparatus 400. The image analyzer 450 may be coupled to the rest of the apparatus 400 in many different ways; as such, the illustrated connections are just one example. As another example, the image analyzer 450 may be coupled to the system bus 420, which will allow it to receive its input data from the image capture unit 423 and provide its output to the apparatus 400.

The image analyzer 450 may optionally be included in the apparatus 400 or the entertainment system or console 102, or the image analyzer 450 may be located separately from these devices and systems. And again, it should be well understood that the image analyzer 450 may be implemented, in whole or in part, in software, hardware or some combination of both. In the scenario where the image analyzer 450 is implemented in software, then the block 450 represents the image analyzer function implemented in software.

The program code 404 may generally include one or more instructions that direct the one or more processors to select a pre-calibrated listening zone at runtime and filter out sounds originating from sources outside the pre-calibrated listening zone. The pre-calibrated listening zones may include a listening zone that corresponds to a volume of focus or field of view of the image capture unit 423.

The program code may include one or more instructions which, when executed, cause the apparatus 400 to select a pre-calibrated listening sector that contains a source of sound. Such instructions may cause the apparatus to determine whether a source of sound lies within an initial sector or on a particular side of the initial sector. If the source of sound does not lie within the default sector, the instructions may, when executed, select a different sector on the particular side of the default sector. The different sector may be characterized by an attenuation of the input signals that is closest to an optimum value. These instructions may, when executed, calculate an attenuation of input signals from the microphone array 422 and the attenuation to an optimum value. The instructions may, when executed, cause the apparatus 400 to determine a value of an attenuation of the input signals for one or more sectors and select a sector for which the attenuation is closest to an optimum value.

The program code 404 may optionally include one or more instructions that direct the one or more processors to produce a discrete time domain input signal $x_m(t)$ from the microphones M_0, \dots, M_{M_p} , determine a listening sector, and use the listening sector in a semi-blind source separation to select the finite impulse response filter coefficients to separate out different sound sources from input signal $x_m(t)$. The program 404 may also include instructions to apply one or more fractional delays to selected input signals $x_m(t)$ other than an input signal $x_0(t)$ from a reference microphone M_0 .

Each fractional delay may be selected to optimize a signal to noise ratio of a discrete time domain output signal $y(t)$ from the microphone array. The fractional delays may be selected to such that a signal from the reference microphone M_0 is first in time relative to signals from the other microphone(s) of the array. The program 404 may also include instructions to introduce a fractional time delay Δ into an output signal $y(t)$ of the microphone array so that: $y(t+\Delta)=x(t+\Delta)*b_0+x(t-1+\Delta)*b_1+x(t-2+\Delta)*b_2+\dots+x(t-N+\Delta)b_N$, where Δ is between zero and ± 1 .

The program code 404 may optionally include processor executable instructions including one or more instructions which, when executed cause the image capture unit 423 to monitor a field of view in front of the image capture unit 423, identify one or more of the light sources 434 within the field of view, detect a change in light emitted from the light source(s) 434; and in response to detecting the change, triggering an input command to the processor 401. The use of LEDs in conjunction with an image capture device to trigger actions in a game controller is described e.g., in commonly-owned, U.S. patent application Ser. No. 10/759,782 to Richard L. Marks, filed Jan. 16, 2004 and entitled: METHOD AND APPARATUS FOR LIGHT INPUT DEVICE, which is incorporated herein by reference in its entirety.

The program code 404 may optionally include processor executable instructions including one or more instructions which, when executed, use signals from the inertial sensor and signals generated from the image capture unit from tracking the one or more light sources as inputs to a game system, e.g., as described above. The program code 404 may optionally include processor executable instructions including one or more instructions which, when executed compensate for drift in the inertial sensor 432.

In addition, the program code 404 may optionally include processor executable instructions including one or more instructions which, when executed adjust the gearing and mapping of controller manipulations to game a environment. Such a feature allows a user to change the "gearing" of manipulations of the joystick controller 430 to game state. For example, a 45 degree rotation of the joystick controller 430 may be geared to a 45 degree rotation of a game object. However this 1:1 gearing ratio may be modified so that an X degree rotation (or tilt or yaw or "manipulation") of the controller translates to a Y rotation (or tilt or yaw or "manipulation") of the game object. Gearing may be 1:1 ratio, 1:2 ratio, 1:X ratio or X:Y ratio, where X and Y can take on arbitrary values. Additionally, mapping of input channel to game control may also be modified over time or instantly. Modifications may comprise changing gesture trajectory models, modifying the location, scale, threshold of gestures, etc. Such mapping may be programmed, random, tiered, staggered, etc., to provide a user with a dynamic range of manipulatives. Modification of the mapping, gearing or ratios can be adjusted by the program code 404 according to game play, game state, through a user modifier button (key pad, etc.) located on the joystick controller 430, or broadly in response to the input channel. The input channel may include, but may not be limited to elements of user audio, audio generated by controller, tracking audio generated by the controller, controller button state, video camera output, controller telemetry data, including accelerometer data, tilt, yaw, roll, position, acceleration and any other data from sensors capable of tracking a user or the user manipulation of an object.

In certain embodiments the program code 404 may change the mapping or gearing over time from one scheme

or ratio to another scheme, respectively, in a predetermined time-dependent manner. Gearing and mapping changes can be applied to a game environment in various ways. In one example, a video game character may be controlled under one gearing scheme when the character is healthy and as the character's health deteriorates the system may gear the controller commands so the user is forced to exacerbate the movements of the controller to gesture commands to the character. A video game character who becomes disoriented may force a change of mapping of the input channel as users, for example, may be required to adjust input to regain control of the character under a new mapping. Mapping schemes that modify the translation of the input channel to game commands may also change during gameplay. This translation may occur in various ways in response to game state or in response to modifier commands issued under one or more elements of the input channel. Gearing and mapping may also be configured to influence the configuration and/or processing of one or more elements of the input channel.

In addition, a speaker **436** may be mounted to the joystick controller **430**. In "acoustic radar" embodiments wherein the program code **404** locates and characterizes sounds detected with the microphone array **422**, the speaker **436** may provide an audio signal that can be detected by the microphone array **422** and used by the program code **404** to track the position of the joystick controller **430**. The speaker **436** may also be used to provide an additional "input channel" from the joystick controller **430** to the processor **401**. Audio signals from the speaker **436** may be periodically pulsed to provide a beacon for the acoustic radar to track location. The audio signals (pulsed or otherwise) may be audible or ultrasonic. The acoustic radar may track the user manipulation of the joystick controller **430** and where such manipulation tracking may include information about the position and orientation (e.g., pitch, roll or yaw angle) of the joystick controller **430**. The pulses may be triggered at an appropriate duty cycle as one skilled in the art is capable of applying. Pulses may be initiated based on a control signal arbitrated from the system. The apparatus **400** (through the program code **404**) may coordinate the dispatch of control signals amongst two or more joystick controllers **430** coupled to the processor **401** to assure that multiple controllers can be tracked.

By way of example, embodiments of the present invention may be implemented on parallel processing systems. Such parallel processing systems typically include two or more processor elements that are configured to execute parts of a program in parallel using separate processors. By way of example, and without limitation, FIG. 5 illustrates a type of cell processor **500** according to an embodiment of the present invention. The cell processor **500** may be used as the processor **401** of FIG. 4. In the example depicted in FIG. 5, the cell processor **500** includes a main memory **502**, power processor element (PPE) **504**, and a number of synergistic processor elements (SPEs) **506**. In the example depicted in FIG. 5, the cell processor **500** includes a single PPE **504** and eight SPE **506**. In such a configuration, seven of the SPE **506** may be used for parallel processing and one may be reserved as a back-up in case one of the other seven fails. A cell processor may alternatively include multiple groups of PPEs (PPE groups) and multiple groups of SPEs (SPE groups). In such a case, hardware resources can be shared between units within a group. However, the SPEs and PPEs must appear to software as independent elements. As such, embodiments of the present invention are not limited to use with the configuration shown in FIG. 5.

The main memory **502** typically includes both general-purpose and nonvolatile storage, as well as special-purpose

hardware registers or arrays used for functions such as system configuration, data-transfer synchronization, memory-mapped I/O, and I/O subsystems. In embodiments of the present invention, a signal processing program **503** may be resident in main memory **502**. The signal processing program **503** may run on the PPE. The program **503** may be divided up into multiple signal processing tasks that can be executed on the SPEs and/or PPE.

By way of example, the PPE **504** may be a 64-bit PowerPC Processor Unit (PPU) with associated caches L1 and L2. The PPE **504** is a general-purpose processing unit, which can access system management resources (such as the memory-protection tables, for example). Hardware resources may be mapped explicitly to a real address space as seen by the PPE. Therefore, the PPE can address any of these resources directly by using an appropriate effective address value. A primary function of the PPE **504** is the management and allocation of tasks for the SPEs **506** in the cell processor **500**.

Although only a single PPE is shown in FIG. 5, some cell processor implementations, such as cell broadband engine architecture (CBEA), the cell processor **500** may have multiple PPEs organized into PPE groups, of which there may be more than one. These PPE groups may share access to the main memory **502**. Furthermore the cell processor **500** may include two or more groups SPEs. The SPE groups may also share access to the main memory **502**. Such configurations are within the scope of the present invention.

Each SPE **506** includes a synergistic processor unit (SPU) and its own local storage area LS. The local storage LS may include one or more separate areas of memory storage, each one associated with a specific SPU. Each SPU may be configured to only execute instructions (including data load and data store operations) from within its own associated local storage domain. In such a configuration, data transfers between the local storage LS and elsewhere in a system **500** may be performed by issuing direct memory access (DMA) commands from the memory flow controller (MFC) to transfer data to or from the local storage domain (of the individual SPE). The SPUs are less complex computational units than the PPE **504** in that they do not perform any system management functions. The SPU generally have a single instruction, multiple data (SIMD) capability and typically process data and initiate any required data transfers (subject to access properties set up by the PPE) in order to perform their allocated tasks. The purpose of the SPU is to enable applications that require a higher computational unit density and can effectively use the provided instruction set. A significant number of SPEs in a system managed by the PPE **504** allow for cost-effective processing over a wide range of applications.

Each SPE **506** may include a dedicated memory flow controller (MFC) that includes an associated memory management unit that can hold and process memory-protection and access-permission information. The MFC provides the primary method for data transfer, protection, and synchronization between main storage of the cell processor and the local storage of an SPE. An MFC command describes the transfer to be performed. Commands for transferring data are sometimes referred to as MFC direct memory access (DMA) commands (or MFC DMA commands).

Each MFC may support multiple DMA transfers at the same time and can maintain and process multiple MFC commands. Each MFC DMA data transfer command request may involve both a local storage address (LSA) and an effective address (EA). The local storage address may directly address only the local storage area of its associated

SPE. The effective address may have a more general application, e.g., it may be able to reference main storage, including all the SPE local storage areas, if they are aliased into the real address space.

To facilitate communication between the SPEs 506 and/or between the SPEs 506 and the PPE 504, the SPEs 506 and PPE 504 may include signal notification registers that are tied to signaling events. The PPE 504 and SPEs 506 may be coupled by a star topology in which the PPE 504 acts as a router to transmit messages to the SPEs 506. Alternatively, each SPE 506 and the PPE 504 may have a one-way signal notification register referred to as a mailbox. The mailbox can be used by an SPE 506 to host operating system (OS) synchronization.

The cell processor 500 may include an input/output (I/O) function 508 through which the cell processor 500 may interface with peripheral devices, such as a microphone array 512 and optional image capture unit 513. In addition an Element Interconnect Bus 510 may connect the various components listed above. Each SPE and the PPE can access the bus 510 through a bus interface units BIU. The cell processor 500 may also include two controllers typically found in a processor: a Memory Interface Controller MIC that controls the flow of data between the bus 510 and the main memory 502, and a Bus Interface Controller BIC, which controls the flow of data between the I/O 508 and the bus 510. Although the requirements for the MIC, BIC, BIUs and bus 510 may vary widely for different implementations, those of skill in the art will be familiar their functions and circuits for implementing them.

The cell processor 500 may also include an internal interrupt controller IIC. The IIC component manages the priority of the interrupts presented to the PPE. The IIC allows interrupts from the other components the cell processor 500 to be handled without using a main system interrupt controller. The IIC may be regarded as a second level controller. The main system interrupt controller may handle interrupts originating external to the cell processor.

In embodiments of the present invention, certain computations, such as fractional delays, may be performed in parallel using the PPE 504 and/or one or more of the SPE 506. Each fractional delay calculation may be run as one or more separate tasks that different SPE 506 may take as they become available.

Some embodiments provide a tracking device for use in obtaining information for controlling an execution of a game program by a processor for enabling an interactive game to be played by a user. The tracking device can include a body and at least one PD element. The body can further include a section to be oriented towards a screen when a progress of a game provided via execution of the game apparatus is displayed upon the screen. The at least one PD element can additionally be assembled with the body. A position of the PD element within an image can be recordable by an image capture device when the section is oriented at least partly towards the screen. In operation, positions of the PD element at different points in time are quantifiable to quantify movement of the body in space.

Further, the body can be mountable to a game controller. The game controller can include a game controller body and at least one input device assembled with the game controller body. The input device can be manipulable by a user such that an input from the user can be registered. In some instances the apparatus includes both the tracking device and the game controller.

In some embodiments, the PD element can include a retroreflector. Additionally or alternatively, the PD element

can have a color that has a high contrast relative to a color of a portion of the body adjacent to the PD element. Further, each of the at least one PD element can include a pattern that includes at least two different textures. For example, the textures can differ in at least one of brightness, color, roughness and/or other such relevant textures. In some embodiments, the PD element includes a light source, and in some implementations the light source can include at least one LED.

Further, some embodiments include two, three, four or more PD elements. These multiple PD elements can be oriented in one or more configurations. For example, in implementations with two PD elements, the PD elements can be oriented to define a line, and in some implementations with three PD elements, the elements can be oriented in a triangle. In other implementations having four PD elements, the elements can be arranged or positioned to define four lines. The four lines can define, for example, a rectangle or other relevant configuration.

The PD elements can include light sources and at least one of the light sources can be distinguishable from the other light sources by a characteristic relating to the light output by the at least one light source. The at least one light source can be distinguishable from the other light sources, for example, by at least one of a strobe frequency, an on-off duty cycle, a timing of an on interval within an on-off cycle, a spectral content of the output of the light source, and/or other such relevant distinctions and/or combinations of distinctions. In some embodiments, the body of the tracking device is mountable to the user's body.

The tracking devices according to some embodiments can further include a communications interface that can conduct digital communications with at least one of the processor, the game controller and/or both the processor and the game controller. The communications interface can be substantially any relevant interface, such as a universal asynchronous receiver transmitter ("UART"), universal serial bus ("USB") controller, and/or other such relevant interfaces and/or combinations of interfaces. Typically, the interface is operable to perform at least one of receiving a control signal for controlling an operation of the tracking device, for transmitting a signal from the tracking device for communication with another device, and/or other such communication functionality.

Some embodiments further include a processor operable to execute a game program to display a progress of a game on a screen to enable the game to be interactively played by a user. The position of one or more PD elements can be recordable by an image capture device located, for example, in a vicinity of the screen, and the processor can be configured to detect the position of the PD element within the image using information outputted by the image capture device. Additionally or alternatively, the processor can be operable to detect user input information for controlling execution of the game program from the information outputted by the image capture device, to obtain a series of samples representative of acceleration of the body in space at different points in time from information outputted by the image capture device, and/or to determine a velocity of the body using the series of samples, for example by integrating acceleration values obtained from the series of samples over an interval of time.

The processor can, in some instances, determine a displacement of the body in space by first integrating acceleration values obtained from the series of samples over an interval of time and then integrating a result of the first integrating. Additionally or alternatively, the processor can

determine a position of the body in space by determining the displacement in relation to a previously determined position.

In some instances where the tracking device includes at least two of PD elements, the processor can obtain a series of samples representative of acceleration of the body in at least two degrees of freedom in space using the information outputted by the image capture device. When the tracking device includes at least three of the PD elements, the processor can obtain a series of samples representative of acceleration of the body in at least three degrees of freedom using the information outputted by the image capture device. The three degrees of freedom, for example, can include movement along three orthogonal axes x, y and z, and/or pitch, yaw and roll. In some embodiments, the processor can quantify the movement in six degrees of freedom, which can include, for example, three degrees of freedom and pitch, yaw and roll.

Further, some embodiments provide a controller. The controller can include a body, one or more buttons disposed on the body, and one or more detectable elements disposed on the body that are arranged in an array. Additionally in some implementations, the array is a linear array.

As mentioned above, computer entertainment systems typically include a handheld controller, game controller, or other controller. A user or player uses the controller to send commands or other instructions to the entertainment system to control a video game or other simulation being played. Televisions, stereos, other entertainment systems, and appliances also include handheld controllers.

Various embodiments of the methods, apparatus, schemes and systems described herein provide for the mapping of the three-dimensional movements of a handheld controller to the two-dimensional image plane of a display screen. This allows the three-dimensional movements of the entire controller body itself by the user to be used in controlling aspects of a system in which manipulations are performed on the two-dimensional image plane of the display screen.

For example, FIGS. 6A, 6B and 6C illustrate a system that operates in accordance with an embodiment of the present invention. In this embodiment, the three-dimensional movements of a handheld controller can be used for a mouse-like function in manipulating a pointer on the screen. For example, FIG. 6A illustrates a controller 602 held in the hands 604 of a player. An upward movement 606 of the controller 602 moves a cursor on the screen 608 of a display from a one position 610 up to another position 612. In FIG. 6B, a downward movement 620 of the controller 602 moves a cursor on the screen 608 of the display from a one position 622 down to another position 624. And in FIG. 6C, a sideways movement 630 of the controller 602 moves a cursor on the screen 608 of the display from a one position 632 sideways to another position 634. As will be discussed below, in other embodiments the three-dimensional movements of a handheld controller can be used for other functions, such as in a game for manipulating crosshairs or the like on the screen.

Referring to FIG. 7, there is illustrated a method 700 that operates in accordance with an embodiment of the present invention. The method 700 begins in step 702 in which the three-dimensional movements of a hand-held controller for a system are tracked. Such tracking may be performed in many different ways. For example, such tracking may be performed through inertial, video, acoustical, or infrared analysis in any of the manners described herein above or in any other manner.

In the example of video tracking, for example, a camera peripheral can be used with the computer entertainment

system to detect motions of the hand-held controller body and transfer them into actions in a game. The camera can be used to detect many different types of motions of the controller, such as for example up and down movements, twisting movements, side to side movements, jerking movements, wand-like motions, plunging motions, etc. Again, however, the tracking may alternatively be performed through inertial, acoustical, or infrared analysis. For example, in embodiments that use infrared analysis, an infrared analyzer and a linear infrared array are used to determine a user's position and the orientation of a controller based on looking at the output of the sensors.

In step 704, the tracked three-dimensional movements of the handheld controller are then mapped onto the two-dimensional image plane of the screen of the display for the system. That is, the movements of the controller body itself in three-dimensions are cast onto the two-dimensional image plane that is on the screen. Thus, the three-dimensional movements of the controller are translated onto the X—Y coordinates of the two-dimensional image plane of the screen.

In step 706, one or more images are then displayed on the two-dimensional image plane of the screen based on the mapping of the tracked three-dimensional movements of the handheld controller. The images may comprise many different types of images. For example, as shown in FIGS. 6A, 6B and 6C, the images may comprise a pointer for use in selecting items displayed on the screen. In that example, the whole controller 602 itself becomes a mouse-like device and can be used like a mouse to control and select items on the screen like menus, links, etc.

Various different types of controller movements can be configured to cause various different movements of the images displayed on the screen. For example, the user may lift up on the controller or he or she can twist his or her wrist up, causing certain movements of the images. Or in another example, the user can push down on the controller location, and then point the nose down to have the cursor go further down. Or in another example, the user may move to the left with the position of the controller, but then the user twists the orientation to the left which makes the cursor go to the left. Or in another example, the user may move the controller to the right and also twists the orientation to the right which makes the cursor go to the right. Again, these are just examples and many other types of movements may be configured.

Referring to FIG. 8, there is illustrated another system that operates in accordance with an embodiment of the present invention. In this embodiment, the one or more images may comprise a set of crosshairs, such as for a shooter game. For example, in FIG. 8 the user or player may be walking through a three-dimensional space displayed on a screen 802 with the camera panning and moving through the game. A set of crosshairs 804 of the user's gun or the like are mapped to the X-Y coordinates of the two-dimensional image plane of the screen 802 over the three-dimensional space.

As the user moves the controller body 806 in three-dimensions, the movements cause the two-dimensional crosshairs 804 to move. As shown, a sideways and upward movement 810 of the controller body 806 causes a sideways and upward movement of the two-dimensional crosshairs 804 from one position 812 to another position 814. Thus, the games may comprise a three-dimensional game, but the crosshairs on the screen are mapped to the X and Y coordinates in the two-dimensional plane of the screen over the and three-dimensional space.

The examples described thus far illustrate that embodiments of the present invention allow the controller to be used as a mouse-like device for selecting menus, links, items, etc., but then the controller can change functions and be used for other functions, such as for example, controlling crosshairs in a shooting game. Thus, the detected movements, motions and/or manipulations of the entire controller body by the user may be used as additional commands to control various aspects of the game or other simulation being played.

In some embodiments, as an optional feature, the gearing of the manipulation to two-dimensional mapping may be adjusted or throttled so the user can move the cursor faster or slower based on the level of throttle that is chosen. This provides the user with flexibility in choosing the speed at which the cursor, crosshairs, etc., move in response to the motions and movements of the controller. Such gearing may be adjusted using any buttons or controls on the controller. By way of example, in some embodiments the hearing may be throttled using the variable buttons L2 and R2 (FIGS. 1B, 1C, 1D, and 1E) or any other buttons or controls.

As mentioned above, the three-dimensional movements of the hand-held controller may be tracked in many different ways, such as for example through inertial, video, acoustical, or infrared analysis as described above, or in any other manner. Referring to FIG. 9, there is illustrated a system **900** that operates in accordance with an embodiment of the present invention. As described above, "mixed model" signals may be used whereby signals from one type of sensor may provide part of the tracking information input and signals generated from another type of sensor may provide another part of the tracking information input. As such, in one embodiment a feedback loop may comprise a mixer **902** that may be used to mix signals from any number of different types of sensors **904**, such as inertial, video, acoustical, or infrared sensors. The output from the mixer **902** is then mapped to the two-dimensional image plane of the screen by a mapper **904** or the like. Images are then displayed **906** on the 2D image plane of the screen.

In this way the 3D movements, motions and manipulations of a controller may be sensed and tracked and then mapped through a mixer back to the 2D platform on the screen. By way of example, if video tracking is used, the 3D movements of the controller are cast onto the 2D image plane of the camera, and then the controller movements and transformations from the perspective of the 2D image plane of the camera are mapped onto the 2D platform of the screen.

In other embodiments of the present invention either the X or Y coordinate of the two-dimensional image plane of the screen may optionally stay locked. This way, when a player moves the controller in various directions the image that is displayed on the screen moves only in one direction because one of the X and Y coordinates may be locked. For example, FIG. 10 illustrates a system that operates in accordance with another embodiment of the present invention. In this embodiment, a user or player may be walking through a three-dimensional space displayed on a screen **1002** with the camera panning and moving through the game. A set of crosshairs **1004** of the user's gun or the like are mapped to the X-Y coordinates of the two-dimensional image plane of the screen **1002** over the three-dimensional space.

In this example the Y coordinate is locked. As such, a sideways and upward movement **1010** of the controller body **1006** causes the two-dimensional crosshairs **1004** to move sideways along only the X axis from one position **1012** to another position **1014**. The crosshairs **1004** move only along the X axis because the Y axis has been locked.

In some embodiments the user can hold a button down, which locks in one of the axes. For example, the button may lock in the Y coordinate so wherever the user moves the controller, the image on the screen will move only along the X axis. That is, the Y coordinate will stay fixed. Thus, the user can twist the controller to the right and slide all the way to the right on the X axis, or twist the controller to the left and slide all the way to the left along the X axis. In some embodiments, when the user pushes the button again, this may be configured to unlock the previously locked axis, which again provides the user with full degrees of movement. In some embodiments, the user may push another button to lock in the X-coordinate, which allows the user to slide the crosshairs only up and down.

The hand-held controller may comprise any type of controller in accordance with various embodiments of the present invention. For example, while a video game console controller is illustrated, the controller may instead comprise any other type of controller, such as a traditional controller for a television, stereo, DVD player, etc. By way of example, FIG. 11A illustrates a traditional television controller **1102** that may be used in accordance with various embodiments of the present invention. Or, the controller may instead comprise any other type of object that may be tracked in the manner described herein. By way of example, FIG. 11B illustrates such an object **1104** that may be used in accordance with various embodiments of the present invention.

In some embodiments the position and yaw of the controller may be additive. This would allow controller movements to continue to move the cursor or cross-hairs in the same direction so that the movements "add" to the previous movements.

As mentioned above, detecting and tracking a user's manipulations of a game controller body may be implemented in different ways. For example, an inertial sensor, such as an accelerometer or gyroscope, an image capture unit, such as a digital camera, can be used with the computer entertainment system to detect motions of the hand-held controller body and transfer them into actions in a game. Examples of tracking a controller with an inertial sensor are described, e.g., in U.S. patent application Ser. No. 11/382,033, entitled "SYSTEM, METHOD, AND APPARATUS FOR THREE-DIMENSIONAL INPUT CONTROL", which is incorporated herein by reference. Examples of tracking a controller using image capture are described, e.g., in U.S. patent application Ser. No. 11/382,034, entitled "SCHEME FOR DETECTING AND TRACKING USER MANIPULATION OF A GAME CONTROLLER BODY", which is incorporated herein by reference. In addition, the controller and/or the user may also be tracked acoustically using a microphone array and appropriate signal processing. Examples of such acoustic tracking are described in U.S. patent application Ser. No. 11/381,721, which is incorporated herein by reference.

Acoustic sensing, inertial sensing and image capture can be used individually or in any combination to detect many different types of motions of the controller, such as for example up and down movements, twisting movements, side to side movements, jerking movements, wand-like motions, plunging motions, etc. Such motions may correspond to various commands such that the motions are transferred into actions in a game. Detecting and tracking the user's manipulations of a game controller body can be used to implement many different types of games, simulations, etc., that allow the user to, for example, engage in a sword or lightsaber fight, use a wand to trace the shape of items, engage in many different types of sporting events, engage in

on-screen fights or other encounters, etc. A game program may be configured to track the motion of the controller and recognize certain pre-recorded gestures from the tracked motion. Recognition of one or more of these gestures may trigger a change in the game state.

As mention above, in some embodiments of the present invention controller path information obtained from these different sources may be mixed prior to analysis for gesture recognition. The tracking data from different sources (e.g., acoustic, inertial and image capture) may be mixed in a way that improves the likelihood of recognition of a gesture.

As discussed above, data from inertial, image capture and acoustic sources may be analyzed to generate a path that tracks the position and/or orientation of the controller. As shown in the block diagram of FIG. 12 a system 1200 according to an embodiment of the invention may include an inertial analyzer 1202, an image analyzer 1204 and an acoustic analyzer 1206. Each of these analyzers receives signals from a sensed environment. The analyzers 1202, 1206, 1208 may be implemented in hardware, in software (or firmware) or some combination of two or more of these. Each of the analyzers produces tracking information related the position and/or orientation of an object of interest. By way of example, the object of interest may be the controller 110 referred to above. The image analyzer 1204 may operate in connection with and to form fields below and with respect to methods described in U.S. patent application Ser. No. 11/382,034. The inertial analyzer 1202 may operate in connection with and to form fields below and with respect to methods described in U.S. patent application Ser. No. 11/382,033, entitled "SYSTEM, METHOD, AND APPARATUS FOR THREE-DIMENSIONAL INPUT CONTROL". The acoustic analyzer 1206 may operate in connection with and to form fields below and with respect to methods described in U.S. patent application Ser. No. 11/381,724.

The analyzers 1202, 1204 and 1206 may be regarded as being associated with different channels of inputs of position and/or orientation information. The Mixer 1208 may accept multiple input channels and such channels may contain sample data characterizing the sensed environment, typically from the perspective of the channel. The position and/or orientation information generated by the inertial analyzer 1202, image analyzer 1204 and acoustic analyzer 1206 can be coupled into the input of a mixer 1208. The Mixer 1208 and analyzers 1202, 1204, 1206 may be queried by a game software 1210 and may be configured to interrupt game software in response to events. Events may include gesture recognition events, gearing changes, configuration changes, setting noise levels, setting sampling rate, changing mapping chains, etc, examples of which are discussed below. The mixer 1208 may operate in connection with and to form fields below and with respect to methods described herein.

As discussed above, signals from different input channels, e.g., inertial sensors, video images and/or acoustic sensors may be analyzed by the inertial analyzer 1202, image analyzer 1204 and acoustic analyzer 1206, respectively, to determine the motion and/or orientation of the controller 110 during play of a video game according to an inventive method. Such a method may be implemented as a series of processor executable program code instructions stored in a processor readable medium and executed on a digital processor.

For example, as depicted in FIG. 13A, the video game system 100 may include on the console 102 having the inertial analyzer 1202, image analyzer 1204 and acoustic

analyzer 1206 implemented either in hardware or software. By way of example, the analyzers 1202, 1204, 1206 may be implemented as software instructions running on a suitable processor unit 1302. By way of example, the processor unit 1302 may be a digital processor, e.g., a microprocessor of a type commonly used in video game consoles. A portion of the instructions may be stored in a memory 1306. Alternatively, the inertial analyzer 1202, image analyzer 1204 and acoustic analyzer 1206 may be implemented in hardware, e.g., as an application specific integrated circuit (ASIC). Such analyzer hardware may be located on the controller 110 or on the console 102 or may be remotely located elsewhere. In hardware implementations, the analyzers 1202, 1204, 1206 may be programmable in response to external signals e.g., from the processor 1302 or some other remotely located source, e.g., connected by USB cable, wireless connection, or over a network.

The inertial analyzer 1202 may include or implement instructions that analyze the signals generated by an inertial sensor 113 and utilize information regarding position and/or orientation of the controller 110. Similarly, the image analyzer 1204 may implement instructions that analyze images captured by the image capture unit 112. In addition, the acoustic analyzer may implement instructions that analyze images captured by a microphone array 118. As shown in the flow diagram 1310 of FIG. 13B these signals and/or images may be received by the analyzers 1202, 1204, 1206 as indicated at block 1312. The signals and/or images may be analyzed by the analyzers 1202, 1204, 1206 to determine inertial tracking information 1203, image tracking information 1205 and acoustic tracking information 1207 regarding the position and/or orientation of the controller 110 as indicated at block 1314. The tracking information 1203, 1205, 1207 may be related to one or more degrees of freedom. It is preferred that six degrees of freedom are tracked to characterize the manipulation of the controller 110 or other tracked object. Such degrees of freedom may relate to the controller tilt, yaw, roll and position, velocity or acceleration along the x, y and z-axis.

In some embodiments the controller 110 may also include an acoustic signal generator 115 (e.g., a speaker) to provide a source of sound to facilitate acoustic tracking of the controller 110 with the microphone array 118 and appropriate acoustic signal processing, e.g., as described in U.S. patent application Ser. No. 11/381,724, which is incorporated herein by reference.

As indicated at block 1316, the mixer 1208 mixes the inertial information 1203, image information 1205 and acoustic information 1207 to generate refined position and/or orientation information 1209. By way of example, the mixer 1208 may apply different weights the inertial, image and acoustic tracking information 1203, 1205, 1207 based on game or environmental conditions and the take a weighted average. In addition, the mixer 1208 may include its own mixer analyzer 1304 that analyzes the combined position/orientation information and generates its own resulting "mixer" information that involves combinations of the information generated by the other analyzers.

In an embodiment of the present invention the mixer 1208 may assign a distribution value to the tracking information 1203, 1205, 1207 from the analyzers 1202, 1204, 1206. As noted above, certain sets of input control data may be averaged. In the present embodiment, however, the input control data is assigned a value prior to its being averaged whereby the input control data from some analyzers is of more analytical importance than from others.

The mixer **1208** may take on a number of functionalities in the context of the present system including observation, correction, stabilization, derivation, combination, routing, mixing, reporting, buffering, interrupting other processes and analysis. Such may be performed with respect to the tracking information **1203**, **1205**, **1207** received from one or more of the analyzers **1202**, **1204**, **1206**. While each of the analyzers **1202**, **1204**, **1206** may receive and/or derive certain tracking information, the mixer **1208** may be implemented to optimize the use of the received tracking information **1203**, **1205**, **1207** and generate refined tracking information **1209**.

The analyzers **1202**, **1204**, **1206** and mixer **1208** are preferably configured to provide tracking information similar output formats. Tracking information parameters from any analyzer element **1202**, **1204**, **1206** can be mapped to a single parameter in an analyzer. Alternatively, the mixer **1208** may form tracking information for any of the analyzers **1202**, **1204**, **1206** by processing one or more tracking information parameters from one or more of analyzers **1202**, **1204**, **1206**. The mixer may combine two or more elements of tracking information of the same parameter type taken from the analyzers **1202**, **1204**, **1206** and/or perform functions across multiple parameters of tracking information generated by the analyzers to create a synthetic set of output having the benefit of being generated from multiple channels of input.

The refined tracking information **1209** may be utilized during play of a video game with the system **100** as indicated at block **1318**. In certain embodiments, the position and/or orientation information may be used in relation to gestures made by the user **108** during game play. In some embodiments the mixer **1208** may operate in conjunction with the gesture recognizer **1305** to associate at least one action in a game environment with one or more user actions from the user (e.g., manipulation of the controller in space).

As indicated in the flow diagram **1320** of FIG. **13C**, a path of the controller **110** may be tracked using the position and/or orientation information as indicated at block **1322**. By way of example, and without limitation, the path may include a set of points representing a position of the center of mass of the controller with respect to some system of coordinates. Each position point may be represented by one or more coordinates, e.g., X, Y and Z coordinates in a Cartesian coordinate system. A time may be associated with each point on the path so that both the shape of the path and the progress of the controller along the path may be monitored. In addition, each point in the set may have associated with it data representing an orientation of the controller, e.g., one or more angles of rotation of the controller about its center of mass. Furthermore, each point on the path may have associated with it values of velocity and acceleration of the center of mass of the controller and rates of angular rotation and angular acceleration of the controller about its center of mass.

As indicated at block **1324**, the tracked path may be compared to one or more stored paths corresponding to known and/or pre-recorded gestures **1308** that are relevant to the context of the video game being played. Recognizer **1305** may be configured to recognize a user or process audio authenticated gestures, etc. For example, a user may be identified by the recognizer **1305** through a gesture and that a gesture may be specific to a user. Such a specific gestures may be recorded and included among the pre-recorded gestures **1308** stored in memory **1306**. The recordation process may optionally store audio generated during recordation of a gesture. The sensed environment is sampled into a multi-

channel analyzer and processed. The processor may reference gesture models to determine and authenticate and/or identify a user or objects based on voice or acoustic patterns and to a high degree of accuracy and performance.

As indicated in FIG. **13A**, data **1308** representing the gestures may be stored in the memory **1306**. Examples of gestures include, but are not limited to throwing an object such as a ball, swinging an object such as a bat or golf club, pumping hand pump, opening or closing a door or window, turning steering wheel or other vehicle control, martial arts moves such as punches, sanding movements, wax on wax off, paint the house, shakes, rattles, rolls, football pitches, turning knob movements, 3D MOUSE movements, scrolling movements, movements with known profiles, any recordable movement, movements along any vector back and forth i.e. pump the tire but at some arbitrary orientation in space, movements along a path, movements having precise stop and start times, any time based user manipulation that can be recorded, tracked and repeated within the noise floor, splines, and the like. Each of these gestures may be pre-recorded from path data and stored as a time-based model. Comparison of the path and stored gestures may start with an assumption of a steady state if the path deviates from a steady state the path can be compared to the stored gestures by a process of elimination. If at block **1326** there is no match, the analyzer **1304** may continue tracking the path of the controller **110** at block **1322**. If there is a sufficient match between the path (or a portion thereof) and a stored gesture the state of the game may be changed as indicated at **1328**. Changes of state of the game may include, but are not limited to interrupts, sending control signals, changing variables, etc.

Here is one example of this can occur. Upon determining that the controller **110** has left a steady state the path an analyzer **1202**, **1204**, **1206**, or **1304** tracks movement of the controller **110**. As long as the path of the controller **110** complies with a path defined in the stored gesture models **1308**, those gestures are possible "hits". If the path of the controller **110** deviates (within the noise tolerance setting) from any gesture model **1308**, that gesture model is removed from the hit list. Each gesture reference model includes a time-base in which the gesture is recorded. The analyzer **1202**, **1204**, **1206**, or **1304** compares the controller path data to the stored gestures **1308** at the appropriate time index. Occurrence of a steady state condition resets the clock. When deviating from steady state (i.e. when movements are tracked outside of the noise threshold) the hit list is populated with all potential gesture models. The clock is started and movements of the controller are compared against the hit list. Again, the comparison is a walk through time. If any gesture in the hit list reaches the end of the gesture then it is a hit.

In some embodiments of the present invention the mixer **1208** may assign a distribution value to the tracking information **1203**, **1205**, **1207** from the analyzers **1202**, **1204**, **1206**. As noted above, certain sets of input control data may be averaged. In the present embodiment, however, the input control data is assigned a value prior to its being averaged whereby the input control data from some analyzers is of more analytical importance than from others.

For example, the mixer **1208** may require tracking information related to acceleration and steady state. The mixer **1208** would then receive the tracking information **1203**, **1205**, **1207** as described above. The tracking information may include parameters relating to acceleration and steady state, e.g., as described above. Prior to averaging the data representing this information, the mixer **1208** may assign

distribution values to tracking information data set **1203**, **1205**, **1207**. For example, the x- and y-acceleration parameters from the inertial analyzer **1202** may be weighted at a value of 90%. The x- and y-acceleration data from the image analyzer **1206**, however, may be weighted at only 10%. The acoustic analyzer tracking information **1207** as it pertains to acceleration parameters may be weighted at zero percent, that is, the data has no value.

Similarly, the Z-axis tracking information parameters from the inertial analyzer **1202** may be weighted at 10% whereas the image analyzer Z-axis tracking information may be weighted at 90%. The acoustic analyzer tracking information **1207** may, again, be weighted at 0% value but steady state tracking information from the acoustic analyzer **1206** may be weighted at 100% with the remaining analyzer tracking information be weighted at 0%.

After the appropriate distribution weight has been assigned, the input control data may be averaged in conjunction with that weight to arrive at a weighted average input control data set that is subsequently analyzed by the gesture recognizer **1305** and associated with a particular action in the game environment. The values associated may be pre-defined by the mixer **1208** or by a particular game title. The values may also be the result of the mixer **1208** identifying a particular quality of data coming from the various analyzers and thus making a dynamic adjustment as is further discussed below. The adjustment may also be the result of building a historical knowledge base of when particular data is of particular value in a particular environment and/or in response to the particularities of a given game title.

The mixer **1208** may be configured to operate dynamically during game play. For example, as the mixer **1208** receives various input control data, it may recognize that certain data is consistently outside an acceptable range or quality of data or reflects corrupt data that may be indicative of a processing error at the related input device.

Additionally, certain conditions in a real-world environment might change. For example, natural light in the user's at-home game environment might be increasing as the morning turns to afternoon causing problems with image data capture. Further, a neighborhood or household might become noisier as the day goes on causing problems with audio data capture. Likewise, if a user has been playing for several hours, their reflexes may become less sharp thus causing problems with interpretation of inertial data.

In these instances, or in any other instance wherein the quality of a particular form of input control data is in question, the mixer **1208** may dynamically reassign distribution weight to a particular set of data coming from a particular device such that more or less importance is given to particular input control data as described above. Similarly, the game environment may change over the course of the game wherein the needs of a particular game change thus requiring a reassignment of value or need for particular input control data.

Similarly, the mixer **1208** may recognize that certain data being passed on to the gesture recognizer **1305** is being processed incorrectly, slowly, or not at all based on processing errors or feedback data that may be generated by the gesture recognizer **1305**. In response to this feedback or in recognition of these processing difficulties (e.g., while the image analysis data is within an acceptable range, errors result when an association is made by the gesture recognizer **1305**), the mixer **1208** may adjust what input control data it seeks from what analyzer and when, if at all. The mixer **1208** may further require certain analysis and processing of input

control data by the proper analyzer before it is passed to the mixer **1208**, which may re-process the data (e.g., average the data) such that a further layer of assurance is made that the data passed to the gesture recognizer **1305** will be processed effectively and appropriately.

In some embodiments, the mixer **1208** may recognize that certain data is corrupt, ineffective, or outside a particular variable and may call upon particular input control data or variable related to that data such that it may replace incorrect data or properly analyze and calculate certain data with respect to the necessary variables.

Referring to FIG. **14**, there is illustrated a method **1400** in accordance with an embodiment of the present invention. The method **1400** provides another example of how information from the various sensors may be used, combined and/or mixed to perform tracking of an object such as a controller.

In one example implementation, the method **1400** may be used to track the position of a controller using a video camera where tilt information provided by a sensor in the controller, such as a gyro sensor or accelerometer, is used to optimize controller image detection. Controller image detection is optimized by using a translated compare in which a reference detect profile image of the controller is rotated in accordance with the tilt angle of the controller provided by the sensor.

More specifically, the method **1400**, which may be used in obtaining input data from an object such as a controller, begins in step **1402** where a live image of the object is captured with an image capture device. The image capture device may comprise any type of camera, such as any type of camera described herein. For example, in some embodiments the image capture device may comprise a Z-camera or depth camera or some other type of three-dimensional camera. Such a Z-camera or depth camera may, as described above, provide or measure a depth of each pixel and/or determine the distance of a pixel from the camera.

FIG. **15** illustrates an example of this step. Namely, a live image **1502** of an object **1504** is captured. In some embodiments the object **1504** may comprise a controller. As illustrated, the object **1504** is located in the upper left corner of the camera's field of view.

In step **1404** (FIG. **14**) information related to a tilt angle of the object is received from one or more sensors other than the image capture device. By way of example, the one or more sensors may comprise any one or more of a gyro sensor, accelerometer, or similar sensor. Such sensors may be located in the object.

In some embodiments the gyro sensor may be used if rotation of the object is about the gyro axis. The accelerometer readings and the direction of gravity may be used in all situations. Using the accelerometer readings has the benefit of getting an absolute angular answer that does not drift. In some embodiments both sensors may be used if rotation is about the gyro axis. In some embodiments the information related to the tilt angle of the object may be used to determine or estimate the tilt angle of the object.

Measuring the tilt angle of the object is beneficial because knowing the tilt angle helps the camera tracking, as will be described below. Using the tilt angle is also beneficial because controllers of the type described hereinabove having the ability to be tracked in six degrees of freedom can measure tilt fairly easily. Furthermore, rotation is awkward to measure using a camera.

In step **1406** the information related to a tilt angle of the object is used to obtain at least one rotated reference image of the object. By way of example, the basic reference image

of the object may comprise a profile view of the object, a top view of the object, a view of a user's hand or hands holding the object, or some other view. Thus, in embodiments where the object comprises a controller, the basic reference image of the object may comprise a profile view of the controller, a top view of the controller, a view of the user's hand or hands holding the controller, or some other view.

FIG. 15 illustrates an example of a basic reference image 1506 of the object 1504, which is labeled 1504'. As illustrated, the object 1504' is not rotated.

In some embodiments, a rotated reference image of the object may be obtained by rotating the reference image on-the-fly using the information related to a tilt angle of the object or a determined tilt angle of the object. Or, in some embodiments a set of rotated versions of the reference image may be stored in memory. The information related to a tilt angle of the object, or a determined tilt angle of the object, may be used to select the corresponding rotated reference image from the stored set. The rotated reference image of the object may then be obtained by retrieving it from storage.

FIG. 15 illustrates an example of a rotated reference image 1508 of the object 1504, which is labeled 1504". As illustrated, the object 1504" is rotated in a manner that is the same or similar to the rotation of the object 1504 in the live image 1502.

It was mentioned above that in step 1406 at least one rotated reference image of the object is obtained. The language "at least one" is used because in some embodiments the information related to a tilt angle of the object is used to obtain more than one rotated reference image of the object. Each rotated reference image may be at a slightly different angle around the tilt angle of the object. And in some embodiments, the information related to a tilt angle of the object is used to generate a "set" of rotated reference images around the tilt angle rather than just one reference image exactly at the tilt angle. This way, the tilt angle measurement may be noisy and imperfect because the set will provide rotated reference images having a variety of angles near the tilt angle. The number of rotated reference images in the set may vary depending on the particular application, implementation and level of accuracy needed.

FIG. 16 illustrates an example set of rotated reference images 1602, 1604, 1606, 1608 of the object 1504" around the tilt angle. The tilt angle of the object 1504" in each image is slightly different.

In step 1408 (FIG. 14) the live image of the object is compared with the one or more rotated reference images of the object. In general, the image capture unit looks for an image of the object in the x and y planes, and the image it is looking for is a translated image that reflects the angle of the object as provided by the tilt sensor or accelerometer. Thus, a benefit of the tilt measurement is that instead of matching all possible rotations of the reference image, the image capture unit just needs to check rotations close to the measured tilt angle. The rotations may be close to the measured tilt angle within a determined error tolerance, which might be based on the noise of the tilt sensor. Because the live image is compared against the appropriately rotated reference image, the rotation degree of freedom does not need to be searched during the comparison process, thereby decreasing the comparison calculation cost and increasing the comparison quality.

An optional approach used in some embodiments is to first attempt to match tilt angles around the previously matched tilt angle. This way, even if a tilt angle sensor sporadically produces "bad" data, the camera tracking may not be significantly impacted.

FIG. 15 illustrates an example of such a comparison. Namely, the live image 1502 of the object 1504 is compared with the rotated reference image 1508 of the object 1504". In embodiments where more than one rotated reference image is used as described above, the live image 1502 of the object 1504 is compared with some or all of the rotated reference images. Thus, in some embodiments, the information relating to the tilt angle of the object is used to obtain a plurality of rotated reference images of the object, and then the live image of the object is compared with each of the plurality of rotated reference images of the object.

Finally, in step 1410 (FIG. 14) an indication is generated in response to the live image matching one of the rotated reference images. The indication may comprise any type of flag or signal to indicate to software and/or hardware that a match between the live image and one of the rotated reference images has occurred.

In some embodiments, tracking of the object may be performed by determining the location in the live image where the matches occur. For example, in FIG. 15 a match occurs when the object 1504 is located in the upper left corner of the camera's field of view. This information may be used to determine the location of the object 1504. Additional matches may be used to track the object 1504's movements.

In some embodiments, the one or more reference images and live image may be passed through one or more normalizing filters. This may help to make matching more reliable by evening out lighting variations. By way of example, such normalizing filters may comprise Laplacian, Laplacian of Gaussian, signum of Laplacian of Gaussian, or any other type of filter having similar effects.

Thus, by translating or rotating the reference detect profile image of an object according to the tilt angle of the object provided by a sensor, object image detection may be optimized. Such object image detection may then be used for tracking the position of the object. For example, the method may be used for controller tracking using video input. While using the tilt angle of the object is beneficial, in some embodiments the displacement of the controller may alternatively or additionally be a cue to help the camera tracking for scale changes or horizontal/vertical motion.

It should be well understood that the object may comprise any type of object, such as any type of controller. For example, the object may comprise a remote control of the type that is used for a television, stereo, DVD player, etc. In some embodiments, the above described methods and techniques may be used with two or more controllers simultaneously. For example, the methods and techniques may be used with respect to a controller in each hand of a user, for controllers operated by multiple users, or for similar scenarios. The methods and techniques may be used to simultaneously detect and/or track all such controllers.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/624,637, filed Jan. 18, 2007, entitled "METHOD AND SYSTEM FOR ADDING A NEW PLAYER TO A GAME IN RESPONSE TO CONTROLLER ACTIVITY", is hereby fully incorporated by reference herein in its entirety.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/551,682, filed Oct. 20, 2006, entitled "GAME CONTROL USING THREE-DIMENSIONAL MOTIONS OF CONTROLLER", is hereby fully incorporated by reference herein in its entirety.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/551,197, filed Oct. 19, 2006, entitled "CONTROLLER CONFIGURED TO TRACK USER'S

LEVEL OF ANXIETY AND OTHER MENTAL AND PHYSICAL ATTRIBUTES”, is hereby fully incorporated by reference herein in its entirety.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/536,559, filed Sep. 28, 2006, entitled “MAPPING MOVEMENTS OF A HAND-HELD CONTROLLER TO THE TWO-DIMENSIONAL IMAGE PLANE OF A DISPLAY SCREEN”, is hereby fully incorporated by reference herein in its entirety.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/382,699, filed May 10, 2006, entitled “ATTACHABLE STRUCTURE FOR USE WITH HAND-HELD CONTROLLER HAVING TRACKING ABILITY”, is hereby fully incorporated by reference herein in its entirety.

The entire disclosure of U.S. Provisional Patent Application No. 60/718,145, entitled “AUDIO, VIDEO, SIMULATION, AND USER INTERFACE PARADIGMS”, filed Sep. 15, 2005, is hereby fully incorporated by reference herein in its entirety.

The following applications are all hereby fully incorporated herein by reference in their entireties: U.S. patent application Ser. No. 10/207,677, entitled, “MAN-MACHINE INTERFACE USING A DEFORMABLE DEVICE”, filed on Jul. 27, 2002; U.S. patent application Ser. No. 10/650,409, entitled, “AUDIO INPUT SYSTEM”, filed on Aug. 27, 2003; U.S. patent application Ser. No. 10/663,236, entitled “METHOD AND APPARATUS FOR ADJUSTING A VIEW OF A SCENE BEING DISPLAYED ACCORDING TO TRACKED HEAD MOTION”, filed on Sep. 15, 2003; U.S. patent application Ser. No. 10/759,782, entitled “METHOD AND APPARATUS FOR LIGHT INPUT DEVICE”, filed on Jan. 16, 2004; U.S. patent application Ser. No. 10/820,469, entitled “METHOD AND APPARATUS TO DETECT AND REMOVE AUDIO DISTURBANCES”, filed on Apr. 7, 2004; and U.S. patent application Ser. No. 11/301,673, entitled “METHOD FOR USING RELATIVE HEAD AND HAND POSITIONS TO ENABLE A POINTING INTERFACE VIA CAMERA TRACKING”, filed on Dec. 12, 2005, all of which are hereby incorporated by reference.

The following applications are all hereby fully incorporated herein by reference in their entireties: U.S. patent application Ser. No. 11/381,729, to Xiadong Mao, entitled “ULTRA SMALL MICROPHONE ARRAY”, filed on May 4, 2006, application Ser. No. 11/381,728, to Xiadong Mao, entitled “ECHO AND NOISE CANCELLATION”, filed on May 4, 2006, U.S. patent application Ser. No. 11/381,725, to Xiadong Mao, entitled “METHODS AND APPARATUS FOR TARGETED SOUND DETECTION”, filed on May 4, 2006, U.S. patent application Ser. No. 11/381,727, to Xiadong Mao, entitled “NOISE REMOVAL FOR ELECTRONIC DEVICE WITH FAR FIELD MICROPHONE ON CONSOLE”, filed on May 4, 2006, U.S. patent application Ser. No. 11/381,724, to Xiadong Mao, entitled “METHODS AND APPARATUS FOR TARGETED SOUND DETECTION AND CHARACTERIZATION”, filed on May 4, 2006, U.S. patent application Ser. No. 11/381,721, to Xiadong Mao, entitled “SELECTIVE SOUND SOURCE LISTENING IN CONJUNCTION WITH COMPUTER INTERACTIVE PROCESSING”, filed on May 4, 2006; all of which are hereby incorporated by reference.

The following applications are all hereby fully incorporated herein by reference in their entireties: co-pending application Ser. No. 11/418,988, to Xiadong Mao, entitled “METHODS AND APPARATUSES FOR ADJUSTING A LISTENING AREA FOR CAPTURING SOUNDS”, filed

on May 4, 2006; co-pending application Ser. No. 11/418,989, to Xiadong Mao, entitled “METHODS AND APPARATUSES FOR CAPTURING AN AUDIO SIGNAL BASED ON VISUAL IMAGE”, filed on May 4, 2006; co-pending application Ser. No. 11/429,047, to Xiadong Mao, entitled “METHODS AND APPARATUSES FOR CAPTURING AN AUDIO SIGNAL BASED ON A LOCATION OF THE SIGNAL”, filed on May 4, 2006; co-pending application Ser. No. 11/429,133, to Richard Marks et al., entitled “SELECTIVE SOUND SOURCE LISTENING IN CONJUNCTION WITH COMPUTER INTERACTIVE PROCESSING”, filed on May 4, 2006; and co-pending application Ser. No. 11/429,414, to Richard Marks et al., entitled “COMPUTER IMAGE AND AUDIO PROCESSING OF INTENSITY AND INPUT DEVICES FOR INTERFACING WITH A COMPUTER PROGRAM”, filed on May 4, 2006, all of the entire disclosures of which are incorporated herein by reference.

The following applications are all hereby fully incorporated herein by reference in their entireties: U.S. patent application Ser. No. 11/382,031, entitled “MULTI-INPUT GAME CONTROL MIXER”, filed on May 6, 2006; U.S. patent application Ser. No. 11/382,032, entitled “SYSTEM FOR TRACKING USER MANIPULATIONS WITHIN AN ENVIRONMENT”, filed on May 6, 2006; U.S. patent application Ser. No. 11/382,033, entitled “SYSTEM, METHOD, AND APPARATUS FOR THREE-DIMENSIONAL INPUT CONTROL”, filed on May 6, 2006; U.S. patent application Ser. No. 11/382,035, entitled “INERTIALLY TRACKABLE HAND-HELD CONTROLLER”, filed on May 6, 2006; U.S. patent application Ser. No. 11/382,036, entitled “METHOD AND SYSTEM FOR APPLYING GEARING EFFECTS TO VISUAL TRACKING”, filed on May 6, 2006; U.S. patent application Ser. No. 11/382,041, entitled “METHOD AND SYSTEM FOR APPLYING GEARING EFFECTS TO INERTIAL TRACKING”, filed on May 7, 2006; U.S. patent application Ser. No. 11/382,038, entitled “METHOD AND SYSTEM FOR APPLYING GEARING EFFECTS TO ACOUSTICAL TRACKING”, filed on May 6, 2006; U.S. patent application Ser. No. 11/382,040, entitled “METHOD AND SYSTEM FOR APPLYING GEARING EFFECTS TO MULTI-CHANNEL MIXED INPUT”, filed on May 7, 2006; U.S. patent application Ser. No. 11/382,034, entitled “SCHEME FOR DETECTING AND TRACKING USER MANIPULATION OF A GAME CONTROLLER BODY”, filed on May 6, 2006; U.S. patent application Ser. No. 11/382,037, entitled “SCHEME FOR TRANSLATING MOVEMENTS OF A HAND-HELD CONTROLLER INTO INPUTS FOR A SYSTEM”, filed on May 6, 2006; U.S. patent application Ser. No. 11/382,043, entitled “DETECTABLE AND TRACKABLE HAND-HELD CONTROLLER”, filed on May 7, 2006; U.S. patent application Ser. No. 11/382,039, entitled “METHOD FOR MAPPING MOVEMENTS OF A HAND-HELD CONTROLLER TO GAME COMMANDS”, filed on May 7, 2006; U.S. Design patent application No. 29/259,349, entitled “CONTROLLER WITH INFRARED PORT”, filed on May 6, 2006; U.S. Design patent application No. 29/259,350, entitled “CONTROLLER WITH TRACKING SENSORS”, filed on May 6, 2006; U.S. Patent Application No. 60/798,031, entitled “DYNAMIC TARGET INTERFACE”, filed on May 6, 2006; and U.S. Design patent application No. 29/259,348, entitled “TRACKED CONTROLLER DEVICE”, filed on May 6, 2006; all of which are hereby incorporated herein by reference in their entireties.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/430,594, to Gary Zalewski and Riley R. Russell, entitled "Profile Detection", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/430,593, to Gary Zalewski and Riley R. Russell, entitled "Using Audio/Visual Environment To Select Ads On Game Platform", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/400,997, filed on Apr. 10, 2006, to Larsen and Chen, entitled "System And Method For Obtaining User Information From Voices", is incorporated herein by reference.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/382,259, to Gary Zalewski et al., entitled "Method and apparatus for use in determining lack of user activity in relation to a system", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/382,258, to Gary Zalewski et al., entitled "Method and apparatus for use in determining an activity level of a user in relation to a system", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/382,251, to Gary Zalewski et al., entitled "Handheld controller having detectable elements for tracking purposes", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/382,252, entitled "TRACKING DEVICE FOR USE IN OBTAINING INFORMATION FOR CONTROLLING GAME PROGRAM EXECUTION", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/382,256 entitled "TRACKING DEVICE WITH SOUND EMITTER FOR USE IN OBTAINING INFORMATION FOR CONTROLLING GAME PROGRAM EXECUTION", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. patent application Ser. No. 11/382,250 entitled "OBTAINING INPUT FOR CONTROLLING EXECUTION OF A GAME PROGRAM", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,744, entitled "VIDEO GAME CONTROLLER FRONT FACE", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,743, entitled "VIDEO GAME CONTROLLER", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,767, entitled "VIDEO GAME CONTROLLER", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,768, entitled "VIDEO GAME CONTROLLER", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,763, entitled "ERGONOMIC GAME CONTROLLER DEVICE WITH LEDS AND OPTICAL PORTS", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,759, entitled "GAME CONTROLLER DEVICE WITH LEDS AND OPTICAL PORTS", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,765, entitled "DESIGN FOR OPTICAL GAME CONTROLLER INTERFACE", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,766, entitled "DUAL GRIP GAME CONTROL DEVICE WITH LEDS AND OPTICAL PORTS", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,764, entitled "GAME INTERFACE DEVICE WITH LEDS AND OPTICAL PORTS", filed on May 8, 2006, is incorporated herein by reference.

The entire disclosure of co-pending U.S. Design patent application No. 29/246,762, entitled "ERGONOMIC GAME INTERFACE DEVICE WITH LEDS AND OPTICAL PORTS", filed on May 8, 2006, is incorporated herein by reference.

While the invention herein disclosed has been described by means of specific embodiments and applications thereof, numerous modifications and variations could be made thereto by those skilled in the art without departing from the scope of the invention set forth in the claims.

What is claimed is:

1. A method for use in obtaining input data from an object, comprising:
 - capturing a live image of the object with an image capture device;
 - receiving information related to a tilt angle of the object from one or more sensors other than the image capture device;
 - using the information related to a tilt angle of the object to obtain at least one rotated reference image of the object;
 - comparing the live image of the object with the rotated reference image of the object; and
 - generating an indication in response to the live image matching the rotated reference image.
2. A method in accordance with claim 1, wherein the one or more sensors other than the image capture device comprises a gyro sensor *used* in the object.
3. A method in accordance with claim 1, wherein the one or more sensors other than the image capture device comprises an accelerometer *used* in the object.
4. A method in accordance with claim 1, wherein the rotated reference image of the object is obtained by retrieving it from storage.
5. A method in accordance with claim 1, wherein the rotated reference image of the object is obtained by rotating a reference image of the object.
6. A method in accordance with claim 1, further comprising:
 - passing the live image of the object and the rotated reference image of the object through a normalizing filter.
7. A method in accordance with claim 1, wherein the image capture device [comprises] *functions as* a camera.
8. A method in accordance with claim 1, wherein the image capture device [comprises] *functions as* a Z-camera.
9. A method in accordance with claim 1, wherein the object [comprises] *functions as* a hand-held controller.
10. A method in accordance with claim 1, wherein the information relating to the tilt angle of the object is used to

obtain a plurality of rotated reference images of the object, and the live image of the object is compared with each of the plurality of rotated reference images of the object.

11. An apparatus for use in obtaining input data from an object, comprising:

an image capture device configured to capture a live image of the object; and

a processor based system configured to receive information related to a tilt angle of the object from one or more sensors other than the image capture device, use the information related to a tilt angle of the object to obtain at least one rotated reference image of the object, compare the live image of the object with the rotated reference image of the object, and generate an indication in response to the live image matching the rotated reference image.

12. An apparatus in accordance with claim 11, wherein the one or more sensors other than the image capture device comprises a gyro sensor in the object.

13. An apparatus in accordance with claim 11, wherein the one or more sensors other than the image capture device comprises an accelerometer in the object.

14. An apparatus in accordance with claim 11, wherein the rotated reference image of the object is obtained by retrieving it from storage.

15. An apparatus in accordance with claim 11, wherein the rotated reference image of the object is obtained by rotating a reference image of the object.

16. An apparatus in accordance with claim 11, wherein the processor based system is further configured to pass the live image of the object and the rotated reference image of the object through a normalizing filter.

17. An apparatus in accordance with claim 11, wherein the image capture device comprises a camera.

18. An apparatus in accordance with claim 11, wherein the object comprises a hand-held controller.

19. An apparatus in accordance with claim 11, wherein the information relating to the tilt angle of the object is used to obtain a plurality of rotated reference images of the object, and the live image of the object is compared with each of the plurality of rotated reference images of the object.

20. A non-transitory computer readable storage medium storing a computer program executable by a processor based system, the computer program causing the processor based system to execute steps comprising:

receiving a captured live image of an object from an image capture device;

receiving information related to a tilt angle of the object from one or more sensors other than the image capture device;

using the information related to a tilt angle of the object to obtain at least one rotated reference image of the object;

comparing the live image of the object with the rotated reference image of the object; and

generating an indication in response to the live image matching the rotated reference image.

21. A storage medium in accordance with claim 20, wherein the one or more sensors other than the image capture device comprises a gyro sensor used in the object.

22. A storage medium in accordance with claim 20, wherein the one or more sensors other than the image capture device comprises an accelerometer used in the object.

23. A storage medium in accordance with claim 20, wherein the rotated reference image of the object is obtained by retrieving it from storage.

24. A storage medium in accordance with claim 20, wherein the rotated reference image of the object is obtained by rotating a reference image of the object.

25. A storage medium in accordance with claim 20, wherein the computer program is further configured to cause the processor based system to execute a step comprising:

passing the live image of the object and the rotated reference image of the object through a normalizing filter.

26. A storage medium in accordance with claim 20, wherein the image capture device [comprises] functions as a camera.

27. A storage medium in accordance with claim 20, wherein the image capture device [comprises] functions as a Z-camera.

28. A storage medium in accordance with claim 20, wherein the object [comprises] functions as a hand-held controller.

29. A storage medium in accordance with claim 20, wherein the information relating to the tilt angle of the object is used to obtain a plurality of rotated reference images of the object, and the live image of the object is compared with each of the plurality of rotated reference images of the object.

30. *A method for tracking a device having a body to be worn by a user to produce input data, comprising:*

capturing a plurality of images of the body with an image capture device, the body including infrared (IR) light emitting diodes (LEDs) and the images captured of the body including at least one or more of the IR LEDs for detecting changes in position or orientation of the body in three-dimensional space;

receiving information related to motion of the body from one or more sensors other than the image capture device while capturing said plurality of images of the body, the information related to motion of the body used to identify three-dimensional movements of the body and a tilt angle of the body;

using the images of the body that include the one or more IR LEDs to identify a first part of the tracking information of the body and using the information related to the motion of the body to identify a second part of the tracking information, the second part of the tracking information includes at least one rotated reference image; and

determining the input data based on a combination of both the first part of the tracking information and the second part of the tracking information, the combination includes comparing the at least one rotated reference image with one or more of said plurality of images of the body, wherein the input data is used to control virtual fields of view and virtual movements in a scene of a virtual world when presented on a screen.

31. *The method of claim 30, wherein the one or more sensors other than the image capture device include one of a gyro sensor used in the body of the device, or an accelerometer used in the body of the device, or both a gyro sensor and an accelerometer used in the body of the device; wherein the device is configured for communication with a computer system that processes instructions for the capturing, the receiving, and the using of the method.*

32. *The method of claim 31, wherein the communication used is wireless.*

33. *The method of claim 31, wherein the image capture device is functions to capture images that include a head of the user.*

41

34. The method of claim 30, wherein the image capture device is an infrared (IR) capable camera positioned in a direction that faces in a direction of the body having the IR LEDs, the body used in a space viewable by the image capture device.

35. The method of claim 30, wherein the one or more sensors other than the image capture device function as one or more Micro-Electro-Mechanical Systems (MEMS) sensors.

36. The method of claim 30, wherein detecting changes in position and orientation of the body in three-dimensional space involves analyzing the plurality of images for a pattern of the one or more IR LEDs.

37. The method of claim 30, wherein the determining the input data includes mixing the first part of the tracking data with the second part of the tracking data to generate refined position and orientation information for the virtual movements.

38. The method of claim 30, wherein determining the input data based on a combination of both the first part of the tracking information and the second part of the tracking information includes mapping movements of the body to predefined input commands.

39. A method for tracking a device having a housing, the device is used to provide input data, comprising:
establishing communication between the device and a computer;

receiving, by the computer, inertial sensor data of the device from one or more sensors, the inertial sensor data producing information related to a tilt angle of the housing used to obtain at least one rotated reference image;

receiving a plurality of images of the housing of the device from an image capture device, the housing being dis-

42

posed in space substantially in front of the image capture device, the housing includes infrared (IR) light emitting diodes (LEDs), wherein one or more of the plurality of images captured by the image capture device include at least one or more of the IR LEDs disposed on the housing; and

correcting, at least partially, drift in the inertial sensor data using one or more of the plurality of images captured by the image capture device;

tracking the housing using a combination of information obtained from the plurality of images and information obtained from the inertial sensor data, the combination includes comparing the at least one reference image with one or more of said plurality of images of the housing, the tracking of the device producing the input data that is used to control virtual movements and virtual views presented on a display screen.

40. The method of claim 39, wherein the one or more sensors other than the image capture device include one of a gyro sensor used in the housing of the device, or an accelerometer used in the housing of the device, or both a gyro sensor and an accelerometer used in the housing of the device.

41. The method of claim 39, wherein the housing functions to be worn or held by a user.

42. The method of claim 39, wherein tracking the device includes analyzing the plurality of images for a pattern of the one or more IR LEDs.

43. The method of claim 39, wherein producing the input data includes mapping movements of the housing to predefined input commands.

* * * * *