



- (51) International Patent Classification:  
H04J 4/00 (2006.01)
- (21) International Application Number:  
PCT/US2015/044290
- (22) International Filing Date:  
7 August 2015 (07.08.2015)
- (25) Filing Language:  
English
- (26) Publication Language:  
English
- (30) Priority Data:  
62/034,583 7 August 2014 (07.08.2014) US
- (71) Applicant: ONE MEDIA, LLC [US/US]; 1100 Wilson Blvd, Suite 600, Arlington, VA 22209 (US).
- (72) Inventors: SIMON, Michael, J.; 6471 Forest Hills Court, Frederick, MD 21701 (US). SHELBY, Kevin, A.; 1101 Ottawa Drive, Austin, TX 78733 (US). EARNSHAW, Mark; 61 Allenby Road, Kanata, ON K2K 2J8 (CA).
- (74) Agent: DELUCA, Vincent, M.; Vorys, Sater, Seymour And Pease LLP, 1909 K. St. NW, Ninth Floor, Washington, DC 20006 (US).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:  
— with international search report (Art. 21(3))

(54) Title: DYNAMIC CONFIGURATION OF A FLEXIBLE ORTHOGONAL FREQUENCY DIVISION MULTIPLEXING PHY TRANSPORT DATA FRAME




Figure 1A

(57) Abstract: A base station may generate and transmit a transport stream including a sequence of frames. A frame may include a plurality of partitions, where each partition includes a corresponding set of OFDM symbols. For each partition, the OFDM symbols in that partition may have a corresponding cyclic prefix size and a corresponding FFT size, allowing different partitions to be targeted for different collections of user devices, e.g., user devices having different expected values of maximum delay spread and/or different ranges of mobility. The base station may also dynamically re-configure the sample rate of each frame, allowing further resolution in control of subcarrier spacing. By allowing the cyclic prefixes of different OFDM symbols to have different lengths, it is feasible to construct a frame that conforms to a set payload duration and has arbitrary values of cyclic prefix size per partition and FFT size per partition. The partitions may be multiplexed in time and/or frequency.

WO 2016/022962 A1

**Dynamic Configuration of a Flexible Orthogonal Frequency Division Multiplexing  
PHY Transport Data Frame**

**CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] This application claims priority from US Patent Application No. 62/034,583 filed on August 7, 2014, which is incorporated by reference herein in its entirety.

**FIELD OF THE DISCLOSURE**

[0002] The present disclosure relates to the field of wireless communication, and more particularly, to mechanisms for dynamically constructing Orthogonal Frequency Division Multiplexing (“OFDM”) physical transport frames, to enable flexibility in configuration of transmissions in broadcast networks.

**DESCRIPTION OF THE RELATED ART**

[0003] In today’s world, many electronic devices rely upon wireless connectivity for the reception of data from other connected devices. In a typical wireless deployment, there may be one or more wireless access points that transmit data, and one or more devices that receive data from the wireless access point(s).

[0004] In such a scenario, different devices may have different propagation channel characteristics, and these may affect their wireless data reception from the same wireless access point. For example, a device that is near the wireless access point and/or that has a fixed location (or is slowly moving) may have better propagation channel conditions than would a device that is moving at a high velocity and/or that is further away from the wireless access point. The first device may fall into a group of devices that can receive data encoded and transmitted with one set of parameters (such as a high Forward Error Correction (FEC) code rate, a high modulation level, and/or a smaller subcarrier spacing in an Orthogonal Frequency Division Multiplexing (hereinafter referred to as “OFDM”) system, while the second device may fall into a group of devices that need data to be

encoded and transmitted with a second set of parameters (such as a low FEC code rate, a low modulation level, and/or a wider subcarrier spacing in an OFDM system).

[0005] There are many scenarios where a large number of devices may all wish to receive identical data from a common source. One such example is broadcast television, where a large number of television sets in various homes all receive a common broadcast signal conveying a program of interest. In such scenarios, it is significantly more efficient to broadcast or multicast the data to such devices rather than individually signaling the same data to each device. However, programs with different quality levels (e.g. high definition video, standard definition video, etc) may need to be transmitted to different groups of devices with different propagation channel characteristics. In other scenarios, it may be desirable to transmit device-specific data to a particular device, and the parameters used to encode and transmit that data may depend upon the device's location and/or propagation channel conditions.

[0006] As described above, different sets of transmitted data may need to be transmitted with different encoding and transmission parameters, either simultaneously or in a time-multiplexed fashion (or both). The amount of data to be transmitted in a particular data set and/or the encoding and transmission parameters for that data set may vary with time.

[0007] At the same time, the demand for high-speed wireless data continues to increase, and it is desirable to make the most efficient use possible of the available wireless resources (such as a certain portion of the wireless spectrum) on a potentially time-varying basis.

## SUMMARY

[0008] Modern and future high-speed wireless networks must be designed for efficient handling of a variety of deployment scenarios. Presently disclosed are mechanisms that enable broad flexibility in wireless data delivery, to support services in a full range of deployment scenarios, which might include, but are not limited, to the following: receiver mobility (e.g. fixed, nomadic, mobile); cell size (e.g. macro, micro, pico); single or multiple frequency networks (SFN or MFN); multiplexing of different services; and bandwidth sharing.

[0009] A. In one set of embodiments, a method for constructing and transmitting a frame having a specified temporal length may be implemented as follows. The method may enable flexibility in configuring transmissions from a base station.

[0010] The method may include performing operations using digital circuitry of the base station, wherein said operations include: (a) for each of one or more partitions of the frame, determining a corresponding OFDM symbol length for OFDM symbols belonging to the partition, wherein the OFDM symbol length is based on a corresponding FFT size and a corresponding cyclic prefix size, wherein the corresponding cyclic prefix size satisfies a size constraint based on a corresponding minimum guard interval duration; (b) computing a sum of OFDM symbol lengths in a union of the OFDM symbols over the partitions; (c) computing a number of excess samples based on the sum and a length of a payload region of the frame; and (d) constructing the frame.

[0011] The action of constructing the frame may include, for each OFDM symbol in the union, assigning the OFDM symbol to exactly one of at least one subset of the union using at least one of the number of excess samples and an index of the OFDM symbol, and adding a number to the cyclic prefix size of each OFDM symbol in each of the at least one subset of the union, prior to embedding the OFDM symbols in the frame, wherein a unique number is used for each of the at least one subset of the union.

[0012] The method may also include transmitting the frame over a wireless channel using a transmitter of the base station.

[0013] In some embodiments, the action of constructing the frame also includes, for one of the at least one subset of the union, setting the unique number for that subset to zero.

[0014] In some embodiments, one of the at least one subset of the union represents an initial contiguous subset of the OFDM symbols in the union.

[0015] In some embodiments, the at least one subset of the union and the unique number for each of the at least one subset of the union are determined according to an algorithm known to remote devices that receive said transmissions.

[0016] B. In one set of embodiments, a method for constructing and transmitting a frame by a base station may be implemented as follows.

[0017] The method may include performing operations using digital circuitry of the base station, where the operations include constructing a payload region of the frame. The payload region includes a plurality of partitions, wherein each of the partitions includes a corresponding plurality of OFDM symbols, wherein each partition has a corresponding FFT size and a corresponding cyclic prefix size for OFDM symbols in that partition.

[0018] The method may also involve transmitting the frame over a wireless channel using a transmitter of the base station.

[0019] In some embodiments, the operations also include embedding signaling information in a non-payload region of the frame, wherein the signaling information indicates the FFT size and the cyclic prefix size for each of the partitions.

[0020] In some embodiments, each of the partitions includes a corresponding set of overhead resource elements (such as reference symbols). In these embodiments, the operations may also include scheduling symbol data from one or more service data streams to each of the partitions after having reserved the overhead resource elements within the frame.

[0021] In some embodiments, a first of the partitions is targeted for transmission to mobile devices, and, a second of the partitions is targeted for transmission to fixed devices. In these embodiments, the FFT size corresponding to the first partition may be smaller than the FFT size corresponding to the second partition.

[0022] In some embodiments, a first of the partitions is targeted for transmission to first user devices that are expected to have large delay spreads, and a second of the partitions is targeted for transmission to second user devices that are expected to have smaller delay spreads. In these embodiments, the cyclic prefix size for the first partition may be larger than the cyclic prefix size for the second partition.

[0023] In some embodiments, the frame may be partitioned according to one or more other factors in addition to (or, as an alternative to) the above-described partitioning according to the expected user mobility and required cell coverage as determined by FFT size and cyclic prefix size. For example, factors may include a

data rate, wherein different partitions have different data rates. In particular, different partitions may have a high data rate or a low data rate (along the lines of Internet of Things), with a lower duty cycle for low power reception. In one example, factors may include tight vs. loose clustering where time diversity is sacrificed in the interest of allowing a low power device to wake up, consume the data it needs, and then go back to sleep. In one example, factors may include frequency partitioning that allows the band edges to be coded more robustly using a lower modulation order to permit band shaping or other interference mitigation techniques.

[0024] C. In one set of embodiments, a method for constructing and transmitting a frame by a base station may be implemented as follows.

[0025] The method may include performing operations using digital circuitry of the base station, where the operations include: (a) constructing a plurality of partitions, wherein each of the partitions includes a corresponding set of OFDM symbols, wherein the OFDM symbols in each partition conform to a corresponding FFT size and satisfy a corresponding minimum guard interval; and (b) constructing a frame by time interleaving the OFDM symbols of the partitions to form OFDM symbol clusters, wherein the OFDM symbol clusters are defined by: a specified value of OFDM symbol cluster size for each partition; and a specified value of OFDM symbol cluster period for each partition.

[0026] The method may also include transmitting the frame over a wireless channel using a transmitter of the base station.

[0027] In some embodiments, a first of the partitions is targeted for transmission to mobile devices, and a second of the partitions is targeted for transmission to fixed devices. In these embodiments, the FFT size corresponding to the first partition may be smaller than the FFT size corresponding to the second partition.

[0028] In some embodiments, the above-described operations may also include embedding signaling information in the frame, wherein the signaling information indicates the specified value of OFDM symbol cluster size for each partition and the specified value of OFDM symbol cluster period for each partition.

[0029] In some embodiments, a user device may be configured to: (1) receive the frame; (2) for a particular partition to which the user device has been assigned, determine the corresponding specified values of OFDM symbol cluster size and OFDM symbol cluster period based on the signaling information in the frame; and (3) recover the OFDM symbols belonging to OFDM symbol clusters of the particular partition, using the corresponding specified values.

[0030] D. In one set of embodiments, a method for constructing and transmitting a transport stream by a base station may be implemented as follows. The transport stream includes a frame.

[0031] The method may involve performing operations using digital circuitry of the base station, where the operations include: (a) constructing a payload region of the frame, wherein samples in the payload region correspond to a specified sample rate, wherein the specified sample rate is selected from a universe of possible sample rates supported by transmission circuitry of the base station, wherein the samples in the payload regions are divided into one or more partitions, wherein each of the partitions includes a corresponding set of OFDM symbols; and embedding signaling information in the transport stream, wherein the signaling information includes information indicating the specified sample rate.

[0032] The method may also include transmitting the transport stream over a wireless channel using a transmitter of the base station.

[0033] In some embodiments, the specified sample rate has been specified by an operator of a broadcast network that includes said base station.

[0034] In some embodiments, the above-described signaling information is embedded in a non-payload region of the frame. In an alternative embodiment, the signaling information may be embedded in a previous frame of the transport stream.

[0035] In some embodiments, each partition has a corresponding value of FFT size for OFDM symbols included in that partition.

[0036] In some embodiments, for each partition, the FFT size of that partition and the user-specified sampling rate have been selected to define a subcarrier spacing for that partition that satisfies a specified minimum subcarrier spacing (or Doppler tolerance) for that partition.

**BRIEF DESCRIPTION OF THE DRAWINGS**

[0037] A better understanding of the present invention can be obtained when the following detailed description of the preferred embodiments is considered in conjunction with the following drawings.

[0038] **Figure 1A** illustrates one embodiment of a broadcast network including a plurality of base stations.

[0039] **Figure 1B** illustrates one embodiment of an Orthogonal Frequency Division Multiplexing (“OFDM”) symbol with both a cyclic prefix and a useful portion.

[0040] **Figure 2** illustrates an overview of an example frame structure.

[0041] **Figure 3A** illustrates an example of Physical Partition Data Channel (PPDCH) time multiplexing with distinct time separation of the PPDCH.

[0042] **Figure 3B** illustrates an example Physical Partition Data Channel (PPDCH) time multiplexing with distinct time separation of the PPDCH.

[0043] **Figure 4A** illustrates an example of PPDCH time multiplexing with time interleaving of the PPDCH.

[0044] **Figure 4B** illustrates an example of PPDCH time multiplexing with time interleaving of the PPDCH.

[0045] **Figure 5** illustrates the relationship between different physical channels for carrying payload data, according to one embodiment.

[0046] **Figure 6** illustrates PPDCH sampling rate varied on a per frame basis, according to one embodiment.

[0047] **Figure 7** illustrates an example of distributing excess samples to cyclic prefixes of OFDM symbols within the payload region of a frame, according to one embodiment.

[0048] **Figure 8** illustrates useful subcarriers within an OFDM symbol, according to one embodiment.

[0049] **Figure 9** illustrates an example of PPDCH frequency multiplexing, according to one embodiment.

[0050] **Figure 10** illustrates the layout of logical resources within a PPDCH, according to one embodiment.

[0051] **Figure 11** illustrates logical stripes and logical subbands within a PPDCH, according to one embodiment.

[0052] **Figure 12** illustrates a mapping of virtual stripes belonging to a virtual subband to logical stripes belonging to a logical subband, according to one embodiment.

[0053] **Figure 13** illustrates an example rotation and mapping of virtual stripes to logical stripes, according to one embodiment.

[0054] **Figure 14** illustrates an example rotation and mapping of logical stripes to virtual stripes, according to one embodiment.

[0055] **FIG. 15** illustrates an example of mapping a Physical Service Data CHannel (PSDCH) to virtual resources of a PPDCH, according to one embodiment.

[0056] **Figure 16** illustrates an example of concatenated Physical Frame Data CHannel (PFDCH), PPDCH, and PSDCH descriptors for communication to a receiver, according to one embodiment.

[0057] **Figure 17** illustrates one embodiment of a method for constructing and transmitting a frame by a base station, where the frame includes a plurality of partitions, each having a corresponding FFT size and a corresponding cyclic prefix size.

[0058] **Figure 18** illustrates one embodiment of a method for constructing and transmitting a frame by a base station, where excess samples are distributed to the cyclic prefixes of OFDM symbols in the frame.

[0059] **Figure 19** illustrates one embodiment of a method for constructing and transmitting a frame by a base station, where the frame includes a plurality of partitions, each having a corresponding FFT size and a corresponding cyclic prefix size, wherein the partitions are time interleaved.

[0060] **Figure 20** illustrates one embodiment of a method for constructing and transmitting a frame by a base station, wherein the sample rate associated with payload regions of the frame is configurable.

[0061] While the invention is susceptible to various modifications and alternative forms, specific embodiments thereof are shown by way of example in the drawings and are herein described in detail. It should be understood, however, that the drawings and detailed description thereto are not intended to limit the invention to the particular form disclosed, but on the contrary, the intention is to cover all modifications, equivalents and alternatives falling within the spirit and scope of the present invention as defined by the appended claims.

## DETAILED DESCRIPTION OF THE EMBODIMENTS

### List of Acronyms Used in the Present Patent

|         |  |
|---------|--|
| ATS:    | Auxiliary Termination Symbols              |
| BG:     | Broadcast Gateway                          |
| BS:     | Base Station                               |
| CP:     | Cyclic Prefix                              |
| CRC:    | Cyclic Redundancy Check                    |
| DC:     | Direct Current                             |
| FEC:    | Forward Error Correction                   |
| FFT:    | Fast Fourier Transform                     |
| IFFT:   | Inverse Fast Fourier Transform             |
| LDPC:   | Low Density Parity Check                   |
| MAC:    | Medium Access Control                      |
| MFN:    | Multi-Frequency Network                    |
| MHz:    | Mega Hertz                                 |
| OFDM:   | Orthogonal Frequency Division Multiplexing |
| PDU:    | Protocol Data Unit                         |
| PHY     | PHYSical layer                             |
| PFDCCH: | Physical Frame Data CHannel                |
| PPDCCH: | Physical Partition Data CHannel            |
| PSDCH:  | Physical Service Data CHannel              |
| QAM:    | Quadrature Amplitude Modulation            |
| RS:     | Reference Symbols                          |
| SFN:    | Single Frequency Network                   |

### Broadcast Network Architecture

[0062] In one set of embodiments, a broadcast network **100** may be configured as shown in **Figure 1A**. The broadcast network **100** may include a plurality of base stations **101a**,

**101b...101n**, illustratively suggested by base stations  $BS_1, BS_2, \dots, BS_N$  (hereinafter referred to as base stations **101**). A broadcast gateway (“BG”) **102** may couple to the base stations **101** through any of a variety of communication media. For example, in one embodiment, the broadcast gateway **102** may couple to the base stations **101** via the Internet, or more generally, via a computer network. Each base station **101** wirelessly transmits information to one or more user devices **103**. (Each user device UD is denoted by a solid block circle.) Some of the user devices **103** may be fixed devices such as televisions and desktop computers. Other ones of the user devices **103** may be nomadic devices such as tablet computers or laptop computers. Other ones of the user devices **103** may be mobile devices such as mobile phones, automobile-based devices, aircraft-based devices, etc.

An operator (“Op) **104** of the broadcast network **100** may access the broadcast gateway **102** (e.g., via the Internet), and provide network configuration or operating instructions to the gateway **102**. For example, the operator **104** may provide information such as one or more of the following items: an expected distribution of user device mobility for one or more of the base stations; the cell size of one or more of the base stations; a selection of whether the broadcast network or a subset of the network is to be operated as a single frequency network (SFN) or a multi-frequency network (MFN); a specification of how different services (e.g., television content streams) are to be assigned to different types of user devices; and identification of portions of bandwidth the broadcast network will not be using over corresponding periods of time.

[0063] The broadcast gateway may determine transmission control information for one or more base stations of the broadcast network based on the network configuration or operating instructions. For a given base station, the broadcast gateway may determine: transmission sample rate; number of partitions; sizes of the partitions; FFT size and cyclic prefix size for each partition. The broadcast gateway may send the transmission control information to the base stations so the base stations may construct and transmit frames according to the transmission control information. In other embodiments, the gateway may itself generate frames to be transmitted by each gateway and send the

frames to the base stations. In yet other embodiments, the gateway may generate low level instructions (e.g., physical layer instructions) for the construction of frames to the base stations, and send those instructions to the base stations, which may simply generate frames based on the instructions.

### **OFDM Symbols and FFT / IFFT Sizes**

[0064] An Orthogonal Frequency Division Multiplexing (OFDM) system uses an Inverse Fast Fourier Transform (“IFFT”) operation at the transmitter to convert frequency domain data to the time domain for transmission, and a Fast Fourier Transform (“FFT”) operation at the receiver to convert received time domain values back to the frequency domain in order to recover the originally transmitted data. In the following text, the term FFT is generally used, but the parameters described correspond to the frequency and time dimensions for both the FFT and IFFT operations.

[0065] For illustration purposes, an example base sampling rate of  $F_S = 12.288$  MHz is generally used here. This is not meant to be limiting, and other sampling rates may also be used. The corresponding base time unit corresponding to one sample is  $T_S = 1/F_S$  seconds.

[0066] A range of different FFT/IFFT sizes and cyclic prefix lengths may be supported in order to address a wide variety of propagation conditions and different end user scenarios. A separate entity such as a scheduler may select appropriate FFT/IFFT size(s) and cyclic prefix length(s) for each frame using the following guidelines.

[0067] First, the minimum subcarrier spacing needed to support the intended user mobility is determined. Higher mobile velocities result in larger Doppler shifts, which necessitate wider subcarrier spacing in frequency,  $\Delta f$ . The subcarrier spacing can be calculated as follows. This implies that larger FFT sizes would be used for fixed scenarios, and smaller FFT sizes would be used for mobile scenarios.

equ. (1)

$$\Delta f = \frac{F_S}{\text{FFT size}}$$

[0068] Each OFDM symbol with a total time length of  $T_{\text{Sym}}$  consists of two parts, a cyclic prefix with a time length of  $T_{\text{CP}}$ , and a useful portion with a time length of  $T_U$ , as shown in the example OFDM symbol **102** illustrated in **Figure 1B**. The useful portion **104** of the OFDM symbol **102** refers to the amount of data corresponding to that which is required for the IFFT/FFT operations. The cyclic prefix **106** is just a copy of the last  $N_{\text{CP}}$  samples **108** of the useful portion **104** of the OFDM symbol, and thus essentially represents overhead which is included in the OFDM symbol **102**.

[0069] The useful portion **104** of an OFDM symbol **102** has a number of time samples equal to the size of the FFT ( $N_{\text{FFT}}$ ), and a time length equal to:  
 equ. (2)

$$T_U = \text{FFT size} \times T_S = \frac{1}{\Delta f}$$

[0070] The cyclic prefix **106** contains a specified number of samples ( $N_{\text{CP}}$ ) with a corresponding time length of  $T_{\text{CP}}$ . The cyclic prefix **106** consists of sample values copied from the end of the useful portion of the same OFDM symbol **102** and provides protection against inter-symbol interference between successive OFDM symbols **102**.

[0071] The number of subcarriers actually used within an FFT/IFFT depends on both the subcarrier spacing (which is a function of the FFT size and the sampling frequency) and the bandwidth of the system, since the bandwidth occupied by the used subcarriers must be less than the system bandwidth (in order to allow for a guard band between adjacent channels). Note also that the direct current (DC) carrier is never used.

[0072] Table 1 shows a list of possible FFT sizes that can be used. FFT sizes that are an integer power of 2 may be preferred in a wireless implementation for simplification reasons. The time length ( $T_U$ ) corresponding to the usable portion of each OFDM symbol **102**, the subcarrier spacing ( $\Delta f$ ), and the maximum Doppler velocity that can be handled at an example carrier frequency of 700 MHz are also shown. Here, the maximum Doppler velocity is defined as the receiver velocity which results in a Doppler frequency shift equal to 10% of the subcarrier spacing. (It should be understood that the 10% used here is not essential to the presently disclosed inventions. Indeed, the

percentage may take any value in a range of values.) The values in this table are based on the assumed example sampling frequency of 12.288 MHz.

**Table 1: Example FFT sizes, useful portion time lengths, subcarrier spacings, and maximum Doppler velocities for an example sampling rate of 12.288 MHz**

| FFT Size<br>( $N_{FFT}$ ) | $T_U$ ( $\mu$ s) | $\Delta f$ (Hz) | Maximum Doppler velocity at 700 MHz<br>(km/h) |
|---------------------------|------------------|-----------------|---|
| 1024                      | 83               | 12000           | 1851  |
| 2048                      | 167              | 6000            | 926   |
| 4096                      | 333              | 3000            | 463   |
| 8192                      | 667              | 1500            | 231   |
| 16384                     | 1333             | 750             | 116   |
| 32768                     | 2667             | 375             | 58  |
| 65536                     | 5333             | 188             | 29  |

[0073] Table 2 shows the same information for a different example sampling rate of 18.432 MHz. As can be seen, for a given FFT size, a sampling rate of 18.432 MHz results in a shorter OFDM symbol length ( $T_U$ ), a wider subcarrier spacing ( $\Delta f$ ), and a higher maximum Doppler velocity which can be handled, as compared to a sampling rate of 12.288 MHz.

**Table 2: Example FFT sizes, useful portion time lengths, subcarrier spacings, and maximum Doppler velocities for an example sampling rate of 18.432 MHz**

| FFT Size<br>( $N_{FFT}$ ) | $T_U$ ( $\mu$ s) | $\Delta f$ (Hz) | Maximum Doppler velocity at 700 MHz (km/h) |
|---------------------------|------------------|-----------------|--|
| 1024                      | 56               | 18000           | 2777                                       |
| 2048                      | 111              | 9000            | 1389                                       |
| 4096                      | 222              | 4500            | 694  |
| 8192                      | 444              | 2250            | 347  |
| 16384                     | 889              | 1125            | 174  |

| FFT Size<br>( $N_{FFT}$ ) | $T_U$ ( $\mu$ s) | $\Delta f$ (Hz) | Maximum Doppler velocity<br>at 700 MHz (km/h) |
|---------------------------|------------------|-----------------|---|
| 32768                     | 1778             | 563             | 87  |
| 65536                     | 3556             | 281             | 43  |

**Cyclic Prefix Lengths and Cyclic Prefix Length Selection**

[0074] Next, the cyclic prefix (“CP”) length may be selected to meet the intended range requirement. The cyclic prefix is used to address inter-symbol interference between successive OFDM symbols. Such inter-symbol interference arises from copies of the transmitted signal with slightly different time delays arriving at the receiver, with such copies resulting from identical signal transmissions from multiple base stations in a Single Frequency Network (“SFN”) and/or reflections of a transmitted signal in a multi-path propagation environment. Consequently, in an SFN with significant distances between neighboring base stations (or, potentially, in a propagation environment with significant multi-path scatter), a larger CP length would be selected. Conversely, in an SFN where neighboring base stations are closer together, a shorter CP length may be used.

[0075] The CP length may be viewed as a percent relative to the overall OFDM symbol length (giving the percent overhead consumed by the CP). However, for range planning, it is more useful to view the CP length as measured in samples (as defined by the 12.288 MHz example sampling frequency).

[0076] Radio signals will propagate approximately 24.4 meters in the time of one sample for the example sampling frequency of 12.288 MHz.

[0077] Table 3 gives the cyclic prefix lengths (in number of samples) and corresponding ranges (in km) for various example cyclic prefix lengths specified relative to (as a percentage of) the useful portion of each OFDM symbol. Again, the values in the table are based on the example sampling frequency of 12.288 MHz.

**Table 3: Example cyclic prefix lengths and corresponding ranges**

| $N_{FFT}$ | Cyclic Prefix Length |            |           |            |           |            |           |            |           |            |           |            |           |            |
|-----------|----------------------|------------|-----------|------------|-----------|------------|-----------|------------|-----------|------------|-----------|------------|-----------|------------|
|           | 1.56%                |            | 2.34%     |            | 3.13%     |            | 4.69%     |            | 6.25%     |            | 9.38%     |            | 12.5%     |            |
|           | # Samples            | Range (km) | # Samples | Range (km) | # Samples | Range (km) | # Samples | Range (km) | # Samples | Range (km) | # Samples | Range (km) | # Samples | Range (km) |
| 1024      | 16                   | 0.4        | 24        | 0.6        | 32        | 0.8        | 48        | 1.2        | 64        | 1.6        | 96        | 2.3        | 128       | 3.1        |
| 2048      | 32                   | 0.8        | 48        | 1.2        | 64        | 1.6        | 96        | 2.3        | 128       | 3.1        | 192       | 4.7        | 256       | 6.3        |
| 4096      | 64                   | 1.6        | 96        | 2.3        | 128       | 3.1        | 192       | 4.7        | 256       | 6.3        | 384       | 9.4        | 512       | 12.5       |
| 8192      | 128                  | 3.1        | 192       | 4.7        | 256       | 6.3        | 384       | 9.4        | 512       | 12.5       | 768       | 18.8       | 1024      | 25.0       |
| 16384     | 256                  | 6.3        | 384       | 9.4        | 512       | 12.5       | 768       | 18.8       | 1024      | 25.0       | 1536      | 37.5       | 2048      | 50.0       |
| 32768     | 512                  | 12.5       | 768       | 18.8       | 1024      | 25.0       | 1536      | 37.5       | 2048      | 50.0       | 3072      | 75.0       | 4096      | 100.0      |
| 65536     | 1024                 | 25.0       | 1536      | 37.5       | 2048      | 50.0       | 3072      | 75.0       | 4096      | 100.0      | 6144      | 150.0      | 8192      | 200.0      |

[0078] The above cyclic prefix lengths should be considered to be illustrative examples only. In particular, cyclic prefix lengths should not necessarily be considered to be restricted to be a power of two (or even a multiple of a power of two). Cyclic prefix lengths may have any positive integer value.

**Payload Data Terminology**

[0079] In a wireless system, data may generally be transmitted in a series of frames, which represent a certain period of time. **Figure 2** shows an overview of the general frame structure. A frame **202** can be divided into a payload region **204** which carries actual payload data and zero or more non-payload regions **206** and **208** which may carry control or other signaling information. In the example of **Figure 2**, separate non-payload regions **206** and **208** are shown by the shaded areas at the beginning and end of the frame **202**. The relative lengths in time (horizontal axis) and numbers of symbols for each region are not shown to scale in this example diagram.

[0080] The payload section **204** of the frame may be referred to as the Physical Frame Data CHannel (“PFDCCH”) and carries the actual payload data (as opposed to control or other signaling data) being transmitted by a base station. For illustrative purposes, it can be assumed that each frame **202** has a time length of 1 second and that the payload region (PFDCCH) **204** has a time length of 990 ms, but these example lengths are not meant to be limiting.

[0081] An OFDM wireless frame **202**, particularly the payload portion **204**, is divided into OFDM symbols in the time dimension and sub-carriers in the frequency dimension. The most basic (time-frequency) unit of data carrying capability in OFDM is a resource element, which is defined as one sub-carrier in the frequency dimension by one OFDM symbol in the time dimension. Each resource element can carry one QAM modulation symbol (or QAM constellation).

[0082] The number of sub-carriers available for a fixed system bandwidth depends on the subcarrier spacing, which is in turn dependent upon the selected FFT size and sampling frequency. The time length of an OFDM symbol is also dependent upon the selected FFT size and also upon the selected cyclic prefix length and sampling frequency. The number of OFDM symbols available within a fixed period of time (such as the length of a frame) is dependent upon the time lengths of the individual OFDM symbols contained within that period of time.

[0083] The PFDCH **204** may be divided into one or multiple partitions or Physical Partition Data Channel (hereinafter referred to as "PPDCHs"). A PPDCH is a rectangular logical area measuring some number of sub-carriers in the frequency dimension and some number of OFDM symbols within the time dimension. A PPDCH need not span the full frequency bandwidth of the system, or the full time length of the PFDCH **204**. This allows multiple PPDCHs to be multiplexed in time and/or frequency within the same PFDCH **204**.

[0084] Different PPDCHs may have, but are not constrained to have, different FFT sizes and/or different cyclic prefix lengths. The primary intent behind dividing a PFDCH **204** into multiple PPDCHs is to support the provision of services to different categories of terminals. For example, fixed terminals may be served program data via a PPDCH with a large FFT size and closer subcarrier spacing, while mobile terminals may be served program data via a different PPDCH with a smaller FFT size and wider subcarrier spacing.

[0085] **Figures 3A and 3B** shows two examples of partitioned PFDCHs **302** and **310**, respectively. These example configurations use the previously stated example frame

length of 1 second and PFDCCH length of 990 ms, which leave a 10 ms non-payload region at the beginning of each example frame. In the example illustrated in **Figure 3A**, two PPDCCHs **304** and **306** use different FFT sizes and may be intended to serve nomadic and fixed users, respectively. In the example illustrated in **Figure 3B**, three PPDCCHs **312**, **314** and **316** use different FFT sizes and may be intended to serve mobile, nomadic, and fixed users, respectively. The same cyclic prefix length as measured in samples may be used for all of the PPDCCHs if the desired transmit ranges for different categories of users are desired to be the same. However, there is no constraint requiring the same cyclic prefix length to be used across multiple PPDCCHs, so the configured cyclic prefix length may vary from one PPDCCH to another, and the use of different cyclic prefix lengths for different PPDCCHs may in fact be desirable for certain wireless provisioning scenarios.

[0086] It should be appreciated that although **Figure 3** shows a strict time separation between the different PPDCCHs when time multiplexing is used, OFDM symbols or OFDM symbol clusters from different PPDCCHs can be time-interleaved with each other to maximize time diversity for a given frame configuration, as shown in **Figures 4A** and **4B**. In **Figure 4A**, a PFDCCH **402** is partitioned in a time-interleaved fashion with OFDM symbol clusters **404** belonging to a first PPDCCH, and OFDM symbol clusters **406** belonging to a second PPDCCH. In **Figure 4B**, a PFDCCH **412** is partitioned in a time-interleaved fashion with OFDM symbol clusters **414** belonging to a first PPDCCH, OFDM symbol clusters **416** belonging to a second PPDCCH, and OFDM symbol clusters **418** belonging to a third PPDCCH.

[0087] There are advantages to each of the above approaches. With a strict time separation such as in **Figures 3A** and **3B**, a receiving terminal only needs to activate its radio for a portion of each frame, which can lead to reduced power consumption. With time interleaving such as shown in **Figures 4A** and **4B**, greater time diversity can be achieved.

[0088] Although the PPDCCHs in **Figures 3A** and **3B** and **Figures 4A** and **4B** are the same size, there is no requirement for PPDCCHs within the same frame to be of the same

length. Indeed, since different modulation levels and code rates are likely to be used within different PPDCBs, the data carrying capacities of different PPDCBs may also be very different.

[0089] Each PPDCB within a frame may contain zero or more Physical Service Data Channels (hereinafter referred to as “PSDCH”). It should be appreciated that part or all of the physical resources within a PPDCB may be left unused. The contents of a PSDCH are encoded and transmitted using a specified set of physical resources within the corresponding PPDCB. Each PSDCH contains exactly one transport block for data carrying purposes. A transport block may correspond to a Medium Access Control (“MAC”) Protocol Data Unit (“PDU”) and represents a set of data bytes from upper layers to be transmitted.

[0090] The relationship between the various payload-related physical channels is illustrated in **Figure 5**. Each frame contains one PFDCH **502**. The PFDCH **502** contains one or more PPDCBs **504**. Each PPDCB **504** contains zero or more PSDCHs **506**.

#### **Variable Sampling Rate on a Per Frame Basis**

[0091] Although an example sampling rate of 12.288 MHz has generally been used here for illustrative purposes, it has already previously been stated that this is not meant to be limiting and other sampling rates may also be used.

[0092] In particular, the sampling rate used for the data payload portion of a frame (i.e. the PFDCH) may be allowed to vary on a per frame basis. That is, a non-payload region such as **206** shown in **Figure 2** would use a fixed sampling rate (such as 12.288 MHz) which is known at a receiver. This non-payload region **206** may signal control information which informs the receiver as to the sampling rate which is used for the PFDCH **204** of the same frame **202**. **Figure 6** shows an example of this control signaling. In frame **550**, a sampling rate of 12.288 MHz to be used for the PFDCH **554** is signaled via control information in non-payload region **552**. In frame **560**, a sampling rate of 18.432 MHz to be used for the PFDCH **564** is signaled via control information in

non-payload region **562**. In frame **570**, a sampling rate of 15.36 MHz to be used for the PFDCH **574** is signaled via control information in non-payload region **572**.

[0093] **Figure 6** is intended to be illustrative only, and the use of and signaling of other sampling rates are not precluded. In another embodiment, PFDCH sampling rates may follow a fixed pattern. For example, the PFDCHs of odd-numbered frames may use a lower sampling rate such as 12.288 MHz, while the PFDCHs of even-numbered frames may use a higher sampling rate such as 18.432 MHz. This can be either predetermined or signaled to receiving devices. In yet another embodiment, the sampling rates to be used for received PFDCHs may be signaled separately to receivers rather than being included in control signaling contained within the same frame.

#### **Distribution of Excess Samples to Cyclic Prefixes**

[0094] In a physical sense, the PFDCH consists of a number of consecutive samples in the time domain. This number of samples is equal to the total number of samples in one frame minus the lengths in samples of any non-payload regions of the same frame. For example, there may be 12.288 million samples for the example sampling frequency of 12.288 MHz and example frame length of 1 second.

[0095] After the lengths of the OFDM symbols contained within the PFDCH have been determined, it is quite likely that the total number of samples consumed by these OFDM symbols may be less than the total number of samples assigned to the PFDCH. Depending upon the PFDCH partitioning as described earlier, OFDM symbols belonging to different PFDCHs may have different lengths due to differing FFT sizes and/or cyclic prefix lengths, and it is likely to be an impossible task to ensure that the sum of their lengths exactly equals the number of samples expected to be consumed by the PFDCH. However, it is disadvantageous to place constraints on FFT size selection, cyclic prefix length selection, and/or PFDCH partitioning into multiple PFDCHs, since this would severely reduce the flexibility that is desired for configuring a particular wireless frame. A method for using up any excess samples is required.

[0096] The exact number of excess samples ( $N_{\text{excess}}$ ) to be dealt with for a particular PFDCH can be calculated as:

equ. (3)

$$N_{\text{excess}} = N_{\text{payload}} - \sum_{i=0}^{N_{\text{sym}}-1} N_i$$

where:  $N_{\text{payload}}$  is the number of samples assigned to the PFDCH;  $N_{\text{sym}}$  is the total number of OFDM symbols in the PFDCH (indexing of OFDM symbols begins at 0); and  $N_i$  is the number of samples in the  $i$ th OFDM symbol (equal to the corresponding FFT size plus the specified cyclic prefix length in samples). Note that not all of the OFDM symbols in a PFDCH may be the same size if multiple PPDCHs (with different FFT sizes and/or cyclic prefix lengths) are present.

[0097] The above equation can be simplified to:

equ. (4)

$$N_{\text{excess}} = N_{\text{payload}} - \sum_{p=0}^{N_{\text{PPDCH}}-1} N_{p,\text{sym}} \times (N_{p,\text{FFT}} + N_{p,\text{CP}})$$

where:  $N_{\text{payload}}$  is the number of samples assigned to the PFDCH;  $N_{\text{PPDCH}}$  is the total number of PPDCHs in the PFDCH (indexing of PPDCHs begins at 0);  $N_{p,\text{sym}}$  is the total number of OFDM symbols configured for the  $p^{\text{th}}$  PPDCH;  $N_{p,\text{FFT}}$  is the FFT size configured for the  $p^{\text{th}}$  PPDCH; and  $N_{p,\text{CP}}$  is the cyclic prefix length in samples configured for the  $p^{\text{th}}$  PPDCH.

[0098] **Figure 7** illustrates one example embodiment for distributing excess samples **602**. In particular,

the cyclic prefix lengths **604** for the first  $N_{\text{excess}} \bmod N_{\text{sym}}$  OFDM symbols within the PFDCH are each extended by  $\lceil N_{\text{excess}} / N_{\text{sym}} \rceil$  samples **606**. In addition, the cyclic prefix lengths **604** for the last  $N_{\text{sym}} - (N_{\text{excess}} \bmod N_{\text{sym}})$  OFDM symbols within the PFDCH are each extended by  $\lfloor N_{\text{excess}} / N_{\text{sym}} \rfloor$  samples **606**.

[0099] It should be appreciated that other embodiments for distributing the excess samples among the OFDM symbols within the PFDCH are also possible. For example, a value  $N$ , where  $N < N_{\text{sym}}$ , may be either signaled or predetermined. In order to distribute the excess samples,

the cyclic prefix lengths for the first  $N$  OFDM symbols within the PFDCH are each extended by  $\lceil N_{\text{excess}}/N \rceil$  samples. In addition,

the cyclic prefix length for PFDCH OFDM symbol  $N+1$  is extended by  $N_{\text{excess}} - N \times \lceil N_{\text{excess}}/N \rceil$  samples.

[00100] It will be appreciated by those skilled in the art that further additional embodiments for distributing the excess PFDCH samples may be easily derived.

### **Payload Structure and Mapping**

[00101] This section gives a detailed specification as to how the PFDCH of a wireless frame is structured, how payload partitions (PPDCHs) are specified, how PSDCHs are mapped to specific physical resources, etc. As such, the contents of this section build on the concepts that were introduced earlier.

[00102] The key element behind the design is the concept of mapping virtual resources to logical resources and then logical resources to physical resources.

### **Payload Partition Mapping**

[00103] In a physical sense, the PFDCH consists of a number of consecutive samples in the time domain. This number of samples is equal to the total number of samples in one frame of any non-payload regions in the frame. For example, there may be 12.288 million samples for the example sampling frequency of 12.288 MHz and example frame length of 1 second.

[00104] In a logical sense, the PFDCH is composed of a number of OFDM symbols in the time domain and a number of subcarriers in the frequency domain. The sum of the lengths in samples of all OFDM symbols within the PFDCH prior to excess sample

distribution to cyclic prefixes must be less than or equal to the number of samples available for the PFDCH as calculated above.

[00105] OFDM symbols belonging to the same PPDCH will essentially have the same lengths, subject to excess sample distribution to cyclic prefixes, but OFDM symbols belonging to different PPDCHs may have different lengths. Consequently, not all OFDM symbols within the PFDCH will necessarily have the same length.

[00106] Similarly, the number of subcarriers in the frequency domain is a function of the system bandwidth and the subcarrier spacing. The subcarrier spacing is dependent upon the selected FFT size and the sampling frequency, and may thus vary from one PPDCH to another, if distinct FFT sizes are configured for the two PPDCHs.

[00107] Different PPDCHs may be multiplexed in time and/or frequency.

[00108] Each PPDCH may be referenced via an index (e.g. PPDCH #0, PPDCH #1, ...), so that PSDCHs can be assigned to specific PPDCHs.

[00109] The exact physical resources allocated to a PPDCH may be specified via the following example sets of quantities:

FFT size and cyclic prefix length, which determine the length of each OFDM symbol within the PPDCH; Physical resources allocated to the PPDCH in the time dimension; and Physical resources allocated to the PPDCH in the frequency dimension.

#### **Specifying PPDCH Physical Resources in the Time Dimension**

[00110] In the time dimension, a specific PPDCH may be defined via the following example quantities:

Total number of OFDM symbols assigned to this PPDCH; Absolute OFDM symbol starting position within the PFDCH for this PPDCH (indexing begins at 0); OFDM symbol cluster periodicity for this PPDCH; and Number of consecutive OFDM symbols assigned per OFDM symbol cluster for this PPDCH.

[00111] There is no requirement that the total number of OFDM symbols assigned to a given PPDCH be an integer multiple of the number of consecutive OFDM symbols assigned per OFDM symbol cluster period for this PPDCH.

As an illustrative example, Table 4 shows example parameter settings that correspond to the example payload partitioning shown in **Figures 3A** and **3B**, where there are three equally-sized (in the time dimension) PPDCHs. Here, there is a strict time division between the three PPDCHs. As a result, the PFDCH contains a total of  $440+232+60=732$  OFDM symbols in this example. In particular: PPDCH #0 contains OFDM symbols 0 through 439, each of length 9216 samples; PPDCH #1 contains OFDM symbols 440 through 671, each of length 17408 samples; and PPDCH #2 contains OFDM symbols 672 through 731, each of length 66560 samples.

[00112] Note that there are also some additional excess samples in this example, which may be distributed to the cyclic prefixes of various OFDM symbols.

**Table 4: Example PPDCH parameters (time dimension) for Figures 3A and 3B**

| Quantity   | PPDCH #0  | PPDCH #1  | PPDCH #2  |
|--|-----------|-----------|-----------|
| PPDCH length (seconds)                                     | 0.330 s   | 0.330 s   | 0.330 s   |
| PPDCH length (samples)                                     | 4,055,040 | 4,055,040 | 4,055,040 |
| FFT size   | 8192      | 16384     | 65536     |
| CP length (samples)  | 1024      | 1024      | 1024      |
| OFDM symbol length (samples)                               | 9216      | 17408     | 66560     |
| Total number of OFDM symbols                               | 440       | 232       | 60        |
| Absolute OFDM symbol starting position                     | 0         | 440       | 672       |
| OFDM symbol cluster periodicity                            | 1         | 1         | 1         |
| Number of consecutive OFDM symbols per OFDM symbol cluster | 1         | 1         | 1         |

[00113] In another illustrative example, – the frame structure shown in the lower portion of Figure 4. Table 5 shows example PPDCH parameters that may result in a frame structure illustrated in **Figures 4A** and **4B**. In this example, the PFDCH contains a total of 754 OFDM symbols. In particular:

PPDCH #0 contains OFDM symbols 0-15, 26-41, 52-67, ..., 728-743; PPDCH #1 contains OFDM symbols 16-23, 42-49, 68-75, ..., 744-751; and PPDCH #2 contains OFDM symbols 24-25, 50-51, 76-77, ..., 752-753.

**Table 5: Example PPDCH parameters (time dimension) for Figures 4A and 4B**

| Quantity   | PPDCH #0 | PPDCH #1 | PPDCH #2 |
|--|----------|----------|----------|
| FFT size   | 8192     | 16384    | 65536    |
| CP length (samples)  | 1024     | 1024     | 1024     |
| OFDM symbol length (samples)                               | 9216     | 17408    | 66560    |
| Total number of OFDM symbols                               | 464      | 232      | 58       |
| Absolute OFDM symbol starting position                     | 0        | 16       | 24       |
| OFDM symbol cluster periodicity                            | 26       | 26       | 26       |
| Number of consecutive OFDM symbols per OFDM symbol cluster | 16       | 8        | 2        |

[00114] Note that there is no requirement that different PPDCHs have the same OFDM symbol cluster periodicity, nor that multiple PPDCHs are identically time-interleaved over their full lengths. For example, in Table 5, PPDCH #0 may be divided into two PPDCHs (#0A and #0B) that may either be interleaved with each other in a more macro sense. Table 6 illustrates an example of such a configuration. In particular, PPDCH #0A contains OFDM symbols 0-15, 52-67, 104-119, ..., 672-687, 728-743; PPDCH #0B contains OFDM symbols 26-41, 78-93, 130-145, ..., 646-661, 702-717; PPDCH #1 contains OFDM symbols 16-23, 42-49, 68-75, ..., 744-751; and PPDCH #2 contains OFDM symbols 24-25, 50-51, 76-77, ..., 752-753.

Alternatively, the two PPDCHs may occupy approximately the first and second halves of the PPDCH, respectively. Table 7 illustrates an example of such a configuration. In particular: PPDCH #0A contains OFDM symbols 0-15, 26-41, 52-67, ..., 338-353, 364-

379; PPDCH #0B contains OFDM symbols 390-405, 416-431, ..., 702-717, 728-743; PPDCH #1 contains OFDM symbols 16-23, 42-49, 68-75, ..., 744-751; and PPDCH #2 contains OFDM symbols 24-25, 50-51, 76-77, ..., 752-753.

**Table 6: Additional example PPDCH parameters (time dimension)**

| Quantity   | PPDCH #0A | PPDCH #0B | PPDCH #1 | PPDCH #2 |
|--|-----------|-----------|----------|----------|
| FFT size   | 8192      | 8192      | 16384    | 65536    |
| CP length (samples)  | 1024      | 1024      | 1024     | 1024     |
| OFDM symbol length (samples)                               | 9216      | 9216      | 17408    | 66560    |
| Total number of OFDM symbols                               | 240       | 224       | 232      | 58       |
| Absolute OFDM symbol starting position                     | 0         | 26        | 16       | 24       |
| OFDM symbol cluster periodicity                            | 52        | 52        | 26       | 26       |
| Number of consecutive OFDM symbols per OFDM symbol cluster | 16        | 16        | 8        | 2        |

**Table 7: Additional example PPDCH parameters (time dimension)**

| Quantity                               | PPDCH #0A | PPDCH #0B | PPDCH #1 | PPDCH #2 |
|--|-----------|-----------|----------|----------|
| FFT size                               | 8192      | 8192      | 16384    | 65536    |
| CP length (samples)                    | 1024      | 1024      | 1024     | 1024     |
| OFDM symbol length (samples)           | 9216      | 9216      | 17408    | 66560    |
| Total number of OFDM symbols           | 240       | 224       | 232      | 58       |
| Absolute OFDM symbol starting position | 0         | 390       | 16       | 24       |
| OFDM symbol cluster periodicity        | 26        | 26        | 26       | 26       |

| Quantity   | PPDCH #0A | PPDCH #0B | PPDCH #1 | PPDCH #2 |
|--|-----------|-----------|----------|----------|
| Number of consecutive OFDM symbols per OFDM symbol cluster | 16        | 16        | 8        | 2        |

### Specifying PPDCH Physical Resources in the Frequency Dimension

[00115] The subcarriers within each OFDM symbol can be divided into useful and non-useful subcarriers. Useful subcarriers lie within the system bandwidth minus a guard band, with the exception of the DC subcarrier which is a non-useful subcarrier. Non-useful subcarriers lie outside the system bandwidth minus the guard band.

[00116] The exact number of useful subcarriers is a function of the FFT size and sampling frequency, which together determine the subcarrier spacing, and the system bandwidth.

[00117] **Figure 8** illustrates additional details relating to useful and non-useful subcarriers. Within the full IFFT/FFT range (size) **702**, the useful subcarriers **704** are those which lie within the system bandwidth **706** minus a guard band, with the exception of the DC subcarrier **708**. Non-useful subcarriers **710** lie outside the system bandwidth minus the guard band.

[00118] There is no requirement that all useful subcarriers in an OFDM symbol be explicitly assigned to a PPDCH. Note that each useful resource element can only be assigned to a maximum of one PPDCH. Any useful resource elements that are not associated with a PPDCH may be assigned a value of 0. Non-useful subcarriers may also be assigned a value of 0.

[00119] In the frequency dimension, a specific PPDCH may be defined via the specific quantities. For example, a specific PPDCH may be defined by a number of useful subcarriers belonging to this PPDCH. This quantity must be less than or equal to the total number of all useful subcarriers per OFDM symbol. This specifies the actual size of the PPDCH in the frequency dimension. It should be appreciated that the DC subcarrier is not considered to be a useful subcarrier, so if the DC subcarrier happens

to lie within a particular PPDCH, then that subcarrier is not counted against the number of useful subcarriers belonging to that PPDCH. In one example a specific PPDCH may be defined by an absolute index of the first subcarrier belonging to this PPDCH. Subcarriers may be indexed beginning at 0 and proceeding sequentially upwards to the total number of subcarriers minus 1 (i.e. the FFT size minus 1). Subcarrier 0 is therefore essentially the lowest frequency subcarrier.

[00120] Multiple PPDCHs may be multiplexed beside each other in the frequency dimension. However, there is no actual interleaving of PPDCHs in the frequency dimension. That is, in the frequency dimension, each PPDCH occupies a contiguous set of physical subcarriers.

[00121] **Figure 9** shows an example of two PPDCHs **802** and **804** that have been multiplexed beside each other in the frequency dimension. Approximately 2/3 of the useful subcarriers have been allocated to PPDCH #0 **802**, with the remaining 1/3 of the useful subcarriers being allocated to PPDCH #1 **804**. Table 8 contains the corresponding PPDCH parameters in the frequency dimensions for the two example PPDCHs **802** and **804** shown in **Figure 9**. In this example, both PPDCHs have been configured to use the same FFT size and cyclic prefix length.

**Table 8: Example PPDCH parameters (frequency dimension) for Figure 9**

| Quantity  | PPDCH #0 | PPDCH #1 |
|---|----------|----------|
| FFT size  | 16384    | 16384    |
| CP length (samples)                                   | 1024     | 1024     |
| Subcarrier spacing                                    | 750 Hz   | 750 Hz   |
| System bandwidth                                      | 6 MHz    | 6 MHz    |
| Total number of all useful subcarriers                | 7600     | 7600     |
| Number of useful subcarriers assigned to this PPDCH   | 5000     | 2600     |
| Index of the first subcarrier belonging to this PPDCH | 4392     | 9393     |

### **PSDCH Mapping Within a PPDCH**

[00122] PSDCHs are mapped to virtual resources within their assigned PPDCH,. Virtual resources are then mapped to logical resources within the same PPDCH, and then the logical resources of each PPDCH are mapped to actual physical resources within the PFDCH. This process is described in detail in the following sections.

### **Logical Resources for a PPDCH**

[00123] It has previously been described how a particular PPDCH is associated with corresponding physical resources. Regardless of what exact physical resources belong to a PPDCH, the logical resources of a PPDCH can be considered to be contiguous in both the frequency and time dimensions, as illustrated in **Figure 10**. Here, the logical subcarriers **904** of a PPDCH **902** begin numbering at 0 at the left side of the diagram, which is the lowest frequency, and progress sequentially upwards to the right. Similarly, the logical OFDM symbols **906** of the PPDCH **902** begin numbering at 0 at the top of the diagram, which is earliest time, and progress sequentially upwards moving forward through time, toward the bottom of the diagram.

[00124] **Figure 11** introduces additional logical resource concepts for the contents of a PPDCH. A stripe is a set of resources measuring one subcarrier in the frequency dimension and running for the full time duration of the PPDCH, or all of the OFDM symbols, in the time dimension. Stripes are grouped together in the frequency dimension into subbands, where the subband width of each subband in the frequency dimension is equal to the number of stripes specified for the PPDCH. Each logical subband is composed of a number of logical stripes as illustrated in the diagram, which shows four logical subbands **1004**, **1006**, **1008** and **1010**, each composed of ten logical stripes. A particular stripe **1002** within the PPDCH's logical resources can be referenced via the logical subband index **1006** and the logical stripe index **1002** within that logical subband **1006**. As shown in **Figure 11**, logical subcarriers may begin with the lowest frequency subcarrier at the left and progress upwards in frequency while moving towards the right.

Logical subbands may be indexed beginning with 0 and progress sequentially upwards with frequency.

[00125] There is a constraint that the number of useful subcarriers assigned to a PPDCH must be an integer multiple of the subband-width for that same PPDCH, so that each PPDCH will always contain an integer number of subbands. However, there is no requirement that PPDCH assignments begin with subband 0 or end with subband N-1. In one example, the system might electively depopulate subbands at the band edges to facilitate spectrum sharing or otherwise constrain out-of-band emissions relative to a prescribed spectral mask.

#### **Virtual Resources for a PPDCH**

[00126] Corresponding to each logical subband containing a number of logical stripes is an equally-sized virtual subband containing the same number of virtual stripes. Within each subband, there exists a one-to-one mapping of virtual stripes to logical stripes on a per OFDM symbol basis. This may be considered to be conceptually equivalent to shuffling the virtual stripes in order to obtain the logical stripes. A virtual subband has the same index as the corresponding logical subband.

[00127] **Figure 12** illustrates an example of a mapping of virtual stripes belonging to a virtual subband to logical stripes belonging to a logical subband. Here, each subband has a width of ten stripes ( $W_{SB} = 10$ ). The ten virtual stripes **1106** belonging to the virtual subband **1102** at the top have a one-to-one stripe mapping **1108** to the ten logical stripes **1110** belonging to the logical subband **1104** at the bottom. The stripe mapping **1108** is dependent on the current logical OFDM symbol index **1112**, and may therefore vary from one logical OFDM symbol to the next.

[00128] Table 9 contains an example virtual-to-logical stripe mapping, with Table 10 containing the corresponding example logical-to-virtual stripe mapping. It should be appreciated that the stripe mapping may vary as a function of the logical OFDM symbol index and has a periodicity of  $P_{SM} = 10$  in the time dimension in this example. Without loss of generality, it may be assumed that virtual stripe #0 is always reserved for a

reference symbol or pilot symbol. In Table 10, the logical stripes that contain reference symbols (i.e. which map to virtual stripe #0) have been highlighted with boldface text to show the reference symbol pattern being used in this example. In this example, the reference symbol pattern repeats every five logical OFDM symbols, while the data stripe mapping pattern repeats every ten logical OFDM symbols.

[00129] In Table 9, the logical OFDM symbol index, or the row index, and the virtual stripe index, or the column index, may be used to determine the table entry that corresponds to the logical stripe index for that particular pair of logical OFDM symbol and virtual stripe indices. Conversely, in Table 10, the logical OFDM symbol index, or the row index, and the logical stripe index, or the column index, may be used to determine the table entry that corresponds to the virtual stripe index for that particular pair of logical OFDM symbol and logical stripe indices.

**Table 9: Example virtual stripe to logical stripe mapping**

| Logical OFDM symbol index mod 10 | Virtual stripe index |   |   |   |   |   |   |   |   |   |
|----------------------------------|----------------------|---|---|---|---|---|---|---|---|---|
|                                  | 0                    | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| <b>0</b>                         | 0                    | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 1 |
| <b>1</b>                         | 4                    | 8 | 9 | 0 | 1 | 2 | 3 | 5 | 6 | 7 |
| <b>2</b>                         | 8                    | 4 | 5 | 6 | 7 | 9 | 0 | 1 | 2 | 3 |
| <b>3</b>                         | 2                    | 0 | 1 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| <b>4</b>                         | 6                    | 7 | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 |
| <b>5</b>                         | 0                    | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 1 | 2 |
| <b>6</b>                         | 4                    | 9 | 0 | 1 | 2 | 3 | 5 | 6 | 7 | 8 |
| <b>7</b>                         | 8                    | 5 | 6 | 7 | 9 | 0 | 1 | 2 | 3 | 4 |
| <b>8</b>                         | 2                    | 1 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 |
| <b>9</b>                         | 6                    | 8 | 9 | 0 | 1 | 2 | 3 | 4 | 5 | 7 |

[00130] **Table 10: Example logical stripe to virtual stripe mapping**

| Logical | Logical stripe index |
|---------|----------------------|
|---------|----------------------|

| OFDM symbol index mod 10 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
|--------------------------|---|---|---|---|---|---|---|---|---|---|
| 0                        | 0 | 9 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| 1                        | 3 | 4 | 5 | 6 | 0 | 7 | 8 | 9 | 1 | 2 |
| 2                        | 6 | 7 | 8 | 9 | 1 | 2 | 3 | 4 | 0 | 5 |
| 3                        | 1 | 2 | 0 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
| 4                        | 4 | 5 | 6 | 7 | 8 | 9 | 0 | 1 | 2 | 3 |
| 5                        | 0 | 8 | 9 | 1 | 2 | 3 | 4 | 5 | 6 | 7 |
| 6                        | 2 | 3 | 4 | 5 | 0 | 6 | 7 | 8 | 9 | 1 |
| 7                        | 5 | 6 | 7 | 8 | 9 | 1 | 2 | 3 | 0 | 4 |
| 8                        | 9 | 1 | 0 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
| 9                        | 3 | 4 | 5 | 6 | 7 | 8 | 0 | 9 | 1 | 2 |

[00131] In one example, the set of parameters for each PPDCH include one or more quantities. For example, the set of parameters may include a subband width in the frequency dimension, which may be in units of stripes or subcarriers. In one example, the set of parameters may further include stripe mapping periodicity in the time dimension, which may be in units of logical OFDM symbols. It should be appreciated that the number of logical OFDM symbols in a PPDCH is not required to be an integer multiple of the stripe mapping periodicity. In one example, the set of parameters may further include stripe mapping, which may be in the form of a table with the number of columns equal to the subband width and the number of rows equal to the stripe mapping periodicity. Alternatively, a more compact form of signaling the stripe mapping such as described in the following section may be used.

[00132] It should be appreciated that the concept of virtual OFDM symbols is not defined since virtual OFDM symbols are essentially directly equivalent to logical OFDM symbols. For example, virtual OFDM symbol #N is the same as logical OFDM symbol #N.

**Compact signaling of logical-to-virtual stripe mapping**

[00133] In one example, signaling a complete logical-to-virtual stripe mapping over the air may result in an inefficient use of limited wireless resources due to the potential size of the stripe mapping table that must be transmitted for each PPDCH. Thus, an example a more compact form of signaling the stripe mapping to be used to the receiver is described. This compact signaling then allows the full logical to virtual stripe mapping table to be constructed at the receiver for each PPDCH.

[00134] Two desirable requirements for a good virtual  $\leftrightarrow$  logical stripe mapping are as follows. First,

the stripe mapping should support the ability to have scattered reference symbols. For example, the stripe mapping should support the ability to map reference symbols to different logical stripes in different logical OFDM symbols. Second, the stripe mapping should vary the virtual data stripes that get mapped to the logical stripes adjacent to the reference symbol to avoid some virtual data stripes consistently having better channel estimates than other virtual data stripes.

[00135] In one example, a stripe mapping algorithm for each PPDCH may include a number of quantities, which would reduce the amount of information needing to be signaled over the air. For example,

stripe mapping periodicity ( $P_{SM}$ ) may be the same quantity as has previously been defined. A vector of reference symbol logical stripe mapping positions ( $L_{RS}(k)$ ) may have a length equal to the stripe mapping periodicity. For each OFDM symbol  $k$  (modulo  $P_{SM}$ ), this would specify the logical stripe to which virtual stripe 0 (which contains reference symbols) maps. This allows the reference symbol position to be varied on an OFDM symbol by symbol basis. A vector of stripe rotation may have values with length equal to the stripe mapping periodicity. For each OFDM symbol  $k$  (modulo  $P_{SM}$ ). This would specify the “rotation” to be applied to either: the virtual stripes other than virtual stripe 0, or all of the virtual stripes that carry data rather than a reference symbol, in order to obtain logical stripe indices. This quantity may be labelled  $R_{VL}(k)$ ; or the logical stripes other than the logical stripe  $L_{RS}(k)$  which carries the reference symbol, or all of

the logical stripes that carry data rather than a reference symbol, in order to obtain virtual stripe indices. This quantity may be labelled  $R_{LV}(k)$ .

[00136] Table 11 contains the compact form of specifying the stripe mapping for the example corresponding to Table 9 and Table 10. Recall that for this example, the stripe mapping periodicity is  $P_{SM}=10$ , and the width of the subband is  $W_{SB}=10$ . In addition, the relation between the virtual to logical and logical to virtual stripe rotations can be expressed as:

equ. (5)

$$R_{VL}(k) + R_{LV}(k) = W_{SB} - 1.$$

**Table 11: Example compact form for signaling of stripe mapping data**

| Logical OFDM symbol index mod 10 ( $k$ ) | Logical stripe for reference symbol ( $L_{RS}(k)$ ) | Virtual to logical stripe rotation for data ( $R_{VL}(k)$ ) | Logical to virtual stripe rotation for data ( $R_{LV}(k)$ ) |
|--|---|---|---|
| <i>0</i>                                 | 0   | 1   | 8   |
| <i>1</i>                                 | 4   | 7   | 2   |
| <i>2</i>                                 | 8   | 3   | 6   |
| <i>3</i>                                 | 2   | 9   | 0   |
| <i>4</i>                                 | 6   | 6   | 3   |
| <i>5</i>                                 | 0   | 2   | 7   |
| <i>6</i>                                 | 4   | 8   | 1   |
| <i>7</i>                                 | 8   | 4   | 5   |
| <i>8</i>                                 | 2   | 0   | 9   |
| <i>9</i>                                 | 6   | 7   | 2   |

[00137] **Figure 13** illustrates a conceptual view of how the virtual to logical stripe rotation works. This example corresponds to modulo logical OFDM symbol  $k=6$  from Table 11. As can be seen, the reference symbol on virtual stripe 0 **1202** is mapped straight through to logical stripe  $L_{RS}(k)=4$  **1204**. A rotation (modulo  $W_{SB}=10$ ) of  $R_{VL}(k)=8$  is applied to the data virtual stripes **1206**. These rotated data virtual stripes **1208** are then mapped essentially straight through to the available logical stripes **1210**,

which include all of the logical stripes with the exception of logical stripe #4 **1204** which is already occupied by the reference symbol.

[00138] **Figure 14** shows the corresponding logical to virtual stripe rotation and mapping for modulo logical OFDM symbol  $k=6$  from Table 11. Here, the logical stripe carrying the reference symbol  $L_{RS}(k)=4$  **1302** is extracted and mapped onto virtual stripe #0 **1304**. A rotation modulo  $W_{SB}=10$  of  $R_{LV}(k)=1$  is applied to the data logical stripes **1308**, and then these rotated data logical stripes **1310** are mapped straight through onto the data virtual stripes **1312** #1 through #9.

[00139] Let  $k$  represent the logical OFDM symbol index modulo the stripe mapping periodicity ( $P_{SM}$ ), which equals 10 in this example. At the transmitter, a reference symbol for modulo symbol  $k$  is mapped from virtual stripe index 0 to the corresponding logical stripe index  $L_{RS}(k)$  ( $0 \leq L_{RS}(k) < W_{SB}$ ) given in the table.

equ. (6)

$$S_L(k, L_{RS}(k)) = S_V(k, 0)$$

At the receiver, this process is reversed, and a reference symbol for modulo symbol  $k$  is mapped from the corresponding logical stripe index  $L_{RS}(k)$  given in the table back to virtual stripe index 0.

equ. (7)

$$S_V(k, 0) = S_L(k, L_{RS}(k))$$

For virtual to logical data stripe mapping at the transmitter, the following example procedure can be followed. Let  $S_V(k,i)$  ( $0 < S_V(k,i) < W_{SB}$ ) and  $S_L(k,i)$  ( $0 \leq S_L(k,i) < W_{SB}$  and  $S_L(k,i) \neq L_{RS}(k)$ ) represent a corresponding pair of virtual and logical stripe indices that map to each other for modulo symbol  $k$  ( $0 \leq k < P_{SM}$ ). Let  $R_{VL}(k)$  ( $0 \leq R_{VL}(k) < W_{SB}$  and  $R_{VL}(k) \neq (L_{RS}(k)+W_{SB}-1) \bmod W_{SB}$ ) represent the virtual to logical stripe rotation for data for modulo symbol  $k$ . The logical data stripe index  $S_L(k,i)$  corresponding to a particular virtual data stripe index  $S_V(k,i)$  ( $0 < i < W_{SB}$ ) can then be calculated as follows, noting that for a valid stripe mapping  $R_{VL}(k) \neq (L_{RS}(k)+W_{SB}-1) \bmod W_{SB}$  implies that  $R_{VL}(k) + 1 \neq L_{RS}(k)$  for all  $k$ .

equ. (8)

$$\tilde{L}(k) = \begin{cases} L_{RS}(k) & \text{if } R_{VL}(k) + 1 < L_{RS}(k) \\ L_{RS}(k) + W_{SB} & \text{if } R_{VL}(k) + 1 > L_{RS}(k) \end{cases}$$

$$i = 1 \dots W_{SB} - 1$$

equ. (9)

$$S_V(k, i) = i$$

equ. (10)

$$\tilde{S}(k, i) = S_V(k, i) + R_{VL}(k)$$

equ. (11)

$$S_L(k, i) = \begin{cases} \tilde{S}(k, i) \bmod W_{SB} & \text{if } \tilde{S}(k, i) < \tilde{L}(k) \\ (\tilde{S}(k, i) + 1) \bmod W_{SB} & \text{if } \tilde{S}(k, i) \geq \tilde{L}(k) \end{cases}$$

[00140] At the receiver, the virtual data stripe index  $S_V(k, i)$  corresponding to a particular logical data stripe index  $S_L(k, i)$  ( $0 \leq i < W_{SB}$  and  $i \neq L_{RS}(k)$ ) can then be calculated as shown below.  $R_{LV}(k) = W_{SB} - R_{VL}(k) - 1$  represents the virtual to logical stripe rotation for data for modulo symbol  $k$ .

equ. (12)

$$x(k) = W_{SB} - R_{LV}(k)$$

$$i = 0 \dots W_{SB} - 1 \text{ and } i \neq L_{RS}(k)$$

equ. (13)

$$S_L(k, i) = i$$

If  $x(k) < L_{RS}(k)$  :

equ. (14)

$$S_V(k, i) = \begin{cases} (S_L(k, i) + R_{LV}(k)) \bmod W_{SB} & \text{if } S_L(k, i) < x(k) \text{ or} \\ & S_L(k, i) > L_{RS}(k) \\ (S_L(k, i) + R_{LV}(k) + 1) \bmod W_{SB} & \text{if } x(k) \leq S_L(k, i) < L_{RS}(k) \end{cases}$$

Conversely, if  $x(k) \geq L_{RS}(k)$  :

equ. (15)

$$S_V(k, i) = \begin{cases} (S_L(k, i) + R_{LV}(k)) \bmod W_{SB} & \text{if } L_{RS}(k) < S_L(k, i) < x(k) \\ (S_L(k, i) + R_{LV}(k) + 1) \bmod W_{SB} & \text{if } S_L(k, i) < L_{RS}(k) \text{ or } S_L(k, i) \geq x(k) \end{cases}$$

[00141] Table 12 summarizes the list of parameters that need to be provided for each PPDCH within the PFDCH.

**Table 12: Summary of parameters required for each PPDCH**

| Parameter Category  | Parameter  |
|---------------------|--|
| General             | PPDCH index (may be implicitly signaled by position within a list of PPDCHs)   |
|                     | FFT size   |
|                     | Cyclic prefix length (in samples)  |
| Time dimension      | Total number of OFDM symbols assigned to this PPDCH  |
|                     | Absolute OFDM symbol starting position within the PFDCH for this PPDCH   |
|                     | OFDM symbol cluster periodicity for this PPDCH   |
|                     | Number of consecutive OFDM symbols assigned per OFDM symbol cluster for this PPDCH                                   |
| Frequency dimension | Number of useful subcarriers assigned to this PPDCH (must be an integer multiple of the subband width further below) |
|                     | Absolute index of the first subcarrier belonging to this PPDCH   |
| Stripe mapping      | Subband width in the frequency dimension (in units of stripes or subcarriers)  |
|                     | Stripe mapping periodicity in the time dimension (in units of logical OFDM symbols)                                  |
|                     | Virtual↔Logical stripe mapping table or compact stripe mapping signaling format                                      |

**Mapping a PSDCH to Virtual Resources**

[00142] Virtual stripe #0 may always be reserved for reference symbols. This does not result in any loss of generality since virtual stripe #0 may be mapped to any desired logical stripe.

[00143] The reference symbol density may easily be calculated as the reciprocal of the subband width. In the examples given above with a subband width of 10, the reference symbol density is 10%. Conversely, a desired reference symbol density can also be used to obtain the appropriate subband width to configure.

[00144] A subband block is defined as a set of resource elements measuring one subband in the frequency dimension by one OFDM symbol in the time dimension. Resources may be allocated to a PSDCH in units of subband blocks, where a subset of the virtual stripes within each virtual subband may be assigned to a particular PSDCH.

[00145] Virtual resources may be assigned to a PSDCH via the following parameters:

Total number of subband blocks allocated to this PSDCH; subband index of the first subband block allocated to this PSDCH; subband cluster size or the number of consecutive subband blocks per subband cluster period allocated to this PSDCH; the first subband for a logical OFDM symbol is considered to be consecutive to the last subband for the preceding logical OFDM symbol; subband cluster periodicity for this PSDCH which specifies the periodicity of successive subband clusters that are allocated to this PSDCH; index of the first allocated virtual stripe within a virtual subband for this PSDCH; strip cluster size or the number of consecutive allocated virtual stripes within a virtual subband for this PSDCH; index of the first logical OFDM symbol occupied by this PSDCH; logical OFDM symbol cluster size or the number of consecutive logical OFDM symbols per logical OFDM symbol cluster occupied by this PSDCH; and logical OFDM symbol cluster periodicity for this PSDCH.

[00146] It should be appreciated that the total number of resource elements allocated to a PSDCH may be obtained by multiplying the total number of allocated subband blocks by the number of consecutive allocated virtual stripes within a virtual subband.

[00147] **Figure 15** illustrates how the above parameters can be used to map a PSDCH onto a set of virtual resources within a PPDCH. Table 13 contains the parameters that correspond to the example PSDCH mapping shown in **Figure 15**. In this example, the total number of resource elements allocated to this PSDCH is equal to 16, or the total number of allocated subband blocks, multiplied by 4, or the number of consecutive allocated virtual stripes within a virtual subband, which equals 64. In the diagram, most but not all of the subband clusters **1402** have been circled to show which subbands belong to which subband clusters.

**Table 13: Example PSDCH virtual resource mapping parameters**

| <b>Parameter</b>   | <b>Value</b> |
|--|--------------|
| Total number of allocated subband blocks                                 | 16           |
| Subband index of first subband block                                     | 1            |
| Subband cluster size   | 2            |
| Number of consecutive subband blocks per subband cluster period          |              |
| Subband cluster periodicity  | 3            |
| Index of first allocated virtual stripe within a virtual subband         | 6            |
| Stripe cluster size  | 4            |
| Number of consecutive allocated virtual stripes within a virtual subband |              |
| Index of first occupied logical OFDM symbol                              | 4            |
| Logical OFDM symbol cluster size   | 3            |
| Number of consecutive logical OFDM symbols per OFDM symbol period        |              |
| Logical OFDM symbol cluster periodicity                                  | 8            |

[00148] Within a virtual resource mapping for a PSDCH, modulation symbols may be mapped to resource elements beginning with the first allocated virtual stripe of the first allocated subband block of the first occupied logical OFDM symbol, and progressing by virtual stripe within each subband block, then by subband block within the same logical OFDM symbol, and finally by logical OFDM symbol.

[00149] In the above example, modulation symbols will be mapped to virtual stripes 6/7/8/9 of virtual subband 1 and logical OFDM symbol 4, then to virtual stripes 6/7/8/9 of virtual subband 2 and logical OFDM symbol 4, then to virtual stripes 6/7/8/9 of virtual subband 0 and OFDM symbol 5, then to virtual stripes 6/7/8/9 of virtual subband 1 and OFDM symbol 5, and so on until the total number of allocated subband blocks has been processed.

#### **Frame Content Description Provided to the Receiver**

[00150] In one example, information about the payload content formatting of each frame, including information on the encoding, FFT sizes, etc, is provided to the receiver to facilitate the receiver processing and decoding of the payload contents. There are a variety of methods that may be used to communicate this formatting information to the receiver. For example, the payload content descriptions could be signaled within each frame in one of the non-payload regions shown in Figure 2. Alternatively, if the payload content structure varies more slowly than on a frame-by-frame basis, then the payload content descriptions could be signaled on an as-required basis.

[00151] In one example, the receiver is provided with the number of distinct PPDCHs in the frame and the number of PSDCHs in the frame. For each PPDCH, the receiver is further provided with physical resources allocated to that PPDCH, FFT size, and cyclic prefix length. The physical resources allocated to that PPDCH may include the number of OFDM symbols allocated to that PPDCH, as well as which particular symbols are allocated to that PPDCH. It should be appreciated that distinct PPDCHs may be interleaved with each other. For each PSDCH, the receiver is further provided with service associated with that PSDCH, physical resources allocated to that PSDCH, modulation used for that PSDCH, and transport block size in bytes. The service associated with that PSDCH may be thought of as the data stream flow to which a particular PSDCH belongs. For example, a specific television program may be considered to be a particular service.

[00152] Table 14, Table 15, and Table 16, respectively, provide more detailed descriptions of the parameter fields that may be provided to the receiver. One PFDCH descriptor, listed in Table 14, may be required for each frame. One PPDCH descriptor, listed in Table 15, may be required for each PPDCH contained in the frame. One PSDCH descriptor, listed in Table 16, may be required for each PSDCH contained in the frame.

**Table 14: PFDCH descriptor**

|                          |
|--------------------------|
| <b>Field description</b> |
| Number of PPDCHs         |

**Table 15: PPDCH descriptor**

|   |
|---|
| <b>Field description</b>  |
| FFT size<br>(e.g. 2048, 4096, 8192, 16384, 32768, 65536)  |
| Cyclic prefix length  |
| Total number of OFDM symbols in this PPDCH  |
| Absolute OFDM symbol starting position for this PPDCH   |
| OFDM symbol cluster periodicity   |
| OFDM symbol cluster size<br>(Number of consecutive OFDM symbols per OFDM symbol cluster)  |
| Number of useful subcarriers for this PPDCH   |
| Absolute index of the first subcarrier belonging to this PPDCH  |
| Subband width<br>(Note that the number of useful subcarriers belonging to the PPDCH must be an integer multiple of the subband width) |
| Stripe mapping periodicity in the time dimension  |
| Logical-to-virtual stripe mapping table<br>or<br>Compact stripe mapping parameters  |
| Number of PSDCHs in the PPDCH   |

**Table 16: PSDCH descriptor**

|                          |
|--------------------------|
| <b>Field description</b> |
|--------------------------|

| <b>Field description</b>   |
|--|
| Service associated with this PSDCH   |
| Transport block size   |
| FEC coding type<br>(e.g. Turbo, Low Density Parity Check (LDPC))   |
| Modulation level<br>(e.g. QPSK, 16QAM, 64QAM, 256QAM)  |
| Total number of subband blocks for this PSDCH  |
| Subband index of the first subband block for this PSDCH  |
| Subband cluster size for this PSDCH  |
| Subband cluster periodicity for this PSDCH   |
| Index of the first allocated virtual stripe within a virtual subband for this PSDCH  |
| Number of consecutive allocated virtual stripes within a virtual subband for this PSDCH  |
| Index of the first logical OFDM symbol occupied by this PSDCH  |
| Logical OFDM symbol cluster size<br>(Number of consecutive logical OFDM symbols per OFDM symbol period occupied by this PSDCH) |
| Logical OFDM symbol cluster periodicity for this PSDCH   |

[00153] **Figure 16** shows an example of how all of the various descriptors may be communicated to the receiver. In this example, the single PFDCH descriptor **1502** per frame occurs first, immediately followed by all of the concatenated PPDCH descriptors **1504**. This frame, for example, contains  $n+1$  PPDCHs. This is then followed by all of the concatenated PSDCH descriptors **1506**. In this frame, for example, PPDCH #0 has  $p+1$  PSDCHs and PPDCH # $n$  has  $q+1$  PSDCHs.

[00154] The ordering of the descriptors shown in **Figure 16** can easily be rearranged if so desired. For example, the PSDCH descriptors associated with a particular PPDCH may follow immediately after the descriptor for that PPDCH, instead of all being concatenated together following the group of concatenated PPDCH descriptors.

[00155] In one set of embodiments, a method **1700** for constructing and transmitting a frame may include the actions shown in **Figure 17**. The method **1700** may also include any subset of the features, elements and embodiments previously described. The method **1700** may be implemented by a base station or an access point, for example.

[00156] At step 1710, digital circuitry of the base station may perform operations, wherein the operations include constructing a payload region of the frame, wherein the payload region includes a plurality of partitions, wherein each of the partitions includes a corresponding plurality of OFDM symbols, wherein each partition has a corresponding FFT size and a corresponding cyclic prefix size for OFDM symbols in that partition.

[00157] At step 1720, a transmitter of the base station may transmit the frame over a wireless channel.

[00158] In some embodiments, the operations also include embedding signaling information in a non-payload region of the frame, e.g., as variously described above. The signaling information indicates the FFT size and the cyclic prefix size for each of the partitions. In other embodiments, the signaling information may be embedded elsewhere, e.g., in a previous frame.

[00159] In some embodiments, each of the partitions includes a corresponding set of overhead resource elements, such as reference symbols. In these embodiments, the above-described operations may also include scheduling symbol data from one or more service data streams to each of the partitions after having reserved the overhead resource elements within the frame.

[00160] Different partitions may have different values of FFT size, and thus, different values of subcarrier spacing. For example, the subcarrier spacing for any given partition is the ratio of sample rate to the FFT size for that partition. Consequently, the different partitions will have different amounts of Doppler tolerance, or tolerance to Doppler shift due to motion of user devices. For example, a first of the partitions may be targeted for transmission to mobile devices, while a second of the partitions is targeted for transmission to fixed devices. Thus, the FFT size corresponding to the first partition is configured to be smaller than the FFT size corresponding to the second partition. This allows the first partition to have larger subcarrier spacing, and thus, greater tolerance to the frequency shift of subcarriers due to motion of the mobile devices.

[00161] Furthermore, different partitions may have different cyclic prefix sizes, or guard interval durations, and thus, be able to tolerate different amounts of delay spread.

For example, a first of the partitions may be targeted for transmission to a first set of user devices that are expected to have large delay spreads, while a second of the partitions is targeted for transmission to a second set of user devices that are expected to have smaller delay spreads. Thus, the cyclic prefix size for the first partition is configured to be larger than the cyclic prefix size for the second partition.

[00162] A given user device may receive the transmitted frame using a wireless receiver, and extract the OFDM symbols from the partition to which the user device has been assigned. The OFDM symbols are decoded to obtain digital information signals, which are then displayed or otherwise outputted to a user. The base station may signal to each user device or each type of user device the partition to which it is assigned. The base station may also signal the type of service carried in each partition. The partition may include one or more service data streams, as variously described herein. In the case that the partition includes more than one service data stream, the user device may extract OFDM symbols from one or more of the service data streams for which it has been granted permission to access. The base station may signal to the user device which service data streams it is permitted to access, for example, based on permission control information provided by the broadcast gateway.

[00163] In one set of embodiments, a method **1800** for constructing and transmitting a frame having a specified temporal length may include the actions shown in **Figure 18**. The method **1800** may also include any subset of the features, elements and embodiments previously described. The method **1800** may be implemented by a base station or access point, for example, and may enable flexibility in configuring transmissions from the base station.

[00164] At step **1810**, digital circuitry of the base station may perform operations, where the operations include steps **1815** through **1830**, as follows.

[00165] At step **1815**, for each of one or more partitions of the frame, the digital circuitry may determine a corresponding OFDM symbol length for OFDM symbols belonging to the partition, wherein the OFDM symbol length is based on a corresponding

FFT size and a corresponding cyclic prefix size, wherein the corresponding cyclic prefix size satisfies a size constraint based on a corresponding minimum guard interval duration.

[00166] At step **1820**, the digital circuitry may compute a sum of OFDM symbol lengths, in terms of samples, in a union of the OFDM symbols over the partitions.

[00167] At step **1825**, the digital circuitry may compute a number of excess samples based on the sum and a length, in term of samples, of a payload region of the frame.

[00168] At step **1830**, the digital circuitry may construct the frame. The action of constructing the frame may include, for example, for each OFDM symbol in the union, assigning the OFDM symbol to exactly one of at least one subset of the union using at least one of the number of excess samples and an index of the OFDM symbol, and adding a number to the cyclic prefix size of each OFDM symbol in each of the at least one subset of the union, prior to embedding the OFDM symbols in the frame, wherein a unique number is used for each of the at least one subset of the union.

[00169] Each OFDM symbol belongs to one and only one of the subsets. In other words, the intersection of any two subsets is null, and the union of all of the subsets is the union of all of the OFDM symbols in the frame.

[00170] In some cases, the excess samples may divide evenly between the available OFDM symbols, so that there is only one subset which is equal to the full union. In other embodiments, the excess samples may be distributed to two or more subsets of OFDM symbols.

[00171] As previously described, at least one of the number of excess samples and an index of the OFDM symbol is used to determine into which subset a particular OFDM symbol shall be placed. In some embodiments, only one of the two quantities is used.

[00172] In one example, for a particular subset, the cyclic prefixes of all of the OFDM symbols in that subset may be incremented by the same number. Different subsets may use different numbers.

[00173] At step **1835**, a transmitter of the base station may transmit the frame over a wireless channel.

[00174] In some embodiments, the action of constructing the frame may also include, for one of the at least one subset of the union, setting the unique number for that subset to zero.

[00175] In some embodiments, one of the at least one subset of the union represents an initial contiguous subset of the OFDM symbols in the union.

[00176] In some embodiments, the at least one subset of the union and the unique number for each of the at least one subset of the union are determined according to an algorithm known to remote devices that receive said transmissions.

[00177] A remote device uses knowledge of the subset along with other information, such as the frame start, the length of the preamble in symbols, the start of the payload region, the configured FFT sizes and cyclic prefix lengths, and PFDCH length, to determine exactly the group of samples in the received frame that corresponds to each OFDM symbol in its assigned partition and assigned service data stream or streams.

[00178] In one set of embodiments, a method for constructing and transmitting a frame having a specified temporal length may be implemented as follows. It should be appreciated that the method may enable flexibility in configuring transmissions from a base station. The method may include performing operations using digital circuitry of the base station, wherein said operations include: (a) computing a sum of sample lengths of OFDM symbols assigned to a payload region of a frame; (b) computing a number of excess samples based on the sum and a sample length of the payload region; and (c) constructing the frame, where the action of constructing the frame includes distributing the excess samples to one or more cyclic prefixes of one or more of the OFDM symbols assigned to the frame. The frame may be transmitted onto a wireless channel using a transmitter of the base station.

[00179] In one set of embodiments, a method **1900** for constructing and transmitting a frame may include the actions shown in **Figure 19**. The method **1900** may

also include any subset of the features, elements and embodiments previously described. The method **1900** may be implemented by a base station or access point, for example.

[00180] At step **1910**, digital circuitry of the base station may perform operations, wherein the operations include **1915** and **1920**, as follows.

[00181] At step **1915**, the digital circuitry may construct a plurality of partitions, wherein each of the partitions includes a corresponding set of OFDM symbols, wherein the OFDM symbols in each partition conform to a corresponding FFT size and satisfy a corresponding minimum guard interval. In other words, for each partition, each OFDM symbol in that partition has a cyclic prefix that is greater than or equal to the minimum guard interval for that partition and has an FFT size equal to the FFT size of that partition.

[00182] At step **1920**, the digital circuitry may construct a frame by time interleaving the OFDM symbols of the partitions to form OFDM symbol clusters, as variously described above. Each of the OFDM symbol clusters belongs to a corresponding one of the partitions. The OFDM symbol clusters may be defined by a specified value of OFDM symbol cluster size for each partition, and a specified value of OFDM symbol cluster period for each partition.

[00183] At step **1930**, a transmitter of the base station may transmit the frame over a wireless channel.

[00184] In some embodiments, a first of the partitions may be targeted for transmission to mobile devices, while a second of the partitions is targeted for transmission to fixed devices. Thus, the FFT size corresponding to the first partition is configured to be smaller than the FFT size corresponding to the second partition.

[00185] In some embodiments, the above-described operations also include embedding signaling information in the frame, wherein the signaling information indicates the specified value of OFDM symbol cluster size for each partition and the specified value of OFDM symbol cluster period for each partition. A user device may be configured to receive the frame, and recover the signaling information from the frame. For a particular partition to which the user device has been assigned, the user device

determines the corresponding specified values of OFDM symbol cluster size and OFDM symbol cluster period based on the signaling information in the frame. The user device may then recover the OFDM symbols belonging to the OFDM symbol clusters of the particular partition, using the corresponding specified values.

[00186] In one set of embodiments, a method **2000** for constructing and transmitting a transport stream may include the actions shown in **Figure 20**, where the transport stream includes a frame. The method **2000** may also include any subset of the features, elements and embodiments previously described above. The method **2000** may be implemented by a base station or access point, for example.

[00187] At step **2010**, digital circuitry of the base station may perform operations, wherein the operations include **2015** and **2020**, as follows.

[00188] At **2015**, the digital circuitry may construct a payload region of the frame, wherein samples in the payload region correspond to a specified sample rate, wherein the specified sample rate is selected from a universe of possible sample rates supported by transmission circuitry of the base station, wherein the samples in the payload regions are divided into one or more partitions, wherein each of the partitions includes a corresponding set of OFDM symbols.

[00189] At step **2020**, the digital circuitry may embed signaling information in the transport stream, wherein the signaling information includes information indicating the specified sample rate.

[00190] At step **2030**, a transmitter of the base station may transmit the transport stream over a wireless channel.

[00191] In some embodiments, the sample rate has been specified by an operator of a broadcast network that includes said base station. The operator may specify the sample rate, for example, by accessing the broadcast gateway **102** illustrated in Figure 1A.

[00192] In some embodiments, the signaling information is embedded in a non-payload region of the frame.

[00193] In some embodiments, each partition has a corresponding value of FFT size for OFDM symbols included in that partition.

[00194] In some embodiments, for each partition, the FFT size for the partition and the sampling rate have been selected to define a subcarrier spacing for the partition that satisfies a specified minimum subcarrier spacing or Doppler tolerance for that partition.

[00195] A given user device may wirelessly receive the transport stream, including the frame and the signalling information. The user device may configure its OFDM receiver and/or analog-to-digital conversion circuitry to use the sample rate specified by the signaling information in order to capture samples of the payload region of the frame. The user device may then decode an appropriate partition and service data stream or streams of the frame as variously described.

#### **Contrasts with DVB**

[00196] Digital Video Broadcasting (“DVB”) and Second Generation Terrestrial DVB-T2 includes a Future Extension Frame (“FEF”) as the mechanism to enable a mixed Super Frame (“SF”) structure. According to DVB, the mixed Super Frame permits with the same network to transmit in the same frequency band both fixed and mobile TV services each with an optimized waveform such as time segmented transmission of T2 and FEF frames.

[00197] To preserve backward compatibility, DVB-T2 imposes several constraints to allow the introduction of FEFs. For example, according to DVB-T2, the ratio of T2 frames to FEFs is fixed and is repeated inside a SF. In addition, an SF must start with a T2-frame and should end with a FEF. Also, it is not possible to have 2 consecutive FEFs according to DVB-T2.

[00198] The present disclosure imposes no such constraints. In particular, the ratio of transport resources allocated between FFT modes and respective partitions is determined statistically based on the respective configuration in each mode, including FFT size, CP duration, and payload extent in symbols. In addition,

there are no restrictions on the FFT mode inserted at either the start or end of a frame. Also,

the FFT modes will repeat in succession as needed to satisfy the statistical multiplexing arrangement.

[00199] One significant difference between the present disclosure and DVB-T2 lies in the manner in which FFT modes are multiplexed. DVB-T2 with FEF operates on the basis of frames distributed over the duration of a SF. Services are essentially multiplexed in time on individual frame boundaries separated by P1 preambles. The present disclosure, on the other hand, describes a scheduling arrangement that permits services to be multiplexed on OFDM symbol boundaries within the same frame, providing substantial added flexibility. More than two modes can be multiplexed in the same transport, providing multiple levels of mobility vs. throughput efficiency. Time multiplexing on symbol boundaries increases the extent of either mode, maximizing time diversity. The frame configuration is signaled to the receiver, indicating the periodicity of each FFT mode and the symbols needed to recover the payload associated with either service.

[00200] The present disclosure further permits the option to separate partitions in the frequency domain, thereby confining each partition to separate sets of subcarriers. This is a capability not readily addressable within DVB.

[00201] Efforts to merge different FFT modes within a single DVB frame would require a change in the preamble structure, undermining backward compatibility with legacy receivers. Given the manner in which frames are multiplexed in DVB, confined to separate P1 preamble regions, there is no gain in time diversity. Restrictions imposed on the ratio of T2 to FE frames limits the usefulness of this DVB multiplexing arrangement to a limited set of hand-crafted use case scenarios.

[00202] Any of the various embodiments described herein may be realized in any of various forms, e.g., as a computer-implemented method, as a computer-readable

memory medium, as a computer system, etc. A system may be realized by one or more custom-designed hardware devices such as Application Specific Integrated Circuits (ASICs), by one or more programmable hardware elements such as Field Programmable Gate Arrays (FPGAs), by one or more processors executing stored program instructions, or by any combination of the foregoing.

[00203] In some embodiments, a non-transitory computer-readable memory medium may be configured so that it stores program instructions and/or data, where the program instructions, if executed by a computer system, cause the computer system to perform a method, e.g., any of the method embodiments described herein, or, any combination of the method embodiments described herein, or, any subset of any of the method embodiments described herein, or, any combination of such subsets.

[00204] In some embodiments, a computer system may be configured to include a processor (or a set of processors) and a memory medium, where the memory medium stores program instructions, where the processor is configured to read and execute the program instructions from the memory medium, where the program instructions are executable to implement any of the various method embodiments described herein (or, any combination of the method embodiments described herein, or, any subset of any of the method embodiments described herein, or, any combination of such subsets). The computer system may be realized in any of various forms. For example, the computer system may be a personal computer (in any of its various realizations), a workstation, a computer on a card, an application-specific computer in a box, a server computer, a client computer, a hand-held device, a mobile device, a wearable computer, a sensing device, a television, a video acquisition device, a computer embedded in a living organism, etc. The computer system may include one or more display devices. Any of the various computational results disclosed herein may be displayed via a display device or otherwise presented as output via a user interface device.

[00205] Although the embodiments above have been described in considerable detail, numerous variations and modifications will become apparent to those skilled in the art

once the above disclosure is fully appreciated. It is intended that the following claims be interpreted to embrace all such variations and modifications.

**CLAIMS**

1. A method for constructing a data frame, the method comprising the steps of:
  - dividing, by a processor, a frame into a plurality of partitions;
  - for each of the plurality of partitions, determining, by a processor, a length of an associated OFDM symbol;
  - calculating, by a processor, a sum of OFDM symbol lengths in a union of the OFDM symbols over the plurality of partitions;
  - computing, by a processor, a number of excess samples based on the calculated sum and based on a length of a payload region of the frame; and
  - for each OFDM symbol in the union, assigning, by a processor, the OFDM symbol to one of at least one subset of the union using at least one of the number of excess samples and an index of the OFDM symbol, and adding a number to a cyclic prefix size of each OFDM symbol in each of the at least one subset of the union, prior to embedding the OFDM symbols in the frame.
2. The method of claim 1, wherein the OFDM symbol length is based on a corresponding FFT size and a corresponding cyclic prefix size, and wherein the corresponding cyclic prefix satisfies a size constraint based on a corresponding minimum guard interval duration.
3. The method of claim 1, wherein a unique number is used for each of the at least one subset of the union.
4. The method of claim 1, further comprising the step of the computer, for one of the at least one subset of the union, setting the unique number for that subset to zero.

5. The method of claim 1, wherein one of the at least one subset of the union represents an initial contiguous subset of the OFDM symbols in the union.
6. The method of claim 1, wherein the at least one subset of the union and the unique number for each of the at least one subset of the union are determined according to an algorithm known to a remote computing device configured to receive the data frame.
7. The method of claim 1, further comprising the step of the computer embedding signaling information in the data frame.
8. The method of claim 1, further comprising the step of the computer interleaving the OFDM symbols of the partitions to form OFDM symbol clusters.
9. A system for constructing a data frame, the system comprising one or more processors, one or more non-transitory computer-readable storage devices, and computer executable program instructions stored on at least one of the one or more storage devices for execution by at least one of the one or more processors, the program instructions comprising:  
  
instructions for constructing a plurality of partitions, wherein each of the partitions comprise a corresponding set of OFDM symbols, wherein the OFDM symbols in each partition conform to a corresponding FFT size and satisfy a corresponding minimum guard interval; and

instructions for constructing a frame by time interleaving the OFDM symbols of the partitions to form OFDM symbol clusters, wherein the OFDM symbol clusters are defined by:

- a specified value of OFDM symbol cluster size for each partition; and
- a specified value of OFDM symbol cluster period for each partition.

10. The system of claim 9, wherein the program instructions further comprise program instructions for
  - determining a length of an associated OFDM symbol for each of the plurality of partitions;
  - calculating a sum of OFDM symbol lengths in a union of the OFDM symbols over the plurality of partitions;
  - computing a number of excess samples based on the calculated sum and based on a length of a payload region of the frame; and
  - for each OFDM symbol in the union, assigning the OFDM symbol to one of at least one subset of the union using at least one of the number of excess samples and an index of the OFDM symbol, and adding a number to a cyclic prefix size of each OFDM symbol in each of the at least one subset of the union, prior to embedding the OFDM symbols in the frame.
11. The system of claim 9, wherein the instructions for constructing a plurality of partitions are configured to construct a first of the partitions for transmission to a mobile computing device, and to constructs a second of the partitions for transmission to fixed computing device, wherein the FFT size corresponding to the first partition is smaller than the FFT size corresponding to the second partition.

12. The system of claim 9, wherein the program instructions further comprise program instructions for embedding signaling information in the frame, wherein the signaling information indicates a specified value of the OFDM symbol cluster size for each partition and the specified value of the OFDM symbol cluster period for each partition.
13. The system of claim 9, further comprising a user device, wherein the user device comprises one or more processors, one or more non-transitory computer-readable storage devices, and computer executable instructions stored on at least one of the one or more storage devices for execution by at least one of the one or more processors, the program instructions comprising:  
  
instructions for determining, for a particular partition to which the user device has been assigned, the corresponding specified values of OFDM symbol cluster size and OFDM symbol cluster period based on the signaling information in the frame; and  
  
instructions for recovering the OFDM symbols belonging to the OFDM symbol clusters of the particular partition, using the corresponding specified values.
14. The system of claim 9, further comprising a transmitter configured to transmit the data frame over a wireless communication channel.
15. A computer program product for constructing a transport stream including a data frame, the computer program product comprising one or more non-transitory computer-readable storage devices having stored thereon computer executable instructions that when executed cause at least one processor to:

construct a payload region of the frame, wherein samples in the payload region correspond to a specified sample rate, wherein the specified sample rate is selected from a universe of sample rates supported by transmission circuitry of a base station, wherein first program instructions are further configured to divide the samples in the payload region into one or more partitions, wherein each of the partitions comprises a corresponding set of OFDM symbols; and

embed signaling information in the transport stream, wherein the signaling information comprises data indicative of the specified sample rate.

16. The computer program product of claim 15, wherein the first program instructions are configured to receive data indicative of the specified sample rate from an operator of a broadcast network.
17. The computer program product of claim 15, wherein the second program instructions are configured to embed the signaling information in a non-payload region of the frame.
18. The computer program product of claim 15, wherein the one or more partitions comprises a corresponding value of FFT size for OFDM symbols associated with the one or more partitions.
19. The computer program product of claim 18, wherein the first program instructions are further configured to, for each partition, select the FFT size for the partition and the specified sampling rate to define a subcarrier spacing for the partition that satisfies a specified minimum subcarrier spacing for the partition.




Figure 1A





Figure 1B

3/21



**Figure 2**




Figure 3A




Figure 3B




Figure 4A







Figure 4B



**Figure 5**



**Figure 6**



**Figure 7**

9/21






Figure 8




**Figure 9**

11/21



**Figure 10**





**Figure 12**




Figure. 13




Figure 14




Figure 15





Figure 16

18/21

**Figure 17**

19/21






Figure 18

20/21

**Figure 19**



**Figure 20**

**INTERNATIONAL SEARCH REPORT**

International application No.  
PCT/US 15/44290

**A. CLASSIFICATION OF SUBJECT MATTER**  
 IPC(8) - H04J 4/00 (2015.01)  
 CPC - H04L 1/08, H04L 5/003, H04J 4/00  
 According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**  
 Minimum documentation searched (classification system followed by classification symbols)  
 IPC(8): H04J 4/00 (2015.01)  
 CPC: H04L 1/08, H04L 5/003, H04J 4/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
 USPC: 370/478 (keyword limited - see terms below)

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
 PatBase; GOOGLE; GoogleScholar; GooglePatents  
 Search Terms: construct data frame, partition, OFDM, symbol, frame, cyclic prefix, sample, symbol length, payload region, unique number, FFT, carrier, cluster, embedded, guard interval, transport stream, sample rate

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

| Category* | Citation of document, with indication, where appropriate, of the relevant passages   | Relevant to claim No. |
|-----------|--|-----------------------|
| A         | US 2009/0028258 A1 (Ma et al.) 29 January 2009 (29.01.2009), entire document, especially; abstract, para. [0007], [0048], [0116] | 1 - 19                |
| A         | US 2006/0002367 A1 (Lee et al.) 05 January 2006 (05.01.2006), entire document, especially; abstract, Claim 10                    | 1 - 14                |
| A         | US 2002/0150126 A1 (Kovacevic) 17 October 2002 (17.10.2002), entire document, especially; abstract, para. [0015], [0029]         | 15 - 19               |
| A         | US 2008/0095195 A1 (Ahmadi et al.) 24 April 2008 (24.04.2008), entire document   | 1 - 19                |
| A         | US 2013/0279614 A1 (Walton et al.) 24 October 2013 (24.10.2013), entire document   | 1 - 19                |
| A         | US 2012/0183107 A1 (Zhu et al.) 19 July 2012 (19.07.2012), entire document   | 1 - 19                |

Further documents are listed in the continuation of Box C.

|   |  |
|---|--|
| * Special categories of cited documents:  | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention  |
| "A" document defining the general state of the art which is not considered to be of particular relevance  | "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone   |
| "E" earlier application or patent but published on or after the international filing date   | "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art |
| "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | "&" document member of the same patent family  |
| "O" document referring to an oral disclosure, use, exhibition or other means  |  |
| "P" document published prior to the international filing date but later than the priority date claimed  |  |

|   |  |
|---|--|
| Date of the actual completion of the international search<br>25 September 2015 (25.09.2015) | Date of mailing of the international search report<br><b>26 OCT 2015</b> |
|---|--|

|   |  |
|---|--|
| Name and mailing address of the ISA/US<br>Mail Stop PCT, Attn: ISA/US, Commissioner for Patents<br>P.O. Box 1450, Alexandria, Virginia 22313-1450<br>Facsimile No. 571-273-8300 | Authorized officer:<br>Lee W. Young<br><br>PCT Helpdesk: 571-272-4300<br>PCT OSP: 571-272-7774 |
|---|--|