




(72) WICKELMAIER, PETER, DE

(72) ÖREY, SUAVI, DE

(72) EHRHART, PETER, DE


(71) MAGNET-MOTOR GESELLSCHAFT FÜR MAGNETMOTORISCHE
TECHNIK MBH, DE

(51) Int.Cl.⁶ H05K 7/20, H01L 23/34

(30) 1996/12/20 (196 53 523.9) DE

(54) **SUPPORT DE COMPOSANTS A REFROIDISSEMENT PAR
CIRCULATION D'AIR DES COMPOSANTS ELECTRIQUES**

(54) **COMPONENT HOLDER WITH CIRCULATING AIR COOLING
OF ELECTRICAL COMPONENTS**



(57) L'invention concerne un support de composants (2), sur lequel sont montés des composants électriques (4) et qui présentent au moins un canal (14) dans lequel s'écoule un liquide de refroidissement. Ledit support de composants (2) se caractérise en ce qu'il comporte un corps de refroidissement d'air (6), et en ce qu'un ventilateur (8) est associé à ce support (2), au moyen duquel un courant d'air de circulation peut être produit pour permettre le refroidissement par air d'au moins une partie des composants (4) et le refroidissement au retour de l'air au niveau du corps de refroidissement d'air (6).

(57) The invention relates to a component holder (2) with electrical components mounted thereon and having at least one channel (14) for a coolant. The invention is characterized in that the component holder (2) has an air-cooling body (6) and a fan (8) allocated to the component holder (2), by means of which a circulating air flow can be produced for cooling at least one part of the components (4) and for recooling (6) at the cooling body.




PCT
WELTORGANISATION FÜR GEISTIGES EIGENTUM
Internationales Büro
INTERNATIONALE ANMELDUNG VERÖFFENTLICHT NACH DEM VERTRAG ÜBER DIE
INTERNATIONALE ZUSAMMENARBEIT AUF DEM GEBIET DES PATENTWESENS (PCT)

(51) Internationale Patentklassifikation ⁶ : H05K 7/20, H01L 23/34	A1	(11) Internationale Veröffentlichungsnummer: WO 98/28961 (43) Internationales Veröffentlichungsdatum: 2. Juli 1998 (02.07.98)		
<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; vertical-align: top; padding: 5px;"> (21) Internationales Aktenzeichen: PCT/EP97/07207 (22) Internationales Anmeldedatum: 19. Dezember 1997 (19.12.97) (30) Prioritätsdaten: 196 53 523.9 20. Dezember 1996 (20.12.96) DE (71) Anmelder (für alle Bestimmungsstaaten ausser US): MAGNET-MOTOR GESELLSCHAFT FÜR MAGNETMOTORISCHE TECHNIK MBH [DE/DE]; Petersbrunner Strasse 2, D-82319 Starnberg (DE). (72) Erfinder; und (75) Erfinder/Anmelder (nur für US): WICKELMAIER, Peter [DE/DE]; Michaeliburg Strasse 20, D-81671 München (DE). ÖREY, Suavi [DE/DE]; Alspitzstrasse 16a, D-82319 Söcking (DE). EHRHART, Peter [DE/DE]; Saalburgstrasse 24a, D-81375 München (DE). (74) Anwalt: KLUNKER, SCHMITT-NILSON, HIRSCH; Winzerstrasse 106, D-80797 München (DE). </td> <td style="width: 50%; vertical-align: top; padding: 5px;"> (81) Bestimmungsstaaten: BR, CA, JP, MX, SG, US, eurasisches Patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), europäisches Patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Veröffentlicht <i>Mit internationalem Recherchenbericht. Vor Ablauf der für Änderungen der Ansprüche zugelassenen Frist. Veröffentlichung wird wiederholt falls Änderungen eintreffen.</i> </td> </tr> </table>			(21) Internationales Aktenzeichen: PCT/EP97/07207 (22) Internationales Anmeldedatum: 19. Dezember 1997 (19.12.97) (30) Prioritätsdaten: 196 53 523.9 20. Dezember 1996 (20.12.96) DE (71) Anmelder (für alle Bestimmungsstaaten ausser US): MAGNET-MOTOR GESELLSCHAFT FÜR MAGNETMOTORISCHE TECHNIK MBH [DE/DE]; Petersbrunner Strasse 2, D-82319 Starnberg (DE). (72) Erfinder; und (75) Erfinder/Anmelder (nur für US): WICKELMAIER, Peter [DE/DE]; Michaeliburg Strasse 20, D-81671 München (DE). ÖREY, Suavi [DE/DE]; Alspitzstrasse 16a, D-82319 Söcking (DE). EHRHART, Peter [DE/DE]; Saalburgstrasse 24a, D-81375 München (DE). (74) Anwalt: KLUNKER, SCHMITT-NILSON, HIRSCH; Winzerstrasse 106, D-80797 München (DE).	(81) Bestimmungsstaaten: BR, CA, JP, MX, SG, US, eurasisches Patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), europäisches Patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Veröffentlicht <i>Mit internationalem Recherchenbericht. Vor Ablauf der für Änderungen der Ansprüche zugelassenen Frist. Veröffentlichung wird wiederholt falls Änderungen eintreffen.</i>
(21) Internationales Aktenzeichen: PCT/EP97/07207 (22) Internationales Anmeldedatum: 19. Dezember 1997 (19.12.97) (30) Prioritätsdaten: 196 53 523.9 20. Dezember 1996 (20.12.96) DE (71) Anmelder (für alle Bestimmungsstaaten ausser US): MAGNET-MOTOR GESELLSCHAFT FÜR MAGNETMOTORISCHE TECHNIK MBH [DE/DE]; Petersbrunner Strasse 2, D-82319 Starnberg (DE). (72) Erfinder; und (75) Erfinder/Anmelder (nur für US): WICKELMAIER, Peter [DE/DE]; Michaeliburg Strasse 20, D-81671 München (DE). ÖREY, Suavi [DE/DE]; Alspitzstrasse 16a, D-82319 Söcking (DE). EHRHART, Peter [DE/DE]; Saalburgstrasse 24a, D-81375 München (DE). (74) Anwalt: KLUNKER, SCHMITT-NILSON, HIRSCH; Winzerstrasse 106, D-80797 München (DE).	(81) Bestimmungsstaaten: BR, CA, JP, MX, SG, US, eurasisches Patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), europäisches Patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Veröffentlicht <i>Mit internationalem Recherchenbericht. Vor Ablauf der für Änderungen der Ansprüche zugelassenen Frist. Veröffentlichung wird wiederholt falls Änderungen eintreffen.</i>			

(54) Title: **COMPONENT HOLDER WITH CIRCULATING AIR COOLING OF ELECTRICAL COMPONENTS**

(54) Bezeichnung: **BAUELEMENTTRÄGER MIT LUFT-UMWÄLZKÜHLUNG DER ELEKTRISCHEN BAUELEMENTE**



(57) Abstract

The invention relates to a component holder (2) with electrical components mounted thereon and having at least one channel (14) for a coolant. The invention is characterized in that the component holder (2) has an air-cooling body (6) and a fan (8) allocated to the component holder (2), by means of which a circulating air flow can be produced for cooling at least one part of the components (4) and for recooling (6) at the cooling body.

(57) Zusammenfassung

Bauelementträger (2) mit daran angebrachten elektrischen Bauelementen (4), aufweisend mindestens einen Kanal (14) für Kühlflüssigkeit, dadurch gekennzeichnet, daß der Bauelementträger (2) einen Luftkühlkörper (6) aufweist, und daß dem Bauelementträger (2) ein Lüfter (8) zugeordnet ist, mit dem ein Umwälz-Luftstrom zur Luftkühlung mindestens eines Teils der Bauelemente (4) und zur Luftrückkühlung an dem Luftkühlkörper (6) erzeugbar ist.

Component Holder with Circulating Air Cooling of Electrical Components

This invention relates to a component carrier with electric or electronic components mounted thereon, having at least one channel for cooling liquid.

Such component carriers are used as carriers for components of electronic power devices, the cooling liquid flowing in the channel serving to cool the power components. They are offered on the market either as plug-in elements without a package or firmly integrated in a package. Due to the constantly increasing packing density of electronic power devices the cooling of the power components is an ever greater problem. Furthermore component carriers with the electric components are frequently used in closed systems, for example to fulfill requirements for EMC tightness and IP requirements. Improved removal of the arising thermal dissipation power therefore constitutes an essential potential for further increasing the packing density and compactness of electronic power devices.

It is therefore the problem of the present invention to provide a component carrier which improves removal of the thermal dissipation power of electronic components.

This is obtained according to the invention in that the component carrier has an air cooling body, and a fan is associated with the component carrier for producing a forced air stream for air cooling at least part of the components and for air recooling on the air cooling body. In operation the forced air stream permits optimal cooling of the components which are almost solely dependent on air cooling, e.g. a plurality of capacitors or an internal cabling of the electronic power device. For components mounted due to their design on bases cooled by the liquid cooling, an additional air cooling can also be effected via the package walls of the components. The invention thus offers the possibility of combining liquid

cooling via the mounting bases of the components with additional air cooling. The air recooling can be effected on an air cooling body cooled by the cooling liquid of the liquid cooling.

The component carrier is preferably composed at least of a carrier plate with the components and the air cooling body. It is particularly preferred for the carrier plate and air cooling body to be interconnected areally and enclose the at least one channel between each other. This results in an especially simple structure and thus to a facilitation of work in producing the component carrier. The channel can be easily worked from the surface of one of the plate-like elements before the two are interconnected. Alternatively the component carrier may also be of integral design. For example the channel can be cast in an integral component carrier.

Further it is preferred for the at least one channel to be provided with an inlet and outlet such that both openings are located on or near one face of the component carrier. This arrangement provides an especially simple possibility of connection for supplying cooling liquid and removing cooling liquid, and the two can be combined on one side of the component carrier. Alternatively it can also be advantageous to provide at least one channel with an inlet and outlet such that the openings are located on or near opposite faces of the component carrier.

It has proved especially favorable to form the air cooling body with cooling ribs or cooling slats. This provides an especially large heat exchange surface, which accordingly contributes to especially great heat exchange in operation. Heat exchange can in addition be promoted by using a material with good heat conductivity for the air cooling body. It is also recommendable to use a material with good heat conductivity for the carrier plate in order to permit good cooling of the mounting bases.

It has also proved particularly preferable to dispose the fan such that in operation the air stream produced by opera-

tion of the fan leads away from the fan on one side of the component carrier and leads to the fan on the other side of the component carrier. Circulation can thus take place in a closed circuit. The component carrier itself serves as a partition between the air flowing toward the fan and that flowing away from the fan. The special advantage becomes apparent when the components are all disposed on one side of the component carrier and the air cooling body on the other side. The circulating air cools the components on the first part of its flow path and is recooled by the air cooling body on the other side when flowing back. It can also be advantageous to provide an air cooling body on the side where the components are disposed as well, for example in the vicinity of a component with especially great dissipation power emission. It is also conceivable to dispose air cooling bodies and components jointly on both sides of the component carrier.

It can also be preferred for at least one flow opening to be provided in the component carrier through which at least part of the air stream can flow from one side to the other. Alternatively or in addition to the circulation around the total component carrier, this can form circulation around part of the component carrier. This is preferred in particular when a component carrier flow opening is disposed near a component such that the part of the air stream flowing therethrough can cool it selectively. Depending on the special spatial arrangement of the flow opening through the component carrier and the component on the component carrier one can supply an air stream with a certain temperature to the component very selectively, thereby obtaining especially optimal removal of dissipation power. The cross section and number of the flow openings can be coordinated with the cooling effects to be achieved on the package surfaces of the components. The position of the flow opening is one of the factors determining the temperature of the partial air stream or total air stream. When fixing the geometrical position of the flow openings through the component carrier one preferably adjusts an opti-

imum with respect to temperature, volume throughput and pressure drop of the cooling air.

A guiding element is preferably provided on the component carrier for selectively guiding part of the air stream. This permits the air stream to be guided for example selectively onto a component or around a component. Such a guiding element can be a simple plate-like guiding element, for example in the form of a baffle plate. However it can also be in particular a nozzle-like guiding element associated with a flow opening. Such a guiding element can not only guide the air flowing through the flow opening selectively onto a component but can also accelerate the air flow locally and thus provide especially high local cooling power. For reasons of production technology, among other things, it is particularly preferred to provide a slip-on nozzle-like guiding element which can for example be simply slipped on the flow opening. In general it is particularly preferred to coordinate the geometrical mounting position of the components on the component carrier, the guidance of the air stream in a circulation around the total component carrier and/or part of the component carrier, the arrangement of guiding elements, flow opening, etc., with the dissipation power to be removed and the permissible temperature increase, and design them accordingly. The dissipation power taken up by the component carrier via the component mounting bases with the corresponding temperature conditions is also to be included in such considerations. It can be preferred to provide components cooled via the mounting base which have high dissipation power and require low working temperatures, in the vicinity of the cooling water inlet and to provide ones which have high dissipation power but can cope with higher working temperatures, in the vicinity of the cooling water outlet.

A further important factor for design is the flow cross section between the outer limit of the system in operation and the component carrier. This has an essential influence on the speed of the air stream on the air cooling body and the speed

and distribution of the air stream near the components. It can be dimensioned so as to obtain an optimum of air volume throughput and speed on the components, on the one hand, and recooling on the air cooling body, on the other.

The fan is preferably disposed on one of the faces of the component carrier. This ensures especially simple mounting and especially easy access and moreover leads to especially favorable flow patterns. The fan can be in particular a cross flow fan or, preferably, a radial fan.

The subject matter of the invention is further an electronic device having one of the above-described component carriers disposed in a package such that in operation the air stream is guided between one side of the component carrier and the package wall and between the other side of the component carrier and the package wall. In the electronic device two component carriers are preferably provided with a joint fan in a package, the sides with the components or the sides with the air cooling bodies being disposed opposite each other and forming a flow channel for the air stream between each other. The air stream thus flows part of the flow path in a joint flow channel, cooling either the components of the two opposite component carriers there or being cooled by the opposite air cooling bodies there, and is then divided on the second part of its flow path to flow back on the corresponding component carrier sides protruding away from each other. The reverse direction of flow can also be preferred. The advantage of this arrangement is that only one joint fan is provided for two component carriers. This permits an even more compact arrangement.

The invention will be explained more closely in the following by embodiments shown in the drawing, in which:

Fig. 1 shows a longitudinal section through an inventive component carrier;

Fig. 2 shows a cross section through an inventive component carrier; and

Fig. 3 shows a longitudinal section as in Fig. 1 showing a special kind of arrangement of two component carriers.

Fig. 1 shows component carrier 2 with electric components 4 mounted thereon, air cooling body 6 and fan 8. Component carrier 2 is disposed in package 10. It is composed of carrier plate 12 on which components 4 are mounted, and air cooling body 6. Carrier plate 12 and air cooling body 6 are substantially plate-shaped elements interconnected areally and enclosing channel 14 between each other.

As evident from Fig. 2, the channel is a relatively flat rectangle in cross section and extends substantially over the whole width of component carrier 2. Channel 14 can be worked, e.g. milled, relatively easily from board element 12 or air cooling body 6 before the two plate-shaped elements are interconnected areally. The inlet and outlet for cooling liquid are located on opposite faces of component carrier 2 in the shown embodiment and not shown in the drawings. The cooling liquid flowing through channel 14 serves firstly to cool the components fastened to the component carrier via their mounting base area, and further to recool the air circulated by fan 8 on air cooling body 6. This leads to an especially high cooling effect with relatively low effort.

Air cooling body 6 is preferably made of an especially heat-conducting material and provided with cooling ribs or cooling slats 16 to increase the heat exchange surface in order to achieve maximum heat transfer between the air stream and the cooling liquid.

Fan 8, which is a radial fan to attain a maximum pressure difference, is disposed on one of the faces of component carrier 2 so that the air stream produced thereby leads away therefrom on the upper side of component carrier 2 and leads to fan 8 on the underside of the carrier, as shown by arrows in Fig. 1. When flowing past electronic power components 4 the air stream picks up dissipation power released in the form of heat and emits it to the cooling liquid at air cooling body 6 on the upper side. The air stream flows through a channel

formed substantially by package wall 10 and component carrier 2 both on the upper side and on the underside. Viewing Fig. 2, one can see that the air channels are limited by walls of package 10 on the side as well and the air channel of the upper side is separated from that of the underside by carrier 2 protruding as far as package 10 in each case.

Through component carrier 2 there are a plurality of flow openings 18 through which part of the air stream can flow from the upper side to the underside. In Fig. 1 one can see that flow openings 18 are disposed so as to be associated with individual components 4 so that the latter are selectively cooled substantially by the part of the air stream flowing through corresponding flow opening 18. Channel 14 for cooling liquid is of course closed off from flow openings 18 and is therefore narrower in the area of flow openings 18 than in the area shown in Fig. 2.

The view of Fig. 3 shows the arrangement of two component carriers 2 "back to back" with fan 8 in package 10. One can see how air cooling bodies 6 of component carriers 2 are aligned with each other and how the sides of component carriers 2 where components 4 are mounted point away from each other. This forms between component carriers 2 a channel which is sandwiched by air cooling bodies 6 on two sides. Therefore one can dispense with one fan 8 for two component carriers 2 compared to the arrangement shown in Figs. 1 and 2. Improved cooling power can also result. This permits an even more compact construction. Compared with the above-described embodiment the direction of circulation is reversed in the embodiment of Fig. 3, i.e. the air stream leads from air cooling bodies 6 to fan 8 and away therefrom to components 4. In addition only one closed circulation circuit is shown for each individual component carrier 2 so that the air flows around the faces of component carrier 2 and no flow openings are provided therebetween.

Claims

1. A component carrier (2) with electric components (4) mounted thereon, having at least one channel (14) for cooling liquid, characterized in that the component carrier (2) has an air cooling body (6), and a fan (8) is associated with the component carrier (2) for producing a forced air stream for air cooling at least part of the components (4) and for air recooling on the air cooling body (6).

2. The component carrier (2) of claim 1, characterized in that it is composed at least of a carrier plate (12) with the components (4) and the air cooling body (6).

3. The component carrier (2) of claim 2, characterized in that the carrier plate (12) and the air cooling body (6) are interconnected areally and enclose the at least one channel (14) between each other.

4. The component carrier (2) of any of claims 1 to 3, characterized in that the at least one channel (14) is provided with an inlet and outlet such that both openings are located on or near one face of the component carrier (2).

5. The component carrier (2) of any of claims 1 to 3, characterized in that the at least one channel (14) is provided with an inlet and outlet such that the openings are located on or near opposite faces of the component carrier (2).

6. The component carrier (2) of any of the above claims, characterized in that the air cooling body (6) has cooling ribs or cooling slats (16).

7. The component carrier (2) of any of the above claims, characterized in that the fan (8) is disposed such that in operation the air stream produced by operation of the fan (8) leads away from the fan (8) on one side of the component carrier (2) and leads to the fan (8) on the other side of the component carrier (2).

8. The component carrier (2) of any of the above claims, characterized in that at least one flow opening (18) is pro-

vided therein through which at least part of the air stream can flow from one side to the other side.

9. The component carrier (2) of claim 8, characterized in that a flow opening (18) of the component carrier (2) is disposed near a component (4) such that the partial air stream flowing therethrough can cool the component selectively.

10. The component carrier (2) of any of the above claims, characterized in that a guiding element is provided for selectively guiding part of the air stream.

11. The component carrier (2) of claim 10, characterized in that a guiding element is provided for selectively guiding part of the air stream to a component (4).

12. The component carrier (2) of claim 10 or 11, characterized in that a nozzle-like guiding element is associated with a flow opening (18).

13. The component carrier (2) of claim 12, characterized in that a slip-on nozzle-like guiding element is provided.

14. The component carrier (2) of any of the above claims, characterized in that the fan (8) is disposed on one of the faces of the component carrier (2).

15. The component carrier (2) of any of the above claims, characterized in that the fan (8) is a cross flow fan.

16. The component carrier (2) of any of the above claims, characterized in that the fan (8) is a radial fan.

17. An electronic device having the component carrier (2) of any of claims 1 to 16, characterized in that the component carrier (2) is disposed in a package (10) such that the air stream is guided in operation between one side of the component carrier (2) and the package wall and between the other side of the component carrier (2) and the package wall.

18. The electronic device of claim 17, characterized in that two component carriers (2) are provided with a joint fan (8) in a package (10), the sides with the components (2) or the sides with the air cooling bodies (6) being disposed opposite each other and forming a flow channel for the air stream between each other.

FIG.1




FIG. 2




FIG. 3

