



US010436428B2

(12) **United States Patent**  
**Duong et al.**

(10) **Patent No.:** **US 10,436,428 B2**  
(45) **Date of Patent:** **Oct. 8, 2019**

(54) **SYSTEMS AND METHODS FOR LIGHTING FIXTURES**

(71) Applicant: **Fluence Bioengineering**, Austin, TX (US)

(72) Inventors: **Dung Duong**, Austin, TX (US); **Randy Johnson**, Austin, TX (US); **Nick Klase**, Austin, TX (US)

(73) Assignee: **Fluence Bioengineering, Inc.**, Austin, TX (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/697,149**

(22) Filed: **Sep. 6, 2017**

(65) **Prior Publication Data**

US 2018/0356048 A1 Dec. 13, 2018

**Related U.S. Application Data**

(60) Provisional application No. 62/516,412, filed on Jun. 7, 2017.

(51) **Int. Cl.**  
**F21V 23/00** (2015.01)  
**H05K 1/05** (2006.01)

(Continued)

(52) **U.S. Cl.**  
CPC ..... **F21V 23/005** (2013.01); **A01G 7/045** (2013.01); **F21K 9/232** (2016.08); **F21K 9/90** (2013.01); **F21S 4/28** (2016.01); **F21V 7/005** (2013.01); **F21V 7/0066** (2013.01); **F21V 7/05** (2013.01); **F21V 15/015** (2013.01); **F21V 17/107** (2013.01); **F21V 19/003** (2013.01); **F21V 19/0015** (2013.01); **F21V 23/001** (2013.01); **F21V 23/02** (2013.01); **F21V 29/70** (2015.01); **F21V 29/74** (2015.01); **F21V 29/83**

(2015.01); **H05K 1/0203** (2013.01); **H05K 1/0209** (2013.01); **H05K 1/0274** (2013.01); **H05K 1/0277** (2013.01); **H05K 1/05** (2013.01); **H05K 1/056** (2013.01); **H05K 1/181** (2013.01); **H05K 1/182** (2013.01); **H05K 1/185** (2013.01); **H05K 3/0014** (2013.01); **H05K 3/28** (2013.01);  
(Continued)

(58) **Field of Classification Search**  
CPC ..... F21V 21/30; F21V 21/26; F21Y 2105/10  
See application file for complete search history.

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

2008/0062689 A1\* 3/2008 Villard ..... F21V 14/02 362/249.07  
2010/0177514 A1\* 7/2010 Liu ..... F21S 8/04 362/235

(Continued)

**FOREIGN PATENT DOCUMENTS**

KR 2011-0022262 \* 8/2009

**OTHER PUBLICATIONS**


Young, Lee W., International Search Report and Written Opinion of the International Searching Authority, for counterpart application PCT/US2018/034544, dated Aug. 24, 2018, U.S. Patent and Trademark Office, Alexandria, Virginia, U.S., 3 pages.

*Primary Examiner* — Evan P Dzierzynski  
(74) *Attorney, Agent, or Firm* — Yutian Ling

(57) **ABSTRACT**

Examples of the present disclosure are related to systems and methods for lighting fixtures. More particularly, embodiments disclose lighting fixtures utilizing metal core PCB (MCPCB) for thermal, mechanical, and/or optical controls.

**16 Claims, 6 Drawing Sheets**



- (51) **Int. Cl.**  
*H05K 1/18* (2006.01)  
*H05K 1/02* (2006.01)  
*H05K 3/32* (2006.01)  
*F21K 9/90* (2016.01)  
*F21V 29/74* (2015.01)  
*F21V 29/70* (2015.01)  
*F21V 29/83* (2015.01)  
*F21K 9/232* (2016.01)  
*A01G 7/04* (2006.01)  
*F21V 7/00* (2006.01)  
*F21V 7/05* (2006.01)  
*H05K 3/00* (2006.01)  
*H05K 3/28* (2006.01)  
*H05K 3/44* (2006.01)  
*F21S 4/28* (2016.01)  
*F21V 15/015* (2006.01)  
*F21V 17/10* (2006.01)  
*F21V 19/00* (2006.01)  
*F21V 23/02* (2006.01)  
*H05B 33/08* (2006.01)  
*H05B 37/02* (2006.01)

- F21Y 115/10* (2016.01)  
*F21Y 105/16* (2016.01)  
*F21Y 103/10* (2016.01)  
 (52) **U.S. Cl.**  
 CPC ..... *H05K 3/32* (2013.01); *H05K 3/44*  
 (2013.01); *F21Y 2103/10* (2016.08); *F21Y*  
*2105/16* (2016.08); *F21Y 2115/10* (2016.08);  
*H05B 33/0854* (2013.01); *H05B 37/0227*  
 (2013.01); *H05B 37/0272* (2013.01); *H05K*  
*2201/066* (2013.01); *H05K 2201/09009*  
 (2013.01); *H05K 2201/10106* (2013.01)

(56) **References Cited**  
 U.S. PATENT DOCUMENTS

2013/0039050	A1	2/2013	Dau et al.	
2014/0160740	A1	6/2014	Hwang et al.	
2016/0003453	A1*	1/2016	Klase .....	F21V 14/02 362/220
2018/0163957	A1*	6/2018	Zhou .....	F21V 21/06

\* cited by examiner




FIGURE 1




FIGURE 2




FIGURE 3




FIGURE 4




FIGURE 5




FIGURE 6

## SYSTEMS AND METHODS FOR LIGHTING FIXTURES

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims a benefit of priority under 35 U.S.C. § 119 to Provisional Application No. 62/516,412 filed on Jun. 7, 2017, which is fully incorporated herein by reference in their entirety.

### BACKGROUND INFORMATION

#### Field of the Disclosure

Examples of the present disclosure are related to systems and methods for lighting fixtures. More particularly, embodiments disclose lighting fixtures utilizing bends in metal-core PCB (MCPCB) and orthogonal braces for thermal, mechanical, and/or optical controls.

#### Background

Controlled environment agriculture, especially vertical farming is becoming more prevalent in the US and around the world. Vertical farming relies on light fixtures to illuminate a plant canopy. The light fixtures uniformly distribute radiant flux over the plant canopy, while removing heat from light sources (typically LEDs). The light fixtures' efficacy and cost directly impacts the operational expenses associated with vertical farming. As fixture height directly influences a number of vertical layers within a growth volume, it is important to minimize a form factor or vertical height of the fixture

Operating higher-powered lights in a vertical growth is more costly than utilizing free sunlight in greenhouses or field-grown. To overcome these costs, vertical farming must have an increased yield, shorter growth cycles, more consistent product, less water usage, farm to plate timeframe, high nutrient content, and other tangible advantages.

Although light emitting diodes (LEDs) used in vertical farming are more efficient than traditional higher-powered lights, their manufacturing costs are also higher. Additionally, their performance is negatively impacted with thermal rise. The terminal rise requires the light fixtures to dissipate heat more efficiently. This generated heat causes issues such as decreased longevity and lower fixture efficacy. To circumvent the requirements to dissipate the heat, some manufacturers have built complex LED fixtures. This has led to conventional LED fixtures being coupled to heat sinks.

This has led to conventional LED fixtures being coupled to heat sinks. Conventional LED fixtures utilize LEDs that are positioned on a printed circuit board. PCB substrates may be made of different materials such as FR4, Aluminum, copper, etc. In most application, an insulative substrate is necessary such as FR4. In higher power applications, a highly thermally conductive substrate is desired. For LEDs, thermal dissipation is paramount and therefore Aluminum substrates are often utilized. When metal is used as the substrate, the term metal core printed circuit board is used or more commonly MCPCB. The linear MCPCB is then coupled to the heatsink to dissipate the heat. The process leads to inefficient thermal transfer or increased thermal resistance between the heat source (LEDs) and the heatsink. This process to affix the LEDs to the MCPCB and then to

couple the MCPCB to the heat sink requires time and resources. This can be an arduous, time consuming, and costly task.

Accordingly, needs exist for more effective and efficient systems and methods for light fixtures systems with supports that extend in a direction orthogonal to the bends of the heat sink.

### SUMMARY

Embodiments disclosed herein describe systems and methods for a light fixture that utilizes MCPCB for thermal, mechanical, and/or optical controls. In embodiments, a MCPCB sheet may be directly populated with electronic components, such as LEDs, connectors, fuses, etc. The board may then be coated for protection. The MCPCB sheet may then be cut into a single panel. Next, the single panel MCPCB is bent at least one time, wherein the bend may increase the rigidity and mechanical strength of the system, be more aesthetically pleasing, and allow for thermal and optical controls. The bent MCPCB panel can then be assembled into a light fixture. The light fixture may include a plurality of bent panels that are coupled together via brackets.

The brackets may be configured to be positioned over a center portion of the bent panels. The positioning of the panels may be configured to give the system mechanical strength in a direction that is perpendicular to the bends in the panels, while also allowing multiple bent panels to be coupled together. Furthermore, electrical components may be configured to be positioned through, over, and/or embedded within the brackets to reduce the footprint, sizing, etc. of the system.

In embodiments, multiple brackets may be coupled together via a hinge. The hinge may allow for multiple sections of the system to be folded over itself while not in use, while sharing a same power supply when in use.

These, and other, aspects of the invention will be better appreciated and understood when considered in conjunction with the following description and the accompanying drawings. The following description, while indicating various embodiments of the invention and numerous specific details thereof, is given by way of illustration and not of limitation. Many substitutions, modifications, additions or rearrangements may be made within the scope of the invention, and the invention includes all such substitutions, modifications, additions or rearrangements.

### BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting and non-exhaustive embodiments of the present invention are described with reference to the following figures, wherein like reference numerals refer to like parts throughout the various views unless otherwise specified.

FIG. 1 depicts a light fixture, according to an embodiment.

FIG. 2 depicts a light fixture according to an embodiment.

FIG. 3 depicts a light fixture, according to an embodiment.

FIG. 4 depicts a light fixture, according to an embodiment.

FIG. 5 depicts a light fixture, according to an embodiment.

FIG. 6 depicts a method of utilizing a light fixture, according to an embodiment.

Corresponding reference characters indicate corresponding components throughout the several views of the drawings. Skilled artisans will appreciate that elements in the figures are illustrated for simplicity and clarity and have not necessarily been drawn to scale. For example, the dimensions of some of the elements in the figures may be exaggerated relative to other elements to help improve understanding of various embodiments of the present disclosure. Also, common but well-understood elements that are useful or necessary in a commercially feasible embodiment are often not depicted in order to facilitate a less obstructed view of these various embodiments of the present disclosure.

#### DETAILED DESCRIPTION

In the following description, numerous specific details are set forth in order to provide a thorough understanding of the present embodiments. It will be apparent, however, to one having ordinary skill in the art that the specific detail need not be employed to practice the present embodiments. In other instances, well-known materials or methods have not been described in detail in order to avoid obscuring the present embodiments.

FIG. 1 depicts a MCPCB LED bar system **100**, according to an embodiment. System **100** may be configured to utilize bends in a MCPCB lighting fixture for thermal, mechanical, and optical controls. System **100** may include MCPCB **110**, light sources **120**, and bends **130**. Utilizing bends **130**, MCPCB **110** may be substantially isothermal having somewhat uniform temperatures across MCPCB **110**.

MCPCB **110** may be formed of any metal, including: copper, 3003 AL, 5052 AL, and/or other desired metals. In specific implementations, MCPCB **110** may be formed of a metal or substrate with a very low emissivity. However such a system would be much larger than a system with a high emissivity platform. To increase the emissivity of the MCPCB **110**, MCPCB **110** may be anodized, may have a solder mask that yields higher emissivity than anodized aluminum, and/or have a painted surface that yields higher emissivity than anodized aluminum. MCPCB **110** may be positioned in a panel having a longer longitudinal axis than a lateral axis. MCPCB **110** may have a thickness that is based on the thermal properties generated by light sources **120**. For example, MCPCB **110** may have a thickness that is around 1.6 mm.

Light sources **120** may be light emitting diodes (LEDs) or any other device that is configured to emit light. Light sources **120** may be directly embedded or positioned on MCPCB **110**, such that additional operations to affix tape or thermal adhesives to MCPCB **110**, a heat sink, or both are not required. Light sources **120** may be positioned from a first end of MCPCB **110** to a second end of MCPCB **110**. Light sources **120** may be configured to generate heat in response to creating and emitting light.

Bends **130** may be positioned from the first end to the second end of MCPCB **110**. Bends **130** may be configured to add rigidity and/or mechanical strength to system **100**, add form for aesthetics, operate as a heat sink to guide the flow of air, and allow for optical controls.

FIG. 2 depicts a MCPCB fixture **200**, according to an embodiment. Elements depicted in FIG. 2 may be described above, and for the sake of brevity an additional description of these elements is omitted.

As depicted in FIG. 2, fixture **200** may include a plurality of bent MCPCBs **110**, a first bracket **210**, a second bracket **220**, and hinge **270**.

The plurality of bent MCPCBs **110** may be positioned in parallel with each other. However, in other embodiments, the plurality of bent MCPCBs **110** may be askew from one another. The plurality of bent MCPCBs **110** may be positioned equidistance from adjacent bent MCPCBs **110**. However, in other embodiments, the plurality of bent MCPCBs **110** may be positioned at different distanced from one another.

Brackets **210**, **220** may be polymer or metal (al, steel) brackets, braces, support structures, etc. that are configured to a first set of bent MCPCBs **110** and a second set of bent MCPCBs **110** together, respectively. Brackets **210**, **220** may be configured to be positioned orthogonal to the bends **130**. By positioning brackets **210**, **220** in a direction orthogonal to bends **130**, brackets **210**, **220** may supply mechanical rigidity and support to fixture **200** in a lateral axis of fixture **200**. In embodiments, the first and second sets of bent MCPCBs **110** may have the same number of MCPCBs **110** or different numbers. Furthermore, the bent MCPCBs **110** in the groups may be the same or different sizes, with the same light sources or different light sources, may be symmetrical or asymmetrical with respect to each other, emit the same or different light patterns, etc. Accordingly, based on the characteristics between the first set of bent MCPCBs **110** and the second set of bent MCPCBs **110**, the first and second sets may be configured to emit light patterns to the same and/or different light patterns over the different areas of interest.

Brackets **210**, **220** may include cutouts **215**, first rail **230**, second rail **240**, channel **214**, and coupling orifices **212**.

Cutouts **215** may be positioned on the lower surfaces of brackets **210**, **220**. Cutouts **215** may be configured to receive the upper surfaces of MCPCBs **110**. In embodiments, cutouts **215** may be shaped to correspond with the upper surfaces of MCPCBs **110**. Accordingly, when MCPCBs **110** are inserted into cutouts **215**, the inner surfaces of cutouts **215** may be positioned adjacent to the upper surface of MCPCBs **110**. This may form a continuous surface that allows heat to flow up and around the sidewalls of brackets **210**, **220**. Furthermore, when MCPCBs **110** are positioned within cutouts **215** the bottom surfaces MCPCBs **110** may be flush with the bottom surfaces of cutouts **215**.

First rail **230** may be positioned on a first side of brackets **210**, **220** and second rail **240** may be positioned on a second side of brackets **210**, **220**, wherein channel **214** may be positioned between first rail **230** and second rail **240**. The upper ends of first rail **230** and second rail **240** may be vertically offset from the upper surface of channel **214**. This may allow heat generated by the light sources to be channeled towards the longitudinal axis of brackets **210**, **220**, which may be orthogonal to the longitudinal axis of MCPCBs **110**.

Channel **214** may extend between first rail **230** and second rail **240**, wherein the upper surface of channel **214** is below the upper surfaces of first rail **230** and second rail **240**. Channel **214** may include coupling orifices **212** that extend through the body of channel **214**. The coupling orifices **212** may be configured to receive coupling mechanisms (i.e. screws, bolts, etc.) to couple MCPCBs **110** to brackets **210**, **220**.

Hinge **270** may be positioned between first bracket **210** and second bracket **220**, wherein hinge **270** is configured to couple first bracket **210** and second bracket **220**. Hinge **270** may be configured to allow fixture **200** to fold over itself along a longitudinal axis of brackets **210**, **220**. More specifically, hinge **270** may be configured to allow first bracket **210** to rotate relative to second bracket **220**. This may allow first bracket **210** and second bracket **220** to be positioned in

5

the same plane in a first mode when fully extended, and allow first bracket **210** and second bracket **220** to be positioned in two parallel planes in a second mode when fully collapsed. This may allow fixture **200** to have a smaller width during transportation and installation. In embodiments, hinge **270** may be positioned at a point that is in the center of the longitudinal axis of brackets **210**, **220**. This may allow system **200** to be symmetrical when folded or unfolded. It should be appreciated that system **200** may include more than one hinge. This would allow system **200** to be longer in length when system **200** is extended, and the same size when system **200** is collapsed around the hinges.

In embodiments, the coupling orifices **212** may also allow the brackets **210**, **220** to be coupled to a support structure, such as a wall, ceiling, etc. Responsive to coupling a first bracket **210** to the support structure, the second bracket **220** may rotate while the first bracket remains fixed in place. This may allow the profile of system **200** to be reduced and/or altered when system **200** is affixed to the support structure. Furthermore, responsive to rotating the second bracket **220**, the light pattern on an area of interest by light sources associated with first bracket **210** and second bracket may change based on the rotation.

FIG. 3 depicts a MCPCB fixture **200**, according to an embodiment. Elements depicted in FIG. 3 may be described above, and for the sake of brevity an additional description of these elements is omitted.

As depicted in FIG. 3, hinge **270** may work as a mechanical bearing that allows first bracket **210** to rotate relative to second bracket **220**. This may decrease the angle of system **200** to be below one hundred eighty degrees, but higher than ninety degrees.

FIGS. 4 and 5 depict a MCPCB fixture **200**, according to an embodiment. Elements depicted in FIGS. 4 and 5 may be described above, and for the sake of brevity an additional description of these elements is omitted.

As depicted by FIG. 4, hinge **270** may allow first bracket **210** and/or second bracket **220** to rotate relative to one another.

As depicted in FIG. 5, responsive to rotating first bracket **210** relative to second bracket **220**, the ends of the bends associated with the first set of MCPCBs **110** may be positioned adjacent to the ends of the bends associated with the second set of MCPCBs **110**. Furthermore, the lower surfaces of first bracket **210** may be positioned adjacent or proximate to the lower surface of second bracket **220**. This may minimize the profile occupied by system **200**. Furthermore, by positioning the ends of MCPCBs **110** adjacent to each other, the light sources associated with the MCPCBs **110** may be protected. In further embodiments, hinge **270** may include a lock, which allows system **100** to be releasably positioned in the first extended mode, or the second folded mode.

FIG. 6 illustrates a method **600** for utilizing a bracketed light fixture, according to an embodiment. The operations of method **600** presented below are intended to be illustrative. In some embodiments, method **600** may be accomplished with one or more additional operations not described, and/or without one or more of the operations discussed. Additionally, the order in which the operations of method **600** are illustrated in FIG. 6 and described below is not intended to be limiting.

At operation **610**, a bracketed light fixture may be positioned in a folded mode. In the folded mode, a first set of bent panels may be rotated about a hinge to be positioned adjacent to a second set of bent panels. In the folded mode, the body of the bent panels may shield their associated light

6

sources from the elements. This may assist in protecting the light sources during transportation and installation.

At operation **620**, the first set of bent panels may be rotated around the hinge.

At operation **630**, the first set of bent panels may be positioned in an extended mode, such that the first set of bent panels are in the same plane as the second set of bent panels.

Although the present technology has been described in detail for the purpose of illustration based on what is currently considered to be the most practical and preferred implementations, it is to be understood that such detail is solely for that purpose and that the technology is not limited to the disclosed implementations, but, on the contrary, is intended to cover modifications and equivalent arrangements that are within the spirit and scope of the appended claims. For example, it is to be understood that the present technology contemplates that, to the extent possible, one or more features of any implementation can be combined with one or more features of any other implementation.

Reference throughout this specification to “one embodiment”, “an embodiment”, “one example” or “an example” means that a particular feature, structure or characteristic described in connection with the embodiment or example is included in at least one embodiment of the present invention. Thus, appearances of the phrases “in one embodiment”, “in an embodiment”, “one example” or “an example” in various places throughout this specification are not necessarily all referring to the same embodiment or example. Furthermore, the particular features, structures or characteristics may be combined in any suitable combinations and/or sub-combinations in one or more embodiments or examples. In addition, it is appreciated that the figures provided herewith are for explanation purposes to persons ordinarily skilled in the art and that the drawings are not necessarily drawn to scale.

The flowcharts and block diagrams in the flow diagrams illustrate the architecture, functionality, and operation of possible implementations of systems, methods, and computer program products according to various embodiments of the present invention. In this regard, each block in the flowcharts or block diagrams may represent a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It will also be noted that each block of the block diagrams and/or flowchart illustrations, and combinations of blocks in the block diagrams and/or flowchart illustrations, may be implemented by special purpose hardware-based systems that perform the specified functions or acts, or combinations of special purpose hardware and computer instructions.

What is claimed is:

1. A light fixture comprising:

a first set of panels, each of the panels with the first set of panels having a first end and a second end, wherein each of the panels within the first set of panels includes at least one bend;

a first bracket extending across the first set of panels in a direction that is orthogonal to each of the first set of panels, the first bracket being configured to couple each of the panels within the first set of panels together, the first bracket being positioned between the first end and the second end of each of the panels within the first set of panels, and the first bracket having a width that is smaller than a distance from the first end to the second end;

cutouts having a first side positioned on a first side of the first bracket and a second side positioned on a second side of the first bracket, the cutouts being shaped to

correspond with the at least one bend of each of the first set of panels, wherein when a corresponding panel is positioned with a first cutout a bottom surface of the corresponding panel is flush with a bottom surface of the first cutout, the corresponding panel extending away from the first side of the first cutout and the second side of the first cutout.

2. The light fixture of claim 1, further comprising:  
 a second set of panels;  
 a second bracket extending across the second set of panels;  
 a hinge configured to couple the first bracket with the second bracket.

3. The light fixture of claim 2, wherein the hinge is configured to allow the first bracket to rotate relative to the second bracket.

4. The light fixture of claim 3, wherein the first set of panels and second set of panels include concave bends, wherein light sources are configured to be positioned within the concave bends.

5. The light fixture of claim 4, wherein in a first mode the first set of panels and configured to be coplanar with the second set of panels.

6. The light fixture of claim 5, wherein in a second mode the first set of panels are configured to be positioned adjacent to the second set of panels.

7. The light fixture of claim 6, wherein the second mode the light sources are shielded by the concave bends.

8. The light fixture of claim 6, wherein the first bracket rotates one hundred eighty degrees between the first mode and the second mode.

9. A method for a light fixture comprising:  
 coupling a first bracket to a first set of panels in a direction that is orthogonal to each of the first set of panels, each of the panels with the first set of panels having a first end and a second end, the first bracket being positioned between a first end and a second end of each of the panels within the first set of panels, and the first bracket

having a width that is smaller than a distance from the first end to the second end;  
 creating cutouts within the first bracket, the cutouts having a first side positioned on a first side of the first bracket and a second side positions on a second side of the first bracket the cutouts being shaped to correspond with the at least one bend of each of the first set of panels;  
 positioning a first panel within the first cutout, the first being one panel within the first set of panels, wherein when the first panel is positioned with the first cutout a bottom surface of the first panel is flush with a bottom surface of the first cutout, and the first panel extends away from the first side of the first cutout and the second side of the first cutout.

10. The method of claim 9, further comprising:  
 coupling a second bracket to a second set of panels in a direction that is orthogonal to each of the second set of panels,  
 coupling the first bracket with the second bracket via a hinge.

11. The method of claim 10, further comprising:  
 rotating the first bracket relative to the second bracket via the hinge.

12. The method of claim 11, further comprising:  
 positioning light sources within concave bends within the first set of panels and the second set of panels.

13. The method of claim 12, wherein in a first mode the first set of panels and configured to be coplanar with the second set of panels.

14. The method of claim 13, wherein in a second mode the first set of panels are configured to be positioned adjacent to the second set of panels.

15. The method of claim 14, wherein the second mode the light sources are shielded by the concave bends.

16. The method of claim 15, wherein the first bracket rotates one hundred eighty degrees between the first mode and the second mode.

\* \* \* \* \*