

WO 2017/046298 A1

TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE,

Declarations under Rule 4.17:

— *of inventorship (Rule 4.17(iv))*

Published:

— *with international search report (Art. 21(3))*

CONTROL MECHANISM FOR STEERABLE ROD

FIELD OF INVENTION

The present invention pertains to the field of medical devices, in particular orthopedic
5 devices. The invention especially relates to improved mechanisms for controlling a rod
used for creating cavities in tissue.

BACKGROUND OF INVENTION

Vertebral compression fractures involve the collapse of one or more vertebral bodies in
10 the spine. Vertebral compression fractures or related spinal deformities may initiate, for
instance, from metastatic diseases, injuries or osteoporosis.

Conventional surgery for treating vertebral compression, often referred to as
vertebroplasty, includes a cannula or a needle inserted through the posterior of a targeted
vertebral body, usually through the pedicles. Once positioned within the compressed
15 vertebral body, bone cement is pushed through the needle into the vertebral body.
Variations of vertebroplasty include the deployment of mechanical devices or expansion
of a balloon to restore the height of the vertebral body and to create a void in a compressed
vertebral body; bone cement is then inserted into the space to stabilize the devices and to
strengthen the vertebral body.

20 In order to sufficiently access a vertebral body for complete infusion of cement it is known
to use curved needle enabling interdigitation of the cement.

Such curved needles are often made of shape-memory alloys. For instance, WO 00/33909
discloses a needle assembly comprising a hollow, curved, superelastic infusion needle.
The needle assembly comprises an infusion needle made of a superelastic material such
25 as nitinol and an outer cannula for introduction into the body of a patient. The said rigid
outer cannula is required as the initial access to the vertebral body must be made using a
relatively straight approach. Upon deployment from the outer cannula, the needle cannula
substantially returns to the preformed curved configuration for the introduction of

materials at areas lateral to the entry path of the needle assembly. In order to avoid coring the bone tissue during introduction, a trocar is inserted inside the outer cannula during introduction; once the outer cannula has been directed to the target site, the trocar is removed and the infusion needle is inserted into the said outer cannula.

- 5 However, with such devices, the friction between the curved needle and the outer cannula prevents easy introduction of the curved needle. As a result, there is a need for device creating voids within tissue with reduced friction during insertion between the curved needle or rod and the outer cannula directed to the target site.

- 10 WO2014/093464 discloses a friction reduction covering sized to be received in a cannula and a cavity creation member, biased from a retracted to a deployed configuration, sized to be disposed in the friction reduction covering. With such devices, the curved needle is enclosed within a rigid covering. Consequently, there is reduced friction between the curved needle and the cannula during the surgical procedure. However, within WO2014/093464 the friction reduction covering is not secured to the handle and slides
15 freely in at least one direction.

Therefore there is still of need for improved control of the deployment of the curved needle relative to the handle and/or the friction reduction covering.

SUMMARY

- 20 To this end, the present invention relates to a mechanism for controlling rods used for creating cavities in tissue. The control mechanism may further be used for injecting material within said cavity. The present invention also relates to steerable devices for creating cavities and injecting material in tissue, the said devices comprising the control mechanism of the invention and the rod.
- 25 The present invention thus relates to a control mechanism for controlling a rod having a preformed bent and at least one key, the control mechanism comprising:
- a handle comprising a sliding ring , a sliding shaft and a drive shaft , each extending along a longitudinal axis and comprising a central opening; wherein

- the sliding ring is threadedly connected to the sliding shaft;
- the drive shaft and the sliding shaft are connected by blocking means which prevent axial rotation between the drive shaft and the sliding shaft and which allow the drive shaft to slide within the sliding shaft; and
- 5 - the drive shaft and the sliding ring are connected by connecting means which prevent axial displacement between the drive shaft and the sliding ring and which allow axial rotation between the drive shaft and the sliding ring; and
- the internal surface of the drive shaft comprises at least one longitudinal groove or keyseat configured to engage the at least one key of the rod;
- 10 and
- a friction reduction cannula configured to receive the rod; wherein the friction reduction cannula is secured to the sliding shaft or to the drive shaft.

According to one embodiment, the sliding ring comprises a threaded inner surface and the sliding shaft comprises at least one protrusion protruding outwardly from the sliding
15 shaft and engaging the at least one threaded inner surface of the sliding ring so that axial rotation of the sliding ring causes the sliding shaft to move back and forth along the longitudinal axis.

According to one embodiment, the blocking means comprise at least one key or at least one longitudinal keyseat within the external surface of the drive shaft engaged in
20 respectively at least one longitudinal keyseat or at least one key within the internal surface of the sliding shaft.

According to one embodiment, the connecting means between the drive shaft and the sliding ring comprise a bearing such as a plain bearing.

According to one embodiment, the friction reduction cannula has a longitudinal axis and
25 comprises an opening configured to receive and restrain at least partially the rod, especially the preformed bent, in a straight configuration along the longitudinal axis.

According to one embodiment, the friction reduction cannula is made from steel, preferably stainless steel.

According to one embodiment, the friction reduction cannula comprises a proximal part and a distal part, wherein the distal part is more flexible than the proximal part so that the proximal part restrains the rod in the straight configuration and the distal part does not restrain the rod in the straight configuration.

- 5 According to one embodiment, the proximal part of the friction reduction cannula is made from steel, such as stainless steel and a distal part is made from a polymeric material such as polyether block amide.

According to one embodiment, the drive shaft further comprises at its proximal end a connecting thread.

- 10 According to one embodiment, the control mechanism further comprising a connecting cap comprising a threaded inner surface assembled onto the connecting thread, the said connecting cap comprising a plurality of flexible lugs, protruding distally and outwardly, designed to engage a plurality of openings at or near the proximal end of the sliding ring thereby preventing rotation of the sliding ring.
- 15 According to one embodiment, the connecting cap further comprises at least one protrusion or recess, preferably a sawtooth protrusion or a sawtooth recess.

According to one embodiment, the sliding shaft further comprises a hub protruding distally and outwardly.

- 20 According to one embodiment, the hub comprises a locking ring designed to secure the sliding shaft with a trocar.

The present invention also relates to a steerable device comprising a control mechanism according to the invention and a rod having a preformed bent and at least one key, the rod being preferably made from a superelastic material, such as an alloy of nickel and titanium.

- 25 According to one embodiment, the angle of deflection of the rod ranges from 20° to 150°, preferably from 30° to 130°, more preferably from 40° to 110°.

According to one embodiment, the rod comprises at its proximal end a knob comprising a threaded inner surface designed to be assembled onto the connecting cap, the knob and the rod being connected by means of a bearing which allow axial rotation between the knob and the rod.

- 5 According to one embodiment, the knob further comprises at least one protrusion or recess, preferably a sawtooth protrusion or a sawtooth recess designed to be engaged with respectively at least one recess or protrusion of the connecting cap thereby preventing rotation between the connecting cap and the knob.

10 The present invention also relates to a steerable system comprising a steerable device according to the present invention and a trocar, preferably a bone access trocar, suitable to be positioned adjacent to an exterior surface of a targeted tissue.

According to one embodiment, the steerable device, especially the friction reduction cannula, is inserted in the trocar and connected by the locking ring. According to an alternative embodiment, the trocar is threadedly connected to the hub.

- 15 According to one embodiment, the control mechanism comprises a friction reduction cannula made from steel, preferably stainless steel.

DEFINITIONS

In the present invention, the following terms have the following meanings:

- 20 – As used herein the singular forms “a”, “an”, and “the” include plural reference unless the context clearly dictates otherwise.
- The term “**about**” is used herein to mean approximately, roughly, around, or in the region of. When the term “about” is used in conjunction with a numerical range, it modifies that range by extending the boundaries above and below the numerical
- 25 values set forth. In general, the term "about" is used herein to modify a numerical value above and below the stated value by a variance of 20 percent, preferably of 5 percent.

- The words “**proximal**” and “**distal**” refer to directions respectively towards and away from the surgeon using the medical device.
- “**Rod**” or “**Steerable rod**” refers to a rod or bar comprising a part having a predefined bent or curvature.
- 5 – “**Secured**” means attached, coupled or connected in a non-detachable manner unintentionally. Therefore, the term secured may comprise for instance the term integrally connected or over-molded.
- “**Tissue**” refers herein to soft tissue or hard tissue. According to a preferred embodiment, tissue refers to hard tissue such as bone tissue.

10

DETAILED DESCRIPTION

The following detailed description will be better understood when read in conjunction with the drawings. For the purpose of illustrating, the device is shown in the preferred embodiments. It should be understood, however that the application is not limited to the
15 precise arrangements, structures, features, embodiments, and aspect shown. The drawings are not drawn to scale and are not intended to limit the scope of the claims to the embodiments depicted.

According to a first aspect of the invention, there is provided a control mechanism for controlling a rod used for creating cavities in tissue, comprising a friction reduction
20 cannula and a handle.

As depicted in figure 1, the control mechanism **100** elongates along a longitudinal axis **101** between a proximal end **100a** and a distal end **100b** spaced apart from the proximal end **100a**. The control mechanism **100** comprises a friction reduction cannula **110** and a handle **130**.

25 As depicted in figures 2, 3 and 4, the handle **130** is configured to be grasped by the user and comprises a sliding ring **131**, a sliding shaft **132** and a drive shaft **133**. The handle **130** extends along a longitudinal axis **101** from a proximal end to a distal end.

The sliding ring **131** is cylindrical or tubular, extends along a longitudinal axis **101** and comprises a central opening from a proximal end **131a** to a distal end **131b**. According to one embodiment, the central opening is configured to receive the sliding shaft **132** and the drive shaft **133**. According to one embodiment, the sliding ring **131**, especially the
5 central opening comprises a threaded inner surface. According to one embodiment, the threaded inner surface of the sliding ring **131** is a cylindrical surface formed with a continuous thread.

The sliding shaft **132** is cylindrical or tubular, extends along a longitudinal axis **101** and comprises a central opening from a proximal end **132a** to a distal end **132b**. According to
10 one embodiment, the central opening is configured to receive a drive shaft **133**. According to one embodiment, the sliding ring **131** is cylindrical and is outside and encloses at least partially the sliding shaft **132**. According to one embodiment, the sliding shaft **132** comprises at least one tab, pin or protrusion **1321** extending outwardly, preferably at the proximal end thereof **132a**. According to one embodiment, the outer surface of the sliding
15 shaft **132** comprises marks indicating the translation of the sliding ring **131** relative to the sliding shaft **132**.

The sliding ring **131** is threadedly connected to the sliding shaft **132**. According to one embodiment, the protrusion(s) **1321** of the sliding shaft **132** engage or mate with threaded inner surface of the sliding ring **131**. More particularly, the external protrusion(s) **1321** of
20 the sliding shaft **132** is engaged with the internal thread of threaded inner surface of the sliding ring **131**. Rotation of the sliding ring **131** causes sliding shaft **132** to move relatively along a helical path of the thread of threaded inner surface of the sliding ring **131**. More particularly, rotation of the sliding ring **131** causes protrusions **1321** of the sliding shaft **132** to track the helical path of the thread of threaded inner surface of the
25 sliding ring **131**. So, rotation about the longitudinal axis of the sliding ring **131** causes the sliding shaft **132** to move back and forth along the longitudinal axis **101**, relative to the sliding ring **131**. With respect to the sliding shaft **132**, rotation of the sliding ring **131** causes the sliding ring **131** to move back and forth along the longitudinal axis **101** in rotation.

According to an alternative embodiment wherein the sliding ring is threadedly connected to the sliding shaft; the sliding shaft **132** comprises a threaded outer surface and the sliding ring comprises at least one tab, pin or protrusion extending inwardly, preferably at the distal end thereof and engage the threaded outer surface of the sliding shaft.

- 5 The drive shaft **133** is cylindrical or tubular, extends along a longitudinal axis **101** and comprises a central opening from a proximal end **133a** to a distal end **133b**. According to one embodiment, the sliding shaft **132** is cylindrical and is outside and encloses at least partially the drive shaft **133**. According to one embodiment, the drive shaft **133** is configured to slide longitudinally inside the sliding shaft **132**.
- 10 According to one embodiment, the drive shaft **133** and the sliding shaft **132** are connected by blocking means which prevent axial rotation between the drive shaft **133** and the sliding shaft **132** and which allow the drive shaft **133** to slide within the sliding shaft **132**. According to one embodiment, the drive shaft **133** comprises at least one key sliding in a keyseat, such as at least one longitudinal slot, in the internal surface of the sliding shaft
- 15 **132**. Alternatively, the sliding shaft **132** comprises at least one key sliding in a keyseat, such as at least one longitudinal slot, in the external surface of the drive shaft **133**. Consequently, the drive shaft **133** is prevented from rotating axially relative to said sliding shaft **132**.

- According to one embodiment, the drive shaft **133** is connected to the sliding ring **131** by
- 20 means of a connecting means, such as shoulders and grooves. According to one embodiment, the said connecting means form a bearing, such as a plain bearing. According to one embodiment, the bearing allows axial rotation of the sliding ring **131** relative to the drive shaft **133** about the longitudinal axis of the rod. According to one embodiment, the bearing prevents any other degrees of freedom. According to one
- 25 embodiment, the drive shaft **133** is connected with the sliding ring **131** by means of a bearing which prevents axial displacement between the drive shaft **132** and the sliding ring **131** and which allows axial rotation between the drive shaft **132** and the sliding ring **131**. Consequently, as the threads of the sliding ring **131** track the protrusions(s) **1321** of the sliding shaft **132**, driving the sliding ring **131** into a helical path, the drive shaft **133**
- 30 translates in a longitudinal axis relative to the sliding shaft **132**. According to one

embodiment, the drive shaft **133** and the sliding ring **131** are connected together at or near their proximal end **131a**, **133a**.

According to one embodiment, the proximal end **133a** of the drive shaft **133** comprises a connecting thread **1331**, protruding proximally. In one embodiment, the said connecting
5 thread **1331** is any connecting thread known by one skilled in the art such as a “luer” type allowing connections of multiple devices equipped with mating threads.

According to one embodiment, the handle **130** comprises a connecting cap **135** comprising an inner thread so that the connecting cap **135** can be assembled onto the connecting thread **1331**. According to one embodiment the connecting cap **135** comprises
10 a plurality of flexible lugs **1351** protruding outwardly and distally. Said flexible lugs **1351** engage a plurality of openings at or near the proximal end **131a** of the sliding ring **131** thereby preventing rotation of the sliding ring. Consequently when the connecting cap **135** is assembled onto the connecting thread **1331**, the sliding ring **131** cannot axially rotate about the longitudinal axis **101** relative to the sliding shaft **132**. According to one
15 embodiment, the outer surface of the connecting cap **135** comprises a thread.

According to one embodiment, the sliding shaft **132** comprises a hub **1322** extending distally and outwardly from the sliding shaft **132**. According to one embodiment, the connection between the hub **1322** and the sliding shaft **132** prevents any degrees of freedom. According to one embodiment, the sliding shaft **132** and the hub **1322** are
20 integral. According to one embodiment, the handle **130**, especially the sliding shaft **132**, more particularly the hub **1322**, comprises arrows pointing to the same direction.

According to one embodiment, the handle **130** may be manipulated from a retracted position to a deployed position. In the retracted position, the protrusion(s) **1321** of the sliding shaft **132** engage the distal end of the thread of the sliding ring **131**, as depicted in
25 figures 5, 6 and 9. In the deployed configuration, the protrusion **1321** of the sliding shaft **132** engage the proximal end of the thread of the sliding ring **131** as depicted in figures 7, 8 and 9.

As depicted in figure 1, the friction reduction cannula **110** extends along a longitudinal axis **101**. The friction reduction cannula defines a proximal end **110a** and a distal end **110b** that is spaced apart from the proximal end **110a** along the longitudinal axis. The friction reduction cannula **110** also defines an outer cannula surface and an inner cannula surface opposite the outer cannula surface. The inner cannula surface defines a cannula opening elongating along the longitudinal axis between the proximal end **110a** and the distal end **110b**.

According to one embodiment, the cross-sectional section of the inner cannula surface of the friction reduction cannula **110** is constant along the longitudinal axis. According to one embodiment, as depicted in figure 10, 11 and 12; the friction reduction cannula opening is configured and sized to receive at least a portion of a rod **210**. The friction reduction cannula **110** is configured to enclose at least partially a rod **210** as depicted in figure 10, 11 and 12.

According to one embodiment, when used with a rod **210**, the friction reduction cannula **110** is configured to restrain at least partially the rod **210** in a straight configuration along the longitudinal axis in order to ease insertion of the rod within a trocar **310**, such as a bone access trocar. According to one embodiment, the friction reduction cannula **110** is configured to be used coaxially with the rod **210** for restraining at least partially the rod **210** in a straight configuration along the longitudinal axis.

According to one embodiment, the cross-sectional section of the outer cannula surface of the friction reduction cannula **110** is constant along the longitudinal axis. According to one embodiment, the friction reduction cannula opening is configured and sized to be received in at least a portion of a trocar **310**, such as a bone access trocar. The trocar **310** is configured to enclose at least partially the friction reduction cannula **110** as depicted in figure 4.

According to one embodiment, the handle **130** further comprises locking means configured to connect a trocar **310**, sized to enclose at least partially the friction reduction cannula **110**, to the handle **130**. As detailed hereafter, said locking means may be positioned on the hub **1322** and may be a locking ring **1323** or any connecting thread.

According to one embodiment, as depicted in figures 2 and 3, the friction reduction cannula **110** is secured to drive shaft **133**. According to a preferred embodiment, the proximal end of the friction reduction cannula **110a** is secured to distal end **133b** of the drive shaft **133**. In one exemplary embodiment, the drive shaft **133** is molded over the friction reduction cannula **110**. According to one embodiment, the friction reduction cannula **110** and the drive shaft **133** are connected by an O-ring.

According to an alternative embodiment, as depicted in figures 16, 17 and 18, the friction reduction cannula **110** is secured to the sliding shaft **132**, especially with the hub **1322**. According to a preferred embodiment, the proximal end of the friction reduction cannula **110a** is secured to the distal end of the sliding shaft **132b**, especially with the hub **1322**.

According to one embodiment, as depicted in figure 11, the friction reduction cannula **110** comprises a proximal part **111** and a distal part **112**. According to one embodiment, the distal part of the friction reduction cannula **112** is more flexible than the proximal part of the friction reduction cannula **111**. According to one embodiment, the proximal part of the friction reduction cannula **111** is made from steel, preferably stainless steel. According to one embodiment, the distal part of the friction reduction cannula **112** is made from polymeric material, such as polyether block amide. According to one embodiment, the ratio between the length along the longitudinal axis of the distal part **112** and the length along the longitudinal axis of the proximal part **111** is ranging from 1/2 to 1/6. According to one embodiment, when used with a rod having a predefined bent, the distal part of the friction reduction cannula **112** has a length equal to the length of the bent part of the rod **210**.

According to one embodiment, when used with a rod **210** having a predefined bent, the proximal part of the friction reduction cannula **111** is configured to restrain the rod **210** in a straight configuration when the distal end **210b** of the rod does not extend out distally from the proximal part **111**. According to one embodiment, the distal part of the friction reduction cannula **112** is not configured to restrain the rod **210** in a straight configuration when the distal end **210b** of the rod **210** extends out distally from the proximal part **111**; the distal part **112** follows the curvature of the rod **210**.

According to one embodiment, when the friction reduction cannula **110** is secured to the drive shaft **133**, the friction reduction cannula is made of two parts: a proximal part **111** and a distal part **112** more flexible than the proximal part.

5 According to one embodiment, in order to avoid that the distal part **112** shrinks during insertion in the tissue, the distal part comprises metal reinforcements. According to one embodiment, the polymeric material of the distal part **112** is over-molded on the metallic reinforcements.

10 According to an alternative embodiment, the friction reduction cannula **110** is made in a single piece. According to said embodiment, the friction reduction cannula **111** is made from steel, preferably stainless steel.

According to one embodiment, when used with a rod **210**, the friction reduction cannula **110** is configured to restrain the rod **210** in a straight configuration when the distal end of the rod **210b** does not extend out distally from the friction reduction cannula **110**.

15 According to one embodiment, when the friction reduction cannula **110** is secured with the sliding shaft **132**, the friction reduction cannula **110** is made in a single piece.

According to a second aspect of the invention, there is also provided a steerable device for creating cavities and injecting material in tissue using minimally invasive techniques.

20 The steerable device **200** according to the invention comprises the control mechanism **100** of the invention and a rod **210**. The rod **210** passes through the drive shaft **133** and the sliding shaft **132** of the control mechanism **100**.

25 According to one embodiment, the rod **210** has a predefined bend. According to one embodiment, only the distal part of the rod is bent, preferably from 1 to 50%, preferably from 2 to 25%, more preferably from 5 to 10% of the length of the rod **210**. According to said embodiment, the proximal part of the rod **210** extends along a longitudinal axis **101**. The rod **210** defines a proximal end **210a** and a distal end **210b** that is spaced apart from the proximal end **210a**. According to one embodiment, the angle of deflection of the rod **210** ranges from 20° to 150°, preferably from 30° to 130°, more preferably from 40° to 110° (as measured from the longitudinal axis). According to one embodiment, the cross-

sectional section of the rod **210** is constant. According to one embodiment, the rod **210** has no opening along its length.

According to one embodiment, the length of the rod **210** along the longitudinal axis **110** is equal to the length along the longitudinal axis **110** from the proximal end of the handle
5 **130** to the distal end of the friction reduction cannula **110b**.

According to one embodiment, the rod **210** comprises a superelastic material, preferably an alloy of nickel and titanium.

According to one embodiment, the rod **210** comprises a knob **211** at its proximal end **210a**. According to one embodiment, the knob **211** is free in rotation relative to the rod
10 **210**. According to one embodiment, the rod **210** is connected to the knob **211** by means of a bearing, such as a plain bearing. According to one embodiment, the bearing allows axial rotation of the knob **211** relative to the rod **210** about the longitudinal axis of the rod. According to one embodiment, the knob **211** comprises a threaded inner surface suitable for mating the thread of the connecting cap **135**. Due to the bearing, the knob **211**
15 of the rod **210** may be screw on the connecting cap **135** without axial rotation of the rod **210**. According to one embodiment, the knob **211** further comprises at the distal end of the threaded inner surface a protrusion, such as a sawtooth protrusion, or a recess to be engaged in respectively a recess or a protrusion **1352** within the connecting cap **135**. Thus, once the knob **211** has been screwed onto the connecting cap **135** so that the protrusion
20 **1352** engages the recess, the knob **211** and the connecting cap **135** do not rotate independently. Thus unscrewing of the knob **211** disengages the connecting cap **135** from the connecting thread **1331**.

According to one embodiment, once the protrusion **1352** of the connecting cap engages a recess of the knob **211**, the threaded inner surface of the knob **211** depresses the flexible
25 lugs **1351** inside the central opening of the sliding ring, so that the sliding ring **131** may be rotated relative to the drive shaft **133**. Consequently, when the knob **211** of the rod **210** has been screwed onto the connecting cap **135**, the sliding ring **131** can axially rotate about the longitudinal axis **101** relative to the sliding shaft **132**.

According to one embodiment, the deflection plane of the rod **210** may be pre-determined. According to one embodiment, the rod **210** comprises, preferably proximally, at least one key sliding in a keyseat, such as at least one longitudinal slot, in the internal surface of the drive shaft **133**. Consequently, the rod **210** is prevented from rotating axially relative to said drive shaft **133**. Due to the said key of the rod **210**, the deflection plane of the rod **210** may be predefined relative to the drive shaft **133**. According to one embodiment, as the drive shaft **133** is prevented from axially rotating relative to the sliding shaft **132**, the deflection plane of the rod **210** is also predefined relative to the sliding shaft **132** and thus relative to the hub **1322** of the handle; so that the arrows of the hub **1322** point towards the direction of the preformed bent of the rod **210**.

According to a further aspect of the invention, there is provided a steerable system **300** for creating cavities and injecting material in tissue using minimally invasive techniques.

The steerable system **300** according to the invention comprises the steerable device of the invention and a trocar **310**, such as a bone access trocar.

According to one embodiment, the trocar **310** extends along a longitudinal axis **101** from a proximal end **310a** to a distal end **310b** spaced apart from the proximal end **310a** along the longitudinal axis **101**. According to one embodiment, the length of the trocar **310** along the longitudinal axis **101** is equal to the length along the longitudinal axis **101** of the friction reduction cannula **130** from the hub **1322** to the distal end of the friction reduction cannula **110b**.

The trocar **310** also defines an outer trocar surface and an inner trocar surface opposite the outer trocar surface. The inner trocar surface defines a trocar opening elongating along the longitudinal axis **101** between the distal end **310b** and the proximal end **310a**. According to one embodiment, the trocar opening is configured and sized to receive at least a portion of the steerable device according to the invention, especially at least a portion of the friction reduction cannula **110**. According to one embodiment, the cross-sectional section of the inner surface of the trocar **310** is constant along the longitudinal axis **101**.

According to one embodiment, the trocar **310** is connected to the distal end of the handle **130**, preferably to the distal end of the sliding shaft **132b**, more preferably to the hub **1322**. According to one embodiment, the control mechanism **100**, especially the friction reduction cannula **110**, is inserted in the trocar **310** and the trocar **310** is connected to the

5 distal end of the handle **130**, preferably to the distal end of the sliding shaft **132b**, more preferably to the hub **1322**, by a locking ring **1323**. According to one embodiment, the trocar **310** comprises a connecting thread **311** at its proximal end **310a**. The said connecting thread **311** is any connecting thread known by one skilled in the art such as a “luer” type allowing connections of multiple devices equipped with mating threads

10 According to said embodiment, the trocar **310**, especially the connecting thread **311**, is threadedly connected to the distal end of the handle **130**, preferably to the distal end of the sliding shaft **132b**, more preferably to the hub **1322**, in a detachable manner.

According to one embodiment, the hub **1322** comprises a locking ring **1323** for locking the trocar **310** onto the handle **130**. According to one embodiment, the mating surfaces

15 between the sliding shaft **132** and the trocar **310** guarantee that the control mechanism **100** is properly located onto the trocar **310** both in longitudinal translation and in axial rotation about the longitudinal axis. According to one embodiment, when the locking ring **1323** is actuated, there is no degree of freedom between the handle **130** and the trocar **310**; the trocar **130** is secured to the hub **1322**.

20 According to one embodiment (as explained hereabove), when the friction reduction cannula **110** is made in a single piece, the friction reduction cannula **110** is secured to the sliding shaft **132**.

In use, the rod **210** is inserted within the control mechanism **100** with the handle **130** is in the retracted position. The knob **211** of the rod **210** is screwed onto the connecting cap

25 **135**. In this position, the rod **210** is in a straight configuration. The control mechanism **100** comprising the rod **210** in its retracted position may then be slid through the trocar **310** which has been placed in an appropriate location in the patient's tissue. The rod may then be deployed by rotating the sliding ring in the deployed configuration. In the deployed configuration, the rod **210** extends laterally outside of the friction reduction

30 cannula **110** and of the trocar **310**. Said steps may be repeated with different direction of

the deflection plane, in order to create multiple interdigitated cavities. Once the cavities have been created, the rod **210** may be removed by unscrewing the knob **211** and thus allowing access to the connecting thread **1331** (the connecting cap **135** being removed with the knob **211**). An injection device **320** may then be connected to the connecting
5 thread **1331** in order to inject material within the created cavities through the drive shaft **133** and the friction reduction cannula **110**.

According to one embodiment (as explained hereabove), when the friction reduction cannula **110** is made in a two parts, the friction reduction cannula **110** is secured with the drive shaft **133**.

10 When the friction reduction cannula **110** comprises a proximal part **111** and a distal part **112**, the steerable device **110** needs to be armed in order to bring the distal end of the rod **210b** from a retracted position inside the proximal part of the friction reduction cannula **111**, as depicted in figure 10, to an operational position at the distal end of the distal part of the friction reduction cannula **112**, as depicted in figures 5 and 6.

15 To this end, once the control mechanism **100** comprising the rod **210** is slid through the trocar **310** which has been placed in an appropriate location in the patient's tissue and then locked onto the trocar **310**, the rod **210** is pushed until the knob **211** comes in contact with the connecting cap **135**. The knob **211** is then screwed on the connecting cap **135**. As explained hereabove, screwing fully knob **211** onto the connecting cap **135**, protrusion
20 or recess of the knob **211** engages respectively a recess or protrusion **1352** of the connecting cap **135**, thus locking the knob **211** on the connecting cap **135**. Screwing fully knob **211** onto the connecting cap **135** also pushes inwards the flexible lugs **1351**, freeing them from the corresponding openings in the proximal end of the sliding ring **131a**, thus allowing rotation of the sliding ring **131**.

25 According to one embodiment, when the distal end of the threaded inner surface of the sliding ring **131** engages with the protrusion(s) **1321** of the sliding shaft **132** (retracted position), and when the steerable device is secured to the trocar **310**, the translation of the drive shaft to the deployed position caused by the rotation of the sliding ring **131** drives

both the friction reduction cannula **110** and the rod **210** to extends out of the trocar laterally, thus creating a cured cavity in the tissue, as depicted in figures 7 and 8.

Once the cavity has been created, the rod **210** may be removed by unscrewing the knob **211** and thus allowing access to the connecting thread **1331** (the connecting cap **135** being removed with the knob **211**). An injection device may then be connected to the connecting thread **1331** in order to inject material within the created cavities through the drive shaft **133** and the friction reduction cannula **110**, as depicted in figures 13, 14 and 15. Due to the flexible part of the friction reduction cannula **112** and by rotating the handle from the deployed position to the retracted position, material may be injected in a retrograde manner.

According to one embodiment, the material may be any material known to one skilled in the art, such as bone cement.

While various embodiments have been described and illustrated, the detailed description is not to be construed as being limited hereto. Various modifications can be made to the embodiments by those skilled in the art without departing from the true spirit and scope of the disclosure as defined by the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

As explained in the specification hereabove, figures 1 to 15 relate to a control mechanism, a steerable device and a steerable system wherein the friction reduction cannula comprises a distal part and a proximal part and is connected to the drive shaft. Figures 16 to 18 relate to a control mechanism, a steerable device and a steerable system wherein the friction reduction cannula is made of a single piece and is connected to the sliding shaft.

Figure 1 is a front view of the control mechanism according to one embodiment of the invention.

Figure 2 is a front view of the steerable system with the control mechanism in the retracted position according to one embodiment of the invention, without the rod.

Figure 3 is a sectional view of the steerable system of figure 2 along plane AA.

Figure 4 is a sectional view of figure 2 along plane BB.

Figure 5 is a front view of the steerable system with the control mechanism in the armed position according to one embodiment of the invention.

5 **Figure 6** is a sectional view of the steerable system of figure 5 along plane AA.

Figure 7 is a front view of the steerable system with the control mechanism in the deployed position according to one embodiment of the invention.

Figure 8 is a sectional view of the steerable system of figure 7 along plane AA.

Figure 9 is a sectional view of the steerable system of figures 5 and 7 along plane BB.

10 **Figure 10** is a front view of the steerable device in the retracted position according to one embodiment of the invention.

Figure 11 is a sectional view of the steerable device according to figure 10 along plane AA.

Figure 12 is a sectional view of the steerable device of figure 10 along plane BB.

15 **Figure 13** is a front view of the steerable system with the control mechanism connected with an injection device.

Figure 14 is a sectional view of the steerable system of figure 13 along plane AA.

Figure 15 is a sectional view of figure 13 along plane BB.

20 **Figure 16** is a front view of the steerable system with the control mechanism in the retracted position according to one embodiment of the invention, without the rod.

Figure 17 is a sectional view of the steerable system of figure 16 along plane AA.

Figure 18 is a sectional view of figure 16 along plane BB.

REFERENCES

- 100 – Control mechanism;
- 100a – Proximal end of the control mechanism;
- 100b – Distal end of the control mechanism;
- 5 101 – Longitudinal axis of the control mechanism;
- 110 – Friction reduction cannula;
- 110a – Proximal end of the friction reduction cannula;
- 110b – Distal end of the friction reduction cannula;
- 111 – Proximal part of the friction reduction cannula;
- 10 112 – Distal part of the friction reduction cannula;
- 130 – Handle;
- 131 – Sliding ring;
- 131a – Proximal end of the sliding ring;
- 131b – Distal end of the sliding ring;
- 15 132 – Sliding shaft;
- 132a – Proximal end of the sliding shaft;
- 132b – Distal end of the sliding shaft;
- 1321 – Protrusion of the sliding shaft;
- 1322 – Hub;
- 20 1323 – Locking ring;
- 133 – Drive shaft;
- 133a – Proximal end of the drive shaft;
- 133b – Distal end of the drive shaft;
- 1331 – Connecting thread;
- 25 135 – Connecting cap;
- 1351 – Flexible lug;
- 1352 – Protrusion;
- 200 – Steerable device;
- 210 – Rod;
- 30 210a – Proximal end of the rod;
- 210b – Distal end of the rod;

- 211 – Knob of the rod;
- 300 – Steerable system;
- 310 – Trocar;
- 310a – Proximal end of the trocar;
- 5 310b – Distal end of the trocar;
- 311 – Connecting thread;
- 320 – Injection device.

CLAIMS:

1. A control mechanism for controlling a rod having a preformed bent and at least one key, the control mechanism comprising:
 - a handle comprising a sliding ring, a sliding shaft and a drive shaft, each extending along a longitudinal axis and comprising a central opening; wherein the sliding ring is threadedly connected to the sliding shaft;
 - the drive shaft and the sliding shaft are connected by blocking means which prevent axial rotation between the drive shaft and the sliding shaft and which allow the drive shaft to slide within the sliding shaft; and
 - the drive shaft and the sliding ring are connected by connecting means which prevent axial displacement between the drive shaft and the sliding ring and which allow axial rotation between the drive shaft and the sliding ring; and
 - the internal surface of the drive shaft comprises at least one longitudinal groove or keyseat configured to engage the at least one key of the rod; and
 - a friction reduction cannula configured to receive the rod; wherein
 - the friction reduction cannula is secured to the sliding shaft or to the drive shaft.
2. The control mechanism according to claim 1, wherein the sliding ring comprises a threaded inner surface and the sliding shaft comprises at least one protrusion protruding outwardly from the sliding shaft and engaging the at least one threaded inner surface of the sliding ring so that axial rotation of the sliding ring causes the sliding shaft to move back and forth along the longitudinal axis.
3. The control mechanism according to claim 1 or claim 2, wherein the blocking means comprise at least one key or at least one longitudinal keyseat within the external surface of the drive shaft engaged in respectively at least one longitudinal keyseat or at least one key within the internal surface of the sliding shaft.
4. The control mechanism according to any one of claims 1 to 3, wherein the connecting means between the drive shaft and the sliding ring comprise a bearing.

5. The control mechanism according to any one of claims 1 to 4, wherein the friction reduction cannula has a longitudinal axis and comprises an opening configured to receive and restrain at least partially the rod, especially the preformed bent, in a straight configuration along the longitudinal axis.

6. The control mechanism according to claim 5, wherein the friction reduction cannula comprises a proximal part and a distal part, wherein the distal part is more flexible than the proximal part so that the proximal part restrains the rod in the straight configuration and the distal part does not restrain the rod in the straight configuration.

7. The control mechanism according to any one of claims 1 to 6, wherein the drive shaft further comprises at its proximal end a connecting thread.

8. The control mechanism according to claim 7, further comprising a connecting cap comprising a threaded inner surface assembled onto the connecting thread, the said connecting cap comprising a plurality of flexible lugs, protruding distally and outwardly, designed to engage a plurality of openings at or near the proximal end of the sliding ring thereby preventing rotation of the sliding ring.

9. A steerable device comprises a control mechanism according to any one of claims 1 to 8 and a rod having a preformed bent and at least one key, the rod being made from a superelastic material.

10. The steerable device according to claim 9, wherein the rod comprises at its proximal end a knob comprising a threaded inner surface designed to be assembled onto the connecting cap, the knob and the rod being connected by means of a bearing which allow axial rotation between the knob and the rod.

2/12




FIG. 2




FIG. 3

3/12




FIG. 4

4/12




FIG. 5




FIG. 6

5/12




FIG. 7




FIG. 8

6/12




FIG. 9

8/12




FIG. 11




FIG. 12

9/12




FIG. 13




FIG. 14

10/12




FIG. 15

11/12




FIG. 16




FIG. 17

12/12




FIG. 18




FIG. 5