



US 20190201118A1

(19) **United States**

(12) **Patent Application Publication**
Shelton, IV et al.

(10) **Pub. No.: US 2019/0201118 A1**

(43) **Pub. Date: Jul. 4, 2019**

(54) **DISPLAY ARRANGEMENTS FOR
ROBOT-ASSISTED SURGICAL PLATFORMS**

Publication Classification

(51) **Int. Cl.**

A61B 34/00 (2006.01)

A61B 34/35 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 34/25** (2016.02); **A61B 34/35**

(2016.02); **A61B 2017/00477** (2013.01); **A61B**

34/77 (2016.02); **A61B 34/76** (2016.02)

(71) Applicant: **Ethicon LLC**, Guaynabo, PR (US)

(72) Inventors: **Frederick E. Shelton, IV**, Hillsboro,
OH (US); **David C. Yates**, West
Chester, OH (US); **Jason L. Harris**,
Lebanon, OH (US)

(21) Appl. No.: **15/940,690**

(22) Filed: **Mar. 29, 2018**


Related U.S. Application Data

(60) Provisional application No. 62/649,307, filed on Mar.
28, 2018, provisional application No. 62/611,341,
filed on Dec. 28, 2017, provisional application No.
62/611,340, filed on Dec. 28, 2017, provisional ap-
plication No. 62/611,339, filed on Dec. 28, 2017.

(57)

ABSTRACT

Various surgical systems are disclosed. A surgical system comprises a robotic tool, a robot control system, a surgical instrument, and a surgical hub. The robot control system comprises a control console and a control unit in signal communication with the control console and the robotic tool. The surgical hub comprises a display. The surgical hub is in signal communication with the robot control system. The surgical hub is configured to detect the surgical instrument and represent the surgical instrument on the display.







FIG. 1






FIG. 3

FIG. 4




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24





FIG. 25A FIG. 25B




FIG. 26A




FIG. 26B




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33







FIG. 34








FIG. 38




FIG. 39




FIG. 41




FIG. 40




FIG. 42





FIG. 43






FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49

DISPLAY ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims the benefit of priority under 35 U.S.C. 119(e) to U.S. Provisional Patent Application Ser. No. 62/649,307, titled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, filed Mar. 28, 2018, the disclosure of which is herein incorporated by reference in its entirety.

[0002] This application also claims the benefit of priority under 35 U.S.C. 119(e) to U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, to U.S. Provisional Patent Application Ser. No. 62/611,340, titled CLOUD-BASED MEDICAL ANALYTICS, filed Dec. 28, 2017, and to U.S. Provisional Patent Application Ser. No. 62/611,339, titled ROBOT ASSISTED SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of each of which is herein incorporated by reference in its entirety.

BACKGROUND

[0003] The present disclosure relates to robotic surgical systems. Robotic surgical systems can include a central control unit, a surgeon's command console, and a robot having one or more robotic arms. Robotic surgical tools can be releasably mounted to the robotic arm(s). The number and type of robotic surgical tools can depend on the type of surgical procedure. Robotic surgical systems can be used in connection with one or more displays and/or one or more handheld surgical instruments during a surgical procedure.

SUMMARY

[0004] In one general aspect, a surgical system is provided. The surgical system comprises: a robotic tool; a robot control system; a surgical instrument; and a surgical hub. The robot control system comprises: a control console and a control unit in signal communication with the control console and the robotic tool. The surgical hub comprises a display. The surgical hub is in signal communication with the robot control system. The surgical hub is configured to detect the surgical instrument and represent the surgical instrument on the display.

[0005] In another general aspect, a surgical system is provided. The surgical system comprises: a robotic tool and a robot control system, comprising a control console and a control unit in signal communication with the control console and the robotic tool. The surgical system further comprises a surgical instrument operable in a plurality of operating states, and also comprises a surgical hub. The surgical hub comprises a display. The surgical hub is in signal communication with the robot control system. The surgical hub is configured to detect an activated operating state of the surgical instrument and represent the active operating state on the display.

[0006] In yet another general aspect, a surgical system is provided. The surgical system comprises: a robotic tool and a robot control system comprising a control console and a control unit in signal communication with the control console and the robotic tool. The surgical system also comprises a surgical instrument, a surgical hub, and a display. The surgical hub is in signal communication with the robot

control system. The surgical hub is configured to detect the surgical instrument. The display is in signal communication with the surgical hub. The surgical hub is configured to represent the surgical instrument on the display.

BRIEF DESCRIPTION OF THE FIGURES

[0007] The features of various aspects are set forth with particularity in the appended claims. The various aspects, however, both as to organization and methods of operation, together with further objects and advantages thereof, may best be understood by reference to the following description, taken in conjunction with the accompanying drawings as follows.

[0008] FIG. 1 is a block diagram of a computer-implemented interactive surgical system, in accordance with at least one aspect of the present disclosure.

[0009] FIG. 2 is a surgical system being used to perform a surgical procedure in an operating room, in accordance with at least one aspect of the present disclosure.

[0010] FIG. 3 is a surgical hub paired with a visualization system, a robotic system, and an intelligent instrument, in accordance with at least one aspect of the present disclosure.

[0011] FIG. 4 is a partial perspective view of a surgical hub enclosure, and of a combo generator module slidably receivable in a drawer of the surgical hub enclosure, in accordance with at least one aspect of the present disclosure.

[0012] FIG. 5 is a perspective view of a combo generator module with bipolar, ultrasonic, and monopolar contacts and a smoke evacuation component, in accordance with at least one aspect of the present disclosure.

[0013] FIG. 6 illustrates individual power bus attachments for a plurality of lateral docking ports of a lateral modular housing configured to receive a plurality of modules, in accordance with at least one aspect of the present disclosure.

[0014] FIG. 7 illustrates a vertical modular housing configured to receive a plurality of modules, in accordance with at least one aspect of the present disclosure.

[0015] FIG. 8 illustrates a surgical data network comprising a modular communication hub configured to connect modular devices located in one or more operating theaters of a healthcare facility, or any room in a healthcare facility specially equipped for surgical operations, to the cloud, in accordance with at least one aspect of the present disclosure.

[0016] FIG. 9 illustrates a computer-implemented interactive surgical system, in accordance with at least one aspect of the present disclosure.

[0017] FIG. 10 illustrates a surgical hub comprising a plurality of modules coupled to the modular control tower, in accordance with at least one aspect of the present disclosure.

[0018] FIG. 11 illustrates one aspect of a Universal Serial Bus (USB) network hub device, in accordance with at least one aspect of the present disclosure.

[0019] FIG. 12 illustrates a logic diagram of a control system of a surgical instrument or tool, in accordance with at least one aspect of the present disclosure.

[0020] FIG. 13 illustrates a control circuit configured to control aspects of the surgical instrument or tool, in accordance with at least one aspect of the present disclosure.

[0021] FIG. 14 illustrates a combinational logic circuit configured to control aspects of the surgical instrument or tool, in accordance with at least one aspect of the present disclosure.

[0022] FIG. 15 illustrates a sequential logic circuit configured to control aspects of the surgical instrument or tool, in accordance with at least one aspect of the present disclosure.

[0023] FIG. 16 illustrates a surgical instrument or tool comprising a plurality of motors which can be activated to perform various functions, in accordance with at least one aspect of the present disclosure.

[0024] FIG. 17 is a schematic diagram of a robotic surgical instrument configured to operate a surgical tool described herein, in accordance with at least one aspect of the present disclosure.

[0025] FIG. 18 illustrates a block diagram of a surgical instrument programmed to control the distal translation of a displacement member, in accordance with at least one aspect of the present disclosure.

[0026] FIG. 19 is a schematic diagram of a surgical instrument configured to control various functions, in accordance with at least one aspect of the present disclosure.

[0027] FIG. 20 is a simplified block diagram of a generator configured to provide inductorless tuning, among other benefits, in accordance with at least one aspect of the present disclosure.

[0028] FIG. 21 illustrates an example of a generator, which is one form of the generator of FIG. 20, in accordance with at least one aspect of the present disclosure.

[0029] FIG. 22 is a schematic of a robotic surgical system, in accordance with one aspect of the present disclosure.

[0030] FIG. 23 is a schematic of a robotic surgical system, in accordance with at least one aspect of the present disclosure.

[0031] FIG. 24 is a block diagram of control components for the robotic surgical system of FIG. 23, in accordance with at least one aspect of the present disclosure.

[0032] FIG. 25A is an elevation view of an ultrasonic surgical tool positioned out of contact with tissue, in accordance with at least one aspect of the present disclosure.

[0033] FIG. 25B is an elevation view of the ultrasonic surgical tool of FIG. 25A positioned in abutting contact with tissue, in accordance with at least one aspect of the present disclosure.

[0034] FIG. 26A is an elevation view of a monopolar cautery pencil positioned out of contact with tissue, in accordance with at least one aspect of the present disclosure.

[0035] FIG. 26B is an elevation view of the monopolar cautery pencil of FIG. 26A positioned in abutting contact with tissue, in accordance with at least one aspect of the present disclosure.

[0036] FIG. 27 is a graphical display of continuity and current over time for the ultrasonic surgical tool of FIGS. 25A and 25B, in accordance with at least one aspect of the present disclosure.

[0037] FIG. 28 illustrates an end effector comprising radio frequency (RF) data sensors located on a jaw member, in accordance with at least one aspect of the present disclosure.

[0038] FIG. 29 illustrates the sensors shown in FIG. 28 mounted to or formed integrally with a flexible circuit, in accordance with at least one aspect of the present disclosure.

[0039] FIG. 30 is a flow chart depicting an automatic activation mode of a surgical instrument, in accordance with at least one aspect of the present disclosure.

[0040] FIG. 31 is a perspective view of an end effector of a bipolar radio frequency (RF) surgical tool having a smoke evacuation pump for use with a robotic surgical system,

depicting the surgical tool clamping and treating tissue, in accordance with at least one aspect of the present disclosure.

[0041] FIG. 32 is a block diagram of a surgical system comprising a robotic surgical system, a handheld surgical instrument, and a surgical hub, in accordance with at least one aspect of the present disclosure.

[0042] FIG. 33 is a perspective view of a handle portion of a handheld surgical instrument including a display and further depicting a detail view of the display depicting information from the instrument itself, in accordance with at least one aspect of the present disclosure.

[0043] FIG. 34 is a perspective view of the handle portion of the handheld surgical instrument of FIG. 33 depicting the instrument paired with a surgical hub and further including a detail view of the display depicting information from the surgical hub, in accordance with at least one aspect of the present disclosure.

[0044] FIG. 35 is a schematic of a colon resection procedure, in accordance with at least one aspect of the present disclosure.

[0045] FIG. 36 is a graphical display of force over time for the colon resection procedure displayed on the instrument display in FIG. 35, in accordance with at least one aspect of the present disclosure.

[0046] FIG. 37 is a schematic of a robotic surgical system during a surgical procedure including a plurality of hubs and interactive secondary displays, in accordance with at least one aspect of the present disclosure.

[0047] FIG. 38 is a detail view of the interactive secondary displays of FIG. 37, in accordance with at least one aspect of the present disclosure.

[0048] FIG. 39 is a block diagram of a robotic surgical system comprising more than one robotic arm, in accordance with at least one aspect of the present disclosure.

[0049] FIG. 40 is a schematic of a surgical procedure utilizing the robotic surgical system of FIG. 39, in accordance with at least one aspect of the present disclosure.

[0050] FIG. 41 shows graphical representations of forces and positional displacements experienced by the robotic arms of FIG. 39, in accordance with at least one aspect of the present disclosure.

[0051] FIG. 42 is a flow chart depicting an algorithm for controlling the position of the robotic arms of a robotic surgical system, in accordance with at least one aspect of the present disclosure.

[0052] FIG. 43 is a flow chart depicting an algorithm for controlling the forces exerted by robotic arms of a robotic surgical system, in accordance with at least one aspect of the present disclosure.

[0053] FIG. 44 is a flow chart depicting an algorithm for monitoring the position and forces exerted by robotic arms of a robotic surgical system, in accordance with at least one aspect of the present disclosure.

[0054] FIG. 45 is a block diagram of a surgical system comprising a robotic surgical system, a powered handheld surgical instrument, and a surgical hub, in accordance with at least one aspect of the present disclosure.

[0055] FIG. 46 is a perspective view of a robotic tool and a handheld surgical instrument during a surgical procedure, in accordance with at least one aspect of the present disclosure.

[0056] FIG. 47 is a schematic depicting communication links between surgical hubs and a primary server, in accordance with at least one aspect of the present disclosure.

[0057] FIG. 48 is a flow chart depicting a queue for external output of data received from the various surgical hubs of FIG. 47, in accordance with at least one aspect of the present disclosure.

[0058] FIG. 49 is a timeline depicting situational awareness of a surgical hub, in accordance with one aspect of the present disclosure.

DETAILED DESCRIPTION

[0059] Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on Mar. 28, 2018, each of which is herein incorporated by reference in its entirety:

[0060] U.S. Provisional Patent Application Ser. No. 62/649,302, titled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES;

[0061] U.S. Provisional Patent Application Ser. No. 62/649,294, titled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD;

[0062] U.S. Provisional Patent Application Ser. No. 62/649,300, titled SURGICAL HUB SITUATIONAL AWARENESS;

[0063] U.S. Provisional Patent Application Ser. No. 62/649,309, titled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER;

[0064] U.S. Provisional Patent Application Ser. No. 62/649,310, titled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS;

[0065] U.S. Provisional Patent Application Ser. No. 62/649,291, titled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT;

[0066] U.S. Provisional Patent Application Ser. No. 62/649,296, titled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES;

[0067] U.S. Provisional Patent Application Ser. No. 62/649,333, titled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER;

[0068] U.S. Provisional Patent Application Ser. No. 62/649,327, titled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES;

[0069] U.S. Provisional Patent Application Ser. No. 62/649,315, titled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK;

[0070] U.S. Provisional Patent Application Ser. No. 62/649,313, titled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES;

[0071] U.S. Provisional Patent Application Ser. No. 62/649,320, titled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;

[0072] U.S. Provisional Patent Application Ser. No. 62/649,307, titled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and

[0073] U.S. Provisional Patent Application Ser. No. 62/649,323, titled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

[0074] Applicant of the present application owns the following U.S. patent applications, filed on Mar. 29, 2018, each of which is herein incorporated by reference in its entirety:

[0075] U.S. patent application Ser. No. _____, titled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES; Attorney Docket No. END8499USNP/170766;

[0076] U.S. patent application Ser. No. _____, titled INTERACTIVE SURGICAL SYSTEMS WITH CONDITION HANDLING OF DEVICES AND DATA CAPABILITIES; Attorney Docket No. END8499USNP1/170766-1;

[0077] U.S. patent application Ser. No. _____, titled SURGICAL HUB COORDINATION OF CONTROL AND COMMUNICATION OF OPERATING ROOM DEVICES; Attorney Docket No. END8499USNP2/170766-2;

[0078] U.S. patent application Ser. No. _____, titled SPATIAL AWARENESS OF SURGICAL HUBS IN OPERATING ROOMS; Attorney Docket No. END8499USNP3/170766-3;

[0079] U.S. patent application Ser. No. _____, titled COOPERATIVE UTILIZATION OF DATA DERIVED FROM SECONDARY SOURCES BY INTELLIGENT SURGICAL HUBS; Attorney Docket No. END8499USNP4/170766-4;

[0080] U.S. patent application Ser. No. _____, titled SURGICAL HUB CONTROL ARRANGEMENTS; Attorney Docket No. END8499USNP5/170766-5;

[0081] U.S. patent application Ser. No. _____, titled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD; Attorney Docket No. END8500USNP/170767;

[0082] U.S. patent application Ser. No. _____, titled COMMUNICATION HUB AND STORAGE DEVICE FOR STORING PARAMETERS AND STATUS OF A SURGICAL DEVICE TO BE SHARED WITH CLOUD BASED ANALYTICS SYSTEMS; Attorney Docket No. END8500USNP1/170767-1;

[0083] U.S. patent application Ser. No. _____, titled SELF DESCRIBING DATA PACKETS GENERATED AT AN ISSUING INSTRUMENT; Attorney Docket No. END8500USNP2/170767-2;

[0084] U.S. patent application Ser. No. _____, titled DATA PAIRING TO INTERCONNECT A DEVICE MEASURED PARAMETER WITH AN OUTCOME; Attorney Docket No. END8500USNP3/170767-3;

[0085] U.S. patent application Ser. No. _____, titled SURGICAL HUB SITUATIONAL AWARENESS; Attorney Docket No. END8501USNP/170768;

[0086] U.S. patent application Ser. No. _____, titled SURGICAL SYSTEM DISTRIBUTED PROCESSING; Attorney Docket No. END8501USNP1/170768-1;

[0087] U.S. patent application Ser. No. _____, titled AGGREGATION AND REPORTING OF SURGICAL HUB DATA; Attorney Docket No. END8501USNP2/170768-2;

[0088] U.S. patent application Ser. No. _____, titled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER; Attorney Docket No. END8502USNP/170769;

- [0089] U.S. patent application Ser. No. _____, titled DISPLAY OF ALIGNMENT OF STAPLE CARTRIDGE TO PRIOR LINEAR STAPLE LINE; Attorney Docket No. END8502USNP1/170769-1;
- [0090] U.S. patent application Ser. No. _____, titled STERILE FIELD INTERACTIVE CONTROL DISPLAYS; Attorney Docket No. END8502USNP2/170769-2;
- [0091] U.S. patent application Ser. No. _____, titled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS; Attorney Docket No. END8503USNP/170770;
- [0092] U.S. patent application Ser. No. _____, titled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT; Attorney Docket No. END8504USNP/170771;
- [0093] U.S. patent application Ser. No. _____, titled CHARACTERIZATION OF TISSUE IRREGULARITIES THROUGH THE USE OF MONO-CHROMATIC LIGHT REFRACTIVITY; Attorney Docket No. END8504USNP1/170771-1; and
- [0094] U.S. patent application Ser. No. _____, titled DUAL CMOS ARRAY IMAGING; Attorney Docket No. END8504USNP2/170771-2.
- [0095] Applicant of the present application owns the following U.S. patent applications, filed on Mar. 29, 2018, each of which is herein incorporated by reference in its entirety:
- [0096] U.S. patent application Ser. No. _____, titled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES; Attorney Docket No. END8506USNP/170773;
- [0097] U.S. patent application Ser. No. _____, titled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL HUBS; Attorney Docket No. END8506USNP1/170773-1;
- [0098] U.S. patent application Ser. No. _____, titled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER; Attorney Docket No. END8507USNP/170774;
- [0099] U.S. patent application Ser. No. _____, titled CLOUD-BASED MEDICAL ANALYTICS FOR LINKING OF LOCAL USAGE TRENDS WITH THE RESOURCE ACQUISITION BEHAVIORS OF LARGER DATA SET; Attorney Docket No. END8507USNP1/170774-1;
- [0100] U.S. patent application Ser. No. _____, titled CLOUD-BASED MEDICAL ANALYTICS FOR MEDICAL FACILITY SEGMENTED INDIVIDUALIZATION OF INSTRUMENT FUNCTION; Attorney Docket No. END8507USNP2/170774-2;
- [0101] U.S. patent application Ser. No. _____, titled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES; Attorney Docket No. END8508USNP/170775;
- [0102] U.S. patent application Ser. No. _____, titled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK; Attorney Docket No. END8509USNP/170776; and
- [0103] U.S. patent application Ser. No. _____, titled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES; Attorney Docket No. END8510USNP/170777.
- [0104] Applicant of the present application owns the following U.S. patent applications, filed on Mar. 29, 2018, each of which is herein incorporated by reference in its entirety:
- [0105] U.S. patent application Ser. No. _____, titled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; Attorney Docket No. END8511USNP/170778;
- [0106] U.S. patent application Ser. No. _____, titled COMMUNICATION ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; Attorney Docket No. END8511USNP1/170778-1;
- [0107] U.S. patent application Ser. No. _____, titled CONTROLS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; Attorney Docket No. END8511USNP2/170778-2;
- [0108] U.S. patent application Ser. No. _____, titled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; Attorney Docket No. END8512USNP/170779;
- [0109] U.S. patent application Ser. No. _____, titled CONTROLLERS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; Attorney Docket No. END8512USNP1/170779-1;
- [0110] U.S. patent application Ser. No. _____, titled COOPERATIVE SURGICAL ACTIONS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; Attorney Docket No. END8512USNP2/170779-2; and
- [0111] U.S. patent application Ser. No. _____, titled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; Attorney Docket No. END8513USNP/170780.
- [0112] Before explaining various aspects of surgical devices and generators in detail, it should be noted that the illustrative examples are not limited in application or use to the details of construction and arrangement of parts illustrated in the accompanying drawings and description. The illustrative examples may be implemented or incorporated in other aspects, variations and modifications, and may be practiced or carried out in various ways. Further, unless otherwise indicated, the terms and expressions employed herein have been chosen for the purpose of describing the illustrative examples for the convenience of the reader and are not for the purpose of limitation thereof. Also, it will be appreciated that one or more of the following-described aspects, expressions of aspects, and/or examples, can be combined with any one or more of the other following-described aspects, expressions of aspects and/or examples.
- [0113] Referring to FIG. 1, a computer-implemented interactive surgical system 100 includes one or more surgical systems 102 and a cloud-based system (e.g., the cloud 104 that may include a remote server 113 coupled to a storage device 105). Each surgical system 102 includes at least one surgical hub 106 in communication with the cloud 104 that may include a remote server 113. In one example, as illustrated in FIG. 1, the surgical system 102 includes a visualization system 108, a robotic system 110, and a handheld intelligent surgical instrument 112, which are configured to communicate with one another and/or the hub 106. In some aspects, a surgical system 102 may include an M number of hubs 106, an N number of visualization

systems **108**, an O number of robotic systems **110**, and a P number of handheld intelligent surgical instruments **112**, where M, N, O, and P are integers greater than or equal to one.

[0114] FIG. 3 depicts an example of a surgical system **102** being used to perform a surgical procedure on a patient who is lying down on an operating table **114** in a surgical operating room **116**. A robotic system **110** is used in the surgical procedure as a part of the surgical system **102**. The robotic system **110** includes a surgeon's console **118**, a patient side cart **120** (surgical robot), and a surgical robotic hub **122**. The patient side cart **120** can manipulate at least one removably coupled surgical tool **117** through a minimally invasive incision in the body of the patient while the surgeon views the surgical site through the surgeon's console **118**. An image of the surgical site can be obtained by a medical imaging device **124**, which can be manipulated by the patient side cart **120** to orient the imaging device **124**. The robotic hub **122** can be used to process the images of the surgical site for subsequent display to the surgeon through the surgeon's console **118**.

[0115] Other types of robotic systems can be readily adapted for use with the surgical system **102**. Various examples of robotic systems and surgical tools that are suitable for use with the present disclosure are described in U.S. Provisional Patent Application Ser. No. 62/611,339, titled ROBOT ASSISTED SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety.

[0116] Various examples of cloud-based analytics that are performed by the cloud **104**, and are suitable for use with the present disclosure, are described in U.S. Provisional Patent Application Ser. No. 62/611,340, titled CLOUD-BASED MEDICAL ANALYTICS, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety.

[0117] In various aspects, the imaging device **124** includes at least one image sensor and one or more optical components. Suitable image sensors include, but are not limited to, Charge-Coupled Device (CCD) sensors and Complementary Metal-Oxide Semiconductor (CMOS) sensors.

[0118] The optical components of the imaging device **124** may include one or more illumination sources and/or one or more lenses. The one or more illumination sources may be directed to illuminate portions of the surgical field. The one or more image sensors may receive light reflected or refracted from the surgical field, including light reflected or refracted from tissue and/or surgical instruments.

[0119] The one or more illumination sources may be configured to radiate electromagnetic energy in the visible spectrum as well as the invisible spectrum. The visible spectrum, sometimes referred to as the optical spectrum or luminous spectrum, is that portion of the electromagnetic spectrum that is visible to (i.e., can be detected by) the human eye and may be referred to as visible light or simply light. A typical human eye will respond to wavelengths in air that are from about 380 nm to about 750 nm.

[0120] The invisible spectrum (i.e., the non-luminous spectrum) is that portion of the electromagnetic spectrum that lies below and above the visible spectrum (i.e., wavelengths below about 380 nm and above about 750 nm). The invisible spectrum is not detectable by the human eye. Wavelengths greater than about 750 nm are longer than the red visible spectrum, and they become invisible infrared

(IR), microwave, and radio electromagnetic radiation. Wavelengths less than about 380 nm are shorter than the violet spectrum, and they become invisible ultraviolet, x-ray, and gamma ray electromagnetic radiation.

[0121] In various aspects, the imaging device **124** is configured for use in a minimally invasive procedure. Examples of imaging devices suitable for use with the present disclosure include, but not limited to, an arthroscope, angioscope, bronchoscope, choledochoscope, colonoscope, cytoscope, duodenoscope, enteroscope, esophagogastro-duodenoscope (gastroscope), endoscope, laryngoscope, nasopharyngo-neproscope, sigmoidoscope, thoracoscope, and ureterscope.

[0122] In one aspect, the imaging device employs multi-spectrum monitoring to discriminate topography and underlying structures. A multi-spectral image is one that captures image data within specific wavelength ranges across the electromagnetic spectrum. The wavelengths may be separated by filters or by the use of instruments that are sensitive to particular wavelengths, including light from frequencies beyond the visible light range, e.g., IR and ultraviolet. Spectral imaging can allow extraction of additional information the human eye fails to capture with its receptors for red, green, and blue. The use of multi-spectral imaging is described in greater detail under the heading "Advanced Imaging Acquisition Module" in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety. Multi-spectrum monitoring can be a useful tool in relocating a surgical field after a surgical task is completed to perform one or more of the previously described tests on the treated tissue.

[0123] It is axiomatic that strict sterilization of the operating room and surgical equipment is required during any surgery. The strict hygiene and sterilization conditions required in a "surgical theater," i.e., an operating or treatment room, necessitate the highest possible sterility of all medical devices and equipment. Part of that sterilization process is the need to sterilize anything that comes in contact with the patient or penetrates the sterile field, including the imaging device **124** and its attachments and components. It will be appreciated that the sterile field may be considered a specified area, such as within a tray or on a sterile towel, that is considered free of microorganisms, or the sterile field may be considered an area, immediately around a patient, who has been prepared for a surgical procedure. The sterile field may include the scrubbed team members, who are properly attired, and all furniture and fixtures in the area.

[0124] In various aspects, the visualization system **108** includes one or more imaging sensors, one or more image processing units, one or more storage arrays, and one or more displays that are strategically arranged with respect to the sterile field, as illustrated in FIG. 2. In one aspect, the visualization system **108** includes an interface for HL7, PACS, and EMR. Various components of the visualization system **108** are described under the heading "Advanced Imaging Acquisition Module" in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety.

[0125] As illustrated in FIG. 2, a primary display **119** is positioned in the sterile field to be visible to an operator at

the operating table **114**. In addition, a visualization tower **111** is positioned outside the sterile field. The visualization tower **111** includes a first non-sterile display **107** and a second non-sterile display **109**, which face away from each other. The visualization system **108**, guided by the hub **106**, is configured to utilize the displays **107**, **109**, and **119** to coordinate information flow to operators inside and outside the sterile field. For example, the hub **106** may cause the visualization system **108** to display a snap-shot of a surgical site, as recorded by an imaging device **124**, on a non-sterile display **107** or **109**, while maintaining a live feed of the surgical site on the primary display **119**. The snap-shot on the non-sterile display **107** or **109** can permit a non-sterile operator to perform a diagnostic step relevant to the surgical procedure, for example.

[0126] In one aspect, the hub **106** is also configured to route a diagnostic input or feedback entered by a non-sterile operator at the visualization tower **111** to the primary display **119** within the sterile field, where it can be viewed by a sterile operator at the operating table. In one example, the input can be in the form of a modification to the snap-shot displayed on the non-sterile display **107** or **109**, which can be routed to the primary display **119** by the hub **106**.

[0127] Referring to FIG. 2, a surgical instrument **112** is being used in the surgical procedure as part of the surgical system **102**. The hub **106** is also configured to coordinate information flow to a display of the surgical instrument **112**. For example, in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety. A diagnostic input or feedback entered by a non-sterile operator at the visualization tower **111** can be routed by the hub **106** to the surgical instrument display **115** within the sterile field, where it can be viewed by the operator of the surgical instrument **112**. Example surgical instruments that are suitable for use with the surgical system **102** are described under the heading "Surgical Instrument Hardware" and in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety, for example.

[0128] Referring now to FIG. 3, a hub **106** is depicted in communication with a visualization system **108**, a robotic system **110**, and a handheld intelligent surgical instrument **112**. The hub **106** includes a hub display **135**, an imaging module **138**, a generator module **140**, a communication module **130**, a processor module **132**, and a storage array **134**. In certain aspects, as illustrated in FIG. 3, the hub **106** further includes a smoke evacuation module **126** and/or a suction/irrigation module **128**.

[0129] During a surgical procedure, energy application to tissue, for sealing and/or cutting, is generally associated with smoke evacuation, suction of excess fluid, and/or irrigation of the tissue. Fluid, power, and/or data lines from different sources are often entangled during the surgical procedure. Valuable time can be lost addressing this issue during a surgical procedure. Detangling the lines may necessitate disconnecting the lines from their respective modules, which may require resetting the modules. The hub modular enclosure **136** offers a unified environment for managing the power, data, and fluid lines, which reduces the frequency of entanglement between such lines.

[0130] Aspects of the present disclosure present a surgical hub for use in a surgical procedure that involves energy application to tissue at a surgical site. The surgical hub includes a hub enclosure and a combo generator module slidably receivable in a docking station of the hub enclosure. The docking station includes data and power contacts. The combo generator module includes two or more of an ultrasonic energy generator component, a bipolar RF energy generator component, and a monopolar RF energy generator component that are housed in a single unit. In one aspect, the combo generator module also includes a smoke evacuation component, at least one energy delivery cable for connecting the combo generator module to a surgical instrument, at least one smoke evacuation component configured to evacuate smoke, fluid, and/or particulates generated by the application of therapeutic energy to the tissue, and a fluid line extending from the remote surgical site to the smoke evacuation component.

[0131] In one aspect, the fluid line is a first fluid line and a second fluid line extends from the remote surgical site to a suction and irrigation module slidably received in the hub enclosure. In one aspect, the hub enclosure comprises a fluid interface.

[0132] Certain surgical procedures may require the application of more than one energy type to the tissue. One energy type may be more beneficial for cutting the tissue, while another different energy type may be more beneficial for sealing the tissue. For example, a bipolar generator can be used to seal the tissue while an ultrasonic generator can be used to cut the sealed tissue. Aspects of the present disclosure present a solution where a hub modular enclosure **136** is configured to accommodate different generators, and facilitate an interactive communication therebetween. One of the advantages of the hub modular enclosure **136** is enabling the quick removal and/or replacement of various modules.

[0133] Aspects of the present disclosure present a modular surgical enclosure for use in a surgical procedure that involves energy application to tissue. The modular surgical enclosure includes a first energy-generator module, configured to generate a first energy for application to the tissue, and a first docking station comprising a first docking port that includes first data and power contacts, wherein the first energy-generator module is slidably movable into an electrical engagement with the power and data contacts and wherein the first energy-generator module is slidably movable out of the electrical engagement with the first power and data contacts.

[0134] Further to the above, the modular surgical enclosure also includes a second energy-generator module configured to generate a second energy, different than the first energy, for application to the tissue, and a second docking station comprising a second docking port that includes second data and power contacts, wherein the second energy-generator module is slidably movable into an electrical engagement with the power and data contacts, and wherein the second energy-generator module is slidably movable out of the electrical engagement with the second power and data contacts.

[0135] In addition, the modular surgical enclosure also includes a communication bus between the first docking port and the second docking port, configured to facilitate communication between the first energy-generator module and the second energy-generator module.

[0136] Referring to FIGS. 3-7, aspects of the present disclosure are presented for a hub modular enclosure 136 that allows the modular integration of a generator module 140, a smoke evacuation module 126, and a suction/irrigation module 128. The hub modular enclosure 136 further facilitates interactive communication between the modules 140, 126, 128. As illustrated in FIG. 5, the generator module 140 can be a generator module with integrated monopolar, bipolar, and ultrasonic components supported in a single housing unit 139 slidably insertable into the hub modular enclosure 136. As illustrated in FIG. 5, the generator module 140 can be configured to connect to a monopolar device 146, a bipolar device 147, and an ultrasonic device 148. Alternatively, the generator module 140 may comprise a series of monopolar, bipolar, and/or ultrasonic generator modules that interact through the hub modular enclosure 136. The hub modular enclosure 136 can be configured to facilitate the insertion of multiple generators and interactive communication between the generators docked into the hub modular enclosure 136 so that the generators would act as a single generator.

[0137] In one aspect, the hub modular enclosure 136 comprises a modular power and communication backplane 149 with external and wireless communication headers to enable the removable attachment of the modules 140, 126, 128 and interactive communication therebetween.

[0138] In one aspect, the hub modular enclosure 136 includes docking stations, or drawers, 151, herein also referred to as drawers, which are configured to slidably receive the modules 140, 126, 128. FIG. 4 illustrates a partial perspective view of a surgical hub enclosure 136, and a combo generator module 145 slidably receivable in a docking station 151 of the surgical hub enclosure 136. A docking port 152 with power and data contacts on a rear side of the combo generator module 145 is configured to engage a corresponding docking port 150 with power and data contacts of a corresponding docking station 151 of the hub modular enclosure 136 as the combo generator module 145 is slid into position within the corresponding docking station 151 of the hub module enclosure 136. In one aspect, the combo generator module 145 includes a bipolar, ultrasonic, and monopolar module and a smoke evacuation module integrated together into a single housing unit 139, as illustrated in FIG. 5.

[0139] In various aspects, the smoke evacuation module 126 includes a fluid line 154 that conveys captured/collected smoke and/or fluid away from a surgical site and to, for example, the smoke evacuation module 126. Vacuum suction originating from the smoke evacuation module 126 can draw the smoke into an opening of a utility conduit at the surgical site. The utility conduit, coupled to the fluid line, can be in the form of a flexible tube terminating at the smoke evacuation module 126. The utility conduit and the fluid line define a fluid path extending toward the smoke evacuation module 126 that is received in the hub enclosure 136.

[0140] In various aspects, the suction/irrigation module 128 is coupled to a surgical tool comprising an aspiration fluid line and a suction fluid line. In one example, the aspiration and suction fluid lines are in the form of flexible tubes extending from the surgical site toward the suction/irrigation module 128. One or more drive systems can be configured to cause irrigation and aspiration of fluids to and from the surgical site.

[0141] In one aspect, the surgical tool includes a shaft having an end effector at a distal end thereof and at least one energy treatment associated with the end effector, an aspiration tube, and an irrigation tube. The aspiration tube can have an inlet port at a distal end thereof and the aspiration tube extends through the shaft. Similarly, an irrigation tube can extend through the shaft and can have an inlet port in proximity to the energy deliver implement. The energy deliver implement is configured to deliver ultrasonic and/or RF energy to the surgical site and is coupled to the generator module 140 by a cable extending initially through the shaft.

[0142] The irrigation tube can be in fluid communication with a fluid source, and the aspiration tube can be in fluid communication with a vacuum source. The fluid source and/or the vacuum source can be housed in the suction/irrigation module 128. In one example, the fluid source and/or the vacuum source can be housed in the hub enclosure 136 separately from the suction/irrigation module 128. In such example, a fluid interface can be configured to connect the suction/irrigation module 128 to the fluid source and/or the vacuum source.

[0143] In one aspect, the modules 140, 126, 128 and/or their corresponding docking stations on the hub modular enclosure 136 may include alignment features that are configured to align the docking ports of the modules into engagement with their counterparts in the docking stations of the hub modular enclosure 136. For example, as illustrated in FIG. 4, the combo generator module 145 includes side brackets 155 that are configured to slidably engage with corresponding brackets 156 of the corresponding docking station 151 of the hub modular enclosure 136. The brackets cooperate to guide the docking port contacts of the combo generator module 145 into an electrical engagement with the docking port contacts of the hub modular enclosure 136.

[0144] In some aspects, the drawers 151 of the hub modular enclosure 136 are the same, or substantially the same size, and the modules are adjusted in size to be received in the drawers 151. For example, the side brackets 155 and/or 156 can be larger or smaller depending on the size of the module. In other aspects, the drawers 151 are different in size and are each designed to accommodate a particular module.

[0145] Furthermore, the contacts of a particular module can be keyed for engagement with the contacts of a particular drawer to avoid inserting a module into a drawer with mismatching contacts.

[0146] As illustrated in FIG. 4, the docking port 150 of one drawer 151 can be coupled to the docking port 150 of another drawer 151 through a communications link 157 to facilitate an interactive communication between the modules housed in the hub modular enclosure 136. The docking ports 150 of the hub modular enclosure 136 may alternatively, or additionally, facilitate a wireless interactive communication between the modules housed in the hub modular enclosure 136. Any suitable wireless communication can be employed, such as for example Air Titan-Bluetooth.

[0147] FIG. 6 illustrates individual power bus attachments for a plurality of lateral docking ports of a lateral modular housing 160 configured to receive a plurality of modules of a surgical hub 206. The lateral modular housing 160 is configured to laterally receive and interconnect the modules 161. The modules 161 are slidably inserted into docking stations 162 of lateral modular housing 160, which includes a backplane for interconnecting the modules 161. As illus-

trated in FIG. 6, the modules 161 are arranged laterally in the lateral modular housing 160. Alternatively, the modules 161 may be arranged vertically in a lateral modular housing.

[0148] FIG. 7 illustrates a vertical modular housing 164 configured to receive a plurality of modules 165 of the surgical hub 106. The modules 165 are slidably inserted into docking stations, or drawers, 167 of vertical modular housing 164, which includes a backplane for interconnecting the modules 165. Although the drawers 167 of the vertical modular housing 164 are arranged vertically, in certain instances, a vertical modular housing 164 may include drawers that are arranged laterally. Furthermore, the modules 165 may interact with one another through the docking ports of the vertical modular housing 164. In the example of FIG. 7, a display 177 is provided for displaying data relevant to the operation of the modules 165. In addition, the vertical modular housing 164 includes a master module 178 housing a plurality of sub-modules that are slidably received in the master module 178.

[0149] In various aspects, the imaging module 138 comprises an integrated video processor and a modular light source and is adapted for use with various imaging devices. In one aspect, the imaging device is comprised of a modular housing that can be assembled with a light source module and a camera module. The housing can be a disposable housing. In at least one example, the disposable housing is removably coupled to a reusable controller, a light source module, and a camera module. The light source module and/or the camera module can be selectively chosen depending on the type of surgical procedure. In one aspect, the camera module comprises a CCD sensor. In another aspect, the camera module comprises a CMOS sensor. In another aspect, the camera module is configured for scanned beam imaging. Likewise, the light source module can be configured to deliver a white light or a different light, depending on the surgical procedure.

[0150] During a surgical procedure, removing a surgical device from the surgical field and replacing it with another surgical device that includes a different camera or a different light source can be inefficient. Temporarily losing sight of the surgical field may lead to undesirable consequences. The module imaging device of the present disclosure is configured to permit the replacement of a light source module or a camera module midstream during a surgical procedure, without having to remove the imaging device from the surgical field.

[0151] In one aspect, the imaging device comprises a tubular housing that includes a plurality of channels. A first channel is configured to slidably receive the camera module, which can be configured for a snap-fit engagement with the first channel. A second channel is configured to slidably receive the light source module, which can be configured for a snap-fit engagement with the second channel. In another example, the camera module and/or the light source module can be rotated into a final position within their respective channels. A threaded engagement can be employed in lieu of the snap-fit engagement.

[0152] In various examples, multiple imaging devices are placed at different positions in the surgical field to provide multiple views. The imaging module 138 can be configured to switch between the imaging devices to provide an optimal view. In various aspects, the imaging module 138 can be configured to integrate the images from the different imaging device.

[0153] Various image processors and imaging devices suitable for use with the present disclosure are described in U.S. Pat. No. 7,995,045, titled COMBINED SBI AND CONVENTIONAL IMAGE PROCESSOR, which issued on Aug. 9, 2011, which is herein incorporated by reference in its entirety. In addition, U.S. Pat. No. 7,982,776, titled SBI MOTION ARTIFACT REMOVAL APPARATUS AND METHOD, which issued on Jul. 19, 2011, which is herein incorporated by reference in its entirety, describes various systems for removing motion artifacts from image data. Such systems can be integrated with the imaging module 138. Furthermore, U.S. Patent Application Publication No. 2011/0306840, titled CONTROLLABLE MAGNETIC SOURCE TO FIXTURE INTRACORPOREAL APPARATUS, which published on Dec. 15, 2011, and U.S. Patent Application Publication No. 2014/0243597, titled SYSTEM FOR PERFORMING A MINIMALLY INVASIVE SURGICAL PROCEDURE, which published on Aug. 28, 2014, each of which is herein incorporated by reference in its entirety.

[0154] FIG. 8 illustrates a surgical data network 201 comprising a modular communication hub 203 configured to connect modular devices located in one or more operating theaters of a healthcare facility, or any room in a healthcare facility specially equipped for surgical operations, to a cloud-based system (e.g., the cloud 204 that may include a remote server 213 coupled to a storage device 205). In one aspect, the modular communication hub 203 comprises a network hub 207 and/or a network switch 209 in communication with a network router. The modular communication hub 203 also can be coupled to a local computer system 210 to provide local computer processing and data manipulation. The surgical data network 201 may be configured as passive, intelligent, or switching. A passive surgical data network serves as a conduit for the data, enabling it to go from one device (or segment) to another and to the cloud computing resources. An intelligent surgical data network includes additional features to enable the traffic passing through the surgical data network to be monitored and to configure each port in the network hub 207 or network switch 209. An intelligent surgical data network may be referred to as a manageable hub or switch. A switching hub reads the destination address of each packet and then forwards the packet to the correct port.

[0155] Modular devices 1a-1n located in the operating theater may be coupled to the modular communication hub 203. The network hub 207 and/or the network switch 209 may be coupled to a network router 211 to connect the devices 1a-1n to the cloud 204 or the local computer system 210. Data associated with the devices 1a-1n may be transferred to cloud-based computers via the router for remote data processing and manipulation. Data associated with the devices 1a-1n may also be transferred to the local computer system 210 for local data processing and manipulation. Modular devices 2a-2m located in the same operating theater also may be coupled to a network switch 209. The network switch 209 may be coupled to the network hub 207 and/or the network router 211 to connect to the devices 2a-2m to the cloud 204. Data associated with the devices 2a-2m may be transferred to the cloud 204 via the network router 211 for data processing and manipulation. Data associated with the devices 2a-2m may also be transferred to the local computer system 210 for local data processing and manipulation.

[0156] It will be appreciated that the surgical data network 201 may be expanded by interconnecting multiple network hubs 207 and/or multiple network switches 209 with multiple network routers 211. The modular communication hub 203 may be contained in a modular control tower configured to receive multiple devices 1a-1n/2a-2m. The local computer system 210 also may be contained in a modular control tower. The modular communication hub 203 is connected to a display 212 to display images obtained by some of the devices 1a-1n/2a-2m, for example during surgical procedures. In various aspects, the devices 1a-1n/2a-2m may include, for example, various modules such as an imaging module 138 coupled to an endoscope, a generator module 140 coupled to an energy-based surgical device, a smoke evacuation module 126, a suction/irrigation module 128, a communication module 130, a processor module 132, a storage array 134, a surgical device coupled to a display, and/or a non-contact sensor module, among other modular devices that may be connected to the modular communication hub 203 of the surgical data network 201.

[0157] In one aspect, the surgical data network 201 may comprise a combination of network hub(s), network switch(es), and network router(s) connecting the devices 1a-1n/2a-2m to the cloud. Any one of or all of the devices 1a-1n/2a-2m coupled to the network hub or network switch may collect data in real time and transfer the data to cloud computers for data processing and manipulation. It will be appreciated that cloud computing relies on sharing computing resources rather than having local servers or personal devices to handle software applications. The word “cloud” may be used as a metaphor for “the Internet,” although the term is not limited as such. Accordingly, the term “cloud computing” may be used herein to refer to “a type of Internet-based computing,” where different services—such as servers, storage, and applications—are delivered to the modular communication hub 203 and/or computer system 210 located in the surgical theater (e.g., a fixed, mobile, temporary, or field operating room or space) and to devices connected to the modular communication hub 203 and/or computer system 210 through the Internet. The cloud infrastructure may be maintained by a cloud service provider. In this context, the cloud service provider may be the entity that coordinates the usage and control of the devices 1a-1n/2a-2m located in one or more operating theaters. The cloud computing services can perform a large number of calculations based on the data gathered by smart surgical instruments, robots, and other computerized devices located in the operating theater. The hub hardware enables multiple devices or connections to be connected to a computer that communicates with the cloud computing resources and storage.

[0158] Applying cloud computer data processing techniques on the data collected by the devices 1a-1n/2a-2m, the surgical data network provides improved surgical outcomes, reduced costs, and improved patient satisfaction. At least some of the devices 1a-1n/2a-2m may be employed to view tissue states to assess leaks or perfusion of sealed tissue after a tissue sealing and cutting procedure. At least some of the devices 1a-1n/2a-2m may be employed to identify pathology, such as the effects of diseases, using the cloud-based computing to examine data including images of samples of body tissue for diagnostic purposes. This includes localization and margin confirmation of tissue and phenotypes. At least some of the devices 1a-1n/2a-2m may be employed to

identify anatomical structures of the body using a variety of sensors integrated with imaging devices and techniques such as overlaying images captured by multiple imaging devices. The data gathered by the devices 1a-1n/2a-2m, including image data, may be transferred to the cloud 204 or the local computer system 210 or both for data processing and manipulation including image processing and manipulation. The data may be analyzed to improve surgical procedure outcomes by determining if further treatment, such as the application of endoscopic intervention, emerging technologies, a targeted radiation, targeted intervention, and precise robotics to tissue-specific sites and conditions, may be pursued. Such data analysis may further employ outcome analytics processing, and using standardized approaches may provide beneficial feedback to either confirm surgical treatments and the behavior of the surgeon or suggest modifications to surgical treatments and the behavior of the surgeon.

[0159] In one implementation, the operating theater devices 1a-1n may be connected to the modular communication hub 203 over a wired channel or a wireless channel depending on the configuration of the devices 1a-1n to a network hub. The network hub 207 may be implemented, in one aspect, as a local network broadcast device that works on the physical layer of the Open System Interconnection (OSI) model. The network hub provides connectivity to the devices 1a-1n located in the same operating theater network. The network hub 207 collects data in the form of packets and sends them to the router in half duplex mode. The network hub 207 does not store any media access control/internet protocol (MAC/IP) to transfer the device data. Only one of the devices 1a-1n can send data at a time through the network hub 207. The network hub 207 has no routing tables or intelligence regarding where to send information and broadcasts all network data across each connection and to a remote server 213 (FIG. 9) over the cloud 204. The network hub 207 can detect basic network errors such as collisions, but having all information broadcast to multiple ports can be a security risk and cause bottlenecks.

[0160] In another implementation, the operating theater devices 2a-2m may be connected to a network switch 209 over a wired channel or a wireless channel. The network switch 209 works in the data link layer of the OSI model. The network switch 209 is a multicast device for connecting the devices 2a-2m located in the same operating theater to the network. The network switch 209 sends data in the form of frames to the network router 211 and works in full duplex mode. Multiple devices 2a-2m can send data at the same time through the network switch 209. The network switch 209 stores and uses MAC addresses of the devices 2a-2m to transfer data.

[0161] The network hub 207 and/or the network switch 209 are coupled to the network router 211 for connection to the cloud 204. The network router 211 works in the network layer of the OSI model. The network router 211 creates a route for transmitting data packets received from the network hub 207 and/or network switch 211 to cloud-based computer resources for further processing and manipulation of the data collected by any one of or all the devices 1a-1n/2a-2m. The network router 211 may be employed to connect two or more different networks located in different locations, such as, for example, different operating theaters of the same healthcare facility or different networks located in different operating theaters of different healthcare facilities.

ties. The network router **211** sends data in the form of packets to the cloud **204** and works in full duplex mode. Multiple devices can send data at the same time. The network router **211** uses IP addresses to transfer data.

[0162] In one example, the network hub **207** may be implemented as a USB hub, which allows multiple USB devices to be connected to a host computer. The USB hub may expand a single USB port into several tiers so that there are more ports available to connect devices to the host system computer. The network hub **207** may include wired or wireless capabilities to receive information over a wired channel or a wireless channel. In one aspect, a wireless USB short-range, high-bandwidth wireless radio communication protocol may be employed for communication between the devices **1a-1n** and devices **2a-2m** located in the operating theater.

[0163] In other examples, the operating theater devices **1a-1n/2a-2m** may communicate to the modular communication hub **203** via Bluetooth wireless technology standard for exchanging data over short distances (using short-wavelength UHF radio waves in the ISM band from 2.4 to 2.485 GHz) from fixed and mobile devices and building personal area networks (PANs). In other aspects, the operating theater devices **1a-1n/2a-2m** may communicate to the modular communication hub **203** via a number of wireless or wired communication standards or protocols, including but not limited to Wi-Fi (IEEE 802.11 family), WiMAX (IEEE 802.16 family), IEEE 802.20, long-term evolution (LTE), and Ev-DO, HSPA+, HSDPA+, HSUPA+, EDGE, GSM, GPRS, CDMA, TDMA, DECT, and Ethernet derivatives thereof, as well as any other wireless and wired protocols that are designated as 3G, 4G, 5G, and beyond. The computing module may include a plurality of communication modules. For instance, a first communication module may be dedicated to shorter-range wireless communications such as Wi-Fi and Bluetooth, and a second communication module may be dedicated to longer-range wireless communications such as GPS, EDGE, GPRS, CDMA, WiMAX, LTE, Ev-DO, and others.

[0164] The modular communication hub **203** may serve as a central connection for one or all of the operating theater devices **1a-1n/2a-2m** and handles a data type known as frames. Frames carry the data generated by the devices **1a-1n/2a-2m**. When a frame is received by the modular communication hub **203**, it is amplified and transmitted to the network router **211**, which transfers the data to the cloud computing resources by using a number of wireless or wired communication standards or protocols, as described herein.

[0165] The modular communication hub **203** can be used as a standalone device or be connected to compatible network hubs and network switches to form a larger network. The modular communication hub **203** is generally easy to install, configure, and maintain, making it a good option for networking the operating theater devices **1a-1n/2a-2m**.

[0166] FIG. 9 illustrates a computer-implemented interactive surgical system **200**. The computer-implemented interactive surgical system **200** is similar in many respects to the computer-implemented interactive surgical system **100**. For example, the computer-implemented interactive surgical system **200** includes one or more surgical systems **202**, which are similar in many respects to the surgical systems **102**. Each surgical system **202** includes at least one surgical hub **206** in communication with a cloud **204** that may

include a remote server **213**. In one aspect, the computer-implemented interactive surgical system **200** comprises a modular control tower **236** connected to multiple operating theater devices such as, for example, intelligent surgical instruments, robots, and other computerized devices located in the operating theater. As shown in FIG. 10, the modular control tower **236** comprises a modular communication hub **203** coupled to a computer system **210**. As illustrated in the example of FIG. 9, the modular control tower **236** is coupled to an imaging module **238** that is coupled to an endoscope **239**, a generator module **240** that is coupled to an energy device **241**, a smoke evacuator module **226**, a suction/irrigation module **228**, a communication module **230**, a processor module **232**, a storage array **234**, a smart device/instrument **235** optionally coupled to a display **237**, and a non-contact sensor module **242**. The operating theater devices are coupled to cloud computing resources and data storage via the modular control tower **236**. A robot hub **222** also may be connected to the modular control tower **236** and to the cloud computing resources. The devices/instruments **235**, visualization systems **208**, among others, may be coupled to the modular control tower **236** via wired or wireless communication standards or protocols, as described herein. The modular control tower **236** may be coupled to a hub display **215** (e.g., monitor, screen) to display and overlay images received from the imaging module, device/instrument display, and/or other visualization systems **208**. The hub display also may display data received from devices connected to the modular control tower in conjunction with images and overlaid images.

[0167] FIG. 10 illustrates a surgical hub **206** comprising a plurality of modules coupled to the modular control tower **236**. The modular control tower **236** comprises a modular communication hub **203**, e.g., a network connectivity device, and a computer system **210** to provide local processing, visualization, and imaging, for example. As shown in FIG. 10, the modular communication hub **203** may be connected in a tiered configuration to expand the number of modules (e.g., devices) that may be connected to the modular communication hub **203** and transfer data associated with the modules to the computer system **210**, cloud computing resources, or both. As shown in FIG. 10, each of the network hubs/switches in the modular communication hub **203** includes three downstream ports and one upstream port. The upstream network hub/switch is connected to a processor to provide a communication connection to the cloud computing resources and a local display **217**. Communication to the cloud **204** may be made either through a wired or a wireless communication channel.

[0168] The surgical hub **206** employs a non-contact sensor module **242** to measure the dimensions of the operating theater and generate a map of the surgical theater using either ultrasonic or laser-type non-contact measurement devices. An ultrasound-based non-contact sensor module scans the operating theater by transmitting a burst of ultrasound and receiving the echo when it bounces off the perimeter walls of an operating theater as described under the heading "Surgical Hub Spatial Awareness Within an Operating Room" in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety, in which the sensor module is configured to determine the size of the operating theater and to adjust Bluetooth-pairing distance

limits. A laser-based non-contact sensor module scans the operating theater by transmitting laser light pulses, receiving laser light pulses that bounce off the perimeter walls of the operating theater, and comparing the phase of the transmitted pulse to the received pulse to determine the size of the operating theater and to adjust Bluetooth pairing distance limits, for example.

[0169] The computer system **210** comprises a processor **244** and a network interface **245**. The processor **244** is coupled to a communication module **247**, storage **248**, memory **249**, non-volatile memory **250**, and input/output interface **251** via a system bus. The system bus can be any of several types of bus structure(s) including the memory bus or memory controller, a peripheral bus or external bus, and/or a local bus using any variety of available bus architectures including, but not limited to, 9-bit bus, Industrial Standard Architecture (ISA), Micro-Charmel Architecture (MSA), Extended ISA (EISA), Intelligent Drive Electronics (IDE), VESA Local Bus (VLB), Peripheral Component Interconnect (PCI), USB, Advanced Graphics Port (AGP), Personal Computer Memory Card International Association bus (PCMCIA), Small Computer Systems Interface (SCSI), or any other proprietary bus.

[0170] The processor **244** may be any single-core or multicore processor such as those known under the trade name ARM Cortex by Texas Instruments. In one aspect, the processor may be an LM4F230H5QR ARM Cortex-M4F Processor Core, available from Texas Instruments, for example, comprising an on-chip memory of 256 KB single-cycle flash memory, or other non-volatile memory, up to 40 MHz, a prefetch buffer to improve performance above 40 MHz, a 32 KB single-cycle serial random access memory (SRAM), an internal read-only memory (ROM) loaded with StellarisWare® software, a 2 KB electrically erasable programmable read-only memory (EEPROM), and/or one or more pulse width modulation (PWM) modules, one or more quadrature encoder inputs (QEI) analogs, one or more 12-bit analog-to-digital converters (ADCs) with 12 analog input channels, details of which are available for the product datasheet.

[0171] In one aspect, the processor **244** may comprise a safety controller comprising two controller-based families such as TMS570 and RM4x, known under the trade name Hercules ARM Cortex R4, also by Texas Instruments. The safety controller may be configured specifically for IEC 61508 and ISO 26262 safety critical applications, among others, to provide advanced integrated safety features while delivering scalable performance, connectivity, and memory options.

[0172] The system memory includes volatile memory and non-volatile memory. The basic input/output system (BIOS), containing the basic routines to transfer information between elements within the computer system, such as during start-up, is stored in non-volatile memory. For example, the non-volatile memory can include ROM, programmable ROM (PROM), electrically programmable ROM (EPROM), EEPROM, or flash memory. Volatile memory includes random-access memory (RAM), which acts as external cache memory. Moreover, RAM is available in many forms such as SRAM, dynamic RAM (DRAM), synchronous DRAM (SDRAM), double data rate SDRAM (DDR SDRAM), enhanced SDRAM (ESDRAM), Synchlink DRAM (SLDRAM), and direct Rambus RAM (DRRAM).

[0173] The computer system **210** also includes removable/non-removable, volatile/non-volatile computer storage media, such as for example disk storage. The disk storage includes, but is not limited to, devices like a magnetic disk drive, floppy disk drive, tape drive, Jaz drive, Zip drive, LS-60 drive, flash memory card, or memory stick. In addition, the disk storage can include storage media separately or in combination with other storage media including, but not limited to, an optical disc drive such as a compact disc ROM device (CD-ROM), compact disc recordable drive (CD-R Drive), compact disc rewritable drive (CD-RW Drive), or a digital versatile disc ROM drive (DVD-ROM). To facilitate the connection of the disk storage devices to the system bus, a removable or non-removable interface may be employed.

[0174] It is to be appreciated that the computer system **210** includes software that acts as an intermediary between users and the basic computer resources described in a suitable operating environment. Such software includes an operating system. The operating system, which can be stored on the disk storage, acts to control and allocate resources of the computer system. System applications take advantage of the management of resources by the operating system through program modules and program data stored either in the system memory or on the disk storage. It is to be appreciated that various components described herein can be implemented with various operating systems or combinations of operating systems.

[0175] A user enters commands or information into the computer system **210** through input device(s) coupled to the I/O interface **251**. The input devices include, but are not limited to, a pointing device such as a mouse, trackball, stylus, touch pad, keyboard, microphone, joystick, game pad, satellite dish, scanner, TV tuner card, digital camera, digital video camera, web camera, and the like. These and other input devices connect to the processor through the system bus via interface port(s). The interface port(s) include, for example, a serial port, a parallel port, a game port, and a USB. The output device(s) use some of the same types of ports as input device(s). Thus, for example, a USB port may be used to provide input to the computer system and to output information from the computer system to an output device. An output adapter is provided to illustrate that there are some output devices like monitors, displays, speakers, and printers, among other output devices that require special adapters. The output adapters include, by way of illustration and not limitation, video and sound cards that provide a means of connection between the output device and the system bus. It should be noted that other devices and/or systems of devices, such as remote computer(s), provide both input and output capabilities.

[0176] The computer system **210** can operate in a networked environment using logical connections to one or more remote computers, such as cloud computer(s), or local computers. The remote cloud computer(s) can be a personal computer, server, router, network PC, workstation, micro-processor-based appliance, peer device, or other common network node, and the like, and typically includes many or all of the elements described relative to the computer system. For purposes of brevity, only a memory storage device is illustrated with the remote computer(s). The remote computer(s) is logically connected to the computer system through a network interface and then physically connected via a communication connection. The network interface encompasses communication networks such as

local area networks (LANs) and wide area networks (WANs). LAN technologies include Fiber Distributed Data Interface (FDDI), Copper Distributed Data Interface (CDDI), Ethernet/IEEE 802.3, Token Ring/IEEE 802.5 and the like. WAN technologies include, but are not limited to, point-to-point links, circuit-switching networks like Integrated Services Digital Networks (ISDN) and variations thereon, packet-switching networks, and Digital Subscriber Lines (DSL).

[0177] In various aspects, the computer system 210 of FIG. 10, the imaging module 238 and/or visualization system 208, and/or the processor module 232 of FIGS. 9-10, may comprise an image processor, image processing engine, media processor, or any specialized digital signal processor (DSP) used for the processing of digital images. The image processor may employ parallel computing with single instruction, multiple data (SIMD) or multiple instruction, multiple data (MIMD) technologies to increase speed and efficiency. The digital image processing engine can perform a range of tasks. The image processor may be a system on a chip with multicore processor architecture.

[0178] The communication connection(s) refers to the hardware/software employed to connect the network interface to the bus. While the communication connection is shown for illustrative clarity inside the computer system, it can also be external to the computer system 210. The hardware/software necessary for connection to the network interface includes, for illustrative purposes only, internal and external technologies such as modems, including regular telephone-grade modems, cable modems, and DSL modems, ISDN adapters, and Ethernet cards.

[0179] FIG. 11 illustrates a functional block diagram of one aspect of a USB network hub 300 device, according to one aspect of the present disclosure. In the illustrated aspect, the USB network hub device 300 employs a TUSB2036 integrated circuit hub by Texas Instruments. The USB network hub 300 is a CMOS device that provides an upstream USB transceiver port 302 and up to three downstream USB transceiver ports 304, 306, 308 in compliance with the USB 2.0 specification. The upstream USB transceiver port 302 is a differential root data port comprising a differential data minus (DM0) input paired with a differential data plus (DP0) input. The three downstream USB transceiver ports 304, 306, 308 are differential data ports where each port includes differential data plus (DP1-DP3) outputs paired with differential data minus (DM1-DM3) outputs.

[0180] The USB network hub 300 device is implemented with a digital state machine instead of a microcontroller, and no firmware programming is required. Fully compliant USB transceivers are integrated into the circuit for the upstream USB transceiver port 302 and all downstream USB transceiver ports 304, 306, 308. The downstream USB transceiver ports 304, 306, 308 support both full-speed and low-speed devices by automatically setting the slew rate according to the speed of the device attached to the ports. The USB network hub 300 device may be configured either in bus-powered or self-powered mode and includes a hub power logic 312 to manage power.

[0181] The USB network hub 300 device includes a serial interface engine 310 (SIE). The SIE 310 is the front end of the USB network hub 300 hardware and handles most of the protocol described in chapter 8 of the USB specification. The SIE 310 typically comprehends signaling up to the transaction level. The functions that it handles could include:

packet recognition, transaction sequencing, SOP, EOP, RESET, and RESUME signal detection/generation, clock/data separation, non-return-to-zero invert (NRZI) data encoding/decoding and bit-stuffing, CRC generation and checking (token and data), packet ID (PID) generation and checking/decoding, and/or serial-parallel/parallel-serial conversion. The 310 receives a clock input 314 and is coupled to a suspend/resume logic and frame timer 316 circuit and a hub repeater circuit 318 to control communication between the upstream USB transceiver port 302 and the downstream USB transceiver ports 304, 306, 308 through port logic circuits 320, 322, 324. The SIE 310 is coupled to a command decoder 326 via interface logic to control commands from a serial EEPROM via a serial EEPROM interface 330.

[0182] In various aspects, the USB network hub 300 can connect 127 functions configured in up to six logical layers (tiers) to a single computer. Further, the USB network hub 300 can connect to all peripherals using a standardized four-wire cable that provides both communication and power distribution. The power configurations are bus-powered and self-powered modes. The USB network hub 300 may be configured to support four modes of power management: a bus-powered hub, with either individual-port power management or ganged-port power management, and the self-powered hub, with either individual-port power management or ganged-port power management. In one aspect, using a USB cable, the USB network hub 300, the upstream USB transceiver port 302 is plugged into a USB host controller, and the downstream USB transceiver ports 304, 306, 308 are exposed for connecting USB compatible devices, and so forth.

Surgical Instrument Hardware

[0183] FIG. 12 illustrates a logic diagram of a control system 470 of a surgical instrument or tool in accordance with one or more aspects of the present disclosure. The system 470 comprises a control circuit. The control circuit includes a microcontroller 461 comprising a processor 462 and a memory 468. One or more of sensors 472, 474, 476, for example, provide real-time feedback to the processor 462. A motor 482, driven by a motor driver 492, operably couples a longitudinally movable displacement member to drive the I-beam knife element. A tracking system 480 is configured to determine the position of the longitudinally movable displacement member. The position information is provided to the processor 462, which can be programmed or configured to determine the position of the longitudinally movable drive member as well as the position of a firing member, firing bar, and I-beam knife element. Additional motors may be provided at the tool driver interface to control I-beam firing, closure tube travel, shaft rotation, and articulation. A display 473 displays a variety of operating conditions of the instruments and may include touch screen functionality for data input. Information displayed on the display 473 may be overlaid with images acquired via endoscopic imaging modules.

[0184] In one aspect, the microcontroller 461 may be any single-core or multicore processor such as those known under the trade name ARM Cortex by Texas Instruments. In one aspect, the main microcontroller 461 may be an LM4F230H5QR ARM Cortex-M4F Processor Core, available from Texas Instruments, for example, comprising an on-chip memory of 256 KB single-cycle flash memory, or other non-volatile memory, up to 40 MHz, a prefetch buffer

to improve performance above 40 MHz, a 32 KB single-cycle SRAM, and internal ROM loaded with StellarisWare® software, a 2 KB EEPROM, one or more PWM modules, one or more QEI analogs, and/or one or more 12-bit ADCs with 12 analog input channels, details of which are available for the product datasheet.

[0185] In one aspect, the microcontroller **461** may comprise a safety controller comprising two controller-based families such as TMS570 and RM4x, known under the trade name Hercules ARM Cortex R4, also by Texas Instruments. The safety controller may be configured specifically for IEC 61508 and ISO 26262 safety critical applications, among others, to provide advanced integrated safety features while delivering scalable performance, connectivity, and memory options.

[0186] The microcontroller **461** may be programmed to perform various functions such as precise control over the speed and position of the knife and articulation systems. In one aspect, the microcontroller **461** includes a processor **462** and a memory **468**. The electric motor **482** may be a brushed direct current (DC) motor with a gearbox and mechanical links to an articulation or knife system. In one aspect, a motor driver **492** may be an A3941 available from Allegro Microsystems, Inc. Other motor drivers may be readily substituted for use in the tracking system **480** comprising an absolute positioning system. A detailed description of an absolute positioning system is described in U.S. Patent Application Publication No. 2017/0296213, titled SYSTEMS AND METHODS FOR CONTROLLING A SURGICAL STAPLING AND CUTTING INSTRUMENT, which published on Oct. 19, 2017, which is herein incorporated by reference in its entirety.

[0187] The microcontroller **461** may be programmed to provide precise control over the speed and position of displacement members and articulation systems. The microcontroller **461** may be configured to compute a response in the software of the microcontroller **461**. The computed response is compared to a measured response of the actual system to obtain an “observed” response, which is used for actual feedback decisions. The observed response is a favorable, tuned value that balances the smooth, continuous nature of the simulated response with the measured response, which can detect outside influences on the system.

[0188] In one aspect, the motor **482** may be controlled by the motor driver **492** and can be employed by the firing system of the surgical instrument or tool. In various forms, the motor **482** may be a brushed DC driving motor having a maximum rotational speed of approximately 25,000 RPM. In other arrangements, the motor **482** may include a brushless motor, a cordless motor, a synchronous motor, a stepper motor, or any other suitable electric motor. The motor driver **492** may comprise an H-bridge driver comprising field-effect transistors (FETs), for example. The motor **482** can be powered by a power assembly releasably mounted to the handle assembly or tool housing for supplying control power to the surgical instrument or tool. The power assembly may comprise a battery which may include a number of battery cells connected in series that can be used as the power source to power the surgical instrument or tool. In certain circumstances, the battery cells of the power assembly may be replaceable and/or rechargeable. In at least one example, the battery cells can be lithium-ion batteries which can be coupleable to and separable from the power assembly.

[0189] The motor driver **492** may be an A3941 available from Allegro Microsystems, Inc. The A3941 **492** is a full-bridge controller for use with external N-channel power metal-oxide semiconductor field-effect transistors (MOSFETs) specifically designed for inductive loads, such as brush DC motors. The driver **492** comprises a unique charge pump regulator that provides full (>10 V) gate drive for battery voltages down to 7 V and allows the A3941 to operate with a reduced gate drive, down to 5.5 V. A bootstrap capacitor may be employed to provide the above battery supply voltage required for N-channel MOSFETs. An internal charge pump for the high-side drive allows DC (100% duty cycle) operation. The full bridge can be driven in fast or slow decay modes using diode or synchronous rectification. In the slow decay mode, current recirculation can be through the high-side or the lowside FETs. The power FETs are protected from shoot-through by resistor-adjustable dead time. Integrated diagnostics provide indications of under-voltage, overtemperature, and power bridge faults and can be configured to protect the power MOSFETs under most short circuit conditions. Other motor drivers may be readily substituted for use in the tracking system **480** comprising an absolute positioning system.

[0190] The tracking system **480** comprises a controlled motor drive circuit arrangement comprising a position sensor **472** according to one aspect of this disclosure. The position sensor **472** for an absolute positioning system provides a unique position signal corresponding to the location of a displacement member. In one aspect, the displacement member represents a longitudinally movable drive member comprising a rack of drive teeth for meshing engagement with a corresponding drive gear of a gear reducer assembly. In other aspects, the displacement member represents the firing member, which could be adapted and configured to include a rack of drive teeth. In yet another aspect, the displacement member represents a firing bar or the I-beam, each of which can be adapted and configured to include a rack of drive teeth. Accordingly, as used herein, the term displacement member is used generically to refer to any movable member of the surgical instrument or tool such as the drive member, the firing member, the firing bar, the I-beam, or any element that can be displaced. In one aspect, the longitudinally movable drive member is coupled to the firing member, the firing bar, and the I-beam. Accordingly, the absolute positioning system can, in effect, track the linear displacement of the I-beam by tracking the linear displacement of the longitudinally movable drive member. In various other aspects, the displacement member may be coupled to any position sensor **472** suitable for measuring linear displacement. Thus, the longitudinally movable drive member, the firing member, the firing bar, or the I-beam, or combinations thereof, may be coupled to any suitable linear displacement sensor. Linear displacement sensors may include contact or non-contact displacement sensors. Linear displacement sensors may comprise linear variable differential transformers (LVDT), differential variable reluctance transducers (DVRT), a slide potentiometer, a magnetic sensing system comprising a movable magnet and a series of linearly arranged Hall effect sensors, a magnetic sensing system comprising a fixed magnet and a series of movable, linearly arranged Hall effect sensors, an optical sensing system comprising a movable light source and a series of linearly arranged photo diodes or photo detectors, an optical sensing system comprising a fixed light source and a series

of movable linearly, arranged photo diodes or photo detectors, or any combination thereof.

[0191] The electric motor 482 can include a rotatable shaft that operably interfaces with a gear assembly that is mounted in meshing engagement with a set, or rack, of drive teeth on the displacement member. A sensor element may be operably coupled to a gear assembly such that a single revolution of the position sensor 472 element corresponds to some linear longitudinal translation of the displacement member. An arrangement of gearing and sensors can be connected to the linear actuator, via a rack and pinion arrangement, or a rotary actuator, via a spur gear or other connection. A power source supplies power to the absolute positioning system and an output indicator may display the output of the absolute positioning system. The displacement member represents the longitudinally movable drive member comprising a rack of drive teeth formed thereon for meshing engagement with a corresponding drive gear of the gear reducer assembly. The displacement member represents the longitudinally movable firing member, firing bar, I-beam, or combinations thereof.

[0192] A single revolution of the sensor element associated with the position sensor 472 is equivalent to a longitudinal linear displacement d_1 of the displacement member, where d_1 is the longitudinal linear distance that the displacement member moves from point “a” to point “b” after a single revolution of the sensor element coupled to the displacement member. The sensor arrangement may be connected via a gear reduction that results in the position sensor 472 completing one or more revolutions for the full stroke of the displacement member. The position sensor 472 may complete multiple revolutions for the full stroke of the displacement member.

[0193] A series of switches, where n is an integer greater than one, may be employed alone or in combination with a gear reduction to provide a unique position signal for more than one revolution of the position sensor 472. The state of the switches are fed back to the microcontroller 461 that applies logic to determine a unique position signal corresponding to the longitudinal linear displacement $d_1 + d_2 + \dots + d_n$ of the displacement member. The output of the position sensor 472 is provided to the microcontroller 461. The position sensor 472 of the sensor arrangement may comprise a magnetic sensor, an analog rotary sensor like a potentiometer, or an array of analog Hall-effect elements, which output a unique combination of position signals or values.

[0194] The position sensor 472 may comprise any number of magnetic sensing elements, such as, for example, magnetic sensors classified according to whether they measure the total magnetic field or the vector components of the magnetic field. The techniques used to produce both types of magnetic sensors encompass many aspects of physics and electronics. The technologies used for magnetic field sensing include search coil, fluxgate, optically pumped, nuclear precession, SQUID, Hall-effect, anisotropic magnetoresistance, giant magnetoresistance, magnetic tunnel junctions, giant magnetoimpedance, magnetostrictive/piezoelectric composites, magnetodiode, magnetotransistor, fiber-optic, magneto-optic, and microelectromechanical systems-based magnetic sensors, among others.

[0195] In one aspect, the position sensor 472 for the tracking system 480 comprising an absolute positioning system comprises a magnetic rotary absolute positioning system. The position sensor 472 may be implemented as an

AS5055EQFT single-chip magnetic rotary position sensor available from Austria Microsystems, AG. The position sensor 472 is interfaced with the microcontroller 461 to provide an absolute positioning system. The position sensor 472 is a low-voltage and low-power component and includes four Hall-effect elements in an area of the position sensor 472 that is located above a magnet. A high-resolution ADC and a smart power management controller are also provided on the chip. A coordinate rotation digital computer (CORDIC) processor, also known as the digit-by-digit method and Volder’s algorithm, is provided to implement a simple and efficient algorithm to calculate hyperbolic and trigonometric functions that require only addition, subtraction, bitshift, and table lookup operations. The angle position, alarm bits, and magnetic field information are transmitted over a standard serial communication interface, such as a serial peripheral interface (SPI) interface, to the microcontroller 461. The position sensor 472 provides 12 or 14 bits of resolution. The position sensor 472 may be an AS5055 chip provided in a small QFN 16-pin $4 \times 4 \times 0.85$ mm package.

[0196] The tracking system 480 comprising an absolute positioning system may comprise and/or be programmed to implement a feedback controller, such as a PID, state feedback, and adaptive controller. A power source converts the signal from the feedback controller into a physical input to the system: in this case the voltage. Other examples include a PWM of the voltage, current, and force. Other sensor(s) may be provided to measure physical parameters of the physical system in addition to the position measured by the position sensor 472. In some aspects, the other sensor(s) can include sensor arrangements such as those described in U.S. Pat. No. 9,345,481, titled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, which issued on May 24, 2016, which is herein incorporated by reference in its entirety; U.S. Patent Application Publication No. 2014/0263552, titled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, which published on Sep. 18, 2014, which is herein incorporated by reference in its entirety; and U.S. patent application Ser. No. 15/628,175, titled TECHNIQUES FOR ADAPTIVE CONTROL OF MOTOR VELOCITY OF A SURGICAL STAPLING AND CUTTING INSTRUMENT, filed Jun. 20, 2017, which is herein incorporated by reference in its entirety. In a digital signal processing system, an absolute positioning system is coupled to a digital data acquisition system where the output of the absolute positioning system will have a finite resolution and sampling frequency. The absolute positioning system may comprise a compare-and-combine circuit to combine a computed response with a measured response using algorithms, such as a weighted average and a theoretical control loop, that drive the computed response towards the measured response. The computed response of the physical system takes into account properties like mass, inertial, viscous friction, inductance resistance, etc., to predict what the states and outputs of the physical system will be by knowing the input.

[0197] The absolute positioning system provides an absolute position of the displacement member upon power-up of the instrument, without retracting or advancing the displacement member to a reset (zero or home) position as may be required with conventional rotary encoders that merely count the number of steps forwards or backwards that the

motor **482** has taken to infer the position of a device actuator, drive bar, knife, or the like.

[0198] A sensor **474**, such as, for example, a strain gauge or a micro-strain gauge, is configured to measure one or more parameters of the end effector, such as, for example, the amplitude of the strain exerted on the anvil during a clamping operation, which can be indicative of the closure forces applied to the anvil. The measured strain is converted to a digital signal and provided to the processor **462**. Alternatively, or in addition to the sensor **474**, a sensor **476**, such as, for example, a load sensor, can measure the closure force applied by the closure drive system to the anvil. The sensor **476**, such as, for example, a load sensor, can measure the firing force applied to an I-beam in a firing stroke of the surgical instrument or tool. The I-beam is configured to engage a wedge sled, which is configured to upwardly cam staple drivers to force out staples into deforming contact with an anvil. The I-beam also includes a sharpened cutting edge that can be used to sever tissue as the I-beam is advanced distally by the firing bar. Alternatively, a current sensor **478** can be employed to measure the current drawn by the motor **482**. The force required to advance the firing member can correspond to the current drawn by the motor **482**, for example. The measured force is converted to a digital signal and provided to the processor **462**.

[0199] In one form, the strain gauge sensor **474** can be used to measure the force applied to the tissue by the end effector. A strain gauge can be coupled to the end effector to measure the force on the tissue being treated by the end effector. A system for measuring forces applied to the tissue grasped by the end effector comprises a strain gauge sensor **474**, such as, for example, a micro-strain gauge, that is configured to measure one or more parameters of the end effector, for example. In one aspect, the strain gauge sensor **474** can measure the amplitude or magnitude of the strain exerted on a jaw member of an end effector during a clamping operation, which can be indicative of the tissue compression. The measured strain is converted to a digital signal and provided to a processor **462** of the microcontroller **461**. A load sensor **476** can measure the force used to operate the knife element, for example, to cut the tissue captured between the anvil and the staple cartridge. A magnetic field sensor can be employed to measure the thickness of the captured tissue. The measurement of the magnetic field sensor also may be converted to a digital signal and provided to the processor **462**.

[0200] The measurements of the tissue compression, the tissue thickness, and/or the force required to close the end effector on the tissue, as respectively measured by the sensors **474**, **476**, can be used by the microcontroller **461** to characterize the selected position of the firing member and/or the corresponding value of the speed of the firing member. In one instance, a memory **468** may store a technique, an equation, and/or a lookup table which can be employed by the microcontroller **461** in the assessment.

[0201] The control system **470** of the surgical instrument or tool also may comprise wired or wireless communication circuits to communicate with the modular communication hub as shown in FIGS. 8-11.

[0202] FIG. 13 illustrates a control circuit **500** configured to control aspects of the surgical instrument or tool according to one aspect of this disclosure. The control circuit **500** can be configured to implement various processes described herein. The control circuit **500** may comprise a microcon-

troller comprising one or more processors **502** (e.g., micro-processor, microcontroller) coupled to at least one memory circuit **504**. The memory circuit **504** stores machine-executable instructions that, when executed by the processor **502**, cause the processor **502** to execute machine instructions to implement various processes described herein. The processor **502** may be any one of a number of single-core or multicore processors known in the art. The memory circuit **504** may comprise volatile and non-volatile storage media. The processor **502** may include an instruction processing unit **506** and an arithmetic unit **508**. The instruction processing unit may be configured to receive instructions from the memory circuit **504** of this disclosure.

[0203] FIG. 14 illustrates a combinational logic circuit **510** configured to control aspects of the surgical instrument or tool according to one aspect of this disclosure. The combinational logic circuit **510** can be configured to implement various processes described herein. The combinational logic circuit **510** may comprise a finite state machine comprising a combinational logic **512** configured to receive data associated with the surgical instrument or tool at an input **514**, process the data by the combinational logic **512**, and provide an output **516**.

[0204] FIG. 15 illustrates a sequential logic circuit **520** configured to control aspects of the surgical instrument or tool according to one aspect of this disclosure. The sequential logic circuit **520** or the combinational logic **522** can be configured to implement various processes described herein. The sequential logic circuit **520** may comprise a finite state machine. The sequential logic circuit **520** may comprise a combinational logic **522**, at least one memory circuit **524**, and a clock **529**, for example. The at least one memory circuit **524** can store a current state of the finite state machine. In certain instances, the sequential logic circuit **520** may be synchronous or asynchronous. The combinational logic **522** is configured to receive data associated with the surgical instrument or tool from an input **526**, process the data by the combinational logic **522**, and provide an output **528**. In other aspects, the circuit may comprise a combination of a processor (e.g., processor **502**, FIG. 13) and a finite state machine to implement various processes herein. In other aspects, the finite state machine may comprise a combination of a combinational logic circuit (e.g., combinational logic circuit **510**, FIG. 14) and the sequential logic circuit **520**.

[0205] FIG. 16 illustrates a surgical instrument or tool comprising a plurality of motors which can be activated to perform various functions. In certain instances, a first motor can be activated to perform a first function, a second motor can be activated to perform a second function, a third motor can be activated to perform a third function, a fourth motor can be activated to perform a fourth function, and so on. In certain instances, the plurality of motors of robotic surgical instrument **600** can be individually activated to cause firing, closure, and/or articulation motions in the end effector. The firing, closure, and/or articulation motions can be transmitted to the end effector through a shaft assembly, for example.

[0206] In certain instances, the surgical instrument system or tool may include a firing motor **602**. The firing motor **602** may be operably coupled to a firing motor drive assembly **604** which can be configured to transmit firing motions, generated by the motor **602** to the end effector, in particular to displace the I-beam element. In certain instances, the firing motions generated by the motor **602** may cause the

staples to be deployed from the staple cartridge into tissue captured by the end effector and/or the cutting edge of the I-beam element to be advanced to cut the captured tissue, for example. The I-beam element may be retracted by reversing the direction of the motor 602.

[0207] In certain instances, the surgical instrument or tool may include a closure motor 603. The closure motor 603 may be operably coupled to a closure motor drive assembly 605 which can be configured to transmit closure motions, generated by the motor 603 to the end effector, in particular to displace a closure tube to close the anvil and compress tissue between the anvil and the staple cartridge. The closure motions may cause the end effector to transition from an open configuration to an approximated configuration to capture tissue, for example. The end effector may be transitioned to an open position by reversing the direction of the motor 603.

[0208] In certain instances, the surgical instrument or tool may include one or more articulation motors 606a, 606b, for example. The motors 606a, 606b may be operably coupled to respective articulation motor drive assemblies 608a, 608b, which can be configured to transmit articulation motions generated by the motors 606a, 606b to the end effector. In certain instances, the articulation motions may cause the end effector to articulate relative to the shaft, for example.

[0209] As described above, the surgical instrument or tool may include a plurality of motors which may be configured to perform various independent functions. In certain instances, the plurality of motors of the surgical instrument or tool can be individually or separately activated to perform one or more functions while the other motors remain inactive. For example, the articulation motors 606a, 606b can be activated to cause the end effector to be articulated while the firing motor 602 remains inactive. Alternatively, the firing motor 602 can be activated to fire the plurality of staples, and/or to advance the cutting edge, while the articulation motor 606 remains inactive. Furthermore the closure motor 603 may be activated simultaneously with the firing motor 602 to cause the closure tube and the I-beam element to advance distally as described in more detail hereinbelow.

[0210] In certain instances, the surgical instrument or tool may include a common control module 610 which can be employed with a plurality of motors of the surgical instrument or tool. In certain instances, the common control module 610 may accommodate one of the plurality of motors at a time. For example, the common control module 610 can be coupleable to and separable from the plurality of motors of the robotic surgical instrument individually. In certain instances, a plurality of the motors of the surgical instrument or tool may share one or more common control modules such as the common control module 610. In certain instances, a plurality of motors of the surgical instrument or tool can be individually and selectively engaged with the common control module 610. In certain instances, the common control module 610 can be selectively switched from interfacing with one of a plurality of motors of the surgical instrument or tool to interfacing with another one of the plurality of motors of the surgical instrument or tool.

[0211] In at least one example, the common control module 610 can be selectively switched between operable engagement with the articulation motors 606a, 606b and operable engagement with either the firing motor 602 or the closure motor 603. In at least one example, as illustrated in

FIG. 16, a switch 614 can be moved or transitioned between a plurality of positions and/or states. In a first position 616, the switch 614 may electrically couple the common control module 610 to the firing motor 602; in a second position 617, the switch 614 may electrically couple the common control module 610 to the closure motor 603; in a third position 618a, the switch 614 may electrically couple the common control module 610 to the first articulation motor 606a; and in a fourth position 618b, the switch 614 may electrically couple the common control module 610 to the second articulation motor 606b, for example. In certain instances, separate common control modules 610 can be electrically coupled to the firing motor 602, the closure motor 603, and the articulations motor 606a, 606b at the same time. In certain instances, the switch 614 may be a mechanical switch, an electromechanical switch, a solid-state switch, or any suitable switching mechanism.

[0212] Each of the motors 602, 603, 606a, 606b may comprise a torque sensor to measure the output torque on the shaft of the motor. The force on an end effector may be sensed in any conventional manner, such as by force sensors on the outer sides of the jaws or by a torque sensor for the motor actuating the jaws.

[0213] In various instances, as illustrated in FIG. 16, the common control module 610 may comprise a motor driver 626 which may comprise one or more H-Bridge FETs. The motor driver 626 may modulate the power transmitted from a power source 628 to a motor coupled to the common control module 610 based on input from a microcontroller 620 (the “controller”), for example. In certain instances, the microcontroller 620 can be employed to determine the current drawn by the motor, for example, while the motor is coupled to the common control module 610, as described above.

[0214] In certain instances, the microcontroller 620 may include a microprocessor 622 (the “processor”) and one or more non-transitory computer-readable mediums or memory units 624 (the “memory”). In certain instances, the memory 624 may store various program instructions, which when executed may cause the processor 622 to perform a plurality of functions and/or calculations described herein. In certain instances, one or more of the memory units 624 may be coupled to the processor 622, for example.

[0215] In certain instances, the power source 628 can be employed to supply power to the microcontroller 620, for example. In certain instances, the power source 628 may comprise a battery (or “battery pack” or “power pack”), such as a lithium-ion battery, for example. In certain instances, the battery pack may be configured to be releasably mounted to a handle for supplying power to the surgical instrument 600. A number of battery cells connected in series may be used as the power source 628. In certain instances, the power source 628 may be replaceable and/or rechargeable, for example.

[0216] In various instances, the processor 622 may control the motor driver 626 to control the position, direction of rotation, and/or velocity of a motor that is coupled to the common control module 610. In certain instances, the processor 622 can signal the motor driver 626 to stop and/or disable a motor that is coupled to the common control module 610. It should be understood that the term “processor” as used herein includes any suitable microprocessor, microcontroller, or other basic computing device that incorporates the functions of a computer’s central processing unit

(CPU) on an integrated circuit or, at most, a few integrated circuits. The processor is a multipurpose, programmable device that accepts digital data as input, processes it according to instructions stored in its memory, and provides results as output. It is an example of sequential digital logic, as it has internal memory. Processors operate on numbers and symbols represented in the binary numeral system.

[0217] In one instance, the processor 622 may be any single-core or multicore processor such as those known under the trade name ARM Cortex by Texas Instruments. In certain instances, the microcontroller 620 may be an LM4F230H5QR, available from Texas Instruments, for example. In at least one example, the Texas Instruments LM4F230H5QR is an ARM Cortex-M4F Processor Core comprising an on-chip memory of 256 KB single-cycle flash memory, or other non-volatile memory, up to 40 MHz, a prefetch buffer to improve performance above 40 MHz, a 32 KB single-cycle SRAM, an internal ROM loaded with StellarisWare® software, a 2 KB EEPROM, one or more PWM modules, one or more QEI analogs, one or more 12-bit ADCs with 12 analog input channels, among other features that are readily available for the product datasheet. Other microcontrollers may be readily substituted for use with the module 4410. Accordingly, the present disclosure should not be limited in this context.

[0218] In certain instances, the memory 624 may include program instructions for controlling each of the motors of the surgical instrument 600 that are couplable to the common control module 610. For example, the memory 624 may include program instructions for controlling the firing motor 602, the closure motor 603, and the articulation motors 606a, 606b. Such program instructions may cause the processor 622 to control the firing, closure, and articulation functions in accordance with inputs from algorithms or control programs of the surgical instrument or tool.

[0219] In certain instances, one or more mechanisms and/or sensors such as, for example, sensors 630 can be employed to alert the processor 622 to the program instructions that should be used in a particular setting. For example, the sensors 630 may alert the processor 622 to use the program instructions associated with firing, closing, and articulating the end effector. In certain instances, the sensors 630 may comprise position sensors which can be employed to sense the position of the switch 614, for example. Accordingly, the processor 622 may use the program instructions associated with firing the I-beam of the end effector upon detecting, through the sensors 630 for example, that the switch 614 is in the first position 616; the processor 622 may use the program instructions associated with closing the anvil upon detecting, through the sensors 630 for example, that the switch 614 is in the second position 617; and the processor 622 may use the program instructions associated with articulating the end effector upon detecting, through the sensors 630 for example, that the switch 614 is in the third or fourth position 618a, 618b.

[0220] FIG. 17 is a schematic diagram of a robotic surgical instrument 700 configured to operate a surgical tool described herein according to one aspect of this disclosure. The robotic surgical instrument 700 may be programmed or configured to control distal/proximal translation of a displacement member, distal/proximal displacement of a closure tube, shaft rotation, and articulation, either with single or multiple articulation drive links. In one aspect, the surgical instrument 700 may be programmed or configured

to individually control a firing member, a closure member, a shaft member, and/or one or more articulation members. The surgical instrument 700 comprises a control circuit 710 configured to control motor-driven firing members, closure members, shaft members, and/or one or more articulation members.

[0221] In one aspect, the robotic surgical instrument 700 comprises a control circuit 710 configured to control an anvil 716 and an I-beam 714 (including a sharp cutting edge) portion of an end effector 702, a removable staple cartridge 718, a shaft 740, and one or more articulation members 742a, 742b via a plurality of motors 704a-704e. A position sensor 734 may be configured to provide position feedback of the I-beam 714 to the control circuit 710. Other sensors 738 may be configured to provide feedback to the control circuit 710. A timer/counter 731 provides timing and counting information to the control circuit 710. An energy source 712 may be provided to operate the motors 704a-704e, and a current sensor 736 provides motor current feedback to the control circuit 710. The motors 704a-704e can be operated individually by the control circuit 710 in an open-loop or closed-loop feedback control.

[0222] In one aspect, the control circuit 710 may comprise one or more microcontrollers, microprocessors, or other suitable processors for executing instructions that cause the processor or processors to perform one or more tasks. In one aspect, a timer/counter 731 provides an output signal, such as the elapsed time or a digital count, to the control circuit 710 to correlate the position of the I-beam 714 as determined by the position sensor 734 with the output of the timer/counter 731 such that the control circuit 710 can determine the position of the I-beam 714 at a specific time (t) relative to a starting position or the time (t) when the I-beam 714 is at a specific position relative to a starting position. The timer/counter 731 may be configured to measure elapsed time, count external events, or time external events.

[0223] In one aspect, the control circuit 710 may be programmed to control functions of the end effector 702 based on one or more tissue conditions. The control circuit 710 may be programmed to sense tissue conditions, such as thickness, either directly or indirectly, as described herein. The control circuit 710 may be programmed to select a firing control program or closure control program based on tissue conditions. A firing control program may describe the distal motion of the displacement member. Different firing control programs may be selected to better treat different tissue conditions. For example, when thicker tissue is present, the control circuit 710 may be programmed to translate the displacement member at a lower velocity and/or with lower power. When thinner tissue is present, the control circuit 710 may be programmed to translate the displacement member at a higher velocity and/or with higher power. A closure control program may control the closure force applied to the tissue by the anvil 716. Other control programs control the rotation of the shaft 740 and the articulation members 742a, 742b.

[0224] In one aspect, the control circuit 710 may generate motor set point signals. The motor set point signals may be provided to various motor controllers 708a-708e. The motor controllers 708a-708e may comprise one or more circuits configured to provide motor drive signals to the motors 704a-704e to drive the motors 704a-704e as described herein. In some examples, the motors 704a-704e may be brushed DC electric motors. For example, the velocity of the

motors **704a-704e** may be proportional to the respective motor drive signals. In some examples, the motors **704a-704e** may be brushless DC electric motors, and the respective motor drive signals may comprise a PWM signal provided to one or more stator windings of the motors **704a-704e**. Also, in some examples, the motor controllers **708a-708e** may be omitted and the control circuit **710** may generate the motor drive signals directly.

[0225] In one aspect, the control circuit **710** may initially operate each of the motors **704a-704e** in an open-loop configuration for a first open-loop portion of a stroke of the displacement member. Based on the response of the robotic surgical instrument **700** during the open-loop portion of the stroke, the control circuit **710** may select a firing control program in a closed-loop configuration. The response of the instrument may include a translation distance of the displacement member during the open-loop portion, a time elapsed during the open-loop portion, the energy provided to one of the motors **704a-704e** during the open-loop portion, a sum of pulse widths of a motor drive signal, etc. After the open-loop portion, the control circuit **710** may implement the selected firing control program for a second portion of the displacement member stroke. For example, during a closed-loop portion of the stroke, the control circuit **710** may modulate one of the motors **704a-704e** based on translation data describing a position of the displacement member in a closed-loop manner to translate the displacement member at a constant velocity.

[0226] In one aspect, the motors **704a-704e** may receive power from an energy source **712**. The energy source **712** may be a DC power supply driven by a main alternating current power source, a battery, a super capacitor, or any other suitable energy source. The motors **704a-704e** may be mechanically coupled to individual movable mechanical elements such as the I-beam **714**, anvil **716**, shaft **740**, articulation **742a**, and articulation **742b** via respective transmissions **706a-706e**. The transmissions **706a-706e** may include one or more gears or other linkage components to couple the motors **704a-704e** to movable mechanical elements. A position sensor **734** may sense a position of the I-beam **714**. The position sensor **734** may be or include any type of sensor that is capable of generating position data that indicate a position of the I-beam **714**. In some examples, the position sensor **734** may include an encoder configured to provide a series of pulses to the control circuit **710** as the I-beam **714** translates distally and proximally. The control circuit **710** may track the pulses to determine the position of the I-beam **714**. Other suitable position sensors may be used, including, for example, a proximity sensor. Other types of position sensors may provide other signals indicating motion of the I-beam **714**. Also, in some examples, the position sensor **734** may be omitted. Where any of the motors **704a-704e** is a stepper motor, the control circuit **710** may track the position of the I-beam **714** by aggregating the number and direction of steps that the motor **704** has been instructed to execute. The position sensor **734** may be located in the end effector **702** or at any other portion of the instrument. The outputs of each of the motors **704a-704e** include a torque sensor **744a-744e** to sense force and have an encoder to sense rotation of the drive shaft.

[0227] In one aspect, the control circuit **710** is configured to drive a firing member such as the I-beam **714** portion of the end effector **702**. The control circuit **710** provides a motor set point to a motor control **708a**, which provides a

drive signal to the motor **704a**. The output shaft of the motor **704a** is coupled to a torque sensor **744a**. The torque sensor **744a** is coupled to a transmission **706a** which is coupled to the I-beam **714**. The transmission **706a** comprises movable mechanical elements such as rotating elements and a firing member to control the movement of the I-beam **714** distally and proximally along a longitudinal axis of the end effector **702**. In one aspect, the motor **704a** may be coupled to the knife gear assembly, which includes a knife gear reduction set that includes a first knife drive gear and a second knife drive gear. A torque sensor **744a** provides a firing force feedback signal to the control circuit **710**. The firing force signal represents the force required to fire or displace the I-beam **714**. A position sensor **734** may be configured to provide the position of the I-beam **714** along the firing stroke or the position of the firing member as a feedback signal to the control circuit **710**. The end effector **702** may include additional sensors **738** configured to provide feedback signals to the control circuit **710**. When ready to use, the control circuit **710** may provide a firing signal to the motor control **708a**. In response to the firing signal, the motor **704a** may drive the firing member distally along the longitudinal axis of the end effector **702** from a proximal stroke start position to a stroke end position distal to the stroke start position. As the firing member translates distally, an I-beam **714**, with a cutting element positioned at a distal end, advances distally to cut tissue located between the staple cartridge **718** and the anvil **716**.

[0228] In one aspect, the control circuit **710** is configured to drive a closure member such as the anvil **716** portion of the end effector **702**. The control circuit **710** provides a motor set point to a motor control **708b**, which provides a drive signal to the motor **704b**. The output shaft of the motor **704b** is coupled to a torque sensor **744b**. The torque sensor **744b** is coupled to a transmission **706b** which is coupled to the anvil **716**. The transmission **706b** comprises movable mechanical elements such as rotating elements and a closure member to control the movement of the anvil **716** from the open and closed positions. In one aspect, the motor **704b** is coupled to a closure gear assembly, which includes a closure reduction gear set that is supported in meshing engagement with the closure spur gear. The torque sensor **744b** provides a closure force feedback signal to the control circuit **710**. The closure force feedback signal represents the closure force applied to the anvil **716**. The position sensor **734** may be configured to provide the position of the closure member as a feedback signal to the control circuit **710**. Additional sensors **738** in the end effector **702** may provide the closure force feedback signal to the control circuit **710**. The pivotable anvil **716** is positioned opposite the staple cartridge **718**. When ready to use, the control circuit **710** may provide a closure signal to the motor control **708b**. In response to the closure signal, the motor **704b** advances a closure member to grasp tissue between the anvil **716** and the staple cartridge **718**.

[0229] In one aspect, the control circuit **710** is configured to rotate a shaft member such as the shaft **740** to rotate the end effector **702**. The control circuit **710** provides a motor set point to a motor control **708c**, which provides a drive signal to the motor **704c**. The output shaft of the motor **704c** is coupled to a torque sensor **744c**. The torque sensor **744c** is coupled to a transmission **706c** which is coupled to the shaft **740**. The transmission **706c** comprises movable mechanical elements such as rotating elements to control the

rotation of the shaft **740** clockwise or counterclockwise up to and over 360°. In one aspect, the motor **704c** is coupled to the rotational transmission assembly, which includes a tube gear segment that is formed on (or attached to) the proximal end of the proximal closure tube for operable engagement by a rotational gear assembly that is operably supported on the tool mounting plate. The torque sensor **744c** provides a rotation force feedback signal to the control circuit **710**. The rotation force feedback signal represents the rotation force applied to the shaft **740**. The position sensor **734** may be configured to provide the position of the closure member as a feedback signal to the control circuit **710**. Additional sensors **738** such as a shaft encoder may provide the rotational position of the shaft **740** to the control circuit **710**.

[0230] In one aspect, the control circuit **710** is configured to articulate the end effector **702**. The control circuit **710** provides a motor set point to a motor control **708d**, which provides a drive signal to the motor **704d**. The output shaft of the motor **704d** is coupled to a torque sensor **744d**. The torque sensor **744d** is coupled to a transmission **706d** which is coupled to an articulation member **742a**. The transmission **706d** comprises movable mechanical elements such as articulation elements to control the articulation of the end effector **702** $\pm 65^\circ$. In one aspect, the motor **704d** is coupled to an articulation nut, which is rotatably journaled on the proximal end portion of the distal spine portion and is rotatably driven thereon by an articulation gear assembly. The torque sensor **744d** provides an articulation force feedback signal to the control circuit **710**. The articulation force feedback signal represents the articulation force applied to the end effector **702**. Sensors **738**, such as an articulation encoder, may provide the articulation position of the end effector **702** to the control circuit **710**.

[0231] In another aspect, the articulation function of the robotic surgical system **700** may comprise two articulation members, or links, **742a**, **742b**. These articulation members **742a**, **742b** are driven by separate disks on the robot interface (the rack) which are driven by the two motors **708d**, **708e**. When the separate firing motor **704a** is provided, each of articulation links **742a**, **742b** can be antagonistically driven with respect to the other link in order to provide a resistive holding motion and a load to the head when it is not moving and to provide an articulation motion as the head is articulated. The articulation members **742a**, **742b** attach to the head at a fixed radius as the head is rotated. Accordingly, the mechanical advantage of the push-and-pull link changes as the head is rotated. This change in the mechanical advantage may be more pronounced with other articulation link drive systems.

[0232] In one aspect, the one or more motors **704a-704e** may comprise a brushed DC motor with a gearbox and mechanical links to a firing member, closure member, or articulation member. Another example includes electric motors **704a-704e** that operate the movable mechanical elements such as the displacement member, articulation links, closure tube, and shaft. An outside influence is an unmeasured, unpredictable influence of things like tissue, surrounding bodies, and friction on the physical system. Such outside influence can be referred to as drag, which acts in opposition to one of electric motors **704a-704e**. The outside influence, such as drag, may cause the operation of the physical system to deviate from a desired operation of the physical system.

[0233] In one aspect, the position sensor **734** may be implemented as an absolute positioning system. In one aspect, the position sensor **734** may comprise a magnetic rotary absolute positioning system implemented as an AS5055EQFT single-chip magnetic rotary position sensor available from Austria Microsystems, AG. The position sensor **734** may interface with the control circuit **710** to provide an absolute positioning system. The position may include multiple Hall-effect elements located above a magnet and coupled to a CORDIC processor, also known as the digit-by-digit method and Volder's algorithm, that is provided to implement a simple and efficient algorithm to calculate hyperbolic and trigonometric functions that require only addition, subtraction, bitshift, and table lookup operations.

[0234] In one aspect, the control circuit **710** may be in communication with one or more sensors **738**. The sensors **738** may be positioned on the end effector **702** and adapted to operate with the robotic surgical instrument **700** to measure the various derived parameters such as the gap distance versus time, tissue compression versus time, and anvil strain versus time. The sensors **738** may comprise a magnetic sensor, a magnetic field sensor, a strain gauge, a load cell, a pressure sensor, a force sensor, a torque sensor, an inductive sensor such as an eddy current sensor, a resistive sensor, a capacitive sensor, an optical sensor, and/or any other suitable sensor for measuring one or more parameters of the end effector **702**. The sensors **738** may include one or more sensors. The sensors **738** may be located on the staple cartridge **718** deck to determine tissue location using segmented electrodes. The torque sensors **744a-744e** may be configured to sense force such as firing force, closure force, and/or articulation force, among others. Accordingly, the control circuit **710** can sense (1) the closure load experienced by the distal closure tube and its position, (2) the firing member at the rack and its position, (3) what portion of the staple cartridge **718** has tissue on it, and (4) the load and position on both articulation rods.

[0235] In one aspect, the one or more sensors **738** may comprise a strain gauge, such as a micro-strain gauge, configured to measure the magnitude of the strain in the anvil **716** during a clamped condition. The strain gauge provides an electrical signal whose amplitude varies with the magnitude of the strain. The sensors **738** may comprise a pressure sensor configured to detect a pressure generated by the presence of compressed tissue between the anvil **716** and the staple cartridge **718**. The sensors **738** may be configured to detect impedance of a tissue section located between the anvil **716** and the staple cartridge **718** that is indicative of the thickness and/or fullness of tissue located therebetween.

[0236] In one aspect, the sensors **738** may be implemented as one or more limit switches, electromechanical devices, solid-state switches, Hall-effect devices, magneto-resistive (MR) devices, giant magneto-resistive (GMR) devices, magnetometers, among others. In other implementations, the sensors **738** may be implemented as solid-state switches that operate under the influence of light, such as optical sensors, IR sensors, ultraviolet sensors, among others. Still, the switches may be solid-state devices such as transistors (e.g., FET, junction FET, MOSFET, bipolar, and the like). In other implementations, the sensors **738** may include electrical conductorless switches, ultrasonic switches, accelerometers, and inertial sensors, among others.

[0237] In one aspect, the sensors 738 may be configured to measure forces exerted on the anvil 716 by the closure drive system. For example, one or more sensors 738 can be at an interaction point between the closure tube and the anvil 716 to detect the closure forces applied by the closure tube to the anvil 716. The forces exerted on the anvil 716 can be representative of the tissue compression experienced by the tissue section captured between the anvil 716 and the staple cartridge 718. The one or more sensors 738 can be positioned at various interaction points along the closure drive system to detect the closure forces applied to the anvil 716 by the closure drive system. The one or more sensors 738 may be sampled in real time during a clamping operation by the processor of the control circuit 710. The control circuit 710 receives real-time sample measurements to provide and analyze time-based information and assess, in real time, closure forces applied to the anvil 716.

[0238] In one aspect, a current sensor 736 can be employed to measure the current drawn by each of the motors 704a-704e. The force required to advance any of the movable mechanical elements such as the I-beam 714 corresponds to the current drawn by one of the motors 704a-704e. The force is converted to a digital signal and provided to the control circuit 710. The control circuit 710 can be configured to simulate the response of the actual system of the instrument in the software of the controller. A displacement member can be actuated to move an I-beam 714 in the end effector 702 at or near a target velocity. The robotic surgical instrument 700 can include a feedback controller, which can be one of any feedback controllers, including, but not limited to a PID, a state feedback, a linear-quadratic (LQR), and/or an adaptive controller, for example. The robotic surgical instrument 700 can include a power source to convert the signal from the feedback controller into a physical input such as case voltage, PWM voltage, frequency modulated voltage, current, torque, and/or force, for example. Additional details are disclosed in U.S. patent application Ser. No. 15/636,829, titled CLOSED LOOP VELOCITY CONTROL TECHNIQUES FOR ROBOTIC SURGICAL INSTRUMENT, filed Jun. 29, 2017, which is herein incorporated by reference in its entirety.

[0239] FIG. 18 illustrates a block diagram of a surgical instrument 750 programmed to control the distal translation of a displacement member according to one aspect of this disclosure. In one aspect, the surgical instrument 750 is programmed to control the distal translation of a displacement member such as the I-beam 764. The surgical instrument 750 comprises an end effector 752 that may comprise an anvil 766, an I-beam 764 (including a sharp cutting edge), and a removable staple cartridge 768.

[0240] The position, movement, displacement, and/or translation of a linear displacement member, such as the I-beam 764, can be measured by an absolute positioning system, sensor arrangement, and position sensor 784. Because the I-beam 764 is coupled to a longitudinally movable drive member, the position of the I-beam 764 can be determined by measuring the position of the longitudinally movable drive member employing the position sensor 784. Accordingly, in the following description, the position, displacement, and/or translation of the I-beam 764 can be achieved by the position sensor 784 as described herein. A control circuit 760 may be programmed to control the translation of the displacement member, such as the I-beam 764. The control circuit 760, in some examples, may com-

prise one or more microcontrollers, microprocessors, or other suitable processors for executing instructions that cause the processor or processors to control the displacement member, e.g., the I-beam 764, in the manner described. In one aspect, a timer/counter 781 provides an output signal, such as the elapsed time or a digital count, to the control circuit 760 to correlate the position of the I-beam 764 as determined by the position sensor 784 with the output of the timer/counter 781 such that the control circuit 760 can determine the position of the I-beam 764 at a specific time (t) relative to a starting position. The timer/counter 781 may be configured to measure elapsed time, count external events, or time external events.

[0241] The control circuit 760 may generate a motor set point signal 772. The motor set point signal 772 may be provided to a motor controller 758. The motor controller 758 may comprise one or more circuits configured to provide a motor drive signal 774 to the motor 754 to drive the motor 754 as described herein. In some examples, the motor 754 may be a brushed DC electric motor. For example, the velocity of the motor 754 may be proportional to the motor drive signal 774. In some examples, the motor 754 may be a brushless DC electric motor and the motor drive signal 774 may comprise a PWM signal provided to one or more stator windings of the motor 754. Also, in some examples, the motor controller 758 may be omitted, and the control circuit 760 may generate the motor drive signal 774 directly.

[0242] The motor 754 may receive power from an energy source 762. The energy source 762 may be or include a battery, a super capacitor, or any other suitable energy source. The motor 754 may be mechanically coupled to the I-beam 764 via a transmission 756. The transmission 756 may include one or more gears or other linkage components to couple the motor 754 to the I-beam 764. A position sensor 784 may sense a position of the I-beam 764. The position sensor 784 may be or include any type of sensor that is capable of generating position data that indicate a position of the I-beam 764. In some examples, the position sensor 784 may include an encoder configured to provide a series of pulses to the control circuit 760 as the I-beam 764 translates distally and proximally. The control circuit 760 may track the pulses to determine the position of the I-beam 764. Other suitable position sensors may be used, including, for example, a proximity sensor. Other types of position sensors may provide other signals indicating motion of the I-beam 764. Also, in some examples, the position sensor 784 may be omitted. Where the motor 754 is a stepper motor, the control circuit 760 may track the position of the I-beam 764 by aggregating the number and direction of steps that the motor 754 has been instructed to execute. The position sensor 784 may be located in the end effector 752 or at any other portion of the instrument.

[0243] The control circuit 760 may be in communication with one or more sensors 788. The sensors 788 may be positioned on the end effector 752 and adapted to operate with the surgical instrument 750 to measure the various derived parameters such as gap distance versus time, tissue compression versus time, and anvil strain versus time. The sensors 788 may comprise a magnetic sensor, a magnetic field sensor, a strain gauge, a pressure sensor, a force sensor, an inductive sensor such as an eddy current sensor, a resistive sensor, a capacitive sensor, an optical sensor, and/or

any other suitable sensor for measuring one or more parameters of the end effector **752**. The sensors **788** may include one or more sensors.

[0244] The one or more sensors **788** may comprise a strain gauge, such as a micro-strain gauge, configured to measure the magnitude of the strain in the anvil **766** during a clamped condition. The strain gauge provides an electrical signal whose amplitude varies with the magnitude of the strain. The sensors **788** may comprise a pressure sensor configured to detect a pressure generated by the presence of compressed tissue between the anvil **766** and the staple cartridge **768**. The sensors **788** may be configured to detect impedance of a tissue section located between the anvil **766** and the staple cartridge **768** that is indicative of the thickness and/or fullness of tissue located therebetween.

[0245] The sensors **788** may be configured to measure forces exerted on the anvil **766** by a closure drive system. For example, one or more sensors **788** can be at an interaction point between a closure tube and the anvil **766** to detect the closure forces applied by a closure tube to the anvil **766**. The forces exerted on the anvil **766** can be representative of the tissue compression experienced by the tissue section captured between the anvil **766** and the staple cartridge **768**. The one or more sensors **788** can be positioned at various interaction points along the closure drive system to detect the closure forces applied to the anvil **766** by the closure drive system. The one or more sensors **788** may be sampled in real time during a clamping operation by a processor of the control circuit **760**. The control circuit **760** receives real-time sample measurements to provide and analyze time-based information and assess, in real time, closure forces applied to the anvil **766**.

[0246] A current sensor **786** can be employed to measure the current drawn by the motor **754**. The force required to advance the I-beam **764** corresponds to the current drawn by the motor **754**. The force is converted to a digital signal and provided to the control circuit **760**.

[0247] The control circuit **760** can be configured to simulate the response of the actual system of the instrument in the software of the controller. A displacement member can be actuated to move an I-beam **764** in the end effector **752** at or near a target velocity. The surgical instrument **750** can include a feedback controller, which can be one of any feedback controllers, including, but not limited to a PID, a state feedback, LQR, and/or an adaptive controller, for example. The surgical instrument **750** can include a power source to convert the signal from the feedback controller into a physical input such as case voltage, PWM voltage, frequency modulated voltage, current, torque, and/or force, for example.

[0248] The actual drive system of the surgical instrument **750** is configured to drive the displacement member, cutting member, or I-beam **764**, by a brushed DC motor with gearbox and mechanical links to an articulation and/or knife system. Another example is the electric motor **754** that operates the displacement member and the articulation driver, for example, of an interchangeable shaft assembly. An outside influence is an unmeasured, unpredictable influence of things like tissue, surrounding bodies and friction on the physical system. Such outside influence can be referred to as drag which acts in opposition to the electric motor **754**. The outside influence, such as drag, may cause the operation of the physical system to deviate from a desired operation of the physical system.

[0249] Various example aspects are directed to a surgical instrument **750** comprising an end effector **752** with motor-driven surgical stapling and cutting implements. For example, a motor **754** may drive a displacement member distally and proximally along a longitudinal axis of the end effector **752**. The end effector **752** may comprise a pivotable anvil **766** and, when configured for use, a staple cartridge **768** positioned opposite the anvil **766**. A clinician may grasp tissue between the anvil **766** and the staple cartridge **768**, as described herein. When ready to use the instrument **750**, the clinician may provide a firing signal, for example by depressing a trigger of the instrument **750**. In response to the firing signal, the motor **754** may drive the displacement member distally along the longitudinal axis of the end effector **752** from a proximal stroke begin position to a stroke end position distal of the stroke begin position. As the displacement member translates distally, an I-beam **764** with a cutting element positioned at a distal end, may cut the tissue between the staple cartridge **768** and the anvil **766**.

[0250] In various examples, the surgical instrument **750** may comprise a control circuit **760** programmed to control the distal translation of the displacement member, such as the I-beam **764**, for example, based on one or more tissue conditions. The control circuit **760** may be programmed to sense tissue conditions, such as thickness, either directly or indirectly, as described herein. The control circuit **760** may be programmed to select a firing control program based on tissue conditions. A firing control program may describe the distal motion of the displacement member. Different firing control programs may be selected to better treat different tissue conditions. For example, when thicker tissue is present, the control circuit **760** may be programmed to translate the displacement member at a lower velocity and/or with lower power. When thinner tissue is present, the control circuit **760** may be programmed to translate the displacement member at a higher velocity and/or with higher power.

[0251] In some examples, the control circuit **760** may initially operate the motor **754** in an open loop configuration for a first open loop portion of a stroke of the displacement member. Based on a response of the instrument **750** during the open loop portion of the stroke, the control circuit **760** may select a firing control program. The response of the instrument may include, a translation distance of the displacement member during the open loop portion, a time elapsed during the open loop portion, energy provided to the motor **754** during the open loop portion, a sum of pulse widths of a motor drive signal, etc. After the open loop portion, the control circuit **760** may implement the selected firing control program for a second portion of the displacement member stroke. For example, during the closed loop portion of the stroke, the control circuit **760** may modulate the motor **754** based on translation data describing a position of the displacement member in a closed loop manner to translate the displacement member at a constant velocity. Additional details are disclosed in U.S. patent application Ser. No. 15/720,852, titled SYSTEM AND METHODS FOR CONTROLLING A DISPLAY OF A SURGICAL INSTRUMENT, filed Sep. 29, 2017, which is herein incorporated by reference in its entirety.

[0252] FIG. 19 is a schematic diagram of a surgical instrument **790** configured to control various functions according to one aspect of this disclosure. In one aspect, the surgical instrument **790** is programmed to control distal translation of a displacement member such as the I-beam

764. The surgical instrument **790** comprises an end effector **792** that may comprise an anvil **766**, an I-beam **764**, and a removable staple cartridge **768** which may be interchanged with an RF cartridge **796** (shown in dashed line).

[0253] In one aspect, sensors **788** may be implemented as a limit switch, electromechanical device, solid-state switches, Hall-effect devices, MR devices, GMR devices, magnetometers, among others. In other implementations, the sensors **638** may be solid-state switches that operate under the influence of light, such as optical sensors, IR sensors, ultraviolet sensors, among others. Still, the switches may be solid-state devices such as transistors (e.g., FET, junction FET, MOSFET, bipolar, and the like). In other implementations, the sensors **788** may include electrical conductorless switches, ultrasonic switches, accelerometers, and inertial sensors, among others.

[0254] In one aspect, the position sensor **784** may be implemented as an absolute positioning system comprising a magnetic rotary absolute positioning system implemented as an AS5055EQFT single-chip magnetic rotary position sensor available from Austria Microsystems, AG. The position sensor **784** may interface with the control circuit **760** to provide an absolute positioning system. The position may include multiple Hall-effect elements located above a magnet and coupled to a CORDIC processor, also known as the digit-by-digit method and Volder's algorithm, that is provided to implement a simple and efficient algorithm to calculate hyperbolic and trigonometric functions that require only addition, subtraction, bitshift, and table lookup operations.

[0255] In one aspect, the I-beam **764** may be implemented as a knife member comprising a knife body that operably supports a tissue cutting blade thereon and may further include anvil engagement tabs or features and channel engagement features or a foot. In one aspect, the staple cartridge **768** may be implemented as a standard (mechanical) surgical fastener cartridge. In one aspect, the RF cartridge **796** may be implemented as an RF cartridge. These and other sensors arrangements are described in commonly-owned U.S. patent application Ser. No. 15/628,175, titled TECHNIQUES FOR ADAPTIVE CONTROL OF MOTOR VELOCITY OF A SURGICAL STAPLING AND CUTTING INSTRUMENT, filed Jun. 20, 2017, which is herein incorporated by reference in its entirety.

[0256] The position, movement, displacement, and/or translation of a linear displacement member, such as the I-beam **764**, can be measured by an absolute positioning system, sensor arrangement, and position sensor represented as position sensor **784**. Because the I-beam **764** is coupled to the longitudinally movable drive member, the position of the I-beam **764** can be determined by measuring the position of the longitudinally movable drive member employing the position sensor **784**. Accordingly, in the following description, the position, displacement, and/or translation of the I-beam **764** can be achieved by the position sensor **784** as described herein. A control circuit **760** may be programmed to control the translation of the displacement member, such as the I-beam **764**, as described herein. The control circuit **760**, in some examples, may comprise one or more microcontrollers, microprocessors, or other suitable processors for executing instructions that cause the processor or processors to control the displacement member, e.g., the I-beam **764**, in the manner described. In one aspect, a timer/counter **781** provides an output signal, such as the elapsed time or a

digital count, to the control circuit **760** to correlate the position of the I-beam **764** as determined by the position sensor **784** with the output of the timer/counter **781** such that the control circuit **760** can determine the position of the I-beam **764** at a specific time (t) relative to a starting position. The timer/counter **781** may be configured to measure elapsed time, count external events, or time external events.

[0257] The control circuit **760** may generate a motor set point signal **772**. The motor set point signal **772** may be provided to a motor controller **758**. The motor controller **758** may comprise one or more circuits configured to provide a motor drive signal **774** to the motor **754** to drive the motor **754** as described herein. In some examples, the motor **754** may be a brushed DC electric motor. For example, the velocity of the motor **754** may be proportional to the motor drive signal **774**. In some examples, the motor **754** may be a brushless DC electric motor and the motor drive signal **774** may comprise a PWM signal provided to one or more stator windings of the motor **754**. Also, in some examples, the motor controller **758** may be omitted, and the control circuit **760** may generate the motor drive signal **774** directly.

[0258] The motor **754** may receive power from an energy source **762**. The energy source **762** may be or include a battery, a super capacitor, or any other suitable energy source. The motor **754** may be mechanically coupled to the I-beam **764** via a transmission **756**. The transmission **756** may include one or more gears or other linkage components to couple the motor **754** to the I-beam **764**. A position sensor **784** may sense a position of the I-beam **764**. The position sensor **784** may be or include any type of sensor that is capable of generating position data that indicate a position of the I-beam **764**. In some examples, the position sensor **784** may include an encoder configured to provide a series of pulses to the control circuit **760** as the I-beam **764** translates distally and proximally. The control circuit **760** may track the pulses to determine the position of the I-beam **764**. Other suitable position sensors may be used, including, for example, a proximity sensor. Other types of position sensors may provide other signals indicating motion of the I-beam **764**. Also, in some examples, the position sensor **784** may be omitted. Where the motor **754** is a stepper motor, the control circuit **760** may track the position of the I-beam **764** by aggregating the number and direction of steps that the motor has been instructed to execute. The position sensor **784** may be located in the end effector **792** or at any other portion of the instrument.

[0259] The control circuit **760** may be in communication with one or more sensors **788**. The sensors **788** may be positioned on the end effector **792** and adapted to operate with the surgical instrument **790** to measure the various derived parameters such as gap distance versus time, tissue compression versus time, and anvil strain versus time. The sensors **788** may comprise a magnetic sensor, a magnetic field sensor, a strain gauge, a pressure sensor, a force sensor, an inductive sensor such as an eddy current sensor, a resistive sensor, a capacitive sensor, an optical sensor, and/or any other suitable sensor for measuring one or more parameters of the end effector **792**. The sensors **788** may include one or more sensors.

[0260] The one or more sensors **788** may comprise a strain gauge, such as a micro-strain gauge, configured to measure the magnitude of the strain in the anvil **766** during a clamped condition. The strain gauge provides an electrical signal

whose amplitude varies with the magnitude of the strain. The sensors **788** may comprise a pressure sensor configured to detect a pressure generated by the presence of compressed tissue between the anvil **766** and the staple cartridge **768**. The sensors **788** may be configured to detect impedance of a tissue section located between the anvil **766** and the staple cartridge **768** that is indicative of the thickness and/or fullness of tissue located therebetween.

[0261] The sensors **788** may be configured to measure forces exerted on the anvil **766** by the closure drive system. For example, one or more sensors **788** can be at an interaction point between a closure tube and the anvil **766** to detect the closure forces applied by a closure tube to the anvil **766**. The forces exerted on the anvil **766** can be representative of the tissue compression experienced by the tissue section captured between the anvil **766** and the staple cartridge **768**. The one or more sensors **788** can be positioned at various interaction points along the closure drive system to detect the closure forces applied to the anvil **766** by the closure drive system. The one or more sensors **788** may be sampled in real time during a clamping operation by a processor portion of the control circuit **760**. The control circuit **760** receives real-time sample measurements to provide and analyze time-based information and assess, in real time, closure forces applied to the anvil **766**.

[0262] A current sensor **786** can be employed to measure the current drawn by the motor **754**. The force required to advance the I-beam **764** corresponds to the current drawn by the motor **754**. The force is converted to a digital signal and provided to the control circuit **760**.

[0263] An RF energy source **794** is coupled to the end effector **792** and is applied to the RF cartridge **796** when the RF cartridge **796** is loaded in the end effector **792** in place of the staple cartridge **768**. The control circuit **760** controls the delivery of the RF energy to the RF cartridge **796**.

[0264] Additional details are disclosed in U.S. patent application Ser. No. 15/636,096, titled SURGICAL SYSTEM COUPLABLE WITH STAPLE CARTRIDGE AND RADIO FREQUENCY CARTRIDGE, AND METHOD OF USING SAME, filed Jun. 28, 2017, which is herein incorporated by reference in its entirety.

Generator Hardware

[0265] FIG. 20 is a simplified block diagram of a generator **800** configured to provide inductorless tuning, among other benefits. Additional details of the generator **800** are described in U.S. Pat. No. 9,060,775, titled SURGICAL GENERATOR FOR ULTRASONIC AND ELECTROSURGICAL DEVICES, which issued on Jun. 23, 2015, which is herein incorporated by reference in its entirety. The generator **800** may comprise a patient isolated stage **802** in communication with a non-isolated stage **804** via a power transformer **806**. A secondary winding **808** of the power transformer **806** is contained in the isolated stage **802** and may comprise a tapped configuration (e.g., a center-tapped or a non-center-tapped configuration) to define drive signal outputs **810a**, **810b**, **810c** for delivering drive signals to different surgical instruments, such as, for example, an ultrasonic surgical instrument, an RF electrosurgical instrument, and a multifunction surgical instrument which includes ultrasonic and RF energy modes that can be delivered alone or simultaneously. In particular, drive signal outputs **810a**, **810c** may output an ultrasonic drive signal (e.g., a 420V root-mean-square (RMS) drive signal) to an

ultrasonic surgical instrument, and drive signal outputs **810b**, **810c** may output an RF electrosurgical drive signal (e.g., a 100V RMS drive signal) to an RF electrosurgical instrument, with the drive signal output **810b** corresponding to the center tap of the power transformer **806**.

[0266] In certain forms, the ultrasonic and electrosurgical drive signals may be provided simultaneously to distinct surgical instruments and/or to a single surgical instrument, such as the multifunction surgical instrument, having the capability to deliver both ultrasonic and electrosurgical energy to tissue. It will be appreciated that the electrosurgical signal, provided either to a dedicated electrosurgical instrument and/or to a combined multifunction ultrasonic/electrosurgical instrument may be either a therapeutic or sub-therapeutic level signal where the sub-therapeutic signal can be used, for example, to monitor tissue or instrument conditions and provide feedback to the generator. For example, the ultrasonic and RF signals can be delivered separately or simultaneously from a generator with a single output port in order to provide the desired output signal to the surgical instrument, as will be discussed in more detail below. Accordingly, the generator can combine the ultrasonic and electrosurgical RF energies and deliver the combined energies to the multifunction ultrasonic/electrosurgical instrument. Bipolar electrodes can be placed on one or both jaws of the end effector. One jaw may be driven by ultrasonic energy in addition to electrosurgical RF energy, working simultaneously. The ultrasonic energy may be employed to dissect tissue, while the electrosurgical RF energy may be employed for vessel sealing.

[0267] The non-isolated stage **804** may comprise a power amplifier **812** having an output connected to a primary winding **814** of the power transformer **806**. In certain forms, the power amplifier **812** may comprise a push-pull amplifier. For example, the non-isolated stage **804** may further comprise a logic device **816** for supplying a digital output to a digital-to-analog converter (DAC) circuit **818**, which in turn supplies a corresponding analog signal to an input of the power amplifier **812**. In certain forms, the logic device **816** may comprise a programmable gate array (PGA), a FPGA, programmable logic device (PLD), among other logic circuits, for example. The logic device **816**, by virtue of controlling the input of the power amplifier **812** via the DAC circuit **818**, may therefore control any of a number of parameters (e.g., frequency, waveform shape, waveform amplitude) of drive signals appearing at the drive signal outputs **810a**, **810b**, **810c**. In certain forms and as discussed below, the logic device **816**, in conjunction with a processor (e.g., a DSP discussed below), may implement a number of DSP-based and/or other control algorithms to control parameters of the drive signals output by the generator **800**.

[0268] Power may be supplied to a power rail of the power amplifier **812** by a switch-mode regulator **820**, e.g., a power converter. In certain forms, the switch-mode regulator **820** may comprise an adjustable buck regulator, for example. The non-isolated stage **804** may further comprise a first processor **822**, which in one form may comprise a DSP processor such as an Analog Devices ADSP-21469 SHARC DSP, available from Analog Devices, Norwood, Mass., for example, although in various forms any suitable processor may be employed. In certain forms the DSP processor **822** may control the operation of the switch-mode regulator **820** responsive to voltage feedback data received from the power amplifier **812** by the DSP processor **822** via an ADC circuit

824. In one form, for example, the DSP processor **822** may receive as input, via the ADC circuit **824**, the waveform envelope of a signal (e.g., an RF signal) being amplified by the power amplifier **812**. The DSP processor **822** may then control the switch-mode regulator **820** (e.g., via a PWM output) such that the rail voltage supplied to the power amplifier **812** tracks the waveform envelope of the amplified signal. By dynamically modulating the rail voltage of the power amplifier **812** based on the waveform envelope, the efficiency of the power amplifier **812** may be significantly improved relative to a fixed rail voltage amplifier schemes.

[0269] In certain forms, the logic device **816**, in conjunction with the DSP processor **822**, may implement a digital synthesis circuit such as a direct digital synthesizer control scheme to control the waveform shape, frequency, and/or amplitude of drive signals output by the generator **800**. In one form, for example, the logic device **816** may implement a DDS control algorithm by recalling waveform samples stored in a dynamically updated lookup table (LUT), such as a RAM LUT, which may be embedded in an FPGA. This control algorithm is particularly useful for ultrasonic applications in which an ultrasonic transducer, such as an ultrasonic transducer, may be driven by a clean sinusoidal current at its resonant frequency. Because other frequencies may excite parasitic resonances, minimizing or reducing the total distortion of the motional branch current may correspondingly minimize or reduce undesirable resonance effects. Because the waveform shape of a drive signal output by the generator **800** is impacted by various sources of distortion present in the output drive circuit (e.g., the power transformer **806**, the power amplifier **812**), voltage and current feedback data based on the drive signal may be input into an algorithm, such as an error control algorithm implemented by the DSP processor **822**, which compensates for distortion by suitably pre-distorting or modifying the waveform samples stored in the LUT on a dynamic, ongoing basis (e.g., in real time). In one form, the amount or degree of pre-distortion applied to the LUT samples may be based on the error between a computed motional branch current and a desired current waveform shape, with the error being determined on a sample-by-sample basis. In this way, the pre-distorted LUT samples, when processed through the drive circuit, may result in a motional branch drive signal having the desired waveform shape (e.g., sinusoidal) for optimally driving the ultrasonic transducer. In such forms, the LUT waveform samples will therefore not represent the desired waveform shape of the drive signal, but rather the waveform shape that is required to ultimately produce the desired waveform shape of the motional branch drive signal when distortion effects are taken into account.

[0270] The non-isolated stage **804** may further comprise a first ADC circuit **826** and a second ADC circuit **828** coupled to the output of the power transformer **806** via respective isolation transformers **830**, **832** for respectively sampling the voltage and current of drive signals output by the generator **800**. In certain forms, the ADC circuits **826**, **828** may be configured to sample at high speeds (e.g., 80 mega samples per second (MSPS)) to enable oversampling of the drive signals. In one form, for example, the sampling speed of the ADC circuits **826**, **828** may enable approximately 200× (depending on frequency) oversampling of the drive signals. In certain forms, the sampling operations of the ADC circuit **826**, **828** may be performed by a single ADC circuit receiving input voltage and current signals via a

two-way multiplexer. The use of high-speed sampling in forms of the generator **800** may enable, among other things, calculation of the complex current flowing through the motional branch (which may be used in certain forms to implement DDS-based waveform shape control described above), accurate digital filtering of the sampled signals, and calculation of real power consumption with a high degree of precision. Voltage and current feedback data output by the ADC circuits **826**, **828** may be received and processed (e.g., first-in-first-out (FIFO) buffer, multiplexer) by the logic device **816** and stored in data memory for subsequent retrieval by, for example, the DSP processor **822**. As noted above, voltage and current feedback data may be used as input to an algorithm for pre-distorting or modifying LUT waveform samples on a dynamic and ongoing basis. In certain forms, this may require each stored voltage and current feedback data pair to be indexed based on, or otherwise associated with, a corresponding LUT sample that was output by the logic device **816** when the voltage and current feedback data pair was acquired. Synchronization of the LUT samples and the voltage and current feedback data in this manner contributes to the correct timing and stability of the pre-distortion algorithm.

[0271] In certain forms, the voltage and current feedback data may be used to control the frequency and/or amplitude (e.g., current amplitude) of the drive signals. In one form, for example, voltage and current feedback data may be used to determine impedance phase. The frequency of the drive signal may then be controlled to minimize or reduce the difference between the determined impedance phase and an impedance phase setpoint (e.g., 0°), thereby minimizing or reducing the effects of harmonic distortion and correspondingly enhancing impedance phase measurement accuracy. The determination of phase impedance and a frequency control signal may be implemented in the DSP processor **822**, for example, with the frequency control signal being supplied as input to a DDS control algorithm implemented by the logic device **816**.

[0272] In another form, for example, the current feedback data may be monitored in order to maintain the current amplitude of the drive signal at a current amplitude setpoint. The current amplitude setpoint may be specified directly or determined indirectly based on specified voltage amplitude and power setpoints. In certain forms, control of the current amplitude may be implemented by control algorithm, such as, for example, a proportional-integral-derivative (PID) control algorithm, in the DSP processor **822**. Variables controlled by the control algorithm to suitably control the current amplitude of the drive signal may include, for example, the scaling of the LUT waveform samples stored in the logic device **816** and/or the full-scale output voltage of the DAC circuit **818** (which supplies the input to the power amplifier **812**) via a DAC circuit **834**.

[0273] The non-isolated stage **804** may further comprise a second processor **836** for providing, among other things user interface (UI) functionality. In one form, the UI processor **836** may comprise an Atmel AT91SAM9263 processor having an ARM 926EJ-S core, available from Atmel Corporation, San Jose, Calif., for example. Examples of UI functionality supported by the UI processor **836** may include audible and visual user feedback, communication with peripheral devices (e.g., via a USB interface), communication with a foot switch, communication with an input device (e.g., a touch screen display) and communication with an

output device (e.g., a speaker). The UI processor **836** may communicate with the DSP processor **822** and the logic device **816** (e.g., via SPI buses). Although the UI processor **836** may primarily support UI functionality, it may also coordinate with the DSP processor **822** to implement hazard mitigation in certain forms. For example, the UI processor **836** may be programmed to monitor various aspects of user input and/or other inputs (e.g., touch screen inputs, foot switch inputs, temperature sensor inputs) and may disable the drive output of the generator **800** when an erroneous condition is detected.

[0274] In certain forms, both the DSP processor **822** and the UI processor **836**, for example, may determine and monitor the operating state of the generator **800**. For the DSP processor **822**, the operating state of the generator **800** may dictate, for example, which control and/or diagnostic processes are implemented by the DSP processor **822**. For the UI processor **836**, the operating state of the generator **800** may dictate, for example, which elements of a UI (e.g., display screens, sounds) are presented to a user. The respective DSP and UI processors **822**, **836** may independently maintain the current operating state of the generator **800** and recognize and evaluate possible transitions out of the current operating state. The DSP processor **822** may function as the master in this relationship and determine when transitions between operating states are to occur. The UI processor **836** may be aware of valid transitions between operating states and may confirm if a particular transition is appropriate. For example, when the DSP processor **822** instructs the UI processor **836** to transition to a specific state, the UI processor **836** may verify that requested transition is valid. In the event that a requested transition between states is determined to be invalid by the UI processor **836**, the UI processor **836** may cause the generator **800** to enter a failure mode.

[0275] The non-isolated stage **804** may further comprise a controller **838** for monitoring input devices (e.g., a capacitive touch sensor used for turning the generator **800** on and off, a capacitive touch screen). In certain forms, the controller **838** may comprise at least one processor and/or other controller device in communication with the UI processor **836**. In one form, for example, the controller **838** may comprise a processor (e.g., a Meg168 8-bit controller available from Atmel) configured to monitor user input provided via one or more capacitive touch sensors. In one form, the controller **838** may comprise a touch screen controller (e.g., a QT5480 touch screen controller available from Atmel) to control and manage the acquisition of touch data from a capacitive touch screen.

[0276] In certain forms, when the generator **800** is in a “power off” state, the controller **838** may continue to receive operating power (e.g., via a line from a power supply of the generator **800**, such as the power supply **854** discussed below). In this way, the controller **838** may continue to monitor an input device (e.g., a capacitive touch sensor located on a front panel of the generator **800**) for turning the generator **800** on and off. When the generator **800** is in the power off state, the controller **838** may wake the power supply (e.g., enable operation of one or more DC/DC voltage converters **856** of the power supply **854**) if activation of the “on/off” input device by a user is detected. The controller **838** may therefore initiate a sequence for transitioning the generator **800** to a “power on” state. Conversely, the controller **838** may initiate a sequence for transitioning

the generator **800** to the power off state if activation of the “on/off” input device is detected when the generator **800** is in the power on state. In certain forms, for example, the controller **838** may report activation of the “on/off” input device to the UI processor **836**, which in turn implements the necessary process sequence for transitioning the generator **800** to the power off state. In such forms, the controller **838** may have no independent ability for causing the removal of power from the generator **800** after its power on state has been established.

[0277] In certain forms, the controller **838** may cause the generator **800** to provide audible or other sensory feedback for alerting the user that a power on or power off sequence has been initiated. Such an alert may be provided at the beginning of a power on or power off sequence and prior to the commencement of other processes associated with the sequence.

[0278] In certain forms, the isolated stage **802** may comprise an instrument interface circuit **840** to, for example, provide a communication interface between a control circuit of a surgical instrument (e.g., a control circuit comprising handpiece switches) and components of the non-isolated stage **804**, such as, for example, the logic device **816**, the DSP processor **822**, and/or the UI processor **836**. The instrument interface circuit **840** may exchange information with components of the non-isolated stage **804** via a communication link that maintains a suitable degree of electrical isolation between the isolated and non-isolated stages **802**, **804**, such as, for example, an IR-based communication link. Power may be supplied to the instrument interface circuit **840** using, for example, a low-dropout voltage regulator powered by an isolation transformer driven from the non-isolated stage **804**.

[0279] In one form, the instrument interface circuit **840** may comprise a logic circuit **842** (e.g., logic circuit, programmable logic circuit, PGA, FPGA, PLD) in communication with a signal conditioning circuit **844**. The signal conditioning circuit **844** may be configured to receive a periodic signal from the logic circuit **842** (e.g., a 2 kHz square wave) to generate a bipolar interrogation signal having an identical frequency. The interrogation signal may be generated, for example, using a bipolar current source fed by a differential amplifier. The interrogation signal may be communicated to a surgical instrument control circuit (e.g., by using a conductive pair in a cable that connects the generator **800** to the surgical instrument) and monitored to determine a state or configuration of the control circuit. The control circuit may comprise a number of switches, resistors, and/or diodes to modify one or more characteristics (e.g., amplitude, rectification) of the interrogation signal such that a state or configuration of the control circuit is uniquely discernable based on the one or more characteristics. In one form, for example, the signal conditioning circuit **844** may comprise an ADC circuit for generating samples of a voltage signal appearing across inputs of the control circuit resulting from passage of interrogation signal therethrough. The logic circuit **842** (or a component of the non-isolated stage **804**) may then determine the state or configuration of the control circuit based on the ADC circuit samples.

[0280] In one form, the instrument interface circuit **840** may comprise a first data circuit interface **846** to enable information exchange between the logic circuit **842** (or other element of the instrument interface circuit **840**) and a first data circuit disposed in or otherwise associated with a

surgical instrument. In certain forms, for example, a first data circuit may be disposed in a cable integrally attached to a surgical instrument handpiece or in an adaptor for interfacing a specific surgical instrument type or model with the generator **800**. The first data circuit may be implemented in any suitable manner and may communicate with the generator according to any suitable protocol, including, for example, as described herein with respect to the first data circuit. In certain forms, the first data circuit may comprise a non-volatile storage device, such as an EEPROM device. In certain forms, the first data circuit interface **846** may be implemented separately from the logic circuit **842** and comprise suitable circuitry (e.g., discrete logic devices, a processor) to enable communication between the logic circuit **842** and the first data circuit. In other forms, the first data circuit interface **846** may be integral with the logic circuit **842**.

[0281] In certain forms, the first data circuit may store information pertaining to the particular surgical instrument with which it is associated. Such information may include, for example, a model number, a serial number, a number of operations in which the surgical instrument has been used, and/or any other type of information. This information may be read by the instrument interface circuit **840** (e.g., by the logic circuit **842**), transferred to a component of the non-isolated stage **804** (e.g., to logic device **816**, DSP processor **822**, and/or UI processor **836**) for presentation to a user via an output device and/or for controlling a function or operation of the generator **800**. Additionally, any type of information may be communicated to the first data circuit for storage therein via the first data circuit interface **846** (e.g., using the logic circuit **842**). Such information may comprise, for example, an updated number of operations in which the surgical instrument has been used and/or dates and/or times of its usage.

[0282] As discussed previously, a surgical instrument may be detachable from a handpiece (e.g., the multifunction surgical instrument may be detachable from the handpiece) to promote instrument interchangeability and/or disposability. In such cases, conventional generators may be limited in their ability to recognize particular instrument configurations being used and to optimize control and diagnostic processes accordingly. The addition of readable data circuits to surgical instruments to address this issue is problematic from a compatibility standpoint, however. For example, designing a surgical instrument to remain backwardly compatible with generators that lack the requisite data reading functionality may be impractical due to, for example, differing signal schemes, design complexity, and cost. Forms of instruments discussed herein address these concerns by using data circuits that may be implemented in existing surgical instruments economically and with minimal design changes to preserve compatibility of the surgical instruments with current generator platforms.

[0283] Additionally, forms of the generator **800** may enable communication with instrument-based data circuits. For example, the generator **800** may be configured to communicate with a second data circuit contained in an instrument (e.g., the multifunction surgical instrument). In some forms, the second data circuit may be implemented in a many similar to that of the first data circuit described herein. The instrument interface circuit **840** may comprise a second data circuit interface **848** to enable this communication. In one form, the second data circuit interface **848**

may comprise a tri-state digital interface, although other interfaces may also be used. In certain forms, the second data circuit may generally be any circuit for transmitting and/or receiving data. In one form, for example, the second data circuit may store information pertaining to the particular surgical instrument with which it is associated. Such information may include, for example, a model number, a serial number, a number of operations in which the surgical instrument has been used, and/or any other type of information.

[0284] In some forms, the second data circuit may store information about the electrical and/or ultrasonic properties of an associated ultrasonic transducer, end effector, or ultrasonic drive system. For example, the first data circuit may indicate a burn-in frequency slope, as described herein. Additionally or alternatively, any type of information may be communicated to second data circuit for storage therein via the second data circuit interface **848** (e.g., using the logic circuit **842**). Such information may comprise, for example, an updated number of operations in which the instrument has been used and/or dates and/or times of its usage. In certain forms, the second data circuit may transmit data acquired by one or more sensors (e.g., an instrument-based temperature sensor). In certain forms, the second data circuit may receive data from the generator **800** and provide an indication to a user (e.g., a light emitting diode indication or other visible indication) based on the received data.

[0285] In certain forms, the second data circuit and the second data circuit interface **848** may be configured such that communication between the logic circuit **842** and the second data circuit can be effected without the need to provide additional conductors for this purpose (e.g., dedicated conductors of a cable connecting a handpiece to the generator **800**). In one form, for example, information may be communicated to and from the second data circuit using a one-wire bus communication scheme implemented on existing cabling, such as one of the conductors used transmit interrogation signals from the signal conditioning circuit **844** to a control circuit in a handpiece. In this way, design changes or modifications to the surgical instrument that might otherwise be necessary are minimized or reduced. Moreover, because different types of communications implemented over a common physical channel can be frequency-band separated, the presence of a second data circuit may be “invisible” to generators that do not have the requisite data reading functionality, thus enabling backward compatibility of the surgical instrument.

[0286] In certain forms, the isolated stage **802** may comprise at least one blocking capacitor **850-1** connected to the drive signal output **810b** to prevent passage of DC current to a patient. A single blocking capacitor may be required to comply with medical regulations or standards, for example. While failure in single-capacitor designs is relatively uncommon, such failure may nonetheless have negative consequences. In one form, a second blocking capacitor **850-2** may be provided in series with the blocking capacitor **850-1**, with current leakage from a point between the blocking capacitors **850-1**, **850-2** being monitored by, for example, an ADC circuit **852** for sampling a voltage induced by leakage current. The samples may be received by the logic circuit **842**, for example. Based changes in the leakage current (as indicated by the voltage samples), the generator **800** may determine when at least one of the blocking

capacitors **850-1**, **850-2** has failed, thus providing a benefit over single-capacitor designs having a single point of failure.

[0287] In certain forms, the non-isolated stage **804** may comprise a power supply **854** for delivering DC power at a suitable voltage and current. The power supply may comprise, for example, a 400 W power supply for delivering a 48 VDC system voltage. The power supply **854** may further comprise one or more DC/DC voltage converters **856** for receiving the output of the power supply to generate DC outputs at the voltages and currents required by the various components of the generator **800**. As discussed above in connection with the controller **838**, one or more of the DC/DC voltage converters **856** may receive an input from the controller **838** when activation of the “on/off” input device by a user is detected by the controller **838** to enable operation of, or wake, the DC/DC voltage converters **856**.

[0288] FIG. 21 illustrates an example of a generator **900**, which is one form of the generator **800** (FIG. 20). The generator **900** is configured to deliver multiple energy modalities to a surgical instrument. The generator **900** provides RF and ultrasonic signals for delivering energy to a surgical instrument either independently or simultaneously. The RF and ultrasonic signals may be provided alone or in combination and may be provided simultaneously. As noted above, at least one generator output can deliver multiple energy modalities (e.g., ultrasonic, bipolar or monopolar RF, irreversible and/or reversible electroporation, and/or microwave energy, among others) through a single port, and these signals can be delivered separately or simultaneously to the end effector to treat tissue.

[0289] The generator **900** comprises a processor **902** coupled to a waveform generator **904**. The processor **902** and waveform generator **904** are configured to generate a variety of signal waveforms based on information stored in a memory coupled to the processor **902**, not shown for clarity of disclosure. The digital information associated with a waveform is provided to the waveform generator **904** which includes one or more DAC circuits to convert the digital input into an analog output. The analog output is fed to an amplifier **1106** for signal conditioning and amplification. The conditioned and amplified output of the amplifier **906** is coupled to a power transformer **908**. The signals are coupled across the power transformer **908** to the secondary side, which is in the patient isolation side. A first signal of a first energy modality is provided to the surgical instrument between the terminals labeled ENERGY1 and RETURN. A second signal of a second energy modality is coupled across a capacitor **910** and is provided to the surgical instrument between the terminals labeled ENERGY2 and RETURN. It will be appreciated that more than two energy modalities may be output and thus the subscript “n” may be used to designate that up to n ENERGYn terminals may be provided, where n is a positive integer greater than 1. It also will be appreciated that up to “n” return paths RETURNn may be provided without departing from the scope of the present disclosure.

[0290] A first voltage sensing circuit **912** is coupled across the terminals labeled ENERGY1 and the RETURN path to measure the output voltage therebetween. A second voltage sensing circuit **924** is coupled across the terminals labeled ENERGY2 and the RETURN path to measure the output voltage therebetween. A current sensing circuit **914** is disposed in series with the RETURN leg of the secondary side

of the power transformer **908** as shown to measure the output current for either energy modality. If different return paths are provided for each energy modality, then a separate current sensing circuit should be provided in each return leg. The outputs of the first and second voltage sensing circuits **912**, **924** are provided to respective isolation transformers **916**, **922** and the output of the current sensing circuit **914** is provided to another isolation transformer **918**. The outputs of the isolation transformers **916**, **922**, **922** in the on the primary side of the power transformer **908** (non-patient isolated side) are provided to a one or more ADC circuit **926**. The digitized output of the ADC circuit **926** is provided to the processor **902** for further processing and computation. The output voltages and output current feedback information can be employed to adjust the output voltage and current provided to the surgical instrument and to compute output impedance, among other parameters. Input/output communications between the processor **902** and patient isolated circuits is provided through an interface circuit **920**. Sensors also may be in electrical communication with the processor **902** by way of the interface circuit **920**.

[0291] In one aspect, the impedance may be determined by the processor **902** by dividing the output of either the first voltage sensing circuit **912** coupled across the terminals labeled ENERGY1/RETURN or the second voltage sensing circuit **924** coupled across the terminals labeled ENERGY2/RETURN by the output of the current sensing circuit **914** disposed in series with the RETURN leg of the secondary side of the power transformer **908**. The outputs of the first and second voltage sensing circuits **912**, **924** are provided to separate isolation transformers **916**, **922** and the output of the current sensing circuit **914** is provided to another isolation transformer **916**. The digitized voltage and current sensing measurements from the ADC circuit **926** are provided to the processor **902** for computing impedance. As an example, the first energy modality ENERGY1 may be ultrasonic energy and the second energy modality ENERGY2 may be RF energy. Nevertheless, in addition to ultrasonic and bipolar or monopolar RF energy modalities, other energy modalities include irreversible and/or reversible electroporation and/or microwave energy, among others. Also, although the example illustrated in FIG. 21 shows a single return path RETURN may be provided for two or more energy modalities, in other aspects, multiple return paths RETURNn may be provided for each energy modality ENERGYn. Thus, as described herein, the ultrasonic transducer impedance may be measured by dividing the output of the first voltage sensing circuit **912** by the current sensing circuit **914** and the tissue impedance may be measured by dividing the output of the second voltage sensing circuit **924** by the current sensing circuit **914**.

[0292] As shown in FIG. 21, the generator **900** comprising at least one output port can include a power transformer **908** with a single output and with multiple taps to provide power in the form of one or more energy modalities, such as ultrasonic, bipolar or monopolar RF, irreversible and/or reversible electroporation, and/or microwave energy, among others, for example, to the end effector depending on the type of treatment of tissue being performed. For example, the generator **900** can deliver energy with higher voltage and lower current to drive an ultrasonic transducer, with lower voltage and higher current to drive RF electrodes for sealing tissue, or with a coagulation waveform for spot coagulation using either monopolar or bipolar RF electrosurgical elec-

trodes. The output waveform from the generator 900 can be steered, switched, or filtered to provide the frequency to the end effector of the surgical instrument. The connection of an ultrasonic transducer to the generator 900 output would be preferably located between the output labeled ENERGY1 and RETURN as shown in FIG. 21. In one example, a connection of RF bipolar electrodes to the generator 900 output would be preferably located between the output labeled ENERGY2 and RETURN. In the case of monopolar output, the preferred connections would be active electrode (e.g., pencil or other probe) to the ENERGY2 output and a suitable return pad connected to the RETURN output.

[0293] Additional details are disclosed in U.S. Patent Application Publication No. 2017/0086914, titled TECHNIQUES FOR OPERATING GENERATOR FOR DIGITALLY GENERATING ELECTRICAL SIGNAL WAVEFORMS AND SURGICAL INSTRUMENTS, which published on Mar. 30, 2017, which is herein incorporated by reference in its entirety.

[0294] As used throughout this description, the term “wireless” and its derivatives may be used to describe circuits, devices, systems, methods, techniques, communications channels, etc., that may communicate data through the use of modulated electromagnetic radiation through a non-solid medium. The term does not imply that the associated devices do not contain any wires, although in some aspects they might not. The communication module may implement any of a number of wireless or wired communication standards or protocols, including but not limited to Wi-Fi (IEEE 802.11 family), WiMAX (IEEE 802.16 family), IEEE 802.20, long term evolution (LTE), Ev-DO, HSPA+, HSDPA+, HSUPA+, EDGE, GSM, GPRS, CDMA, TDMA, DECT, Bluetooth, Ethernet derivatives thereof, as well as any other wireless and wired protocols that are designated as 3G, 4G, 5G, and beyond. The computing module may include a plurality of communication modules. For instance, a first communication module may be dedicated to shorter range wireless communications such as Wi-Fi and Bluetooth and a second communication module may be dedicated to longer range wireless communications such as GPS, EDGE, GPRS, CDMA, WiMAX, LTE, Ev-DO, and others.

[0295] As used herein a processor or processing unit is an electronic circuit which performs operations on some external data source, usually memory or some other data stream. The term is used herein to refer to the central processor (central processing unit) in a system or computer systems (especially systems on a chip (SoCs)) that combine a number of specialized “processors.”

[0296] As used herein, a system on a chip or system on chip (SoC or SOC) is an integrated circuit (also known as an “IC” or “chip”) that integrates all components of a computer or other electronic systems. It may contain digital, analog, mixed-signal, and often radio-frequency functions—all on a single substrate. A SoC integrates a microcontroller (or microprocessor) with advanced peripherals like graphics processing unit (GPU), Wi-Fi module, or coprocessor. A SoC may or may not contain built-in memory.

[0297] As used herein, a microcontroller or controller is a system that integrates a microprocessor with peripheral circuits and memory. A microcontroller (or MCU for microcontroller unit) may be implemented as a small computer on a single integrated circuit. It may be similar to a SoC; an SoC may include a microcontroller as one of its components. A

microcontroller may contain one or more core processing units (CPUs) along with memory and programmable input/output peripherals. Program memory in the form of Ferroelectric RAM, NOR flash or OTP ROM is also often included on chip, as well as a small amount of RAM. Microcontrollers may be employed for embedded applications, in contrast to the microprocessors used in personal computers or other general purpose applications consisting of various discrete chips.

[0298] As used herein, the term controller or microcontroller may be a stand-alone IC or chip device that interfaces with a peripheral device. This may be a link between two parts of a computer or a controller on an external device that manages the operation of (and connection with) that device.

[0299] Any of the processors or microcontrollers described herein, may be implemented by any single core or multicore processor such as those known under the trade name ARM Cortex by Texas Instruments. In one aspect, the processor may be an LM4F230H5QR ARM Cortex-M4F Processor Core, available from Texas Instruments, for example, comprising on-chip memory of 256 KB single-cycle flash memory, or other non-volatile memory, up to 40 MHz, a prefetch buffer to improve performance above 40 MHz, a 32 KB single-cycle serial random access memory (SRAM), internal read-only memory (ROM) loaded with StellarisWare® software, 2 KB electrically erasable programmable read-only memory (EEPROM), one or more pulse width modulation (PWM) modules, one or more quadrature encoder inputs (QEI) analog, one or more 12-bit Analog-to-Digital Converters (ADC) with 12 analog input channels, details of which are available for the product datasheet.

[0300] In one aspect, the processor may comprise a safety controller comprising two controller-based families such as TMS570 and RM4x known under the trade name Hercules ARM Cortex R4, also by Texas Instruments. The safety controller may be configured specifically for IEC 61508 and ISO 26262 safety critical applications, among others, to provide advanced integrated safety features while delivering scalable performance, connectivity, and memory options.

[0301] Modular devices include the modules (as described in connection with FIGS. 3 and 9, for example) that are receivable within a surgical hub and the surgical devices or instruments that can be connected to the various modules in order to connect or pair with the corresponding surgical hub. The modular devices include, for example, intelligent surgical instruments, medical imaging devices, suction/irrigation devices, smoke evacuators, energy generators, ventilators, insufflators, and displays. The modular devices described herein can be controlled by control algorithms. The control algorithms can be executed on the modular device itself, on the surgical hub to which the particular modular device is paired, or on both the modular device and the surgical hub (e.g., via a distributed computing architecture). In some exemplifications, the modular devices’ control algorithms control the devices based on data sensed by the modular device itself (i.e., by sensors in, on, or connected to the modular device). This data can be related to the patient being operated on (e.g., tissue properties or insufflation pressure) or the modular device itself (e.g., the rate at which a knife is being advanced, motor current, or energy levels). For example, a control algorithm for a surgical stapling and cutting instrument can control the rate at which

the instrument's motor drives its knife through tissue according to resistance encountered by the knife as it advances.

Situational Awareness

[0302] Situational awareness is the ability of some aspects of a surgical system to determine or infer information related to a surgical procedure from data received from databases and/or instruments. The information can include the type of procedure being undertaken, the type of tissue being operated on, or the body cavity that is the subject of the procedure. With the contextual information related to the surgical procedure, the surgical system can, for example, improve the manner in which it controls the modular devices (e.g. a robotic arm and/or robotic surgical tool) that are connected to it and provide contextualized information or suggestions to the surgeon during the course of the surgical procedure.

[0303] Referring now to FIG. 49, a timeline 5200 depicting situational awareness of a hub, such as the surgical hub 106 or 206, for example, is depicted. The timeline 5200 is an illustrative surgical procedure and the contextual information that the surgical hub 106, 206 can derive from the data received from the data sources at each step in the surgical procedure. The timeline 5200 depicts the typical steps that would be taken by the nurses, surgeons, and other medical personnel during the course of a lung segmentectomy procedure, beginning with setting up the operating theater and ending with transferring the patient to a post-operative recovery room.

[0304] The situationally aware surgical hub 106, 206 receives data from the data sources throughout the course of the surgical procedure, including data generated each time medical personnel utilize a modular device that is paired with the surgical hub 106, 206. The surgical hub 106, 206 can receive this data from the paired modular devices and other data sources and continually derive inferences (i.e., contextual information) about the ongoing procedure as new data is received, such as which step of the procedure is being performed at any given time. The situational awareness system of the surgical hub 106, 206 is able to, for example, record data pertaining to the procedure for generating reports, verify the steps being taken by the medical personnel, provide data or prompts (e.g., via a display screen) that may be pertinent for the particular procedural step, adjust modular devices based on the context (e.g., activate monitors, adjust the field of view (FOV) of the medical imaging device, or change the energy level of an ultrasonic surgical instrument or RF electrosurgical instrument), and take any other such action described above.

[0305] As the first step S202 in this illustrative procedure, the hospital staff members retrieve the patient's Electronic Medical Record (EMR) from the hospital's EMR database. Based on select patient data in the EMR, the surgical hub 106, 206 determines that the procedure to be performed is a thoracic procedure.

[0306] Second step S204, the staff members scan the incoming medical supplies for the procedure. The surgical hub 106, 206 cross-references the scanned supplies with a list of supplies that are utilized in various types of procedures and confirms that the mix of supplies corresponds to a thoracic procedure. Further, the surgical hub 106, 206 is also able to determine that the procedure is not a wedge procedure (because the incoming supplies either lack certain

supplies that are necessary for a thoracic wedge procedure or do not otherwise correspond to a thoracic wedge procedure).

[0307] Third step S206, the medical personnel scan the patient band via a scanner that is communicably connected to the surgical hub 106, 206. The surgical hub 106, 206 can then confirm the patient's identity based on the scanned data.

[0308] Fourth step S208, the medical staff turns on the auxiliary equipment. The auxiliary equipment being utilized can vary according to the type of surgical procedure and the techniques to be used by the surgeon, but in this illustrative case they include a smoke evacuator, insufflator, and medical imaging device. When activated, the auxiliary equipment that are modular devices can automatically pair with the surgical hub 106, 206 that is located within a particular vicinity of the modular devices as part of their initialization process. The surgical hub 106, 206 can then derive contextual information about the surgical procedure by detecting the types of modular devices that pair with it during this pre-operative or initialization phase. In this particular example, the surgical hub 106, 206 determines that the surgical procedure is a VATS procedure based on this particular combination of paired modular devices. Based on the combination of the data from the patient's EMR, the list of medical supplies to be used in the procedure, and the type of modular devices that connect to the hub, the surgical hub 106, 206 can generally infer the specific procedure that the surgical team will be performing. Once the surgical hub 106, 206 knows what specific procedure is being performed, the surgical hub 106, 206 can then retrieve the steps of that procedure from a memory or from the cloud and then cross-reference the data it subsequently receives from the connected data sources (e.g., modular devices and patient monitoring devices) to infer what step of the surgical procedure the surgical team is performing.

[0309] Fifth step S210, the staff members attach the EKG electrodes and other patient monitoring devices to the patient. The EKG electrodes and other patient monitoring devices are able to pair with the surgical hub 106, 206. As the surgical hub 106, 206 begins receiving data from the patient monitoring devices, the surgical hub 106, 206 thus confirms that the patient is in the operating theater.

[0310] Sixth step S212, the medical personnel induce anesthesia in the patient. The surgical hub 106, 206 can infer that the patient is under anesthesia based on data from the modular devices and/or patient monitoring devices, including EKG data, blood pressure data, ventilator data, or combinations thereof, for example. Upon completion of the sixth step S212, the pre-operative portion of the lung segmentectomy procedure is completed and the operative portion begins.

[0311] Seventh step S214, the patient's lung that is being operated on is collapsed (while ventilation is switched to the contralateral lung). The surgical hub 106, 206 can infer from the ventilator data that the patient's lung has been collapsed, for example. The surgical hub 106, 206 can infer that the operative portion of the procedure has commenced as it can compare the detection of the patient's lung collapsing to the expected steps of the procedure (which can be accessed or retrieved previously) and thereby determine that collapsing the lung is the first operative step in this particular procedure.

[0312] Eighth step S216, the medical imaging device (e.g., a scope) is inserted and video from the medical imaging device is initiated. The surgical hub 106, 206 receives the

medical imaging device data (i.e., video or image data) through its connection to the medical imaging device. Upon receipt of the medical imaging device data, the surgical hub **106, 206** can determine that the laparoscopic portion of the surgical procedure has commenced. Further, the surgical hub **106, 206** can determine that the particular procedure being performed is a segmentectomy, as opposed to a lobectomy (note that a wedge procedure has already been discounted by the surgical hub **106, 206** based on data received at the second step **S204** of the procedure). The data from the medical imaging device **124** (FIG. 2) can be utilized to determine contextual information regarding the type of procedure being performed in a number of different ways, including by determining the angle at which the medical imaging device is oriented with respect to the visualization of the patient's anatomy, monitoring the number or medical imaging devices being utilized (i.e., that are activated and paired with the surgical hub **106, 206**), and monitoring the types of visualization devices utilized. For example, one technique for performing a VATS lobectomy places the camera in the lower anterior corner of the patient's chest cavity above the diaphragm, whereas one technique for performing a VATS segmentectomy places the camera in an anterior intercostal position relative to the segmental fissure. Using pattern recognition or machine learning techniques, for example, the situational awareness system can be trained to recognize the positioning of the medical imaging device according to the visualization of the patient's anatomy. As another example, one technique for performing a VATS lobectomy utilizes a single medical imaging device, whereas another technique for performing a VATS segmentectomy utilizes multiple cameras. As yet another example, one technique for performing a VATS segmentectomy utilizes an infrared light source (which can be communicably coupled to the surgical hub as part of the visualization system) to visualize the segmental fissure, which is not utilized in a VATS lobectomy. By tracking any or all of this data from the medical imaging device, the surgical hub **106, 206** can thereby determine the specific type of surgical procedure being performed and/or the technique being used for a particular type of surgical procedure.

[0313] Ninth step **S218**, the surgical team begins the dissection step of the procedure. The surgical hub **106, 206** can infer that the surgeon is in the process of dissecting to mobilize the patient's lung because it receives data from the RF or ultrasonic generator indicating that an energy instrument is being fired. The surgical hub **106, 206** can cross-reference the received data with the retrieved steps of the surgical procedure to determine that an energy instrument being fired at this point in the process (i.e., after the completion of the previously discussed steps of the procedure) corresponds to the dissection step. In certain instances, the energy instrument can be an energy tool mounted to a robotic arm of a robotic surgical system.

[0314] Tenth step **S220**, the surgical team proceeds to the ligation step of the procedure. The surgical hub **106, 206** can infer that the surgeon is ligating arteries and veins because it receives data from the surgical stapling and cutting instrument indicating that the instrument is being fired. Similarly to the prior step, the surgical hub **106, 206** can derive this inference by cross-referencing the receipt of data from the surgical stapling and cutting instrument with the retrieved

steps in the process. In certain instances, the surgical instrument can be a surgical tool mounted to a robotic arm of a robotic surgical system.

[0315] Eleventh step **S222**, the segmentectomy portion of the procedure is performed. The surgical hub **106, 206** can infer that the surgeon is transecting the parenchyma based on data from the surgical stapling and cutting instrument, including data from its cartridge. The cartridge data can correspond to the size or type of staple being fired by the instrument, for example. As different types of staples are utilized for different types of tissues, the cartridge data can thus indicate the type of tissue being stapled and/or transected. In this case, the type of staple being fired is utilized for parenchyma (or other similar tissue types), which allows the surgical hub **106, 206** to infer that the segmentectomy portion of the procedure is being performed.

[0316] Twelfth step **S224**, the node dissection step is then performed. The surgical hub **106, 206** can infer that the surgical team is dissecting the node and performing a leak test based on data received from the generator indicating that an RF or ultrasonic instrument is being fired. For this particular procedure, an RF or ultrasonic instrument being utilized after parenchyma was transected corresponds to the node dissection step, which allows the surgical hub **106, 206** to make this inference. It should be noted that surgeons regularly switch back and forth between surgical stapling/cutting instruments and surgical energy (i.e., RF or ultrasonic) instruments depending upon the particular step in the procedure because different instruments are better adapted for particular tasks. Therefore, the particular sequence in which the stapling/cutting instruments and surgical energy instruments are used can indicate what step of the procedure the surgeon is performing. Moreover, in certain instances, robotic tools can be utilized for one or more steps in a surgical procedure and/or handheld surgical instruments can be utilized for one or more steps in the surgical procedure. The surgeon(s) can alternate between robotic tools and handheld surgical instruments and/or can use the devices concurrently, for example. Upon completion of the twelfth step **S224**, the incisions are closed up and the post-operative portion of the procedure begins.

[0317] Thirteenth step **S226**, the patient's anesthesia is reversed. The surgical hub **106, 206** can infer that the patient is emerging from the anesthesia based on the ventilator data (i.e., the patient's breathing rate begins increasing), for example.

[0318] Lastly, the fourteenth step **S228** is that the medical personnel remove the various patient monitoring devices from the patient. The surgical hub **106, 206** can thus infer that the patient is being transferred to a recovery room when the hub loses EKG, BP, and other data from the patient monitoring devices. As can be seen from the description of this illustrative procedure, the surgical hub **106, 206** can determine or infer when each step of a given surgical procedure is taking place according to data received from the various data sources that are communicably coupled to the surgical hub **106, 206**.

[0319] Situational awareness is further described in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety. In certain instances, operation of a robotic surgical system, including the various robotic surgical systems disclosed herein, for example, can be con-

trolled by the hub **106**, **206** based on its situational awareness and/or feedback from the components thereof and/or based on information from the cloud **104**.

Robotic Systems

[0320] Robotic surgical systems can be used in minimally invasive medical procedures. During such medical procedures, a patient can be placed on a platform adjacent to a robotic surgical system, and a surgeon can be positioned at a command console that is remote from the platform and/or from the robot. For example, the surgeon can be positioned outside the sterile field that surrounds the surgical site. The surgeon provides input to a user interface via an input device at the command console to manipulate a surgical tool coupled to an arm of the robotic system. The input device can be a mechanical input devices such as control handles or joysticks, for example, or contactless input devices such as optical gesture sensors, for example.

[0321] The robotic surgical system can include a robot tower supporting one or more robotic arms. At least one surgical tool (e.g. an end effector and/or endoscope) can be mounted to the robotic arm. The surgical tool(s) can be configured to articulate relative to the respective robotic arm via an articulating wrist assembly and/or to translate relative to the robotic arm via a linear slide mechanism, for example. During the surgical procedure, the surgical tool can be inserted into a small incision in a patient via a cannula or trocar, for example, or into a natural orifice of the patient to position the distal end of the surgical tool at the surgical site within the body of the patient. Additionally or alternatively, the robotic surgical system can be employed in an open surgical procedure in certain instances.

[0322] A schematic of a robotic surgical system **15000** is depicted in FIG. 22. The robotic surgical system **15000** includes a central control unit **15002**, a surgeon's console **15012**, a robot **15022** including one or more robotic arms **15024**, and a primary display **15040** operably coupled to the control unit **15002**. The surgeon's console **15012** includes a display **15014** and at least one manual input device **15016** (e.g., switches, buttons, touch screens, joysticks, gimbals, etc.) that allow the surgeon to telemanipulate the robotic arms **15024** of the robot **15022**. The reader will appreciate that additional and alternative input devices can be employed.

[0323] The central control unit **15002** includes a processor **15004** operably coupled to a memory **15006**. The processor **15004** includes a plurality of inputs and outputs for interfacing with the components of the robotic surgical system **15000**. The processor **15004** can be configured to receive input signals and/or generate output signals to control one or more of the various components (e.g., one or more motors, sensors, and/or displays) of the robotic surgical system **15000**. The output signals can include, and/or can be based upon, algorithmic instructions which may be pre-programmed and/or input by the surgeon or another clinician. The processor **15004** can be configured to accept a plurality of inputs from a user, such as the surgeon at the console **15012**, and/or may interface with a remote system. The memory **15006** can be directly and/or indirectly coupled to the processor **15004** to store instructions and/or databases.

[0324] The robot **15022** includes one or more robotic arms **15024**. Each robotic arm **15024** includes one or more motors **15026** and each motor **15026** is coupled to one or more motor drivers **15028**. For example, the motors **15026**, which

can be assigned to different drivers and/or mechanisms, can be housed in a carriage assembly or housing. In certain instances, a transmission intermediate a motor **15026** and one or more drivers **15028** can permit coupling and decoupling of the motor **15026** to one or more drivers **15028**. The drivers **15028** can be configured to implement one or more surgical functions. For example, one or more drivers **15028** can be tasked with moving a robotic arm **15024** by rotating the robotic arm **15024** and/or a linkage and/or joint thereof. Additionally, one or more drivers **15028** can be coupled to a surgical tool **15030** and can implement articulating, rotating, clamping, sealing, stapling, energizing, firing, cutting, and/or opening, for example. In certain instances, the surgical tools **15030** can be interchangeable and/or replaceable. Examples of robotic surgical systems and surgical tools are further described herein.

[0325] The reader will readily appreciate that the computer-implemented interactive surgical system **100** (FIG. 1) and the computer-implemented interactive surgical system **200** (FIG. 9) can incorporate the robotic surgical system **15000**. Additionally or alternatively, the robotic surgical system **15000** can include various features and/or components of the computer-implemented interactive surgical systems **100** and **200**.

[0326] In one exemplification, the robotic surgical system **15000** can encompass the robotic system **110** (FIG. 2), which includes the surgeon's console **118**, the surgical robot **120**, and the robotic hub **122**. Additionally or alternatively, the robotic surgical system **15000** can communicate with another hub, such as the surgical hub **106**, for example. In one instance, the robotic surgical system **15000** can be incorporated into a surgical system, such as the computer-implemented interactive surgical system **100** (FIG. 1) or the computer-implemented interactive surgical system **200** (FIG. 9), for example. In such instances, the robotic surgical system **15000** may interact with the cloud **104** or the cloud **204**, respectively, and the surgical hub **106** or the surgical hub **206**, respectively. In certain instances, a robotic hub or a surgical hub can include the central control unit **15002** and/or the central control unit **15002** can communicate with a cloud. In other instances, a surgical hub can embody a discrete unit that is separate from the central control unit **15002** and which can communicate with the central control unit **15002**.

[0327] Another robotic surgical system is depicted in FIGS. 23 and 24. With reference to FIG. 23, the robotic surgical system **13000** includes robotic arms **13002**, **13003**, a control device **13004**, and a console **13005** coupled to the control device **13004**. As illustrated in FIG. 23, the surgical system **13000** is configured for use on a patient **13013** lying on a patient table **13012** for performance of a minimally invasive surgical operation. The console **13005** includes a display device **13006** and input devices **13007**, **13008**. The display device **13006** is set up to display three-dimensional images, and the manual input devices **13007**, **13008** are configured to allow a clinician to telemanipulate the robotic arms **13002**, **13003**. Controls for a surgeon's console, such as the console **13005**, are further described in International Patent Publication No. WO2017/075121, filed Oct. 27, 2016, titled HAPTIC FEEDBACK FOR A ROBOTIC SURGICAL SYSTEM INTERFACE, which is herein incorporated by reference in its entirety.

[0328] Each of the robotic arms **13002**, **13003** is made up of a plurality of members connected through joints and

includes a surgical assembly **13010** connected to a distal end of a corresponding robotic arm **13002**, **13003**. Support of multiple arms is further described in U.S. Patent Application Publication No. 2017/0071693, filed Nov. 11, 2016, titled SURGICAL ROBOTIC ARM SUPPORT SYSTEMS AND METHODS OF USE, which is herein incorporated by reference in its entirety. Various robotic arm configurations are further described in International Patent Publication No. WO2017/044406, filed Sep. 6, 2016, titled ROBOTIC SURGICAL CONTROL SCHEME FOR MANIPULATING ROBOTIC END EFFECTORS, which is herein incorporated by reference in its entirety. In an exemplification, the surgical assembly **13010** includes a surgical instrument **13020** supporting an end effector **13023**. Although two robotic arms **13002**, **13003**, are depicted, the surgical system **13000** may include a single robotic arm or more than two robotic arms **13002**, **13003**. Additional robotic arms are likewise connected to the control device **13004** and are telemanipulatable via the console **13005**. Accordingly, one or more additional surgical assemblies **13010** and/or surgical instruments **13020** may also be attached to the additional robotic arm(s).

[0329] The robotic arms **13002**, **13003** may be driven by electric drives that are connected to the control device **13004**. According to an exemplification, the control device **13004** is configured to activate drives, for example, via a computer program, such that the robotic arms **13002**, **13003** and the surgical assemblies **13010** and/or surgical instruments **13020** corresponding to the robotic arms **13002**, **13003**, execute a desired movement received through the manual input devices **13007**, **13008**. The control device **13004** may also be configured to regulate movement of the robotic arms **13002**, **13003** and/or of the drives.

[0330] The control device **13004** may control a plurality of motors (for example, Motor 1 . . . n) with each motor configured to drive a pushing or a pulling of one or more cables, such as cables coupled to the end effector **13023** of the surgical instrument **13020**. In use, as these cables are pushed and/or pulled, the one or more cables affect operation and/or movement of the end effector **13023**. The control device **13004** coordinates the activation of the various motors to coordinate a pushing or a pulling motion of one or more cables in order to coordinate an operation and/or movement of one or more end effectors **13023**. For example, articulation of an end effector by a robotic assembly such as the surgical assembly **13010** is further described in U.S. Patent Application Publication No. 2016/0303743, filed Jun. 6, 2016, titled WRIST AND JAW ASSEMBLIES FOR ROBOTIC SURGICAL SYSTEMS and in International Patent Publication No. WO2016/144937, filed Mar. 8, 2016, titled MEASURING HEALTH OF A CONNECTOR MEMBER OF A ROBOTIC SURGICAL SYSTEM, each of which is herein incorporated by reference in its entirety. In an exemplification, each motor is configured to actuate a drive rod or a lever arm to affect operation and/or movement of end effectors **13023** in addition to, or instead of, one or more cables.

[0331] Driver configurations for surgical instruments, such as drive arrangements for a surgical end effector, are further described in International Patent Publication No. WO2016/183054, filed May 10, 2016, titled COUPLING INSTRUMENT DRIVE UNIT AND ROBOTIC SURGICAL INSTRUMENT, International Patent Publication No. WO2016/205266, filed Jun. 15, 2016, titled ROBOTIC

SURGICAL SYSTEM TORQUE TRANSDUCTION SENSING, International Patent Publication No. WO2016/205452, filed Jun. 16, 2016, titled CONTROLLING ROBOTIC SURGICAL INSTRUMENTS WITH BIDIRECTIONAL COUPLING, and International Patent Publication No. WO2017/053507, filed Sep. 22, 2016, titled ELASTIC SURGICAL INTERFACE FOR ROBOTIC SURGICAL SYSTEMS, each of which is herein incorporated by reference in its entirety. The modular attachment of surgical instruments to a driver is further described in International Patent Publication No. WO2016/209769, filed Jun. 20, 2016, titled ROBOTIC SURGICAL ASSEMBLIES, which is herein incorporated by reference in its entirety. Housing configurations for a surgical instrument driver and interface are further described in International Patent Publication No. WO2016/144998, filed Mar. 9, 2016, titled ROBOTIC SURGICAL SYSTEMS, INSTRUMENT DRIVE UNITS, AND DRIVE ASSEMBLIES, which is herein incorporated by reference in its entirety. Various endocutter instrument configurations for use with the robotic arms **13002**, **13003** are further described in International Patent Publication No. WO2017/053358, filed Sep. 21, 2016, titled SURGICAL ROBOTIC ASSEMBLIES AND INSTRUMENT ADAPTERS THEREOF and International Patent Publication No. WO2017/053363, filed Sep. 21, 2016, titled ROBOTIC SURGICAL ASSEMBLIES AND INSTRUMENT DRIVE CONNECTORS THEREOF, each of which is herein incorporated by reference in its entirety. Bipolar instrument configurations for use with the robotic arms **13002**, **13003** are further described in International Patent Publication No. WO2017/053698, filed Sep. 23, 2016, titled ROBOTIC SURGICAL ASSEMBLIES AND ELECTROMECHANICAL INSTRUMENTS THEREOF, which is herein incorporated by reference in its entirety. Repositionable shaft arrangements for use with the robotic arms **13002**, **13003** are further described in International Patent Publication No. WO2017/116793, filed Dec. 19, 2016, titled ROBOTIC SURGICAL SYSTEMS AND INSTRUMENT DRIVE ASSEMBLIES, which is herein incorporated by reference in its entirety.

[0332] The control device **13004** includes any suitable logic control circuit adapted to perform calculations and/or operate according to a set of instructions. The control device **13004** can be configured to communicate with a remote system “RS,” either via a wireless (e.g., Bluetooth, LTE, etc.) and/or wired connection. The remote system “RS” can include data, instructions and/or information related to the various components, algorithms, and/or operations of system **13000**. The remote system “RS” can include any suitable electronic service, database, platform, cloud “C” (see FIG. 23), or the like. The control device **13004** may include a central processing unit operably connected to memory. The memory may include transitory type memory (e.g., RAM) and/or non-transitory type memory (e.g., flash media, disk media, etc.). In some exemplifications, the memory is part of, and/or operably coupled to, the remote system “RS”.

[0333] The control device **13004** can include a plurality of inputs and outputs for interfacing with the components of the system **13000**, such as through a driver circuit. The control device **13004** can be configured to receive input signals and/or generate output signals to control one or more of the various components (e.g., one or more motors) of the system **13000**. The output signals can include, and/or can be

based upon, algorithmic instructions which may be pre-programmed and/or input by a user. The control device **13004** can be configured to accept a plurality of user inputs from a user interface (e.g., switches, buttons, touch screen, etc. of operating the console **13005**) which may be coupled to remote system “RS.”

[0334] A memory **13014** can be directly and/or indirectly coupled to the control device **13004** to store instructions and/or databases including pre-operative data from living being(s) and/or anatomical atlas(es). The memory **13014** can be part of, and/or or operatively coupled to, remote system “RS.”

[0335] In accordance with an exemplification, the distal end of each robotic arm **13002**, **13003** is configured to releasably secure the end effector **13023** (or other surgical tool) therein and may be configured to receive any number of surgical tools or instruments, such as a trocar or retractor, for example.

[0336] A simplified functional block diagram of a system architecture **13400** of the robotic surgical system **13010** is depicted in FIG. 24. The system architecture **13400** includes a core module **13420**, a surgeon master module **13430**, a robotic arm module **13440**, and an instrument module **13450**. The core module **13420** serves as a central controller for the robotic surgical system **13000** and coordinates operations of all of the other modules **13430**, **13440**, **13450**. For example, the core module **13420** maps control devices to the arms **13002**, **13003**, determines current status, performs all kinematics and frame transformations, and relays resulting movement commands. In this regard, the core module **13420** receives and analyzes data from each of the other modules **13430**, **13440**, **13450** in order to provide instructions or commands to the other modules **13430**, **13440**, **13450** for execution within the robotic surgical system **13000**. Although depicted as separate modules, one or more of the modules **13420**, **13430**, **13440**, and **13450** are a single component in other exemplifications.

[0337] The core module **13420** includes models **13422**, observers **13424**, a collision manager **13426**, controllers **13428**, and a skeleton **13429**. The models **13422** include units that provide abstracted representations (base classes) for controlled components, such as the motors (for example, Motor 1 . . . n) and/or the arms **13002**, **13003**. The observers **13424** create state estimates based on input and output signals received from the other modules **13430**, **13440**, **13450**. The collision manager **13426** prevents collisions between components that have been registered within the system **13010**. The skeleton **13429** tracks the system **13010** from a kinematic and dynamics point of view. For example, the kinematics item may be implemented either as forward or inverse kinematics, in an exemplification. The dynamics item may be implemented as algorithms used to model dynamics of the system’s components.

[0338] The surgeon master module **13430** communicates with surgeon control devices at the console **13005** and relays inputs received from the console **13005** to the core module **13420**. In accordance with an exemplification, the surgeon master module **13430** communicates button status and control device positions to the core module **13420** and includes a node controller **13432** that includes a state/mode manager **13434**, a fail-over controller **13436**, and a N-degree of freedom (“DOF”) actuator **13438**.

[0339] The robotic arm module **13440** coordinates operation of a robotic arm subsystem, an arm cart subsystem, a set

up arm, and an instrument subsystem in order to control movement of a corresponding arm **13002**, **13003**. Although a single robotic arm module **13440** is included, it will be appreciated that the robotic arm module **13440** corresponds to and controls a single arm. As such, additional robotic arm modules **13440** are included in configurations in which the system **13010** includes multiple arms **13002**, **13003**. The robotic arm module **13440** includes a node controller **13442**, a state/mode manager **13444**, a fail-over controller **13446**, and a N-degree of freedom (“DOF”) actuator **13348**.

[0340] The instrument module **13450** controls movement of an instrument and/or tool component attached to the arm **13002**, **13003**. The instrument module **13450** is configured to correspond to and control a single instrument. Thus, in configurations in which multiple instruments are included, additional instrument modules **13450** are likewise included. In an exemplification, the instrument module **13450** obtains and communicates data related to the position of the end effector or jaw assembly (which may include the pitch and yaw angle of the jaws), the width of or the angle between the jaws, and the position of an access port. The instrument module **13450** has a node controller **13452**, a state/mode manager **13454**, a fail-over controller **13456**, and a N-degree of freedom (“DOF”) actuator **13458**.

[0341] The position data collected by the instrument module **13450** is used by the core module **13420** to determine when the instrument is within the surgical site, within a cannula, adjacent to an access port, or above an access port in free space. The core module **13420** can determine whether to provide instructions to open or close the jaws of the instrument based on the positioning thereof. For example, when the position of the instrument indicates that the instrument is within a cannula, instructions are provided to maintain a jaw assembly in a closed position. When the position of the instrument indicates that the instrument is outside of an access port, instructions are provided to open the jaw assembly.

[0342] Additional features and operations of a robotic surgical system, such as the surgical robot system depicted in FIGS. 23 and 24, are further described in the following references, each of which is herein incorporated by reference in its entirety:

[0343] U.S. Patent Application Publication No. 2016/0303743, filed Jun. 6, 2016, titled WRIST AND JAW ASSEMBLIES FOR ROBOTIC SURGICAL SYSTEMS;

[0344] U.S. Patent Application Publication No. 2017/0071693, filed Nov. 11, 2016, titled SURGICAL ROBOTIC ARM SUPPORT SYSTEMS AND METHODS OF USE;

[0345] International Patent Publication No. WO2016/144937, filed Mar. 8, 2016, titled MEASURING HEALTH OF A CONNECTOR MEMBER OF A ROBOTIC SURGICAL SYSTEM;

[0346] International Patent Publication No. WO2016/144998, filed Mar. 9, 2016, titled ROBOTIC SURGICAL SYSTEMS, INSTRUMENT DRIVE UNITS, AND DRIVE ASSEMBLIES;

[0347] International Patent Publication No. WO2016/183054, filed May 10, 2016, titled COUPLING INSTRUMENT DRIVE UNIT AND ROBOTIC SURGICAL INSTRUMENT;

- [0348] International Patent Publication No. WO2016/205266, filed Jun. 15, 2016, titled ROBOTIC SURGICAL SYSTEM TORQUE TRANSDUCTION SENSING;
- [0349] International Patent Publication No. WO2016/205452, filed Jun. 16, 2016, titled CONTROLLING ROBOTIC SURGICAL INSTRUMENTS WITH BIDIRECTIONAL COUPLING;
- [0350] International Patent Publication No. WO2016/209769, filed Jun. 20, 2016, titled ROBOTIC SURGICAL ASSEMBLIES;
- [0351] International Patent Publication No. WO2017/044406, filed Sep. 6, 2016, titled ROBOTIC SURGICAL CONTROL SCHEME FOR MANIPULATING ROBOTIC END EFFECTORS;
- [0352] International Patent Publication No. WO2017/053358, filed Sep. 21, 2016, titled SURGICAL ROBOTIC ASSEMBLIES AND INSTRUMENT ADAPTERS THEREOF;
- [0353] International Patent Publication No. WO2017/053363, filed Sep. 21, 2016, titled ROBOTIC SURGICAL ASSEMBLIES AND INSTRUMENT DRIVE CONNECTORS THEREOF;
- [0354] International Patent Publication No. WO2017/053507, filed Sep. 22, 2016, titled ELASTIC SURGICAL INTERFACE FOR ROBOTIC SURGICAL SYSTEMS;
- [0355] International Patent Publication No. WO2017/053698, filed Sep. 23, 2016, titled ROBOTIC SURGICAL ASSEMBLIES AND ELECTROMECHANICAL INSTRUMENTS THEREOF;
- [0356] International Patent Publication No. WO2017/075121, filed Oct. 27, 2016, titled HAPTIC FEEDBACK CONTROLS FOR A ROBOTIC SURGICAL SYSTEM INTERFACE;
- [0357] International Patent Publication No. WO2017/116793, filed Dec. 19, 2016, titled ROBOTIC SURGICAL SYSTEMS AND INSTRUMENT DRIVE ASSEMBLIES.

[0358] The robotic surgical systems and features disclosed herein can be employed with the robotic surgical system of FIGS. 23 and 24. The reader will further appreciate that various systems and/or features disclosed herein can also be employed with alternative surgical systems including the computer-implemented interactive surgical system 100, the computer-implemented interactive surgical system 200, the robotic surgical system 110, the robotic hub 122, the robotic hub 222, and/or the robotic surgical system 15000, for example.

[0359] In various instances, a robotic surgical system can include a robotic control tower, which can house the control unit of the system. For example, the control unit 13004 of the robotic surgical system 13000 (FIG. 23) can be housed within a robotic control tower. The robotic control tower can include a robotic hub such as the robotic hub 122 (FIG. 2) or the robotic hub 222 (FIG. 9), for example. Such a robotic hub can include a modular interface for coupling with one or more generators, such as an ultrasonic generator and/or a radio frequency generator, and/or one or more modules, such as an imaging module, suction module, an irrigation module, a smoke evacuation module, and/or a communication module.

[0360] A robotic hub can include a situational awareness module, which can be configured to synthesize data from

multiple sources to determine an appropriate response to a surgical event. For example, a situational awareness module can determine the type of surgical procedure, step in the surgical procedure, type of tissue, and/or tissue characteristics, as further described herein. Moreover, such a module can recommend a particular course of action or possible choices to the robotic system based on the synthesized data. In various instances, a sensor system encompassing a plurality of sensors distributed throughout the robotic system can provide data, images, and/or other information to the situational awareness module. Such a situational awareness module can be incorporated into a control unit, such as the control unit 13004, for example. In various instances, the situational awareness module can obtain data and/or information from a non-robotic surgical hub and/or a cloud, such as the surgical hub 106 (FIG. 1), the surgical hub 206 (FIG. 10), the cloud 104 (FIG. 1), and/or the cloud 204 (FIG. 9), for example. Situational awareness of a surgical system is further disclosed herein and in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, and U.S. Provisional Patent Application Ser. No. 62/611,340, titled CLOUD-BASED MEDICAL ANALYTICS, filed Dec. 28, 2017, the disclosure of each of which is herein incorporated by reference in its entirety.

[0361] In certain instances, the activation of a surgical tool at certain times during a surgical procedure and/or for certain durations may cause tissue trauma and/or may prolong a surgical procedure. For example, a robotic surgical system can utilize an electrosurgical tool having an energy delivery surface that should only be energized when a threshold condition is met. In one example, the energy delivery surface should only be activated when the energy delivery surface is in contact with the appropriate, or targeted, tissue. As another example, a robotic surgical system can utilize a suction element that should only be activated when a threshold condition is met, such as when an appropriate volume of fluid is present. Due to visibility restrictions, evolving situations, and the multitude of moving parts during a robotic surgical procedure, it can be difficult for a clinician to determine and/or monitor certain conditions at the surgical site. For example, it can be difficult to determine if an energy delivery surface of an electrosurgical tool is in contact with tissue. It can also be difficult to determine if a particular suctioning pressure is sufficient for the volume of fluid in the proximity of the suctioning port.

[0362] Moreover, a plurality of surgical devices can be used in certain robotic surgical procedures. For example, a robotic surgical system can use one or more surgical tools during the surgical procedure. Additionally, one or more handheld instruments can also be used during the surgical procedure. One or more of the surgical devices can include a sensor. For example, multiple sensors can be positioned around the surgical site and/or the operating room. A sensor system including the one or more sensors can be configured to detect one or more conditions at the surgical site. For example, data from the sensor system can determine if a surgical tool mounted to the surgical robot is being used and/or if a feature of the surgical tool should be activated. More specifically, a sensor system can detect if an electrosurgical device is positioned in abutting contact with tissue, for example. As another example, a sensor system can detect if a suctioning element of a surgical tool is applying a sufficient suctioning force to fluid at the surgical site.

[0363] When in an automatic activation mode, the robotic surgical system can automatically activate one or more features of one or more surgical tools based on data, images, and/or other information received from the sensor system. For example, an energy delivery surface of an electrosurgical tool can be activated upon detecting that the electrosurgical tool is in use (e.g. positioned in abutting contact with tissue). As another example, a suctioning element on a surgical tool can be activated when the suction port is moved into contact with a fluid. In certain instances, the surgical tool can be adjusted based on the sensed conditions.

[0364] A robotic surgical system incorporating an automatic activation mode can automatically provide a scenario-specific result based on detected condition(s) at the surgical site. The scenario-specific result can be outcome-based, for example, and can streamline the decision-making process of the clinician. In certain instances, such an automatic activation mode can improve the efficiency and/or effectiveness of the clinician. For example, the robotic surgical system can aggregate data to compile a more complete view of the surgical site and/or the surgical procedure in order to determine the best possible course of action. Additionally or alternatively, in instances in which the clinician makes fewer decisions, the clinician can be better focused on other tasks and/or can process other information more effectively.

[0365] In one instance, a robotic surgical system can automatically adjust a surgical tool based on the proximity of the tool to a visually-detectable need and/or the situational awareness of the system. Referring to FIGS. 25A and 25B, an ultrasonic surgical tool for a robotic system 13050 is depicted in two different positions. In a first position, as depicted in FIG. 25A, the blade 13052 of an ultrasonic surgical tool 13050 is positioned out of contact with tissue 13060. In such a position, a sensor on the ultrasonic surgical tool 13050 can detect a high resistance. When the resistance detected is above a threshold value, the ultrasonic blade 13052 can be de-energized. Referring now to FIG. 25B, the ultrasonic blade 13052 is depicted in a second position in which the distal end of the blade 13052 is positioned in abutting contact with tissue 13060. In such instances, a sensor on the ultrasonic surgical tool 13050 can detect a low resistance. When the detected resistance is below a threshold value, the ultrasonic blade 13052 can be activated such that therapeutic energy is delivered to the tissue 13060. Alternative sensor configurations are also envisioned and various sensors are further described herein.

[0366] Referring to FIGS. 26A and 26B, another surgical tool, a monopolar cautery pencil 13055, is depicted in two different positions. In a first position, as depicted in FIG. 26A, the monopolar cautery pencil 13055 is positioned out of contact with tissue. In such a position, a sensor on the monopolar cautery pencil 13055 can detect a high resistance. When the resistance detected is above a threshold value, the monopolar cautery pencil 13055 can be de-energized. Referring now to FIG. 26B, the monopolar cautery pencil 13055 is depicted in a second position in which the distal end of the monopolar cautery pencil 13055 is positioned in abutting contact with tissue. In such instances, a sensor on the monopolar cautery pencil 13055 can detect a low resistance. When the detected resistance is below a threshold value, the monopolar cautery pencil 13055 can be activated such that therapeutic energy is delivered to the tissue. Alternative sensor configurations are also envisioned and various sensors are further described herein.

[0367] FIG. 27 shows a graphical display 13070 of continuity C and current I over time t for the ultrasonic surgical tool 13050 of FIGS. 25A and 25B. Similarly, the monopolar cautery pencil 13055 can generate a graphical display similar in many respects to the graphical display 13070, in certain instances. In the graphical display 13070, continuity C is represented by a dotted line, and current I is represented by a solid line. When the resistance is high and above a threshold value, the continuity C can also be high. The threshold value can be between 40 and 400 ohms, for example. At time A', the continuity C can decrease below the threshold value, which can indicate a degree of tissue contact. As a result, the robotic surgical system can automatically activate advanced energy treatment of the tissue. The ultrasonic transducer current depicted in FIG. 27 increases from time A' to B' when the continuity parameters indicate the degree of tissue contact. In various instances, the current I can be capped at a maximum value indicated at B', which can correspond to an open jaw transducer limit, such as in instances in which the jaw is not clamped, as shown in FIGS. 25A and 25B. In various instances, the situational awareness module of the robotic surgical system may indicate that the jaw is unclamped. Referring again to the graphical display 13070 in FIG. 27, energy is applied until time C', at which time a loss of tissue contact is indicated by the increase in continuity C above the threshold value. As a result, the ultrasonic transducer current I can decrease to zero as the ultrasonic blade is de-energized.

[0368] In various instances, a sensor system can be configured to detect at least one condition at the surgical site. For example, a sensor of the sensor system can detect tissue contact by measuring continuity along the energy delivery surface of the ultrasonic blade. Additionally or alternatively, the sensor system can include one or more additional sensors positioned around the surgical site. For example, one or more surgical tools and/or instruments being used in the surgical procedure can be configured to detect a condition at the surgical site. The sensor system can be in signal communication with a processor of the robotic surgical system. For example, the robotic surgical system can include a central control tower including a control unit housing a processor and memory, as further described herein. The processor can issue commands to the surgical tool based on inputs from the sensor system. In various instances, situational awareness can also dictate and/or influence the commands issued by the processor.

[0369] Turning now to FIG. 28, an end effector 196400 includes RF data sensors 196406, 196408a, 196408b located on jaw member 196402. The end effector 196400 includes jaw member 196402 and an ultrasonic blade 196404. The jaw member 196402 is shown clamping tissue 196410 located between the jaw member 196402 and the ultrasonic blade 196404. A first sensor 196406 is located in a center portion of the jaw member 196402. Second and third sensors 196408a, 196408b, respectively, are located on lateral portions of the jaw member 196402. The sensors 196406, 196408a, 196408b are mounted or formed integrally with a flexible circuit 196412 (shown more particularly in FIG. 29) configured to be fixedly mounted to the jaw member 196402.

[0370] The end effector 196400 is an example end effector for various surgical devices described herein. The sensors 196406, 196408a, 196408b are electrically connected to a control circuit via interface circuits. The sensors 196406,

196408a, **196408b** are battery powered and the signals generated by the sensors **196406**, **196408a**, **196408b** are provided to analog and/or digital processing circuits of the control circuit.

[0371] In one aspect, the first sensor **196406** is a force sensor to measure a normal force F_3 applied to the tissue **196410** by the jaw member **196402**. The second and third sensors **196408a**, **196408b** include one or more elements to apply RF energy to the tissue **196410**, measure tissue impedance, down force F_1 , transverse forces F_2 , and temperature, among other parameters. Electrodes **196409a**, **196409b** are electrically coupled to an energy source such as an electrical circuit and apply RF energy to the tissue **196410**. In one aspect, the first sensor **196406** and the second and third sensors **196408a**, **196408b** are strain gauges to measure force or force per unit area. It will be appreciated that the measurements of the down force F_1 , the lateral forces F_2 , and the normal force F_3 may be readily converted to pressure by determining the surface area upon which the force sensors **196406**, **196408a**, **196408b** are acting upon. Additionally, as described with particularity herein, the flexible circuit **196412** may include temperature sensors embedded in one or more layers of the flexible circuit **196412**. The one or more temperature sensors may be arranged symmetrically or asymmetrically and provide tissue **196410** temperature feedback to control circuits of an ultrasonic drive circuit and an RF drive circuit.

[0372] One or more sensors such as a magnetic field sensor, a strain gauge, a pressure sensor, a force sensor, an inductive sensor such as, for example, an eddy current sensor, a resistive sensor, a capacitive sensor, an optical sensor, and/or any other suitable sensor, may be adapted and configured to measure tissue compression and/or impedance.

[0373] FIG. 29 illustrates one aspect of the flexible circuit **196412** shown in FIG. 28 in which the sensors **196406**, **196408a**, **196408b** may be mounted to or formed integrally therewith. The flexible circuit **196412** is configured to fixedly attach to the jaw member **196402**. As shown particularly in FIG. 29, asymmetric temperature sensors **196414a**, **196414b** are mounted to the flexible circuit **196412** to enable measuring the temperature of the tissue **196410** (FIG. 28).

[0374] The reader will appreciate that alternative surgical tools can be utilized in the automatic activation mode described above with respect to FIGS. 25A-29.

[0375] FIG. 30 is a flow chart **13150** depicting an automatic activation mode **13151** of a surgical tool. In various instances, the robotic surgical system and processor thereof is configured to implement the processes indicated in FIG. 30. Initially, a sensor system is configured to detect a condition at step **13152**. The detected condition is communicated to a processor, which compares the detected condition to a threshold parameter at step **13154**. The threshold parameter can be a maximum value, minimum value, or range of values. If the sensed condition is an out-of-bounds condition, the processor can adjust the surgical function at step **13156** and the processor can repeat the comparison process of steps **13152** and **13154**. If the sensed condition is not an out-of-bounds condition, no adjustment is necessary (**13158**) and the comparison process of steps **13152** and **13154** can be repeated again.

[0376] In various instances, the robotic surgical system can permit a manual override mode **13153**. For example,

upon activation of the manual override input **13160**, such as by a clinician, the surgical system can exit the automatic activation mode **13151** at step **13162** depicted in FIG. 30. In such instances, even when a sensed condition is an out-of-bounds condition, the surgical function would not be automatically adjusted by the processor. However, in such instances, the processor can issue a warning or recommendation to the clinician recommending a particular course of action based on the sensed condition(s).

[0377] In various instances, an automatic activation mode can be utilized with a robotic surgical system including a suctioning feature. In one instance, a robotic surgical system can communicate with a suction and/or irrigation tool. For example, a suction and/or irrigation device (see module **128** in FIG. 3) can communicate with a robotic surgical system via the surgical hub **106** (FIG. 1) and/or the surgical hub **206** (FIG. 9) and a suction and/or irrigation tool can be mounted to a robotic arm. The suction/irrigation device can include a distal suction port and a sensor. In another instance, a robotic surgical tool, such as an electrosurgical tool, can include a suctioning feature and a suction port on the end effector of the tool.

[0378] Referring to FIG. 31, when a suction port on an end effector **13210** is moved into contact with a fluid, a processor of the robotic surgical system can automatically activate the suction feature. For example, a fluid detection sensor **13230** on the tool **13200** can detect fluid **13220** in the proximity of the tool **13200** and/or contacting the tool **13200**. The fluid detection sensor **13230** can be a continuity sensor, for example. The fluid detection sensor **13230** can be in signal communication with the processor such that the processor is configured to receive input and/or feedback from the fluid detection sensor **13230**. In certain instances, the suctioning feature can be automatically activated when the suction port is moved into proximity with a fluid **13220**. For example, when the suction port moves within a predefined spatial range of a fluid **13220**, the suction feature can be activated by the processor. The fluid **13220** can be saline, for example, which can be provided to the surgical site to enhance conductivity and/or irrigate the tissue.

[0379] In various instances, the tool can be a smoke evacuation tool and/or can include a smoke evacuation system, for example. A detail view of an end effector **13210** of a bipolar radio-frequency surgical tool **13200** is shown in FIG. 31. The end effector **13210** is shown in a clamped configuration. Moreover, smoke and steam **13220** from an RF weld accumulate around the end effector **13210**. In various instances, to improve visibility and efficiency of the tool **13200**, the smoke and steam **13220** at the surgical site can be evacuated along a smoke evacuation channel **13240** extending proximally from the end effector. The evacuation channel **13240** can extend through the shaft **13205** of the surgical tool **13200** to the interface of the surgical tool **13200** and the robot. The evacuation channel **13240** can be coupled to a pump for drawing the smoke and/or steam **13220** along the smoke evacuation channel **13240** within the shaft **13205** of the surgical tool **13200**. In various instances, the surgical tool **13200** can include insufflation, cooling, and/or irrigation capabilities, as well.

[0380] In one instance, the intensity of the suction pressure can be automatically adjusted based on a measured parameter from one or more surgical devices. In such instances, the suction pressure can vary depending on the sensed parameters. Suction tubing can include a sensor for

detecting the volume of fluid being extracted from the surgical site. When increased volumes of fluid are being extracted, the power to the suction feature can be increased such that the suctioning pressure is increased. Similarly, when decreased volumes of fluid are being extracted, the power to the suction feature can be decreased such that the suctioning pressure is decreased.

[0381] In various instances, the sensing system for a suction tool can include a pressure sensor. The pressure sensor can detect when an occlusion is obstructing, or partially obstructing, the fluid flow. The pressure sensor can also detect when the suction port is moved into abutting contact with tissue. In such instances, the processor can reduce and/or pause the suctioning force to release the tissue and/or clear the obstruction. In various instances, the processor can compare the detected pressure to a threshold maximum pressure. Exceeding the maximum threshold pressure may lead to unintentional tissue trauma from the suctioning tool. Thus, to avoid such trauma, the processor can reduce and/or pause the suctioning force to protect the integrity of tissue in the vicinity thereof.

[0382] A user can manually override the automatic adjustments implemented in the automatic activation mode(s) described herein. The manual override can be a one-time adjustment to the surgical tool. In other instances, the manual override can be a setting that turns off the automatic activation mode for a specific surgical action, a specific duration, and/or a global override for the entire procedure.

[0383] In one aspect, the robotic surgical system includes a processor and a memory communicatively coupled to the processor, as described herein. The processor is communicatively coupled to a sensor system, and the memory stores instructions executable by the processor to determine a use of a robotic tool based on input from the sensor system and to automatically energize an energy delivery surface of the robotic tool when the use is determined, as described herein.

[0384] In various aspects, the present disclosure provides a control circuit to automatically energize an energy delivery surface, as described herein. In various aspects, the present disclosure provides a non-transitory computer readable medium storing computer readable instructions which, when executed, cause a machine to automatically energize an energy delivery surface of a robotic tool, as described herein.

[0385] In one aspect, the robotic surgical system includes a processor and a memory communicatively coupled to the processor, as described herein. The processor is communicatively coupled to a fluid detection sensor, and the memory stores instructions executable by the processor to receive input from the fluid detection sensor and to automatically activate a suctioning mode when fluid is detected, as described herein.

[0386] In various aspects, the present disclosure provides a control circuit to automatically activate a suctioning mode, as described herein. In various aspects, the present disclosure provides a non-transitory computer readable medium storing computer readable instructions which, when executed, cause a machine to automatically activate a suctioning mode, as described herein.

[0387] Multiple surgical devices, including a robotic surgical system and various handheld instruments, can be used by a clinician during a particular surgical procedure. When manipulating one or more robotic tools of the robotic surgical system, a clinician is often positioned at a surgeon's command console or module, which is also referred to as a

remote control console. In various instances, the remote control console is positioned outside of a sterile field and, thus, can be remote to the sterile field and, in some instances, remote to the patient and even to the operating room. If the clinician desires to use a handheld instrument, the clinician may be required to step away from the remote control console. At this point, the clinician may be unable to control the robotic tools. For example, the clinician may be unable to adjust the position or utilize the functionality of the robotic tools. Upon stepping away from the remote control console, the clinician may also lose sight of one or more displays on the robotic surgical system. The separation between the control points for the handheld instruments and the robotic surgical system may inhibit the effectiveness with which the clinician can utilize the surgical devices, both robotic tools and surgical instruments, together.

[0388] In various instances, an interactive secondary display is configured to be in signal communication with the robotic surgical system. The interactive secondary display includes a control module in various instances. Moreover, the interactive secondary display is configured to be wireless and movable around an operating room. In various instances, the interactive secondary display is positioned within a sterile field. In one instance, the interactive secondary display allows the clinician to manipulate and control the one or more robotic tools of the robotic surgical system without having to be physically present at the remote control console. In one instance, the ability for the clinician to operate the robotic surgical system away from the remote control console allows multiple devices to be used in a synchronized manner. As a safety measure, in certain instances, the remote control console includes an override function configured to prohibit control of the robotic tools by the interactive secondary display.

[0389] FIG. 32 depicts a surgical system 13100 for use during a surgical procedure that utilizes a surgical instrument 13140 and a robotic surgical system 13110. The surgical instrument 13140 is a powered handheld instrument. The surgical instrument 13140 can be a radio frequency (RF) instrument, an ultrasonic instrument, a surgical stapler, and/or a combination thereof, for example. The surgical instrument 13140 includes a display 13142 and a processor 13144. In certain instances, the handheld surgical instrument 13140 can be a smart or intelligent surgical instrument having a plurality of sensors and a wireless communication module.

[0390] The robotic surgical system 13110 includes a robot 13112 including at least one robotic tool 13117 configured to perform a particular surgical function. The robotic surgical system 13110 is similar in many respects to robotic surgical system 13000 discussed herein. The robotic tool 13117 is movable in a space defined by a control envelope of the robotic surgical system 13110. In various instances, the robotic tool 13117 is controlled by various clinician inputs at a remote control console 13116. In other words, when a clinician applies an input at the remote control console 13116, the clinician is away from the patient's body and outside of a sterile field 13138. Clinician input to the remote control console 13116 is communicated to a robotic control unit 13114 that includes a robot display 13113 and a processor 13115. The processor 13115 directs the robotic tool(s) 13117 to perform the desired function(s).

[0391] In various instances, the surgical system 13100 includes a surgical hub 13120, which is similar in many

respects to the hub **106**, the hub **206**, the robotic hub **122**, or the robotic hub **222**, for example. The surgical hub **13120** is configured to enhance cooperative and/or coordinated usage of the robotic surgical system **13110** and the surgical instrument(s) **13140**. The surgical hub **13120** is in signal communication with the control unit **13114** of the robotic surgical system **13110** and the processor **13144** of the surgical instrument(s) **13140**. In various instances, a signal is transmitted through a wireless connection, although any suitable connection can be used to facilitate the communication. The control unit **13114** of the robotic surgical system **13110** is configured to send information to the surgical hub **13120** regarding the robotic tool(s) **13117**. Such information includes, for example, a position of the robotic tool(s) **13117** within the surgical site, an operating status of the robotic tool(s) **13117**, a detected force by the robotic tool(s), and/or the type of robotic tool(s) **13117** attached to the robotic surgical system **13110**, although any relevant information and/or operating parameters can be communicated. Examples of surgical hubs are further described herein and in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety.

[0392] In other instances, the robotic surgical system **13110** can encompass the surgical hub **13120** and/or the control unit **13114** can be incorporated into the surgical hub **13120**. For example, the robotic surgical system **13110** can include a robotic hub including a modular control tower that includes a computer system and a modular communication hub. One or more modules can be installed in the modular control tower of the robotic hub. Examples of robotic hubs are further described herein and in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety.

[0393] The processor **13144** of the surgical instrument(s) **13140** is configured to send information to the surgical hub **13120** regarding the surgical instrument **13140**. Such information includes, for example, a position of the surgical instrument(s) **13140** within the surgical site, an operating status of the surgical instrument(s) **13140**, a detected force by the surgical instrument(s) **13140**, and/or identification information regarding the surgical instrument(s) **13140**, although any relevant information and/or operating parameters can be sent to the surgical hub.

[0394] In various instances, a hub display **13125** is in signal communication with the surgical hub **13120** and may be incorporated into the modular control tower, for example. The hub display **13125** is configured to display information received from the robotic surgical system **13110** and the surgical instrument(s) **13140**. The hub display **13125** can be similar in many respects to the visualization system **108** (FIG. 1), for example. In one aspect, the hub display **13125** can include an array of displays such as video monitors and/or heads-up displays around the operating room, for example.

[0395] In various instances, the surgical hub **13120** is configured to recognize when the surgical instrument **13140** is activated by a clinician via wireless communication signal(s). Upon activation, the surgical instrument **13140** is configured to send identification information to the surgical hub **13120**. Such identification information may include, for

example, a model number of the surgical instrument, an operating status of the surgical instrument, and/or a location of the surgical instrument, although other suitable device parameters can be communicated. In various instances, the surgical hub **13120** is configured to utilize the communicated information to assess the compatibility of the surgical instrument **13140** with the capabilities of the surgical hub **13120**. Examples of capabilities of the surgical hub with compatible surgical instruments are further discussed herein.

[0396] In various instances, the control unit **13114** of the robotic surgical system **13110** is configured to communicate a video feed to the surgical hub **13120**, and the surgical hub **13120** is configured to communicate the information, or a portion thereof, to the surgical instrument **13140**, which can replicate a portion of the robot display **13113**, or other information from the robotic surgical system **13110**, on a display **13142** of the surgical instrument **13140**. In other instances, the robotic surgical system **13110** (e.g. the control unit **13114** or surgical tool **13117**) can communicate directly with the surgical instrument **13140**, such as when the robotic surgical system **13110** includes a robotic hub and/or the surgical tool **13117** includes a wireless communication module, for example. The reproduction of a portion of the robot display **13113** on the surgical instrument **13140** allows the clinician to cooperatively use both surgical devices by providing, for example, alignment data to achieve integrated positioning of the surgical instrument **13140** relative to the robotic tool(s) **13117**. In various instances, the clinician is able to remove any unwanted information displayed on the display **13142** of the surgical instrument **13140**.

[0397] Referring still to FIG. 32, in various instances, the surgical system **13100** further includes an interactive secondary display **13130** within the sterile field **13138**. The interactive secondary display **13130** is also a local control module within the sterile field **13138**. The remote control console **13116**, or the primary control, can be positioned outside the sterile field **13138**. For example, the interactive secondary display **13130** can be a handheld mobile electronic device, such as an iPad® tablet, which can be placed on a patient or the patient's table during a surgical procedure. For example, the interactive secondary display **13130** can be placed on the abdomen or leg of the patient during the surgical procedure. In other instances, the interactive secondary display **13130** can be incorporated into the surgical instrument **13140** within the sterile field **13138**. In various instances, the interactive secondary display **13130** is configured to be in signal communication with the robotic surgical system **13110** and/or the surgical instrument **13140**. In such instances, the interactive secondary display **13130** is configured to display information received from the robotic tool(s) **13117** (for example, robotic tool 1, robotic tool 2, . . . robotic tool n) and the surgical instruments **13140** (for example, surgical instrument 1, surgical instrument 2, . . . surgical instrument n). The interactive secondary display **13130** depicts tool information **13133** and instrument information **13135** thereon. In various instances, the user is able to interact with the interactive secondary display **13130** to customize the size and/or location of the information displayed.

[0398] Referring still to FIG. 32, in various instances, the surgical hub **13120** is configured to transmit robot status information of the surgical robot system **13100** to the surgical instrument **13140**, and the surgical instrument

13140 is configured to display the robot status information on the display **13142** of the surgical instrument **13140**.

[0399] In various instances, the display **13142** of the surgical instrument **13140** is configured to communicate commands through the surgical hub **13120** to the control unit **13114** of the robotic surgical system **13110**. After viewing and interpreting the robot status information displayed on the display **13142** of the surgical instrument **13140** as described herein, a clinician may want to utilize one or more functions of the robotic surgical system **13110**. Using the buttons and/or a touch-sensitive display **13142** on the surgical instrument **13140**, the clinician is able to input a desired utilization of and/or adjustment to the robotic surgical system **13110**. The clinician input is communicated from the surgical instrument **13140** to the surgical hub **13120**. The surgical hub **13120** is then configured to communicate the clinician input to the control unit **13114** of the robotic surgical system **13110** for implementation of the desired function. In other instances, the handheld surgical instrument **13140** can communicate directly with the control unit **13114** of the robotic surgical system **13110**, such as when the robotic surgical system **13110** includes a robotic hub, for example.

[0400] In various instances, the surgical hub **13120** is in signal communication with both the robotic surgical system **13110** and the surgical instrument **13140**, allowing the surgical system **13110** to adjust multiple surgical devices in a synchronized, coordinated, and/or cooperative manner. The information communicated between the surgical hub **13120** and the various surgical devices includes, for example, surgical instrument identification information and/or the operating status of the various surgical devices. In various instances, the surgical hub **13120** is configured to detect when the surgical instrument **13140** is activated. In one instance, the surgical instrument **13140** is an ultrasonic dissector. Upon activation of the ultrasonic dissector, the surgical hub **13120** is configured to communicate the received activation information to the control unit **13114** of the robotic surgical system **13110**.

[0401] In various instances, the surgical hub **13120** automatically communicates the information to the control unit **13114** of the robotic surgical system **13110**. The reader will appreciate that the information can be communicated at any suitable time, rate, interval and/or schedule. Based on the information received from the surgical hub **13120**, the control unit **13114** of the robotic surgical system **13110** is configured to decide whether to activate at least one robotic tool **13117** and/or activate a particular operating mode, such as a smoke evacuation mode, for example. For example, upon activation of a surgical tool that is known to generate, or possibly generate, smoke and/or contaminants at the surgical site, such as an ultrasonic dissector, the robotic surgical system **13110** can automatically activate the smoke evacuation mode or can cue the surgeon to activate the smoke evacuation mode. In various instances, the surgical hub **13120** is configured to continuously communicate additional information to the control unit **13114** of the robotic surgical system **13110**, such as various sensed tissue conditions, in order to adjust, continue, and/or suspend further movement of the robotic tool **13117** and/or the entered operating mode.

[0402] In various instances, the surgical hub **13120** may calculate parameters, such as smoke generation intensity, for example, based on the additional information communicated

from the surgical instrument **13140**. Upon communicating the calculated parameter to the control unit **13114** of the robotic surgical system **13110**, the control unit **13114** is configured to move at least one robotic tool and/or adjust the operating mode to account for the calculated parameter. For example, when the robotic surgical system **13110** enters the smoke evacuation mode, the control unit **13114** is configured to adjust a smoke evacuation motor speed to be proportionate to the calculated smoke generation intensity.

[0403] In certain instances, an ultrasonic tool mounted to the robot **13112** can include a smoke evacuation feature that can be activated by the control unit **13114** to operate in a smoke evacuation mode. In other instances, a separate smoke evacuation device can be utilized. For example, a smoke evacuation tool can be mounted to another robotic arm and utilized during the surgical procedure. In still other instances, a smoke evacuation instrument that is separate from the robotic surgical system **13110** can be utilized. The surgical hub **13120** can coordinate communication between the robotically-controlled ultrasonic tool and the smoke evacuation instrument, for example.

[0404] In FIGS. 33-36, various surgical devices and components thereof are described with reference to a colon resection procedure. The reader will appreciate that the surgical devices, systems, and procedures described with respect to those figures are an exemplary application of the system of FIG. 32. Referring now to FIG. 33, a handle portion **13202** of a handheld surgical instrument **13300** is depicted. In certain aspects, the handheld surgical instrument **13300** corresponds to the surgical instrument **13140** of the surgical system **13110** in FIG. 32. In one instance, the handheld surgical instrument **13300** is a powered circular stapler and includes a display **13310** on the handle portion **13302** thereof.

[0405] Before pairing the handheld surgical instrument **13300** to a robotic surgical system (e.g. the robotic surgical system **13110** in FIG. 32) via the surgical hub **13320** (FIG. 34), as described herein, the display **13310** on the handle **13302** of the handheld surgical instrument **13300** can include information regarding the status of the instrument **13300**, such as the clamping load **13212**, the anvil status **13214**, and/or the instrument or cartridge status **13216**, for example. In various instances, the display **13310** of the handheld surgical instrument **13300** includes an alert **13318** to the user that communicates the status of the firing system. In various instances, the display **13310** is configured to display the information in a manner that communicates the most important information to the user. For example, in various instances, the display **13310** is configured to display warning information in a larger size, in a flashing manner, and/or in a different color. When the handheld surgical instrument **13300** is not paired with a surgical hub, the display **13310** can depict information gathered only from the handheld surgical instrument **13300** itself.

[0406] Referring now to FIG. 34, after pairing the handheld surgical instrument **13300** with the surgical hub **13320**, as described herein with respect to FIG. 32, for example, the information detected and displayed by the handheld surgical instrument **13300** can be communicated to the surgical hub **13320** and displayed on a hub display (e.g. the hub display **13125** of FIG. 32). Additionally or alternatively, the information can be displayed on the display of the robotic surgical system. Additionally or alternatively, the information can be displayed on the display **13310** on the handle

portion **13302** of the handheld surgical instrument **13300**. In various instances, a clinician can decide what information is displayed at the one or multiple locations. As mentioned above, in various instances, the clinician is able to remove any unwanted information displayed on the display **13310** of the handheld surgical instrument **13300**, the display of the robotic surgical system, and/or the display on the hub display.

[0407] Referring still to FIG. **34**, after pairing the handheld surgical instrument **13300** with the robotic surgical system, the display **13310** on the handle portion **13302** of the handheld surgical instrument **13300** can be different than the display **13310** on the handheld surgical instrument **13300** before pairing with the robotic surgical system. For example, procedural information from the surgical hub **13320** and/or robotic surgical system can be displayed on the powered circular stapler. For example, as seen in FIG. **34**, robot status information including alignment information **13312** from the surgical hub **13320** and one or more retraction tensions **13316**, **13317** exerted by a robotic tool on particular tissue(s), is displayed on the display **13310** of the handheld surgical instrument **13300** for the convenience of the clinician. In various instances, the display **13310** of the handheld surgical instrument **13300** includes an alert **13318** to the user that communicates a parameter monitored by the surgical hub **13320** during a surgical procedure. In various instances, the display **13310** is configured to display the information in a manner that communicates the most important information to the user. For example, in various instances, the display **13310** is configured to display warning information in a larger size, in a flashing manner, and/or in a different color.

[0408] Referring still to FIG. **34**, the display **13310** of the handheld surgical instrument **13300** is configured to display information regarding one or more retraction tensions **13316**, **13317** exerted by one or more devices during a surgical procedure involving one or more robotic tools. For example, the handheld surgical instrument **13300**, the powered circular stapler, is involved in the colon resection procedure of FIG. **35**. In this procedure, one device (e.g. a robotic tool) is configured to grasp colonic tissue and another device (e.g. the handheld circular stapler) is configured to grasp rectal tissue. As the devices move apart from one another, the force of retracting the colonic tissue F_{RC} and the force of retracting the rectal tissue F_{RR} are monitored. In the illustrated example, an alert notification **13318** is issued to the user as the force of retracting the colonic tissue has exceeded a predetermined threshold. Predetermined thresholds for both retracting forces F_{RC} , F_{RR} are indicated by horizontal dotted lines on the display **13310**. The user is notified when one or both thresholds are surpassed and/or reached in an effort to minimize damage and/or trauma to the surrounding tissue.

[0409] In FIG. **36**, graphical displays **13330**, **13340** of retracting forces F_{RC} , F_{RR} are illustrated. In the circumstances illustrated in the graphical displays **13330**, **13340**, the user is notified when pre-determined thresholds are exceeded, depicted by the shaded region **13332** of the graphical display **13330**, indicating that the retracting force of the colonic tissue F_{RC} has exceeded a predetermined threshold of 0.5 lbs.

[0410] In certain instances, it can be difficult to align the end effector of a circular stapler with targeted tissue during a colorectal procedure because of visibility limitations. For

example, referring again to FIG. **35**, during a colon resection, the surgical instrument **13300**, a circular stapler, can be positioned adjacent to a transected rectum **13356**. Moreover, the anvil **13301** of the surgical instrument **13300** can be engaged with a transected colon **13355**. A robotic tool **13374** is configured to engage the anvil **13301** and apply the retracting force F_{RC} . It can be difficult to confirm the relative position of the surgical instrument **13300** with the targeted tissue, for example, with the staple line through the transected colon **13355**. In certain instances, information from the surgical hub **13320** and robotic surgical system can facilitate the alignment. For example, as shown in FIG. **34**, the center of the surgical instrument **13300** can be shown relative to the center of the targeted tissue **13318** on the display screen **13310** of the surgical instrument **13300**. In certain instances, and as shown in FIG. **35**, sensors and a wireless transmitter on the surgical instrument **13300** can be configured to convey positioning information to the surgical hub **13320**, for example.

[0411] A colorectal procedure, visibility limitations thereof, and an alignment tool for a surgical hub are further described herein and in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety.

[0412] As mentioned above, the display **13310** on the handheld instrument **13300** can also be configured to alert the clinician in certain scenarios. For example, the display **13310** in FIG. **34** includes an alert **13318** because the one or more of the forces exceed the predefined force thresholds. Referring again to FIGS. **35** and **36**, during the colon resection, the robotic arm can exert a first force F_{RC} on the anvil, and the handheld instrument **13300** can exert a second force F_{RR} on the rectum **13356**. The tension on the rectum **13356** by the circular stapler can be capped at a first limit (for example 0.5 lb in FIG. **36**), and the tension on the colon **13355** from the robotic arm can be capped at a second limit (for example 0.5 lb in FIG. **36**). An intervention may be suggested to the clinician when the tension on the rectum **13356** or colon **13355** exceeds a threshold value.

[0413] The tension on the colon F_{RC} in FIGS. **35** and **36** can be ascertained by resistance to the robotic arm, and thus, can be determined by a control unit (e.g. the control unit **13114** of the robotic surgical system **13110**). Such information can be communicated to the handheld surgical instrument **13300** and displayed on the display **13310** thereof in the sterile field such that the information is readily available to the appropriate clinician in real-time, or near real-time, or any suitable interval, rate, and/or schedule, for example.

[0414] In various instances, a surgical system, such as a surgical system **13360** of FIGS. **37** and **38**, includes interactive secondary displays **13362**, **13364** within the sterile field. The interactive secondary displays **13362**, **13364** are also mobile control modules in certain instances and can be similar to the interactive secondary displays **13130** in FIG. **32**, for example. A surgeon's command console, or remote control module, **13370**, is the primary control module and can be positioned outside the sterile field. In one instance, the interactive secondary display **13362** can be a mobile device, a watch, and/or a small tablet, which can be worn on the wrist and/or forearm of the user, and the interactive secondary display **13364** can be a handheld mobile electronic device, such as an iPad® tablet, which can be placed on a patient **13361** or the patient's table during a surgical

procedure. For example, the interactive secondary displays **13362**, **13364** can be placed on the abdomen or leg of the patient **13361** during the surgical procedure. In other instances, the interactive secondary displays **13362**, **13364** can be incorporated into a handheld surgical instrument **13366** within the sterile field.

[0415] In one instance, the surgical system **13360** is shown during a surgical procedure. For example, the surgical procedure can be the colon resection procedure described herein with respect to FIGS. **33-36**. In such instances, the surgical system **13360** includes a robot **13372** and a robotic tool **13374** extending into the surgical site. The robotic tool can be an ultrasonic device comprising an ultrasonic blade and a clamp arm, for example. The surgical system **13360** also includes the remote command console **13370** that encompasses a robotic hub **13380**. The control unit for the robot **13372** is housed in the robotic hub **13380**. A surgeon **13371** is initially positioned at the remote command console **13370**. An assistant **13367** holds the handheld surgical instrument **13366**, a circular stapler that extends into the surgical site. The assistant **13367** also holds a secondary display **13364** that communicates with the robotic hub **13380**. The secondary display **13364** is a mobile digital electronic device, which can be secured to the assistant's forearm, for example. The handheld surgical instrument **13366** includes a wireless communication module. A second surgical hub **13382** is also stationed in the operating room. The surgical hub **13382** includes a generator module and can include additional modules as further described herein and in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety.

[0416] Referring primarily to FIG. **37**, hubs **13380**, **13382** include wireless communication modules such that a wireless communication link is established between the two hubs **13380**, **13382**. Additionally, the robotic hub **13380** is in signal communication with the interactive secondary displays **13362**, **13364** within the sterile field. The hub **13382** is in signal communication with the handheld surgical instrument **13366**. If the surgeon **13371** moves over towards the patient **13361** and within the sterile field (as indicated by the reference character **13371'**), the surgeon **13371** can use one of the wireless interactive displays **13362**, **13364** to operate the robot **13372** away from the remote command console **13370**. The plurality of secondary displays **13362**, **13364** within the sterile field allows the surgeon **13371** to move away from the remote command console **13370** without losing sight of important information for the surgical procedure and controls for the robotic tools utilized therein.

[0417] The interactive secondary displays **13362**, **13364** permit the clinician to step away from the remote command console **13370** and into the sterile field while maintaining control of the robot **13372**. For example, the interactive secondary displays **13362**, **13364** allow the clinician to maintain cooperative and/or coordinated control over the powered handheld surgical instrument(s) **13366** and the robotic surgical system at the same time. In various instances, information is communicated between the robotic surgical system, one or more powered handheld surgical instruments **13366**, surgical hubs **13380**, **13382**, and the interactive secondary displays **13362**, **13364**. Such information may include, for example, the images on the display of the robotic surgical system and/or the powered handheld

surgical instruments, a parameter of the robotic surgical system and/or the powered handheld surgical instruments, and/or a control command for the robotic surgical system and/or the powered handheld surgical instruments.

[0418] In various instances, the control unit of the robotic surgical system (e.g. the control unit **13113** of the robotic surgical system **13110**) is configured to communicate at least one display element from the surgeon's command console (e.g. the console **13116**) to an interactive secondary display (e.g. the display **13130**). In other words, a portion of the display at the surgeon's console is replicated on the display of the interactive secondary display, integrating the robot display with the interactive secondary display. The replication of the robot display on to the display of the interactive secondary display allows the clinician to step away from the remote command console without losing the visual image that is displayed there. For example, at least one of the interactive secondary displays **13362**, **13364** can display information from the robot, such as information from the robot display and/or the surgeon's command console **13370**.

[0419] In various instances, the interactive secondary displays **13362**, **13364** are configured to control and/or adjust at least one operating parameter of the robotic surgical system. Such control can occur automatically and/or in response to a clinician input. Interacting with a touch-sensitive screen and/or buttons on the interactive secondary display(s) **13362**, **13364**, the clinician is able to input a command to control movement and/or functionality of the one or more robotic tools. For example, when utilizing a handheld surgical instrument **13366**, the clinician may want to move the robotic tool **13374** to a different position. To control the robotic tool **13374**, the clinician applies an input to the interactive secondary display(s) **13362**, **13364**, and the respective interactive secondary display(s) **13362**, **13364** communicates the clinician input to the control unit of the robotic surgical system in the robotic hub **13380**.

[0420] In various instances, a clinician positioned at the remote command console **13370** of the robotic surgical system can manually override any robot command initiated by a clinician input on the one or more interactive secondary displays **13362**, **13364**. For example, when a clinician input is received from the one or more interactive secondary displays **13362**, **13364**, a clinician positioned at the remote command console **13370** can either allow the command to be issued and the desired function performed or the clinician can override the command by interacting with the remote command console **13370** and prohibiting the command from being issued.

[0421] In certain instances, a clinician within the sterile field can be required to request permission to control the robot **13372** and/or the robotic tool **13374** mounted thereto. The surgeon **13371** at the remote command console **13370** can grant or deny the clinician's request. For example, the surgeon can receive a pop-up or other notification indicating the permission is being requested by another clinician operating a handheld surgical instrument and/or interacting with an interactive secondary display **13362**, **13364**.

[0422] In various instances, the processor of a robotic surgical system, such as the robotic surgical systems **13000** (FIG. **23**), **13400** (FIG. **24**), **13150** (FIG. **30**), **13100** (FIG. **32**), and/or the surgical hub **13380**, **13382**, for example, is programmed with pre-approved functions of the robotic surgical system. For example, if a clinician input from the interactive secondary display **13362**, **13364** corresponds to

a pre-approved function, the robotic surgical system allows for the interactive secondary display **13362**, **13364** to control the robotic surgical system and/or does not prohibit the interactive secondary display **13362**, **13364** from controlling the robotic surgical system. If a clinician input from the interactive secondary display **13362**, **13364** does not correspond to a pre-approved function, the interactive secondary display **13362**, **13364** is unable to command the robotic surgical system to perform the desired function. In one instance, a situational awareness module in the robotic hub **13370** and/or the surgical hub **13382** is configured to dictate and/or influence when the interactive secondary display can issue control motions to the robot surgical system.

[0423] In various instances, an interactive secondary display **13362**, **13364** has control over a portion of the robotic surgical system upon making contact with the portion of the robotic surgical system. For example, when the interactive secondary display **13362**, **13364** is brought into contact with the robotic tool **13374**, control of the contacted robotic tool **13374** is granted to the interactive secondary display **13362**, **13364**. A clinician can then utilize a touch-sensitive screen and/or buttons on the interactive secondary display **13362**, **13364** to input a command to control movement and/or functionality of the contacted robotic tool **13374**. This control scheme allows for a clinician to reposition a robotic arm, reload a robotic tool, and/or otherwise reconfigure the robotic surgical system. In a similar manner as discussed above, the clinician **13371** positioned at the remote command console **13370** of the robotic surgical system can manually override any robot command initiated by the interactive secondary display **13362**, **13364**.

[0424] In one aspect, the robotic surgical system includes a processor and a memory communicatively coupled to the processor, as described herein. The memory stores instructions executable by the processor to receive a first user input from a console and to receive a second user input from a mobile wireless control module for controlling a function of a robotic surgical tool, as described herein.

[0425] In various aspects, the present disclosure provides a control circuit to receive a first user input from a console and to receive a second user input from a mobile wireless control module for controlling a function of a robotic surgical tool, as described herein. In various aspects, the present disclosure provides a non-transitory computer readable medium storing computer readable instructions which, when executed, cause a machine to receive a first user input from a console and to receive a second user input from a mobile wireless control module for controlling a function of a robotic surgical tool, as described herein.

[0426] A robotic surgical system may include multiple robotic arms that are configured to assist the clinician during a surgical procedure. Each robotic arm may be operable independently of the others. A lack of communication may exist between each of the robotic arms as they are independently operated, which may increase the risk of tissue trauma. For example, in a scenario where one robotic arm is configured to apply a force that is stronger and in a different direction than a force configured to be applied by a second robotic arm, tissue trauma can result. For example, tissue trauma and/or tearing may occur when a first robotic arm applies a strong retracting force to the tissue while a second robotic arm is configured to rigidly hold the tissue in place.

[0427] In various instances, one or more sensors are attached to each robotic arm of a robotic surgical system.

The one or more sensors are configured to sense a force applied to the surrounding tissue during the operation of the robotic arm. Such forces can include, for example, a holding force, a retracting force, and/or a dragging force. The sensor from each robotic arm is configured to communicate the magnitude and direction of the detected force to a control unit of the robotic surgical system. The control unit is configured to analyze the communicated forces and set limits for maximum loads to avoid causing trauma to the tissue in a surgical site. For example, the control unit may minimize the holding force applied by a first robotic arm if the retracting or dragging force applied by a second robotic arm increases.

[0428] FIG. 39 depicts a robotic surgical system **13800** including a control unit **13820** and a robot **13810**. The robotic surgical system **13800** is similar in many respects to the robotic surgical system **13000** including the robot **13002** (FIG. 23), for example. The control unit **13820** includes a processor **13822** and a display **13824**. The robot **13810** includes two robotic arms, **13830**, **13840** configured to carry out various surgical functions. Each of the robotic arms **13830**, **13840** are independently operable and are free to move in a space defining a control envelope of the robotic surgical system **13800**. The one or more robotic arms, **13830**, **13840**, are configured to receive a tool, such as a stapler, a radio frequency (RF) tool, an ultrasonic blade, graspers, and/or a cutting instrument, for example. Other suitable surgical tool can be used. In various instances, the robotic arms **13830**, **13840** each include a different tool configured to perform different functions. In other instances, all of the robotic arms **13830**, **13840** include the same tool, although any suitable arrangement can be used.

[0429] The first robotic arm **13830** includes a first driver **13834** and a first motor **13836**. When activated by the processor **13822**, the first motor **13836** drives the first driver **13834** actuating the corresponding component of the first robotic arm **13830**. The second robotic arm **13840** includes a second driver, **13844** and a second motor **13846**. When activated by the processor **13822**, the second motor **13846** drives the second driver **13844** actuating the corresponding component of the second robotic arm **13840**.

[0430] Each of the robotic arms **13830**, **13840**, includes a sensor **13832**, **13842** in signal communication with the processor **13822** of the control unit **13820**. The sensors **13832**, **13842** can be positioned on the drivers **13834**, **13844**, respectively, and/or on the motors **13836**, **13846**, respectively. In various instances, the sensors **13832**, **13842** are configured to detect the location of each individual robotic arm **13830**, **13840** within the control envelope of the robotic surgical system **13800**. The sensors **13832**, **13842** are configured to communicate the detected locations to the processor **13822** of the robotic surgical system **13800**. In various instances, the positions of the robotic arms **13830**, **13840** are displayed on the display **13824** of the control unit **13820**. As described in more detail below, in various instances, the processor **13822** is configured to run an algorithm to implement position limits specific to each robotic arm **13830**, **13840** in an effort to avoid tissue trauma and damage to the robotic surgical system **13800**, for example. Such position limits may increase the clinician's ability to cooperatively operate numerous robotic arms **13830**, **13840** of the robotic surgical system **13800** at the same time.

[0431] In various instances, the sensors **13832**, **13842** are configured to detect the force exerted by each robotic arm **13830**, **13840**. The sensors **13832**, **13842** can be torque sensors. As stated above, each robotic arm **13830**, **13840** of the robotic surgical system **13800** is independently operable. During a particular surgical procedure, a clinician may want to perform different surgical functions with each robotic arm **13830**, **13840**. Upon detecting the exerted forces of each robotic arm **13830**, **13840**, each sensor **13832**, **13842** is configured to communicate the detected forces to the processor **13822**. The processor **13822** is then configured to analyze the communicated information and set maximum and/or minimum force limits for each robotic arm **13830**, **13840** to reduce the risk of causing tissue trauma, for example. In addition, the processor **13822** is configured to continuously monitor the exerted forces by each robotic arm **13830**, **13840** and, based on the direction and magnitude of the exerted forces, proportionally control each robotic arm **13830**, **13840** with respect to one another. For example, the opposing force between two robotic arms **13830**, **13840** can be measured and maintained below a maximum force limit. To maintain the opposing force below a maximum force limit, at least one of the forces can be reduced, which can result in displacement of the robotic arm **13830**, **13840**.

[0432] By way of example, FIG. 40 depicts a surgical site and a portion of the surgical system **13800**, which includes three robotic arms, including a robotic arm **13850** (a third robotic arm) in addition to the robotic arms **13830** and **13840**, which are also schematically depicted in FIG. 39. The first robotic arm **13830** is configured to hold a portion of stomach connective tissue. In order to hold the portion of stomach connective tissue, the first robotic arm **13830** exerts an upward force F_{H1} . The second robotic arm **13840** applies a dragging and/or cutting force F_{D2} to the tissue. Simultaneously, the third robotic arm **13850** retracts a portion of liver tissue away from the current surgical cut location, further exposing the next surgical cut location. In order to move the portion of liver tissue out of the way of the advancing second robotic arm **13840**, the third robotic arm **13850** applies a retracting force F_{R3} away from the second robotic arm **13840**. In various exemplifications, as the second robotic arm **13840** advances further into the surgical site, the control unit of the robotic surgical system directs the third robotic arm **13850** to increase the exerted retracting force F_{R3} to continue exposing the next surgical cut location. While FIG. 40 depicts a particular surgical procedure and specific robotic arms, any suitable surgical procedure can be performed, and any suitable combination of robotic arms can utilize the control algorithms disclosed herein.

[0433] FIG. 41 depicts graphical representations **13852**, **13854** of the forces exerted by the robotic arms **13830**, **13840**, and **13850** of FIG. 40 and the relative locations of the robotic arm **13830**, **13840**, and **13850**, respectively, from the particular surgical procedure detailed above. The graphical display **13852** in FIG. 41 represents the exerted forces of each robotic arm **13830**, **13840**, and **13850** over a period of time, while the graphical display **13854** represents the relative positions of each robotic arm **13830**, **13840**, and **13850** over the same period of time. As discussed above, the first robotic arm **13830** is configured to exert a holding force F_{H1} on a portion of stomach connective tissue. The holding force F_{H1} is represented by a solid line on the graphs **13852**, **13854**. The second robotic arm **13840** is configured to exert a dragging and/or cutting force F_{D2} on the stomach connective

tive tissue. The dragging force F_{D2} is represented by a dash-dot line on the graphs **13852**, **13854**. The third robotic arm **13850** is configured to exert a retracting force F_{R3} on a portion of liver tissue. The retracting force F_{R3} is represented by a dotted line on the graphs **13852**, **13854**.

[0434] In various instances, the control unit of the robotic surgical system imposes at least one force threshold, such as a maximum force threshold, as depicted in the graphical display **13852**. Thus, the third robotic arm **13850** is prevented from exerting a retraction force F_{R3} greater than the maximum retraction force threshold. Such maximum force limits are imposed in order to avoid tissue trauma and/or avoid damage to the various robotic arms **13830**, **13840**, and **13850**, for example.

[0435] Additionally or alternatively, the control unit **13820** of the robotic surgical system **13800** can impose least one force threshold, such as a minimum force threshold, as depicted in the graphical display **13852**. In the depicted instance, the first robotic arm **13830** is prevented from exerting a holding force F_{H1} less than the minimum holding force threshold. Such minimum force limits are imposed in order to avoid maintain appropriate tissue tension and/or visibility of the surgical site, for example.

[0436] In various instances, the control unit **13820** of the robotic surgical system **13800** imposes maximum force differentials detected between various robotic arms during a load control mode. In order to set maximum force differentials, the control unit **13820** of the robotic surgical system is configured to continuously monitor the difference in magnitude and direction of opposing forces by the robotic arms. As stated above, the first robotic arm **13830** is configured to hold a portion of the stomach connective tissue by exerting a holding force F_{H1} . The second robotic arm **13840** is configured to apply a dragging force F_{D2} , which opposes the holding force F_{H1} exerted by the first robotic arm **13830**. In various instances, maximum force differentials prevent inadvertent overloading and/or damaging an object caught between the robotic arms **13830**, **13840**, and **13850**. Such objects include, for example, surrounding tissue and/or surgical components like clasps, gastric bands, and/or sphincter reinforcing devices. $F_{max\ opposing}$ represents the maximum force differential set by the control unit **13820** in this particular exemplification.

[0437] As can be seen in the graphical display **13852**, the holding force F_{H1} and the dragging force F_{D2} both increase in magnitude at the beginning of the surgical procedure. Such an increase in magnitudes can indicate a pulling of the tissue. The holding force F_{H1} and the dragging force F_{D2} increase in opposite directions to a point where the difference between the opposing forces is equal to $F_{max\ opposing}$. In the graphic display **13852**, the slanted lines highlight the point in time when $F_{max\ opposing}$ is reached. Upon reaching $F_{max\ opposing}$, the processor **13822** instructs the first robotic arm **13830** to reduce the holding force F_{H1} and continues to allow the second robotic arm **13840** to exert the dragging force F_{D2} at the same value, and may allow a clinician to increase the dragging force. In various instances, the value of $F_{max\ opposing}$ is set by the processor **13822** based on various variables, such as the type of surgery and/or relevant patient demographics. In various instances, $F_{max\ opposing}$ is a default value stored in a memory of the processor **13822**.

[0438] The relative positions of the robotic arms **13830**, **13840**, and **13850** within the surgical site are depicted in the graph display **13854** of FIG. 41. As the first robotic arm

13830 exerts a holding force F_{H1} on the stomach connective tissue and the third robotic arm **13850** exerts a retracting force F_{R3} on the liver tissue, the surgical site becomes clear and allows the second robotic arm **13840** to exert a dragging and/or cutting force F_{D2} on the desired tissue. The second robotic arm **13840** and the third robotic arm **13850** become farther away from the first robotic arm **13830** as the procedure progresses. When the force differential $F_{max\ opposing}$ is reached between the holding force F_{H1} and the dragging force F_{D2} , the first robotic arm **13830** is moved closer towards the second robotic arm **13840**, lessening the exerted holding force F_{H1} by the first robotic arm **13830**. In one aspect, the processor **13822** can transition the first robotic arm **13830** from the load control mode into a position control mode such that the position of the first robotic arm **13830** is held constant. As depicted in the graphical representations of FIG. 41, when the first robotic arm **13830** is held in a constant position, the force control for the second robotic arm **13840** can continue to displace the second robotic arm **13840**.

[0439] In various instances, the control unit **13820** of the robotic surgical system directs the first robotic arm **13830** to hold a specific position until a pre-determined force threshold between the first robotic arm **13830** and a second robotic arm **13840** is reached. When the pre-determined force threshold is reached, the first robotic arm **13830** is configured to automatically move along with the second robotic arm **13840** in order to maintain the pre-determined force threshold. The first robotic arm **13830** stops moving (or may move at a different rate) when the detected force of the second robotic arm **13840** no longer maintains the pre-determined force threshold.

[0440] In various instances, the control unit **13820** of the robotic surgical system is configured to alternate between the position control mode and the load control mode in response to detected conditions by the robotic arms **13830**, **13840**, and **13850**. For example, when the first robotic arm **13830** and the second robotic arm **13840** of the robotic surgical system **13800** are freely moving throughout a surgical site, the control unit **13820** may impose a maximum force that each arm **13830**, **13840** can exert. In various instances, the first and second arms **13830**, **13840** each include a sensor configured to detect resistance. In other instances, the sensors can be positioned on a surgical tool, such as an intelligent surgical stapler or jawed tool. A resistance can be encountered upon contact with tissue and/or other surgical instruments. When such resistance is detected, the control unit **13820** may activate the load control mode and lower the exerted forces by one and/or more than one of the robotic arms **13830**, **13840** to, for example, reduce damage to the tissue. In various instances, the control unit **13820** may activate the position control mode and move the one and/or more than one of the robotic arms **13830**, **13840** to a position where such resistance is no longer detected.

[0441] In one aspect, the processor **13822** of the control unit **13820** is configured to switch from the load control mode to the position control mode upon movement of a surgical tool mounted to one of the robotic arms **13830**, **13840** outside a defined surgical space. For example, if one of the robotic arms **13830**, **13840** moves out of a defined boundary around the surgical site, or into abutting contact with an organ or other tissue, or too close to another surgical device, the processor **13822** can switch to a position control

mode and prevent further movement of the robotic arm **13830**, **13840** and/or move the robotic arm **13830**, **13840** back within the defined surgical space.

[0442] Turning now to the flow chart shown in FIG. 42, an algorithm **13500** is initiated at step **13501** when the clinician and/or the robotic surgical system activates one or more of the robotic arms at step **13505**. The algorithm **13500** can be employed by the robotic surgical system **13800** in FIG. 39, for example. Each robotic arm is in signal communication with the processor **13822** of the robotic surgical system. Following activation, each robotic arm is configured to send information to the processor. In various instances, the information may include, for example, identification of the tool attachment and/or the initial position of the activated robotic arm. In various instances, such information is communicated automatically upon attachment of the tool to the robotic arm, upon activation of the robotic arm by the robotic surgical system, and/or after interrogation of the robotic arm by the processor, although the information may be sent at any suitable time. Furthermore, the information may be sent automatically and/or in response to an interrogation signal.

[0443] Based on the information gathered from each of the activated robotic arms at step **13510**, the processor is configured to set a position limit for each specific robotic arm within a work envelope of the robotic surgical system at step **13515**. The position limit can set three-dimensional boundaries for where each robotic arm can travel. The setting of position limits allows for efficient and cooperative usage of each activated robotic arm while, for example, preventing trauma to surrounding tissue and/or collisions between activated robotic arms. In various instances, the processor includes a memory including a set of stored data to assist in defining each position limit. The stored data can be specific to the particular surgical procedure, the robotic tool attachment, and/or relevant patient demographics, for example. In various instances, the clinician can assist in the definition of the position limit for each activated robotic arm. The processor is configured to determine if the robotic arms are still activated at step **13520**. If the processor determines that the robotic arms are no longer activated, the processor is configured to end position monitoring at step **13522**. Once the processor determines that the robotic arms are still activated, the processor is configured to monitor the position of each activated robotic arm at step **13525**.

[0444] The processor is then configured to evaluate whether the detected position is within the predefined position limit(s) at step **13530**. In instances where information is unable to be gathered from the robotic arm and clinician input is absent, a default position limit is assigned at step **13533**. Such a default position limit assigns a conservative three-dimensional boundary to minimize, for example, tissue trauma and/or collisions between robotic arms. If the detected limit is within the position limit, the processor is configured to allow the robotic arm(s) to remain in position and/or freely move within the surgical site at step **13535**, and the monitoring process continues as long as the robotic arm is still activated. If the detected limit is outside of the position limit, the processor is configured to move the robotic arm back into the position limit at step **13532**, and the monitoring process continues as long as the robotic arm is still activated.

[0445] The processor is configured to continuously monitor the position of each robotic arm at step **13525**. In various instances, the processor is configured to repeatedly send

interrogation signals in pre-determined time intervals. As discussed above, if the detected position exceeds the position limit set for the specific robotic arm, in certain instances, the processor is configured to automatically move the robotic arm back within the three-dimensional boundary at step **13532**. In certain instances, the processor is configured to re-adjust the position limits of the other robotic arms in response to one robotic arm exceeding its original position limit. In certain instances, prior to moving the robotic arm back within its position limit and/or adjusting the position limits of the other robotic arms, the processor is configured to alert the clinician. If the detected position is within the position limit set for the robotic arm, the processor permits the robotic arm to remain in the same position and/or freely travel until the detected position exceeds the position limit at step **13535**. If the processor is unable to detect the position of the robotic arm, the processor is configured to alert the clinician and/or assign the robotic arm with the default position limit at step **13533**. The processor is configured to monitor the position of each robotic arm until the surgery is completed and/or the robotic arm is deactivated.

[0446] Similar to the algorithm of FIG. **42**, the flow chart of FIG. **43** depicts an algorithm **13600** that is initiated at step **13601** when a clinician and/or a robotic surgical system activates one or more of the robotic arms at step **13605**. The algorithm **13600** can be employed by the robotic surgical system **13800** in FIG. **39**, for example. Each robotic arm is in signal communication with the processor. Following activation, each robotic arm is configured to send information to the processor at step **13610**. In various instances, the information may include, for example, identification of the tool attachment, exerted forces detected by one or more force sensors on the robotic arm, and/or the initial position of the activated robotic arm. In various instances, such information is communicated automatically upon attachment of the tool to the robotic arm, upon activation of the robotic arm by the robotic surgical system, and/or after interrogation of the robotic arm by the processor, although the information may be sent at any suitable time. Furthermore, the information may be sent automatically and/or in response to an interrogation signal.

[0447] Based on the information gathered from each of the activated robotic arms, the processor is configured to set a force limit for each specific robotic arm at step **13615**. The force limit sets maximum and minimum force thresholds for forces exerted by each robotic arm. Additionally or alternatively, a force limit can be the maximum force differential between two or more arms. The setting of force limits allows for efficient and cooperative usage of all of the activated robotic arms while, for example, preventing trauma to surrounding tissue and/or damage to the robotic arms. In various instances, the processor includes a memory including a set of stored data to assist in defining each force limit. The stored data can be specific to the particular surgical procedure, the robotic tool attachment, and/or relevant patient demographics, for example. In various instances, the clinician can assist in the definition of the force limit for each activated robotic arm. In instances where information is unable to be gathered from the robotic arm and clinician input is absent, a default force limit is assigned. Such a default force limit assigns conservative maximum and minimum force thresholds to minimize, for example, tissue trauma and/or damage to the robotic arms.

[0448] The processor is configured to determine if the robotic arm is active at step **13620**. If the processor determines that the robotic arm has been deactivated, the processor is configured to end force monitoring at step **13622**. Once it has been determined that the robotic arm is still activated at step **13620**, the processor is configured to continuously monitor the force exerted by each robotic arm at step **13625**. In various instances, the processor is configured to repeatedly send interrogation signals in pre-determined time intervals. If the detected force exceeds the maximum force threshold set for the specific robotic arm, in certain instances, the processor is configured to automatically decrease the force exerted by the robotic arm and/or decrease an opposing force exerted by another robotic arm at step **13632**. In certain instances, the processor is configured to re-adjust the force limits assigned to the other robotic arms in response to one robotic arm exceeding its original force limits. In certain instances, prior to adjusting the force exerted by the robotic arm, adjusting the opposing force exerted by another robotic arm, and/or adjusting the force limits of the other robotic arms, the processor is configured to alert the clinician. If the detected force is within the force limit set for the robotic arm, the robotic arm is permitted to maintain the exertion of the force and/or the clinician can increase or decrease the exerted force until the force is out of the set force limit at step **13635**. If the processor is unable to detect the exerted force of the robotic arm, the processor is configured to alert the clinician and/or assign the robotic arm with a default force limit at step **13633**. The processor is configured to monitor the exerted force of each robotic arm until the surgery is completed and/or the robotic arm is deactivated at step **13620**.

[0449] Similar to the algorithms of FIGS. **42** and **43**, the flow chart of FIG. **44** depicts an algorithm **13700** that is initiated **13701** when a clinician and/or a robotic surgical system activates one or more of the robotic arms **13705**. The algorithm **13700** can be employed by the robotic surgical system **13800** in FIG. **39**, for example. Each robotic arm is in signal communication with the processor. Following activation, each robotic arm is configured to send information to the processor at step **13710**. In various instances, the information may include, for example, identification of the tool attachment, forces detected by one or more force sensors on the robotic arm, and/or the initial position of the activated robotic arm. In various instances, such information is communicated automatically upon attachment of the tool to the robotic arm, upon activation of the robotic arm by the robotic surgical system, and/or after interrogation of the robotic arm by the processor, although the information may be sent at any suitable time. In various instances, the information is sent automatically and/or in response to an interrogation signal.

[0450] Based on the information gathered from all of the activated robotic arms, the processor is configured to set both a position limit within a work envelope of the robotic surgical system and a force limit for each specific robotic arm at step **13715**. The position limit sets three-dimensional boundaries for where each robotic arm can travel. The setting of position limits allows for efficient and cooperative usage of all of the activated robotic arms while, for example, preventing trauma to surrounding tissue and/or collisions between activated robotic arms. The force limit sets maximum and/or minimum force thresholds for forces exerted by each robotic arm. Additionally or alternatively, a force limit

can be the maximum force differential between two or more arms. The setting of force limits allows for efficient and cooperative usage of the activated robotic arms while, for example, preventing trauma to surrounding tissue and/or damage to the robotic arms.

[0451] In various instances, the processor includes a memory including a set of stored data to assist in defining each position limit and force limit. The stored data can be specific to the particular surgical procedure, the robotic tool attachment, and/or relevant patient demographics, for example. In various instances, the clinician can assist in the definition of the position limit and force limit for each activated robotic arm. In instances where information is unable to be gathered from the robotic arm and clinician input is absent, a default position limit and/or default force limit is assigned to the robotic arm. Such a default position limit assigns a conservative three-dimensional boundary to minimize, for example, tissue trauma and/or collisions between robotic arms, while the default force limit assigns conservative maximum and/or minimum force thresholds to minimize, for example, tissue trauma and/or damage to the robotic arms. In various instances, the processor is configured to adjust the position limit of one robotic arm based on the force limit of another robotic arm, adjust the force limit of one robotic arm based on the position limit of another robotic arm, and vice versa.

[0452] The processor is configured to determine whether the robotic arm is active at step **13720**. Once the processor has determined that the robotic arm is activated at step **13720**, the processor is configured to continuously monitor the position of each arm **13737** and the force exerted by each robotic arm at step **13725**. If the robotic arm is no longer activated, the processor is configured to end position monitoring at step **13727** and end force monitoring at step **13722**. In various instances, the processor is configured to repeatedly send interrogation signals in pre-determined time intervals. If the detected position exceeds the position limit set for the specific robotic arm, in certain instances, the processor is configured to automatically move the robotic arm back within the three-dimensional boundary at step **13742**. In certain instances, prior to moving the robotic arm back within its position limit, the processor is configured to alert the clinician. If the detected position is within the position limit set for the robotic arm, the robotic arm is permitted to remain in the same position and/or freely travel until the detected position exceeds the position limit at step **13745**. If the processor is unable to detect the position of the robotic arm, the processor is configured to alert the clinician and/or rewrite the original position limit of the robotic arm with the default position limit at step **13743**. The processor is configured to monitor the position of each robotic arm until the surgery is completed and/or the robotic arm is deactivated.

[0453] In certain instances, the robotic surgical system includes a manual override configured to control the position of each robotic arm. If the detected force exceeds the maximum force threshold set for the specific robotic arm, in certain instances, the processor is configured to automatically decrease the force exerted by the robotic arm and/or decrease an opposing force exerted by another robotic arm at step **13732**. In certain instances, prior to decreasing the force exerted by the robotic arm and/or decrease the opposing force exerted by another robotic arm, the processor is configured to alert the clinician. If the detected force is within the force limit set for the robotic arm, the robotic arm

is permitted to maintain the exertion of the force and/or increase or decrease the exerted force until the force is out of the set force limit at step **13735**. If the processor is unable to detect the exerted force of the robotic arm, the processor is configured to alert the clinician and/or rewrite the original force limit of the robotic arm with the default force limit at step **13733**. The processor is configured to monitor the exerted force of each robotic arm until the surgery is completed and/or the robotic arm is deactivated.

[0454] In various instances, the position monitoring system and the force monitoring system are interconnected. In certain instances, the force monitoring system can override the resultant decision **13742**, **14743**, **14745** of the position detection step **13740**. In certain instances, the position monitoring system can override the resultant decision **13732**, **13733**, **13735** of the force detection step **13730**. In other instances, the position monitoring system and the force monitoring system are independent of one another.

[0455] A clinician can manually override the automatic adjustments implemented in the automatic load and/or position control mode(s) described herein. The manual override can be a one-time adjustment to the surgical robot. In other instances, the manual override can be a setting that turns off the automatic load and/or position mode for a specific surgical action, a specific duration, and/or a global override for the entire procedure.

[0456] In one aspect, the robotic surgical system includes a processor and a memory communicatively coupled to the processor, as described herein. The processor is communicatively coupled to a first force sensor and a second force sensor, and the memory stores instructions executable by the processor to affect cooperative movement of a first robotic arm and a second robotic arm based on a first input from the first force sensor and from a second input from the second force sensor in a load control mode, as described herein.

[0457] In various aspects, the present disclosure provides a control circuit to affect cooperative movement of a first robotic arm and a second robotic arm, as described herein. In various aspects, the present disclosure provides a non-transitory computer readable medium storing computer readable instructions which, when executed, cause a machine to affect cooperative movement of a first robotic arm and a second robotic arm, as described herein.

[0458] During a particular surgical procedure, clinicians may rely on one or more powered handheld surgical instruments in addition to a robotic surgical system. In various instances, the instruments are controlled and monitored through different platforms, which may inhibit communication between the instruments and the robotic surgical system. For example, the instruments can be produced by different manufacturers and even by competitors. Such instruments may have different communication packages and/or communication and/or linking protocols. The lack of communication between a powered instrument and the robotic surgical system may hinder cooperative and/or coordinated usage and may complicate the surgical procedure for the clinician. For example, each surgical instrument may include an individual display to communicate various information and operating parameters. In such a scenario, a clinician may have to look at numerous instrument-specific displays to monitor the operating status of and analyze data gathered by each device.

[0459] In various instances, a robotic surgical system is configured to detect the presence of other powered surgical

instruments that are controlled by platforms other than the robotic surgical system. The robotic surgical system can incorporate a hub, i.e., a robotic hub like the robotic hubs **122** (FIG. 2) and **222** (FIG. 9), which can detect other powered surgical instruments, for example. In other instances, a stand-alone surgical hub like the hub **106** (FIGS. 1-3) or the hub **206** (FIG. 9) in communication with the robotic surgical system can facilitate detection of the non-robotic surgical instruments and cooperative and/or coordinated usage of the detected surgical instruments with the robotic surgical system. The hub, which can be a robotic hub or a surgical hub, is configured to display the position and orientation of the powered surgical instruments with respect to the work envelope of the robotic surgical system. In certain instances, the work envelope can be an operating room, for example. A surgical hub having spatial awareness capabilities is further described herein and in U.S. Provisional Patent Application Ser. No. 62/611,341, titled INTERACTIVE SURGICAL PLATFORM, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety. In one aspect, the hub can first ascertain the boundaries of the work envelope and then detect the presence of other powered surgical instruments within the work envelope.

[0460] FIG. 45 depicts a surgical system **13860** including a robotic surgical system **13865**, a surgical instrument **13890**, and a surgical hub **13870**. The surgical instrument **13890** is a powered handheld instrument, and can be a motorized surgical stapler, such as the motorized linear stapler depicted in FIG. 46, for example. The surgical system **13865** can be similar in many respects to the robotic surgical system **13000** (FIG. 23), for example. As described herein, the surgical hub **13870** can be incorporated into the robotic surgical system **13865**, for example. The surgical hub **13870** is configured to be in signal communication with the robotic surgical system **13865** and the surgical instrument **13890**. In other instances, the surgical system **13860** can include additional handheld surgical instruments. The robotic surgical system **13865** includes a robot **13861**, which can be similar to the robot **13002**, for example. The robotic surgical system **13865** also includes a control unit **13862** and a surgeon's command console, or remote control module, **13864**. The surgeon's command console **13864** is configured to receive a clinician input. The control unit **13862** includes a robot display **13868** and a processor **13866**. The surgical instrument **13890** includes a display **13894** and a processor **13892**.

[0461] In various instances, the surgical hub **13870** includes a surgical hub display **13880**, which can be similar to the displays of the visualization system **108** (FIG. 1). The surgical hub display **13880** can include, for example, a heads up display. The surgical hub **13880** is configured to detect the presence of the surgical instrument **13890** within a certain distance of the surgical hub **13870**. For example, the surgical hub **13870** is configured to detect the presence of all activated surgical instruments **13890** within one operating room, although any suitable distance can be monitored. In various instances, the surgical hub **13870** is configured to display the presence of all activated surgical instruments **13890** on the surgical hub display **13880**.

[0462] A particular handheld surgical instrument communicates via a first communication process through a first language. A particular robotic surgical system communicates via a second communication process through a second

language. In various instances, the first communication process is the same as the second communication process. When the first communication process is the same as the second communication process, the surgical instrument **13890** is configured to directly communicate information to the surgical hub **13870** and/or to the robotic surgical system **13865**. Such information includes, for example, a model number and/or type of the surgical instrument, a position of the surgical instrument, an operating status of the surgical instrument, and/or any other relevant parameter of the surgical instrument.

[0463] In various instances, the first communication process is different from the second communication process. For example, a surgical system (e.g. a robot) developed by a first manufacturer may utilize a first proprietary language or communication scheme and a surgical system (e.g. a handheld surgical tool) developed by a second manufacturer may utilize a second, different proprietary language or communication scheme. Despite the language difference/barrier, the surgical hub **13870** and/or surgical robot **13865** is configured to sense surgical instruments **13890** that operate on different communication processes. When the surgical hub **13870** does not recognize the communication process utilized by a particular powered handheld surgical instrument, the surgical hub **13870** is configured to detect various signals, such as Wi-Fi and Bluetooth transmissions emitted by activated powered handheld surgical instruments. Based on the detected signal transmissions, the surgical hub **13870** is configured to alert the clinician of all powered handheld surgical instruments that do not use the same communication process as the robotic surgical system **13865**. All data received from newly-detected powered handheld surgical instruments can be stored within the surgical hub **13870** so that the newly-detected powered handheld surgical instruments are recognized by the surgical hub **13870** in the future.

[0464] In various instances, the surgical hub **13870** is configured to detect the presence of powered handheld surgical instruments by sensing a magnetic presence of a battery, power usage, and/or electro-magnetic field emitted from activated powered handheld surgical instruments, regardless of whether the activated powered handheld surgical instruments made any attempt to communicate with another surgical instrument, such as the robotic surgical system.

[0465] The robot **13861** and the surgical instrument **13890** are exemplified in an example surgical procedure in FIG. 46. In this exemplification, the surgical instrument **13890** is an articulating linear stapler. As depicted in FIG. 46, the surgical instrument **13890** includes a motor **13895** in the handle **13892** thereof. In other instances, the surgical instrument **13890** can include a plurality of motors positioned throughout the surgical instrument. The motor **13895** is configured to emit an electromagnetic field **13896**, which can be detected by the robotic surgical system **13865** or the surgical hub **13870**. For example, the main robot tower or the modular control tower of the surgical hub **13870** can include a receiver for detecting the electromagnetic fields within the operating room.

[0466] In one aspect, a processor of the robotic surgical system (e.g. a processor of the control unit **13862**) is configured to calculate a boundary around the surgical instrument **13890**. For example, based on the electromagnetic field **13896** and corresponding type of surgical instrument, the processor can determine the dimensions of the

surgical instrument **13890** and possible range of positions thereof. For example, when the surgical instrument **13890** includes one or more articulation joints **13891**, the range of positions can encompass the articulated positions of the surgical instrument **13890**.

[0467] In one instance, the robotic surgical system can calculate a first wider boundary B_2 around the surgical instrument. When a robotic surgical tool approaches the wider boundary B_2 , the robotic surgical tool **13861** can issue a notification or warning to the surgeon that the robotic surgical tool attached to the robot **13861** is approaching another surgical instrument **13890**. In certain instances, if the surgeon continues to advance the robotic surgical tool toward the surgical instrument **13890** and to a second narrower boundary B_1 , the robotic surgical system **13865** can stop advancing the robotic surgical tool. For example, if the robotic surgical tool crosses the narrower boundary B_1 , advancement of the robotic surgical tool can be stopped. In such instances, if the surgeon still desires to continue advancing the robotic surgical tool within the narrower boundary B_1 , the surgeon can override the hard stop feature of the robotic surgical system **13865**.

[0468] Referring again to FIG. 45, the surgical system **13860** includes multiple display monitors. Each handheld surgical instrument **13890** and the robotic surgical system **13865** is configured to communicate a video and/or image feed representative of the display on each device to the surgical hub **13870** and/or the hub display **13880**. Such video and/or image feeds can include operating parameters of and/or detected conditions by each handheld surgical instrument **13890** and/or the robotic surgical system **13865**. The hub **13870** is configured to control the displayed video and/or image feeds on each of the one or more display monitors throughout the system **13800**. In various instances, each of the display monitors displays an individual video and/or image feed from a particular surgical device or system. In various instances, the individual video and/or image feed can be overlaid with additional information and/or video and/or image feeds from other devices or systems. Such information can include operating parameters and/or detected conditions. The surgical hub **13870** is configured to request which display monitor displays which video and/or image feed. In other words, the communication link between the surgical hub **13870** and the hub display **13880** allows the surgical hub **13870** to dictate which video and/or image feed is assigned to which display monitor, while direct control of the one or more display monitors remains with the video hub. In various instances, the hub display **13880** is configured to separate one or more of the display monitors from the surgical hub **13870** and allow a different surgical hub or surgical device to display relevant information on the separated display monitors.

[0469] In various instances, the surgical hub is configured to communicate stored data with other data systems within an institution data barrier allowing for cooperative utilization of data. Such established data systems may include, for example, an electronic medical records (EMR) database. The surgical hub is configured to utilize the communication between the surgical hub and the EMR database to link overall surgical trends for the hospital with local data sets recorded during use of the surgical hub.

[0470] In various instances, the surgical hub is located in a particular operating room at a hospital and/or surgery center. As shown in FIG. 47, the hospital and/or surgery

center includes operating rooms, OR_1 , OR_2 , OR_3 , and OR_4 . Three of the operating rooms OR_2 , OR_3 , and OR_4 shown in FIG. 47 includes a surgical hub **13910**, **13920**, **13930**, respectively, however any suitable number of surgical hubs can be used. Each surgical hub **13910**, **13920**, **13930** is configured to be in signal communication with one another, represented by signal arrows A. Each surgical hub **13910**, **13920**, **13930** is also configured to be in signal communication with a primary server **13940**, represented by signal arrows B in FIG. 47.

[0471] In various exemplifications, as data is communicated between the surgical hub(s) **13910**, **13920**, **13930** and the various surgical instruments during a surgical procedure, the surgical hub(s) **13910**, **13920**, **13930** are configured to temporarily store the communicated data. At the end of the surgical procedure and/or at the end of a pre-determined time period, each surgical hub **13910**, **13920**, **13930** is configured to communicate the stored information to the primary server **13940**. Once the stored information is communicated to the primary server **13940**, the information can be deleted from the memory of the individual surgical hub **13910**, **13920**, **13930**. The stored information is communicated to the primary server **13940** to alleviate the competition amongst the surgical hubs **13910**, **13920**, **13930** for bandwidth to transmit the stored data to cloud analytics "C", for example. Instead, the primary server **13940** is configured to compile and store and communicated data. The primary server **13940** is configured to be the single clearinghouse for communication of information back to the individual surgical hubs **13910**, **13920**, **13930** and/or for external downloading. In addition, as all of the data is stored in one location in the primary server **13940**, the data is better protected from data destructive events, such as power surges and/or data intrusion, for example. In various instances, the primary server **13940** includes additional server-level equipment that allows for better data integrity. Examples of cloud systems are further described herein and in U.S. Provisional Patent Application Ser. No. 62/611,340, titled CLOUD-BASED MEDICAL ANALYTICS, filed Dec. 28, 2017, the disclosure of which is herein incorporated by reference in its entirety.

[0472] Referring to FIGS. 47 and 48, as data begins to be communicated from each control hub **13910**, **13920**, **13930** to the primary server **13940**, a queue **13990** is created to prioritize the order in which data is communicated. In various instances, the queue **13990** prioritizes data as first in, first out, although any suitable prioritization protocol can be used. In various instances, the queue **13990** is configured to re-prioritize the order in which received data is communicated when priority events and/or abnormal data are detected. As illustrated in FIG. 48, a first surgical hub communicates a first set of data at a time $t=1$ at block **13960**. As the first set of data is the only data in the queue for external output at block **13992**, the first set of data is the first to be communicated. Thus, the queue **13990** prioritizes the first set of data for external output at block **13965**. A second surgical hub communicates a second set of data at a time $t=2$ at block **13970**. At the time $t=2$, the first set of data has not been externally communicated at block **13994**. However, because no priority events and/or abnormal data are present in the second set of data, the second set of data is the second in line to be externally communicated at block **13975**. A third surgical hub communicates a third set of data flagged as urgent at a time $t=3$ at block **13980**. At the time $t=3$, the

first set of data and the second set of data have not been externally communicated, however a priority event has been detected in the third set of data at block **13985**. The queue is configured to re-prioritize the sets of data to allow the prioritized third set of data to be in the first position for external output at block **13996** above the first set of data and the second set of data collected at time $t=1$ and $t=2$, respectively.

[0473] In one aspect, the surgical hub includes a processor and a memory communicatively coupled to the processor, as described herein. The memory stores instructions executable by the processor to detect the presence of a powered surgical instrument and represent the powered surgical instrument on a hub display, as described herein.

[0474] In various aspects, the present disclosure provides a control circuit to detect the presence of a powered surgical instrument and represent the powered surgical instrument on a hub display, as described herein. In various aspects, the present disclosure provides a non-transitory computer readable medium storing computer readable instructions which, when executed, cause a machine to detect the presence of a powered surgical instrument and represent the powered surgical instrument on a hub display, as described herein.

[0475] The entire disclosures of:

[0476] U.S. Pat. No. 9,072,535, filed May 27, 2011, titled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, which issued Jul. 7, 2015;

[0477] U.S. Pat. No. 9,072,536, filed Jun. 28, 2012, titled DIFFERENTIAL LOCKING ARRANGEMENTS FOR ROTARY POWERED SURGICAL INSTRUMENTS, which issued Jul. 7, 2015;

[0478] U.S. Pat. No. 9,204,879, filed Jun. 28, 2012, titled FLEXIBLE DRIVE MEMBER, which issued on Dec. 8, 2015;

[0479] U.S. Pat. No. 9,561,038, filed Jun. 28, 2012, titled INTERCHANGEABLE CLIP APPLIER, which issued on Feb. 7, 2017;

[0480] U.S. Pat. No. 9,757,128, filed Sep. 5, 2014, titled MULTIPLE SENSORS WITH ONE SENSOR AFFECTING A SECOND SENSOR'S OUTPUT OR INTERPRETATION, which issued on Sep. 12, 2017;

[0481] U.S. patent application Ser. No. 14/640,935, titled OVERLAID MULTI SENSOR RADIO FREQUENCY (RF) ELECTRODE SYSTEM TO MEASURE TISSUE COMPRESSION, filed Mar. 6, 2015, now U.S. Patent Application Publication No. 2016/0256071;

[0482] U.S. patent application Ser. No. 15/382,238, titled MODULAR BATTERY POWERED HAND-HELD SURGICAL INSTRUMENT WITH SELECTIVE APPLICATION OF ENERGY BASED ON TISSUE CHARACTERIZATION, filed Dec. 16, 2016, now U.S. Patent Application Publication No. 2017/0202591; and

[0483] U.S. patent application Ser. No. 15/237,753, titled CONTROL OF ADVANCEMENT RATE AND APPLICATION FORCE BASED ON MEASURED FORCES, filed Aug. 16, 2016, now U.S. Patent Application Publication No. 2018/0049822;

are herein incorporated by reference in their respective entireties.

[0484] Various aspects of the subject matter described herein are set out in the following numbered examples.

Example 1

[0485] A surgical system comprises a robotic tool, a robot control system, a surgical instrument, and a surgical hub comprising a display. The robot control system comprises a control console and a control unit in signal communication with the control console and the robotic tool. The surgical hub is in signal communication with the robot control system, and wherein the surgical hub is configured to detect the surgical instrument and represent the surgical instrument on the display.

Example 2

[0486] The surgical system of Example 1, wherein the surgical instrument comprises a motorized, autonomous surgical instrument.

Example 3

[0487] The surgical system of any one of Examples 1 and 2, wherein the surgical instrument is independent of the robot control system.

Example 4

[0488] The surgical system of any one of Examples 1-3, wherein the surgical hub is configured to display a location of the surgical instrument on the display.

Example 5

[0489] The surgical system of any one of Examples 1-4, wherein the surgical hub is configured to display an operating status of the surgical instrument on the display.

Example 6

[0490] The surgical system of any one of Examples 1-5, wherein the display comprises a heads up display.

Example 7

[0491] The surgical system of any one of Examples 1-6, wherein the surgical hub further comprises a situational awareness module configured to recommend a surgical function based on the detection of the surgical instrument relative to a position of the robotic tool.

Example 8

[0492] A surgical system comprises a robotic tool, a robot control system, a surgical instrument operable in a plurality of operating states, and a surgical hub comprising a display. The robot control system comprises a control console and a control unit in signal communication with the control console and the robotic tool. The surgical hub is in signal communication with the robot control system, and the surgical hub is configured to detect an activated operating state of the surgical instrument and represent the active operating state on the display.

Example 9

[0493] The surgical system of Example 8, wherein the surgical instrument comprises a motorized surgical device.

Example 10

[0494] The surgical system of any one of Examples 8 and 9, wherein the surgical instrument is an autonomous surgical instrument.

Example 11

[0495] The surgical system of any one of Examples 8-10, wherein the surgical hub is configured to display an orientation of the surgical instrument on the display.

Example 12

[0496] The surgical system of any one of Examples 8-11, wherein the surgical hub is configured to display an operating status of the surgical instrument on the display.

Example 13

[0497] The surgical system of any one of Examples 8-12, further comprising a situational awareness module configured to recommend a surgical function based on the detection of the surgical instrument relative to a position of the robotic tool.

Example 14

[0498] A surgical system comprises a robotic tool, a robot control system, a surgical instrument, a surgical hub, and a display in signal communication with the surgical hub. The robot control system comprises a control console and a control unit in signal communication with the control console and the robotic tool. The surgical hub is in signal communication with the robot control system, and the surgical hub is configured to detect the surgical instrument. The surgical hub is configured to represent the surgical instrument on the display.

Example 15

[0499] The surgical system of Example 14, wherein the surgical instrument comprises a motorized surgical instrument.

Example 16

[0500] The surgical system of any one of Examples 14 and 15, wherein the surgical instrument is independent of the robot control system.

Example 17

[0501] The surgical system of any one of Examples 14-16, wherein the surgical hub is configured to display a position of the surgical instrument on the display.

Example 18

[0502] The surgical system of any one of Examples 14-17, wherein the surgical hub is configured to display an operating status of the surgical instrument on the display.

Example 19

[0503] The surgical system of any one of Examples 14-18, wherein the display comprises a heads up display.

Example 20

[0504] The surgical system of any one of Examples 14-19, further comprising a situational awareness module configured to recommend a surgical function based on the detection of the surgical instrument relative to a position of the robotic tool.

[0505] While several forms have been illustrated and described, it is not the intention of the applicant to restrict or limit the scope of the appended claims to such detail. Numerous modifications, variations, changes, substitutions, combinations, and equivalents to those forms may be implemented and will occur to those skilled in the art without departing from the scope of the present disclosure. Moreover, the structure of each element associated with the described forms can be alternatively described as a means for providing the function performed by the element. Also, where materials are disclosed for certain components, other materials may be used. It is therefore to be understood that the foregoing description and the appended claims are intended to cover all such modifications, combinations, and variations as falling within the scope of the disclosed forms. The appended claims are intended to cover all such modifications, variations, changes, substitutions, modifications, and equivalents.

[0506] The foregoing detailed description has set forth various forms of the devices and/or processes via the use of block diagrams, flowcharts, and/or examples. Insofar as such block diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such block diagrams, flowcharts, and/or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof. Those skilled in the art will recognize that some aspects of the forms disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and/or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, those skilled in the art will appreciate that the mechanisms of the subject matter described herein are capable of being distributed as one or more program products in a variety of forms, and that an illustrative form of the subject matter described herein applies regardless of the particular type of signal bearing medium used to actually carry out the distribution.

[0507] Instructions used to program logic to perform various disclosed aspects can be stored within a memory in the system, such as dynamic random access memory (DRAM), cache, flash memory, or other storage. Furthermore, the instructions can be distributed via a network or by way of other computer readable media. Thus a machine-readable medium may include any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computer), but is not limited to, floppy diskettes, optical disks, compact disc, read-only memory (CD-ROMs), and magneto-optical disks, read-only memory (ROMs), random access memory (RAM), erasable programmable read-only

memory (EPROM), electrically erasable programmable read-only memory (EEPROM), magnetic or optical cards, flash memory, or a tangible, machine-readable storage used in the transmission of information over the Internet via electrical, optical, acoustical or other forms of propagated signals (e.g., carrier waves, infrared signals, digital signals, etc.). Accordingly, the non-transitory computer-readable medium includes any type of tangible machine-readable medium suitable for storing or transmitting electronic instructions or information in a form readable by a machine (e.g., a computer).

[0508] As used in any aspect herein, the term “control circuit” may refer to, for example, hardwired circuitry, programmable circuitry (e.g., a computer processor comprising one or more individual instruction processing cores, processing unit, processor, microcontroller, microcontroller unit, controller, digital signal processor (DSP), programmable logic device (PLD), programmable logic array (PLA), or field programmable gate array (FPGA)), state machine circuitry, firmware that stores instructions executed by programmable circuitry, and any combination thereof. The control circuit may, collectively or individually, be embodied as circuitry that forms part of a larger system, for example, an integrated circuit (IC), an application-specific integrated circuit (ASIC), a system on-chip (SoC), desktop computers, laptop computers, tablet computers, servers, smart phones, etc. Accordingly, as used herein “control circuit” includes, but is not limited to, electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program (e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of random access memory), and/or electrical circuitry forming a communications device (e.g., a modem, communications switch, or optical-electrical equipment). Those having skill in the art will recognize that the subject matter described herein may be implemented in an analog or digital fashion or some combination thereof.

[0509] As used in any aspect herein, the term “logic” may refer to an app, software, firmware and/or circuitry configured to perform any of the aforementioned operations. Software may be embodied as a software package, code, instructions, instruction sets and/or data recorded on non-transitory computer readable storage medium. Firmware may be embodied as code, instructions or instruction sets and/or data that are hard-coded (e.g., nonvolatile) in memory devices.

[0510] As used in any aspect herein, the terms “component,” “system,” “module” and the like can refer to a computer-related entity, either hardware, a combination of hardware and software, software, or software in execution.

[0511] As used in any aspect herein, an “algorithm” refers to a self-consistent sequence of steps leading to a desired result, where a “step” refers to a manipulation of physical quantities and/or logic states which may, though need not necessarily, take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared,

and otherwise manipulated. It is common usage to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. These and similar terms may be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities and/or states.

[0512] A network may include a packet switched network. The communication devices may be capable of communicating with each other using a selected packet switched network communications protocol. One example communications protocol may include an Ethernet communications protocol which may be capable permitting communication using a Transmission Control Protocol/Internet Protocol (TCP/IP). The Ethernet protocol may comply or be compatible with the Ethernet standard published by the Institute of Electrical and Electronics Engineers (IEEE) titled “IEEE 802.3 Standard”, published in December, 2008 and/or later versions of this standard. Alternatively or additionally, the communication devices may be capable of communicating with each other using an X.25 communications protocol. The X.25 communications protocol may comply or be compatible with a standard promulgated by the International Telecommunication Union-Telecommunication Standardization Sector (ITU-T). Alternatively or additionally, the communication devices may be capable of communicating with each other using a frame relay communications protocol. The frame relay communications protocol may comply or be compatible with a standard promulgated by Consultative Committee for International Telegraph and Telephone (CCITT) and/or the American National Standards Institute (ANSI). Alternatively or additionally, the transceivers may be capable of communicating with each other using an Asynchronous Transfer Mode (ATM) communications protocol. The ATM communications protocol may comply or be compatible with an ATM standard published by the ATM Forum titled “ATM-MPLS Network Interworking 2.0” published August 2001, and/or later versions of this standard. Of course, different and/or after-developed connection-oriented network communication protocols are equally contemplated herein.

[0513] Unless specifically stated otherwise as apparent from the foregoing disclosure, it is appreciated that, throughout the foregoing disclosure, discussions using terms such as “processing,” “computing,” “calculating,” “determining,” “displaying,” or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system’s registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

[0514] One or more components may be referred to herein as “configured to,” “configurable to,” “operable/operative to,” “adapted/adaptable,” “able to,” “conformable/conformed to,” etc. Those skilled in the art will recognize that “configured to” can generally encompass active-state components and/or inactive-state components and/or standby-state components, unless context requires otherwise.

[0515] The terms “proximal” and “distal” are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term “proximal” refers to the portion closest to the clinician and the term “distal” refers to the portion located away from the clinician. It will be further

appreciated that, for convenience and clarity, spatial terms such as “vertical”, “horizontal”, “up”, and “down” may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

[0516] Those skilled in the art will recognize that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as “open” terms (e.g., the term “including” should be interpreted as “including but not limited to,” the term “having” should be interpreted as “having at least,” the term “includes” should be interpreted as “includes but is not limited to,” etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases “at least one” and “one or more” to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles “a” or “an” limits any particular claim containing such introduced claim recitation to claims containing only one such recitation, even when the same claim includes the introductory phrases “one or more” or “at least one” and indefinite articles such as “a” or “an” (e.g., “a” and/or “an” should typically be interpreted to mean “at least one” or “one or more”); the same holds true for the use of definite articles used to introduce claim recitations.

[0517] In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited number (e.g., the bare recitation of “two recitations,” without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to “at least one of A, B, and C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, and C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to “at least one of A, B, or C, etc.” is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., “a system having at least one of A, B, or C” would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that typically a disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms unless context dictates otherwise. For example, the phrase “A or B” will be typically understood to include the possibilities of “A” or “B” or “A and B.”

[0518] With respect to the appended claims, those skilled in the art will appreciate that recited operations therein may generally be performed in any order. Also, although various operational flow diagrams are presented in a sequence(s), it

should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently. Examples of such alternate orderings may include overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Furthermore, terms like “responsive to,” “related to,” or other past-tense adjectives are generally not intended to exclude such variants, unless context dictates otherwise.

[0519] It is worthy to note that any reference to “one aspect,” “an aspect,” “an exemplification,” “one exemplification,” and the like means that a particular feature, structure, or characteristic described in connection with the aspect is included in at least one aspect. Thus, appearances of the phrases “in one aspect,” “in an aspect,” “in an exemplification,” and “in one exemplification” in various places throughout the specification are not necessarily all referring to the same aspect. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more aspects.

[0520] Any patent application, patent, non-patent publication, or other disclosure material referred to in this specification and/or listed in any Application Data Sheet is incorporated by reference herein, to the extent that the incorporated materials is not inconsistent herewith. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

[0521] In summary, numerous benefits have been described which result from employing the concepts described herein. The foregoing description of the one or more forms has been presented for purposes of illustration and description. It is not intended to be exhaustive or limiting to the precise form disclosed. Modifications or variations are possible in light of the above teachings. The one or more forms were chosen and described in order to illustrate principles and practical application to thereby enable one of ordinary skill in the art to utilize the various forms and with various modifications as are suited to the particular use contemplated. It is intended that the claims submitted herewith define the overall scope.

What is claimed is:

1. A surgical system, comprising:

a robotic tool;

a robot control system, comprising:

a control console; and

a control unit in signal communication with said control console and said robotic tool;

a surgical instrument; and

a surgical hub comprising a display, wherein said surgical hub is in signal communication with said robot control system, and wherein said surgical hub is configured to detect said surgical instrument and represent said surgical instrument on said display.

2. The surgical system of claim 1, wherein said surgical instrument comprises a motorized, autonomous surgical instrument.

3. The surgical system of claim 1, wherein said surgical instrument is independent of said robot control system.

4. The surgical system of claim 1, wherein said surgical hub is configured to display a location of said surgical instrument on said display.

5. The surgical system of claim 1, wherein said surgical hub is configured to display an operating status of said surgical instrument on said display.

6. The surgical system of claim 1, wherein said display comprises a heads up display.

7. The surgical system of claim 1, wherein said surgical hub further comprises a situational awareness module configured to recommend a surgical function based on the detection of said surgical instrument relative to a position of said robotic tool.

8. A surgical system, comprising:

a robotic tool;

a robot control system, comprising:

a control console; and

a control unit in signal communication with said control console and said robotic tool;

a surgical instrument operable in a plurality of operating states; and

a surgical hub comprising a display, wherein said surgical hub is in signal communication with said robot control system, and wherein said surgical hub is configured to detect an activated operating state of said surgical instrument and represent said active operating state on said display.

9. The surgical system of claim 8, wherein said surgical instrument comprises a motorized surgical device.

10. The surgical system of claim 8, wherein said surgical instrument is an autonomous surgical instrument.

11. The surgical system of claim 8, wherein said surgical hub is configured to display an orientation of said surgical instrument on said display.

12. The surgical system of claim 8, wherein said surgical hub is configured to display an operating status of said surgical instrument on said display.

13. The surgical system of claim 8, further comprising a situational awareness module configured to recommend a surgical function based on the detection of said surgical instrument relative to a position of said robotic tool.

14. A surgical system, comprising:

a robotic tool;

a robot control system, comprising:

a control console; and

a control unit in signal communication with said control console and said robotic tool;

a surgical instrument;

a surgical hub, wherein said surgical hub is in signal communication with said robot control system, and wherein said surgical hub is configured to detect said surgical instrument; and

a display in signal communication with said surgical hub, wherein said surgical hub is configured to represent said surgical instrument on said display.

15. The surgical system of claim 14, wherein said surgical instrument comprises a motorized surgical instrument.

16. The surgical system of claim 14, wherein said surgical instrument is independent of said robot control system.

17. The surgical system of claim 14, wherein said surgical hub is configured to display a position of said surgical instrument on said display.

18. The surgical system of claim 14, wherein said surgical hub is configured to display an operating status of said surgical instrument on said display.

19. The surgical system of claim 14, wherein said display comprises a heads up display.

20. The surgical system of claim 14, further comprising a situational awareness module configured to recommend a surgical function based on the detection of said surgical instrument relative to a position of said robotic tool.

* * * * *