



(12) **United States Patent**
Widener

(10) **Patent No.:** **US 10,815,828 B2**
(45) **Date of Patent:** **Oct. 27, 2020**

(54) **HOT GAS PATH COMPONENTS INCLUDING PLURALITY OF NOZZLES AND VENTURI**

(56) **References Cited**

(71) Applicant: **General Electric Company**,
Schenectady, NY (US)
(72) Inventor: **Stanley Kevin Widener**, Greer, SC
(US)
(73) Assignee: **General Electric Company**,
Schenectady, NY (US)

U.S. PATENT DOCUMENTS

4,278,400 A 7/1981 Yamarik et al.
4,330,235 A 5/1982 Araki
4,573,865 A * 3/1986 Hsia F01D 5/187
165/109.1
7,162,876 B2 1/2007 Hoff et al.
7,238,001 B2 7/2007 Rushton
8,550,774 B2 10/2013 Maltson
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 188 days.

DE 19727407 A1 1/1999
EP 0626036 B1 10/1996
(Continued)

FOREIGN PATENT DOCUMENTS

(21) Appl. No.: **16/205,799**

OTHER PUBLICATIONS

(22) Filed: **Nov. 30, 2018**

U.S. Appl. No. 16/205,931, Notice of Allowance dated Jun. 22, 2020, 18 pages.

(65) **Prior Publication Data**

US 2020/0173306 A1 Jun. 4, 2020

(Continued)

Primary Examiner — Richard A Edgar

(74) *Attorney, Agent, or Firm* — James Pemrick; Hoffman Warnick LLC

(51) **Int. Cl.**
F01D 25/12 (2006.01)
F01D 9/04 (2006.01)

(57) **ABSTRACT**


Hot gas path (HGP) components for turbine systems are disclosed. The HGP component may include a body including a forward end, an aft end, and an inner portion positioned adjacent a hot gas flow path for the turbine system. The body may also include an outer portion formed radially opposite the inner portion, and a plurality of nozzles extending through the outer portion. Additionally, body may include an intermediate portion formed between the inner portion and the outer portion, and a plurality of venturi extending through the intermediate portion. The plurality of venturi may be in fluid communication with the plurality of nozzles.

(52) **U.S. Cl.**
CPC **F01D 25/12** (2013.01); **F01D 9/04** (2013.01); **F05D 2260/20** (2013.01)

(58) **Field of Classification Search**
CPC F01D 5/186; F01D 5/187; F01D 5/188;
F01D 5/189; F01D 5/18; F01D 25/12;
F01D 9/04; F05D 2260/20; F05D
2260/201; F05D 2260/202; F05D
2260/204; F05D 2260/221

See application file for complete search history.

20 Claims, 16 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

8,726,672	B2	5/2014	Ciofini et al.
10,309,228	B2	6/2019	Dutta et al.
2015/0300266	A1	10/2015	Glahn et al.
2017/0356299	A1	12/2017	Dutta et al.

FOREIGN PATENT DOCUMENTS

EP	2180162	B1	12/2015
EP	1440223	B2	11/2017
EP	3146184	B1	3/2018

OTHER PUBLICATIONS

Extended European Search Report and Opinion issued in connection with corresponding EP Application No. 19211669.7 dated Apr. 9, 2020, 7 pages.

* cited by examiner




FIG. 1





FIG. 2







FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7




FIG. 9




FIG. 10




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

HOT GAS PATH COMPONENTS INCLUDING PLURALITY OF NOZZLES AND VENTURI

BACKGROUND OF THE INVENTION

The disclosure relates generally to hot gas path components for turbine systems, and more particularly, to hot gas path components that include a plurality of nozzles and venturi formed therein.

Conventional turbomachines, such as gas turbine systems, generate power for electric generators. In general, gas turbine systems generate power by passing a fluid (e.g., hot gas) through a turbine component of the gas turbine system. More specifically, inlet air may be drawn into a compressor to be compressed. Once compressed, the inlet air is mixed with fuel to form a combustion product, which may be reacted by a combustor of the gas turbine system to form the operational fluid (e.g., hot gas) of the gas turbine system. The fluid may then flow through a fluid flow path for rotating a plurality of rotating blades and rotor or shaft of the turbine component for generating the power. The fluid may be directed through the turbine component via the plurality of rotating blades and a plurality of stationary nozzles or vanes positioned between the rotating blades. As the plurality of rotating blades rotate the rotor of the gas turbine system, a generator, coupled to the rotor, may generate power from the rotation of the rotor.

To improve operational efficiencies turbine components may include hot gas path components, such as turbine shrouds and/or nozzle bands, to further define the flow path of the operational fluid. Turbine shrouds, for example, may be positioned radially adjacent rotating blades of the turbine component and may direct the operational fluid within the turbine component and/or define the outer bounds of the fluid flow path for the operational fluid. During operation, turbine shrouds may be exposed to high temperature operational fluids flowing through the turbine component. Over time and/or during exposure, the turbine shrouds may undergo undesirable thermal expansion. The thermal expansion of turbine shrouds may result in damage to the shrouds and/or may not allow the shrouds to maintain a seal within the turbine component for defining the fluid flow path for the operational fluid. When the turbine shrouds become damaged or no longer form a satisfactory seal within the turbine component, the operational fluid may leak from the flow path, which in turn reduces the operational efficiency of the turbine component and the entire turbine system.

To minimize thermal expansion and degradation, turbine shrouds are typically cooled. Conventional processes for cooling turbine shrouds include film cooling and impingement cooling. Film cooling involves the process of flowing cooling air over the hot surfaces of the turbine shroud during operation of the turbine component. Impingement cooling utilizes holes or apertures formed through the turbine shroud to provide cooling air to the cold side of various portions of the turbine shroud during operation. Typically in conventional systems, only high pressure cooling air may be provided to and utilized by the turbine shroud for cooling. This is because the cooling air provided to conventional turbine shrouds for cooling must overcome the internal pressure of the turbine hot operational fluid, to assure that no hot fluid exits the flowpath into component spaces that may incur damage from the hot fluid. As a result, substantially all or most of the cooling air flowing through conventional gas turbine static components must be provided from high-pressure sources, which are subject to a greater quantity of compressor pumping work. Cooling air from lower-pressure

sources that may otherwise be available to cool the components cannot be used if the pressure is too low. This in turn may reduce the operational efficiency of the gas turbine system, and/or may require supplemental high pressure air generation system to be incorporated within the gas turbine system. Using supplemental high pressure air generation systems to provide additional high pressure air to the system thus add undesirable build, installation, maintenance, and/or operational expenses to the gas turbine system.

BRIEF DESCRIPTION OF THE INVENTION

A first aspect of the disclosure provides a hot gas path (HGP) component of a turbine system. The HGP component includes: a body including: a forward end; an aft end positioned opposite the forward end; an inner portion positioned adjacent a hot gas flow path for the turbine system, the inner portion extending between the forward end and aft end; an outer portion formed radially opposite the inner portion and extending between the forward end and aft end; a plurality of nozzles extending through the outer portion; an intermediate portion formed between the inner portion and the outer portion; and a plurality of venturi extending through the intermediate portion, the plurality of venturi in fluid communication with the plurality of nozzles.

A second aspect of the disclosure provides a turbine system including: a turbine casing; a plurality of turbine blades positioned within the turbine casing and circumferentially about a rotor; a plurality of supports circumferentially disposed around the turbine casing and positioned radially adjacent the plurality of turbine blades, each of the plurality of supports including: at least one high pressure supply conduit in fluid communication with a high pressure fluid flowing adjacent to and upstream of the support; and at least one low pressure supply conduit in fluid communication with a low pressure fluid flowing adjacent to and downstream of the support; and a plurality of hot gas path (HGP) components coupled to the plurality of supports and extending radially between the plurality of supports and the plurality of turbine blades, each of the plurality of HGP components including: a body including: a forward end; an aft end positioned opposite the forward end; an inner portion positioned adjacent the plurality of turbine blades, the inner portion extending between the forward end and aft end; an outer portion formed radially opposite the inner portion and extending between the forward end and aft end; a plurality of nozzles extending through the outer portion; an intermediate portion formed between the inner portion and the outer portion; and a plurality of venturi extending through the intermediate portion, the plurality of venturi in fluid communication with the plurality of nozzles.

A third aspect of the disclosure provides a turbine system including a turbine casing; a plurality of supports circumferentially disposed around the turbine casing, each of the plurality of supports including: at least one high pressure supply conduit in fluid communication with a high pressure fluid flowing adjacent to and downstream of the support; and at least one low pressure supply conduit in fluid communication with a low pressure fluid flowing adjacent to and upstream of the support; and a plurality of stator vanes coupled to the plurality of supports, the plurality of stator vanes positioned circumferentially about the turbine casing, wherein each stator vane of the plurality of stator vanes includes: an airfoil; and a hot gas path (HGP) component coupled to the airfoil, the HGP component including: a body including: a forward end; an aft end positioned opposite the forward end; an inner portion positioned adjacent the plu-

3

ality of turbine blades, the inner portion extending between the forward end and aft end; an outer portion formed radially opposite the inner portion and extending between the forward end and aft end; a plurality of nozzles extending through the outer portion; an intermediate portion formed between the inner portion and the outer portion; and a plurality of venturi extending through the intermediate portion, the plurality of venturi in fluid communication with the plurality of nozzles.

The illustrative aspects of the present disclosure are designed to solve the problems herein described and/or other problems not discussed.

BRIEF DESCRIPTION OF THE DRAWINGS

These and other features of this disclosure will be more readily understood from the following detailed description of the various aspects of the disclosure taken in conjunction with the accompanying drawings that depict various embodiments of the disclosure, in which:

FIG. 1 shows a schematic diagram of a gas turbine system, according to embodiments of the disclosure.

FIG. 2 shows a side view of a portion of a turbine of the gas turbine system of FIG. 1 including a turbine blade, a stator vane, a rotor, a casing, a hot gas path component, and a support, according to embodiments of the disclosure.

FIG. 3 shows an enlarged side view of a portion of the gas turbine system of FIG. 2, according to embodiments of the disclosure.

FIG. 4 shows an isometric view of the hot gas path component of FIGS. 2 and 3, according to embodiments of the disclosure.

FIG. 5 shows a cross-sectional side view of the hot gas path component taken along line CS-CS in FIG. 4, according to embodiments of the disclosure.

FIG. 6 shows an enlarged cross-sectional side view of the hot gas path component of FIG. 5, according to embodiments of the disclosure.

FIG. 7 shows an enlarged side view of a portion of the gas turbine system of FIG. 2, according to additional embodiments of the disclosure.

FIG. 8 shows a cross-sectional side view of the hot gas path component shown in FIG. 7, according to embodiments of the disclosure.

FIG. 9 shows an enlarged side view of a portion of the gas turbine system of FIG. 2, according to further embodiments of the disclosure.

FIG. 10 shows an enlarged side view of a portion of the gas turbine system of FIG. 1, according to additional embodiments of the disclosure.

FIG. 11 shows a cross-sectional side view of the hot gas path component of FIG. 10, according to embodiments of the disclosure.

FIG. 12 shows an enlarged side view of a portion of the gas turbine system of FIG. 1, according to another embodiment of the disclosure.

FIG. 13 shows a cross-sectional side view of the hot gas path component of FIG. 12, according to embodiments of the disclosure.

FIG. 14 shows a side view of a portion of a turbine of the gas turbine system of FIG. 1 including two turbine blades, a stator vane including a hot gas path component, a rotor, a casing, and a support, according to additional embodiments of the disclosure.

FIG. 15 shows an enlarged side view of a portion of the gas turbine system of FIG. 14, according to additional embodiments of the disclosure.

4

FIG. 16 shows a block diagram of an additive manufacturing process including a non-transitory computer readable storage medium storing code representative of a hot gas path component according to embodiments of the disclosure.

It is noted that the drawings of the disclosure are not to scale. The drawings are intended to depict only typical aspects of the disclosure, and therefore should not be considered as limiting the scope of the disclosure. In the drawings, like numbering represents like elements between the drawings.

DETAILED DESCRIPTION OF THE INVENTION

As an initial matter, in order to clearly describe the current disclosure it will become necessary to select certain terminology when referring to and describing relevant machine components within the scope of this disclosure. When doing this, if possible, common industry terminology will be used and employed in a manner consistent with its accepted meaning. Unless otherwise stated, such terminology should be given a broad interpretation consistent with the context of the present application and the scope of the appended claims. Those of ordinary skill in the art will appreciate that often a particular component may be referred to using several different or overlapping terms. What may be described herein as being a single part may include and be referenced in another context as consisting of multiple components. Alternatively, what may be described herein as including multiple components may be referred to elsewhere as a single part.

In addition, several descriptive terms may be used regularly herein, and it should prove helpful to define these terms at the onset of this section. These terms and their definitions, unless stated otherwise, are as follows. As used herein, “downstream” and “upstream” are terms that indicate a direction relative to the flow of a fluid, such as the working fluid through the turbine engine or, for example, the flow of air through the combustor or coolant through one of the turbine’s component systems. The term “downstream” corresponds to the direction of flow of the fluid, and the term “upstream” refers to the direction opposite to the flow. The terms “forward” and “aft,” without any further specificity, refer to directions, with “forward” referring to the front or compressor end of the engine, and “aft” referring to the rearward or turbine end of the engine. Additionally, the terms “leading” and “trailing” may be used and/or understood as being similar in description as the terms “forward” and “aft,” respectively. It is often required to describe parts that are at differing radial, axial and/or circumferential positions. The “A” axis represents an axial orientation. As used herein, the terms “axial” and/or “axially” refer to the relative position/direction of objects along axis A, which is substantially parallel with the axis of rotation of the turbine system (in particular, the rotor section). As further used herein, the terms “radial” and/or “radially” refer to the relative position/direction of objects along a direction “R” (see, FIG. 1), which is substantially perpendicular with axis A and intersects axis A at only one location. Finally, the term “circumferential” refers to movement or position around axis A (e.g., direction “C”).

As indicated above, the disclosure provides hot gas path components for turbine systems, and more particularly, to hot gas path components that include a plurality of nozzles and venturi formed therein.

These and other embodiments are discussed below with reference to FIGS. 1-16. However, those skilled in the art

will readily appreciate that the detailed description given herein with respect to these Figures is for explanatory purposes only and should not be construed as limiting.

FIG. 1 shows a schematic view of an illustrative gas turbine system 10. Gas turbine system 10 may include a compressor 12. Compressor 12 compresses an incoming flow of air 18. Compressor 12 delivers a flow of compressed air 20 to a combustor 22. Combustor 22 mixes the flow of compressed air 20 with a pressurized flow of fuel 24 and ignites the mixture to create a flow of combustion gases 26. Although only a single combustor 22 is shown, gas turbine system 10 may include any number of combustors 22. The flow of combustion gases 26 is in turn delivered to a turbine 28, which typically includes a plurality of turbine blades including airfoils (see, FIG. 2) and stator vanes (see, FIG. 2). The flow of combustion gases 26 drives turbine 28, and more specifically the plurality of turbine blades of turbine 28, to produce mechanical work. The mechanical work produced in turbine 28 drives compressor 12 via a rotor 30 extending through turbine 28, and may be used to drive an external load 32, such as an electrical generator and/or the like.

Gas turbine system 10 may also include an exhaust frame 34. As shown in FIG. 1, exhaust frame 34 may be positioned adjacent to turbine 28 of gas turbine system 10. More specifically, exhaust frame 34 may be positioned adjacent to turbine 28 and may be positioned substantially downstream of turbine 28 and/or the flow of combustion gases 26 flowing from combustor 22 to turbine 28. As discussed herein, a portion (e.g., outer casing) of exhaust frame 34 may be coupled directly to an enclosure, shell, or casing 36 of turbine 28.

Subsequent to combustion gases 26 flowing through and driving turbine 28, combustion gases 26 may be exhausted, flow-through and/or discharged through exhaust frame 34 in a flow direction (D). In the non-limiting example shown in FIG. 1, combustion gases 26 may flow through exhaust frame 34 in the flow direction (D) and may be discharged from gas turbine system 10 (e.g., to the atmosphere). In another non-limiting example where gas turbine system 10 is part of a combined cycle power plant (e.g., including gas turbine system and a steam turbine system), combustion gases 26 may discharge from exhaust frame 34, and may flow in the flow direction (D) into a heat recovery steam generator of the combined cycle power plant.

Turning to FIG. 2, a portion of turbine 28 is shown. Specifically, FIG. 2 shows a side view of a portion of turbine 28 including a stage of turbine blades 38 (one shown), and a stage of stator vanes 40 (one shown) positioned within casing 36 of turbine 28. As discussed herein, each stage (e.g., first stage, second stage (not shown), third stage (not shown)) of turbine blades 38 may include a plurality of turbine blades 38 that may be coupled to and positioned circumferentially around rotor 30 and may be driven by combustion gases 26 to rotate rotor 30. Additionally, each stage (e.g., first stage, second stage (not shown), third stage (not shown)) of stator vanes 40 may include a plurality of stator vanes that may be coupled to and/or positioned circumferentially about casing 36 of turbine 28. In the non-limiting example shown in FIG. 2, stator vanes 40 may include a plurality of hot gas path (HGP) components 200. For example, HGP components 200 of stator vanes 40 may include and/or be formed as an outer platform 200A positioned adjacent and/or coupling stator vanes 40 to casing 26 of turbine 28, and an inner platform 200B positioned opposite the outer platform 200A. Stator vanes 40 of turbine 28 may also include an airfoil 42 positioned between outer

platform 200A and inner platform 200B. Outer platform 200A and inner platform 200B of stator vanes 40 may define a flow path (FP) for the combustion gases 26 flowing over stator vanes 40.

Stator vane 40 may be coupled to casing 36 via support 202. Support 202 may extend radially inward from casing 36 of turbine 28, and may be configured to be coupled to and/or receive HGP component formed as outer platform 200A of stator vanes 40 to couple, position, and/or secure stator vanes 40 to and/or within casing 36. In the non-limiting example, support 202 may be coupled and/or fixed to casing 36 of turbine 28. More specifically, support 202 may be circumferentially disposed around casing 36, and may be positioned axially adjacent turbine blades 38. In another non-limiting example (not shown), support 202 may be formed integral with casing 36 for coupling, positioning, and/or securing stator vanes 40 to and/or within casing 36. In another non-limiting example (not shown), support 202 may be coupled and/or affixed directly to a support for a HGP component associated with turbine blade 38, as discussed herein.

Each turbine blade 38 of turbine 28 may include an airfoil 46 extending radially from rotor 30 and positioned within the flow path (FP) of combustion gases 26 flowing through turbine 28. Each airfoil 46 may include a tip portion 48 positioned radially opposite rotor 30. Turbine blades 38 and stator vanes 40 may also be positioned axially adjacent to one another within casing 36. In the non-limiting example shown in FIG. 2, stator vanes 40 may be positioned axially adjacent and downstream of turbine blades 38. Not all turbine blades 38, stator vanes 40 and/or all of rotor 30 of turbine 28 are shown for clarity. Additionally, although only a portion of a single stage of turbine blades 38 and stator vanes 40 of turbine 28 are shown in FIG. 2, turbine 28 may include a plurality of stages of turbine blades and stator vanes, positioned axially throughout casing 36 of turbine 28.

Turbine 28 of gas turbine system 10 (see, FIG. 1) may also include a plurality of hot gas path (HGP) components 100. In a non-limiting example shown in FIG. 2, HGP component 100 may be turbine shrouds included within turbine 28. In this non-limiting examples discussed herein with respect to FIGS. 2-13, HGP component 100 and turbine shroud may be used interchangeably. Turbine 28 may include a stage of HGP components 100 (one shown). HGP components 100 may correspond with the stage of turbine blades 38 and/or the stage of stator vanes 40. That is, and as discussed herein, the stage of HGP components 100 may be positioned within turbine 28 adjacent the stage of turbine blades 38 and/or the stage of stator vanes 40 to interact with and provide a seal in the flow path (FP) of combustion gases 26 flowing through turbine 28. In the non-limiting example shown in FIG. 2, the stage of HGP components 100 may be positioned radially adjacent and/or may substantially surround or encircle the stage of turbine blades 38. HGP components 100 may be positioned radially adjacent tip portion 48 of airfoil 46 for turbine blade 38. Additionally, HGP components 100 may also be positioned axially adjacent and/or upstream of stator vanes 40 of turbine 28.

Similar to stator vanes 40, the stage of HGP components 100 may include a plurality of HGP components 100 that may be coupled to and positioned circumferentially about casing 36 of turbine 28. In the non-limiting example shown in FIG. 2, HGP components 100 may be coupled to casing 36 via support 102 extending radially inward from casing 36 of turbine 28. Support 102 may be configured to be coupled to and/or receive fasteners or hooks (see, FIG. 4) of HGP components 100 to couple, position, and/or secure HGP

components **100** to casing **36** of turbine **28**. In the non-limiting example, support **102** may be coupled and/or fixed to casing **36** of turbine **28**. More specifically, support **102** may be circumferentially disposed around casing **36**, and may be positioned radially adjacent turbine blades **38**. In another non-limiting example (not shown), support **102** may be formed integral with casing **36** for coupling, positioning, and/or securing HGP components **100** to casing **36**. Similar to turbine blades **38** and/or stator vanes **40**, although only a portion of the stage of HGP components **100** of turbine **28** is shown in FIG. 2, turbine **28** may include a plurality of stages of HGP components **100**, positioned axially throughout casing **36** of turbine **28** and coupled to casing **26** using support **102**.

Turning to FIG. 3, an enlarged portion of turbine **28** including HGP component **100** and support **102** is shown. As discussed herein, HGP component **100** and support **102** of turbine **28** may include various additional features that permit use of low pressure fluid (LPF), along with the high pressure fluid (HPF), to cool HGP component **100** during operation of turbine **28**. The inclusion of these features in HGP components **100** and/or support **102** may reduce the amount of high pressure fluid required to cool HGP component **100**, which in turn reduces fuel consumption and/or heat rate within turbine system **10** (see, FIG. 1).

As shown in FIGS. 2 and 3, support **102** may include a high pressure fluid chamber **104**. High pressure fluid chamber **104** may be formed within support **102**, radially adjacent to, and/or radially outward from HGP component **100**. Additionally, and as discussed herein, high pressure fluid chamber **104** may be fluidly coupled and/or in fluid communication with features (e.g., nozzles) of HGP component **100**. High pressure fluid chamber **104** may be formed in support **102** to receive high pressure fluid (HPF) flowing through and/or within turbine **28** that may be subsequently provided to HGP component **100** during operation of gas turbine system **10** (see, FIG. 1). In the non-limiting example shown in FIGS. 2 and 3, high pressure fluid (HPF) may be flowing within turbine **28** and/or turbine casing **36**. Specifically, the HPF may be flowing in and/or through area **50** of turbine **28**, substantially adjacent to and/or upstream of support **102**. The HPF may be any suitable fluid (e.g., air) flowing within turbine **28** suitable to cool HGP component **100** during operation of turbine system **10** (see, FIG. 1). In a non-limiting example, the HPF may be fluid flowing from compressor discharge chamber (CDC) of turbine **28**.

Support **102** may also include at least one high pressure supply conduit **106** formed therein. High pressure supply conduit **106** may be in fluid communication with and/or fluidly coupled to high pressure fluid chamber **104**. That is, high pressure supply conduit **106** may be in fluid communication with area **50** containing the HPF, as well as high pressure fluid chamber **104**. As a result, high pressure supply conduit **106** may receive the HPF flowing through area **50**, and may provide the HPF to high pressure fluid chamber **104** of support **102**. Once received from high pressure supply conduit **106**, high pressure fluid chamber **104** may provide the HPF to HGP component **100**, as discussed herein. Although shown in the non-limiting example as only including a single high pressure supply conduit **106**, it is understood that support **102** may include a plurality of high pressure supply conduits **106** (e.g., FIG. 7) for providing HPF to HGP component **100**.

As shown in FIGS. 2 and 3, support **102** may also include at least one low pressure supply conduit **108**. Low pressure supply conduit(s) **108** may be in fluid communication with and/or fluidly coupled to an area **52** within of turbine casing

36 that may contain a low pressure fluid (LPF). The LPF may be flowing substantially adjacent to and/or downstream of support **102** for turbine **28**. As such, area **52** containing the LPF may be formed between support **102** and outer platform **200A** of stator vane **40**. Additionally as shown in FIGS. 2 and 3, and discussed herein, low pressure supply conduit(s) **108** may be fluidly coupled to and/or in fluid communication with HGP component **100** to provide the LPF from area **52** to HGP component **100** during operation of turbine system **10** (see, FIG. 1). The LPF may be any suitable fluid (e.g., air) flowing within turbine **28** to cool HGP component **100**, as discussed herein. In a non-limiting example, the LPF may be compressor extraction fluid of turbine **28** flowing between turbine blades **38** and stator vanes **40**.

In the non-limiting example shown in FIGS. 2 and 3, support **102** may include and/or be formed as a single, continuous, and/or non-disjointed component or part. In the non-limiting example, and because support **102** is formed from a single, continuous, and/or non-disjointed component or part, support **102** may not require the building, joining, coupling, and/or assembling of various parts to completely form support **102**, and/or may not require building, joining, coupling, and/or assembling of various parts before support **102** can be installed and/or implemented within turbine system **10** (see, FIG. 1). Rather, once single, continuous, and/or non-disjointed support **102** is built to include the various features therein (e.g., high pressure supply conduit **106**, low pressure supply conduit **108**), support **102** may be immediately installed within turbine system **10** and/or turbine casing **36**.

In the non-limiting example, support **102**, and the various features formed therein e.g., high pressure fluid chamber **104**, high pressure supply conduit **106**, low pressure supply conduit **108**), may be formed using any suitable additive manufacturing process(es) and/or method. For example, support **102** may be formed by direct metal laser melting (DMLM) (also referred to as selective laser melting (SLM)), direct metal laser sintering (DMLS), electronic beam melting (EBM), stereolithography (SLA), binder jetting, or any other suitable additive manufacturing process(es). Additionally, support **102** may be formed from any material that may be utilized by additive manufacturing process(es), and/or capable of withstanding the operational characteristics (e.g., exposure temperature, exposure pressure, and the like) experienced by support **102** within gas turbine system **10** during operation.

In another non-limiting example, support **102** may be formed as multiple and/or distinct portions or components. For example, support **102** may be formed from two distinct components or parts including at least a portion of the various features of support **102**. The two components forming support **102** may be joined, coupled, and/or affixed to one another before support **102** is installed in turbine **28** within gas turbine system **10**. Each component forming support **102**, and the various features of support **102**, may be formed using any suitable manufacturing process(es) and/or method. For example, support **102** including the two, distinct components may be formed by milling, turning, cutting, casting, molding, drilling, and the like. In a further non-limiting example, support **102** may be formed from a single piece of material by performing suitable material removal or subtraction processes including, but not limited to, milling, turning, cutting, drilling, and the like.

FIGS. 4-6 show various views of HGP component **100** of turbine **28** for gas turbine system **10** of FIG. 1. Specifically, FIG. 4 shows an isometric view of HGP component **100**,

FIG. 5 shows a cross-sectional side view of HGP component 100 taken along line CS-CS in FIG. 4, and FIG. 6 shows an enlarged cross-sectional side view of a portion of HGP component 100 in FIG. 5.

HGP component 100 may include a body 110. In the non-limiting example shown in FIGS. 4 and 5, HGP component 100 may include and/or be formed as a unitary body 110 such that HGP component 100 is a single, continuous, and/or non-disjointed component or part. In the non-limiting example shown in FIGS. 4 and 5, because HGP component 100 includes a unitary body, HGP component 100 may not require the building, joining, coupling, and/or assembling of various parts to completely form HGP component 100, and/or may not require building, joining, coupling, and/or assembling of various parts before HGP component 100 can be installed and/or implemented within turbine system 10 (see, FIG. 1). Rather, once single, continuous, and/or non-disjointed unitary body 110 for HGP component 100 is built, as discussed herein, HGP component 100 may be immediately installed within turbine system 10.

In the non-limiting example, unitary body 110 of HGP component 100, and the various components and/or features of HGP component 100, may be formed using any suitable additive manufacturing process(es) and/or method. For example, HGP component 100 including unitary body 110 may be formed by direct metal laser melting (DMLM) (also referred to as selective laser melting (SLM)), direct metal laser sintering (DMLS), electronic beam melting (EBM), stereolithography (SLA), binder jetting, or any other suitable additive manufacturing process(es). Additionally, unitary body 110 of HGP component 100 may be formed from any material that may be utilized by additive manufacturing process(es) to form HGP component 100, and/or capable of withstanding the operational characteristics (e.g., exposure temperature, exposure pressure, and the like) experienced by HGP component 100 within gas turbine system 10 during operation.

In another non-limiting example, body 110 of HGP component 100 may be formed as multiple and/or distinct portions or components (see, FIGS. 7 and 8). For example, and as discussed herein, body 110 of HGP component 100 may be formed from a first part that may include hooks 112, 118 and an inner surface, and a second part that may include the outer surface (and a portion of internal features) of HGP component 100. The two components forming body 110 of HGP component 100 may be joined, coupled, and/or affixed to one another to form HGP component 100 before being installed in turbine 28 within gas turbine system 10. Each component forming body 110, and the various components and/or features of HGP component 100, may be formed using any suitable manufacturing process(es) and/or method. For example, HGP component 100 including body 110 including the two, distinct components may be formed by milling, turning, cutting, casting, molding, drilling, and the like.

HGP component 100 may also include various ends, sides, and/or surfaces. For example, and as shown in FIGS. 4 and 5, body 110 of HGP component 100 may include a forward end 120 and an aft end 122 positioned opposite forward end 120. Forward end 120 may be positioned upstream of aft end 122, such that combustion gases 26 flowing through the flow path (FP) defined within turbine 28 may flow adjacent forward end 120 before flowing by adjacent aft end 122 of body 110 of HGP component 100. As shown in FIGS. 3 and 4, forward end 120 may include first hook 112 configured to be coupled to and/or engage support 102 of casing 36 for turbine 28 to couple, position, and/or

secure HGP components 100 within casing 36 (see, FIG. 2). Additionally, aft end 122 may include second hook 118 positioned and/or formed on body 110 opposite first hook 112. Similar to first hook 112, second hook 118 may be configured to be coupled to and/or engage support 102 of casing 36 for turbine 28 to couple, position, and/or secure HGP components 100 within casing 36 (see, FIG. 2).

Additionally, body 110 of HGP component 100 may also include a first side 124, and a second side 126 positioned opposite first side 124. As shown in FIG. 4, first side 124 and second side 126 may extend and/or be formed between forward end 120 and aft end 122. First side 124 and second side 126 of body 110 may be substantially closed and/or may include solid end walls or caps. As such, and as discussed herein, the solid end walls of first side 124 and second side 126 may substantially prevent fluid within turbine 28 (e.g., combustion gases 26, cooling fluids) from entering HGP component 100, and/or cooling fluid from exiting internal portions (e.g., passages, plenums) formed within HGP component 100 via first side 124 and/or second side 126.

As shown in FIGS. 4 and 5 body 110 of HGP component 100 may also include an outer surface 128. In the non-limiting example, outer surface 128 may face high pressure fluid chamber 104 formed between body 110 of HGP component 100 and support 102 (see, FIG. 2). More specifically, outer surface 128 may be positioned, formed, face, and/or directly exposed in high pressure fluid chamber 104 formed within support 102. As discussed herein, high pressure fluid chamber 104 of support 102 may receive and/or provide HPF to HGP component 100 during operation of turbine 28. In addition to facing high pressure fluid chamber 104, outer surface 128 of body 110 for HGP component 100 may also be formed, extend, and/or positioned between forward end 120 and aft end 122, as well as first side 124 and second side 126, respectively.

Body 110 of HGP component 100 may also include inner surface 130 formed opposite outer surface 128. That is, and as shown in the non-limiting example in FIGS. 4 and 5, inner surface 130 of body 110 of HGP component 100 may be formed radially opposite and/or radially inward from outer surface 128. Briefly returning to FIG. 2, and with continued reference to FIGS. 4 and 5, inner surface 130 may face the hot gas flow path (FP) of combustion gases 26 flowing through turbine 28 (see, FIG. 2). More specifically, inner surface 130 may be positioned, formed, face, and/or directly exposed to the hot gas flow path (FP) of combustion gases 26 flowing through turbine casing 36 of turbine 28 for gas turbine system 10. Additionally as shown in FIG. 2, inner surface 130 of body 110 for HGP component 100 may be positioned radially adjacent tip portion 48 of airfoil 46. In addition to facing the hot gas flow path (FP) of combustion gases 26, and similar to outer surface 128, inner surface 130 of body 110 for HGP component 100 may also be formed and/or positioned between forward end 120 and aft end 122, and first side 124 and second side 126, respectively.

Turning to FIGS. 5 and 6, and with continued reference to FIGS. 2-4, additional features of HGP component 100 are now discussed. HGP component 100 may include an inner portion 132. As shown in FIG. 5, inner portion 132 may be formed as an integral portion of unitary body 110 for HGP component 100. Additionally, inner portion 132 may include inner surface 130, and/or inner surface 130 may be formed on inner portion 132 of body 110 for HGP component 100. Inner portion 132 of body 110 for HGP component 100 may be formed, positioned, and/or extend between forward end 120 and aft end 122, and first side 124 and second side 126, respectively. Additionally, inner portion 132 may be formed

11

integral with the solid side walls formed on first side **124** and second side **126** of body **110** (see, FIG. **4**). Briefly returning to FIGS. **2** and **3**, inner portion **132** of HGP component **100** may also be positioned adjacent hot gas flow path (FP) for turbine **28** of turbine system **10**, and/or may be radially adjacent and/or radially outward from tip portion **48** of airfoil **46**. As discussed herein, inner portion **132** of HGP component **100** may at least partially form and/or define at least one cooling channel within HGP component **100**.

HGP component **100** may include an outer portion **134** formed radially opposite inner portion **132**. Similar to inner portion **132**, as shown in FIG. **5**, outer portion **134** may be formed as an integral portion of unitary body **110** for HGP component **100**. Outer portion **134** may include outer surface **128**, and/or outer surface **128** may be formed on outer portion **134** of body **110** for HGP component **100**. Outer portion **134** of body **110** for HGP component **100** may be formed, positioned, and/or extend between forward end **120** and aft end **122**, and first side **124** and second side **126**, respectively. Additionally, and also similar to inner portion **132**, outer portion **134** may be formed integral with the solid side walls formed on first side **124** and second side **126** of body **110**. As shown in FIGS. **3** and **5**, outer portion **134** may be formed (radially) adjacent high pressure fluid chamber **104** of support **102**. Outer portion **134** of HGP component **100** may at least partially form and/or define low pressure fluid channel within HGP component **100**, as discussed herein.

As shown in the non-limiting example of FIG. **5**, HGP component **100** may also include an intermediate portion **136**. Intermediate portion **136** may be formed (radially) between inner portion **132** and outer portion **134** of unitary body **110** of HGP component **100**. Similar to inner portion **132** and outer portion **134**, and as shown in FIG. **5**, intermediate portion **136** of HGP component **100** may be formed as an integral portion of body **110** for HGP component **100**. Intermediate portion **136** of body **110** for HGP component **100** may be formed, positioned, and/or extend between forward end **120** and aft end **122**, and first side **124** and second side **126**, respectively, and may be formed integral with the solid side walls formed on first side **124** and second side **126** of body **110** (see, FIG. **4**).

Inner portion **132**, outer portion **134**, and/or intermediate portion **136** may at least partially form and/or define channels within HGP component **100**. For example, intermediate portion **136** and outer portion **134** may define and/or form a low pressure fluid channel **138** within HGP component **100**. More specifically, low pressure fluid channel **138** may be formed between intermediate portion **136** and outer portion **134** of unitary body **110** for HGP component **100**. Low pressure fluid channel **138** may extend substantially between forward end **120** and aft end **122**, and first side **124** and second side **126**, respectively, of unitary body **110**. As discussed herein, low pressure fluid channel **138** may receive LPF via an opening(s) **140** formed through HGP component **100** and in fluid communication with low pressure supply conduit(s) **108** (portion shown in phantom) of support **102**.

In the non-limiting example shown in FIG. **5**, intermediate portion **136** and inner portion **132** may also define and/or form a cooling channel **142** within HGP component **100**. That is, cooling channel **142** may be formed between intermediate portion **136** and inner portion **132** of unitary body **110** for HGP component **100**. Cooling channel **142** may extend substantially between forward end **120** and aft end **122**, and first side **124** and second side **126**, respectively, of body **110**. As discussed herein, cooling channel **142** may

12

receive the HPF and low pressure fluid (LPF) to cool HGP component **100** during operation of gas turbine system **10** (see, FIG. **1**), and may subsequently expel or exhaust the HPF and LPF from HGP component **10** via exhaust holes **144**.

In order to provide the HPF and the LPF within the various portions (e.g., channels **138**, **142**) of HGP component **100** to cool the component, HGP component **100** and/or body **110** may also include a plurality and/or array of openings formed therein. For example, outer portion **134** and intermediate portion **136** of HGP component **100** may each include a plurality and/or array of openings, nozzles, and/or venturi formed therein and/or extending there-through. In the non-limiting example shown in FIGS. **4-6**, outer portion **134** may include a plurality of high pressure openings or nozzles **146** (hereafter, "nozzles **146**") formed therein or extending therethrough. Each of the plurality of nozzles **146** may be formed through outer surface **128** and outer portion **134** of unitary body **110** for HGP component **100**. The plurality of nozzles **146** formed through outer portion **134** may be in fluid communication with and/or fluidly coupled to high pressure fluid chamber **104** of support **102**. As a result of being fluidly coupled to high pressure fluid chamber **104**, each of the plurality of nozzles **146** may also be in fluid communication with the HPF flowing through turbine **28** and/or high pressure supply conduit(s) **106** of support **102** (see, FIG. **3**). Additionally, and as shown in FIG. **5**, the plurality of nozzles **146** formed through outer portion **134** may fluidly couple high pressure fluid chamber **104** of support **102** and low pressure fluid channel **138** of HGP component **100**. As discussed herein, each of the plurality of nozzles **146** formed through outer portion **134** may receive the HPF from the high pressure supply conduit **106** and/or high pressure fluid chamber **104** of support **102**, and subsequently provide or flow the HPF to low pressure fluid channel **138** of HGP component **100**.

Also shown in the non-limiting example of FIGS. **4-6**, intermediate portion **136** may include a plurality of low pressure openings or venturi **148** (hereafter, "venturi **148**") formed therein or extending therethrough. Each of the plurality of venturi **148** may be formed or extend through intermediate portion **136** of unitary body **110** for HGP component **100**. The plurality of venturi **148** formed through intermediate portion **136** may be in fluid communication with and/or may fluidly couple low pressure fluid channel **138** and cooling channel **142** formed within unitary body **110** for HGP component **100**. Additionally, and because venturi **148** are in fluid communication with low pressure fluid channel **138**, venturi **148** of HGP component **100** may also be in fluid communication with the LPF flowing through low pressure fluid channel **138**, and/or may be in fluid communication with low pressure supply conduit(s) **108** of support **102** providing the LPF to low pressure fluid channel **138**. As discussed herein, each of the plurality of venturi **148** formed through intermediate portion **136** may receive the LPF from low pressure fluid channel **138**, and subsequently provide or flow the LPF to cooling channel **142**. Additionally, and as discussed herein, each of the plurality of venturi **148** may receive the high pressure fluid (HPF) flowing through low pressure fluid channel **138** via the plurality of nozzles **146**, and subsequently provide or flow the HPF to cooling channel **142**. As discussed herein, nozzles **146** of HGP component **100** may differ from venturi **148** of HGP component **100** based on the size, shape, and/or configuration (e.g., the inclusion of a diffuser).

Turning to FIG. **6**, and with continued reference to FIG. **5**, an enlarged cross-section view of HGP component **100**

including a single nozzle **146** and a single venturi **148** is shown. In the non-limiting example shown in FIGS. **5** and **6**, the plurality of nozzles **146** formed in outer portion **134** and the plurality of venturi **148** formed in intermediate portion **136** of HGP component **100** may be radially and/or concentrically aligned. That is, each of the plurality of nozzles **146** may be aligned and/or substantially concentric with a corresponding venturi **148**. Additionally, and as shown in the non-limiting example FIG. **6**, each of the plurality of nozzles **146** formed in outer portion **134** may include a section **150** that may extend into a corresponding venturi **148** formed in intermediate portion **136**. Specifically, section **150** of may extend into and/or may be positioned partially within and/or surrounded by the radially and/or concentrically aligned, corresponding venturi **148** of HGP component **100**. As discussed herein, section **150** of each nozzles **146** may extend into corresponding venturi **148** to direct HPF through venturi **148**. Additionally, or alternatively, section **150** of each nozzles **146** may extend into corresponding venturi **148** to direct low pressure fluid (LPF) flowing through low pressure fluid channel **138** into venturi **148**, and/or prevent the LPF from flowing radially outward through nozzles **146**.

As shown in FIG. **6**, each of the plurality of nozzles **146** may be sized differently and/or may include a distinct dimension than the plurality of venturi **148**. That is, a dimension (e.g., diameter) of the plurality of nozzles **146** may be distinct from a dimension of the plurality of venturi **148**. In the non-limiting example, each of the plurality of nozzles **146** formed in outer portion **134** may include a first diameter (D_1) at the throat or neck (e.g., narrowest part) of the nozzle opening or configuration. Additionally, each of the plurality of venturi **148** formed in intermediate portion **136** may include a second diameter (D_2) at the throat (e.g., narrowest part) of the venturi opening or configuration. As shown in the non-limiting example in FIG. **6**, the second diameter (D_2) of each venturi **148** may be greater or larger than the first diameter (D_1) of nozzle **146**. In non-limiting examples the second diameter of venturi **148** may be at least twice as large (e.g., 2:1 ratio or greater) than the first diameter (D_1) of nozzle **146**. In other non-limiting examples, the second diameter of venturi **148** may be marginally larger (e.g., 10% larger) than the first diameter (D_1) of nozzle **146**. The size or dimension of each of the first diameter (D_1) and the second diameter (D_2), as well as the difference between first diameter (D_1) and the second diameter (D_2) may improve the velocity and/or pressure of the HPF and LPF flowing through HGP component **100**, as discussed herein.

It is understood that the size and/or number of nozzles **146** and venturi **148** formed within HGP component **100**, as shown in FIGS. **5** and **6**, is merely illustrative. As such, HGP component **100** may include larger or smaller nozzles **146** and venturi **148**, and/or may include more or less nozzles **146** and venturi **148** formed therein. Additionally, although the nozzles **146** and venturi **148** are both shown to be substantially uniform in size and/or shape, it is understood that each of the plurality of nozzles **146** and venturi **148** formed in HGP component **100** may include distinct sizes and/or shapes. The size, shapes, and/or number of nozzles **146** and venturi **148** formed in HGP component **100** may depend at least in part on various parameters (e.g., exposure temperature, exposure pressure, position within turbine casing **36**, HPF operational pressure/temperature, LPF operational pressure/temperature, and the like) of gas turbine system **10** during operation. Additionally, or alternatively, the size, shapes, and/or number of nozzles **146** and venturi **148** formed in HGP component **100** may be dependent, at

least in part on the characteristics (e.g., inner portion **132** thickness, outer portion **134** thickness, volume of cooling channel **142**, and so on) of HGP component **100**.

Additionally as shown in FIG. **6**, intermediate portion **136** of unitary body **110** for HGP component **100** may also include a plurality of diffusers **152**. Each of the plurality of diffusers **152** may be formed integral with a corresponding venturi **148** formed through intermediate portion **136**. That is, and as shown in FIG. **6**, diffuser **152** may be formed integral with each venturi **148** and may be positioned radially adjacent the venturi **148**, and more specifically the throat (e.g., narrowest part) of each venturi **148**. Diffuser **152** may also be formed adjacent and/or extend radially toward inner portion **132** of body **110** of HGP component **100**. In the non-limiting example, diffuser **152** may include a diverging shape, geometry, and/or configuration that gets larger or wider as diffuser **152** extends (radially) closer toward inner portion **132** of HGP component **100**. In the non-limiting example, the largest dimension (e.g., diameter) of diffuser **152** may be formed at an end **154** radially adjacent inner portion **132**. End **154** of diffuser **152** may include a third diameter (D_3), that may be larger or greater than first diameter (D_1) of nozzles **146** and second diameter (D_2) of venturi **148**. In addition to the size or dimension of each of the first diameter (D_1) and the second diameter (D_2), the size of the third diameter (D_3) of each diffuser **152** of HGP component **100** may increase a static pressure of the HPF and LPF flowing through HGP component **100**, as discussed herein.

Furthermore, although discussed herein as being substantially circular and/or including distinct diameters (e.g., first diameter (D_1), the second diameter (D_2), and so on), it is understood that nozzles **146**, venturi **148**, and/or diffusers **152** may be formed from distinct shapes or configurations. As such, the dimensions of each of nozzles **146**, venturi **148**, and diffusers **152** may not include a diameter. That is for example, nozzles **146**, venturi **148**, and/or diffusers **152** may be substantially square or polygonal. In these non-limiting examples, each of nozzles **146**, venturi **148**, and diffusers **152** may include unique and/or distinct areas (e.g., dimension). More specifically, the throat of nozzles **146** may include a first area (A_1), the throat of venturi **148** may include a second area (A_2) that may be larger than the first area (A_1) of nozzles **146**, and diffusers **152** may include a third area (A_3) that is larger than both the first area (A_1) and the second area (A_2), respectively.

Additionally as shown in FIGS. **4-6**, HGP component **100** may also include a plurality of support pins **156**. Specifically, body **110** of HGP component **100** may include a plurality of support pins **156** positioned/extending between, and formed integral with inner portion **132** and intermediate portion **136**, as well as intermediate portion **136** and outer portion **134**. As shown in FIGS. **5** and **6**, the plurality of support pins **156** extending between inner portion **132** and intermediate portion **136** may also be positioned within cooling channel **142**, and the plurality of support pins **156** extending between intermediate portion **136** and outer portion **134** may be positioned within low pressure fluid channel **138**. The plurality of support pins **156** may be positioned throughout body **110** for HGP component **100** to provide support, structure, and/or rigidity to inner portion **132**, outer portion **134**, and/or intermediate portion **136**. The inclusion of the plurality of support pins **156** extending between and/or be formed integral with inner portion **132**, outer portion **134**, and/or intermediate portion **136** provides additional support, structure, and/or rigidity to the various portions of HGP component **100**, and may substantially prevent

vibration of the same during operation of gas turbine system 10. In addition to providing support, structure, and/or rigidity to inner portion 132, outer portion 134, and/or intermediate portion 136, the plurality of support pins 156 positioned within low pressure fluid channel 138 and/or cooling channel 142 may also aid in the heat transfer and/or cooling of HGP component 100 during operation of gas turbine system 10 (see, FIG. 1), as discussed herein. The plurality of support pins 156 may be formed integral with inner portion 132, outer portion 134, and/or intermediate portion 136 when forming unitary body 110 of HGP component 100 using any suitable additive manufacturing process(es) and/or method.

The size, shape, and/or number of support pins 156 positioned within HGP component 100, as shown in FIGS. 4-6, is merely illustrative. As such, HGP component 100 may include larger or smaller support pins 156, varying sized support pins 156, and/or may include more or less support pins 156 formed therein. The size, shapes, and/or number of support pins 156 formed in HGP component 100 may be dependent, at least in part on the operational characteristics (e.g., exposure temperature, exposure pressure, position within turbine casing 36, and the like) of gas turbine system 10 during operation. Additionally, or alternatively, the size, shapes, and/or number of support pins 156 formed in HGP component 100 may be dependent, at least in part on the characteristics (e.g., inner portion 132 thickness, outer portion 134 thickness, height of channels 138, 142, and so on) of HGP component 100.

With reference to FIGS. 3-6, an example flow path of HPF and LPF through HGP component 100 is described. Specifically in FIGS. 3, 5 and 6, the flow direction of the fluid may be represented by arrows and may be labeled as "HPF" and "LPF."

In the non-limiting example, HPF may flow from area 50, through high pressure supply conduit 106 (see, FIG. 3), and into high pressure fluid chamber 104 of support 102. From high pressure fluid chamber 104, the HPF may flow through the plurality of nozzles 146 formed through outer portion 134. In the non-limiting example where nozzles 146 are radially aligned and/or concentric with venturi 148, the HPF may flow directly into and/or through the venturi 148 formed through intermediate portion 136. The HPF may mix with and substantially energize or increase the velocity of the LPF also flowing through venturi 148. The HPF may flow through the venturi 148, may be diffused by diffuser 152 of intermediate portion 136, and may flow to cooling channel 142 of HGP component 100. Once inside cooling channel 142, the mixture of HPF and LPF may substantially cool inner portion 132 of HGP component 100 and may flow through cooling channel 142 toward forward end 120 or aft end 122 before being exhausted from HGP component via exhaust holes 144 of cooling channel 142.

Simultaneous to and/or independently of the HPF flowing through HGP component 100, LPF may be provided to and flow through HGP component 100 as well. LPF may flow from area 52, through low pressure supply conduit(s) 108 of support 102 (see, FIG. 3). In the non-limiting example, low pressure supply conduit 108 may be in direct fluid communication with opening 140 of low pressure fluid channel 138 formed through aft end 122 of HGP component 100. Additionally, and as shown in phantom, a distinct low pressure supply conduit 108 may be in direct fluid communication with a distinct opening 140 of low pressure fluid channel 138 formed through forward end 120 of HGP component 100. As such, LPF may be provided on opposite sides or ends of low pressure fluid channel 138. Once provided to low pressure

fluid channel 138, the LPF may flow through the plurality of venturi 148 formed through intermediate portion 136. In the non-limiting example where section 150 (see, FIG. 6) of nozzles 146 extends into venturi 148, nozzles 146 may direct the LPF through venturi 148. Additionally where nozzles 146 are radially aligned and/or concentric with venturi 148 the LPF may flow directly into venturi 148 and may mix with the HPF and substantially be charge or experience an increase in velocity when flowing through venturi 148. Similar to the HPF the LPF may flow through the venturi 148, may be diffused by diffuser 152 of intermediate portion 136, and may flow to cooling channel 142 of HGP component 100. Once inside cooling channel 142, the LPF, along with the HPF, may substantially cool inner portion 132 of HGP component 100 and may flow through cooling channel 142 toward forward end 120 or aft end 122 before being exhausted from HGP component via exhaust holes 144 and 145 of cooling channel 142 (see, FIG. 5).

FIGS. 7 and 8 show various views of another non-limiting example of turbine 28 including HGP component 100 and support 102. Specifically, FIG. 7 shows an enlarged side view of a non-limiting example of a portion of turbine 28 of gas turbine system 10 (see, FIG. 1) including HGP component 100 coupled to support 102, and FIG. 8 shows a cross-sectional side view of another non-limiting example of HGP component 100 shown in FIG. 7. It is understood that similarly numbered and/or named components may function in a substantially similar fashion. Redundant explanation of these components has been omitted for clarity.

As shown in FIG. 7, and with comparison to the non-limiting example discussed herein with respect to FIG. 3, support 102 may not include high pressure fluid chamber 104 (see, FIG. 3). Rather support 102 may be formed as a substantially solid and/or continuous component or part that may abut or contact outer surface 128 of HGP component 100, and may include a plurality of supply conduits formed therein. In the non-limiting example shown in FIG. 7, support 102 may include a plurality of high pressure supply conduits 106, and a single low pressure supply conduit 108 formed therein. The plurality of high pressure supply conduits 106 may extend through support 102, e.g., to forward end 120 or aft end 122 of HGP component 100. Additionally, each of the plurality of high pressure supply conduits 106 may be in direct fluid communication and/or fluidly coupled directly to HGP component 100. That is, each of the plurality of high pressure supply conduit 106 of support 102 may be in fluid communication and/or fluidly coupled to area 50 and a channel (e.g., high pressure fluid channel) (see, FIG. 8) of HGP component 100. As discussed herein, high pressure supply conduits 106 may provide the high pressure fluid (HPF) from area 50 to HGP component 100 during operation of gas turbine system 10 (see, FIG. 1).

Turning to FIG. 8, and with continued reference to FIG. 7, HGP component 100 may include additional features and/or components when utilized in turbine 28. For example, and as discussed herein, HGP component 100 may not be formed from a unitary body 110. Rather, HGP component 100 may be formed from a first part 157, and a distinct, second part 158. More specifically, HGP component 100 may be formed from and/or include first part 157 and second part 158 that may be joined, coupled, and/or affixed to first part 157. As shown in FIG. 8, first part 157 of HGP component 100 may include hooks 112, 118, inner surface 130 and inner portion 132 of HGP component 100. Additionally in the non-limiting example, first part 157 of HGP component 100 may include a portion of low pressure fluid

channel(s) **138** including opening(s) **140** and a portion of a high pressure fluid channel(s) **160** including opening(s) **162**, as discussed herein.

Second part **158** may include distinct features and/or portions of HGP component **100** than first part **157**. For example, second part **158** may include outer portion **134**, intermediate portion **136**, and a top plate **159** including outer surface **128** of HGP component **100**, as discussed herein. Additionally in the non-limiting example, second part **158** may also include nozzles **146** formed through outer portion **134**, venturi **148** formed through intermediate portion **136**, and a plurality of support pins **156** extending between and/or from outer portion **134**, intermediate portion **136**, and top plate **159**, respectively. As shown in FIG. **8**, second part **158** may also include a portion of low pressure fluid channel(s) **138** formed between outer portion **134** and intermediate portion **136**, as well as a portion of high pressure fluid channel(s) **160** formed between outer portion **134** and top plate **159**. Cooling channel **142** may be formed between first part **157** and second part **158**, and more specifically, intermediate portion **136** of second part **158** and inner portion **132** of first part **157**.

In the non-limiting example shown in FIG. **8**, first part **157** and second part **158** may be formed from distinct materials. For example, first part **157** including hooks **112**, **118** and inner portion **132** may be formed from a first metal or alloy having a first set of material properties and/or characteristics (e.g., melting point, heat transfer characteristics, hardness, ductility, and the like), while second part **158** may be formed from a second metal or alloy having a second set of material properties and/or characteristics. Alternatively, first part **157** and second part **158** may be formed from identical materials. Each of first part **157** and second part **158** may each be formed individually and/or separately using any suitable manufacturing process including, but not limited to milling, turning, cutting, casting, molding, drilling, and the like. Additionally, first part **157** and second part **158** may be joined, coupled, and/or affixed to one another to form HGP component **100** using any suitable joining process or technique including, but not limited to, welding, fastening, melting, sintering, brazing, and the like.

In the non-limiting example shown in FIG. **8**, HGP component **100** may also include top plate **159** formed radially outward, radially adjacent, and/or radially above outer portion **134** of second part **158**. Additionally as shown in FIGS. **7** and **8**, top plate **159** may be positioned radially inward from and/or may substantially contact or abut a portion of support **102**. Top plate **159** may be formed from a substantially solid or continuous (e.g., no openings or venturi) component that may be formed, extend, and/or positioned substantially between forward end **120** and aft end **122**, as well as first side **124** and second side **126**, respectively. In the non-limiting example discussed herein, top plate **159** may be part of or formed in second part **158** forming HGP component **100**. In other non-limiting examples (not shown), top plate **159** may be separate component or part of HGP component **100** that may be joined, coupled, and/or affixed to first part **157** and/or second part **158** to form HGP component **100**.

Additionally as shown in FIG. **8**, HGP component **100** may also include high pressure fluid channel **160**. High pressure fluid channel **160** may be formed between outer portion **134** and top plate **159**. That is, top plate **159** and outer portion **134** for HGP component **100** may define and/or form high pressure fluid channel **160** within HGP component **100**. High pressure fluid channel **160** may extend

substantially between forward end **120** and aft end **122**, and first side **124** and second side **126**, respectively, of HGP component **100**. High pressure fluid channel **160** may include openings **162** extending through first part **157** of HGP component **100** and/or formed adjacent forward end **120** or aft end **122** of HGP component **100**. Openings **162** may be fluidly coupled to a respective high pressure supply conduit **106** (portion shown in phantom) to receive HPF from high pressure supply conduits **106** of support **102** and subsequently supply the HPF to high pressure fluid channel **160**. High pressure fluid channel **160** may supply or provide the HPF to the plurality of nozzles **146** formed through outer portion **134**. As similarly discussed herein, the HPF may flow through the nozzles **146** to mix with and substantially energize or increase the velocity of the LPF as it flows through venturi **148**. The HPF may be provided to cooling channel **142** of HGP component **100** before being exhausted from HGP component **100** via the array of openings **145**.

FIG. **9** shows another non-limiting example of an enlarged side view of a portion of turbine **28** of gas turbine system **10** (see, FIG. **1**) including HGP component **100** coupled to support **102**. In the non-limiting example, HGP component **100** may be formed as unitary body **110**, as similarly discussed herein with respect to FIGS. **3-5**. Additionally, in the non-limiting example, support **102** may only include a single high pressure supply conduit **106**. High pressure supply conduit **106** may be formed and/or extend through support **102** from area **50** to adjacent forward end **120** of unitary body **110** for HGP component **100**. As similarly discussed herein, high pressure supply conduit **106** of support **102** may be in fluid communication and/or fluidly coupled to area **50** and HGP component **100** (e.g., high pressure fluid channel **160**) (see, FIG. **8**) to provide the high pressure fluid (HPF) from area **50** to HGP component **100** during operation of gas turbine system **10** (see, FIG. **1**).

Additionally in the non-limiting example shown in FIG. **9**, support **102** may include a low pressure fluid chamber **164**. Low pressure fluid chamber **164** may be formed within support **102**, radially adjacent to, and/or radially outward from HGP component **100**. Low pressure fluid chamber **164** may be formed in support **102** to receive low pressure fluid (LPF) flowing through and/or within area **52** of turbine **28** that may be subsequently provided to HGP component **100** during operation of gas turbine system **10** (see, FIG. **1**). For example, low pressure fluid chamber **164** may be fluidly coupled to and/or in fluid communication with at least one low pressure inlet **166**, and at least one low pressure supply conduit **108** formed within support **102**. In the non-limiting example low pressure inlet **166** may be in fluid communication with and/or fluidly coupled to area **52** within of turbine casing **36** that may contain LPF, and may be in fluid communication with and/or fluidly coupled to low pressure fluid chamber **164**. Low pressure inlet **166** may receive the LPF from area **52** and provide the LPF to low pressure fluid chamber **164**. Once received in low pressure fluid chamber **164**, the LPF may be provided to the at least one low pressure supply conduit **108**, and subsequently provided to low pressure fluid channel **138** (see, FIG. **5**) of HGP component **100** via low pressure supply conduit **108**, as similarly discussed herein.

FIGS. **10** and **11** show various views of another non-limiting example of turbine **28** including HGP component **100** and support **102**. Specifically, FIG. **10** shows an enlarged side view of a non-limiting example of a portion of turbine **28** of gas turbine system **10** (see, FIG. **1**) including HGP component **100** coupled to support **102**, and FIG. **11** shows a cross-sectional side view of another non-limiting

example of HGP component **100** shown in FIG. **10**. It is understood that similarly numbered and/or named components may function in a substantially similar fashion. Redundant explanation of these components has been omitted for clarity.

Similar to the non-limiting example shown in FIG. **9**, support **102** may include low pressure fluid chamber **164**. Low pressure fluid chamber **164** may be formed in support **102** radially adjacent to, and/or radially outward from HGP component **100**. As discussed herein, low pressure fluid chamber **164** may receive low pressure fluid (LPF) flowing through and/or within area **52** of turbine **28**. In the non-limiting example, low pressure fluid chamber **164** may be fluidly coupled to and/or in direct fluid communication with low pressure supply conduit **108** formed within support **102**. Low pressure supply conduit **108** may be in fluid communication with and/or fluidly coupled to area **52** within of turbine casing **36** that may contain LPF, and may provide LPF to low pressure fluid chamber **164**.

However, the non-limiting example shown in FIGS. **10** and **11** includes HGP component **100** and/or support **102** having distinct configurations than other non-limiting examples of HGP component **100** and/or support **102** discussed herein. For example, and distinct from the non-limiting example shown in FIG. **9**, low pressure fluid chamber **164** may be fluidly coupled and/or in direct fluid communication with features of HGP component **100**. More specifically, and as shown in FIGS. **10** and **11**, low pressure fluid chamber **164** may be formed (radially) adjacent outer portion **134** of HGP component **100** such that outer portion **134** of HGP component **100** may at least partially form and/or define low pressure fluid chamber **164** within HGP component **100**. Additionally, low pressure fluid chamber **164** may be fluidly coupled and/or in direct fluid communication with the plurality of nozzles **146** formed or extending through outer portion **134** of HGP component **100**. As a result of being formed radially adjacent to and in direct fluid communication with the plurality of nozzles **146** extending through outer portion **134**, low pressure fluid chamber **164** may provide LFP to each of the plurality of nozzles **146** when cooling HGP component **100**, as discussed herein.

Support **102** may also include at least one high pressure supply conduit **106** formed therein. High pressure supply conduit **106** may be in direct fluid communication with and/or fluidly coupled to area **50** containing the HPF, as well as HGP component **100**. More specifically, and as shown in FIGS. **10** and **11**, high pressure supply conduit **106** may be in fluid communication with and/or may fluidly couple area **50** of turbine **28** (see, FIG. **10**) and high pressure fluid channel **160** of HGP component **100** (see, FIG. **11**) to provide HPF from area **50** to high pressure fluid channel **160** of HGP component **100**. In the non-limiting example shown in FIG. **11**, high pressure supply conduit **106** may be in fluid communication with high pressure fluid channel **160** via opening **162** formed through forward end **120** of HGP component **100**. As a result of low pressure fluid chamber **164** being in direct fluid communication with nozzles **146**, and distinct from the non-limiting examples discussed herein (e.g., FIG. **9**), high pressure fluid channel **160** may be formed between and/or defined by outer portion **134** and intermediate portion **136** of body **110** for HGP component **100**. Each of the plurality of venturi **148** formed or extending through intermediate portion **136** may in turn be fluidly coupled and/or in direct fluid communication with high pressure fluid channel **160** and may receive HPF when cooling HGP component **100**, as discussed herein.

With reference to FIGS. **10** and **11**, an example flow path of LPF and HPF through HGP component **100** is described. In the non-limiting example, LPF may flow from area **52**, through low pressure supply conduit(s) **108** of support **102** (see, FIG. **10**) to low pressure fluid chamber **164**. From low pressure fluid chamber **164**, the LPF may flow through the plurality of nozzles **146** formed through outer portion **134**. In the non-limiting example where nozzles **146** are radially aligned and/or concentric with venturi **148**, the LPF may flow directly into and/or through the venturi **148** formed through intermediate portion **136**. Additionally or alternatively, LPF may flow from each of the plurality of nozzles **146** include high pressure fluid channel **160** formed between outer portion **134** and intermediate portion **136** of HGP component **100** shown in FIG. **11**. The LPF may mix with and substantially be energized or increase in velocity with the HPF also flowing through venturi **148**, as discussed herein. The LPF may flow through the venturi **148**, may be diffused by diffuser **152** of intermediate portion **136**, and may flow to cooling channel **142** of HGP component **100**. Once inside cooling channel **142**, the mixture of LPF and HPF may substantially cool inner portion **132** of HGP component **100** and may flow through cooling channel **142** toward forward end **120** or aft end **122** before being exhausted from HGP component via exhaust holes **144** of cooling channel **142**.

Simultaneous to and/or independently of the LPF flowing through HGP component **100**, HPF may flow from area **50**, through high pressure supply conduit **106** formed in support **102** (see, FIG. **10**). High pressure supply conduit **106** may be in direct fluid communication with opening **162** of high pressure fluid channel **160** formed through forward end **120** of HGP component **100**. Once provided to high pressure fluid channel **160**, the HPF may flow through the plurality of venturi **148** formed through intermediate portion **136**. In the non-limiting example where a section (e.g., section **150**; see, FIG. **6**) of nozzles **146** extends into venturi **148**, nozzles **146** may direct the HPF through venturi **148**. Additionally where nozzles **146** are radially aligned and/or concentric with venturi **148** the HPF may flow directly into venturi **148** and may mix with the LPF. HPF flowing through high pressure fluid channel **160** and/or venturi **148** may substantially charge or increase the velocity of LPF flowing through venturi **148** from nozzles **146**. Similar to the LPF, the HPF may flow through the venturi **148**, may be diffused by diffuser **152** of intermediate portion **136**, and may flow to cooling channel **142** of HGP component **100**. Once inside cooling channel **142**, the HPF, along with the LPF, may substantially cool inner portion **132** of HGP component **100** and may flow through cooling channel **142** toward forward end **120** or aft end **122** before being exhausted from HGP component via exhaust holes **144** and **145** of cooling channel **142** (see, FIG. **11**).

FIGS. **12** and **13** show various views of another non-limiting example of turbine **28** including HGP component **100** and support **102**. Specifically, FIG. **12** shows an enlarged side view of a non-limiting example of a portion of turbine **28** of gas turbine system **10** (see, FIG. **1**) including HGP component **100** coupled to support **102**, and FIG. **13** shows a cross-sectional side view of another non-limiting example of HGP component **100** shown in FIG. **12**. It is understood that similarly numbered and/or named components may function in a substantially similar fashion. Redundant explanation of these components has been omitted for clarity.

Similar to the non-limiting example shown in FIG. **7**, support **102** shown in the non-limiting example of FIG. **12**

may not include an internal pressure chamber (e.g., high pressure fluid chamber **104**, low pressure fluid chamber **164**). As such, and similar to FIGS. **7** and **8**, HGP component **100** may include a top plate **159** formed radially outward, radially adjacent, and/or radially above outer portion **134** of HGP component **100**. Top plate **159** may be positioned radially inward from and/or may substantially contact or abut a portion of support **102**, as shown in FIG. **12**.

However, the non-limiting example shown in FIGS. **12** and **13** includes HGP component **100** and/or support **102** having distinct configurations than other non-limiting examples (e.g., FIGS. **7** and **8**) of HGP component **100** and/or support **102** discussed herein. For example, although support **102** includes high pressure supply conduit **106**, and low pressure supply conduit **108**, each supply conduit **106**, **108** may be formed through support **102** in distinct areas and/or may be fluidly coupled to distinct portions of HGP component **100** than the non-limiting example discussed herein with respect to FIGS. **7** and **8**. Specifically, support **102** may include a single high pressure supply conduit **106** formed therein. High pressure supply conduits **106** may extend through support **102**, to adjacent forward end **120** of HGP component **100**. High pressure supply conduit **106** may be in direct fluid communication and/or fluidly coupled directly to HGP component **100**, and area **50**, respectively, to provide HPF from area **50** to HGP component **100** during operation of gas turbine system **10** (see, FIG. **1**). In the non-limiting example, high pressure supply conduit **106** may be fluidly coupled to and/or in direct fluid communication with high pressure fluid channel **160** via opening **162** (see, FIG. **13**) formed through forward end **120** of HGP component **100**. As shown in FIGS. **12** and **13**, and similar to the non-limiting example shown in FIGS. **10** and **11**, high pressure fluid channel **160** may be formed between and/or defined by outer portion **134** and intermediate portion **136** of body **110** for HGP component **100**. Each of the plurality of venturi **148** formed or extending through intermediate portion **136** may in turn be fluidly coupled and/or in direct fluid communication with high pressure fluid channel **160** and may receive HPF when cooling HGP component **100**. That is, HPF may flow from high pressure supply conduit **106** directly to high pressure fluid channel **160**, and subsequently through the plurality of venturi **148** extending through intermediate portion **136**. As similarly discussed herein with respect to FIGS. **10** and **11**, HPF flowing through the plurality of venturi **148** may mix with LPF provided by the plurality of nozzles **146**, into cooling channel **142** before being discharged from HGP component **100**.

Additionally as shown in the non-limiting example of FIG. **12**, support **102** may include a plurality of low pressure supply conduits **108**. The plurality of low pressure supply conduits **108** may extend through support **102** toward forward end **120** and aft end **122**, respectively, of HGP component **100**. Additionally, each of the plurality of low pressure supply conduits **108** may be in direct fluid communication and/or fluidly coupled directly to HGP component **100**. That is, each of the plurality of low pressure supply conduit **108** of support **102** may be in fluid communication and/or fluidly coupled to area **50**, as well as low pressure fluid channel **138**, via opening **140** (see, FIG. **13**), of HGP component **100**. As shown in FIGS. **12** and **13**, low pressure fluid channel **138** may be formed between and/or defined by outer portion **134** and top plate **159** of body **110** for HGP component **100**. Each of the plurality of nozzles **146** formed or extending through outer portion **134** may in turn be fluidly coupled and/or in direct fluid communication with low pressure fluid channel **138** and may receive LPF

when cooling HGP component **100**. That is, LPF may flow from each of the plurality of low pressure supply conduits **108** directly to low pressure fluid channel **138**, and subsequently through the plurality of nozzles **146** extending through outer portion **134**. From the plurality of nozzles **146**, and as similarly discussed herein with respect to FIGS. **10** and **11**, LPF flowing through the plurality of nozzles **146** may flow into the plurality of venturi **148**, and may mix with HPF, before flowing into cooling channel **142** and being discharged from HGP component **100**.

FIGS. **14** and **15** show additional views of another non-limiting example of HGP component **200** included in turbine **28** of gas turbine system **10**. Specifically, FIG. **14** shows a side view of a portion of turbine **28** including two stages of turbine blades **38**, and a stage of stator vanes **40** including HGP components **200A**, **200B** positioned within casing **36** of turbine **28**, and FIG. **15** shows an enlarged portion of turbine **28** including HGP component **200A** and support **202**. It is understood that similarly numbered and/or named components may function in a substantially similar fashion. Redundant explanation of these components has been omitted for clarity.

In the non-limiting example shown in FIGS. **14** and **15**, and as discussed herein with respect to FIG. **2**, HGP components **200A**, **200B** may be formed as an outer platform and inner platform, respectively, of stator vane **40**, and may be coupled and/or affixed to airfoil **42** of stator vane **40**. Additionally as discussed herein, support **202** may extend radially inward from casing **36** of turbine **28**, and may be configured to be coupled to and/or receive HGP component **200A** (e.g., outer platform) of stator vanes **40** to couple, position, and/or secure stator vanes **40** to and/or within casing **36**. In this non-limiting example shown in FIGS. **14** and **15**, and similar to HGP component **100** and turbine shroud discussed herein (see, FIGS. **2-13**), HGP component **200A** and outer platform of stator vane **40** may be used interchangeably, and HGP component **200B** and inner platform may be used interchangeably.

As shown in FIGS. **14** and **15**, HGP components **200A**, **200B** and support **202** may be surrounded by high pressure fluid (HPF) and low pressure fluid (LPF) flowing within turbine **28**. Specifically, area **52** positioned upstream of HGP component **200A** and support **202** may include LPF, while area **50** positioned downstream of HGP component **200A** and support **202** may include HPF. Additionally, area **52** positioned upstream of HGP component **200B** may include LPE, and area **50** positioned downstream of HGP component **200B** may include HPF.

Similar to HGP component **100** (e.g., turbine shroud) and support **102** discussed herein, HGP component **200A** and support **202** may be configured to and/or may include features that may allow HGP component **200A** to be cooled using HPF and LPF. For example, and as shown in FIG. **15**, support **202** may include at least one high pressure supply conduit **206** formed therein. High pressure supply conduit **206** may be in fluid communication with and/or fluidly coupled to area **50** containing the HPF, as well as HGP component **200A**. High pressure supply conduit **206** may receive the HPF flowing through area **50**, and may provide the HPF directly to HGP component **200A**, as discussed herein. Although shown in the non-limiting example as only including a single high pressure supply conduit **206**, it is understood that support **202** may include a plurality of high pressure supply conduits **206** for providing HPF to HGP component **200A**.

Support **202** may also include at least one low pressure supply conduit **208**. Low pressure supply conduit(s) **208**

23

may be in fluid communication with and/or fluidly coupled to area 52 containing LPF. As shown in FIG. 15, and discussed herein, low pressure supply conduit(s) 208 may be fluidly coupled to and/or in fluid communication with HGP component 200A to provide the LPF from area 52 to HGP component 200A during operation of turbine system 10 (see, FIG. 1).

HGP component 200A (e.g., outer platform) may also include a body including a plurality of surfaces, portions, fluid channels, nozzles, and venturi that may be used to cool HGP component 200A using HPF and LPF flowing through turbine 28. For example, and as shown in FIG. 15, HGP component 200A may include body 210. In the non-limiting example shown in FIG. 1, HGP component 200A may include and/or be formed as a unitary body 210 such that HGP component 200A is a single, continuous, and/or non-disjointed component or part. In the non-limiting example, unitary body 210 of HGP component 200A, and the various components and/or features of HGP component 200A, may be formed using any suitable additive manufacturing process(es) and/or method, as similarly discussed herein. In another non-limiting example, body 210 of HGP component 200A may be formed as multiple and/or distinct portions or components (not shown), as similarly discussed herein (see, FIGS. 7 and 8).

HGP component 200A may also include inner surface 230 positioned, formed, facing, directly exposed to, and/or partially defining the hot gas flow path (FP) of combustion gases 26 flowing through turbine casing 36 of turbine 28 for gas turbine system 10. Inner surface 230 of body 210 for HGP component 200A may be positioned radially adjacent to airfoil 42 of stator vane 40. In addition to facing the hot gas flow path (FP) of combustion gases 26, inner surface 230 of body 210 may also be formed and/or positioned between forward end 220 and aft end 222 of HGP component 200A.

As shown in FIG. 15, HGP component 200A may also include an inner portion 232. Inner portion 232 may be formed as an integral portion of (unitary) body 210 for HGP component 200A. Additionally, inner portion 232 may include inner surface 230, and/or inner surface 230 may be formed on inner portion 232 of body 210 for HGP component 200A. Inner portion 232 of body 210 for HGP component 200A may be formed, positioned, and/or extend between forward end 220 and aft end 222, and opposite sides (not shown) of HGP component 200A. Additionally, inner portion 232 may be formed integral with the solid side walls formed on the sides of body 210 (not shown). Inner portion 232 of HGP component 200A may also be positioned adjacent hot gas flow path (FP) for turbine 28 of turbine system 10.

HGP component 200A may also include an outer portion 234 formed radially opposite inner portion 232. Similar to inner portion 232, outer portion 234 may be formed as an integral portion of unitary body 210 for HGP component 200A. Outer portion 234 of body 210 for HGP component 200A may be formed, positioned, and/or extend between forward end 220 and aft end 222, and opposite sides (not shown) of body 210, respectively. Outer portion 234 of HGP component 200A may at least partially form and/or define various fluid channels within HGP component 200A, as discussed herein.

As shown in the non-limiting example of FIG. 15, HGP component 200A may also include an intermediate portion 236. Intermediate portion 236 may be formed (radially) between inner portion 232 and outer portion 234 of unitary body 210 of HGP component 200A. Similar to inner portion 232 and outer portion 234, and as shown in FIG. 1, inter-

24

mediate portion 236 of HGP component 200A may be formed as an integral portion of body 210 for HGP component 200A. Intermediate portion 236 of body 210 for HGP component 200A may be formed, positioned, and/or extend between forward end 220 and aft end 222, and opposite sides of body 210, and may be formed integral with the solid side walls formed on the opposite sides (not shown).

HGP component 200A may also include top plate 259 formed radially outward, radially adjacent, and/or radially above outer portion 234 of body 210. Top plate 259 may be positioned radially inward from and/or may substantially contact or abut a portion of support 202. Top plate 259 may be formed from a substantially solid or continuous (e.g., no openings or venturi) component that may be formed, extend, and/or positioned substantially between forward end 220 and aft end 222, as well as opposite sides of body 210, respectively. In the non-limiting example, top plate 259 may form and/or define outer surface 228 of HGP component 200A.

Inner portion 232, outer portion 234, intermediate portion 236, and/or top plate 259 may at least partially form and/or define channels within HGP component 200A. For example, intermediate portion 236 and outer portion 234 may define and/or form a low pressure fluid channel 238 within HGP component 200A. More specifically, low pressure fluid channel 238 may be formed between intermediate portion 236 and outer portion 234 of unitary body 210 for HGP component 200A. Low pressure fluid channel 238 may extend substantially between forward end 220 and aft end 222, and opposite sides of unitary body 210. As discussed herein, low pressure fluid channel 238 may receive LPF via an opening(s) formed through HGP component 200A and in fluid communication with low pressure supply conduit(s) 208 of support 202.

In the non-limiting example shown in FIG. 15, intermediate portion 236 and inner portion 232 may also define and/or form a cooling channel 242 within HGP component 200A. That is, cooling channel 242 may be formed between intermediate portion 236 and inner portion 232 of unitary body 210 for HGP component 200A. Cooling channel 242 may extend substantially between forward end 220 and aft end 222, and opposite sides (not shown) of body 210. Cooling channel 238 may receive the HPF and low pressure fluid (LPF) to cool HGP component 200A during operation of gas turbine system 10 (see, FIG. 1), and may subsequently expel or exhaust the HPF and LPF from HGP component 10 via exhaust holes 244, 245.

HGP component 200A may also include high pressure fluid channel 260. High pressure fluid channel 260 may be formed between outer portion 234 and top plate 259. That is, top plate 259 and outer portion 234 for HGP component 200A may define and/or form high pressure fluid channel 260 within HGP component 200A. High pressure fluid channel 260 may extend substantially between forward end 220 and aft end 222, and opposite sides of body 210. High pressure fluid channel 260 may include an opening(s) fluidly coupled to high pressure supply conduit 206 to receive HPF from high pressure supply conduits 206 of support 202 and subsequently supply the HPF to high pressure fluid channel 260. In another non-limiting example (not shown), HGP component 200A may not include top plate 259. As such, high pressure fluid channel 260 may be formed between outer portion 234 and support 202, and may be in direct fluid communication with high pressure supply conduit 206 for receiving HPF, as discussed herein.

Additionally, and similar to HGP component 100 discussed herein with respect to FIGS. 2-9, HGP component

200A may include a plurality of nozzles 246 and venturi 248 formed therein. For example, outer portion 234 of HGP component 200A may include a plurality of openings or nozzles 246 (hereafter, "nozzles 146") formed therein or therethrough. Each of the plurality of nozzles 246 may be formed through outer portion 234 of unitary body 210 for HGP component 200A. The plurality of nozzles 246 formed through outer portion 234 may be in fluid communication with and/or fluidly coupled to high pressure fluid channel 260 of HGP component 200A. Additionally, and as shown in FIG. 15, the plurality of nozzles 246 formed through outer portion 134 may fluidly couple high pressure fluid channel 260 and low pressure fluid channel 238 of HGP component 200A. As discussed herein, each of the plurality of nozzles 246 formed through outer portion 234 may receive the HPF from the high pressure supply conduit 206 and/or high pressure fluid channel 260, and subsequently provide or flow the HPF to low pressure fluid channel 238 of HGP component 200A.

Also shown in the non-limiting example of FIG. 15, intermediate portion 236 may include a plurality of openings or venturi 248 (hereafter, "venturi 248") formed therein or therethrough. Each of the plurality of venturi 248 may be formed through intermediate portion 236 of body 210 for HGP component 200A. The plurality of venturi 248 formed through intermediate portion 236 may be in fluid communication with and/or may fluidly couple low pressure fluid channel 238 and cooling channel 242 formed within body 210 for HGP component 200A. Additionally, and because venturi 248 are in fluid communication with low pressure fluid channel 238, venturi 248 of HGP component 200A may also be in fluid communication with the LPF flowing through low pressure fluid channel 238, and/or may be in fluid communication with low pressure supply conduit(s) 208 of support 202 providing the LPF to low pressure fluid channel 238. As discussed herein, each of the plurality of venturi 248 formed through intermediate portion 236 may receive the LPF from low pressure fluid channel 238, and subsequently provide or flow the LPF to cooling channel 242. Additionally, and as discussed herein, each of the plurality of venturi 248 may receive the HPF flowing through low pressure fluid channel 238 via the plurality of nozzles 246, and subsequently provide or flow the HPF to cooling channel 242.

The plurality of nozzles 246 and venturi 248 formed within HGP component 200A may include substantially similar features as the plurality of nozzles 146 and venturi 148 of HGP component 100 discussed herein with respect to FIGS. 5 and 6. For example as shown in FIG. 15, the plurality of nozzles 246 formed in outer portion 234 and the plurality of venturi 248 formed in intermediate portion 236 of HGP component 200A may be radially and/or concentrically aligned. That is, each of the plurality of nozzles 246 may be aligned and/or substantially concentric with a corresponding venturi 248. Additionally, nozzles 246 may include a first dimension, for example a first diameter at throat (see e.g., FIG. 6) that is smaller than a second dimension or diameter of each venturi 248 at the throat (see e.g., FIG. 6) of venturi 248. Additionally, each venturi 248 may also include a diffuser (see e.g., FIG. 6) having a third dimension or diameter (see e.g., FIG. 6) that may be larger or greater than first dimension or diameter of nozzles 246 and second dimension or diameter of venturi 248. The various features of nozzles 246 and venturi 248 of HGP component 200A may aid in the mixing of HPF and LPF, and substantially energize or increase the velocity of the LPF to

cool HGP component 200A during operation of turbine 28 of gas turbine system 10, as similarly discussed herein.

It is understood that HGP component 200B formed as inner platform of stator vane 40 may include similar features as HGP component 200A discussed herein with respect to FIGS. 14 and 15. More specifically, HGP component 200B of stator vane 40 may include a body including a plurality of surfaces, portions, fluid channels, nozzles, and venturi that may be substantially identical to that of HGP component 200A. However distinct from HGP component 200A, HGP component 200B may include a low pressure fluid channel (e.g., low pressure fluid channel 238) in direct fluid communication with area 52 positioned adjacent rotor 30 of turbine 28, and a high pressure fluid channel (e.g., high pressure fluid channel 260) in direct fluid communication with area 50 positioned adjacent rotor 30. As similarly discussed herein, area 52 may include LPF and area 50 may include HPF, which may be used to cool HGP component 200B during operation of turbine 28. In another non-limiting example (not shown), HPF and LPF may be supplied from areas 50, 52 positioned adjacent casing 36, and subsequently supplied to HGP component 200B via conduits formed through airfoil 46.

Similar to those non-limiting examples shown and discussed herein with respect FIGS. 10-13, features and/or components of HGP components 200A, 200B may be positioned in distinct portions and/or configured different than the non-limiting example shown in FIG. 15. For example, low pressure fluid channel 238 in fluid communication with low pressure supply conduit 208 may formed, positioned, and/or defined between top plate 259 and outer plate 234 including the plurality of nozzles 246. Additionally, high pressure fluid channel 260 in fluid communication with high pressure supply conduit 206 may be formed, positioned, and/or defined between outer plate 234 and intermediate plate 236 including the plurality of venturi 248. As similarly discussed herein with respect to FIGS. 12 and 13, LPF flowing through the plurality of nozzles 246 in HGP component 200A, 200B may flow into and mix with HPF flowing through the plurality of venturi 248, before flowing into cooling channel 242 and being discharged from HGP component 200A, 200B.

By utilizing support 102, 202 and HGP component 100, 200 as discussed herein with respect to FIGS. 2-15, turbine 28 of gas turbine system 10 may utilize both HPF and LPF found within turbine 28 to cool HGP component 100, 200. Additionally, the ratio of HPF and LPF that may be used to cool HGP component 100, 200 may include larger amounts of LPF than HPF.

Hot gas path (HGP) component 100, 200 and support 102, 202 (see, FIGS. 2-11, respectively) may be formed in a number of ways. In one embodiment, HGP component 100, 200 and support 102, 202 may be made by casting. However, as noted herein, additive manufacturing is particularly suited for manufacturing HGP component 100, 200 including unitary body 110 (and support 102, 202). As used herein, additive manufacturing (AM) may include any process of producing an object through the successive layering of material rather than the removal of material, which is the case with conventional processes. Additive manufacturing can create complex geometries without the use of any sort of tools, molds or fixtures, and with little or no waste material. Instead of machining components from solid billets of plastic or metal, much of which is cut away and discarded, the only material used in additive manufacturing is what is required to shape the part. Additive manufacturing processes may include but are not limited to: 3D printing, rapid

prototyping (RP), direct digital manufacturing (DDM), binder jetting, selective laser melting (SLM) and direct metal laser melting (DMLM). In the current setting, DMLM or SLM have been found advantageous.

To illustrate an example of an additive manufacturing process, FIG. 16 shows a schematic/block view of an illustrative computerized additive manufacturing system 900 for generating an object 902. In this example, system 900 is arranged for DMLM. It is understood that the general teachings of the disclosure are equally applicable to other forms of additive manufacturing. Object 902 is illustrated as HGP component 100 (see, FIGS. 2-13), but may also include HGP component 200 (see, FIGS. 14 and 15). AM system 900 generally includes a computerized additive manufacturing (AM) control system 904 and an AM printer 906. AM system 900, as will be described, executes code 920 that includes a set of computer-executable instructions defining HGP component 100 to physically generate the object 902 using AM printer 906. Each AM process may use different raw materials in the form of, for example, fine-grain powder, liquid (e.g., polymers), sheet, etc., a stock of which may be held in a chamber 910 of AM printer 906. In the instant case, HGP component 100 may be made of a metal or metal compound capable of withstanding the environment of gas turbine system 10 (see, FIG. 1). As illustrated, an applicator 912 may create a thin layer of raw material 914 spread out as the blank canvas from which each successive slice of the final object will be created. In other cases, applicator 912 may directly apply or print the next layer onto a previous layer as defined by code 920, e.g., where a metal binder jetting process is used. In the example shown, a laser or electron beam 916 fuses particles for each slice, as defined by code 920, but this may not be necessary where a quick setting liquid plastic/polymer is employed. Various parts of AM printer 906 may move to accommodate the addition of each new layer, e.g., a build platform 918 may lower and/or chamber 910 and/or applicator 912 may rise after each layer.

AM control system 904 is shown implemented on computer 930 as computer program code. To this extent, computer 930 is shown including a memory 932, a processor 934, an input/output (I/O) interface 936, and a bus 938. Further, computer 930 is shown in communication with an external I/O device/resource 940 and a storage system 942. In general, processor 934 executes computer program code, such as AM control system 904, that is stored in memory 932 and/or storage system 942 under instructions from code 920 representative of HGP component 100, described herein. While executing computer program code, processor 934 can read and/or write data to/from memory 932, storage system 942, I/O device 940 and/or AM printer 906. Bus 938 provides a communication link between each of the components in computer 930, and I/O device 940 can comprise any device that enables a user to interact with computer (e.g., keyboard, pointing device, display, etc.). Computer 930 is only representative of various possible combinations of hardware and software. For example, processor 934 may comprise a single processing unit, or be distributed across one or more processing units in one or more locations, e.g., on a client and server. Similarly, memory 932 and/or storage system 942 may reside at one or more physical locations. Memory 932 and/or storage system 942 can comprise any combination of various types of non-transitory computer readable storage medium including magnetic media, optical media, random access memory (RAM), read only memory (ROM), etc. Computer 930 can comprise any type of com-

puting device such as a network server, a desktop computer, a laptop, a handheld device, a mobile phone, a pager, a personal data assistant, etc.

Additive manufacturing processes begin with a non-transitory computer readable storage medium (e.g., memory 932, storage system 942, etc.) storing code 920 representative of HGP component 100. As noted, code 920 includes a set of computer-executable instructions defining outer electrode that can be used to physically generate the tip, upon execution of the code by system 900. For example, code 920 may include a precisely defined 3D model of HGP component 100 and can be generated from any of a large variety of well-known computer aided design (CAD) software systems such as AutoCAD®, TurboCAD®, DesignCAD 3D Max, etc. In this regard, code 920 can take any now known or later developed file format. For example, code 920 may be in the Standard Tessellation Language (STL) which was created for stereolithography CAD programs of 3D Systems, or an additive manufacturing file (AMF), which is an American Society of Mechanical Engineers (ASME) standard that is an extensible markup-language (XML) based format designed to allow any CAD software to describe the shape and composition of any three-dimensional object to be fabricated on any AM printer. Code 920 may be translated between different formats, converted into a set of data signals and transmitted, received as a set of data signals and converted to code, stored, etc., as necessary. Code 920 may be an input to system 900 and may come from a part designer, an intellectual property (IP) provider, a design company, the operator or owner of system 900, or from other sources. In any event, AM control system 904 executes code 920, dividing HGP component 100 into a series of thin slices that it assembles using AM printer 906 in successive layers of liquid, powder, sheet or other material. In the DMLM example, each layer is melted to the exact geometry defined by code 920 and fused to the preceding layer. Subsequently, the HGP component 100 may be exposed to any variety of finishing processes, e.g., those described herein for recontouring or other minor machining, sealing, polishing, etc. Technical effects of the disclosure include, e.g., providing a hot gas path component that includes a plurality venturi formed therein. The unitary body of the hot gas path component (formed using additive manufacturing) allows for the formation of various layers of venturi and the utilization of low pressure fluid in cooling the component. This results in a reduced amount of fluid required to cool the hot gas path component, which in turn reduces fuel consumption and/or heat rate within the turbine system.

The terminology used herein is for the purpose of describing particular embodiments only and is not intended to be limiting of the disclosure. As used herein, the singular forms “a”, “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. It will be further understood that the terms “comprises” and/or “comprising,” when used in this specification, specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. “Optional” or “optionally” means that the subsequently described event or circumstance may or may not occur, and that the description includes instances where the event occurs and instances where it does not.

Approximating language, as used herein throughout the specification and claims, may be applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is

related. Accordingly, a value modified by a term or terms, such as “about,” “approximately” and “substantially,” are not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value. Here and throughout the specification and claims, range limitations may be combined and/or interchanged, such ranges are identified and include all the sub-ranges contained therein unless context or language indicates otherwise. “Approximately” as applied to a particular value of a range applies to both values, and unless otherwise dependent on the precision of the instrument measuring the value, may indicate +/-10% of the stated value(s).

The corresponding structures, materials, acts, and equivalents of all means or step plus function elements in the claims below are intended to include any structure, material, or act for performing the function in combination with other claimed elements as specifically claimed. The description of the present disclosure has been presented for purposes of illustration and description, but is not intended to be exhaustive or limited to the disclosure in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art without departing from the scope and spirit of the disclosure. The embodiment was chosen and described in order to best explain the principles of the disclosure and the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

What is claimed is:

1. A hot gas path (HGP) component of a turbine system, the HGP component comprising:
 - a body including:
 - a forward end;
 - an aft end positioned opposite the forward end;
 - an inner portion positioned adjacent a hot gas flow path for the turbine system, the inner portion extending between the forward end and aft end;
 - an outer portion formed radially opposite the inner portion and extending between the forward end and aft end;
 - a plurality of nozzles extending through the outer portion;
 - an intermediate portion formed between the inner portion and the outer portion; and
 - a plurality of venturi extending through the intermediate portion, the plurality of venturi in fluid communication with the plurality of nozzles.
2. The HGP component of claim 1, wherein:
 - each of the plurality of nozzles include a first dimension; and
 - each of the plurality of venturi include a second dimension that is greater than the first dimension.
3. The HGP component of claim 2, wherein the body further includes:
 - a plurality of diffusers, each one of the plurality of diffusers formed integral with a corresponding venturi of the plurality of venturi, adjacent the inner portion of the body.
4. The HGP component of claim 3, wherein each of the plurality of diffusers includes a third dimension, the third dimension being greater than the second dimension of the plurality of venturi.
5. The HGP component of claim 1, wherein the body further includes:
 - a low pressure fluid channel formed between the intermediate portion and the outer portion, the low pressure

- fluid channel receiving a low pressure fluid and providing the low pressure fluid to the plurality of venturi; and
 - a cooling channel formed between the intermediate portion and the inner portion, the cooling channel receiving a high pressure fluid and the low pressure fluid.
6. The HGP component of claim 5, wherein the body further includes:
 - a high pressure fluid channel formed radially outward from the outer portion, the high pressure fluid channel receiving the high pressure fluid and providing the high pressure fluid to the plurality of nozzles.
 7. The HGP component of claim 1, wherein a section of each of the plurality of nozzles of the outer portion extends within a corresponding venturi of the intermediate portion.
 8. The HGP component of claim 1, wherein the body further includes:
 - a high pressure fluid channel formed between the intermediate portion and the outer portion, the high pressure fluid channel receiving a high pressure fluid and providing the high pressure fluid to the plurality of venturi; and
 - a cooling channel formed between the intermediate portion and the inner portion, the cooling channel receiving a low pressure fluid and the high pressure fluid.
 9. The HGP component of claim 8, wherein the body further includes:
 - a low pressure fluid channel formed radially outward from the outer portion, the low pressure fluid channel receiving the low pressure fluid and providing the low pressure fluid to the plurality of nozzles.
 10. A turbine system comprising:
 - a turbine casing;
 - a plurality of turbine blades positioned within the turbine casing and circumferentially about a rotor;
 - a plurality of supports circumferentially disposed around the turbine casing and positioned radially adjacent the plurality of turbine blades, each of the plurality of supports including:
 - at least one high pressure supply conduit in fluid communication with a high pressure fluid flowing adjacent to and upstream of the support; and
 - at least one low pressure supply conduit in fluid communication with a low pressure fluid flowing adjacent to and downstream of the support; and
 - a plurality of hot gas path (HGP) components coupled to the plurality of supports and extending radially between the plurality of supports and the plurality of turbine blades, each of the plurality of HGP components including:
 - a body including:
 - a forward end;
 - an aft end positioned opposite the forward end;
 - an inner portion positioned adjacent the plurality of turbine blades, the inner portion extending between the forward end and aft end;
 - an outer portion formed radially opposite the inner portion and extending between the forward end and aft end;
 - a plurality of nozzles extending through the outer portion; and
 - an intermediate portion formed between the inner portion and the outer portion; and
 - a plurality of venturi extending through the intermediate portion, the plurality of venturi in fluid communication with the plurality of nozzles.

31

- 11. The turbine system of claim 10, wherein each of the plurality of supports further includes:
 - a high pressure fluid chamber positioned radially adjacent the HGP component, the high pressure fluid chamber fluidly coupled to the at least one high pressure supply conduit to receive the high pressure fluid and provide the high pressure fluid to the HGP component.
- 12. The turbine system of claim 10, wherein the at least one high pressure supply conduit includes:
 - a plurality of high pressure supply conduits extending through the support, each of the plurality of high pressure supply conduits in fluid communication with the HGP component to supply the high pressure fluid to one of:
 - the plurality of nozzles of the HGP component, or
 - the plurality of venturi of the HGP component.
- 13. The turbine system of claim 10, wherein the body of each HGP component of the plurality of HGP components further includes a top plate formed above the outer portion, the top plate positioned radially inward from and contacting the support.
- 14. The turbine system of claim 13, wherein the body of each HGP component of the plurality of HGP components further includes:
 - a high pressure fluid channel formed between the outer portion and the top plate, the high pressure fluid channel fluidly coupled to the at least one high pressure supply conduit to receive the high pressure fluid from the at least one high pressure supply conduit and provide the high pressure fluid to the plurality of nozzles of the outer portion.
- 15. The turbine system of claim 13, wherein the body of each HGP component of the plurality of HGP components further includes:
 - a low pressure fluid channel formed between the outer portion and the top plate, the low pressure fluid channel fluidly coupled to the at least one low pressure supply conduit to receive the low pressure fluid from the at least one low pressure supply conduit and provide the low pressure fluid to the plurality of nozzles of the outer portion.
- 16. The turbine system of claim 10, wherein each of the plurality of supports further includes:
 - a low pressure fluid chamber positioned radially adjacent the HGP component, the low pressure fluid chamber fluidly coupled to the at least one low pressure supply conduit to provide the low pressure fluid to the HGP component.
- 17. The turbine system of claim 16, wherein each of the plurality of supports further includes:

32

- at least one low pressure inlet fluidly coupled to the low pressure fluid chamber, the at least one low pressure inlet receiving the low pressure fluid and providing the low pressure fluid to the low pressure fluid chamber.
- 18. The turbine system of claim 16, wherein the low pressure fluid chamber formed in the support is at least partially defined by the outer portion of the HGP component and is in direct fluid communication with each of the plurality of nozzles extending through the outer portion.
- 19. A turbine system comprising:
 - a turbine casing;
 - a plurality of supports circumferentially disposed around the turbine casing, each of the plurality of supports including:
 - at least one high pressure supply conduit in fluid communication with a high pressure fluid flowing adjacent to and downstream of the support; and
 - at least one low pressure supply conduit in fluid communication with a low pressure fluid flowing adjacent to and upstream of the support; and
 - a plurality of stator vanes coupled to the plurality supports, the plurality of stator vanes positioned circumferentially about the turbine casing, wherein each stator vane of the plurality of stator vanes includes:
 - an airfoil; and
 - a hot gas path (HGP) component coupled to the airfoil, the HGP component including:
 - a body including:
 - a forward end;
 - an aft end positioned opposite the forward end;
 - an inner portion positioned adjacent the plurality of turbine blades, the inner portion extending between the forward end and aft end;
 - an outer portion formed radially opposite the inner portion and extending between the forward end and aft end;
 - a plurality of nozzles extending through the outer portion; and
 - an intermediate portion formed between the inner portion and the outer portion; and
 - a plurality of venturi extending through the intermediate portion, the plurality of venturi in fluid communication with the plurality of nozzles.
- 20. The turbine system of claim 19, wherein the body of the HGP component further includes a top plate formed above the outer portion, the top plate positioned radially adjacent to and contacting the support.

* * * * *