

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
1 November 2007 (01.11.2007)

PCT

(10) International Publication Number
WO 2007/123308 A1


- (51) International Patent Classification:
A41G 5/00 (2006.01)
- (21) International Application Number:
PCT/KR2007/001553
- (22) International Filing Date: 30 March 2007 (30.03.2007)
- (25) Filing Language: Korean
- (26) Publication Language: English
- (30) Priority Data:
10-2006-0037425 26 April 2006 (26.04.2006) KR
- (71) Applicant (for all designated States except US): Joo San Co., Ltd [KR/KR]; 1505 Byuksan Digital Valley 5th, 60-73, Gasan-dong Geumcheon-gu, Seoul 153-801 (KR).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): CHANG, In-Young [KR/KR]; 1487-110, Seocho 3-dong Seocho-gu, Seoul 137-869 (KR).
- (74) Agent: HAM, Hyun-Kyung; 14F., Kukdong Building, 60-1, Chungmuro 3-ka, Chung-ku, Seoul 100-705 (KR).

- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: HAIR EXTENSION KIT AND EXTENSION-HAIR FIXING METHOD



(57) Abstract: A hair extension kit and an extension-hair fixing method are disclosed. The hair extension kit enables user's hair 12 to be coupled with extended hairs 1 and 1', and includes a fastening ring 2 formed in a hollow shape, each upper ends of the extended hairs 1 and 1' being attached to an inner peripheral surface of the fastening ring 2; a guiding loop 4 having a portion thereof received in the fastening ring 2 and a guiding and holding part 3 formed at the lower end thereof, the guiding loop 4 being removable from the fastening ring 2; and a drawing loop 10 having a portion thereof received between an inner wall of the fastening ring 2 and the corresponding part of the guiding loop 4 and a drawing and holding part 11 formed at the lower end thereof, the drawing loop 10 being removable from the fastening ring 2. The hair extension kit can increase the coupling force between the user's hair and the extension-hair by means of a fastening ring, thereby preventing the extension-hair from slipping down or falling out from the user's hair, even if a physical pull force is applied to the extension-hair or oil content of the user's hair is increased. Furthermore, it can conceal the outside of the fastening ring by winding the user's hair around the inner and outer peripheral surfaces of the fastening ring, thereby rendering a more natural hair style for the extension-hair and the user's hair.

WO 2007/123308 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

HAIR EXTENSION KIT AND EXTENSION-HAIR FIXING METHOD**Technical Field**

The present invention relates to a hair extension
5 kit and an extension-hair fixing method which can
replenish a thin haired human with hairs or rendering a
more natural hair style by making short hair long. More
particularly, the present invention relates to a hair
extension kit and an extension-hair fixing method which
10 can increase a coupling force between an extension-hair
and user's hair by inserting a guiding loop and a drawing
loop into a fastening ring with extended hairs attached
to the inner peripheral surface thereof (herein, an
assembly of the extended hair and the fastening ring is
15 referred to as extension-hair), winding the user's hair
around the fastening ring using the two loops, and then
compressing or bending the fastening ring, and further
preventing the extension-hair from slipping down or
falling out from the user's hair.

20

Background Art

Recently, as women have been interested in their
appearance and beauty, various accessories or stuffs are
being developed. Especially, in hairdressing and other
25 beauty treatment, hair styling showing individual
characters by changing a hair style and hair color, such
as hair dyeing, is widely used.

Particularly, in recent years, partial wigs using
original hair or synthetic hair are acquiring a greater
30 vogue than hairstyling or coloring, for instance, short
hair is made long utilizing various kinds of partial wigs,
or a bridge type partial wig is made utilizing a pre-

colored state of partial wigs.

As mentioned above, in case of making short hair long, an extension-hair made of human hair or synthetic hair is used. If it is desired to connect an extended
5 hair to a user's hair, a predetermined number of an extended hair are taken out from extended hairs stacked on a work table, an adhesive is applied to the end of the extended hair, and then the extended hair is attached to the end of hair desired to be connected, thereby the
10 user's hair and the extended hair is connected by the medium of the adhesive.

In that case, the adhesive melted by an intense heat is applied in overlapped part of the extended hair end and the user's hair end, and then as the adhesive
15 starts to be hardened, a hairdresser makes a roll of the adhesive directly with fingers to form it round and solidify it.

However, a technique of the typical extension-hair as above stated is a manner that a certain amount of the
20 extended hair is taken out of extended hairs stacked on the work table. Thus there are a lot of hairs dropping on the floor or falling around, so it is not economical. Moreover, also the number of the hairs is not in constant, this makes it difficult to expect a high quality of a
25 beauty state.

Especially, in a case that the user's hair and the extended hair are connected using a liquid adhesive injecting device, the applied amount of the liquid
adhesive is not constant, thus the size of the resulting
30 adhered part is not constant as well as the operation is so messy. Further, a technique of coating the liquid adhesive on the ends of the certain amount of the

extended hair needs an intense heat directly applied to the user's hair in order to melt the hardened adhesive when an adhered state of the user's hair and the extended hair is sometime to be released, so this may lead to the damage to the hair as well as the risk of burning. In addition, the melted adhesive flows down or makes the operation messy.

To overcome the above-described problem, the present applicant had registered an extension-hair in Korean Utility Model Registration No. 316019 and Korean Utility Model Registration No. 333865, which disclose an extension-hair which fastens user's hair and the extended hair each other by pressurizing a contraction tube or a connection ring after passing user's hair through the contraction tube or the connection ring, with a certain amount of extended hair being adhered in advance to the contraction tube or the connection tube or the like.

The extension-hair includes a hook loop or a guiding loop separately provided with, each of the loops is used so that the user's hair can pass easily through the contraction tube or the connection ring.

However, the aforementioned extension-hair has such a structure that the user's hair is inserted through the contraction tube or the connection ring. Thus, there is a problem that if the compression force is weak due to the contraction of the contraction tube or a bending and fastening force of the connection ring is weak, the extension-hair slips down or falls out from the user's hair.

Particularly, user's hair has a certain degree of oil content, thus the coupling force becomes weaker because the frictional force to an all kinds of hair is

reduced due to the oil content. Further, if a practitioner applies the extension-hair with a weak fastening force in the process of application of the extension-hair, the fastening force of the extension-hair
5 becomes more weakened.

Moreover, if a considerable pull force is applied to the extension-hair due to combing or an unexpected problem, there is a risk that the extension-hair with the weak fastening force may slip down or fall out from the
10 user's hair in most cases. Further, a customer who has paid a high price for the application of an extension-hair may feel quite unpleasant if even one extension-hair falls out from the user's hair.

15 **Disclosure**

Technical Problem

Therefore, the present invention has been made to solve the above-mentioned problems, and an object of the present invention is to provide a hair extension kit and
20 an extension-hair fixing method, which can increase a coupling force between user's hair and extension-hair through a fastening ring, thereby preventing the extension-hair from slipping down or falling out from the user's hair even if a physical pull force is applied
25 thereto or oil content of user's hair is increased.

Another object of the present invention is to provide a hair extension kit and an extension-hair fixing method, which can conceal the outer side of the fastening ring by winding the user's hair around the inner and
30 outer peripheral surfaces of the fastening ring, thereby rendering a more natural hair style with the extension-hair and the user's hair.

Technical Solution

In order to accomplish the above-mentioned objects, the present invention provides a hair extension kit enabling user's hair to be coupled with extended hairs, which includes a fastening ring formed in a hollow shape, each upper ends of the extended hairs being attached to the inner peripheral surface of the fastening ring; a guiding loop having a portion thereof received in the fastening ring and a guiding and holding part formed at the lower end thereof, the guiding loop being removable from the fastening ring; and a drawing loop having a portion thereof received between an inner wall of the fastening ring and the corresponding part of the guiding loop and a drawing and holding part formed at the lower end thereof, the drawing loop being removable from the fastening ring. Herein, an assembly of the extended hair and the fastening ring is referred to as "extension-hair".

In addition, the present invention provides the following detailed embodiments in conjunction with the above-mentioned embodiment.

According to an embodiment of the present invention, the fastening ring is deformable by an external force so as to increase the coupling force between the user's hair and the extended hair in a state that the guiding loop and the drawing loop are removed from the fastening ring, respectively.

According to the embodiment of the present invention, each of the lower portions of the guiding loop and the drawing loop is twisted with a predetermined number of windings.

In another aspect of the present invention, there

is provided an extension-hair fixing method, which comprises the steps of: inserting user's hair into a guiding loop, and drawing the user's hair downwardly through a fastening ring using a guiding and holding part
5 of the guiding loop; penetrating the user's hair through the drawing loop in order to allow the user's hair to wrap around an outer peripheral surface of the fastening ring using the guiding loop, and removing the guiding loop from the user's hair; and drawing down the user's
10 hair through the fastening ring using a drawing and holding part of the drawing loop, and removing the drawing loop from the user's hair.

In addition, the present invention further provides the following detailed embodiment in conjunction with the
15 above-mentioned embodiment.

According to an embodiment of the present invention, the extension-hair fixing method further comprises the step of deforming the fastening ring by an external force so as to increase the coupling force between the user's
20 hair and the extended hair.

Description of Drawings

The above objects, other features and advantages of the present invention will become more apparent by
25 describing the preferred embodiments thereof with reference to the accompanying drawings, in which:

FIG. 1 is a perspective view showing a schematic construction of a hair extension kit according to an exemplary embodiment of the present invention;

30 FIG. 2 is an enlarged sectional view showing the main parts of the hair extension kit according to the exemplary embodiment of the present invention;

FIGS. 3 to 7 are perspective views showing a used state of an hair extension kit according to the exemplary embodiment of present invention, wherein FIG. 3 is a perspective view of user's hair inserted into a loop portion of a guiding loop protruding above a fastening ring, FIG. 4 is a perspective view of the guiding loop and the user's hair drawn down the fastening ring, FIG. 5 is a perspective view of the drawn guiding loop and the user's hair inserted into a loop portion of a drawing loop, FIG. 6 is a perspective view of the drawing loop and the user's hair being drawn down the fastening ring when the guiding loop is removed, and FIG. 7 is a perspective view of the user's hair wound around the inner and outer peripheral surfaces of the fastening ring and the extended hair being fastened by the compression of the fastening ring;

FIG. 8 is a perspective view showing the extension-hair being applied to the user's hair using the hair extension kit according to the present invention; and

FIG. 9 is a perspective view showing a schematic construction of a hair extension kit according to another embodiment of the present invention, wherein each of the lower portions of the guiding loop and the drawing loop is twisted with a predetermined number of windings.

25

Best Mode

Hereinafter, preferred embodiments of the present invention will now be described in detail with reference to FIGS. 1, 2 and 9.

FIG. 1 is a perspective view showing a schematic construction of a hair extension kit according to an exemplary embodiment of the present invention, FIG. 2 is

30

an enlarged sectional view showing the main parts of the hair extension kit according to the exemplary embodiment of the present invention.

As shown in FIGS. 1 and 2, the hair extension kit according to the exemplary embodiment of the present invention largely includes a fastening ring 2 having a hollow shape, a guiding loop 4 and a drawing loop 10.

Herein, the fastening ring 2 is formed in a hollow shape capable of fastening extended hairs 1 and 1', and each upper ends of the extended hairs 1 and 1' are attached to the inner peripheral surface of the fastening ring 2. The fastening ring 2 serves to not only fasten the extended hairs 1 and 1' but also firmly couple the extended hairs 1 and 1' of the fastening ring 2 with user's hair 12 after inserting it into the user's hair 12 in the future.

The guiding loop 4 having a portion thereof received in the fastening ring 2, and a guiding and holding part 3 formed at lower end thereof, and removably inserted into the fastening ring 2. A loop-shaped upper portion of the guiding loop 4 is inserted through an inner part of the fastening ring 2 and protrudes towards an exterior thereof. The guiding loop 4 can be removed by drawing out the guiding and holding part 3 provided at lower end of the fastening ring 2. The guiding loop 4 also serves to allow the user's hair 12 to be drawn down through the inner part of the fastening ring 2 to the exterior thereof and then wound around the fastening ring 2.

The drawing loop 10 having a portion thereof received between an inner wall of the fastening ring 2 and the corresponding part of the guiding loop 4, and a

drawing and holding part 11 formed at lower end thereof, and removably inserted into the fastening ring 2. A loop-shaped upper portion of the drawing loop 10 is inserted through an inner part of the fastening ring 2 and protrudes towards an exterior thereof. The drawing loop 10 can be removed by drawing out the drawing and holding part 11 provided at lower end of the fastening ring 2. The drawing loop 10 also serves to allow the user's hair 12 inserted through the guiding loop 4 to be drawn down through the inner part of the fastening ring 2 downward.

Meanwhile, the fastening ring 2 is provided to be deformable by an external force so as to increase the coupling force between the user's hair 12 and the extended hairs 1 and 1' in a state that the guiding loop 4 and the drawing loop 10 are removed from the fastening ring 2, respectively.

It is preferable that the fastening ring 2 is made of materials capable of being readily deformed by a predetermined external force applied by practitioners, and then continuously maintaining such a deformed state. In a preferable embodiment, the fastening ring 2 may be made of metals such as aluminum, nickel, copper, and mixture thereof.

In addition, the fastening ring 2 can be provided in various forms such as circle, cylindrical, tetragonal, C shape, etc., in consideration of the variety of articles as well as the deformability of the fastening ring 2 due to the external force. It is preferred that the fastening ring 2 has a size of such an extent that it is not easily exposed to the outside when the application is finished. The fastening ring 2 may be made of metals having the same color sense as the actual color of the

extended hairs 1 and 1', or a coating layer or paint layer having the same color sense as the actual color of the extended hairs 1 and 1' may be formed on the surface of the fastening ring 2.

5 Meanwhile, each of the upper ends of the extended hairs 1 and 1' is attached to the inner peripheral surface of the fastening ring 2 by the medium of an adhesive or a separated attaching member (not shown). At this time, each of the upper ends of the extended hair 1
10 and 1' is preferably attached in such a manner that it protrudes slightly from the end of the fastening ring 2 to the exterior thereof so that it can prevent the user's hair 12 from being damaged by the end portion of the fastening ring 2.

15 Moreover, in the hair extension kit according to another embodiment of the present invention, each of the lower portions of the guiding loop 4 and the drawing loop 10, as shown in FIG. 9, may be twisted with the predetermined number of windings. In this case, the
20 guiding loop 4 and the drawing loop 10 become stiff by means of the corresponding twisted parts so as to continuously maintain the deformed state, thereby preventing the two loops 4 and 10 from being entangled with each other in advance.

25 Hereinafter, using the hair extension kit having the aforementioned construction, the procedure for coupling the fastening ring having the extended hairs attached thereto with the user's hair will now be described in detail with reference to FIGS. 1 to 8.

30 Firstly, a plurality of hair extension kits, in which each of the guiding loop 4 and the drawing loop 10 are inserted into the fastening ring 2 having the

extended hairs 1 and 1' made of a certain amount of human hair or synthetic hair are prepared (shown in FIGS. 1 and 2).

Next, in a state that a practitioner has put up the
5 corresponding hair extension kit above the user's head where it will be applied, after inserting a certain amount of the user's hair 12 into the guiding loop 4 of the hair extension kit, the guiding and holding part 3 of the guiding loop 4 is pulled down to the fastening ring 2
10 and then the user's hair 12 is drawn down through the fastening ring 2 (shown in FIGS. 3 and 4).

Next, the user's hair 12 is penetrated through the drawing loop 10 using the guiding loop 4 in such a manner that the user's hair 12 can be wrapped around an outer
15 peripheral surface of the fastening ring 2, and then the guiding loop 4 is removed from the user's hair 12 (shown in FIG. 5).

And then, after drawing down the user's hair 12 through the fastening ring 2 using the drawing and
20 holding part 11 of the drawing loop 10, the drawing loop 10 is removed from the user's hair 12 (shown in FIG. 6).

At this time, the user's hair 12 is wrapped around the inner and outer peripheral surfaces of the fastening ring 2, as shown in FIGS. 5 and 6, forming the user's
25 wound hair portion 12'.

And then, the fastening ring 2 is compressed and deformed using a tool such as a nipper and so on so as to increase the coupling force between the user's hair 12 and the extended hairs 1 and 1' (referring to FIG. 7).

30 Accordingly, the coupling state of the user's hair 12 and the extended hairs 1 and 1' can be firmly maintained even if a certain degree of oil content of the

user's hair 12 is increased or unexpected pulling force is applied to the extended hairs 1 and 1' because the user's hair 12 is wound around the inner and outer peripheral surface of the fastening ring 2 having the extended hairs 1 and 1' attached thereto and the fastening ring 2 is compressed and deformed by the external force.

Next, in the rest of user's hair 12 where the extension-hair will be applied, the coupling procedure is accomplished, as shown in FIG. 8, using the corresponding hair extension kit according to the aforementioned procedure, by allowing the fastening ring 2 having the extended hairs 1 and 1' attached thereto to be coupled with the corresponding user's hair 12 where the extension-hair will be applied in stages, respectively.

Meanwhile, after the application is finished, if user wishes to release the coupling state of the user's hair 12 and the fastening ring 2 having the extended hairs 1 and 1' attached thereto due to the user's hair 12 being sufficiently grown up, or user's demand during use, etc., the user might remove the fastening ring 2 from the user's hair 12 after compressing both longitudinal sides of the compressed fastening ring 2 using a tool such as a nipper and then makes a gap in middle portion thereof.

The forgoing embodiments are merely exemplary and are not to be construed as limiting the present invention. The present teachings can be readily applied to other types of apparatuses. The description of the present invention is intended to be illustrative, and not to limit the scope of the claims. Many alternatives, modifications, and variations will be apparent to those skilled in the art.

Industrial Applicability

As mentioned above, the present invention can increase the coupling force between the user's hair and the extension-hair by means of a fastening ring thereby preventing the extension-hair from slipping down or falling out from the user's hair, even if a physical pull force is applied to the extension-hair or oil content of user's hair is increased.

10 Furthermore, the present invention can conceal the outside of the fastening ring by winding the user's hair around the inner and outer peripheral surfaces of the fastening ring, thereby rendering a more natural hair style for the extension-hair and the user's hair.

CLAIMS

1. A hair extension kit enabling user's hair 12 to be coupled with extended hairs 1 and 1', the hair extension kit comprising:

5 a fastening ring 2 formed in a hollow shape, each upper ends of the extended hairs 1 and 1' being attached to an inner peripheral surface of the fastening ring 2;

a guiding loop 4 having a portion thereof received in the fastening ring 2 and a guiding and holding part 3
10 formed at the lower end thereof, the guiding loop 4 being removable from the fastening ring 2; and

a drawing loop 10 having a portion thereof received between an inner wall of the fastening ring 2 and the corresponding part of the guiding loop 4 and a drawing
15 and holding part 11 formed at the lower end thereof, the drawing loop 10 being removable from the fastening ring 2.

2. The hair extension kit as claimed in claim 1, wherein the fastening ring 2 is deformable by an external
20 force so as to increase the coupling force between the user's hair 12 and the extended hairs 1 and 1' in a state that the guiding loop 4 and the drawing loop 10 are removed from the fastening ring 2, respectively.

25 3. The hair extension kit as claimed in claim 1 or 2, wherein each of the lower portions of the guiding loop 4 and the drawing loop 10 is twisted with a predetermined number of windings.

30 4. An extension-hair fixing method, comprising the steps of:

inserting user's hair 12 into a guiding loop 4, and

drawing the user's hair 12 downwardly through a fastening ring 2 using a guiding and holding part 3 of the guiding loop 4;

5 penetrating the user's hair 12 through the drawing loop 10 in order to allow the user's hair 12 to wrap around an outer peripheral surface of the fastening ring 2 using the guiding loop 4, and removing the guiding loop 4 from the user's hair 12; and

10 drawing down the user's hair 12 through the fastening ring 2 using a drawing and holding part 11 of the drawing loop 10, and removing the drawing loop 10 from the user's hair 12.

5. The extension-hair fixing method as claimed in 15 claim 4, further comprising the step of deforming the fastening ring 2 by an external force so as to increase a coupling force between the user's hair 12 and the extended hairs 1 and 1'.

1/6

FIG. 1




FIG. 2





FIG. 3



3/6

FIG. 4





FIG. 5



4/6

FIG. 6




FIG. 7




FIG. 8





FIG. 9



INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR2007/001553**A. CLASSIFICATION OF SUBJECT MATTER***A41G 5/00(2006.01)i*

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 8 A41G

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Utility models and applications for Utility models since 1975
Japanese Utility models and application for Utility models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKIPASS(KIPO internal)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2005/0011530 A1 (CHANG, IN-YOUNG) 20 January 2005 See claims 1-5 and figures 1-6.	1-5
A	JP 2004-323985 A (INOUE, AKIRA) 18 November 2004 See abstract and figures 1-11.	1-5
A	KR 10-2005-0102981 A (BEAUTY KOREA CO., LTD) 27 October 2005 See abstract and figures 1-23.	1-5

 Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 APRIL 2007 (27.04.2007)

Date of mailing of the international search report

30 APRIL 2007 (30.04.2007)

Name and mailing address of the ISA/KR

Korean Intellectual Property Office
920 Dunsan-dong, Seo-gu, Daejeon 302-701,
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

LEE, Won Jae

Telephone No. 82-42-481-5620



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR2007/001553

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US20050011530 A1	20.01.2005	AU2003277722AA EP01651070A1 US2005011530AA US7032602BB W02005006898A1	04.02.2005 03.05.2006 20.01.2005 25.04.2006 27.01.2005
JP 2004-323985 A	18.11.2004	NONE	
KR 10-2005-0102981 A	27.10.2005	NONE	