



(12) **EUROPEAN PATENT APPLICATION**

(21) Application number : **95302084.9**

(51) Int. Cl.⁶ : **C11D 3/39, C11D 3/28**

(22) Date of filing : **29.03.95**

(30) Priority : **13.04.94 GB 9407629**
15.09.94 GB 9418580

(43) Date of publication of application :
15.11.95 Bulletin 95/46

(84) Designated Contracting States :
AT BE CH DE DK ES FR GB GR IE IT LI NL PT
SE

(71) Applicant : **THE PROCTER & GAMBLE**
COMPANY
One Procter & Gamble Plaza
Cincinnati, Ohio 45202 (US)

(72) Inventor : **MacBeath, Fiona Susan**
5 Cheswick Drive
Gosforth, Newcastle upon Tyne NE3 5DF (GB)
Inventor : **Knox, Rhona Alexandra**
34 Shaftesbury Grove
Heaton, Newcastle upon Tyne NE6 5JB (GB)

(74) Representative : **Gibson, Tony Nicholas et al**
Procter & Gamble Limited,
Whitley Road
Longbenton, Newcastle upon Tyne NE12 9TS
(GB)

(54) **Bleaching compositions.**

(57) There is provided a bleaching composition containing
(a) a non Mn(II) compound transition metal containing bleach catalyst ;
(b) an oxygen bleach ; and
(c) a corrosion inhibitor compound preferably selected from a paraffin oil and benzotriazole, and combinations thereof.

This invention relates to bleaching compositions containing an oxygen bleach, a transition metal containing bleach catalyst and a corrosion inhibitor compound preferably selected from benzotriazole and a paraffin oil.

The satisfactory removal of bleachable soils/stains such as tea, fruit juice and coloured vegetable soils from soiled/stained substrates is a particular challenge to the formulator of a detergent composition for use in a washing method such as a laundry or machine dishwashing method.

Traditionally, the removal of such bleachable soils/stains has been enabled by the use of bleach components such as oxygen bleaches, including hydrogen peroxide and organic peroxyacids. The organic peroxyacids are often obtained by the in situ perhydrolysis reaction between hydrogen peroxide and an organic peroxyacid bleach precursor.

A problem encountered with the use of peroxyacids in machine dishwashing methods is the tarnishing/corrosion of any silverware components of the washload. Oxygen bleaches tend to give rise to the problem of tarnishing more than chlorine bleaches. The level of tarnishing observed can range from slight discolouration of the silverware to the formation of a dense black coating on the surface of the silverware.

The detergent formulator thus faces the dual challenge of formulating a product which maximises bleachable soil/stain removal but minimises the occurrence of any unwelcome tarnishing effects of the bleach.

The occurrence of any unwelcome tarnishing effects arising from use of oxygen bleaches in a washing method can be related to the nature of the oxygen bleach, and also to both the rate of release of the oxygen bleach and the absolute level of bleach present in the wash solution. A fast rate of release of the bleach to the wash solution tends to exacerbate tarnishing problems, as does a high absolute level of the bleach in the wash solution.

The Applicants have also found that the occurrence of tarnishing is a particular problem when the composition contains, in addition to the oxygen bleach, a transition metal containing bleach catalyst, particularly an Mn(III) or Mn(IV) containing bleach catalyst.

It has been found that enhanced anti-silver tarnishing as well as good cleaning performance can be achieved through the combined use, as a corrosion inhibitor compound, of a paraffin oil, which acts as a silver coating agent, and preferably careful control of oxygen-bleaching power and control of the rate of release of the oxygen bleach.

The rate of release of oxygen bleach should be rapid enough to provide satisfactory cleaning, but not so rapid that tarnishing is enabled. It is the Applicant's belief that a sufficient time interval, prior to release of the oxygen bleach, is preferable to allow for an effective coating on the silverware to form. This coating protects the silver surface from the potential tarnishing effect of the oxygen bleach species.

It has also been found that enhanced anti-silver tarnishing as well as good cleaning performance can be achieved through the use of other corrosion inhibitor compounds, particularly benzotriazole in combination with an oxygen bleach.

The use of paraffin oil as a coating agent component of a silver tarnish inhibiting system for use in a machine dishwashing method has been described in the Applicant's copending PCT Applications No.s US-94/00355 and US-94/00570 and European Application No. 93201918.5, none of which disclose transition metal containing bleach catalysts.

European Patent Application EP-A-0 530 870 in the name of Unilever discloses machine dishwashing compositions containing a dinuclear manganese complex in which the manganese is in the III or IV oxidation state. No recognition is provided therein of the use of corrosion inhibitor compounds to inhibit silver tarnishing.

Summary of the Invention

According to the present invention there is provided a bleaching composition containing
(a) a transition metal containing bleach catalyst wherein said bleach catalyst is not an Mn(II) compound;
(b) an oxygen bleach; and
(c) a corrosion inhibitor compound

Preferably, the corrosion inhibitor compound is selected from a paraffin oil, benzotriazole any derivatives thereof, and preferably any mixtures thereof.

Preferably, a means is provided for controlling the rate of release of available oxygen such that, when using the method described in the present description, the available oxygen is completely released from the composition in a time interval of from 3.5 minutes to 10.0 minutes.

Preferably, the level of available oxygen in the present compositions, measured in units of % available oxygen by weight of the composition, should be from 0.3% to 1.7% measured according to the method described herein.

The transition metal bleach catalyst is preferably selected from the group consisting of $\text{Mn}^{\text{IV}}_2(\text{u-O})_3(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})_2(\text{PF}_6)_2$; $\text{Mn}^{\text{III}}_2(\text{u-O})_1(\text{u-OAc})_2(1,4,7\text{-tri-methyl-1,4,7-triazacyclononane})_2$ -

(ClO₄)₂; Mn^{IV}₄(u-O)₆(1,4,7-triazacyclononane)₄-(ClO₄)₂; Mn^{III}Mn^{IV}₄(u-O)₁(u-OAc)₂(1,4,7-tri-methyl-1,4,7-triazacyclononane)₂-(ClO₄)₃; Mn(1,4,7-trimethyl-1,4,7-triazacyclononane(OCH₃)₃-(PF₆); Co(2,2'-bispyridyl-amine)Cl₂; Di-(isothiocyanato)bispyridylamine-cobalt (II); trisdipridylamine-cobalt (II) perchlorate; Co(2,2-bispyridylamine)₂-O₂ClO₄; Bis-(2,2'-bispyridylamine) copper(II) per-chlorate; tris(di-2-pyridylamine) iron (II) perchlorate; Mn^{IV}(CF₃SO₃)₂; Co(NH₃)₅Cl; binuclear Mn complexed with tetra-N-dentate and bi-N-dentate ligands, including N₄Mn^{III}(u-O)₂Mn^{IV}N₄⁺ and [Bipy₂Mn^{III}(u-O)₂Mn^{IV}bipy₂](ClO₄)₃ and mixtures thereof.

Oxygen bleach

The detergent compositions of the invention contain as an essential component an oxygen bleach. The oxygen bleach may be hydrogen peroxide or a source thereof, an organic peroxyacid or a source thereof, such as a peroxyacid bleach precursor compound.

Where the organic peroxyacid source is a peroxyacid bleach precursor compound, the production of the peroxyacid occurs by an in situ reaction of the precursor with a source of hydrogen peroxide. Suitable sources of hydrogen peroxide include inorganic perhydrate bleaches.

Peroxyacid bleach precursors

Peroxyacid bleach precursors (bleach activators) are preferred peroxyacid sources herein. Peroxyacid bleach precursors are normally incorporated at a level of from 1% to 20% by weight, more preferably from 2% to 5% by weight, most preferably from 3% to 10% by weight of the compositions.

Suitable peroxyacid bleach precursors typically contain one or more N- or O- acyl groups, which precursors can be selected from a wide range of classes. Suitable classes include anhydrides, esters, imides and acylated derivatives of imidazoles and oximes, and examples of useful materials within these classes are disclosed in GB-A-1586789.

Suitable esters are disclosed in GB-A-836988, 864798, 1147871, 2143231 and EP-A-0170386. The acylation products of sorbitol, glucose and all saccharides with benzoylating agents and acetylating agents are also suitable.

Specific O-acylated precursor compounds include 2,3,3-tri-methyl hexanoyl oxybenzene sulfonates, benzoyl oxybenzene sulfonates, nonanoyl-6-amino caproyl oxybenzene sulfonates, monobenzoyltetraacetyl glucose, benzoyl peroxide and cationic derivatives of any of the above, including the alkyl ammonium derivatives and pentaacetyl glucose. Phthalic anhydride is a suitable anhydride type precursor.


Specific cationic derivatives of the O-acyl precursor compounds include 2-(N,N,N-trimethyl ammonium) ethyl sodium 4-sulphophenyl carbonate chloride, and any of the alkyl ammonium derivatives of the benzoyl oxybenzene sulfonates including the 4-(trimethyl ammonium) methyl derivative.

Useful N-acyl compounds are disclosed in GB-A-855735, 907356 and GB-A-1246338.

Preferred precursor compounds of the imide type include N-benzoyl succinimide, tetrabenzoyl ethylene diamine, N-benzoyl substituted ureas and the N,N,N',N' tetra acetylated alkylene diamines wherein the alkylene group contains from 1 to 6 carbon atoms, particularly those compounds in which the alkylene group contains 1, 2 and 6 carbon atoms. Tetraacetyl ethylene diamine (TAED) is particularly preferred.

N-acylated precursor compounds of the lactam class are disclosed generally in GB-A-855735. Whilst the broadest aspect of the invention contemplates the use of any lactam useful as a peroxyacid precursor, preferred materials comprise the caprolactams and valerolactams.

Suitable N-acylated lactam precursors have the formula:



wherein n is from 0 to about 8, preferably from 0 to about 2, and R⁶ is H, an alkyl, aryl, alkoxyaryl or alkaryl group containing from 1 to 12 carbons, or a substituted phenyl group containing from 6 to 18 carbon atoms

Suitable caprolactam bleach precursors are of the formula:



15

20



30

35

40

45


50

55

olactam, 2,4-dichlorobenzoyl valerolactam, terephthaloyl divalerolactam, 4-nitrobenzoyl caprolactam, 4-nitrobenzoyl valerolactam, and mixtures thereof.

Suitable imidazoles include N-benzoyl imidazole and N-benzoyl benzimidazole and other useful N-acyl group-containing peroxyacid precursors include N-benzoyl pyrrolidone, dibenzoyl taurine and benzoyl pyroglutamic acid.




Another preferred class of peroxyacid bleach activator compounds are the amide substituted compounds of the following general formulae:




wherein R¹ is an aryl or alkaryl group with from about 1 to about 14 carbon atoms, R² is an alkylene, arylene, and alkylene group containing from about 1 to 14 carbon atoms, and R⁵ is H or an alkyl, aryl, or alkaryl group containing 1 to 10 carbon atoms and L can be essentially any leaving group. R¹ preferably contains from about 6 to 12 carbon atoms. R² preferably contains from about 4 to 8 carbon atoms. R¹ may be straight chain or branched alkyl, substituted aryl or alkylaryl containing branching, substitution, or both and may be sourced from either synthetic sources or natural sources including for example, tallow fat. Analogous structural variations are permissible for R². The substitution can include alkyl, aryl, halogen, nitrogen, sulphur and other typical substituent groups or organic compounds. R⁵ is preferably H or methyl. R¹ and R⁵ should not contain more than 18 carbon atoms in total. Amide substituted bleach activator compounds of this type are described in EP-A-0170386.

The L group must be sufficiently reactive for the reaction to occur within the optimum time frame (e.g., a wash cycle). However, if L is too reactive, this activator will be difficult to stabilize for use in a bleaching composition. These characteristics are generally paralleled by the pKa of the conjugate acid of the leaving group, although exceptions to this convention are known. Ordinarily, leaving groups that exhibit such behavior are those in which their conjugate acid has a pKa in the range of from about 4 to about 13, preferably from about 6 to about 11 and most preferably from about 8 to about 11.

Preferred bleach precursors are those wherein R¹, R² and R⁵ are as defined for the amide substituted compounds and L is selected from the group consisting of:





and mixtures thereof, wherein R¹ is an alkyl, aryl, or alkaryl group containing from about 1 to about 14 carbon atoms, R³ is an alkyl chain containing from 1 to about 8 carbon atoms, R⁴ is H or R³, and Y is H or a solubilizing group.


20 The preferred solubilizing groups are -SO₃⁻M⁺, -CO₂⁻M⁺, -SO₄⁻M⁺, -N⁺(R³)₄X⁻ and O<-N(R³)₃ and most preferably -SO₃⁻M⁺ and -CO₂⁻M⁺ wherein R³ is an alkyl chain containing from about 1 to about 4 carbon atoms, M is a cation which provides solubility to the bleach activator and X is an anion which provides solubility to the bleach activator. Preferably, M is an alkali metal, ammonium or substituted ammonium cation, with sodium and potassium being most preferred, and X is a halide, hydroxide, methylsulfate or acetate anion. It should be noted that bleach activators with a leaving group that does not contain a solubilizing groups should be well dispersed in the bleaching solution in order to assist in their dissolution.

Preferred examples of bleach activators of the above formulae include (6-octanamidocaproyl)oxybenzenesulfonate, (6-nonanamidocaproyl)oxybenzenesulfonate, (6-decanamidocaproyl)oxybenzenesulfonate, and mixtures thereof.

30 Other preferred precursor compounds include those of the benzoxazin-type, having the formula:




40 including the substituted benzoxazins of the type



wherein R₁ is H, alkyl, alkaryl, aryl, arylalkyl, and wherein R₂, R₃, R₄, and R₅ may be the same or different substituents selected from H, halogen, alkyl, alkenyl, aryl, hydroxyl, alkoxyl, amino, alkyl amino, COOR₆ (wherein R₆ is H or an alkyl group) and carbonyl functions.

55 An especially preferred precursor of the benzoxazin-type is:



Cationic peroxyacid precursors


Cationic peroxyacid precursor compounds are also suitable herein. Typically such cationic peroxyacid precursors are formed by substituting the peroxyacid part with an ammonium or alkyl ammonium group, preferably an ethyl or methyl ammonium group.

Cationic peroxyacid precursors are described in U.S. Patents 4,904,406; 4,751,015; 4,988,451; 4,397,757; 5,269,962; 5,127,852; 5,093,022; 5,106,528; U.K. 1,382,594; EP 475,512, 458,396 and 284,292; and in JP 87-318,332.

Examples of preferred cationic peroxyacid precursors are described in UK Patent Application No. 9407944.9 and copending US Patent Applications having the Procter & Gamble attorneys' docket No's 5410, 5411, 5412 and 5413.


Suitable cationic peroxyacid precursors include any of the ammonium or alkyl ammonium substituted alkyl or benzoyl oxybenzene sulfonates, N-acylated caprolactams, and monobenzoyltetraacetyl glucose benzoyl peroxides.

A preferred cationically substituted benzoyl oxybenzene sulfonate is the 4-(trimethyl ammonium) methyl derivative of benzoyl oxybenzene sulfonate:




A preferred cationically substituted alkyl oxybenzene sulfonate is the methyl ammonium derivative of 2,3,3-trimethyl hexanoyloxybenzene sulfonate.

Preferred cationic peroxyacid precursors of the N-acylated caprolactam class include the trialkyl ammonium methylene benzoyl caprolactams, particularly trimethyl ammonium methylene benzoyl caprolactam:




Another preferred cationic peroxyacid precursor is 2-(N,N,N-trimethyl ammonium) ethyl sodium 4-sulphophenyl carbonate chloride.

Also preferred is trimethyl ammonium methylene meta chloro xlenol:




Betaine ester trimethyl ammonium meta chloro xylenol is also preferred:



Organic peroxyacids

The detergent compositions may also contain organic peroxyacids typically at a level of from 0.5% to 15% by weight, more preferably from 1% to 10% by weight of the composition.

A preferred class of organic peroxyacid compounds are the amide substituted compounds of the following general formulae:



wherein R¹ is an aryl or alkaryl group with from about 1 to about 14 carbon atoms, R² is an alkylene, arylene, and alkarylene group containing from about 1 to 14 carbon atoms, and R⁵ is H or an alkyl, aryl, or alkaryl group containing 1 to 10 carbon atoms. R¹ preferably contains from about 6 to 12 carbon atoms. R² preferably contains from about 4 to 8 carbon atoms. R¹ may be straight chain or branched alkyl, substituted aryl or alkaryl containing branching, substitution, or both and may be sourced from either synthetic sources or natural sources including for example, tallow fat. Analogous structural variations are permissible for R². The substitution can include alkyl, aryl, halogen, nitrogen, sulphur and other typical substituent groups or organic compounds. R⁵ is preferably H or methyl. R¹ and R⁵ should not contain more than 18 carbon atoms in total. Amide substituted organic peroxyacid compounds of this type are described in EP-A-0170386.

Other organic peroxyacids include diperoxy dodecanedioic acid, diperoxy tetra decanedioc acid, diperoxy hexadecanedioc acid, mono- and diperazelaic acid, mono- and diperbrassylic acid, monoperoxy phthalic acid, perbenzoic acid, and their salts as disclosed in, for example, EP-A-0341 947.

Inorganic perhydrate bleaches

The compositions in accord with the invention preferably include, as a hydrogen peroxide source, an inorganic perhydrate salt, most especially when the organic peroxyacid source is a peroxyacid bleach precursor compound.

The inorganic perhydrate salts are normally incorporated in the form of the sodium salt at a level of from 1% to 40% by weight, more preferably from 2% to 30% by weight and most preferably from 5% to 25% by weight of the compositions.

Examples of inorganic perhydrate salts include perborate, percarbonate, perphosphate, persulfate and

persilicate salts. The inorganic perhydrate salts are normally the alkali metal salts. The inorganic perhydrate salt may be included as the crystalline solid without additional protection. For certain perhydrate salts however, the preferred executions of such granular compositions utilize a coated form of the material which provides better storage stability for the perhydrate salt in the granular product.

5 Sodium perborate can be in the form of the monohydrate of nominal formula $\text{NaBO}_2\text{H}_2\text{O}_2$ or the tetrahydrate $\text{NaBO}_2\text{H}_2\text{O}_2 \cdot 3\text{H}_2\text{O}$.

Sodium percarbonate, which is a preferred perhydrate for inclusion in detergent compositions in accordance with the invention, is an addition compound having a formula typically corresponding to $2\text{Na}_2\text{CO}_3 \cdot 3\text{H}_2\text{O}_2$, and is available commercially as a crystalline solid. The percarbonate is most preferably incorporated into such compositions in a coated form which provides in product stability.

10 A suitable coating material providing in product stability comprises mixed salt of a water soluble alkali metal sulphate and carbonate. Such coatings together with coating processes have previously been described in GB-1,466,799, granted to Interlox on 9th March 1977. The weight ratio of the mixed salt coating material to percarbonate lies in the range from 1 : 200 to 1 : 4, more preferably from 1 : 99 to 1 : 9, and most preferably from 1 : 49 to 1 : 19. Preferably, the mixed salt is of sodium sulphate and sodium carbonate which has the general formula $\text{Na}_2\text{SO}_4 \cdot n \cdot \text{Na}_2\text{CO}_3$ wherein n is from 0.1 to 3, preferably n is from 0.3 to 1.0 and most preferably n is from 0.2 to 0.5.

Potassium peroxymonopersulfate is another inorganic perhydrate salt of use in the detergent compositions herein.

20

Bleach catalyst

The compositions contain a transition metal containing bleach catalyst.

25 Herein, the term transition metal bleach catalyst, henceforth 'bleach catalyst', excludes Mn(II) compounds, such as Mn(II) salts and complexes, certain of which have been shown to lead to a reduction in the propensity to cause silver tarnishing.

The bleach catalyst is used in a catalytically effective amount in the compositions and processes herein. By "catalytically effective amount" is meant an amount which is sufficient, under whatever comparative test conditions are employed, to enhance bleaching and removal of the stain or stains of interest from the target substrate. For automatic dishwashing, the target substrate may be, for example, a porcelain cup or plate with tea stain or a polyethylene plate stained with tomato soup. The test conditions will vary, depending on the type of washing appliance used and the habits of the user. Some users elect to use very hot water; others use warm or even cold water in machine dishwashing operations. Of course, the catalytic performance of the bleach catalyst will be affected by such considerations, and the levels of bleach catalyst used in fully-formulated detergent and bleach compositions can be appropriately adjusted. As a practical matter, and not by way of limitation, the compositions and processes herein can be adjusted to provide on the order of at least one part per ten million of the active bleach catalyst species in the aqueous washing liquor, and will preferably provide from about 1 ppm to about 200 ppm of the catalyst species in the wash liquor. To illustrate this point further, on the order of 3 micromolar manganese catalyst is effective at 40°C, pH 10 under European conditions using perborate and a bleach precursor (e.g., benzoyl caprolactam). An increase in concentration of 3-5 fold may be required under U.S. conditions to achieve the same results. Conversely, use of a bleach precursor and the manganese catalyst with perborate may allow the formulator to achieve equivalent bleaching at lower perborate usage levels than products without the manganese catalyst.

The bleach catalyst material herein can comprise the free acid or be in the form of any suitable salts.

45 One type of bleach catalyst is a catalyst system comprising a heavy metal cation of defined bleach catalytic activity, such as copper, iron or manganese III or IV cations, an auxiliary metal cation having little or no bleach catalytic activity, such as zinc or aluminum cations, and a sequestrant having defined stability constants for the catalytic and auxiliary metal cations, particularly ethylenediaminetetraacetic acid, ethylenediaminetetra(methylenephosphonic acid) and water-soluble salts thereof.

50 Other types of bleach catalysts include the manganese-based complexes disclosed in U.S. Pat. 5,246,621 and U.S. Pat. 5,244,594. Preferred examples of these catalysts include $\text{Mn}^{\text{IV}}_2(\text{u-O})_3(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})_2(\text{PF}_6)_2$, $\text{Mn}^{\text{III}}_2(\text{u-O})_1(\text{u-OAc})_2(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})_2(\text{ClO}_4)_2$, $\text{Mn}^{\text{IV}}_4(\text{u-O})_6(1,4,7\text{-triazacyclononane})_4(\text{ClO}_4)_2$, $\text{Mn}^{\text{III}}\text{Mn}^{\text{IV}}_4(\text{u-O})_1(\text{u-OAc})_2(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})_2(\text{ClO}_4)_3$, and mixtures thereof. Others are described in European patent application publication no. 549,272.


55 Other ligands suitable for use herein include 1,5,9-trimethyl-1,5,9-triazacyclododecane, 2-methyl-1,4,7-triazacyclononane, 2-methyl-1,4,7-triazacyclononane, 1,2,4,7-tetramethyl-1,4,7-triazacyclononane, and mixtures thereof.

The bleach catalysts useful in the compositions herein may also be selected as appropriate for the present

invention. For examples of suitable bleach catalysts see U.S. Pat. 5,227,084. See also U.S. Pat. 5,194,416 which teaches mononuclear manganese (IV) complexes such as $\text{Mn}(1,4,7\text{-trimethyl-1,4,7-triazacyclononane})(\text{OCH}_3)_3(\text{PF}_6)$.

Still another type of bleach catalyst, as disclosed in U.S. Pat. 5,114,606, is a water-soluble complex of manganese (III), and/or (IV) with a ligand which is a non-carboxylate polyhydroxy compound having at least three consecutive C-OH groups. Preferred ligands include sorbitol, iditol, dulcitol, mannitol, xylitol, arabitol, adonitol, meso-erythritol, mesoinositol, lactose, and mixtures thereof.

U.S. Pat. 5,114,611 teaches a bleach catalyst comprising a complex of transition metals, including Mn, Co, Fe, or Cu, with an non-(macro)-cyclic ligand. Said ligands are of the formula:



wherein R^1 , R^2 , R^3 , and R^4 can each be selected from H, substituted alkyl and aryl groups such that each $\text{R}^1\text{-N}=\text{C}-\text{R}^2$ and $\text{R}^3\text{-C}=\text{N}-\text{R}^4$ form a five or six-membered ring. Said ring can further be substituted. B is a bridging group selected from O, S, CR^5R^6 , NR^7 and $\text{C}=\text{O}$, wherein R^5 , R^6 , and R^7 can each be H, alkyl, or aryl groups, including substituted or unsubstituted groups. Preferred ligands include pyridine, pyridazine, pyrimidine, pyrazine, imidazole, pyrazole, and triazole rings. Optionally, said rings may be substituted with substituents such as alkyl, aryl, alkoxy, halide, and nitro. Particularly preferred is the ligand 2,2'-bispyridylamine. Preferred bleach catalysts include Co, Cu, Mn, Fe, -bispyridylmethane and -bispyridylamine complexes. Highly preferred catalysts include $\text{Co}(2,2'\text{-bispyridylamine})\text{Cl}_2$, $\text{Di}(\text{isothiocyanato})\text{bispyridylamine-cobalt (II)}$, $\text{tris}(\text{dipyridylamine-cobalt(II) perchlorate})$, $\text{Co}(2,2'\text{-bispyridylamine})_2\text{O}_2\text{ClO}_4$, $\text{Bis}(2,2'\text{-bispyridylamine})\text{copper(II) perchlorate}$, $\text{tris}(\text{di-2-pyridylamine})\text{iron(II) perchlorate}$, and mixtures thereof.

Other examples include binuclear Mn complexed with tetra-N-dentate and bi-N-dentate ligands, including $\text{N}_4\text{Mn}^{\text{III}}(\text{u-O})_2\text{Mn}^{\text{IV}}\text{N}_4)^+$ and $[\text{Bipy}_2\text{Mn}^{\text{III}}(\text{u-O})_2\text{Mn}^{\text{IV}}\text{bipy}_2](\text{ClO}_4)_3$.

Corrosion inhibitor

The compositions contain a corrosion inhibitor which is preferably incorporated at a level of from 0.05% to 10%, preferably from 0.1% to 5% by weight of the total composition.

A preferred corrosion inhibitor herein is benzotriazole and any derivatives thereof.

Another highly preferred corrosion inhibitor is a paraffin oil, typically a predominantly branched aliphatic hydrocarbon having a number of carbon atoms in the range of from 20 to 50; preferred paraffin oil selected from predominantly branched C_{25-45} species with a ratio of cyclic to noncyclic hydrocarbons of from 1:10 to 2:1, preferably from 1:5 to 1:1. A paraffin oil meeting these characteristics, having a ratio of cyclic to noncyclic hydrocarbons of about 32:68, is sold by Wintershall, Salzbergen, Germany, under the trade name WINOG 70.

In a highly preferred aspect, the corrosion inhibitor comprises a mixture of a paraffin oil and benzotriazole.

Other suitable corrosion inhibitor compounds include, mercaptans and diols, especially mercaptans with 4 to 20 carbon atoms including lauryl mercaptan, thiophenol, thionaphthol, thionalide and thioanthranol. Phosphonated octa-decane and other anti-oxidants such as betahydroxytoluene (BHT) are also suitable. Nitrogen-containing compounds such as amines, especially distearylamine and ammonium compounds such as ammonium chloride, ammonium bromide, ammonium sulphate or diammonium hydrogen citrate are also suitable.

Total Available Oxygen (AvO) Level

Preferably, the level of available oxygen in the present compositions, measured in units of % available oxygen by weight of the composition, should be carefully controlled; the level of available oxygen should thus preferably be in the range 0.3% to 2.5%, preferably 0.5% to 1.5%, more preferably 0.6% to 1.2%, measured according to the method described hereunder.

Controlled rate of release of bleach

The rate of release of available oxygen is preferably also controlled; the rate of release of available oxygen from the compositions herein should preferably be such that, when using the method described hereinafter,

the available oxygen is not completely released from the composition until after 3.5 minutes, preferably the available oxygen is released in a time interval of from 3.5 minutes to 10.0 minutes, more preferably from 4.0 minutes to 9.0 minutes, most preferably from 5.0 minutes to 8.5 minutes.

5 Controlled rate of release - means

The means may provide for controlled release of available oxygen to the wash solution. Such means could, for example, include delaying release of the hydrogen peroxide source to the wash solution, by for example, delaying release of any inorganic perhydrate salt, acting as a hydrogen peroxide source, to the wash solution.

10 The controlled release means can include coating any suitable component with a coating designed to provide the controlled release. The coating may therefore, for example, comprise a poorly water soluble material, or be a coating of sufficient thickness that the kinetics of dissolution of the thick coating provide the controlled rate of release.

The coating material may be applied using various methods. Any coating material is typically present at a weight ratio of coating material to bleach of from 1:99 to 1:2, preferably from 1:49 to 1:9.

Suitable coating materials can comprise the alkali and alkaline earth metal sulphates, silicates and carbonates, including calcium carbonate.

A preferred coating material is sodium silicate of $\text{SiO}_2 : \text{Na}_2\text{O}$ ratio from 1.6 : 1 to 3.4 : 1, preferably 2.8 : 1, applied as an aqueous solution to give a level of from 2% to 10%, (normally from 3% to 5%) of silicate solids by weight of the oxygen bleaching species. Magnesium silicate can also be included in the coating.

One method for applying the coating material involves agglomeration. Preferred agglomeration processes include the use of an organic binder material. Any conventional agglomerator/mixer may be used including, but not limited to pan, rotary drum and vertical blender types. Molten coating compositions may also be applied either by being poured onto, or spray atomized onto a moving bed of bleaching agent.

25 Other means of providing the required controlled release include mechanical means for altering the physical characteristics of the bleach to control its solubility and rate of release. Suitable protocols could include compaction, mechanical injection, manual injection, and adjustment of the solubility of the bleach compound by selection of particle size of any particulate component.

Whilst the choice of particle size will depend both on the composition of the particulate component, and the desire to meet the desired controlled release kinetics, it is desirable that the particle size should be more than 500 micrometers, preferably having an average particle diameter of from 800 to 1200 micrometers.

Additional protocols for providing the means of controlled release include the suitable choice of any other components of the detergent composition matrix such that when the composition is introduced to the wash solution the ionic strength environment therein provided enables the required controlled release kinetics to be achieved.

Controlled rate of release- test method

The rate of release of AvO can be measured according to the method now described:

- 40 1. A beaker of water (typically 2 litre) is placed on a stirrer Hotplate, and the stirrer speed is selected to ensure that the product is evenly dispersed through the solution.
2. The detergent composition (typically 8g of product which has been sampled down from a bulk supply using a Pascal sampler), is added and simultaneously a stop clock is started.
- 45 3. The temperature control should be adjusted so as to maintain a constant temperature of 20°C throughout the experiment.
4. Samples are taken from the detergent solution at 2 minute time intervals for 20 mins, starting after 1 minute, and are titrated by the "titration procedure" described below to determine the level of available oxygen at each point.

50 Titration Procedure

1. An aliquot from the detergent solution (above) and 2ml sulphuric acid are added into a stirred beaker
2. Approximately 0.2g ammonium molybdate catalyst (tetra hydrate form) are added
3. 3mls of 10% sodium iodide solution are added
- 55 4. Titration with sodium thiosulphate is conducted until the end point. The end point can be seen using either of two procedures. First procedure consists simply in seeing the yellow iodine colour fading to clear. The second and preferred procedure consists of adding soluble starch when the yellow colour is becoming faint, turning the solution blue. More thiosulphate is added until the end point is reached (blue starch com-

plex is decolourised).

The level of AvO, measured in units of % available oxygen by weight, for the sample at each time interval corresponds to the amount of titre according to the following equation

$$\frac{\text{VolS}_2\text{O}_3(\text{ml}) \times \text{Molarity}(\text{S}_2\text{O}_3) \times 8}{\text{Sample mass (g)}}$$

AvO level is plotted graphically versus time to enable the maximum level of AvO and the time to achieve that maximum level to be determined.

Additional detergent components

The detergent compositions of the invention may also contain additional detergent components. The precise nature of these additional components, and levels of incorporation thereof will depend on the physical form of the composition, and the nature of the cleaning operation for which it is to be used.

When formulated as compositions suitable for use in a machine washing method, eg: machine dishwashing methods, the compositions of the invention preferably contain one or more additional detergent components selected from surfactants, water-insoluble builders, organic polymeric compounds, additional enzymes, suds suppressors, lime soap dispersants, soil suspension and anti-redeposition agents and corrosion inhibitors.

Surfactant

The detergent compositions of the invention may contain as an additional detergent component a surfactant selected from anionic, cationic, nonionic ampholytic, amphoteric and zwitterionic surfactants and mixtures thereof.

The surfactant is typically present at a level of from 0.1 % to 60% by weight. More preferred levels of incorporation of surfactant are from 1% to 35% by weight, most preferably from 1% to 20% by weight.

The surfactant is preferably formulated to be compatible with any enzyme components present in the composition. In liquid or gel compositions the surfactant is most preferably formulated such that it promotes, or at least does not degrade, the stability of any enzyme in these compositions.

A typical listing of anionic, nonionic, ampholytic, and zwitterionic classes, and species of these surfactants, is given in U.S.P. 3,929,678 issued to Laughlin and Heuring on December 30, 1975. Further examples are given in "Surface Active Agents and Detergents" (Vol. I and II by Schwartz, Perry and Berch). A list of suitable cationic surfactants is given in U.S.P. 4,259,217 issued to Murphy on March 31, 1981.

Where present, ampholytic, amphoteric and zwitterionic surfactants are generally used in combination with one or more anionic and/or nonionic surfactants.

Anionic surfactant

Essentially any anionic surfactants useful for deterative purposes can be included in the compositions. These can include salts (including, for example, sodium, potassium, ammonium, and substituted ammonium salts such as mono-, di- and triethanolamine salts) of the anionic sulfate, sulfonate, carboxylate and sarcosinate surfactants.

Other anionic surfactants include the isethionates such as the acyl isethionates, N-acyl taurates, fatty acid amides of methyl tauride, alkyl succinates and sulfosuccinates, monoesters of sulfosuccinate (especially saturated and unsaturated C₁₂-C₁₈ monoesters) diesters of sulfosuccinate (especially saturated and unsaturated C₆-C₁₄ diesters), N-acyl sarcosinates. Resin acids and hydrogenated resin acids are also suitable, such as rosin, hydrogenated rosin, and resin acids and hydrogenated resin acids present in or derived from tallow oil.

Anionic sulfate surfactant

Anionic sulfate surfactants suitable for use herein include the linear and branched primary alkyl sulfates, alkyl ethoxysulfates, fatty oleyl glycerol sulfates, alkyl phenol ethylene oxide ether sulfates, the C₅-C₁₇ acyl-N-(C₁-C₄ alkyl) and -N-(C₁-C₂ hydroxyalkyl) glucamine sulfates, and sulfates of alkylpolysaccharides such as the sulfates of alkylpolyglucoside (the nonionic nonsulfated compounds being described herein).

Alkyl ethoxysulfate surfactants are preferably selected from the group consisting of the C₆-C₁₈ alkyl sulfates which have been ethoxylated with from about 0.5 to about 20 moles of ethylene oxide per molecule. More preferably, the alkyl ethoxysulfate surfactant is a C₆-C₁₈ alkyl sulfate which has been ethoxylated with from about 0.5 to about 20, preferably from about 0.5 to about 5, moles of ethylene oxide per molecule.

Anionic sulfonate surfactant

Anionic sulfonate surfactants suitable for use herein include the salts of C₅-C₂₀ linear alkylbenzene sulfonates, alkyl ester sulfonates, C₆-C₂₂ primary or secondary alkane sulfonates, C₆-C₂₄ olefin sulfonates, sulfonated polycarboxylic acids, alkyl glycerol sulfonates, fatty acyl glycerol sulfonates, fatty oleyl glycerol sulfonates, and any mixtures thereof.

Anionic carboxylate surfactant

Anionic carboxylate surfactants suitable for use herein include the alkyl ethoxy carboxylates, the alkyl polyethoxy polycarboxylate surfactants and the soaps ('alkyl carboxyls'), especially certain secondary soaps as described herein.

Preferred alkyl ethoxy carboxylates for use herein include those with the formula RO(CH₂CH₂O)_xCH₂COO-M⁺ wherein R is a C₆ to C₁₈ alkyl group, x ranges from 0 to 10, and the ethoxylate distribution is such that, on a weight basis, the amount of material where x is 0 is less than about 20 %, and the amount of material where x is greater than 7, is less than about 25 %, the average x is from about 2 to 4 when the average R is C₁₃ or less, and the average x is from about 3 to 10 when the average R is greater than C₁₃, and M is a cation, preferably chosen from alkali metal, alkaline earth metal, ammonium, mono-, di-, and tri-ethanol-ammonium, most preferably from sodium, potassium, ammonium and mixtures thereof with magnesium ions. The preferred alkyl ethoxy carboxylates are those where R is a C₁₂ to C₁₈ alkyl group.

Alkyl polyethoxy polycarboxylate surfactants suitable for use herein include those having the formula RO-(CHR₁-CHR₂-O)-R₃ wherein R is a C₆ to C₁₈ alkyl group, x is from 1 to 25, R₁ and R₂ are selected from the group consisting of hydrogen, methyl acid radical, succinic acid radical, hydroxysuccinic acid radical, and mixtures thereof, wherein at least one R₁ or R₂ is a succinic acid radical or hydroxysuccinic acid radical, and R₃ is selected from the group consisting of hydrogen, substituted or unsubstituted hydrocarbon having between 1 and 8 carbon atoms, and mixtures thereof.

Anionic secondary soap surfactant

Preferred soap surfactants are secondary soap surfactants which contain a carboxyl unit connected to a secondary carbon. The secondary carbon can be in a ring structure, e.g. as in p-octyl benzoic acid, or as in alkyl-substituted cyclohexyl carboxylates. The secondary soap surfactants should preferably contain no ether linkages, no ester linkages and no hydroxyl groups. There should preferably be no nitrogen atoms in the head-group (amphiphilic portion). The secondary soap surfactants usually contain 11-15 total carbon atoms, although slightly more (e.g., up to 16) can be tolerated, e.g. p-octyl benzoic acid.

The following general structures further illustrate some of the preferred secondary soap surfactants:

A. A highly preferred class of secondary soaps comprises the secondary carboxyl materials of the formula R³CH(R⁴)COOM, wherein R³ is CH₃(CH₂)_x and R⁴ is CH₃(CH₂)_y, wherein y can be 0 or an integer from 1 to 4, x is an integer from 4 to 10 and the sum of (x + y) is 6-10, preferably 7-9, most preferably 8.

B. Another preferred class of secondary soaps comprises those carboxyl compounds wherein the carboxyl substituent is on a ring hydrocarbonyl unit, i.e., secondary soaps of the formula R⁵-R⁶-COOM, wherein R⁵ is C⁷-C¹⁰, preferably C⁸-C⁹, alkyl or alkenyl and R⁶ is a ring structure, such as benzene, cyclopentane and cyclohexane. (Note: R⁵ can be in the ortho, meta or para position relative to the carboxyl on the ring.)

C. Still another preferred class of secondary soaps comprises secondary carboxyl compounds of the formula CH₃(CHR)_k-(CH₂)_m-(CHR)_n-CH(COOM)(CHR)_o-(CH₂)_p-(CHR)_q-CH₃, wherein each R is C₁-C₄ alkyl, wherein k, n, o, q are integers in the range of 0-8, provided that the total number of carbon atoms (including the carboxylate) is in the range of 10 to 18.

In each of the above formulas A, B and C, the species M can be any suitable, especially water-solubilizing, counterion.

Especially preferred secondary soap surfactants for use herein are water-soluble members selected from the group consisting of the water-soluble salts of 2-methyl-1-undecanoic acid, 2-ethyl-1-decanoic acid, 2-propyl-1-nonanoic acid, 2-butyl-1-octanoic acid and 2-pentyl-1-heptanoic acid.

Alkali metal sarcosinate surfactant

Other suitable anionic surfactants are the alkali metal sarcosinates of formula R-CON(R¹)CH₂COOM, wherein R is a C₅-C₁₇ linear or branched alkyl or alkenyl group, R¹ is a C₁-C₄ alkyl group and M is an alkali metal ion. Preferred examples are the myristyl and oleyl methyl sarcosinates in the form of their sodium salts.

Nonionic surfactant

Essentially any anionic surfactants useful for deterative purposes can be included in the compositions. Exemplary, non-limiting classes of useful nonionic surfactants are listed below.

Nonionic polyhydroxy fatty acid amide surfactant

Polyhydroxy fatty acid amides suitable for use herein are those having the structural formula R^2CONR^1Z wherein : R^1 is H, C_1 - C_4 hydrocarbyl, 2-hydroxy ethyl, 2-hydroxy propyl, or a mixture thereof, preferable C_1 - C_4 alkyl, more preferably C_1 or C_2 alkyl, most preferably C_1 alkyl (i.e., methyl); and R^2 is a C_5 - C_{31} hydrocarbyl, preferably straight-chain C_5 - C_{19} alkyl or alkenyl, more preferably straight-chain C_9 - C_{17} alkyl or alkenyl, most preferably straight-chain C_{11} - C_{17} alkyl or alkenyl, or mixture thereof; and Z is a polyhydroxyhydrocarbyl having a linear hydrocarbyl chain with at least 3 hydroxyls directly connected to the chain, or an alkoxyated derivative (preferably ethoxylated or propoxylated) thereof. Z preferably will be derived from a reducing sugar in a reductive amination reaction; more preferably Z is a glycyl.

Nonionic condensates of alkyl phenols

The polyethylene, polypropylene, and polybutylene oxide condensates of alkyl phenols are suitable for use herein. In general, the polyethylene oxide condensates are preferred. These compounds include the condensation products of alkyl phenols having an alkyl group containing from about 6 to about 18 carbon atoms in either a straight chain or branched chain configuration with the alkylene oxide.

Nonionic ethoxylated alcohol surfactant

The alkyl ethoxylate condensation products of aliphatic alcohols with from about 1 to about 25 moles of ethylene oxide are suitable for use herein. The alkyl chain of the aliphatic alcohol can either be straight or branched, primary or secondary, and generally contains from 6 to 22 carbon atoms. Particularly preferred are the condensation products of alcohols having an alkyl group containing from 8 to 20 carbon atoms with from about 2 to about 10 moles of ethylene oxide per mole of alcohol.

Nonionic ethoxylated/propoxylated fatty alcohol surfactant

The ethoxylated C_6 - C_{18} fatty alcohols and C_6 - C_{18} mixed ethoxylated/propoxylated fatty alcohols are suitable surfactants for use herein, particularly where water soluble. Preferably the ethoxylated fatty alcohols are the C_{10} - C_{18} ethoxylated fatty alcohols with a degree of ethoxylation of from 3 to 50, most preferably these are the C_{12} - C_{18} ethoxylated fatty alcohols with a degree of ethoxylation from 3 to 40. Preferably the mixed ethoxylated/propoxylated fatty alcohols have an alkyl chain length of from 10 to 18 carbon atoms, a degree of ethoxylation of from 3 to 30 and a degree of propoxylation of from 1 to 10.

Nonionic EO/PO condensates with propylene glycol

The condensation products of ethylene oxide with a hydrophobic base formed by the condensation of propylene oxide with propylene glycol are suitable for use herein. The hydrophobic portion of these compounds preferably has a molecular weight of from about 1500 to about 1800 and exhibits water insolubility. Examples of compounds of this type include certain of the commercially-available Pluronic™ surfactants, marketed by BASF.


Nonionic EO condensation products with propylene oxide/ethylene diamine adducts

The condensation products of ethylene oxide with the product resulting from the reaction of propylene oxide and ethylenediamine are suitable for use herein. The hydrophobic moiety of these products consists of the reaction product of ethylenediamine and excess propylene oxide, and generally has a molecular weight of from about 2500 to about 3000. Examples of this type of nonionic surfactant include certain of the commercially available Tetronic™ compounds, marketed by BASF.

Nonionic alkylpolysaccharide surfactant

Suitable alkylpolysaccharides for use herein are disclosed in U.S. Patent 4,565,647, Llenado, issued January 21, 1986, having a hydrophobic group containing from about 6 to about 30 carbon atoms, preferably from about 10 to about 16 carbon atoms and a polysaccharide, e.g., a polyglycoside, hydrophilic group containing from about 1.3 to about 10, preferably from about 1.3 to about 3, most preferably from about 1.3 to about 2.7 saccharide units. Any reducing saccharide containing 5 or 6 carbon atoms can be used, e.g., glucose, galactose and galactosyl moieties can be substituted for the glucosyl moieties. (Optionally the hydrophobic group is attached at the 2-, 3-, 4-, etc. positions thus giving a glucose or galactose as opposed to a glucoside or galactoside.) The intersaccharide bonds can be, e.g., between the one position of the additional saccharide units and the 2-, 3-, 4-, and/or 6- positions on the preceding saccharide units.

The preferred alkylpolyglycosides have the formula



wherein R² is selected from the group consisting of alkyl, alkylphenyl, hydroxyalkyl, hydroxyalkylphenyl, and mixtures thereof in which the alkyl groups contain from 10 to 18, preferably from 12 to 14, carbon atoms; n is 2 or 3; t is from 0 to 10, preferably 0, and X is from 1.3 to 8, preferably from 1.3 to 3, most preferably from 1.3 to 2.7. The glycosyl is preferably derived from glucose.

Nonionic fatty acid amide surfactant

Fatty acid amide surfactants suitable for use herein are those having the formula: R⁶CON(R⁷)₂ wherein R⁶ is an alkyl group containing from 7 to 21, preferably from 9 to 17 carbon atoms and each R⁷ is selected from the group consisting of hydrogen, C₁-C₄ alkyl, C₁-C₄ hydroxyalkyl, and -(C₂H₄O)_xH, where x is in the range of from 1 to 3.

Amphoteric surfactant

Suitable amphoteric surfactants for use herein include the amine oxide surfactants and the alkyl amphocarboxylic acids.

A suitable example of an alkyl amphocarboxylic acid for use herein is Miranol(TM) C2M Conc. manufactured by Miranol, Inc., Dayton, NJ.

Amine Oxide surfactant

Amine oxides useful herein include those compounds having the formula R³(OR⁴)_xN⁰(R⁵)₂ wherein R³ is selected from an alkyl, hydroxyalkyl, acylamidopropyl and alkyl phenyl group, or mixtures thereof, containing from 8 to 26 carbon atoms, preferably 8 to 18 carbon atoms; R⁴ is an alkylene or hydroxyalkylene group containing from 2 to 3 carbon atoms, preferably 2 carbon atoms, or mixtures thereof; x is from 0 to 5, preferably from 0 to 3; and each R⁵ is an alkyl or hydroxyalkyl group containing from 1 to 3, preferably from 1 to 2 carbon atoms, or a polyethylene oxide group containing from 1 to 3, preferable 1, ethylene oxide groups. The R⁵ groups can be attached to each other, e.g., through an oxygen or nitrogen atom, to form a ring structure.

These amine oxide surfactants in particular include C₁₀-C₁₈ alkyl dimethyl amine oxides and C₈-C₁₈ alkoxy ethyl dihydroxyethyl amine oxides. Examples of such materials include dimethyloctylamine oxide, diethyldodecylamine oxide, bis-(2-hydroxyethyl)dodecylamine oxide, dimethyldodecylamine oxide, dipropyltetradecylamine oxide, methylethylhexadecylamine oxide, dodecylamidopropyl dimethylamine oxide, cetyl dimethylamine oxide, stearyl dimethylamine oxide, tallow dimethylamine oxide and dimethyl-2-hydroxyoctadecylamine oxide. Preferred are C₁₀-C₁₈ alkyl dimethylamine oxide, and C₁₀₋₁₈ acylamido alkyl dimethylamine oxide.

Zwitterionic surfactant

Zwitterionic surfactants can also be incorporated into the detergent compositions hereof. These surfactants can be broadly described as derivatives of secondary and tertiary amines, derivatives of heterocyclic secondary and tertiary amines, or derivatives of quaternary ammonium, quaternary phosphonium or tertiary sulfonium compounds. Betaine and sultaine surfactants are exemplary zwitterionic surfactants for use herein.

Betaine surfactant

The betaines useful herein are those compounds having the formula $R(R^1)_2N^+R^2COO^-$ wherein R is a C₆-C₁₈ hydrocarbyl group, preferably a C₁₀-C₁₆ alkyl group or C₁₀₋₁₆ acylamido alkyl group, each R¹ is typically C₁-C₃ alkyl, preferably methyl, and R² is a C₁-C₅ hydrocarbyl group, preferably a C₁-C₃ alkylene group, more preferably a C₁-C₂ alkylene group. Examples of suitable betaines include coconut acylamidopropyldimethyl betaine; hexadecyl dimethyl betaine; C₁₂₋₁₄ acylamidopropylbetaine; C₈₋₁₄ acylamidohexyldiethyl betaine; 4[C₁₄₋₁₆ acylmethylamidodiethylammonio]-1-carboxybutane; C₁₆₋₁₈ acylamidodimethylbetaine; C₁₂₋₁₆ acylamidopentanedithyl-betaine; [C₁₂₋₁₆ acylmethylamidodimethylbetaine. Preferred betaines are C₁₂₋₁₈ dimethylammonio hexanoate and the C₁₀₋₁₈ acylamidopropane (or ethane) dimethyl (or diethyl) betaines. Complex betaine surfactants are also suitable for use herein.

Sultaine surfactant

The sultaines useful herein are those compounds having the formula $(R(R^1)_2N^+R^2SO_3^-)$ wherein R is a C₆-C₁₈ hydrocarbyl group, preferably a C₁₀-C₁₆ alkyl group, more preferably a C₁₂-C₁₃ alkyl group, each R¹ is typically C₁-C₃ alkyl, preferably methyl, and R² is a C₁-C₆ hydrocarbyl group, preferably a C₁-C₃ alkylene or, preferably, hydroxyalkylene group.

Ampholytic surfactant

Ampholytic surfactants can be incorporated into the detergent compositions herein. These surfactants can be broadly described as aliphatic derivatives of secondary or tertiary amines, or aliphatic derivatives of heterocyclic secondary and tertiary amines in which the aliphatic radical can be straight chain or branched.

Cationic surfactants

Cationic surfactants can also be used in the detergent compositions herein. Suitable cationic surfactants include the quaternary ammonium surfactants selected from mono C₆-C₁₆, preferably C₆-C₁₀ N-alkyl or alkenyl ammonium surfactants wherein the remaining N positions are substituted by methyl, hydroxyethyl or hydroxypropyl groups.

Water-soluble builder compound

The detergent compositions of the present invention may contain as a highly preferred component a water-soluble builder compound, typically present at a level of from 1% to 80% by weight, preferably from 10% to 70% by weight, most preferably from 20% to 60% by weight of the composition.

Suitable water-soluble builder compounds include the water soluble monomeric polycarboxylates, or their acid forms, homo or copolymeric polycarboxylic acids or their salts in which the polycarboxylic acid comprises at least two carboxylic radicals separated from each other by not more than two carbon atoms, carbonates, bicarbonates, borates, phosphates, silicates and mixtures of any of the foregoing.

The carboxylate or polycarboxylate builder can be monomeric or oligomeric in type although monomeric polycarboxylates are generally preferred for reasons of cost and performance.

Suitable carboxylates containing one carboxy group include the water soluble salts of lactic acid, glycolic acid and ether derivatives thereof. Polycarboxylates containing two carboxy groups include the water-soluble salts of succinic acid, malonic acid, (ethylenedioxy) diacetic acid, maleic acid, diglycolic acid, tartaric acid, tartronic acid and fumaric acid, as well as the ether carboxylates and the sulfinyl carboxylates. Polycarboxylates containing three carboxy groups include, in particular, water-soluble citrates, aconitrates and citraconates as well as succinate derivatives such as the carboxymethyloxysuccinates described in British Patent No. 1,379,241, lactoxysuccinates described in British Patent No. 1,389,732, and aminosuccinates described in Netherlands Application 7205873, and the oxypolycarboxylate materials such as 2-oxa-1,1,3-propane tricarboxylates described in British Patent No. 1,387,447.

Polycarboxylates containing four carboxy groups include oxydisuccinates disclosed in British Patent No. 1,261,829, 1,1,2,2-ethane tetracarboxylates, 1,1,3,3-propane tetracarboxylates and 1,1,2,3-propane tetracarboxylates. Polycarboxylates containing sulfo substituents include the sulfosuccinate derivatives disclosed in British Patent Nos. 1,398,421 and 1,398,422 and in U.S. Patent No. 3,936,448, and the sulfonated pyrolysed citrates described in British Patent No. 1,439,000.

Alicyclic and heterocyclic polycarboxylates include cyclopentanecis,cis,cis-tetracarboxylates, cyclopentadienide pentacarboxylates, 2,3,4,5-tetrahydrofuran - cis, cis, cis-tetracarboxylates, 2,5-tetrahydrofuran - cis - dicarboxylates, 2,2,5,5-tetrahydrofuran tetracarboxylates, 1,2,3,4,5,6-hexane - hexacarboxylates and carboxymethyl derivatives of polyhydric alcohols such as sorbitol, mannitol and xylitol. Aromatic polycarboxylates include mellitic acid, pyromellitic acid and the phthalic acid derivatives disclosed in British Patent No. 1,425,343.

Of the above, the preferred polycarboxylates are hydroxycarboxylates containing up to three carboxy groups per molecule, more particularly citrates.

The parent acids of the monomeric or oligomeric polycarboxylate chelating agents or mixtures thereof with their salts, e.g. citric acid or citrate/citric acid mixtures are also contemplated as useful builder components.

Borate builders, as well as builders containing borate-forming materials that can produce borate under detergent storage or wash conditions can also be used but are not preferred at wash conditions less than about 50°C, especially less than about 40°C.

Examples of carbonate builders are the alkaline earth and alkali metal carbonates, including sodium carbonate and sesqui-carbonate and mixtures thereof with ultra-fine calcium carbonate as disclosed in German Patent Application No. 2,321,001 published on November 15, 1973.

Specific examples of water-soluble phosphate builders are the alkali metal tripolyphosphates, sodium, potassium and ammonium pyrophosphate, sodium and potassium and ammonium pyrophosphate, sodium and potassium orthophosphate, sodium polymeta/phosphate in which the degree of polymerization ranges from about 6 to 21, and salts of phytic acid.

Suitable silicates include the water soluble sodium silicates with an SiO_2 : Na_2O ratio of from 1.0 to 2.8, with ratios of from 1.6 to 2.4 being preferred, and 2.0 ratio being most preferred. The silicates may be in the form of either the anhydrous salt or a hydrated salt. Sodium silicate with an SiO_2 : Na_2O ratio of 2.0 is the most preferred silicate.


Silicates are preferably present in the detergent compositions in accord with the invention at a level of from 5% to 50% by weight of the composition, more preferably from 10% to 40% by weight.

Partially soluble or insoluble builder compound

The detergent compositions of the present invention may contain a partially soluble or insoluble builder compound, typically present at a level of from 1% to 80% by weight, preferably from 10% to 70% by weight, most preferably from 20% to 60% weight of the composition.

Examples of partially water soluble builders include the crystalline layered silicates. Examples of largely water insoluble builders include the sodium aluminosilicates.

Crystalline layered sodium silicates have the general formula




wherein M is sodium or hydrogen, x is a number from 1.9 to 4 and y is a number from 0 to 20. Crystalline layered sodium silicates of this type are disclosed in EP-A-0164514 and methods for their preparation are disclosed in DE-A-3417649 and DE-A-3742043. For the purpose of the present invention, x in the general formula above has a value of 2, 3 or 4 and is preferably 2. The most preferred material is δ - $\text{Na}_2\text{Si}_2\text{O}_5$, available from Hoechst AG as NaSKS-6.

The crystalline layered sodium silicate material is preferably present in granular detergent compositions as a particulate in intimate admixture with a solid, water-soluble ionisable material. The solid, water-soluble ionisable material is selected from organic acids, organic and inorganic acid salts and mixtures thereof.

Suitable aluminosilicate zeolites have the unit cell formula $\text{Na}_z[(\text{AlO}_2)_z(\text{SiO}_2)_y]\cdot x\text{H}_2\text{O}$ wherein z and y are at least 6; the molar ratio of z to y is from 1.0 to 0.5 and x is at least 5, preferably from 7.5 to 276, more preferably from 10 to 264. The aluminosilicate material are in hydrated form and are preferably crystalline, containing from 10% to 28%, more preferably from 18% to 22% water in bound form.

The aluminosilicate ion exchange materials can be naturally occurring materials, but are preferably synthetically derived. Synthetic crystalline aluminosilicate ion exchange materials are available under the designations Zeolite A, Zeolite B, Zeolite P, Zeolite X, Zeolite MAP, Zeolite HS and mixtures thereof. Zeolite A has the formula



wherein x is from 20 to 30, especially 27. Zeolite X has the formula $\text{Na}_{86}[(\text{AlO}_2)_{86}(\text{SiO}_2)_{106}]\cdot 276\text{H}_2\text{O}$.

Heavy metal ion sequestrant

The detergent compositions of the invention may contain as a preferred optional component a heavy metal ion sequestrant. By heavy metal ion sequestrant it is meant herein components which act to sequester (chelate)

heavy metal ions. These components may also have calcium and magnesium chelation capacity, but preferentially they show selectivity to binding heavy metal ions such as iron, manganese and copper.

Heavy metal ion sequestrants are preferably present at a level of from 0.005% to 20%, more preferably from 0.1% to 10%, most preferably from 0.5% to 5% by weight of the compositions.

Heavy metal ion sequestrants, which are acidic in nature, having for example phosphonic acid or carboxylic acid functionalities, may be present either in their acid form or as a complex/salt with a suitable counter cation such as an alkali or alkaline metal ion, ammonium, or substituted ammonium ion, or any mixtures thereof. Preferably any salts/complexes are water soluble. The molar ratio of said counter cation to the heavy metal ion sequesterant is preferably at least 1:1.

Suitable heavy metal ion sequestrants for use herein include organic phosphonates, such as the amino alkylene poly (alkylene phosphonates), alkali metal ethane 1-hydroxy disphosphonates and nitrilo trimethylene phosphonates.

Preferred among the above species are diethylene triamine penta (methylene phosphonate), ethylene diamine tri (methylene phosphonate) hexamethylene diamine tetra (methylene phosphonate) and hydroxyethylene 1,1 diphosphonate.

Other suitable heavy metal ion sequesterant for use herein include nitrilotriacetic acid and polyaminocarboxylic acids such as ethylenediaminetetracetic acid, ethylenetriamine pentacetic acid, ethylenediamine disuccinic acid, ethylenediamine diglutamic acid, 2-hydroxypropylenediamine disuccinic acid or any salts thereof.

Especially preferred is ethylenediamine-N,N'-disuccinic acid (EDDS) or the alkali metal, alkaline earth metal, ammonium, or substituted ammonium salts thereof, or mixtures thereof. Preferred EDDS compounds are the free acid form and the sodium or magnesium salt or complex thereof. Examples of such preferred sodium salts of EDDS include Na₂EDDS and Na₃EDDS. Examples of such preferred magnesium complexes of EDDS include MgEDDS and Mg₂EDDS.

Other suitable heavy metal ion sequestrants for use herein are iminodiacetic acid derivatives such as 2-hydroxyethyl diacetic acid or glyceryl imino diacetic acid, described in EP-A-317,542 and EP-A-399,133.

The iminodiacetic acid-N-2-hydroxypropyl sulfonic acid and aspartic acid N-carboxymethyl N-2-hydroxypropyl-3-sulfonic acid sequestrants described in EP-A-516,102 are also suitable herein. The β -alanine-N,N'-diacetic acid, aspartic acid-N,N'-diacetic acid, aspartic acid-N-monoacetic acid and iminodisuccinic acid sequestrants described in EP-A-509,382 are also suitable.

EP-A-476,257 describes suitable amino based sequestrants. EP-A-510,331 describes suitable sequestrants derived from collagen, keratin or casein. EP-A-528,859 describes a suitable alkyl iminodiacetic acid sequesterant. Dipicolinic acid and 2-phosphonobutane-1,2,4-tricarboxylic acid are also suitable. Glycinamide-N,N'-disuccinic acid (GADS) is also suitable.

Enzyme

Another optional ingredient useful in the detergent compositions is one or more additional enzymes.

Preferred additional enzymatic materials include the commercially available lipases, amylases, neutral and alkaline proteases, esterases, cellulases, pectinases, lactases and peroxidases conventionally incorporated into detergent compositions. Suitable enzymes are discussed in US Patents 3,519,570 and 3,533,139.

Preferred commercially available protease enzymes include those sold under the tradenames Alcalase, Savinase, Primase, Durazym, and Esperase by Novo Industries A/S (Denmark), those sold under the tradename Maxatase, Maxacal and Maxapem by Gist-Brocades, those sold by Genencor International, and those sold under the tradename Opticlean and Optimase by Solvay Enzymes. Protease enzyme may be incorporated into the compositions in accordance with the invention at a level of from 0.0001% to 4% active enzyme by weight of the composition.

Preferred amylases include, for example, α -amylases obtained from a special strain of *B licheniformis*, described in more detail in GB-1,269,839 (Novo). Preferred commercially available amylases include for example, those sold under the tradename Rapidase by Gist-Brocades, and those sold under the tradename Termamyl and BAN by Novo Industries A/S. Amylase enzyme may be incorporated into the composition in accordance with the invention at a level of from 0.0001% to 2% active enzyme by weight of the composition.

Lipolytic enzyme (lipase) may be present at levels of active lipolytic enzyme of from 0.0001% to 2% by weight, preferably 0.001% to 1% by weight, most preferably from 0.001% to 0.5% by weight of the compositions.

The lipase may be fungal or bacterial in origin being obtained, for example, from a lipase producing strain of *Humicola* sp., *Thermomyces* sp. or *Pseudomonas* sp. including *Pseudomonas pseudoalcaligenes* or *Pseudomonas fluorescens*. Lipase from chemically or genetically modified mutants of these strains are also useful herein.

A preferred lipase is derived from *Pseudomonas pseudoalcaligenes*, which is described in Granted Euro-

pean Patent, EP-B-0218272.

Another preferred lipase herein is obtained by cloning the gene from Humicola lanuginosa and expressing the gene in Aspergillus oryza, as host, as described in European Patent Application, EP-A-0258 068, which is commercially available from Novo Industri A/S, Bagsvaerd, Denmark, under the trade name Lipolase. This lipase is also described in U.S. Patent 4,810,414, Høge-Jensen et al, issued March 7, 1989.

Where the enzyme is a protease, the ultimate amount in a typical wash solution is from 0.1 to 100 KNPU, but preferably is from 0.5 to 50 KNPU, more preferably from 3 to 30 KNPU.

Where the enzyme is an amylase, the ultimate amount in a typical wash solution is from 1 to 1500 KNU, but preferably is from 5 to 1200 KNU, more preferably from 30 to 450 KNU.

Where the enzyme is a lipase, the ultimate amount in a typical wash solution is from 1 to 300 KLU, but preferably is from 10 to 200 KLU, more preferably from 10 to 100 KLU.

Where the enzyme is a cellulase, the ultimate amount in the wash is typically from 10 to 1200 CEVU, but preferably is from 50 to 1000 CEVU, more preferably from 80 to 500 CEVU.

Enzyme Stabilizing System

Preferred enzyme-containing compositions herein may comprise from about 0.001% to about 10%, preferably from about 0.005% to about 8%, most preferably from about 0.01% to about 6%, by weight of an enzyme stabilizing system. The enzyme stabilizing system can be any stabilizing system which is compatible with the detergent enzyme. Such stabilizing systems can comprise calcium ion, boric acid, propylene glycol, short chain carboxylic acid, boronic acid, and mixtures thereof. Such stabilizing systems can also comprise reversible enzyme inhibitors, such as reversible protease inhibitors.

The compositions herein may further comprise from 0 to about 10%, preferably from about 0.01% to about 6% by weight, of chlorine bleach scavengers, added to prevent chlorine bleach species present in many water supplies from attacking and inactivating the enzymes, especially under alkaline conditions. While chlorine levels in water may be small, typically in the range from about 0.5 ppm to about 1.75 ppm, the available chlorine in the total volume of water that comes in contact with the enzyme during washing is usually large; accordingly, enzyme stability in-use can be problematic.

Suitable chlorine scavenger anions are widely available, and are illustrated by salts containing ammonium cations or sulfite, bisulfite, thiosulfite, thiosulfate, iodide, etc. Antioxidants such as carbamate, ascorbate, etc., organic amines such as ethylenediaminetetraacetic acid (EDTA) or alkali metal salt thereof, monoethanolamine (MEA), and mixtures thereof can likewise be used. Other conventional scavengers such as bisulfate, nitrate, chloride, sources of hydrogen peroxide such as sodium perborate tetrahydrate, sodium perborate monohydrate and sodium percarbonate, as well as phosphate, condensed phosphate, acetate, benzoate, citrate, formate, lactate, malate, tartrate, salicylate, etc. and mixtures thereof can be used if desired.

Organic polymeric compound

Organic polymeric compounds are particularly preferred components of the detergent compositions in accord with the invention. By organic polymeric compound it is meant essentially any polymeric organic compound commonly used as dispersants, and anti-redeposition and soil suspension agents in detergent compositions.

Organic polymeric compound is typically incorporated in the detergent compositions of the invention at a level of from 0.1% to 30%, preferably from 0.5% to 15%, most preferably from 1% to 10% by weight of the compositions.

Examples of organic polymeric compounds include the water soluble organic homo- or co-polymeric polycarboxylic acids or their salts in which the polycarboxylic acid comprises at least two carboxyl radicals separated from each other by not more than two carbon atoms. Polymers of the latter type are disclosed in GB-A-1,596,756. Examples of such salts are polyacrylates of molecular weight 2000-5000 and their copolymers with any suitable other monomer units including modified acrylic, fumaric, maleic, itaconic, aconitic, mesaconic, citraconic and methylenemalononic acid or their salts, maleic anhydride, acrylamide, alkylene, vinylmethyl ether, styrene and any mixtures thereof. Preferred are the copolymers of acrylic acid and maleic anhydride having a molecular weight of from 20,000 to 100,000.

Preferred commercially available acrylic acid containing polymers having a molecular weight below 15,000 include those sold under the tradename Sokalan PA30, PA20, PA15, PA10 and Sokalan CP10 by BASF GmbH, and those sold under the tradename Acusol 45N by Rohm and Haas.

Preferred acrylic acid containing copolymers include those which contain as monomer units: a) from 90% to 10%, preferably from 80% to 20% by weight acrylic acid or its salts and b) from 10% to 90%, preferably

from 20% to 80% by weight of a substituted acrylic monomer or its salts having the general formula $-\text{[CR}_2\text{-CR}_1\text{(CO-O-R}_3\text{)]-}$ wherein at least one of the substituents R_1 , R_2 or R_3 , preferably R_1 or R_2 is a 1 to 4 carbon alkyl or hydroxyalkyl group, R_1 or R_2 can be a hydrogen and R_3 can be a hydrogen or alkali metal salt. Most preferred is a substituted acrylic monomer wherein R_1 is methyl, R_2 is hydrogen (i.e. a methacrylic acid monomer). The most preferred copolymer of this type has a molecular weight of 3500 and contains 60% to 80% by weight of acrylic acid and 40% to 20% by weight of methacrylic acid.

Other suitable polyacrylate/modified polyacrylate copolymers include those copolymers of unsaturated aliphatic carboxylic acids disclosed in U.S. Patents No.s 4,530,766, and 5,084,535 which have a molecular weight of less than 15,000.

Other suitable organic polymeric compounds include the polymers of acrylamide and acrylate having a molecular weight of from 3,000 to 100,000, and the acrylate/fumarate copolymers having a molecular weight of from 2,000 to 80,000.

The polyamino compounds are useful herein including those derived from aspartic acid such as those disclosed in EP-A-305282, EP-A-305283 and EP-A-351629.

Other organic polymeric compounds suitable for incorporation in the detergent compositions herein include cellulose derivatives such as methylcellulose, carboxymethylcellulose and hydroxyethylcellulose.

Further useful organic polymeric compounds are the polyethylene glycols, particularly those of molecular weight 1000-10000, more particularly 2000 to 8000 and most preferably about 4000.

Lime soap dispersant compound

The compositions of the invention may contain a lime soap dispersant compound, which has a lime soap dispersing power (LSDP), as defined hereinafter of no more than 8, preferably no more than 7, most preferably no more than 6. The lime soap dispersant compound is preferably present at a level of from 0.1% to 40% by weight, more preferably 1% to 20% by weight, most preferably from 2% to 10% by weight of the compositions.

A lime soap dispersant is a material that prevents the precipitation of alkali metal, ammonium or amine salts of fatty acids by calcium or magnesium ions. A numerical measure of the effectiveness of a lime soap dispersant is given by the lime soap dispersing power (LSDP) which is determined using the lime soap dispersion test as described in an article by H.C. Borghetty and C.A. Bergman, J. Am. Oil. Chem. Soc., volume 27, pages 88-90, (1950). This lime soap dispersion test method is widely used by practitioners in this art field being referred to, for example, in the following review articles; W.N. Linfield, Surfactant Science Series, Volume 7, p3; W.N. Linfield, Tenside Surf. Det., Volume 27, pages 159-161, (1990); and M.K. Nagarajan, W.F. Masler, Cosmetics and Toiletries, Volume 104, pages 71-73, (1989). The LSDP is the % weight ratio of dispersing agent to sodium oleate required to disperse the lime soap deposits formed by 0.025g of sodium oleate in 30ml of water of 333ppm CaCO_3 ($\text{Ca:Mg}=3:2$) equivalent hardness.

Surfactants having good lime soap dispersant capability will include certain amine oxides, betaines, sulfobetaines, alkyl ethoxysulfates and ethoxylated alcohols.

Exemplary surfactants having a LSDP of no more than 8 for use in accord with the invention include C_{16} - C_{18} dimethyl amine oxide, C_{12} - C_{18} alkyl ethoxysulfates with an average degree of ethoxylation of from 1-5, particularly C_{12} - C_{15} alkyl ethoxysulfate surfactant with a degree of ethoxylation of about 3 (LSDP=4), and the C_{13} - C_{15} ethoxylated alcohols with an average degree of ethoxylation of either 12 (LSDP=6) or 30, sold under the trade names Lutensol A012 and Lutensol A030 respectively, by BASF GmbH.

Polymeric lime soap dispersants suitable for use herein are described in the article by M.K. Nagarajan and W.F. Masler, to be found in Cosmetics and Toiletries, Volume 104, pages 71-73, (1989). Examples of such polymeric lime soap dispersants include certain water-soluble salts of copolymers of acrylic acid, methacrylic acid or mixtures thereof, and an acrylamide or substituted acrylamide, where such polymers typically have a molecular weight of from 5,000 to 20,000.

Suds suppressing system

The detergent compositions of the invention, when formulated for use in machine washing compositions, preferably comprise a suds suppressing system present at a level of from 0.01% to 15%, preferably from 0.05% to 10%, most preferably from 0.1% to 5% by weight of the composition.

Suitable suds suppressing systems for use herein may comprise essentially any known antifoam compound, including, for example silicone antifoam compounds, 2-alkyl and alkanol antifoam compounds.

By antifoam compound it is meant herein any compound or mixtures of compounds which act such as to depress the foaming or sudsing produced by a solution of a detergent composition, particularly in the presence of agitation of that solution.

Particularly preferred antifoam compounds for use herein are silicone antifoam compounds defined herein as any antifoam compound including a silicone component. Such silicone antifoam compounds also typically contain a silica component. The term "silicone" as used herein, and in general throughout the industry, encompasses a variety of relatively high molecular weight polymers containing siloxane units and hydrocarbyl group of various types. Preferred silicone antifoam compounds are the siloxanes, particularly the polydimethylsiloxanes having trimethylsilyl end blocking units.

Other suitable antifoam compounds include the monocarboxylic fatty acids and soluble salts thereof. These materials are described in US Patent 2,954,347, issued September 27, 1960 to Wayne St. John. The monocarboxylic fatty acids, and salts thereof, for use as suds suppressor typically have hydrocarbyl chains of 10 to about 24 carbon atoms, preferably 12 to 18 carbon atoms. Suitable salts include the alkali metal salts such as sodium, potassium, and lithium salts, and ammonium and alkanolammonium salts.

Other suitable antifoam compounds include, for example, high molecular weight fatty esters (e.g. fatty acid triglycerides), fatty acid esters of monovalent alcohols, aliphatic C₁₈-C₄₀ ketones (e.g. stearone) N-alkylated amino triazines such as tri- to hexa-alkylmelamines or di- to tetra alkyl diamine chlortriazines formed as products of cyanuric chloride with two or three moles of a primary or secondary amine containing 1 to 24 carbon atoms, propylene oxide, bis stearic acid amide and monostearyl dialkali metal (e.g. sodium, potassium, lithium) phosphates and phosphate esters.

Copolymers of ethylene oxide and propylene oxide, particularly the mixed ethoxylated/propoxylated fatty alcohols with an alkyl chain length of from 10 to 16 carbon atoms, a degree of ethoxylation of from 3 to 30 and a degree of propoxylation of from 1 to 10, are also suitable antifoam compounds for use herein.

Suitable 2-alkyl-alkanols antifoam compounds for use herein have been described in DE 40 21 265. The 2-alkyl-alkanols suitable for use herein consist of a C₆ to C₁₆ alkyl chain carrying a terminal hydroxy group, and said alkyl chain is substituted in the α position by a C₁ to C₁₀ alkyl chain.

Mixtures of 2-alkyl-alkanols can be used in the compositions according to the present invention.

A preferred suds suppressing system comprises

(a) antifoam compound, preferably silicone antifoam compound, most preferably a silicone antifoam compound comprising in combination

(i) polydimethyl siloxane, at a level of from 50% to 99%, preferably 75% to 95% by weight of the silicone antifoam compound; and

(ii) silica, at a level of from 1% to 50%, preferably 5% to 25% by weight of the silicone/silica antifoam compound;

wherein said silica/silicone antifoam compound is incorporated at a level of from 5% to 50%, preferably 10% to 40% by weight;

(b) a dispersant compound, most preferably comprising a silicone glycol rake copolymer with a polyoxyalkylene content of 72-78% and an ethylene oxide to propylene oxide ratio of from 1:0.9 to 1:1.1, at a level of from 0.5% to 10%, preferably 1% to 10% by weight; a particularly preferred silicone glycol rake copolymer of this type is DCO544, commercially available from DOW Corning under the tradename DCO544;

(c) an inert carrier fluid compound, most preferably comprising a C₁₆-C₁₈ ethoxylated alcohol with a degree of ethoxylation of from 5 to 50, preferably 8 to 15, at a level of from 5% to 80%, preferably 10% to 70%, by weight;

A preferred particulate suds suppressor system useful herein comprises a mixture of an alkylated siloxane of the type hereinabove disclosed and solid silica.

The solid silica can be a fumed silica, a precipitated silica or a silica made by the gel formation technique. The silica particles suitable have an average particle size of from 0.1 to 50 micrometers, preferably from 1 to 20 micrometers and a surface area of at least 50m²/g. These silica particles can be rendered hydrophobic by treating them with dialkylsilyl groups and/or trialkylsilyl groups either bonded directly onto the silica or by means of a silicone resin. It is preferred to employ a silica the particles of which have been rendered hydrophobic with dimethyl and/or trimethyl silyl groups. A preferred particulate antifoam compound for inclusion in the detergent compositions in accordance with the invention suitably contain an amount of silica such that the weight ratio of silica to silicone lies in the range from 1:100 to 3:10, preferably from 1:50 to 1:7.

Another suitable particulate suds suppressing system is represented by a hydrophobic silanated (most preferably trimethyl-silanated) silica having a particle size in the range from 10 nanometers to 20 nanometers and a specific surface area above 50m²/g, intimately admixed with dimethyl silicone fluid having a molecular weight in the range from about 500 to about 200,000 at a weight ratio of silicone to silanated silica of from about 1:1 to about 1:2.

A highly preferred particulate suds suppressing system is described in EP-A-0210731 and comprises a silicone antifoam compound and an organic carrier material having a melting point in the range 50°C to 85°C, wherein the organic carrier material comprises a monoester of glycerol and a fatty acid having a carbon chain

containing from 12 to 20 carbon atoms. EP-A-0210721 discloses other preferred particulate suds suppressing systems wherein the organic carrier material is a fatty acid or alcohol having a carbon chain containing from 12 to 20 carbon atoms, or a mixture thereof, with a melting point of from 45°C to 80°C.

Other highly preferred particulate suds suppressing systems are described in copending European Application 91870007.1 in the name of the Procter and Gamble Company which systems comprise silicone antifoam compound, a carrier material, an organic coating material and glycerol at a weight ratio of glycerol : silicone antifoam compound of 1:2 to 3:1. Copending European Application 91201342.0 also discloses highly preferred particulate suds suppressing systems comprising silicone antifoam compound, a carrier material, an organic coating material and crystalline or amorphous aluminosilicate at a weight ratio of aluminosilicate : silicone antifoam compound of 1:3 to 3:1. The preferred carrier material in both of the above described highly preferred granular suds controlling agents is starch.

An exemplary particulate suds suppressing system for use herein is a particulate agglomerate component, made by an agglomeration process, comprising in combination

(i) from 5% to 30%, preferably from 8% to 15% by weight of the component of silicone antifoam compound, preferably comprising in combination polydimethyl siloxane and silica;

(ii) from 50% to 90%, preferably from 60% to 80% by weight of the component, of carrier material, preferably starch;

(iii) from 5% to 30%, preferably from 10% to 20% by weight of the component of agglomerate binder compound, where herein such compound can be any compound, or mixtures thereof typically employed as binders for agglomerates, most preferably said agglomerate binder compound comprises a C₁₆-C₁₈ ethoxylated alcohol with a degree of ethoxylation of from 50 to 100; and

(iv) from 2% to 15%, preferably from 3% to 10%, by weight of C₁₂-C₂₂ hydrogenated fatty acid.

Form of the compositions

The detergent compositions of the invention can be formulated in any desirable form such as powders, granulates, pastes, liquids, tablets and gels.

Liquid compositions

The detergent compositions of the present invention may be formulated as liquid detergent compositions. Such liquid detergent compositions typically comprise from 94% to 35% by weight, preferably from 90% to 40% by weight, most preferably from 80% to 50% by weight of a liquid carrier, e.g., water, preferably a mixture of water and organic solvent.

Gel compositions

The detergent compositions of the present invention may also be in the form of gels. Such compositions are typically formulated with polyalkenyl polyether having a molecular weight of from about 750,000 to about 4,000,000.

Solid compositions

The detergent compositions of the invention are preferably in the form of solids, such as powders and granules.

The particle size of the components of granular compositions in accordance with the invention should preferably be such that no more than 5% of particles are greater than 1.4mm in diameter and not more than 5% of particles are less than 0.15mm in diameter.

The bulk density of granular detergent compositions in accordance with the present invention typically have a bulk density of at least 450 g/litre, more usually at least 600 g/litre and more preferably from 650 g/litre to 1200 g/litre.

Bulk density is measured by means of a simple funnel and cup device consisting of a conical funnel moulded rigidly on a base and provided with a flap valve at its lower extremity to allow the contents of the funnel to be emptied into an axially aligned cylindrical cup disposed below the funnel. The funnel is 130 mm and 40 mm at its respective upper and lower extremities. It is mounted so that the lower extremity is 140 mm above the upper surface of the base. The cup has an overall height of 90 mm, an internal height of 87 mm and an internal diameter of 84 mm. Its nominal volume is 500 ml.

To carry out a measurement, the funnel is filled with powder by hand pouring, the flap valve is opened

and powder allowed to overfill the cup. The filled cup is removed from the frame and excess powder removed from the cup by passing a straight edged implement e.g. a knife, across its upper edge. The filled cup is then weighed and the value obtained for the weight of powder doubled to provide the bulk density in g/litre. Replicate measurements are made as required.

5

Making processes - granular compositions

In general, granular detergent compositions in accordance with the present invention can be made via a variety of methods including dry mixing, spray drying, agglomeration and granulation.

10

Washing methods

The compositions of the invention may be used in essentially any washing or cleaning method, including machine dishwashing methods.

15

Machine dishwashing method

A preferred machine dishwashing method comprises treating soiled articles selected from crockery, glassware, hollowware and cutlery and mixtures thereof, with an aqueous liquid having dissolved or dispensed therein an effective amount of a machine dishwashing composition in accord with the invention. By an effective amount of the machine dishwashing composition it is meant from 8g to 60g of product dissolved or dispersed in a wash solution of volume from 3 to 10 litres, as are typical product dosages and wash solution volumes commonly employed in conventional machine dishwashing methods.

20

In the detergent compositions, the abbreviated component identifications have the following meanings:

25	XYEZX	: C _{1X} - C _{1Y} sodium alkyl sulfate condensed with an average of Z moles of ethylene oxide per mole
	Nonionic	: C ₁₃ -C ₁₅ mixed ethoxylated/propoxylated fatty alcohol with an average degree of ethoxylation of 3.8 and an average degree of propoxylation of 4.5 sold under the tradename Plurafac LF404 by BASF GmbH
30	Silicate	: Amorphous Sodium Silicate (SiO ₂ :Na ₂ O ratio = 2.0)
	Carbonate	: Anhydrous sodium carbonate
	Phosphate	: Sodium tripolyphosphate
	MA/AA	: Copolymer of 1:4 maleic/acrylic acid, average molecular weight about 80,000
	Mn catalyst	Mn ^{IV} ₂ (u-O) ₃ (1,4,7-trimethyl-1,4,7-triazacyclononane) ₂ -(PF ₆) ₂
35	Citrate	: Tri-sodium citrate dihydrate
	PB4	: Anhydrous sodium perborate tetrahydrate in compacted form such that the available oxygen is released in a 5 minute interval when incorporated into the compositions of the Examples and employing the test method described herein.
40	Percarbonate	: Anhydrous sodium percarbonate bleach of empirical formula 2Na ₂ CO ₃ ·3H ₂ O ₂ coated with a mixed salt of formula Na ₂ SO ₄ ·n·Na ₂ CO ₃ where n is 0.29 and where the weight ratio of percarbonate to mixed salt is 39:1
	TAED	: Tetraacetyl ethylene diamine
	Paraffin	: Paraffin oil sold under the tradename Winog 70 by Wintershall.
45	Protease	: Proteolytic enzyme sold under the tradename Savinase by Novo Industries A/S (approx 2% enzyme activity).
	Amylase	: Amylolytic enzyme sold under the tradename Termamyl 60T by Novo Industries A/S (approx 0.9% enzyme activity)
	Lipase	: Lipolytic enzyme sold under the tradename Lipolase by Novo Industries A/S (approx 2% enzyme activity)
50	DETPMP	: Diethylene triamine penta (methylene phosphonic acid), marketed by Monsanto under the Trade name Dequest 2060
	Granular Suds Suppressor	: 12% Silicone/silica, 18% stearyl alcohol, 70% starch in granular form
	Sulphate	: Anhydrous sodium sulphate.

55

In the following examples all levels of enzyme quoted are expressed as % active enzyme by weight of the composition.

Example 1

The following machine dishwashing detergent compositions were prepared (parts by weight). Composition A is a prior art composition, compositions B to F are in accord with the invention.

5

10

15

20

25

30

35

40

45

50

55

	A	B	C	D	E	F
Citrate	15.0	15.0	-	24.0	24.0	29.0
Phosphate	-	-	46.0	-	-	-
MA/AA	6.0	6.0	-	6.0	6.0	-
Silicate	9.0	9.0	33.0	27.5	27.5	25.7
Carbonate	20.0	20.0	-	12.5	12.5	-
Percarbonate	9.1	9.1	10.4	10.4	10.4	-
PB4	-	-	-	-	-	10.6
TAED	2.2	2.2	3.0	3.0	3.0	4.4
Benzotriazole	-	0.4	0.6	-	0.5	0.3
Paraffin	-	0.5	-	0.6	0.5	0.5
Mn catalyst	0.03	0.03	0.03	0.03	0.03	0.03
Protease	0.04	0.04	0.03	0.04	0.04	0.04
Amylase	0.02	0.02	0.01	0.02	0.01	0.01

Lipase	-	-	0.03	0.03	0.03	-
DETPMP	-	-	-	-	-	0.5
Nonionic	1.7	1.7	1.5	1.5	1.5	1.5
Sulphate	1.4	1.4	2.4	12.1	12.1	3.0
35AE3S	-	-	5.0	-	5.0	-
Granular Suds Suppressor	-	-	1.0	-	1.0	-
misc/moisture to balance						

The compositions provide good soil removal when used in a machine dishwashing process.

Comparative testing 1

The following comparative testing was conducted; composition B of Example I was compared for anti-silver tarnishing performance, to a reference composition (composition A of Example I) containing no benzotriazole or paraffin oil.

The testing involved machine testing, using a Bosch Siemens dishwasher, 20g product dosage, 65°C economy cycles, and 10 cycles.

Performance was graded by 4 expert panellists through visual inspection according to the following scale : where

0 = no tarnish (shiny silver)

1 = very slight tarnish

2 = tarnish

3 = very tarnished

4 = severe tarnish (black coverage)

Results were as follows : (average of the 4 gradings from the panellists)

Composition A	Composition B
3.0	0.5

Composition B shows a reduced level of silver tarnishing in accord with the invention.

Claims

1. A bleaching composition containing
 - (a) a transition metal containing bleach catalyst wherein said bleach catalyst is not an Mn(II) compound;
 - (b) an oxygen bleach; and
 - (c) a corrosion inhibitor compound

2. A bleaching composition according to Claim 1 wherein said corrosion inhibitor compound is selected from a paraffin oil, benzotriazole and derivatives thereof, and any mixtures thereof.
3. A bleaching composition according to either of Claims 1 or 2 wherein a means is provided for controlling the rate of release of available oxygen from said oxygen bleach such that, when using the method described in the present description, the available oxygen is completely released from the composition in a time interval of from 3.5 minutes to 10.0 minutes.
4. A bleaching composition according to any of Claims 1 - 3 wherein the level of available oxygen, measured in units of % available oxygen by weight of the composition, is from 0.3% to 1.7% measured according to the method described herein.
5. A bleaching composition according to any of Claims 1 - 4 wherein said bleach catalyst is selected from the group consisting of $\text{Mn}^{\text{IV}}_2(\text{u-O})_3(1,4,7\text{-trimethyl-}1,4,7\text{-triazacyclononane})_2(\text{PF}_6)_2$; $\text{Mn}^{\text{III}}_2(\text{u-O})_1(\text{u-OAc})_2(1,4,7\text{-tri-methyl-}1,4,7\text{-triazacyclononane})_2(\text{ClO}_4)_2$; $\text{Mn}^{\text{IV}}_4(\text{u-O})_6(1,4,7\text{-triazacyclononane})_4(\text{ClO}_4)_2$; $\text{Mn}^{\text{III}}\text{Mn}^{\text{IV}}_4(\text{u-O})_1(\text{u-OAc})_2(1,4,7\text{-tri-methyl-}1,4,7\text{-triazacyclononane})_2(\text{ClO}_4)_3$; $\text{Mn}(1,4,7\text{-trimethyl-}1,4,7\text{-triazacyclononane}(\text{OCH}_3)_3(\text{PF}_6))$; $\text{Co}(2,2'\text{-bispyridyl-amine})\text{Cl}_2$; $\text{Di}(\text{isothio-cyanato})\text{bispyridylamine-cobalt (II)}$; $\text{tris(dipyridylamine-cobalt (II) per-chlorate)}$; $\text{Co}(2,2\text{-bispyridylamine})_2\text{-O}_2\text{ClO}_4$; $\text{Bis-(}2,2'\text{-bispyridylamine) copper(II) per-chlorate}$; $\text{tris(di-2-pyridylamine) iron (II) perchlorate}$; $\text{Mn}^{\text{IV}}(\text{CF}_3\text{SO}_3)_2$; $\text{Co}(\text{NH}_3)_5\text{Cl}$; binuclear Mn complexed with tetra-N-dentate and bi-N-dentate ligands, including $\text{N}_4\text{Mn}^{\text{III}}(\text{u-O})_2\text{Mn}^{\text{IV}}\text{N}_4$ and $[\text{Bipy}_2\text{Mn}^{\text{III}}(\text{u-O})_2\text{Mn}^{\text{IV}}\text{bipy}_2](\text{ClO}_4)_3$ and mixtures thereof.
6. A bleaching composition according to any of Claims 1-5 wherein the oxygen bleach comprises in combination an inorganic perhydrate salt and an organic peroxyacid precursor compound.
7. A bleaching composition according to any of Claims 1 - 6 containing a heavy metal ion sequestrant present at a level of from 0.005% to 20% by weight of the composition.