

(12) STANDARD PATENT APPLICATION (11) Application No. AU 2012374619 A1
(19) AUSTRALIAN PATENT OFFICE

(54) Title
Medical treatment instrument

(51) International Patent Classification(s)
A61B 17/00 (2006.01)

(21) Application No: **2012374619**

(22) Date of Filing: **2012.07.18**

(43) Publication Date: **2014.02.06**

(43) Publication Journal Date: **2014.02.06**

(71) Applicant(s)
Terumo Kabushiki Kaisha

(72) Inventor(s)
Suehara, Satoru

(74) Agent / Attorney
Pizzey's, PO Box 291, WODEN, ACT, 2606

ABSTRACT

A medical treatment tool (1) includes: an insert portion (3) at least a part of which is provided by a flexing portion (32) that is adapted to be flexed, the insert portion (3) being adapted to be inserted into a human body of a patient; and an inflatable body (5) provided on an outer circumference of the flexing portion (32), the inflatable body (5) being inflated in a radial direction of the flexing portion (32). An axial distal end portion (51) of the inflatable body (5) is fixed to the insert portion (3) while a proximal end portion (52) of the inflatable body (5) is axially movable relative to the insert portion (3).

DESCRIPTION

MEDICAL TREATMENT TOOL

TECHNICAL FIELD

[0001]

5 The present invention relates to a medical treatment tool.

BACKGROUND ART

[0002]

Medical treatment tools that include a flexible insert portion to be inserted into a human body and an inflatable body provided on an outer circumference of the insert
10 portion have been typically known (see, for instance, Patent Literature 1).

The medical treatment tool disclosed in Patent Literature 1 includes a shaft having a flexible joint portion (flexing portion) provided at an end thereof, an inflatable body provided on an outer circumference of the joint portion, and a channel provided along the shaft to be in communication with the inflatable body. The inflatable body is
15 inflatable in a radial direction of the insert portion by a fluid introduced into the inflatable body through the channel.

CITATION LIST

PATENT LITERATURE(S)

[0003]

20 Patent Literature 1 US 2010/0312338 A

SUMMARY OF INVENTION

PROBLEMS TO BE SOLVED BY THE INVENTION

[0004]

However, when the flexing portion of the typically known medical treatment tool
25 as disclosed in Patent Literature 1 is flexed, the inflatable body is pulled in an axial direction of the insert portion, resulting in a deformation of the inflatable body. Thus, the inflatable body cannot be inflated or, on the contrary, a pressure within the inflatable body becomes excessively high to cause a deformation of the flexing portion.

[0005]

An object of the invention is to provide a medical treatment tool that is capable of appropriately inflating an inflatable body provided to a flexing portion.

MEANS FOR SOLVING THE PROBLEMS

[0006]

5 A medical treatment tool according to an aspect of the invention includes: an insert portion that is adapted to be inserted to a human body of a patient, at least a part of the insert portion being provided by a flexing portion adapted to be flexed; and an inflatable body provided on an outer circumference of the flexing portion, the inflatable body being adapted to inflate in a radial direction of the flexing portion. An axial distal
10 end portion of the inflatable body is fixed to the insert portion and a proximal end portion of the inflatable body is axially movable relative to the insert portion.

[0007]

According to the above aspect of the invention, when the flexing portion is flexed, since the proximal end portion of the inflatable body is axially moved relative to
15 the insert portion, the deformation of the inflatable body can be avoided. Thus, the inflatable body can be appropriately inflated.

[0008]

The medical treatment tool according to the above aspect preferably includes a shape retainer that is adapted to retain a shape of the flexing portion after the flexing
20 portion is flexed.

[0009]

According to the above arrangement, since the shape retainer is provided, the shape of the flexing portion after being subjected to the flexing operation can be retained by the shape retainer. Thus, since the shape of the flexing portion can be retained in
25 accordance with an insertion path of the insert portion in a human body of a patient, the inflatable body provided to the flexing portion can be easily inserted into the human body.

[0010]

In the medical treatment tool according to the above aspect, the shape retainer preferably includes: a joint structure in which a plurality of joints are connected, the joint

structure defining the flexing portion; and a manipulation member provided inside the joint structure, the manipulation member controlling a flexure of the flexing portion.

[0011]

According to the above arrangement, since the shape retainer includes the joint
5 structure defining the flexing portion and the manipulation member provided inside the
joint structure, the manipulation member can be accommodated inside the joint structure,
so that the manipulation member can be kept from being caught in a human body of a
patient. Further, since the flexing portion has the joint structure, an operation force
required for the flexing operation of the flexing portion using the manipulation member
10 can be reduced. Accordingly, the insert portion can be easily inserted into the human body
and the inserted insert portion can be easily flexed.

[0012]

In the medical treatment tool according to the above aspect, the insert portion
preferably includes therein a lumen adapted to receive therein and draw therefrom a
15 treatment tool.

[0013]

According to the above arrangement, since the insert portion has the lumen, a
treatment tool can be introduced through the lumen of the insert portion inserted into a
human body of a patient, so that the treatment tool can be easily inserted into the human
20 body.

[0014]

The medical treatment tool according to the above aspect preferably includes a
slide member fixed to the proximal end portion of the inflatable body, the slide member
being adapted to seal the inflatable body and being slidable relative to the insert portion.

25 [0015]

According to the above arrangement, since the proximal end portion of the
inflatable body is fixed to the slide member that is capable of sealing the inflatable body,
the proximal end portion of the inflatable body can be moved relative to the insert portion
in conjunction with the slide movement of the slide member while the inflatable body is

kept sealed.

[0016]

In the medical treatment tool according to the above aspect, the slide member is preferably a tubular member, and the tubular member preferably includes: a slide portion
5 fixed to the proximal end portion of the inflatable body and slidable relative to the insert portion; and a flexible portion including a first end in an axial direction of the tubular member being connected to the slide portion and a second end being fixed to the insert portion.

[0017]

10 According to the above arrangement, since the slide member is provided by the tubular member having the flexible portion and the slide portion, the proximal end portion of the inflatable body can be moved relative to the insert portion in conjunction with the slide movement of the slide portion while the flexible portion absorbs the deformation of the tubular member resulting from the flexing of the insert portion.

15 [0018]

In the medical treatment tool according to the above aspect, the slide member is preferably a sealing member fixed to the proximal end portion of the inflatable body to seal a gap between the proximal end portion and the insert portion.

[0019]

20 According to the above arrangement, since the slide member is provided by the sealing member for sealing the gap between the proximal end portion of the inflatable body and the insert portion, the proximal end portion of the inflatable body can be moved relative to the insert portion in conjunction with the slide movement of the sealing member while the inflatable body is securely sealed.

25 [0020]

In the medical treatment tool according to the above aspect, the proximal end portion of the inflatable body preferably has a stretchable part that is stretchable and contractible in an axial direction of the inflatable body, a part of the proximal end portion closer to a proximal end than the stretchable part being fixed to the insert portion.

[0021]

According to the above arrangement, since the proximal end portion of the inflatable body is stretchable and contractible, when the flexing portion is flexed, the proximal end portion of the inflatable body axially stretches to allow a movement of the proximal end portion of the inflatable body relative to the insert portion.

[0022]

In the medical treatment tool according to the above aspect, the proximal end portion of the inflatable body is preferably folded toward the distal end portion of the inflatable body to be fixed to the insert portion.

10 [0023]

According to the above arrangement, since the proximal end portion of the inflatable body is folded toward the distal end, when flexing the flexing portion, the folded portion of the inflatable body is gradually unfolded to elongate the proximal end portion of the inflatable body. Thus, the proximal end portion of the inflatable body can be moved relative to the insert portion, so that the inflatable body can be appropriately inflated.

[0024]

In the medical treatment tool according to the above aspect, a movement assisting member for assisting an axial movement of the inflatable body is preferably connected to the proximal end portion of the inflatable body.

20 [0025]

According to the above arrangement, since the movement assisting member is connected to the proximal end portion of the inflatable body, the movement of the proximal end portion of the inflatable body can be assisted by the movement assisting member, thereby easily moving the proximal end portion in the axial direction of the insert portion.

[0026]

In the medical treatment tool according to the above aspect, the medical treatment tool is preferably a treatment tool for treating sinusitis.

[0027]

According to the above arrangement, since the medical treatment tool is a paranasal sinus treatment tool and the inflatable body of the paranasal sinus treatment tool can be appropriately inflated, a stenosed area formed in a natural ostium of paranasal sinus due to sinusitis can be widened by the inflatable body for treatment.

5 BRIEF DESCRIPTION OF DRAWINGS

[0028]

Fig. 1 is a plan view showing a medical treatment tool according to a first exemplary embodiment of the invention.

Fig.2 is a partially-sectioned side elevation showing an insertion tube of the
10 medical treatment tool shown in Fig. 1.

Fig.3 is another partially-sectioned side elevation showing the insertion tube of the medical treatment tool shown in Fig. 1.

Fig. 4 is a perspective view of a manipulation member of the medical treatment tool shown in Fig. 1.

Fig.5 is a side elevation showing a flexed state of the insertion tube of the
15 medical treatment tool shown in Fig. 1.

Fig. 6 is a side elevation showing an insertion tube of a medical treatment tool according to a second exemplary embodiment of the invention.

Fig. 7 is a side elevation showing an insertion tube of a medical treatment tool
20 according to a third exemplary embodiment of the invention.

Fig. 8 is a side elevation showing an insertion tube of a medical treatment tool according to a fourth exemplary embodiment of the invention.

Fig. 9 is a side elevation showing an insertion tube of a medical treatment tool according to a fifth exemplary embodiment of the invention.

Fig. 10 is a side elevation showing an insertion tube of a medical treatment tool
25 according to a sixth exemplary embodiment of the invention.

Fig. 11 is a side elevation showing an insertion tube of a medical treatment tool according to a seventh exemplary embodiment of the invention.

Fig. 12 is a side elevation showing an insertion tube of a medical treatment tool

according to an eighth exemplary embodiment of the invention.

DESCRIPTION OF EMBODIMENT(S)

[0029]

Exemplary embodiments of the invention will be described below with reference
5 to the attached drawings.

It should be noted that components in the second and subsequent exemplary
embodiments that are the same as or functionally similar to components in the following
first exemplary embodiment will be denoted by the same reference numerals as those of
the first exemplary embodiment to omit or simplify the explanation thereof.

10 [0030]

First Exemplary Embodiment

As shown in Fig. 1, a medical treatment tool 1 includes: a hub 2; an insert portion
in a form of an insertion tube 3 that is at least partially flexible and is to be inserted into a
human body of a patient; a movable portion 4 (see Figs. 2 and 3) provided on an outer
15 circumference of the insertion tube 3 and axially movable relative to the insertion tube 3;
an inflatable body 5 provided on the outer circumference of the insertion tube 3 and
inflatable in a radial direction of the insertion tube 3; a fluid transportation channel 6 that
transports a fluid to an inside of the inflatable body 5 (see Figs. 2 and 3); and a
manipulation member 7 provided inside the insertion tube 3 for controlling the flexure of
20 the insertion tube 3.

[0031]

The hub 2 includes: an introduction channel 21 that intercommunicates a lumen
33 in the insertion tube 3 with an outside to allow a treatment tool such as an endoscope to
be introduced into the lumen 33; a fluid transportation channel 22 that is branched from
25 the introduction channel 21 so as to transport a fluid such as normal saline into a human
body and to transport a fluid in the human body to the outside; and a position fixing unit
23 that is rotatably provided to the hub 2, the position fixing unit 23 fixing a posture of the
insertion tube 3 flexed by the manipulation member 7.

[0032]

As shown in Figs. 2 and 3, the insertion tube 3 includes: a rigid tube 31 whose axial proximal end is connected to the hub 2; a flexing portion in a form of a flexible tube 32 connected to an axial distal end of the rigid tube 31; and the lumen 33 (a continuous space in the rigid tube 31 and the flexible tube 32) being adapted to receive therein and
5 draw therefrom a treatment tool such as an endoscope.

[0033]

The flexible tube 32 includes a plurality of tubular bodies 34 and 35. The tubular bodies 34 and 35 and the rigid tube 31 are axially connected to provide a joint structure in a mutually pivotable manner.

10 The tubular bodies 34 and 35 respectively include a pivot shaft 341 and a pivot shaft 351, each of which respectively projects in a connecting direction (i.e. an axial direction of each of the tubular bodies 34 and 35) from a first end thereof in the connecting direction.

On the other hand, the rigid tube 31 and the tubular bodies 35 respectively
15 include a pivot support 311 and a pivot support 352, each of which is defined by a recess formed in a second end in the connecting direction (i.e. the axial direction of the rigid tube 31 and the tubular bodies 35). The pivot support 311 supports the pivot shaft 351 of the tubular body 35 while the pivot support 352 support the pivot shaft 341 of the tubular body 34.

20 It should be noted that the pivot shaft 341 and the pivot shaft 351 are provided in pairs and the pivot support 311 and the pivot support 352 are provided in pairs at positions symmetrical with each other around central axes of the rigid tube 31 and the tubular bodies 34 and 35.

[0034]

25 The above-described insertion tube 3 is provided by, for instance, laser-processing of a stainless cylindrical member. With the use of the laser-processing, the insertion tube 3 with the rigid tube 31 and the tubular bodies 34 and 35 being connected can be easily obtained only by cutting the cylindrical member with laser. It should be understood that any material and process other than those mentioned above can be used

for producing the insertion tube 3.

[0035]

The movable portion 4 is provided by a slide member in a form of a tubular member 41 that covers the outer circumference of the insertion tube 3. The tubular member 41 is capable of sealing the inflatable body 5 and sliding relative to the insertion tube 3.

The tubular member 41 includes a slide portion 42 that is fixed to an axial proximal end portion 52 of the inflatable body 5 and is slidable relative to the insertion tube 3 and a flexible portion 43 having an axial first end connected to the slide portion 42 and an axial second end fixed to the insertion tube 3.

[0036]

The slide portion 42 is provided by a member of an excellent slip property such as a metal and a resin and is slidable on the outer circumference of the rigid tube 31.

The flexible portion 43 is provided by a flexible elastic member such as a rubber and a resin and is provided on the outer circumference of the flexible tube 32. An axial distal end of the flexible portion 43 is fixed to the insertion tube 3 whereas a proximal end of the flexible portion 43 is continuous with the slide portion 42. The flexible portion 43 closely covers the outer circumference of the flexible tube 32 to keep the fluid delivered to the inflatable body 5 from entering the flexible tube 32 through the gaps between the tubular body 34 and the tubular body 35, between the tubular bodies 35 and between the tubular body 35 and the rigid tube 31.

[0037]

The inflatable body 5 is provided by an elastic material such as a polymer plastic. An axial distal end portion 51 of the inflatable body 5 is fixed to the insertion tube 3 whereas the proximal end portion 52 of the inflatable body 5 is fixed to the slide portion 42. Thus, the proximal end portion 52 of the inflatable body 5 is axially movable relative to the insertion tube 3 via the slide portion 42. The interior of the inflatable body 5 is in communication with the fluid transportation channel 6. The fluid is introduced into the inflatable body 5 through the fluid transportation channel 6 to radially inflate the inflatable

body 5.

[0038]

The fluid transportation channel 6 is provided along the insertion tube 3. A distal end of the fluid transportation channel 6 is connected to the proximal end portion 52 of the inflatable body 5 to be in communication with the interior of the inflatable body 5. A proximal end of the fluid transportation channel 6 is connected to the position fixing unit 23 (Fig. 1) so as to be axially movable in the axial direction of the insertion tube 3 in conjunction with the proximal end portion 52 of the inflatable body 5.

[0039]

As also shown in Fig. 4, the manipulation member 7 includes: a plurality of separable members 70 that are circumferentially dividable and collectively form a tubular structure in the insertion tube 3; and an annular connecting portion 71 that connects respective axial distal ends of the separable members 70 in the tubular structure.

[0040]

Each of the plurality of separable members 70 is of the same shape. Each of the separable members 70 includes: a cutout portion 73 provided by partially cutting a circumferential side edge 72 of the separable member 70; a wide portion 74 at which the cutout 73 of the separable member 70 is not provided, the wide portion being defined in a form of a circumferentially divided cylindrical member; and a narrow portion 75 at which the cutout portion 73 of the separable member 70 is provided, the narrow portion 75 being narrower than the wide portion 74 by the presence of the cutout portion 73.

[0041]

The cutout portion 73 is provided by cutting each of both the circumferential side edges 72 at the same axial position into the same shape. It should be noted that, in the first exemplary embodiment, the cutout portion 73 is defined at a section between the connecting portion 71 and the wide portion 74.

The wide portion 74 is provided by circumferentially bisecting the cylindrical member. The circumferential side edge 72 of the wide portion 74 is of linear configuration and is axially in slidable contact with the side edge 72 of the adjacent separable member

70. In other words, the separable members 70 are designed such that the circumferential side edges 72 thereof (i.e. other than the cutout portion 73) are axially in slidable contact with each other.

The narrow portion 75 axially extends approximately at the circumferential center of each of the separable members 70 and has a constant circumferential dimension. The narrow portions 75 of the separable members 70 each are provided at positions opposed across the center of the tubular structure.

[0042]

One of the separable members 70 and the other of the separable members 70 of the manipulation member 7 are relatively moved in the axial direction, so that the opposed two narrow portions 75 are flexed in a plane passing the two narrow portions 75 to flex the flexible tube 32. Thus, the manipulation member 7 is disposed in the insertion tube 3 so that the narrow portions 75 are located between the mutually opposing pivot shafts 341 and 351 of the flexible tube 32, or, in other words, the cutout portions 73 are located at the positions of the pivot shafts 341 and 351.

[0043]

Herein, in order to increase an inner diameter of the lumen 33 of the insertion tube 3, an outer diameter of the manipulation member 7 is preferably as large as possible. Thus, the manipulation member 7 is sized such that an outer surface of the manipulation member 7 is in contact with an inner surface of the insertion tube 3.

Further, for the similar reason, the thickness of the manipulation member 7 is preferably as small as possible. Thus, the thickness of the manipulation member 7 is designed to be approximately 0.05 to 1.0 [mm], preferably 0.075 to 0.3 [mm].

[0044]

Similarly to the insertion tube 3, the above-described manipulation member 7 is provided by, for instance, laser-processing of a stainless cylindrical member. It should be understood that any material and process other than those mentioned above can be used for producing the manipulation member 7.

The manipulation member 7 and the flexible tube 32 define a shape retainer 8 that

is adapted to retain a shape of the flexible tube 32 after a flexing operation.

[0045]

The position fixing unit 23 is rotated relative to the hub 2 for flexing the flexible tube 32 of the insertion tube 3 in the above medical treatment tool 1. When the position fixing unit 23 is rotated, as shown in Fig. 5, one of the separable members 70 of the manipulation member 7 is pushed toward the distal end while the other of the separable members 70 is pulled toward the proximal end. As a result, while the adjacent circumferential side edges 72 of the separable members 70 are axially slid, an axial and relative movement occurs between the one of the separable members 70 and the other of the separable members 70. Thus, the flexible tube 32 can be flexed in accordance with the flexure of the narrow portion 75 of the manipulation member 7 while the outer surface of the manipulation member 7 is in slidable contact with the inner surface of the insertion tube 3. It should be noted that the flexed posture of the flexible tube 32 at this time can be fixed by the position fixing unit 23.

15 [0046]

The inflatable body 5 is designed such that only the distal end portion 51 is fixed to the insertion tube 3 while the proximal end portion 52 of the inflatable body 5 is axially movable relative to the insertion tube 3 via the slide portion 42 of the tubular member 41. Thus, when the flexible tube 32 is flexed, the inflatable body 5 is pulled in the axial direction of the insertion tube 3, so that, as shown in Fig. 5, the proximal end portion 52 moves toward the distal end of the insertion tube 3. As a result, since the deformation of the inflatable body 5 can be avoided, when the inflatable body 5 is inflated while the flexible tube 32 is flexed, the inflatable body 5 can be appropriately inflated.

[0047]

25 Next, the process and advantages of using the medical treatment tool 1 in a form of a sinusitis treatment tool will be described below as an example of the usage of the medical treatment tool 1.

Initially, an operator inserts the insertion tube 3 of the medical treatment tool 1 into a nostril. At this time, when an imaging unit such as an endoscope is inserted in the

insertion tube 3 in advance, the operator can insert the insertion tube 3 while checking the status inside the insertion path based on image information acquired by the imaging unit.

[0048]

When the inflatable body 5 of the inserted insertion tube 3 reaches a natural
5 ostium of a paranasal sinus stenosed by sinusitis, the operator introduces a fluid into the inflatable body 5 through the introduction channel 21 to widen the inflatable body 5 to inflate the stenosed area in the natural ostium for treatment. It should be noted that whether or not the stenosed area is widened can be checked based on the image information acquired by the imaging unit by slightly retracting the insertion tube 3 after
10 contracting the inflatable body 5.

[0049]

When the paranasal sinus is filled with a fluid (e.g. snivel) and/or a viscous substance, the insertion tube 3 is inserted into the paranasal sinus through the widened natural ostium for transferring the fluid and/or the viscous substance through the inner
15 cavity of the insertion tube 3 and the fluid transportation channel 22. In addition, a washing fluid such as normal saline may be introduced in the fluid transportation channel 22 for washing the interior of the paranasal sinus with the fluid.

[0050]

The first exemplary embodiment exemplarily offers the following advantages.

20 When the flexible tube 32 is flexed, since the proximal end portion 52 of the inflatable body 5 is axially moved relative to the insertion tube 3, the deformation of the inflatable body 5 can be avoided. Thus, the inflatable body 5 can be appropriately inflated.

[0051]

Since the shape retainer 8 is provided, the shape of the flexible tube 32 after the
25 flexing operation can be retained by the shape retainer 8. Thus, since the shape of the flexible tube 32 can be retained in accordance with the insertion path of the insertion tube 3 in a human body of a patient, the inflatable body 5 provided to the flexible tube 32 can be easily inserted into the human body.

[0052]

Since the shape retainer 8 includes the joint structure constituting the flexible tube 32 and the manipulation member 7 provided inside the joint structure and the manipulation member 7 can be accommodated inside the joint structure, the manipulation member 7 can be kept from being caught in a human body of a patient. Further, since the flexible tube 32 has the joint structure, an operation force required for the flexing operation of the flexible tube 32 using the manipulation member 7 can be reduced. As a result, the insertion tube 3 can be easily inserted into the human body and the inserted insertion tube 3 can be easily flexed.

[0053]

Since the insertion tube 3 has the lumen 33, a treatment tool such as an endoscope can be introduced through the lumen 33 of the insertion tube 3 inserted into the human body, so that the treatment tool can be easily inserted into the human body.

[0054]

Since the proximal end portion 52 of the inflatable body 5 is fixed to the slide portion 42 of the tubular member 41 that is capable of sealing the inflatable body 5, the proximal end portion 52 of the inflatable body 5 can be moved relative to the insertion tube 3 with the slide movement of the slide portion 42 while the inflatable body 5 is kept being sealed.

[0055]

Since the slide member is provided by the tubular member 41 having the flexible portion 43 and the slide portion 42, the proximal end portion 52 of the inflatable body 5 can be moved relative to the insertion tube 3 in conjunction with the slide movement of the slide portion 42 while the flexible portion 43 absorbs the deformation of the tubular member 41 in accordance with the flex of the insertion tube 3.

[0056]

Further, when the medical treatment tool 1 is a paranasal sinus treatment tool, the inflatable body 5 of the paranasal sinus treatment tool can be appropriately inflated. Accordingly, the stenosed area formed in the natural ostium of paranasal sinus due to sinusitis can be widened by the inflatable body 5 for treatment.

[0057]

Second Exemplary Embodiment

Next, a second exemplary embodiment of the invention will be described below with reference to Fig 6.

5 As shown in Fig. 6, a medical treatment tool 1A according to the second exemplary embodiment differs from the first exemplary embodiment in the presence of a slide member in a form of a sealing member 44 provided between a proximal end portion 52A of an inflatable body 5A and the insertion tube 3, and in the structure of a movable portion 4A.

10 [0058]

 The sealing member 44 is an annular member provided between the proximal end portion 52A of the inflatable body 5A and the insertion tube 3. The sealing member 44 seals a gap between the proximal end portion 52A and the insertion tube 3. The sealing member 44 is slidable relative to the insertion tube 3 in conjunction with the proximal end
15 portion 52A of the inflatable body 5A. The fluid transportation channel 6 is connected to a part of the proximal end portion 52A closer to the distal end than the sealing member 44 so that the fluid transportation channel 6 is movable in the axial direction of the insertion tube 3 in conjunction with the proximal end portion 52A. As described above, in the second exemplary embodiment, the proximal end portion 52A of the inflatable body 5A is
20 movable relative to the insertion tube 3 via the sealing member 44 and the sealing member 44 defines the movable portion 4A.

[0059]

 It should be noted that the flexible tubular member 9 (e.g. an elastic member) of the medical treatment tool 1A closely covers the outer circumference of the flexible tube
25 32 to keep the fluid delivered to the inflatable body 5A from entering the interior of the flexible tube 32 through the gaps between the tubular body 34 and the tubular body 35, between the tubular bodies 35 and between the tubular body 35 and the rigid tube 31.

[0060]

 The second exemplary embodiment exemplarily offers the following advantages

in addition to the advantages of the first exemplary embodiment.

Since the slide member is provided by the sealing member 44 for sealing the gap between the proximal end portion 52A of the inflatable body 5A and the insertion tube 3, the proximal end portion 52A of the inflatable body 5A can be moved relative to the
5 insertion tube 3 in conjunction with the slide movement of the sealing member 44 while the inflatable body 5A is securely sealed.

[0061]

Third Exemplary Embodiment

Next, a third exemplary embodiment of the invention will be described below
10 with reference to Fig 7.

As shown in Fig. 7, a medical treatment tool 1B according to the third exemplary embodiment differs from the first exemplary embodiment in the presence of an axially stretchable and contractible proximal end portion 52B of an inflatable body 5B and in the structure of a movable portion 4B.

15 [0062]

The proximal end portion 52B of the inflatable body 5B is in a form of a bellows. A part of the proximal end portion 52B near the proximal end relative to the bellows 53 is fixed to the rigid tube 31. In the third exemplary embodiment, the proximal end portion 52B of the inflatable body 5B is movable relative to the insertion tube 3 in conjunction
20 with stretch and contraction of the bellows 53 and the bellows 53 of the proximal end portion 52B defines the movable portion 4B. It should be noted that the fluid transportation channel 6 is fixed to the rigid tube 31 and to a part of the proximal end portion 52B near the proximal end relative to the bellows 53 so as to be immovable relative to the insertion tube 3.

25 [0063]

The third exemplary embodiment exemplarily offers the following advantages in addition to the advantages of the first exemplary embodiment.

Since the proximal end portion 52B of the inflatable body 5B is stretchable and contractible, when the flexible tube 32 is flexed, the proximal end portion 52B of the

inflatable body 5B axially stretches to allow a movement of the proximal end portion 52B of the inflatable body 5B relative to the insertion tube 3.

[0064]

Fourth Exemplary Embodiment

5 Next, a fourth exemplary embodiment of the invention will be described below with reference to Fig 8.

As shown in Fig. 8, a medical treatment tool 1C according to the fourth exemplary embodiment differs from the first exemplary embodiment in a proximal end portion 52C of an inflatable body 5C that is folded toward the distal end portion 51 to be
10 fixed to the insertion tube 3 and in the structure of a movable portion 4C.

[0065]

The proximal end portion 52C of the inflatable body 5C is folded toward the distal end portion 51 to form a folded portion 54. The folded portion 54 is connected to the flexible portion 43 of the tubular member 41. The slide portion 42 is not provided to the
15 tubular member 41. The folded portion 54 is fixed to the insertion tube 3 via the tubular member 41. In the fourth exemplary embodiment, the proximal end portion 52C of the inflatable body 5C is movable relative to the insertion tube 3 by the presence of the folded portion 54 and the folded portion 54 and the flexible portion 43 of the tubular member 41 define the movable portion 4C. The fluid transportation channel 6 is connected to the
20 proximal end portion 52C of the inflatable body 5C. The fluid transportation channel 6 is movable in the axial direction of the insertion tube 3 in conjunction with the proximal end portion 52C.

[0066]

The fourth exemplary embodiment exemplarily offers the following advantages
25 in addition to the advantages of the first exemplary embodiment.

Since the proximal end portion 52C of the inflatable body 5C is folded toward the distal end portion 51, when the flexible tube 32 is flexed, the folded portion 54 of the inflatable body 5C is gradually unfolded to elongate the proximal end portion 52C of the inflatable body 5C. Thus, the proximal end portion 52C of the inflatable body 5C can be

moved relative to the insertion tube 3, so that the inflatable body 5C can be appropriately inflated.

[0067]

Fifth Exemplary Embodiment

5 Next, a fifth exemplary embodiment of the invention will be described below with reference to Fig 9.

As shown in Fig. 9, a medical treatment tool 1D according to the fifth exemplary embodiment differs from the first exemplary embodiment in that a movement assisting member 10 is connected to the proximal end portion 52 of the inflatable body 5.

10 [0068]

The movement assisting member 10 is provided by a member of an excellent slip property such as a metal and a resin. The movement assisting member 10 extends on an outside of the insertion tube 3 in the axial direction of the insertion tube 3. A distal end of the movement assisting member 10 is fixed to the inflatable body 5, the tubular member
15 41 and the fluid transportation channel 6. Thus, the movement of the inflatable body 5 relative to the insertion tube 3 can be assisted by moving the movement assisting member 10 in the axial direction of the insertion tube 3.

[0069]

20 The fifth exemplary embodiment exemplarily offers the following advantages in addition to the advantages of the first exemplary embodiment.

Since the movement assisting member 10 is connected to the proximal end portion 52 of the inflatable body 5, the movement of the proximal end portion 52 of the inflatable body 5 can be assisted by the movement assisting member 10, thereby easily moving the proximal end portion 52 in the axial direction of the insertion tube 3.

25 [0070]

Sixth Exemplary Embodiment

Next, a sixth exemplary embodiment of the invention will be described below with reference to Fig 10.

As shown in Fig. 10, a medical treatment tool 1E according to the sixth

exemplary embodiment differs from the second exemplary embodiment in that the movement assisting member 10 is connected to the proximal end portion 52A of the inflatable body 5A.

[0071]

5 The movement assisting member 10 extends in the axial direction of the insertion tube 3. The distal end of the movement assisting member 10 is connected to the proximal end portion 52A of the inflatable body 5A. The fluid transportation channel 6 is provided between the movement assisting member 10 and the insertion tube 3. The distal end of the fluid transportation channel 6 is connected to a part of the proximal end portion 52A of the
10 inflatable body 5A closer to the distal end than the sealing member 44.

The sixth exemplary embodiment exemplarily offers the advantages in the fifth exemplary embodiment in addition to the advantages of the second exemplary embodiment.

[0072]

15 Seventh Exemplary Embodiment

Next, a seventh exemplary embodiment of the invention will be described below with reference to Fig 7.

As shown in Fig. 11, a medical treatment tool 1F according to the seventh exemplary embodiment differs from the third exemplary embodiment in that the
20 movement assisting member 10 is connected to the proximal end portion 52B of the inflatable body 5B.

[0073]

The movement assisting member 10 extends in the axial direction of the insertion tube 3. The distal end of the movement assisting member 10 is connected to a part of the
25 proximal end portion 52B of the inflatable body 5B closer to the proximal end than the bellows 53.

The seventh exemplary embodiment exemplarily offers the advantages in the fifth exemplary embodiment in addition to the advantages of the third exemplary embodiment.

[0074]

Eighth Exemplary Embodiment

Next, an eighth exemplary embodiment of the invention will be described below with reference to Fig 12.

As shown in Fig. 12, a medical treatment tool 1G according to the eighth
5 exemplary embodiment differs from the fourth exemplary embodiment in that the movement assisting member 10 is connected to the proximal end portion 52C of the inflatable body 5C.

The eighth exemplary embodiment exemplarily offers the advantages in the fifth exemplary embodiment in addition to the advantages of the fourth exemplary
10 embodiment.

[0075]

Incidentally, it should be understood that the scope of the present invention is not limited to the above-described exemplary embodiments but includes modifications and improvements as long as the modifications and improvements are compatible with the
15 invention.

For instance, though the insertion tube 3 is used as the insert portion and the flexible tube 32 is used as the flexing portion in the above exemplary embodiments, the insert portion and the flexing portion are not necessarily be tubular but may be solid.

[0076]

Any member is usable as the insertion tube 3 as long as at least a part of the member is flexible. For instance, an insertion tube 3 of which entirety is flexible may be used instead of the insertion tube 3 provided with the flexible tube 32 in the above exemplary embodiments, or a partially flexible insertion tube 3 may alternatively be used. Alternatively, an insertion tube 3 of which entirety is provided by the flexible tube 32 may
25 be used.

The insertion tube 3 is not necessarily cylindrical but may have a polygonal cross section.

[0077]

Though the insertion tube 3 and the manipulation member 7 are made of metal

such as stainless, the insertion tube 3 and the manipulation member 7 may be made of other materials including a resin and metal other than stainless as long as the material is flexible.

[0078]

5 Though the manipulation member 7 includes the separable members 70 that are divided into two or four pieces, the number of the divided pieces of the separable members is not limited to two or four as long as a plurality of (i.e. two or more) pieces are provided.

 The shape of the connecting portion 71 of the manipulation member 7 is not limited to that in the above exemplary embodiments but the connecting portion 71 may
10 alternatively have a tubular or linear shape. Further alternatively, the connecting portion 71 may be provided by a plurality of linear members that define bridges between the separable members 70 so that the plurality of linear members intersects at a central axis of the tubular structure of the manipulation member 7.

[0079]

15 Though the fluid transportation channel 6 in the above exemplary embodiments is provided outside and along the insertion tube 3, the fluid transportation channel 6 may alternatively be provided outside the insertion tube 3 concentrically with the insertion tube 3.

[0080]

20 Though the medical treatment tools 1 and 1A to 1G in the above exemplary embodiments are used for inspecting an interior of a paranasal sinus, widening a stenosed area in a natural ostium of a paranasal sinus and treating sinusitis, the medical treatment tools 1 and 1A to 1G may alternatively be used for inspecting and treating the other parts inside a human body.

25 INDUSTRIAL APPLICABILITY

[0081]

 The invention is applicable to a medical treatment tool used for diagnosing and treating a paranasal sinus and to a medical treatment tool for other diagnosis and treatment not accompanied by surgery.

EXPLANATION OF CODES

[0082]

- | | | |
|----|----|--|
| | 1 | medical treatment tool |
| | 3 | insertion tube (insert portion) |
| 5 | 5 | inflatable body |
| | 7 | manipulation member |
| | 8 | shape retainer |
| | 10 | movement assisting member |
| | 32 | flexible tube (flexing portion, joint structure) |
| 10 | 33 | lumen |
| | 41 | tubular member (slide member) |
| | 42 | slide portion |
| | 43 | flexible portion |
| | 44 | sealing member (slide member) |
| 15 | 52 | proximal end portion |

CLAIM(S)

1. A medical treatment tool comprising:
an insert portion that is adapted to be inserted to a human body of a patient, at least a part of the insert portion being provided by a flexing portion adapted to be flexed;
5 and
an inflatable body provided on an outer circumference of the flexing portion, the inflatable body being adapted to inflate in a radial direction of the flexing portion, wherein
an axial distal end portion of the inflatable body is fixed to the insert portion and a proximal end portion of the inflatable body is axially movable relative to the insert
10 portion.
2. The medical treatment tool according to claim 1, further comprising:
a shape retainer that is adapted to retain a shape of the flexing portion after the flexing portion is flexed.
3. The medical treatment tool according to claim 2, wherein
15 the shape retainer comprises:
a joint structure in which a plurality of joints are connected, the joint structure defining the flexing portion; and
a manipulation member provided inside the joint structure, the manipulation member controlling a flexure of the flexing portion.
- 20 4. The medical treatment tool according to any one of claims 1 to 3, wherein
the insert portion comprises therein a lumen adapted to receive therein and draw therefrom a treatment tool.
5. The medical treatment tool according to any one of claims 1 to 4, further comprising:
25 a slide member fixed to the proximal end portion of the inflatable body, the slide member being adapted to seal the inflatable body and being slidable relative to the insert portion.
6. The medical treatment tool according to claim 5, wherein
the slide member is a tubular member, and

the tubular member comprises:

a slide portion fixed to the proximal end portion of the inflatable body and slidable relative to the insert portion; and

a flexible portion comprising a first end in an axial direction of the tubular member being connected to the slide portion and a second end being fixed to the insert portion.

7. The medical treatment tool according to claim 5, wherein

the slide member is a sealing member fixed to the proximal end portion of the inflatable body to seal a gap between the proximal end portion and the insert portion.

10 8. The medical treatment tool according to any one of claims 1 to 4, wherein

the proximal end portion of the inflatable body has a stretchable part that is stretchable and contractible in an axial direction of the inflatable body, a part of the proximal end portion closer to a proximal end than the stretchable part being fixed to the insert portion.

15 9. The medical treatment tool according to any one of claims 1 to 4, wherein

the proximal end portion of the inflatable body is folded toward the distal end portion of the inflatable body to be fixed to the insert portion.

10. The medical treatment tool according to any one of claims 1 to 9, wherein

a movement assisting member for assisting an axial movement of the inflatable body is connected to the proximal end portion of the inflatable body.

11. The medical treatment tool according to any one of claims 1 to 10, wherein

the medical treatment tool is a treatment tool for treating sinusitis.

FIG. 1




FIG. 2




FIG. 3

1





FIG. 4






FIG. 6






FIG. 7














0
1
.
G
—
L

















FIG. 12

