


(10) **Patent No.:** US 11,343,670 B2
(45) **Date of Patent:** May 24, 2022



Related U.S. Application Data

continuation of application No. 15/133,589, filed on
Apr. 20, 2016, now Pat. No. 9,516,490.

(56)

References Cited

U.S. PATENT DOCUMENTS

4,301,415 A 11/1981 McFayden
4,318,055 A 3/1982 Hopwood et al.
4,342,245 A 8/1982 Gross
4,584,534 A 4/1986 Lijphart et al.
4,613,974 A 9/1986 Vokac et al.
4,680,633 A 7/1987 Gerdes et al.
4,803,705 A 2/1989 Gillingham et al.
4,989,219 A 1/1991 Gerdes et al.
5,021,786 A 6/1991 Gerdes
5,124,706 A 6/1992 Gerdes
5,155,672 A 10/1992 Brown
5,165,017 A 11/1992 Eddington et al.
5,184,218 A 2/1993 Gerdes
5,200,715 A 4/1993 Gerdes et al.
5,200,822 A 4/1993 Bronfin et al.
5,327,237 A 7/1994 Gerdes et al.
5,511,100 A 4/1996 Lundberg et al.
5,557,333 A 9/1996 Jungo et al.
6,522,697 B1 2/2003 Spickermann
6,559,757 B1 5/2003 Deller et al.
6,788,154 B2* 9/2004 Maneatis G05F 3/262
327/156
7,856,050 B1 12/2010 Wiss et al.
8,537,952 B1* 9/2013 Arora H03C 3/0925
375/354

9,014,293 B2 4/2015 Gerdes
9,194,946 B1 11/2015 Vacanti
9,516,490 B1 12/2016 Gerdes et al.
9,716,997 B1 7/2017 Gerdes et al.
9,883,375 B2 1/2018 Gerdes et al.
2003/0071684 A1 4/2003 Noon
2004/0247041 A1 12/2004 Biedka et al.
2004/0252531 A1 12/2004 Cheng et al.
2005/0065901 A1 3/2005 Diong
2005/0200391 A1* 9/2005 Steinbach H03L 7/087
327/156
2006/0006914 A1* 1/2006 Fan-Jiang H03L 7/113
327/156
2006/0197564 A1* 9/2006 Yen H03L 7/113
327/156
2007/0041485 A1 2/2007 Chang
2011/0043039 A1 2/2011 Mancebo De Castillo Fagola
2012/0155344 A1 6/2012 Wiley et al.
2012/0171963 A1 7/2012 Tsfaty
2015/0023456 A1 1/2015 Vann et al.
2017/0325085 A1 11/2017 Gerdes et al.
2018/0152833 A1 5/2018 Gerdes et al.

OTHER PUBLICATIONS

International Search Report and Written Opinion for International
Application No. PCT/US2017/028381, dated Aug. 17, 2017, 7
pages.
Extended European Search Report issued in European Application
No. 17786562.3 dated Jul. 16, 2019, 10 pages.

* cited by examiner





FIG. 1A






FIG. 2






FIG. 3A

**FIG. 3B**




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6A

TM Mod. Signal
Trad. Mod. Sig.




FIG. 6B






FIG. 8

FIG. 7

**FIG. 9**

**FIG. 10**

1

IDENTIFYING DEVICES WITH TRANSPPOSITIONAL MODULATION

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation application of U.S. patent application Ser. No. 15/880,753, filed on Jan. 26, 2018, which is a continuation application of U.S. patent application Ser. No. 15/655,380, filed on Jul. 20, 2017, now U.S. Pat. No. 9,883,375, which is a continuation application of U.S. patent application Ser. No. 15/367,482, filed on Dec. 2, 2016, now U.S. Pat. No. 9,716,997, which is a continuation of U.S. patent application Ser. No. 15/133,589, filed on Apr. 20, 2016, now U.S. Pat. No. 9,516,490, which are hereby incorporated by reference in their entirety.

BACKGROUND

Carrier modulation techniques are used to transmit information signals from one location to another. Traditional signal modulation techniques include, for example, amplitude modulation (AM), frequency modulation (FM), phase modulation (PM). In addition, complex modulation techniques exist that incorporate aspects of AM, FM, and PM such as quadrature phase shift keying (QPSK), amplitude phase shift keying (APSK) and including quadrature amplitude modulation (QAM).

SUMMARY

This specification relates to methods and systems for identifying transpositional modulation (TM) capable devices. More specifically, the specification relates to methods and systems for performing device identification and/or device discovery using TM signals. In addition, the specification relates to methods and systems for communications between devices using a combined traditional modulation and TM signal on the same carrier signal. Although discussed in the context of TM, implementations of the present disclosure also may be applicable to identifying other aspects or characteristics of various devices.

In general, innovative aspects of the subject matter described in this specification can be embodied in methods that include the actions of transmitting, by a first device, a transmission signal that includes a carrier signal modulated with a TM signal. Receiving a response signal from a second device in response to the transmission signal. Determining, whether the response signal includes the TM signal. Other implementations of this aspect include corresponding systems, apparatus, and computer programs, configured to perform the actions of the methods, encoded on computer storage devices.

These and other implementations can each optionally include one or more of the following features. Some implementations include determining that the second device is a TM capable device based on determining that the response signal includes the TM signal.

In some implementations, determining whether the response signal includes the TM signal includes mixing the response signal with a second harmonic of a carrier signal of the response signal to produce a mixed signal. In some implementations, determining whether the response signal includes the TM signal includes comparing the mixed signal to a third harmonic of the carrier signal of the response signal.

2

In some implementations, the transmission signal includes the carrier signal modulated with the TM signal and a non-TM modulation signal. In some implementations, the response signal includes a non-TM modulation signal.

5 In some implementations, determining whether the response signal includes the TM signal includes performing a separation and extraction (SEPEX) process on the response signal to remove the non-TM modulation signal.

10 In some implementations, the transmission signal includes the carrier signal modulated with a first TM signal, and determining whether the response includes the TM signal includes determining whether the response signal includes a second, different TM signal.

15 In some implementations, the second TM signal includes information about the second device. In some implementations, the information includes information identifying the second device. In some implementations, the information includes information identifying characteristics of the second device. In some implementations, the second device is installed on a vehicle, and wherein the information includes information about the vehicle. In some implementations, the information includes data from a data recorder installed on the vehicle.

25 In some implementations, the transmission signal is a RADAR signal.

In another general aspect, innovative aspects of the subject matter described in this specification can be embodied in methods that include actions of receiving, by a first device, a transmission signal from a second device, the transmission signal including a carrier signal modulated with a first transpositional modulation (TM) signal. Identifying the first TM signal within the transmission signal. Sending, to the second device, a response signal that includes data encoded within a second TM signal. Other implementations of this aspect include corresponding systems, apparatus, and computer programs, configured to perform the actions of the methods, encoded on computer storage devices.

40 These and other implementations can each optionally include one or more of the following features. In some implementations, the transmission signal includes the carrier signal modulated with the TM signal and a non-TM modulation signal. In some implementations, the response signal includes a non-TM modulation signal.

45 In some implementations, identifying the first TM signal within the transmission signal includes performing a separation and extraction (SEPEX) process on the transmission signal to remove the non-TM modulation signal.

50 In some implementations, the data encoded within the second TM signal includes information about the first device. In some implementations, the information includes information identifying characteristics of the first device. In some implementations, the first device is installed on a vehicle, and wherein the information includes information about the vehicle. In some implementations, the information includes data from a data recorder installed on the vehicle.

55 Particular implementations of the subject matter described in this specification can be implemented so as to realize one or more of the following advantages. Implementations may provide an efficient process for identifying TM capable devices. Implementations may increase the bandwidth of signals transmitted using traditional modulation schemes. Implementations may permit the combination of two differently modulated signals on a single carrier frequency. Some implementations may permit extraction of carrier signals from a modulated signal with little or no a priori information about the modulated signal. Some imple-

mentations may be capable of extracting a carrier from a modulated signal without regard to the type of modulation used in the modulated signal. In other words, some implementations may be able to extract carrier signals while being agnostic to the type of modulation of an input signal.

The details of one or more implementations of the subject matter described in this specification are set forth in the accompanying drawings and the description below. Other features, aspects, and advantages of the subject matter will become apparent from the description, the drawings, and the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A-1B depict example systems in accordance with implementations of the present disclosure.

FIG. 2 depicts a block diagram of an example TM signal transmitter in accordance with implementations of the present disclosure.

FIG. 3A depicts a block diagram of an example carrier extractor in accordance with implementations of the present disclosure.

FIG. 3B depicts a block diagram of an example frequency detector in accordance with implementations of the present disclosure.

FIGS. 4A and 4B depict example control signals generated by a carrier signal extraction device.

FIG. 5 depicts a block diagram of an example TM signal receiver in accordance with implementations of the present disclosure.

FIG. 6A depicts a block diagram of an example TM signal separation and extraction device in accordance with implementations of the present disclosure.

FIG. 6B depicts frequency domain representations of signals at various stages of the TM signal separation and extraction device shown in FIG. 6.

FIGS. 7-10 depict example processes that can be executed in accordance with implementations of the present disclosure.

Like reference numbers and designations in the various drawings indicate like elements.

DETAILED DESCRIPTION

Implementations of the present disclosure generally relate to methods and systems for identifying transpositional modulation (TM) capable devices. More specifically, implementations provide methods and systems for performing device identification and/or device discovery using TM signals. For example, TM signals can be transmitted as a device query signal and devices that are TM capable will be able to respond, while non-TM devices may not be able to respond at all or may not be able to respond with a corresponding TM signal. In addition, some implementations establish communications between devices using a combined traditional modulation and TM signal on the same carrier signal. For example, supplementary information can be carried in a TM signal combined with a traditional modulation signal that is routinely used for communications between devices. The TM signal will not interfere substantially with the traditional modulation signal, thereby, increasing the effective bandwidth of the communications between devices.

Other implementations of the present disclosure generally extract a carrier signal from an existing modulated signal, modulate the extracted carrier signal with a transposition modulation (TM) signal, and combine and retransmit the

existing signal with the TM signal on the same carrier signal. Specifically, the implementations can extract a carrier frequency from a modulated signal in which the carrier signal has been suppressed (e.g., QPSK, QAM, APSK, BPSK). A CAREX (carrier extraction) circuit determines a frequency difference between the frequency of the CAREX output signal and a weighted average of the carrier frequency of the input signal. The calculated difference value is used to continuously tune a signal generator to maintain a minimal difference between the weighted average of the input carrier frequency and the CAREX output. The third harmonic of the extracted carrier is modulated with a data signal generating a TM modulated signal. The TM modulated signal is heterodyned back to the extracted carrier frequency and combined with the existing modulated signal. The combined signal can then be transmitted. Moreover, the TM modulated signal in the combined signal does not interfere with the existing signal because the TM modulation is not recognized by demodulation systems used to demodulate traditional modulation schemes. Instead, the TM signal appears as a slight increase in noise within the existing signal.

Other implementations of the present disclosure generally receive a combined traditional modulation and TM signal on the same carrier signal then separate the TM signal from the combined signal. Specifically, the implementations can separate the existing signal from a combined signal including a traditionally modulated signal (the existing signal) and a TM modulated signal. The existing signal can be demodulated from the carrier signal. An extracted carrier signal can be re-modulated with the demodulated existing signal to re-create the existing signal alone, absent the TM modulated signal. The re-modulated existing signal can be removed from the combined signal leaving only the TM modulated signal which can be demodulated using TM demodulation techniques described herein.

As used herein the terms “Transpositional Modulation,” “TM modulation,” “TM,” and “TM signal” refer to a technique of adding information to a carrier signal without affecting the amplitude, frequency or phase of the carrier signal (or a signal that is modulated according to such a technique). More specifically, for example, the above terms refer to a type of modulation in which information is conveyed by altering (e.g., transposing, time shifting) a harmonic of a carrier signal. For example, although the present disclosure is generally directed to producing Transpositional Modulation by altering the third harmonic of a carrier signal, in some implementations Transpositional Modulation can be produced by altering other harmonics of a carrier signal (e.g., a fourth harmonic, fifth harmonic, sixth harmonic, etc.). Furthermore, Transpositional Modulation and/or TM signals are not detectable by traditional demodulators, for example, those used for amplitude, frequency, or phase modulated signals.

FIG. 1A depicts an example system **100** in accordance with implementations of the present disclosure. The system **100** is a system of communication devices **102**. The system **100** may be a radio frequency (RF) communication system, a satellite communication system, a landline communication system (e.g., a telephony or cable network), an optical communication system, a computer network, or any other system of communication devices **102**. The communication devices **102** include systems for modulating a carrier signal with an information signal using traditional modulation techniques and transmitting and receiving the modulated signal from one communication device **102** to/from another. Traditional modulation techniques include, for example, amplitude modulation (AM), frequency modulation (FM),

5

and phase modulation (PM) in addition to complex modulation techniques that incorporate aspects of AM, FM, and PM such as quadrature phase shift keying (QPSK), amplitude phase shift keying (APSK) and including quadrature amplitude modulation (QAM). In addition, communication devices B and C include a TM transmitter **104** and a TM receiver **106**. In some examples, a TM transmitter **104** and/or a TM receiver **106** can be integrated with traditional transmitters and receivers. The TM transmitter **104** and/or TM receiver **106** can be implemented as hardware devices (e.g., integrated circuits, chip-sets, application specific integrated circuits (ASIC), or field programmable logic arrays (FPGA)) or they can be implemented in software (e.g., as a software defined radio (SDR)).

The system **100** can receive a traditionally modulated signal **108** and combine the traditionally modulated signal **108** with a TM modulated signal **110** on the same carrier using a TM transmitter **104**, thereby increasing the overall bandwidth of the combined signal **112**. The TM modulated signal **110** can be separated from the combined signal **112** and demodulated by a TM receiver **106**. Likewise, the traditionally modulated signal **108** can be separately demodulated with no interference caused by the TM modulated signal **110**. This is possible because TM modulated signals are undecipherable by non-TM receivers, instead appearing as a slight increase of noise in traditionally modulated signals.

For example, communication device A may transmit a QAM signal **108** to communication device B. The TM transmitter **104** at communication device B can receive the QAM signal **108** and extract the carrier signal from the QAM signal **108**. The TM transmitter **104** modulates the extracted carrier signal with a TM signal, combines the TM modulated signal **110** with the QAM signal **108**, and retransmits the combined signal **112**. In some examples, as described below, the TM transmitter **104** can extract a carrier signal from a traditionally modulated signal **108** (e.g., the QAM signal) in which the carrier is suppressed and while having little or no a priori information about the carrier signal (e.g., frequency or phase information).

Communication device C can then receive the combined signal **112**. The TM receiver **106** of communication device C separates and extracts the TM modulated signal **110** from the combined signal **112**, and then demodulates the TM modulated signal **110** to obtain the TM modulated data signal. In some examples, as described below, the TM receiver **106** separates the TM modulated signal **110** from the combined signal **112** by demodulating traditionally modulated signal **108** (e.g., the QAM signal), re-modulating the carrier with only the traditionally modulated signal **108**, and subtracting the re-modulated carrier signal from the combined signal **112** leaving only the TM modulated signal **110**.

In some implementations, the carrier signal can be an intermediate frequency (IF) carrier signal. That is, the carrier signal is not necessarily at the same frequency of the carrier upon which the signal is ultimately be transmitted, but may be at an IF used internally within a system (e.g., a satellite communication system) as an intermediate step in either signal transmission or reception. That is, in the case of signal transmission, a system may up-convert a combined signal **112** from the IF signal to a transmission carrier frequency prior to transmitting the combined signal **112**. Conversely, in the case of signal reception, a system may down-convert a modulated signal from the transmission carrier frequency to an IF frequency before separating the TM modulated signal **110** from the combined signal **112**. In other implementa-

6

tions, an IF carrier signal may not be used, and the transmission carrier signal can be modulated with both a traditionally modulated signal and a TM modulated signal.

In some implementations, because TM signals are not detectable by traditional receivers, a TM capable device can identify whether other devices have TM reception and transmission capabilities by transmitting a carrier signal modulated with a TM signal to the other devices. For example, communication device B can send a query signal **114** that includes a carrier signal modulated with a TM signal to one or more other devices (as indicated by dashed line **115**), such as communication device A and communication device C. Communication device C, which includes a TM transmitter **104** and a TM receiver **106**, will be able to detect the TM modulation within the query signal **114**. However, communication device A, which does not include a TM transmitter **104** or a TM receiver **106**, will detect only the carrier wave of the query signal. Thus, communication device C will be able to respond to the query signal **114**, but communication device A will not. Communication device C sends a response signal **116** (as indicated by dashed line **117**) that includes a carrier signal modulated with a TM signal to communication device B. Communication device B will detect the TM signal included in the response signal **116** and, thereby, determine that communication device C is capable of TM communications.

The query signal **114** can include, for example, only a carrier signal with TM modulation (e.g., signal **110**) or a combined signal **112** including a carrier modulated with both a traditionally modulated signal **108** and a TM modulated signal **110**. In some examples, the query signal **114** can include instructions requesting information about the other device encoded in either a TM modulated signal **110**, a traditionally modulated signal **108**, or both. However, in some examples, the TM modulated signal **110** need not include any specific information or instructions because if another device is not capable of receiving TM signals the other device would not even detect the TM modulated signal **110** or the encoded information. Thus, a TM capable device need only send a response signal **116** that includes TM modulation to indicate that the device is capable of receiving TM signals.

In implementations in which the query signal **114** includes both a traditionally modulated signal **108** and a TM modulated signal **110**, devices that are not capable of TM communications (e.g., communication device A) may send a response to the non-TM portion of the query signal **114**. However, a response from a non-TM capable device would only include a traditionally modulated signal and not a TM modulated signal. Therefore, to determine whether a responding device was TM capable, the querying device (e.g., communication device B) would only need to determine whether the response included a TM modulated signal **110**. If not, the response can be ignored.

In some implementations, the response signal **116** can include information about the responding device. For example, the TM modulated portion of the response signal **116** from a TM capable device (e.g., communication device C) can include information about the device. The information can include, but is not limited to, characteristics of the device such as identifying information, location information for the device, routing tables, identifying information for other TM capable devices in communication with the responding device, network channel characteristics (e.g., noise, bandwidth), handshake data, device pairing data, authentication data (e.g., Out-Of-Band (OOB) authentication data), etc. In some examples, the query signal **114** can

include a request for particular information about the responding device. For example, the TM modulated portion of the query signal **114** from the querying device (e.g., communication device **B**) can include a request for information about the responding device. In such examples, a TM capable responding device would be able to detect the information request and provide the requested information in a response signal **116**.

FIG. **1B** depicts an example environment **130** for employing the techniques discussed above. The example environment is described in the context of vehicle safety (e.g., aviation safety, air traffic control). It is appreciated, however, that implementations of the present disclosure can be realized to identify and/or discover devices and their capabilities in other appropriate environments and contexts including, but not limited to, for example, computer networks, mobile devices (e.g., mobile phones, smartphones, tablet computers, etc.), Internet of Things (IoT) networks, computer peripherals (e.g., plug and play devices), device pairing, authentication protocols, near-field communications (NFC), inventory systems, identifying unmanned aerial vehicles (UAV) or “drones,” maritime identification, automobile toll payment systems, self-driving vehicles, traffic signal pre-emption systems (e.g., used by emergency service vehicles), broadcast and/or cablecast systems, satellite systems, etc.

The environment **130** includes an air traffic control tower **132**, an aircraft **134** that has TM capable communication equipment, and an aircraft **136** that does not have TM capable communication equipment. An air traffic control tower **132** or aircraft **134** can use the techniques described above to identify other aircraft that have TM communication capabilities. For example, the control tower **132** can transmit a transmission signal **138** that includes a TM modulated signal. For example, the transmission signal **138** can be a non-TM signal that is routinely used in aviation safety (e.g., RADAR signal, a radio signal, or an Automatic Dependent Surveillance-Broadcast (ADS-B) signal), but one that also includes a TM modulated signal added to the carrier of the non-TM signal. Aircraft **134**, which has TM capable equipment, can receive and detect both the non-TM signal and the TM signal include in the transmission signal **138**. Aircraft **134** would respond to the TM signal by sending a response signal **140** that also includes a TM signal. A receiver at the control tower **132** can receive the response signal **140** from aircraft **134** and, by identifying the TM signal within the response **140**, identify aircraft **134** as a TM capable aircraft. On the other hand, aircraft **136**, which does not have TM capable equipment, would receive and respond to only the non-TM portion of the transmission signal **138**.

As another example, aircraft **134** can transmit a transmission signal **142** that includes a TM modulated signal. Similar to the example above, the transmission signal **142** can be a non-TM signal that is routinely used in aviation safety (e.g., RADAR signal, a radio signal, or an ADS-B signal), but one that also includes a TM modulated signal added to the carrier of the non-TM signal. Aircraft **136**, which does not have TM capable equipment, would receive the transmission signal **142**, but would not detect the TM portion of the transmission signal **142**. Accordingly, aircraft **136** would send a response signal **144** that does not include a TM signal, and that is only responsive the non-TM portion of the transmission signal **142**. Accordingly, aircraft **134** can readily identify aircraft **136** as not having TM capabilities.

In some implementations, the response signal **140** from a TM capable aircraft **134** can include information about the aircraft **134**. For example, the information can include, but is not limited to, identifying information, location informa-

tion (e.g., GPS data), flight characteristics, ADS-B data, information from a flight data recorder, etc.

Once identified as TM capable, TM signals can be used to communicate additional information between two TM capable aircraft and/or between a TM capable aircraft and a TM capable control tower on the same carrier signals as other (e.g., routine) aviation signals (e.g., radio, ADS-B, and RADAR signals) without affecting the other signals. For example, flight data such as ADS-B data and/or flight data recorder data can be transmitted in the TM portions of routine aviation signals. For example, ADS-B data can be included in the TM portion of a radio communication signal.

In some examples, simply the identification of an aircraft **134** as having TM capabilities may be useful in aviation safety. For example, only particular types or classes of aircraft **134** can be equipped with TM capable receivers and transmitters. In such cases, simply identifying an aircraft as TM capable would indicate the type or class of the aircraft **134**. As another example, the aircraft's control system can be configured to turn TM capabilities on or off at particular times to indicate an operational status of the aircraft **134**. For example, when an aircraft **134** is beginning a landing approach, TM capabilities can be turned on. Thus, a control tower **132** can recognize aircraft that are preparing to land by detecting TM signals from the aircraft **134**.

In some implementations, for example, in the case where a transmission signal **138**, **142** is a RADAR signal, the response signal **140**, **144** can include a reflection of the RADAR signal off of the responding aircraft **134**, **136**. A reflection can include a reflection of both the TM and the non-TM portion of the transmitted signal **138**, **142**. Thus, in order to determine whether the responding aircraft **134**, **136** is TM capable, a TM capable responding aircraft **134**, upon detecting the TM portion of a transmitted RADAR signal, can transmit a response signal **140** in which the TM portion is modified from that of the transmitted signal **138**. For example, the TM signal in the response can be modified to have different modulation characteristics or to include data that identifies the responding aircraft **134** as being TM capable. In some implementations, a transmitting device can select to process only TM portions of a returned RADAR signal.

FIG. **2** depicts a block diagram of an example TM signal transmitter **104** in accordance with implementations of the present disclosure. The TM transmitter **104** includes a carrier extraction portion (CAREX) **206**, a harmonic generation portion **202**, a TM modulating portion **204**, and a heterodyning portion **205**. The carrier extraction portion includes the carrier extractor (CAREX) **206**. The harmonic generation portion **202** includes a second harmonic generator **208** and a third harmonic generator **210**. The TM modulating portion **204** includes a signal optimizer **212** and a TM modulator **214**. And, the heterodyning portion **205** includes a signal mixer **216**, a bandpass filter **218**, and a power amplifier **220**. In addition, the TM transmitter **104** includes a signal coupler **222** and a signal combiner **224**.

In operation, the TM transmitter **104** receives an existing modulated signal (e.g., traditionally modulated signal **108** of FIG. **1**). The signal coupler **222** samples the existing modulated signal and passes the sample of the existing modulated signal to the CAREX **206**. The CAREX **206** extracts a carrier signal (f_c) from the existing modulated signal. The CAREX **206** is described in more detail below in reference to FIGS. **3A-4B**. The output of the CAREX **206** is a pure sinusoidal signal at the fundamental frequency of the carrier from the existing modulated signal. In some examples, the CAREX **206** is agnostic to the type of modulation used in

the existing modulated signal. That is, the CAREX **206** can extract the carrier signal from an existing modulated signal regardless of the type of modulation used in the existing modulated signal. In some examples, the CAREX **206** can extract carrier signals even when the carrier is suppressed in the existing modulated signal, and can do so with little or no a priori information about existing modulated signal's carrier (e.g., frequency or phase modulation information).

The CAREX **206** passes the extracted carrier signal to a second harmonic signal generator **208** and a third harmonic signal generator **210**, which generate signals at the second and third harmonic frequencies ($2f_c$ and $3f_c$ respectively) of the fundamental carrier frequency (f_c). The second and third harmonic signals ($2f_c$, $3f_c$) are used by the TM modulation portion **204** and the heterodyning portion **205** of the TM transmitter **104** to generate a TM modulated signal and to heterodyne the TM modulated signal to the fundamental carrier frequency (f_c).

The TM modulation portion **204** of the TM transmitter **104** modulates the third harmonic ($3f_c$) of the carrier signal (f_c) with a data signal to generate the TM modulated signal. The TM modulated signal is then heterodyned to the frequency of the carrier signal (f_c), combined with the existing modulated signal, and outputted to an antenna for transmission.

In more detail, TM modulation portion **204** receives a data signal for transmission (e.g., a baseband (BB) data signal). The data signal is optionally processed for transmission as a TM modulated signal by the signal optimizer **212**. In some examples, the signal optimizer **212** produces an optional pattern of inversion and non-inversion of the modulating signal, and filters the modulating signal to ensure that the total bandwidth of the data signal is within the channel bandwidth of the existing modulated signal. In some examples, the signal optimizer **212** can include sample-and-hold circuitry and filters to prepare the modulating signal for transmission as a TM modulated signal. In some examples, the signal optimizer **212** can be bypassed or turned off and on.

The TM modulator **214** modulates the third harmonic ($3f_c$) of the carrier signal (f_c) with a data signal to generate the TM modulated signal. For example, the TM modulator **214** modulates the third harmonic ($3f_c$) by introducing a variable time delay based on the data signal. In other words, the TM modulator **214** can use the data signal as a control signal for introducing an appropriate time delay to third harmonic ($3f_c$). As such, an amount of time delay introduced into the third harmonic ($3f_c$) represents discrete bits or symbols of the data signal. The described time delay modulation technique may be considered as time-shift modulation and is performed on the third harmonic ($3f_c$) of the intended carrier frequency ($3f_c$).

The time-shift modulation of the third harmonic ($3f_c$) produces a single set of upper and lower Bessel-like sidebands. The inventor has confirmed such results in laboratory simulations with an oscilloscope and spectrum analyzer. Moreover, the bandwidth of these sidebands can be limited to the bandwidth of an intended communication channel by the optimizer **212** before TM modulation of the signal, as described above.

In some examples, the time delay may be a phase shift. However, the time-shift modulation described above is not equivalent phase modulation. As noted above, the inventor has confirmed in laboratory tests that the time-shift modulation only produces a single pair of upper and lower Bessel-like sidebands. Phase modulation, however, produces a series upper and lower Bessel-like sidebands.

The heterodyning portion **205** prepares the TM modulation signal do be combined with the existing modulated signal and transmitted by the receiver. The TM modulated signal is then heterodyned (e.g., frequency shifted) by mixer **216** down to the fundamental frequency of the carrier signal (f_c). The mixer **216** multiplies the TM modulated signal with the second harmonic of the carrier ($2f_c$) which shifts the TM modulated signal to both the fundamental carrier signal frequency (f_c) and the fifth harmonic frequency of the carrier. The bandpass filter **218** removes signal at the fifth harmonic frequency as well as any additional signals or noise outside of the bandwidth of the TM modulated signal centered at the fundamental carrier signal frequency (f_c).

The TM modulated carrier signal is amplified by power amplifier **220** and combined with the existing modulated signal by the signal combiner **224**. It may be necessary, in some examples, to adjust the phase of the TM modulated carrier signal to match the phase of the carrier in the existing modulated signal before combining the two signals.

FIG. 3A depicts a block diagram of an example CAREX **206** in accordance with implementations of the present disclosure. The CAREX **206** can be implemented as a circuit in a device such as a TM transmitter or TM receiver, for example. In some implementations, the CAREX **206** can be implemented as a standalone device for installation into in a larger system (e.g., an application specific integrated circuit (ASIC) or field programmable logic array (FPGA)). In some implementations, the CAREX **206** can be implemented in software, for example, as a set of instructions in a computing device or a digital signal processor (DSP).

The CAREX **206** operates by determining a center frequency of an input signal (e.g., either modulated or unmodulated), comparing the center frequency to the frequency of a pure sinusoidal signal produced by a signal generator to create a error signal, and adjusting the frequency of the signal generator output signal based on a control signal generated from the error signal until the error signal is minimized. Furthermore, the CAREX **206** does not require a priori information about a carrier signal to extract the carrier signal and can extract carrier signals when the carrier of the modulated signal is suppressed.

The CAREX **206** includes amplitude limiters **302a**, **302b**, filters **304a**, **304b**, frequency detectors **306a**, **306b**, signal generator **308**, difference circuit **310**, and an amplifier **312**. The amplitude limiter **302a** and filter **304a** condition input signal before the input signal is analyzed by the first frequency detector **306a**. The amplitude limiter **302a** removes any variations in the amplitude of the input signal. In other words, the amplitude limiter **302a** stabilizes the amplitude of the input signal. In some examples, the amplitude limiters **302a**, **302b** can be an analog comparator or an automatic gain control (AGC) circuit. The filters **304a**, **304b** are bandpass filters and removes extraneous signals (e.g., harmonics) and noise outside the channel bandwidth of the input signal.

The frequency detectors **306a** and **306b** can be frequency discriminators or quadrature detectors. The first frequency detector **306a** detects the center frequency of the input signal. As shown in the frequency domain plot **320**, an input signal produced by traditional modulation techniques generally has symmetric sidebands **322** located on either side of the carrier frequency **324**. The frequency detector **306a** can determine a center frequency of an input signal based on, for example, the frequencies of the outer edges of the sidebands **322**. Furthermore, the frequency detector **306a** can use the

11

sidebands 322 of an input signal to determine the center frequency even if the carrier signal 324 is suppressed, as illustrated by the dotted line.

The signal generator 308 generates a pure sinusoidal signal (e.g., a single frequency signal) which is provided to a second frequency detector 306b. The signal generator 308 can be, for example, a voltage controlled oscillator (VCO) such as, but not limited to, a voltage controlled LC (inductor-capacitor) oscillator circuit, a voltage controlled crystal oscillator (VCXO), or a temperature-compensated VCXO. The second frequency detector 306b detects the frequency of the output signal from the signal generator 308. In some examples, the output signal from the signal generator 308 is provided to an amplitude limiter 302b and filter 304b before being transmitted to the second frequency detector 306b. The amplitude limiter 302b and filter 304b stabilize and filter the amplitude of the signal generator output signal similar to amplitude limiter 302a and filter 304a.

The output from each of the first and second frequency detectors 306a, 306b is provided as inputs to the differencing circuit 310. The output of both the first and second frequency detectors 306a, 306b can be, in some examples, a direct current (DC) voltage signal representing the center frequency of the input signal and the frequency of the signal generator 308 output signal, respectively. The output of the difference circuit 310 is a error signal representing the difference in frequency between the center frequency of the input signal in the signal generator output signal. The error signal (e.g., a DC voltage) is amplified by amplifier 312 and provided as a control signal to the signal generator 308. The amplifier 312 can be, for example, a high gain integrating circuit that integrates the inputted error signal over time to produce the control signal.

The signal generator 308 adjusts the frequency of its output signal based on the control signal until the frequency of the signal generator 308 output is matched to the center frequency of the input signal. The DC value of the control signal is used to control the frequency of the signal generator output, as shown in FIG. 4B and described below. The signal generator output is provided as the output of the CAREX 206. Frequency domain plot 330 and time domain plot 334 represent an example CAREX 206 output signal. As shown, the output signal of the CAREX 206 is a pure sinusoidal signal having a frequency 332 equivalent to the fundamental carrier frequency of the input signal.

In some implementations, the frequency detectors 306a and 306b are matched. In some examples, the matched frequency detectors 306a and 306b have similar frequency to DC output characteristics over changing modulated input frequencies. In some examples, the matched frequency detectors 306a and 306b have similar thermal and aging properties. In some examples, the amplitude limiters 302a and 302b, and the filters 304a and 304b are matched.

In some examples, when the error signal is minimized the signal generator output is effectively matched to the center frequency of the input signal. For example, the error signal can be considered as minimized when its magnitude is zero or substantially close to zero (e.g., when the control signal has a magnitude that is negligible in relation signal magnitudes measureable or usable by components of the CAREX 206). In some examples, the error signal is considered to be minimized when its magnitude is below a threshold value (e.g., an error tolerance threshold).

In some implementations, the CAREX 206 is adapted to extract carrier frequencies from single sideband signals. In some examples, the CAREX 206 includes a controller that offsets the output signal of the signal generator 308 by an

12

appropriate offset frequency. For example, the output of the frequency generator 308 can be offset after it is fed back to the second frequency detector 306b, so as to not adversely affect the control signal. In some examples, the first frequency detector 306a can be configured to determine a frequency offset based on the bandwidth of the input signal. In such examples, the first frequency detector 306a can adjust the detected frequency by the frequency offset.

FIG. 3B is a block diagram of an example frequency detector 306 in accordance with implementations of the present disclosure. The frequency detector 306 illustrated in FIG. 3B is an example quadrature-based detector circuit. The frequency detector 306 includes a phase shift network 350, a signal mixer 352, and a filter 354. The phase shift network 350 is a frequency sensitive circuit, such as an all pass filter, for example, that causes a phase shift in an input signal that corresponds with the frequency of the input signal. In other words, the phase shift network 350 causes a change in the phase angle of the input signal relative to the frequency of the input signal. In some examples, the phase shift network 350 is tuned to produce a nominal phase shift of 90 degrees (e.g., quadrature to the input signal) for a nominal design frequency (e.g., a 70 MHz IF for a communication system).

The signal mixer 352 can be, for example, a signal multiplier. The signal mixer 352 receives the input signal and an output signal from the phase shift network 350 as inputs. The filter 354 is a low pass filter.

Plot 360 shows example signals at various points in the frequency detector 306. The input signal (Signal A) is passed to the phase shift network 350 and the signal mixer 352. Signal A is shown as a sinusoid for simplicity, however, Signal A can be a modulated signal. Signal B is the output of the phase shift network 350 and is phase shifted relative to the input signal (Signal A). The value of the phase shift corresponds to the frequency of Signal A, and is nominally 90 degrees for a design frequency. Deviations from the design frequency resulting in a phase shift of Signal B that deviates from the nominal 90 degrees. The input signal (Signal A) is mixed with the output of the phase shift network 350 (Signal B) to produce Signal C (e.g., Signal C=Signal A×Signal B). Signal C has a DC offset component corresponding to the phase difference between Signals A and B, and by extension, to the frequency of Signal A. The low pass filter 354 then removes the high frequency components of Signal C leaving only the DC component (Signal D). The deviation of Signal B's phase shift from the a nominal 90 degrees is exaggerated in plot 360 in order to clearly show the resulting DC output signal (Signal D).

FIG. 4A depicts a plot 400 of an example control signal 402 generated in an example CAREX 206. The plotted control signal 402 is an example of the input signal to the signal generator 308 of FIG. 3A. The plotted control signal 452 is broken into several regions (406-410). The regions illustrate a variations 404 in the control signal 402 as the input signal to the CAREX 206 is switched between several different input signals, each modulated using a different type of modulation. The input signal in region 406 is a QPSK modulated signal. The input signal in region 408 is a QAM modulated signal. The input signal in region 410 is an unmodulated carrier signal. Each of the input signals in regions 406-410 is applied to a 70 MHz carrier. The plot 400 illustrates the robustness of the CAREX 206 and its adaptability to extracting carrier signals from various input signals without regard to the types of modulation applied to the carrier signal.

13

FIG. 4B depicts a plot 450 of another example control signal 452 generated in an example CAREX 206. The plotted control signal 452 is an example of the input signal to the signal generator 308 of FIG. 3A. The plotted control signal 452 is broken into several regions (456-460). The regions illustrate transitions 454 of the control signal 452 as the input signal to the CAREX 206 is switched between several different input signals, each having a different carrier frequency. The input signal in region 456 is a 67 MHz carrier signal. The input signal in region 458 is a 73 MHz carrier signal. The input signal in region 460 is a 70 MHz carrier signal. The plot 450 illustrates the robustness of the CAREX 206 and its adaptability to extracting different frequency carrier signals. In some implementations, as shown, the CAREX 206 loop can be designed for a specific center frequency (e.g., 70 MHz as shown). For example, the design center frequency can be a specific carrier frequency or IF of a communication system such as a satellite or radio frequency (RF) communication system, for example.

FIG. 5 depicts a block diagram of an example TM signal receiver 106 in accordance with implementations of the present disclosure. The TM receiver 106 includes a carrier extraction portion (e.g., CAREX 506), a harmonic generation portion 504, a signal separation and extraction portion (SEPEX) device 512, and a TM demodulator 514. As in the TM transmitter 104, the harmonic generation portion includes a second harmonic generator 508 and a third harmonic generator 510. In addition, the TM receiver 106 can include a signal splitter 502 to split a combined input signal (e.g. combined signal 112 of FIG. 1) between the TM receiver 106 and a signal receiver for traditional modulated signals.

In operation, the TM receiver 106 receives a combined input signal and provides the combined signal to both the CAREX 506 and SEPEX device 512. As described above in reference to the TM receiver 106, the CAREX 506 extracts a carrier signal (f_c) from the combined signal, and the second harmonic generator 508 and third harmonic generator 510, respectively, generate second and third harmonics ($2f_c$ and $3f_c$) of the extracted fundamental carrier frequency (f_c). Both the carrier signal (f_c) and second harmonic signal ($2f_c$) are provided to the SEPEX device 512. The third harmonic signal ($3f_c$) is provided to the TM demodulator 514.

The TM demodulation portion 504 separates and extracts the traditionally modulated signal from the combined signal to obtain the TM modulated signal. The SEPEX device 512 provides the TM modulated signal to the TM demodulator 514, which, demodulates the TM modulated signal to obtain a baseband data signal. The SEPEX device 512 separates and extracts the TM modulated signal from the combined signal. In some implementations, before outputting the TM modulated signal, the SEPEX device 512 heterodynes (e.g., up-shifts) the TM modulated signal to the third harmonic frequency ($3f_c$) for demodulation. The SEPEX device 512 is described in more detail below in reference to FIG. 6.

The TM demodulator 514 uses the third harmonic signal ($3f_c$) provided by the third harmonic generator 210 as a reference signal for TM demodulation. The TM demodulator 514 demodulates the TM signal by sensing the time shifts between TM modulated carrier signal from the SEPEX device 512 and the third harmonic signal ($3f_c$). In some examples, the TM demodulator 514 can be a phase detection circuit. In some implementations, the TM demodulator 514 detects the time shifts by determining a correlation between the TM modulated carrier signal and the third harmonic signal ($3f_c$) based on, for example, a product of the two signals.

14

FIG. 6A depicts a block diagram of an example TM signal SEPEX device 512 in accordance with implementations of the present disclosure. The SEPEX device 512 can be implemented as a circuit in a device such as a TM receiver, for example. In some implementations, the SEPEX device 512 can be implemented as a standalone device for installation into in a larger system (e.g., an application specific integrated circuit (ASIC) or field programmable logic array (FPGA)). In some implementations, the SEPEX device 512 can be implemented in software, for example, as a set of instructions in a computing device or a digital signal processor (DSP).

In operation, the SEPEX device 512 demodulates the traditionally modulated signal from the combined signal. Because the TM modulation is not detected by traditional signal demodulation, the resulting signal does not include the TM signal, but only the demodulated data signal from the traditional modulation signal. A “clean” (e.g., un-modulated) carrier is then re-modulated with the previously demodulated data signal from the traditional modulation signal. The SEPEX 512 computes the difference between the combined signal and the re-modulated signal to obtain a TM modulated carrier signal. In other words, the SEPEX device 512 removes a traditionally modulated signal from the combined signal by demodulating the traditionally modulated signal, re-modulating a “clean” (e.g., un-modulated) carrier, and subtracting the re-modulated signal from the combined signal, thereby, leaving only the TM modulated carrier.

The SEPEX device 512 includes a signal demodulator 602, a signal modulator 604, low-pass filters 606a, 606b, a summing circuit 608, a difference circuit 610, a delay circuit 612, a mixer 614, a bandpass filter 616, and an amplitude limiter 618. The demodulator 602 is a non-TM signal demodulator, and the modulator 604 is a non-TM signal modulator. That is, the demodulator 602 and modulator 604 are traditional modulation type (e.g., AM, FM, PM, QAM, APSK, etc.) demodulator and modulator. The demodulator 602 and modulator 604 are depicted as a complex (e.g., quadrature and in-phase) demodulator and modulator, however, in some examples the demodulator 602 and modulator 604 can be a simple (e.g., single phase) demodulator and modulator.

The operation the SEPEX device 512 is described below in more detail and with reference to FIGS. 6A and 6B. FIG. 6B depicts frequency domain representations of signals (A-F) at various stages of the SEPEX device 512. The demodulator 602 receives the combined signal (A) (e.g. combined signal 112 of FIG. 1) as one input, and the carrier signal (f_c) from the CAREX 506 as a second input. The combined signal includes both a traditionally modulated signal and a TM modulated signal. As shown by signal (A) in FIG. 6B, the combined signal includes frequency content from both the TM modulated signal and the traditionally modulated signal centered about the carrier frequency (f_c). The demodulator 602 demodulates the traditional modulated signal from the combined signal producing a baseband data signal. As noted above, because the TM modulation is not detected by traditional signal demodulation, the resulting baseband data signal does not include a TM signal.

In the case of complex modulation, the demodulator 602 demodulates both the in-phase and quadrature phase of the combined signal producing an in-phase and a quadrature phase baseband data signal. The low-pass filters 606a and 606b remove any extraneous signals or noise from the baseband data signals, for example, harmonics introduced by the demodulation process. The resulting baseband data

15

signal, shown by signal (B), includes only the frequency content from the traditionally modulated signal centered at zero frequency (baseband). More specifically, a TM modulated signal does not exist at baseband, and thus, the TM modulated signal is removed by converting the traditionally modulated signal to baseband.

The modulator **604** receives the baseband data signals (e.g., in-phase and quadrature phase signals) as a first input, and the carrier signal (f_c) from the CAREX **506** as a second input. The modulator **604** re-modulates the un-modulated carrier signal (f_c) from the CAREX **506** with the baseband data signals resulting in re-modulated carriers (re-modulated in-phase and quadrature phase carriers) having only the traditionally modulated signal. The in-phase and quadrature phase re-modulated carriers are combined by the summing circuit **608** (signal (C)). FIG. 6B signal (C) shows the re-modulated signal again centered about the carrier frequency (f_c). In some examples, the carrier signal (f_c) may be phase shifted or delayed to account for delays introduced into the baseband data signals during the demodulation and filtering process. This is to ensure that the resulting re-modulated signal is in phase with the combined signal.

The re-modulated signal is subtracted from the combined signal by the difference circuit **610** removing the traditionally modulated signal from the combined signal. The resulting signal, shown by signal (D), includes only the TM modulated carrier signal (f_c). The combined signal is delayed by the delay circuit **612** to account for delays introduced into the re-modulated signal by the demodulation and re-modulation process.

The TM modulated signal is heterodyned (e.g., up-shifted) to the third harmonic ($3f_c$) by the mixer **614**. The mixer **614** multiplies the TM modulated signal with the second harmonic ($2f_c$) of the carrier from the second harmonic generator **508** producing signal (E). Heterodyning the TM modulated carrier signal (f_c) with the second harmonic ($2f_c$) shifts the TM modulated signal to both the third harmonic ($3f_c$) and the negative carrier frequency ($-f_c$) (e.g., a phase inverted version of the TM modulated signal at the carrier frequency). The bandpass filter **616** removes the phase inverted TM signal at the carrier frequency leaving only the TM modulated third harmonic ($3f_c$) (signal (F)), and the optional amplitude limiter **618** removes any variations in the amplitude of the TM modulated third harmonic signal.

In some examples, the SEPEX device **512** can include multiple different types of demodulators **602** and modulators **604**. For example, the SEPEX device **512** can include FM, PM, and QAM demodulators **602** and modulators **604**. In such examples, the SEPEX device **512** can also include a control device that detects the type of traditional modulation on input signal, and sends the input signal to the appropriate set of demodulator and modulator.

Although the SEPEX device **512** is described in the context of separating and extracting a TM modulated signal from a traditionally modulated signal, in some implementations, the SEPEX device **512** can be modified to separate two traditionally modulated signals such as separating non-quadrature modulated signals (e.g., in-phase modulated signal) and quadrature modulated signals. For example, a non-quadrature modulated signal could be separated and extracted from a combined I/Q modulated signal by modifying the SEPEX device **512** shown in FIG. 6A such that only the quadrature modulated signal is demodulated and demodulated by demodulator **602** and modulator **604**.

FIG. 7 depicts an example process **700** for identifying TM capable devices that can be executed in accordance with

16

implementations of the present disclosure. In some examples, the example process **700** can be provided as computer-executable instructions executed using one or more processing devices (e.g., a digital signal processor) or computing devices. In some examples, the process **700** may be hardwired electrical circuitry, for example, as an ASIC or an FPGA device. In some examples, the process **700** may be executed by a software defined radio (SDR).

A signal that includes a carrier signal modulated with a transposition modulation (TM) signal is transmitted (**702**). For example, the signal can be transmitted by an electronic device in a query or discovery request to determine whether devices within range of the signal have TM capabilities. In some implementations, the transmitted signal can include a non-TM signal on the same carrier signal as the TM signal.

A response to the transmitted signal is received (**704**). For example, a second device may receive the transmitted signal and send a response signal. If the second device has TM receiving and transmitting capabilities, the second device can send a response that includes a carrier signal modulated with a TM signal. If the second device does not have TM receiving and transmitting capabilities, the second device will not be able to detect the TM portion of the transmitted signal. Consequently, a non-TM capable second device can only respond to a non-TM portion of the transmitted signal.

It is determined whether the response signal includes a TM signal (**706**). For example, upon receiving the response, the transmitting device can analyze the response to determine whether it includes a TM signal. That is, the transmitting device can analyze the response signal to determine if the carrier includes any TM modulation. If the response includes TM modulation the transmitting device can determine that the second device has TM capabilities. If the response does not include TM modulation, the transmitting device can determine that the second device does not have TM capabilities.

In some implementations, the response can include information about the second device. For example, the second device can include information about the device in a TM portion of a response signal. The information can include, but is not limited to, characteristics of the second device such as identifying information, location information for the device, routing tables, identifying information for other TM capable devices in communication with the second device, network channel characteristics (e.g., noise, bandwidth), etc.

In some implementations, TM modulation can be detected in a signal by mixing a received signal with a second harmonic of the carrier signal. As discussed above in reference to FIGS. 5, 6A, and 6B, mixing the received signal with a second harmonic of its carrier signal will shift the received signal to both the third harmonic ($3f_c$) and the negative carrier frequency ($-f_c$) (e.g., a phase inverted version of the received signal at the carrier frequency) in the frequency domain. This mixed signal can be filtered to remove the phase inverted version that is at the carrier frequency. Any TM modulation in the received signal can be detected by comparing the filtered mixed signal to an unmodulated third harmonic of the carrier signal. The TM modulation can be detected by detecting time shifts in the filtered mixed signal compared with the unmodulated third harmonic of the carrier. For example, if time shifts are not detected, then there is likely no TM modulation. If time shifts are detected, then the received signal includes TM modulation and the filtered mixed signal can be sent to a TM demodulator (e.g., TM demodulator **514** of FIG. 5) to be demodulated. In some implementations, for example when a signal includes a non-TM signal, a separation and extraction

(SEPEX) process (such as that described above in reference to FIGS. 6A and 6B and below in reference to FIG. 10) can be performed on the signal to remove the non-TM signal.

FIG. 8 depicts an example process 800 for providing device identification data that can be executed in accordance with implementations of the present disclosure. In some examples, the example process 800 can be provided as computer-executable instructions executed using one or more processing devices (e.g., a digital signal processor) or computing devices. In some examples, the process 800 may be hardwired electrical circuitry, for example, as an ASIC or an FPGA device. In some examples, the process 800 may be executed by an SDR.

A transmission signal that includes a carrier signal modulated with a first transposition modulation (TM) signal is received (802). For example, the transmission signal can be transmitted by an electronic device in a query or discovery request to determine whether a device that receives the transmission signal ("receiving device") has TM capabilities. In some implementations, the transmitted signal can include a non-TM signal on the same carrier signal as the TM signal.

The first TM signal is identified within the transmission signal (804). For example, upon receiving the transmission signal, the receiving device can analyze the transmission signal to determine whether it includes a TM signal. That is, the receiving device can analyze the transmission signal to determine if the carrier includes any TM modulation. For example, the receiving device can detect and demodulate a TM signal using the processes described above in reference to FIGS. 5-7. In some implementations, for example when a transmission signal includes a non-TM signal, a separation and extraction (SEPEX) process (such as that described above in reference to FIGS. 6A and 6B and below in reference to FIG. 10) can be performed on the signal to remove the non-TM signal.

A response signal that includes information encoded within a second TM signal is sent (806). For example, if the receiving device is TM capable, the receiving device can send information back to a device that sent the transmission signal within the TM signal included in a response to the transmission signal. The information can include, but is not limited to, characteristics of the receiving device such as identifying information, location information for the device, routing tables, identifying information for other TM capable devices in communication with the receiving device, network channel characteristics (e.g., noise, bandwidth), etc.

FIG. 9 depicts an example process 900 for extracting a carrier frequency from an input signal that can be executed in accordance with implementations of the present disclosure. In some examples, the example process 900 can be provided as computer-executable instructions executed using one or more processing devices (e.g., a digital signal processor) or computing devices. In some examples, the process 900 may be hardwired electrical circuitry, for example, as an ASIC or an FPGA device. In some examples, the process 900 may be executed by an SDR.

A center frequency of an input signal is detected (902). For example, the center frequency can be detected based on frequency side lobes of the input signal. In some examples, the input signal can include the carrier signal modulated with the modulation signal. In some examples, the input signal is a carrier signal modulated with a traditional modulation signal and a TM modulation signal. A frequency of a second signal is detected (904). For example, the second signal may be the output of a single generator such as, for example, a VCO or a VCXO. A difference signal (e.g., control signal) is determined based on the center frequency

of the input signal and the frequency of the second signal (906). For example, the difference signal represents a difference in frequency between the center frequency of the input signal and the frequency of the second signal. In some examples, difference signal is a DC voltage signal.

The frequency of the second signal is modified based on the difference signal to provide the carrier signal of the input signal (908), and the second signal is outputted as the carrier signal from the device performing the process 900 (910). For example, a difference signal can be a control signal for the signal generator and can cause the single generator to adjust the frequency of its output signal. The frequency of the second signal is modified until it is matched to the center frequency of the input signal. In some examples, the frequency of the second signal is matched to the center frequency of the input signal when the difference signal reaches a minimum value. In some examples, the minimum value may be a threshold value indicating that the difference between the frequency of the second signal in the center frequency of input signal is within an allowable tolerance. In some examples, the minimum value may be a magnitude of the different signal voltage that is below the threshold minimum voltage magnitude.

FIG. 10 depicts an example process 1000 for separating TM signals from input signals that can be executed in accordance with implementations of the present disclosure. In some examples, the example process 1000 can be provided as computer-executable instructions executed using one or more processing devices (e.g., a digital signal processor) or computing devices. In some examples, the process 1000 may be hardwired electrical circuitry, for example, as an ASIC or an FPGA device. In some examples, the process 1000 may be executed by an SDR.

An input signal including a carrier signal modulated with a first modulation signal and a second modulation signal is received (1002). For example, the first modulation signal may be a traditional type of modulation signal such as, for example, FM, AM, PM, QAM, APSK, etc. The second modulation signal may be a TM modulation signal. The first modulation signal is demodulated from the input signal (1004). For example, the first modulation signal can be demodulated using traditional the modulation techniques. Because traditional demodulation techniques do not recognize TM modulation, the resulting demodulated first modulation signal will not include the TM modulation signal.

The carrier signal is re-modulated using the demodulated first modulation signal to generate a third signal (1006). For example, the third signal includes an un-modulated carrier signal modulated with the first modulation signal. The un-modulated carrier signal has the same frequency as the carrier of the input signal. The first modulation signal is removed from the input signal by subtracting the third signal from the input signal (1008) to extract the second modulation signal (e.g., the TM modulation signal) from the input signal. In some examples, the input signal must be delayed an appropriate amount of time to ensure that it is in phase with the third signal. That is, due to the demodulation and re-modulation process the third signal may be out of phase with the original input signal. Thus, before subtracting the third signal from the input signal, the input signal can be delayed an appropriate amount of time. The extracted second modulation signal is provided to a signal demodulator (1010). For example, an extracted TM modulated signal can be provided to a TM signal demodulator for demodulation.

While the present disclosure is generally directed to generating transpositional modulated signals and demodulating transpositional modulated signals using a third har-

monic of a carrier signal, in some implementations transpositional modulated signals can be generated and demodulated by using other harmonics of a carrier signal (e.g., a fourth harmonic, fifth harmonic, sixth harmonic, etc.).

As used herein the term “vehicle” refers to a manned or unmanned mobile machine that transports people or cargo. For example, vehicles can include, but are not limited to, bicycles, motor vehicles (e.g., motorcycles, cars, trucks, buses), railed vehicles (e.g., trains, trams), watercraft (e.g., ships, boats), aircraft (e.g., planes, helicopters, UAVs) and spacecraft.

Implementations of the subject matter and the operations described in this specification can be realized in analog or digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. Implementations of the subject matter described in this specification can be realized using one or more computer programs, i.e., one or more modules of computer program instructions, encoded on computer storage medium for execution by, or to control the operation of, data processing apparatus. Alternatively or in addition, the program instructions can be encoded on an artificially generated propagated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus for execution by a data processing apparatus. A computer storage medium can be, or be included in, a computer-readable storage device, a computer-readable storage substrate, a random or serial access memory array or device, or a combination of one or more of them. Moreover, while a computer storage medium is not a propagated signal; a computer storage medium can be a source or destination of computer program instructions encoded in an artificially generated propagated signal. The computer storage medium can also be, or be included in, one or more separate physical components or media (e.g., multiple CDs, disks, or other storage devices).

The operations described in this specification can be implemented as operations performed by a data processing apparatus on data stored on one or more computer-readable storage devices or received from other sources.

The term “data processing apparatus” encompasses all kinds of apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, a system on a chip, or multiple ones, or combinations, of the foregoing. The apparatus can include special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application-specific integrated circuit). The apparatus can also include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, a cross-platform runtime environment, a virtual machine, or a combination of one or more of them. The apparatus and execution environment can realize various different computing model infrastructures, such as web services, distributed computing and grid computing infrastructures.

A computer program (also known as a program, software, software application, script, or code) can be written in any form of programming language, including compiled or interpreted languages, declarative or procedural languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, object, or other unit suitable for use in a computing envi-

ronment. A computer program can, but need not, correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub-programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

The processes and logic flows described in this specification can be performed by one or more programmable processors executing one or more computer programs to perform actions by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application-specific integrated circuit).

Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read-only memory or a random access memory or both. Elements of a computer can include a processor for performing actions in accordance with instructions and one or more memory devices for storing instructions and data. Moreover, a computer can be embedded in another device, e.g., a mobile telephone, a personal digital assistant (PDA), a mobile audio or video player, a game console, a Global Positioning System (GPS) receiver, or a portable storage device (e.g., a universal serial bus (USB) flash drive), to name just a few. Devices suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto-optical disks; and CD-ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

While this specification contains many specific implementation details, these should not be construed as limitations on the scope of any implementation of the present disclosure or of what can be claimed, but rather as descriptions of features specific to example implementations. Certain features that are described in this specification in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable sub-combination. Moreover, although features can be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination can be directed to a sub-combination or variation of a sub-combination.

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multitasking and parallel processing can be advantageous. Moreover, the separation of various system

21

components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

Thus, particular implementations of the subject matter have been described. Other implementations are within the scope of the following claims. In some cases, the actions recited in the claims can be performed in a different order and still achieve desirable results. In addition, the processes depicted in the accompanying figures do not necessarily require the particular order shown, or sequential order, to achieve desirable results. In certain implementations, multitasking and parallel processing can be advantageous.

What is claimed is:

1. A method for establishing telecommunications between communication devices, the method comprising:

transmitting, by a first communication device having a transpositional modulating (TM) capable radio transmitter, a query signal that includes a carrier signal modulated with a first TM signal;

receiving a response signal from a second communication device in response to the query signal; and

selectively establishing communications with the second communication device based on determining whether the response signal includes a second TM signal containing information about the second communication device.

2. The method of claim 1, further comprising determining that the second communication device is a TM capable device based on determining that the response signal includes the TM signal.

3. The method of claim 1, wherein selectively establishing communications with the second communication comprises establishing communications with the second communication device in response to determining that the second communication device is a TM capable device.

4. The method of claim 1, wherein the query signal includes the carrier signal modulated with the TM signal and a non-TM modulation signal.

5. The method of claim 1, wherein the response signal includes a non-TM modulation signal.

6. The method of claim 1, wherein selectively establishing communications with the second communication comprises establishing communications with the second communication device in response to determining that the response signal includes the second TM signal containing the information about the second communication device.

7. The method of claim 1, wherein selectively establishing communications with the second communication comprises ceasing communications with the second communication device in response to determining that the response signal does not include the second TM signal containing the information about the second communication device.

8. The method of claim 1, wherein the information about the second device includes characteristics of the second communication device.

9. The method of claim 1, wherein the information about the second device includes handshake data for establishing communications with the first communication device.

10. The method of claim 1, wherein the information about the second device includes device paring data.

22

11. The method of claim 1, wherein the information about the second device includes device authentication data or user authentication data.

12. The method of claim 1, wherein the second TM signal includes information about network channel characteristics.

13. A method for establishing telecommunications between communication devices, the method comprising:

receiving, by a second communication device, a query signal from a first communication device, the query signal including a carrier signal modulated with a first transpositional modulation (TM) signal;

identifying the first TM signal within the query signal; and

in response to identifying the first TM signal, sending, by the second communication device to the first communication device, a response signal that includes information about the second communication device encoded within a second TM signal.

14. The method of claim 13, wherein the query signal includes the carrier signal modulated with the TM signal and a non-TM modulation signal.

15. The method of claim 13, wherein the response signal includes a non-TM modulation signal.

16. The method of claim 13, wherein the information about the second device includes characteristics of the second communication device.

17. The method of claim 13, wherein the information about the second device includes handshake data for establishing communications with the first communication device.

18. The method of claim 13, wherein the information about the second device includes device paring data.

19. The method of claim 13, wherein the information about the second device includes device authentication data or user authentication data.

20. A method for establishing telecommunications between communication devices, the method comprising:

transmitting, by a first communication device, a query signal that includes a first carrier signal modulated with a first modulation signal and a second modulation signal, wherein the second modulation signal does not interfere with the first modulation signal, and wherein the second modulation signal conveys information without directly altering an amplitude, a phase, or a frequency of the first carrier signal;

receiving a response signal from a second communication device in response to the query signal, the response signal including a second carrier signal modulated with a third modulation signal and a fourth modulation signal, wherein the fourth modulation signal does not interfere with the third modulation signal, and wherein the fourth modulation signal conveys information without directly altering an amplitude, a phase, or a frequency of the second carrier signal; and

selectively establishing communications with the second communication device based on determining whether the fourth modulation signal contains information about the second communication device.

* * * * *