



US 20130120064A1

(19) **United States**(12) **Patent Application Publication**
SORRELLS et al.(10) **Pub. No.: US 2013/0120064 A1**(43) **Pub. Date: May 16, 2013**(54) **SYSTEMS AND METHODS OF RF POWER TRANSMISSIONS, MODULATION, AND AMPLIFICATION, INCLUDING CARTESIAN 4-BRANCH EMBODIMENTS**(71) Applicant: **ParkerVision, Inc.**, Jacksonville, FL (US)(72) Inventors: **David F. SORRELLS**, Middleburg, FL (US); **Gregory S. RAWLINS**, Chuluota, FL (US); **Michael W. RAWLINS**, Lake Mary, FL (US)(73) Assignee: **ParkerVision, Inc.**, Jacksonville, FL (US)(21) Appl. No.: **13/734,193**(22) Filed: **Jan. 4, 2013****Related U.S. Application Data**


(63) Continuation of application No. 11/599,390, filed on Nov. 15, 2006, now Pat. No. 8,351,870, which is a continuation of application No. 11/512,359, filed on Aug. 30, 2006, now Pat. No. 7,526,261, which is a continuation of application No. 11/256,172, filed on Oct. 24, 2005, now Pat. No. 7,184,723.

(60) Provisional application No. 60/620,972, filed on Oct. 22, 2004, provisional application No. 60/671,542, filed on Apr. 15, 2005, provisional application No.

60/671,536, filed on Apr. 15, 2005, provisional application No. 60/673,397, filed on Apr. 21, 2005, provisional application No. 60/706,003, filed on Aug. 8, 2005, provisional application No. 60/709,092, filed on Aug. 18, 2005, provisional application No. 60/717,244, filed on Sep. 16, 2005, provisional application No. 60/721,114, filed on Sep. 28, 2005.

Publication Classification(51) **Int. Cl.**
H03F 3/45 (2006.01)
(52) **U.S. Cl.**
CPC **H03F 3/45071** (2013.01)
USPC **330/252**(57) **ABSTRACT**

Methods and systems for vector combining power amplification are disclosed herein. In one embodiment, a plurality of signals are individually amplified, then summed to form a desired time-varying complex envelope signal. Phase and/or frequency characteristics of one or more of the signals are controlled to provide the desired phase, frequency, and/or amplitude characteristics of the desired time-varying complex envelope signal. In another embodiment, a time-varying complex envelope signal is decomposed into a plurality of constant envelope constituent signals. The constituent signals are amplified equally or substantially equally, and then summed to construct an amplified version of the original time-varying envelope signal. Embodiments also perform frequency up-conversion.






FIG.1




FIG. 1A





FIG.1B






FIG. 1D




FIG. 1E




FIG.2




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D





FIG.4






FIG.6






FIG. 7A








FIG. 8B





FIG. 8C






FIG.9A




FIG. 9B




FIG.10




FIG.10A




FIG. 11





FIG.12






FIG. 12B





FIG. 13



4316




FIG.14




FIG.15




FIG.15A




FIG.16




FIG. 17




FIG. 17A






FIG. 17B








FIG.19





FIG.20







FIG. 22






FIG. 24




FIG. 25




FIG.26




FIG. 27




FIG.28




FIG.29





FIG.30






FIG.32




FIG.33




FIG.34




FIG.35




FIG.36




FIG.37




FIG. 38




FIG.39




FIG.40




FIG. 41




FIG.42




FIG.43




FIG.44




FIG.45




FIG.46




FIG. 47




FIG. 48




FIG. 49




FIG.50




FIG. 51A




FIG. 51B




FIG. 51C





FIG. 51D






FIG.51F





FIG. 51G



2 INPUT MULTIPLE INPUT/SINGLE OUTPUT AMPLIFIER WITH
OPTIONAL DRIVER AND PRE-DRIVER

FIG.51H




FIG. 51I

SYSTEMS AND METHODS OF RF POWER TRANSMISSIONS, MODULATION, AND AMPLIFICATION, INCLUDING CARTESIAN 4-BRANCH EMBODIMENTS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application is a continuation of U.S. patent application Ser. No. 11/599,390, filed Nov. 15, 2006, which is a continuation of U.S. patent application Ser. No. 11/512,359 filed on Aug. 30, 2006, which is a continuation of U.S. patent application Ser. No. 11/256,172, which claims the benefit of U.S. Provisional Patent Application No. 60/620,972 filed on Oct. 22, 2004, U.S. Provisional Patent Application No. 60/671,542 filed on Apr. 15, 2005, U.S. Provisional Patent Application No. 60/671,536 filed on Apr. 15, 2005, U.S. Provisional Patent Application No. 60/673,397 filed on Apr. 21, 2005, U.S. Provisional Patent Application No. 60/706,003 filed on Aug. 8, 2005, U.S. Provisional Patent Application No. 60/709,092 filed on Aug. 18, 2005, U.S. Provisional Patent Application No. 60/717,244 filed on Sep. 16, 2005, and U.S. Provisional Patent Application No. 60/721,114 filed on Sep. 28, 2005, all of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

[0002] 1. Field of the Invention

[0003] The present invention relates generally to modulation and on-frequency power amplification. More particularly, the invention relates to methods and systems for vector combining power amplification.

[0004] 2. Background Art

[0005] In power amplifiers, a complex tradeoff typically exists between linearity and power efficiency.

[0006] Linearity is determined by a power amplifier's operating range on a characteristic curve that relates its input to output variables—the more linear the operating range the more linear the power amplifier is said to be. Linearity is a desired characteristic of a power amplifier. In one aspect, for example, it is desired that a power amplifier uniformly amplifies signals of varying amplitude, and/or phase and/or frequency. Accordingly, linearity is an important determiner of the output signal quality of a power amplifier.

[0007] Power efficiency can be calculated using the relationship of the total power delivered to a load divided by the total power supplied to the amplifier. For an ideal amplifier, power efficiency is 100%. Typically, power amplifiers are divided into classes which determine the amplifier's maximum theoretical power efficiency. Power efficiency is clearly a desired characteristic of a power amplifier—particularly, in wireless communication systems where power consumption is significantly dominated by the power amplifier.

[0008] Unfortunately, the traditional tradeoff between linearity and efficiency in power amplifiers is such that the more linear a power amplifier is the less power efficient it is. For example, the most linear amplifier is biased for class A operation, which is the least efficient class of amplifiers. On the other hand, higher class amplifiers such as class B, C, D, E, etc., are more power efficient, but are considerably non-linear which can result in spectrally distorted output signals.

[0009] The tradeoff described above is further accentuated by typical wireless communication signals. Wireless communication signals, such as OFDM, CDMA, and W-CDMA for

example, are generally characterized by their peak-to-average power ratios. The larger the signal's peak to average ratio the more non-linear distortion will be produced when non-linear amplifiers are employed.

[0010] Outphasing amplification techniques have been proposed for RF amplifier designs. In several aspects, however, existing outphasing techniques are deficient in satisfying complex signal amplification requirements, particularly as defined by wireless communication standards, for example.

[0011] In one aspect, existing outphasing techniques employ an isolating and/or a combining element when combining constant envelope constituents of a desired output signal. For example, it is commonly the case that a power combiner is used to combine the constituent signals. This combining approach, however, typically results in a degradation of output signal power due to insertion loss and limited bandwidth, and, correspondingly, a decrease in power efficiency.

[0012] In another aspect, the typically large size of combining elements precludes having them in monolithic amplifier designs.

[0013] What is needed therefore are power amplification methods and systems that solve the deficiencies of existing power amplifying techniques while maximizing power efficiency and minimizing non-linear distortion. Further, power amplification methods and systems that can be implemented without the limitations of traditional power combining circuitry and techniques are needed.

BRIEF SUMMARY OF THE INVENTION

[0014] Embodiments for vector combining power amplification are disclosed herein.

[0015] In one embodiment, a plurality of substantially constant envelope signals are individually amplified, then combined to form a desired time-varying complex envelope signal. Phase and/or frequency characteristics of one or more of the signals are controlled to provide the desired phase, frequency, and/or amplitude characteristics of the desired time-varying complex envelope signal.

[0016] In another embodiment, a time-varying complex envelope signal is decomposed into a plurality of substantially constant envelope constituent signals. The constituent signals are amplified, and then re-combined to construct an amplified version of the original time-varying envelope signal.

[0017] Embodiments of the invention can be practiced with modulated carrier signals and with baseband information and clock signals. Embodiments of the invention also achieve frequency up-conversion. Accordingly, embodiments of the invention represent integrated solutions for frequency up-conversion, amplification, and modulation.

[0018] Embodiments of the invention can be implemented with analog and/or digital controls. The invention can be implemented with analog components or with a combination of analog components and digital components. In the latter embodiment, digital signal processing can be implemented in an existing baseband processor for added cost savings.

[0019] Additional features and advantages of the invention will be set forth in the description that follows. Yet further features and advantages will be apparent to a person skilled in the art based on the description set forth herein or may be learned by practice of the invention. The advantages of the invention will be realized and attained by the structure and

methods particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0020] It is to be understood that both the foregoing summary and the following detailed description are exemplary and explanatory and are intended to provide further explanation of embodiments of the invention as claimed.

BRIEF DESCRIPTION OF THE FIGURES

[0021] Embodiments of the present invention will be described with reference to the accompanying drawings, wherein generally like reference numbers indicate identical or functionally similar elements. Also, generally, the leftmost digit(s) of the reference numbers identify the drawings in which the associated elements are first introduced.

[0022] FIG. 1A is an example that illustrates the generation of an exemplary time-varying complex envelope signal.

[0023] FIG. 1B is another example that illustrates the generation of an exemplary time-varying complex envelope signal.

[0024] FIG. 1C is an example that illustrates the generation of an exemplary time-varying complex envelope signal from the sum of two or more constant envelope signals.

[0025] FIG. 1D illustrates the power amplification of an example time-varying complex envelope signal according to an embodiment of the present invention.

[0026] FIG. 1E is a block diagram that illustrates a vector power amplification embodiment of the present invention.

[0027] FIG. 1 illustrates a phasor representation of a signal.

[0028] FIG. 2 illustrates a phasor representation of a time-varying complex envelope signal.

[0029] FIGS. 3A-3C illustrate an example modulation to generate a time-varying complex envelope signal.

[0030] FIG. 3D is an example that illustrates constant envelope decomposition of a time-varying envelope signal.

[0031] FIG. 4 is a phasor diagram that illustrates a Cartesian 4-Branch Vector Power Amplification (VPA) method of an embodiment of the present invention.

[0032] FIG. 5 is a block diagram that illustrates an exemplary embodiment of the Cartesian 4-Branch VPA method.

[0033] FIG. 6 is a process flowchart embodiment for power amplification according to the Cartesian 4-Branch VPA method.

[0034] FIG. 7A is a block diagram that illustrates an exemplary embodiment of a vector power amplifier for implementing the Cartesian 4-Branch VPA method.

[0035] FIG. 7B is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the Cartesian 4-Branch VPA method.

[0036] FIG. 8A is a block diagram that illustrates another exemplary embodiment of a vector power amplifier according to the Cartesian 4-Branch VPA method.

[0037] FIG. 8B is a block diagram that illustrates another exemplary embodiment of a vector power amplifier according to the Cartesian 4-Branch VPA method.

[0038] FIG. 8C is a block diagram that illustrates another exemplary embodiment of a vector power amplifier according to the Cartesian 4-Branch VPA method.

[0039] FIG. 8D is a block diagram that illustrates another exemplary embodiment of a vector power amplifier according to the Cartesian 4-Branch VPA method.

[0040] FIGS. 9A-9B are phasor diagrams that illustrate a Cartesian-Polar-Cartesian-Polar (CPCP) 2-Branch Vector Power Amplification (VPA) method of an embodiment of the present invention.

[0041] FIG. 10 is a block diagram that illustrates an exemplary embodiment of the CPCP 2-Branch VPA method.

[0042] FIG. 10A is a block diagram that illustrates another exemplary embodiment of the CPCP 2-Branch VPA method.

[0043] FIG. 11 is a process flowchart embodiment for power amplification according to the CPCP 2-Branch VPA method.

[0044] FIG. 12 is a block diagram that illustrates an exemplary embodiment of a vector power amplifier for implementing the CPCP 2-Branch VPA method.

[0045] FIG. 12A is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the CPCP 2-Branch VPA method.

[0046] FIG. 12B is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the CPCP 2-Branch VPA method.

[0047] FIG. 13 is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the CPCP 2-Branch VPA method.

[0048] FIG. 13A is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the CPCP 2-Branch VPA method.

[0049] FIG. 14 is a phasor diagram that illustrates a Direct Cartesian 2-Branch Vector Power Amplification (VPA) method of an embodiment of the present invention.

[0050] FIG. 15 is a block diagram that illustrates an exemplary embodiment of the Direct Cartesian 2-Branch VPA method.

[0051] FIG. 15A is a block diagram that illustrates another exemplary embodiment of the Direct Cartesian 2-Branch VPA method.

[0052] FIG. 16 is a process flowchart embodiment for power amplification according to the Direct Cartesian 2-Branch VPA method.

[0053] FIG. 17 is a block diagram that illustrates an exemplary embodiment of a vector power amplifier for implementing the Direct Cartesian 2-Branch VPA method.

[0054] FIG. 17A is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the Direct Cartesian 2-Branch VPA method.

[0055] FIG. 17B is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the Direct Cartesian 2-Branch VPA method.

[0056] FIG. 18 is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the Direct Cartesian 2-Branch VPA method.

[0057] FIG. 18A is a block diagram that illustrates another exemplary embodiment of a vector power amplifier for implementing the Direct Cartesian 2-Branch VPA method.

[0058] FIG. 19 is a process flowchart that illustrates an I and Q transfer function embodiment according to the Cartesian 4-Branch VPA method.

[0059] FIG. 20 is a block diagram that illustrates an exemplary embodiment of an I and Q transfer function according to the Cartesian 4-Branch VPA method.

[0060] FIG. 21 is a process flowchart that illustrates an I and Q transfer function embodiment according to the CPCP 2-Branch VPA method.

[0061] FIG. 22 is a block diagram that illustrates an exemplary embodiment of an I and Q transfer function according to the CPCP 2-Branch VPA method.

[0062] FIG. 23 is a process flowchart that illustrates an I and Q transfer function embodiment according to the Direct Cartesian 2-Branch VPA method.

[0063] FIG. 24 is a block diagram that illustrates an exemplary embodiment of an I and Q transfer function according to the Direct Cartesian 2-Branch VPA method.

[0064] FIG. 25 is a phasor diagram that illustrates the effect of waveform distortion on a representation of a signal phasor.

[0065] FIG. 26 illustrates magnitude to phase transform functions according to an embodiment of the present invention.

[0066] FIG. 27 illustrates exemplary embodiments of biasing circuitry according to embodiments of the present invention.

[0067] FIG. 28 illustrates a method of combining constant envelope signals according to an embodiment the present invention.

[0068] FIG. 29 illustrates a vector power amplifier output stage embodiment according to the present invention.

[0069] FIG. 30 is a block diagram of a power amplifier (PA) output stage embodiment.

[0070] FIG. 31 is a block diagram of another power amplifier (PA) output stage embodiment.

[0071] FIG. 32 is a block diagram of another power amplifier (PA) output stage embodiment.

[0072] FIG. 33 is a block diagram of another power amplifier (PA) output stage embodiment according to the present invention.

[0073] FIG. 34 is a block diagram of another power amplifier (PA) output stage embodiment according to the present invention.

[0074] FIG. 35 is a block diagram of another power amplifier (PA) output stage embodiment according to the present invention.

[0075] FIG. 36 is a block diagram of another power amplifier (PA) output stage embodiment according to the present invention.

[0076] FIG. 37 illustrates an example output signal according to an embodiment of the present invention.

[0077] FIG. 38 illustrates an exemplary PA embodiment.

[0078] FIG. 39 illustrates an example time-varying complex envelope PA output signal and a corresponding envelop signal.

[0079] FIG. 40 illustrates example timing diagrams of a PA output stage current.

[0080] FIG. 41 illustrates exemplary output stage current control functions.

[0081] FIG. 42 is a block diagram of another power amplifier (PA) output stage embodiment.

[0082] FIG. 43 illustrates an exemplary PA stage embodiment.

[0083] FIG. 44 illustrates an exemplary waved-shaped PA output signal.

[0084] FIG. 45 illustrates a power control method.

[0085] FIG. 46 illustrates another power control method.

[0086] FIG. 47 illustrates an exemplary vector power amplifier embodiment.

[0087] FIG. 48 is a process flowchart for implementing output stage current shaping according to an embodiment of the present invention.

[0088] FIG. 49 is a process flowchart for implementing harmonic control according to an embodiment of the present invention.

[0089] FIG. 50 is a process flowchart for power amplification according to an embodiment of the present invention.

[0090] FIGS. 51A-I illustrate exemplary multiple-input single-output (MISO) output stage embodiments.

[0091] The present invention will be described with reference to the accompanying drawings. The drawing in which an element first appears is typically indicated by the leftmost digit(s) in the corresponding reference number.

DETAILED DESCRIPTION OF THE INVENTION

[0092]

Table of Contents

1. Introduction	
1.1. Example Generation of Time-Varying Complex Envelope Input Signals	
1.2. Example Generation of Time-Varying Complex Envelope Signals from Constant Envelope Signals	
1.3. Vector Power Amplification Overview	
2. General Mathematical Overview	
2.1. Phasor Signal Representation	
2.2. Time-Varying Complex Envelope Signals	
2.3. Constant Envelope Decomposition of Time-Varying Envelope Signals	
3. Vector Power Amplification (VPA) Methods and Systems	
3.1. Cartesian 4-Branch Vector Power Amplifier	
3.2. Cartesian-Polar-Cartesian-Polar (CPCP) 2-Branch Vector Power Amplifier	
3.3. Direct Cartesian 2-Branch Vector Power Amplifier	
3.4. I and Q Data to Vector Modulator Transfer Functions	
3.4.1. Cartesian 4-Branch VPA Transfer Function	
3.4.2. CPCP 2-Branch VPA Transfer Function	
3.4.3. Direct Cartesian 2-Branch VPA Transfer Function	
3.4.4. Magnitude to Phase Shift Transform	
3.4.4.1. Magnitude to Phase Shift Transform for Sinusoidal Signals	
3.4.4.2. Magnitude to Phase Shift Transform for Square Wave Signals	
3.4.5. Waveform Distortion Compensation	
3.5. Output Stage	
3.5.1. Output Stage Embodiments	
3.5.2. Output Stage Current Shaping	
3.5.3. Output Stage Protection	
3.6. Harmonic Control	
3.7. Power Control	
3.8. Exemplary Vector Power Amplifier Embodiment	
4. Summary	
5. Conclusions	

1. INTRODUCTION

[0093] Methods, apparatuses and systems for vector combining power amplification are disclosed herein.

[0094] Vector combining power amplification is an approach for optimizing linearity and power efficiency simultaneously. Generally speaking, and referring to flowchart 502 in FIG. 50, in step 504 a time-varying complex envelope input signal, with varying amplitude and phase, is decomposed into constant envelope constituent signals. In step 506, the constant envelope constituent signals are amplified, and then in step 508 summed to generate an amplified version of the input complex envelope signal. Since substantially constant envelope signals may be amplified with minimal concern for non-linear distortion, the result of summing the constant envelope signals suffers minimal non-linear distortion while providing optimum efficiency.

[0095] Accordingly, vector combining power amplification allows for non-linear power amplifiers to be used to efficiently amplify complex signals whilst maintaining minimal non-linear distortion levels.

[0096] For purposes of convenience, and not limitation, methods and systems of the present invention are sometimes referred to herein as vector power amplification (VPA) methods and systems.

[0097] A high-level description of VPA methods and systems according to embodiments of the present invention is now provided. For the purpose of clarity, certain terms are first defined below. The definitions described in this section are provided for convenience purposes only, and are not limiting. The meaning of these terms will be apparent to persons skilled in the art(s) based on the entirety of the teachings provided herein. These terms may be discussed throughout the specification with additional detail.

[0098] The term signal envelope, when used herein, refers to an amplitude boundary within which a signal is contained as it fluctuates in the time domain. Quadrature-modulated signals can be described by $r(t) = i(t) \cdot \cos(\omega_c t) + q(t) \cdot \sin(\omega_c t)$ where $i(t)$ and $q(t)$ represent in-phase and quadrature signals with the signal envelope $e(t)$, being equal to $e(t) = \sqrt{i(t)^2 + q(t)^2}$ and the phase angle associated with $r(t)$ is related to $\arctan(q(t)/i(t))$.

[0099] The term constant envelope signal, when used herein, refers to in-phase and quadrature signals where $e(t) = \sqrt{i(t)^2 + q(t)^2}$, with $e(t)$ having a relatively or substantially constant value.

[0100] The term time-varying envelope signal, when used herein, refers to a signal having a time-varying signal envelope. A time-varying envelope signal can be described in terms of in-phase and quadrature signals as $e(t) = \sqrt{i(t)^2 + q(t)^2}$, with $e(t)$ having a time-varying value.

[0101] The term phase shifting, when used herein, refers to delaying or advancing the phase component of a time-varying or constant envelope signal relative to a reference phase.

1.1) Example Generation of Complex Envelope Time-Varying Input Signals

[0102] FIGS. 1A and 1B are examples that illustrate the generation of time-varying envelope and phase complex input signals. In FIG. 1A, time-varying envelope carrier signals **104** and **106** are input into phase controller **110**. Phase controller **110** manipulates the phase components of signals **104** and **106**. In other words, phase controller **110** may phase shift signals **104** and **106**. Resulting signals **108** and **112**, accordingly, may be phased shifted relative to signals **104** and **106**. In the example of FIG. 1A, phase controller **110** causes a phase reversal (180 degree phase shift) in signals **104** and **106** at time instant t_o , as can be seen from signals **108** and **112**. Signals **108** and **112** represent time-varying complex carrier signals. Signals **108** and **112** have both time-varying envelopes and phase components. When summed, signals **108** and **112** result in signal **114**. Signal **114** also represents a time-varying complex signal. Signal **114** may be an example input signal into VPA embodiments of the present invention (for example, an example input into step **504** of FIG. **50**).

[0103] Time-varying complex signals may also be generated as illustrated in FIG. 1B. In FIG. 1B, signals **116** and **118** represent baseband signals. For example, signals **116** and **118** may be in-phase (I) and quadrature (Q) baseband components of a signal. In the example of FIG. 1B, signals **116** and **118** undergo a zero crossing as they transition from +1 to -1. Signals **116** and **118** are multiplied by signal **120** or signal **120** phase shifted by 90 degrees. Signal **116** is multiplied by a 0

degree shifted version of signal **120**. Signal **118** is multiplied by a 90 degree shifted version of signal **120**. Resulting signals **122** and **124** represent time-varying complex carrier signals. Note that signals **122** and **124** have envelopes that vary according to the time-varying amplitudes of signals **116** and **118**. Further, signals **122** and **124** both undergo phase reversals at the zero crossings of signals **116** and **118**. Signals **122** and **124** are summed to result in signal **126**. Signal **126** represents a time-varying complex signal. Signal **126** may represent an example input signal into VPA embodiments of the present invention. Additionally, signals **116** and **118** may represent example input signals into VPA embodiments of the present invention.

1.2) Example Generation of Time-Varying Complex Envelope Signals from Constant Envelope Signals

[0104] The description in this section generally relates to the operation of step **508** in FIG. **50**. FIG. 1C illustrates three examples for the generation of time-varying complex signals from the sum of two or more substantially constant envelope signals. A person skilled in the art will appreciate, however, based on the teachings provided herein that the concepts illustrated in the examples of FIG. 1C can be similarly extended to the case of more than two constant envelope signals.

[0105] In example 1 of FIG. 1C, constant envelope signals **132** and **134** are input into phase controller **130**. Phase controller **130** manipulates phase components of signals **132** and **134** to generate signals **136** and **138**, respectively. Signals **136** and **138** represent substantially constant envelope signals, and are summed to generate signal **140**. The phasor representation in FIG. 1C, associated with example 1 illustrates signals **136** and **138** as phasors P_{136} and P_{138} , respectively. Signal **140** is illustrated as phasor P_{140} . In example 1, P_{136} and P_{138} are symmetrically phase shifted by an angle ϕ_1 relative to a reference signal assumed to be aligned with the real axis of the phasor representation. Correspondingly, time domain signals **136** and **138** are phase shifted in equal amounts but opposite directions relative to the reference signal. Accordingly, P_{140} , which is the sum of P_{136} and P_{138} , is in-phase with the reference signal.

[0106] In example 2 of FIG. 1C, substantially constant envelope signals **132** and **134** are input into phase controller **130**. Phase controller **130** manipulates phase components of signals **132** and **134** to generate signals **142** and **144**, respectively. Signals **142** and **144** are substantially constant envelope signals, and are summed to generate signal **150**. The phasor representation associated with example 2 illustrates signals **142** and **144** as phasors P_{142} and P_{144} , respectively. Signal **150** is illustrated as phasor P_{150} . In example 2, P_{142} and P_{144} are symmetrically phase shifted relative to a reference signal. Accordingly, similar to P_{140} , P_{150} is also in-phase with the reference signal. P_{142} and P_{144} , however, are phase shifted by an angle whereby $\phi_2 \neq \phi_1$ relative to the reference signal. P_{150} , as a result, has a different magnitude than P_{140} of example 1. In the time domain representation, it is noted that signals **140** and **150** are in-phase but have different amplitudes relative to each other.

[0107] In example 3 of FIG. 1C, substantially constant envelope signals **132** and **134** are input into phase controller **130**. Phase controller **130** manipulates phase components of signals **132** and **134** to generate signals **146** and **148**, respectively. Signals **146** and **148** are substantially constant envelope signals, and are summed to generate signal **160**. The phasor representation associated with example 3 illustrates

signals **146** and **148** as phasors P_{146} and P_{148} , respectively. Signal **160** is illustrated as phasor P_{160} . In example 3, P_{146} is phased shifted by an angle ϕ_3 relative to the reference signal. P_{148} is phase shifted by an angle ϕ_4 relative to the reference signal. ϕ_3 and ϕ_4 may or may not be equal. Accordingly, P_{160} , which is the sum of P_{146} and P_{148} , is no longer in-phase with the reference signal. P_{160} is phased shifted by an angle Θ relative to the reference signal. Similarly, P_{160} is phase shifted by Θ relative to P_{140} and P_{150} of examples 1 and 2. P_{160} may also vary in amplitude relative to P_{140} as illustrated in example 3.

[0108] In summary, the examples of FIG. 1C demonstrate that a time-varying amplitude signal can be obtained by the sum of two or more substantially constant envelope signals (Example 1). Further, the time-varying signal can have amplitude changes but no phase changes imparted thereon by equally shifting in opposite directions the two or more substantially constant envelope signals (Example 2). Equally shifting in the same direction the two or more constant envelope constituents of the signal, phase changes but no amplitude changes can be imparted on the time-varying signal. Any time-varying amplitude and phase signal can be generated using two or more substantially constant envelope signals (Example 3).

[0109] It is noted that signals in the examples of FIG. 1C are shown as sinusoidal waveforms for purpose of illustration only. A person skilled in the art will appreciate based on the teachings herein that other types of waveforms may also have been used. It should also be noted that the examples of FIG. 1C are provided herein for the purpose of illustration only, and may or may not correspond to a particular embodiment of the present invention.

1.3) Vector Power Amplification Overview

[0110] A high-level overview of vector power amplification is now provided. FIG. 1D illustrates the power amplification of an exemplary time-varying complex input signal **172**. Signals **114** and **126** as illustrated in FIGS. 1A and 1B may be examples of signal **172**. Further, signal **172** may be generated by or comprised of two or more constituent signals such as **104** and **106** (FIG. 1A), **108** and **112** (FIG. 1A), **116** and **118** (FIG. 1B), and **122** and **124** (FIG. 1B).

[0111] In the example of FIG. 1D, VPA **170** represents a VPA system embodiment according to the present invention. VPA **170** amplifies signal **172** to generate amplified output signal **178**. Output signal **178** is amplified efficiently with minimal distortion.

[0112] In the example of FIG. 1D, signals **172** and **178** represent voltage signals $V_{in}(t)$ and $V_{out}(t)$, respectively. At any time instant, in the example of FIG. 1D, $V_{in}(t)$ and $V_{out}(t)$ are related such that $V_{out}(t) = K V_{in}(t + t')$, where K is a scale factor and t' represents a time delay that may be present in the VPA system. For power implication,

$$\frac{V_{out}^2(t)}{Z_{out}} > \frac{V_{in}^2(t)}{Z_{in}},$$

where output signal **178** is a power amplified version out in of input signal **172**.

[0113] Linear (or substantially linear) power amplification of time-varying complex signals, as illustrated in FIG. 1D, is achieved according to embodiments of the present as shown in FIG. 1E.

[0114] FIG. 1E is an example block diagram that conceptually illustrates a vector power amplification embodiment according to embodiments of the present invention. In FIG. 1E, input signal **172** represents a time-varying complex signal. For example, input signal **172** may be generated as illustrated in FIGS. 1A and 1B. In embodiments, signal **172** may be a digital or an analog signal. Further, signal **172** may be a baseband or a carrier-based signal.

[0115] Referring to FIG. 1E, according to embodiments of the present invention, input signal **172** or equivalents thereof are input into VPA **182**. In the embodiment of FIG. 1E, VPA **182** includes a state machine **184** and analog circuitry **186**. State machine **184** may include digital and/or analog components. Analog circuitry **186** includes analog components. VPA **182** processes input signal **172** to generate two or more signals **188**-{**1**, ..., **n**}, as illustrated in FIG. 1E. As described with respect to signals **136**, **138**, **142**, **144**, and **146**, **148**, in FIG. 1C, signals **188**-{**1**, ..., **n**} may or may not be phase shifted relative to each other over different periods of time. Further, VPA **182** generates signals **188**-{**1**, ..., **n**} such that a sum of signals **188**-{**1**, ..., **n**} results in signal **194** which, in certain embodiments, can be an amplified version of signal **172**.

[0116] Still referring to FIG. 1E, signals **188**-{**1**, ..., **n**} are substantially constant envelope signals. Accordingly, the description in the prior paragraph corresponds to step **504** in FIG. 50.

[0117] In the example of FIG. 1E, generally corresponding to step **506** in FIG. 50, constant envelope signals **188**-{**1**, ..., **n**} are each independently amplified by a corresponding power amplifier (PA) **190**-{**1**, ..., **n**} to generate amplified signals **192**-{**1**, ..., **n**}. In embodiments, PAs **190**-{**1**, ..., **n**} amplify substantially equally respective constant envelope signals **188**-{**1**, ..., **n**}. Amplified signals **192**-{**1**, ..., **n**} are substantially constant envelope signals, and in step **508** are summed to generate output signal **194**. Note that output signal **194** can be a linearly (or substantially linearly) amplified version of input signal **172**. Output signal **194** may also be a frequency-upconverted version of input signal **172**, as described herein.

2. GENERAL MATHEMATICAL OVERVIEW

2.1) Phasor Signal Representation

[0118] FIG. 1 illustrates a phasor representation \vec{R} **102** of a signal $r(t)$. A phasor representation of a signal is explicitly representative of the magnitude of the signal's envelope and of the signal's phase shift relative to a reference signal. In this document, for purposes of convenience, and not limitation, the reference signal is defined as being aligned with the real (Re) axis of the orthogonal space of the phasor representation. The invention is not, however, limited to this embodiment. The frequency information of the signal is implicit in the representation, and is given by the frequency of the reference signal. For example, referring to FIG. 1, and assuming that the real axis corresponds to a $\cos(\omega t)$ reference signal, phasor \vec{R} would translate to the function $r(t) = R(t) \cos(\omega t + \phi(t))$, where R is the magnitude of \vec{R} .

[0119] Still referring to FIG. 1, it is noted that phasor \vec{R} can be decomposed into a real part phasor \vec{I} and an imaginary part phasor \vec{Q} . \vec{I} and \vec{Q} are said to be the in-phase and

quadrature phasor components of \vec{R} with respect to the reference signal. It is further noted that the signals that correspond to \vec{I} and \vec{Q} are related to $r(t)$ as $I(t)=R(t)\cdot\cos(\phi(t))$ and $Q(t)=R(t)\cdot\sin(\phi(t))$, respectively. In the time domain, signal $r(t)$ can also be written in terms of its in-phase and quadrature components as follows:

$$r(t)=I(t)\cdot\cos(\omega t)+Q(t)\cdot\sin(\omega t)=R(t)\cdot\cos(\phi(t))\cdot\cos(\omega t)+R(t)\cdot\sin(\phi(t))\cdot\sin(\omega t) \quad (1)$$

[0120] Note that, in the example of FIG. 1, $R(t)$ is illustrated at a particular instant of time.

2.2) Time-Varying Complex Envelope Signals

[0121] FIG. 2 illustrates a phasor representation of a signal $r(t)$ at two different instants of time t_1 and t_2 . It is noted that the magnitude of the phasor, which represents the magnitude of the signal's envelope, as well as its relative phase shift both vary from time t_1 to time t_2 . In FIG. 2, this is illustrated by the varying magnitude of phasors \vec{R}_1 and \vec{R}_2 and their corresponding phase shift angles ϕ_1 and ϕ_2 . Signal $r(t)$, accordingly, is a time-varying complex envelope signal.

[0122] It is further noted, from FIG. 2, that the real and imaginary phasor components of signal $r(t)$ are also time-varying in amplitude. Accordingly, their corresponding time domain signals also have time-varying envelopes.

[0123] FIGS. 3A-3C illustrate an example modulation to generate a time-varying complex envelope signal. FIG. 3A illustrates a view of a signal $m(t)$. FIG. 3B illustrates a view of a portion of a carrier signal $c(t)$. FIG. 3C illustrates a signal $r(t)$ that results from the multiplication of signals $m(t)$ and $c(t)$.

[0124] In the example of FIG. 3A, signal $m(t)$ is a time-varying magnitude signal. $m(t)$ further undergoes a zero crossing. Carrier signal $c(t)$, in the example of FIG. 3B, oscillates at some carrier frequency, typically higher than that of signal $m(t)$.

[0125] From FIG. 3C, it can be noted that the resulting signal $r(t)$ has a time-varying envelope. Further, it is noted, from FIG. 3C, that $r(t)$ undergoes a reversal in phase at the moment when the modulating signal $m(t)$ crosses zero. Having both non-constant envelope and phase, $r(t)$ is said to be a time-varying complex envelope signal.

2.3) Constant Envelope Decomposition of Time-Varying Envelope Signals

[0126] Any phasor of time-varying magnitude and phase can be obtained by the sum of two or more constant magnitude phasors having appropriately specified phase shifts relative to a reference phasor.

[0127] FIG. 3D illustrates a view of an example time-varying envelope and phase signal $S(t)$. For ease of illustration, signal $S(t)$ is assumed to be a sinusoidal signal having a maximum envelope magnitude A . FIG. 3D further shows an example of how signal $S(t)$ can be obtained, at any instant of time, by the sum of two constant envelope signals $S_1(t)$ and $S_2(t)$. Generally, $S_1(t)=A_1\sin(\omega t+\phi_1(t))$ and $S_2(t)=A_2\sin(\omega t+\phi_2(t))$.

[0128] For the purpose of illustration, three views are provided in FIG. 3D that illustrate how by appropriately phasing signals $S_1(t)$ and $S_2(t)$ relative to $S(t)$, signals $S_1(t)$ and $S_2(t)$ can be summed so that $S(t)=K(S_1(t)+S_2(t))$ where K is a constant. In other words, signal $S(t)$ can be decomposed, at

any time instant, into two or more signals. From FIG. 3D, over period T_1 , $S_1(t)$ and $S_2(t)$ are both in-phase relative to signal $S(t)$, and thus sum to the maximum envelope magnitude A of signal $S(t)$. Over period T_3 , however, signals $S_1(t)$ and $S_2(t)$ are 180 degree out-of-phase relative to each other, and thus sum to a minimum envelope magnitude of signal $S(t)$.

[0129] The example of FIG. 3D illustrates the case of sinusoidal signals. A person skilled in the art, however, will understand that any time-varying envelope, which modulates a carrier signal that can be represented by a Fourier series or Fourier transform, can be similarly decomposed into two or more substantially constant envelope signals. Thus, by controlling the phase of a plurality of substantially constant envelope signals, any time-varying complex envelope signal can be generated.

3. VECTOR POWER AMPLIFICATION METHODS AND SYSTEMS

[0130] Vector power amplification methods and systems according to embodiments of the present invention rely on the ability to decompose any time-varying envelope signal into two or more substantially constant envelope constituent signals or to receive or generate such constituent signals, amplify the constituent signals, and then sum the amplified signals to generate an amplified version of the time-varying complex envelope signal.

[0131] In sections 3.1-3.3, vector power amplification (VPA) embodiments of the present invention are provided, including 4-branch and 2-branch embodiments. In the description, each VPA embodiment is first presented conceptually using a mathematical derivation of underlying concepts of the embodiment. An embodiment of a method of operation of the VPA embodiment is then presented, followed by various system level embodiments of the VPA embodiment.

[0132] Section 3.4 presents various embodiments of control modules according to embodiments of the present invention. Control modules according to embodiments of the present invention may be used to enable certain VPA embodiments of the present invention. In some embodiments, the control modules are intermediary between an input stage of the VPA embodiment and a subsequent vector modulation stage of the VPA embodiment.

[0133] Section 3.5 describes VPA output stage embodiments according to embodiments of the present invention. Output stage embodiments are directed to generating the output signal of a VPA embodiment.

[0134] Section 3.6 is directed to harmonic control according to embodiments of the present invention. Harmonic control may be implemented in certain embodiments of the present invention to manipulate the real and imaginary power in the harmonics of the VPA embodiment, thus increasing the power present in the fundamental frequency at the output.

[0135] Section 3.7 is directed to power control according to embodiments of the present invention. Power control may be implemented in certain embodiments of the present invention in order to satisfy power level requirements of applications where VPA embodiments of the present invention may be employed.

3.1 Cartesian 4-Branch Vector Power Amplifier

[0136] According to one embodiment of the invention, herein called the Cartesian 4-Branch VPA embodiment for ease of illustration and not limitation, a time-varying complex

envelope signal is decomposed into 4 substantially constant envelope constituent signals. The constituent signals are equally or substantially equally amplified individually, and then summed to construct an amplified version of the original time-varying complex envelope signal.

[0137] It is noted that 4 branches are employed in this embodiment for purposes of illustration, and not limitation. The scope of the invention covers use of other numbers of branches, and implementation of such variations will be apparent to persons skilled in the art based on the teachings contained herein.

[0138] In one embodiment, a time-varying complex envelope signal is first decomposed into its in-phase and quadrature vector components. In phasor representation, the in-phase and quadrature vector components correspond to the signal's real part and imaginary part phasors, respectively.

[0139] As described above, magnitudes of the in-phase and quadrature vector components of a signal vary proportionally to the signal's magnitude, and are thus not constant envelope when the signal is a time-varying envelope signal. Accordingly, the 4-Branch VPA embodiment further decomposes each of the in-phase and quadrature vector components of the signal into four substantially constant envelope components, two for the in-phase and two for the quadrature signal components. This concept is illustrated in FIG. 4 using a phasor signal representation.

[0140] In the example of FIG. 4, phasors \vec{I}_1 and \vec{I}_2 correspond to the real part phasors of an exemplary time-varying complex envelope signal at two instants of time t_1 and t_2 , respectively. It is noted that phasors \vec{I}_1 and \vec{I}_2 have different magnitudes.

[0141] Still referring to FIG. 4, at instant t_1 , phasor \vec{I}_1 can be obtained by the sum of upper and lower phasors \vec{I}_{U1} and \vec{I}_{L1} . Similarly, at instant t_2 , phasor \vec{I}_2 can be obtained by the sum of upper and lower phasors \vec{I}_{U2} and \vec{I}_{L2} . Note that phasors \vec{I}_{U1} and \vec{I}_{U2} have equal or substantially equal magnitude. Similarly, phasors \vec{I}_{L1} and \vec{I}_{L2} have substantially equal magnitude. Accordingly, the real part phasor of the time-varying envelope signal can be obtained at any time instant by the sum of at least two substantially constant envelope components.

[0142] The phase shifts of phasors \vec{I}_{U1} and \vec{I}_{L1} relative to \vec{I}_1 , as well as the phase shifts of phasors \vec{I}_{U2} and \vec{I}_{L2} relative to \vec{I}_2 are set according to the desired magnitude of phasors \vec{I}_1 and \vec{I}_2 , respectively. In one case, when the upper and lower phasors are selected to have equal magnitude, the upper and lower phasors are symmetrically shifted in phase relative to the phasor. This is illustrated in the example of FIG. 4, and corresponds to \vec{I}_{U1} , \vec{I}_{L1} , \vec{I}_{U2} , and \vec{I}_{L2} all having equal magnitude. In a second case, the phase shift of the upper and lower phasors are substantially symmetrically shifted in phase relative to the phasor. Based on the description herein, anyone skilled in the art will understand that the magnitude and phase shift of the upper and lower phasors do not have to be exactly equal in value.

[0143] As an example, it can be further verified that, for the case illustrated in FIG. 4, the relative phase shifts, illustrated as

$$\frac{\phi_1}{2} \text{ and } \frac{\phi_2}{2}$$

in FIG. 4, are related to the magnitudes of normalized phasors \vec{I}_1 and \vec{I}_2 as follows:

$$\frac{\phi_1}{2} = \cot^{-1} \left(\frac{I_1}{2\sqrt{1 - \frac{I_1^2}{4}}} \right); \text{ and} \quad (2)$$

$$\frac{\phi_2}{2} = \cot^{-1} \left(\frac{I_2}{2\sqrt{1 - \frac{I_2^2}{4}}} \right), \quad (3)$$

[0144] wherein I_1 and I_2 represent the normalized magnitudes of phasors \vec{I}_1 and \vec{I}_2 , respectively, and wherein the domains of I_1 and I_2 are restricted appropriately according to the domain over which equation (2) and (3) are valid. It is noted that equations (2) and (3) are one representation for relating the relative phase shifts to the normalized magnitudes. Other, solutions, equivalent representations, and/or simplified representations of equations (2) and (3) may also be employed. Look up tables relating relative phase shifts to normalized magnitudes may also be used.

[0145] The concept describe above can be similarly applied to the imaginary phasor or the quadrature component part of a signal $r(t)$ as illustrated in FIG. 4. Accordingly, at any time instant t , imaginary phasor part \vec{Q} of signal $r(t)$ can be obtained by summing upper and lower phasor components \vec{Q}_U and \vec{Q}_L of substantially equal and constant magnitude. In this example, \vec{Q}_U and \vec{Q}_L are symmetrically shifted in phase relative to \vec{Q} by an angle set according to the magnitude of \vec{Q} at time t . The relationship of \vec{Q}_U and \vec{Q}_L to the desired phasor \vec{Q} are related as defined in equations 2 and 3 by substituting Q_1 and Q_2 for I_1 and I_2 respectively.

[0146] It follows from the above discussion that, in phasor representation, any phasor \vec{R} of variable magnitude and phase can be constructed by the sum of four substantially constant magnitude phasor components:

$$\begin{aligned} \vec{R} &= \vec{I}_U + \vec{I}_L + \vec{Q}_U + \vec{Q}_L; \\ \vec{I}_U + \vec{I}_L &= \vec{I}; \\ \vec{Q}_U + \vec{Q}_L &= \vec{Q}; \\ I_U = I_L &= \text{constant}; \\ Q_U = Q_L &= \text{constant}; \end{aligned} \quad (4)$$

[0147] where I_U , I_L , Q_U , and Q_L represent the magnitudes of phasors \vec{I}_U , \vec{I}_L , \vec{Q}_U , and \vec{Q}_L , respectively.

[0148] Correspondingly, in the time domain, a time-varying complex envelope sinusoidal signal $r(t) = R(t) \cos(\omega t + \phi)$ is constructed by the sum of four constant envelope signals as follows:

$$\begin{aligned}
 r(t) &= I_U(t) + I_L(t) + Q_U(t) + Q_L(t); \\
 I_U(t) &= \text{sgn}(\vec{I}) \times I_U \times \cos\left(\frac{\phi_I}{2}\right) \times \cos(\omega t) + I_U \times \sin\left(\frac{\phi_I}{2}\right) \times \sin(\omega t); \\
 I_L(t) &= \text{sgn}(\vec{I}) \times I_L \times \cos\left(\frac{\phi_I}{2}\right) \times \cos(\omega t) - I_L \times \sin\left(\frac{\phi_I}{2}\right) \times \sin(\omega t); \\
 Q_U(t) &= \\
 &\quad -\text{sgn}(\vec{Q}) \times Q_U \times \cos\left(\frac{\phi_Q}{2}\right) \times \sin(\omega t) + Q_U \times \sin\left(\frac{\phi_Q}{2}\right) \times \cos(\omega t); \\
 Q_L(t) &= -\text{sgn}(\vec{Q}) \times Q_L \times \cos\left(\frac{\phi_Q}{2}\right) \times \sin(\omega t) - Q_L \times \sin\left(\frac{\phi_Q}{2}\right) \times \cos(\omega t).
 \end{aligned} \tag{5}$$

where $\text{sgn}(\vec{I}) = \pm 1$ depending on whether \vec{I} is in-phase or 180° degrees out-of-phase with the positive real axis. Similarly, $\text{sgn}(\vec{Q}) = \pm 1$ depending on whether \vec{Q} is in-phase or 180° degrees out-of-phase with the imaginary axis.

$$\frac{\phi_I}{2}$$

corresponds to the phase shift of \vec{I}_U and \vec{I}_L relative to the real axis. Similarly,

$$\frac{\phi_Q}{2}$$

corresponds to the phase shift of \vec{Q}_U and \vec{Q}_L relative to the imaginary axis.

$$\frac{\phi_I}{2} \text{ and } \frac{\phi_Q}{2}$$

can be calculated using the equations given in (2) and (3).

[0149] Equations (5) can be further simplified as:

$$\begin{aligned}
 r(t) &= I_U(t) + I_L(t) + Q_U(t) + Q_L(t); \\
 I_U(t) &= \text{sgn}(\vec{I}) \times I_{UX} \times \cos(\omega t) + I_{UY} \times \sin(\omega t); \\
 I_L(t) &= \text{sgn}(\vec{I}) \times I_{LX} \times \cos(\omega t) - I_{LY} \times \sin(\omega t); \\
 Q_U(t) &= -Q_{UX} \times \cos(\omega t) + \text{sgn}(\vec{Q}) \times Q_{UY} \times \sin(\omega t); \\
 Q_L(t) &= -Q_{LX} \times \cos(\omega t) - \text{sgn}(\vec{Q}) \times Q_{LY} \times \sin(\omega t).
 \end{aligned} \tag{6}$$

[0150] where

$$\begin{aligned}
 I_{UX} &= I_U \times \cos\left(\frac{\phi_I}{2}\right) = I_L \times \cos\left(\frac{\phi_I}{2}\right), \\
 I_{UY} &= I_U \times \sin\left(\frac{\phi_I}{2}\right) = I_L \times \sin\left(\frac{\phi_I}{2}\right), \\
 Q_{UX} &= Q_U \times \sin\left(\frac{\phi_Q}{2}\right) = Q_L \times \sin\left(\frac{\phi_Q}{2}\right), \text{ and}
 \end{aligned}$$

-continued

$$Q_{UY} = Q_U \times \cos\left(\frac{\phi_Q}{2}\right) = Q_L \times \cos\left(\frac{\phi_Q}{2}\right).$$

[0151] It can be understood by a person skilled in the art that, whereas the time domain representations in equations (5) and (6) have been provided for the case of a sinusoidal waveform, equivalent representations can be developed for non-sinusoidal waveforms using appropriate basis functions. Further, as understood by a person skilled in the art based on the teachings herein, the above-described two-dimensional decomposition into substantially constant envelope signals can be extended appropriately into a multi-dimensional decomposition.

[0152] FIG. 5 is an example block diagram of the Cartesian 4-Branch VPA embodiment. An output signal $r(t)$ 578 of desired power level and frequency characteristics is generated from baseband in-phase and quadrature components according to the Cartesian 4-Branch VPA embodiment.

[0153] In the example of FIG. 5, a frequency generator such as a synthesizer 510 generates a reference signal $A \times \cos(\omega t)$ 511 having the same frequency as that of output signal $r(t)$ 578. It can be understood by a person skilled in the art that the choice of the reference signal is made according to the desired output signal. For example, if the desired frequency of the reference signal is set to be 2.4 GHz. In this manner, embodiments of the invention achieve frequency up-conversion.

[0154] Referring to FIG. 5, one or more phase splitters are used to generate signals 521, 531, 541, and 551 based on the reference signal 511. In the example of FIG. 5, this is done using phase splitters 512, 514, and 516 and by applying 0° phase shifts at each of the phase splitters. A person skilled in the art will appreciate, however, that various techniques may be used for generating signals 521, 531, 541, and 551 of the reference signal 511. For example, a 1:4 phase splitter may be used to generate the four replicas 521, 531, 541, and 551 in a single step or in the example embodiment of FIG. 5, signal 511 can be directly coupled to signals 521, 531, 541, 551. Depending on the embodiment, a variety of phase shifts may also be applied to result in the desired signals 521, 531, 541, and 551.

[0155] Still referring to FIG. 5, the signals 521, 531, 541, and 551 are each provided to a corresponding vector modulator 520, 530, 540, and 550, respectively. Vector modulators 520, 530, 540, and 550, in conjunction with their appropriate input signals, generate four constant envelope constituents of signal $r(t)$ according to the equations provided in (6). In the example embodiment of FIG. 5, vector modulators 520 and 530 generate the $I_U(t)$ and $I_L(t)$ components, respectively, of signal $r(t)$. Similarly, vector modulators 540 and 550 generate the $Q_U(t)$ and $Q_L(t)$ components, respectively, of signal $r(t)$.

[0156] The actual implementation of each of vector modulators 520, 530, 540, and 550 may vary. It will be understood by a person skilled in the art, for example, that various techniques exist for generating the constant envelope constituents according to the equations in (6).

[0157] In the example embodiment of FIG. 5, each of vector modulators 520, 530, 540, 550 includes an input phase splitter 522, 532, 542, 552 for phasing the signals 522, 531, 541, 551. Accordingly, input phase splitters 522, 532, 542, 552 are used to generate an in-phase and a quadrature components or their respective input signals.

[0158] In each vector modulator 520, 530, 540, 550, the in-phase and quadrature components are multiplied with amplitude information. In FIG. 5, for example, multiplier 524 multiplies the quadrature component of signal 521 with the quadrature amplitude information I_{LX} of $I_L(t)$. In parallel, multiplier 526 multiplies the in-phase replica signal with the in-phase amplitude information $\text{sgn}(I) \times I_{LX}$ of $I_L(t)$.

[0159] To generate the $I_L(t)$ constant envelope constituent signals 525 and 527 are summed using phase splitter 528 or alternate summing techniques. The resulting signal 529 corresponds to the $I_U(t)$ component of signal $r(t)$.

[0160] In similar fashion as described above, vector modulators 530, 540, and 550, respectively, generate the $I_L(t)$, $Q_L(t)$, and $Q_L(t)$ components of signal $r(t)$. $I_L(t)$, $Q_L(t)$, and $Q_L(t)$, respectively, correspond to signals 539, 549, and 559 in FIG. 5.

[0161] Further, as described above, signals 529, 539, 549, and 559 are characterized by having substantially equal and constant magnitude envelopes. Accordingly, when signals 529, 539, 549, and 559 are input into corresponding power amplifiers (PA) 562, 564, 566, and 568, corresponding amplified signals 563, 565, 567, and 569 are substantially constant envelope signals.

[0162] Power amplifiers 562, 564, 566, and 568 amplify each of the signals 529, 539, 549, 559, respectively. In an embodiment, substantially equal power amplification is applied to each of the signals 529, 539, 549, and 559. In an embodiment, the power amplification level of PAs 562, 564, 566, and 568 is set according to the desired power level of output signal $r(t)$.

[0163] Still referring to FIG. 5, amplified signals 563 and 565 are summed using summer 572 to generate an amplified version 573 of the in-phase component $\vec{I}(t)$ of signal $r(t)$. Similarly, amplified signals 567 and 569 are summed using summer 574 to generate an amplified version 575 of the quadrature component $\vec{Q}(t)$ of signal $r(t)$.

[0164] Signals 573 and 575 are summed using summer 576, as shown in FIG. 5, with the resulting signal corresponding to desired output signal $r(t)$.

[0165] It must be noted that, in the example of FIG. 5, summers 572, 574, and 576 are being used for the purpose of illustration only. Various techniques may be used to sum amplified signals 563, 565, 567, and 569. For example, amplified signals 563, 565, 567, and 569 may be summed all in one step to result in signal 578. In fact, according to various VPA embodiments of the present invention, it suffices that the summing is done after amplification. Certain VPA embodiments of the present invention, as will be further described below, use minimally lossy summing techniques such as direct coupling via wire. Alternatively, certain VPA embodiments use conventional power combining techniques. In other embodiments, as will be further described below, power amplifiers 562, 564, 566, and 568 can be implemented as a multiple-input single-output power amplifier.

[0166] Operation of the Cartesian 4-Branch VPA embodiment shall now be further described with reference to the process flowchart of FIG. 6. The process begins at step 610, which includes receiving the baseband representation of the desired output signal. In an embodiment, this involves receiving in-phase (I) and quadrature (Q) components of the desired output signal. In another embodiment, this involves receiving magnitude and phase of the desired output signal. In an embodiment of the Cartesian 4-Branch VPA embodiment, the

I and Q are baseband components. In another embodiment, the I and Q are RF components and are down-converted to baseband.

[0167] Step 620 includes receiving a clock signal set according to a desired output signal frequency of the desired output signal. In the example of FIG. 5, step 620 is achieved by receiving reference signal 511.

[0168] Step 630 includes processing the I component to generate first and second signals having the output signal frequency. The first and second signals have substantially constant and equal magnitude envelopes and a sum equal to the I component. The first and second signals correspond to the $I_U(t)$ and $I_L(t)$ constant envelope constituents described above. In the example of FIG. 5, step 630 is achieved by vector modulators 520 and 530, in conjunction with their appropriate input signals.

[0169] Step 640 includes processing the Q component to generate third and fourth signals having the output signal frequency. The third and fourth signals have substantially constant and equal magnitude envelopes and a sum equal to the Q component. The third and fourth signals correspond to the $Q_U(t)$ and $Q_L(t)$ constant envelope constituents described above. In the example of FIG. 5, step 630 is achieved by vector modulators 540 and 550, in conjunction with their appropriate input signals.

[0170] Step 650 includes individually amplifying each of the first, second, third, and fourth signals, and summing the amplified signals to generate the desired output signal. In an embodiment, the amplification of the first, second, third, and fourth signals is substantially equal and according to a desired power level of the desired output signal. In the example of FIG. 5, step 650 is achieved by power amplifiers 562, 564, 566, and 568 amplifying respective signals 529, 539, 549, and 559, and by summers 572, 574, and 576 summing amplified signals 563, 565, 567, and 569 to generate output signal 578.

[0171] FIG. 7A is a block diagram that illustrates an exemplary embodiment of a vector power amplifier 700 implementing the process flowchart 600 of FIG. 6. In the example of FIG. 7A, optional components are illustrated with dashed lines. In other embodiments, additional components may be optional.

[0172] Vector power amplifier 700 includes an in-phase (I) branch 703 and a quadrature (Q) branch 705. Each of the I and Q branches further comprises a first branch and a second branch.

[0173] In-phase (I) information signal 702 is received by an I Data Transfer Function module 710. In an embodiment, I information signal 702 includes a digital baseband signal. In an embodiment, I Data Transfer Function module 710 samples I information signal 702 according to a sample clock 706. In another embodiment, I information signal 702 includes an analog baseband signal, which is converted to digital using an analog-to-digital converter (ADC) (not shown in FIG. 7A) before being input into I Data Transfer Function module 710. In another embodiment, I information signal 702 includes an analog baseband signal which input in analog form into I Data Transfer Function module 710, which also includes analog circuitry. In another embodiment, I information signal 702 includes a RF signal which is down-converted to baseband before being input into I Data Transfer Function module 710 using any of the above described embodiments.

[0174] I Data Transfer Function module 710 processes I information signal 702, and determines in-phase and quadra-

ture amplitude information of at least two constant envelope constituent signals of I information signal 702. As described above with reference to FIG. 5, the in-phase and quadrature vector modulator input amplitude information corresponds to $\text{sgn}(I) \times I_{UX}$ and I_{UY} , respectively. The operation of I Data Transfer Function module 710 is further described below in section 3.4.

[0175] I Data Transfer Function module 710 outputs information signals 722 and 724 used to control the in-phase and quadrature amplitude components of vector modulators 760 and 762. In an embodiment, signals 722 and 724 are digital signals. Accordingly, each of signals 722 and 724 is fed into a corresponding digital-to-analog converter (DAC) 730 and 732, respectively. The resolution and sample rate of DACs 730 and 732 is selected to achieve the desired I component of the output signal 782. DACs 730 and 732 are controlled by DAC clock signals 723 and 725, respectively. DAC clock signals 723 and 725 may be derived from a same clock signal or may be independent.

[0176] In another embodiment, signals 722 and 724 are analog signals, and DACs 730 and 732 are not required.

[0177] In the exemplary embodiment of FIG. 7A, DACs 730 and 732 convert digital information signals 722 and 724 into corresponding analog signals, and input these analog signals into optional interpolation filters 731 and 733, respectively. Interpolation filters 731 and 733, which also serve as anti-aliasing filters, shape the DACs outputs to produce the desired output waveform. Interpolation filters 731 and 733 generate signals 740 and 742, respectively. Signal 741 represents the inverse of signal 740. Signals 740-742 are input into vector modulators 760 and 762.

[0178] Vector modulators 760 and 762 multiply signals 740-742 with appropriately phased clock signals to generate constant envelope constituents of I information signal 702. The clock signals are derived from a channel clock signal 708 having a rate according to a desired output signal frequency. A plurality of phase splitters, such as 750 and 752, for example, and phasors associated with the vector modulator multipliers may be used to generate the appropriately phased clock signals.

[0179] In the embodiment of FIG. 7A, for example, vector modulator 760 modulates a 90° shifted channel clock signal with quadrature amplitude information signal 740. In parallel, vector modulator 760 modulates an in-phase channel clock signal with in-phase amplitude information signal 742. Vector modulator 760 combines the two modulated signals to generate a first modulated constant envelope constituent 761 of I information signal 702. Similarly, vector modulator 762 generates a second modulated constant envelope constituent 763 of I information signal 702, using signals 741 and 742. Signals 761 and 763 correspond, respectively, to the $I_c(t)$ and $I_s(t)$ constant envelope components described with reference to FIG. 5.

[0180] In parallel and in similar fashion, the Q branch of vector power amplifier 700 generates at least two constant envelope constituent signals of quadrature (Q) information signal 704.

[0181] In the embodiment of FIG. 7A, for example, vector modulator 764 generates a first constant envelope constituent 765 of Q information signal 704, using signals 744 and 746. Similarly, vector modulator 766 generates a second constant envelope constituent 767 of Q information signal 704, using signals 745 and 746.

[0182] As described above with respect to FIG. 5, constituent signals 761, 763, 765, and 767 have substantially equal and constant magnitude envelopes. In the exemplary embodiment of FIG. 7A, signals 761, 763, 765, and 767 are, respectively, input into corresponding power amplifiers (PAs) 770, 772, 774, and 776. PAs 770, 772, 774, and 776 can be linear or non-linear power amplifiers. In an embodiment, PAs 770, 772, 774, and 776 include switching power amplifiers.

[0183] Circuitry 714 and 716 (herein referred to as “auto-bias circuitry” for ease of reference, and not limitation) and in this embodiment, control the bias of PAs 770, 772, 774, and 776 according to I and Q information signals 702 and 704. In the embodiment of FIG. 7A, autobias circuitry 714 and 716 provide, respectively, bias signals 715 and 717 to PAs 770, 772 and PAs 774, 776. Autobias circuitry 714 and 716 are further described below in section 3.5. Embodiments of PAs 770, 772, 774, and 776 are also discussed below in section 3.5.

[0184] In an embodiment, PAs 770, 772, 774, and 776 apply substantially equal power amplification to respective substantially constant envelope signals 761, 763, 765, and 767. In other embodiments, PA drivers are additionally employed to provide additional power amplification. In the embodiment of FIG. 7A, PA drivers 794, 795, 796, and 797 are optionally added between respective vector modulators 760, 762, 764 766 and respective PAs 770, 772, 774, and 776, in each branch of vector power amplifier 700.

[0185] The outputs of PAs 770, 772, 774, and 776 are coupled together to generate output signal 782 of vector power amplifier 700. In an embodiment, the outputs of PAs 770, 772, 774, and 776 are directly coupled together using a wire. Direct coupling in this manner means that there is minimal or no resistive, inductive, or capacitive isolation between the outputs of PAs 770, 772, 774, and 776. In other words, outputs of PAs 770, 772, 774, and 776, are coupled together without intervening components. Alternatively, in an embodiment, the outputs of PAs 770, 772, 774, and 776 are coupled together indirectly through inductances and/or capacitances that result in low or minimal impedance connections, and/or connections that result in minimal isolation and minimal power loss. Alternatively, outputs of PAs 770, 772, 774, and 776 are coupled using well known combining techniques, such as Wilkinson, hybrid, transformers, or known active combiners. In an embodiment, the PAs 770, 772, 774, and 776 provide integrated amplification and power combining in a single operation. In an embodiment, one or more of the power amplifiers and/or drivers described herein are implemented using multiple input, single output power amplification techniques, examples of which are shown in FIGS. 7B, and 51A-H.

[0186] Output signal 782 includes the I and Q characteristics of I and Q information signals 702 and 704. Further, output signal 782 is of the same frequency as that of its constituents, and thus is of the desired up-converted output frequency. In embodiments of vector power amplifier 700, a pull-up impedance 780 is coupled between the output of vector amplifier 700 and a power supply. Output stage embodiments according to power amplification methods and systems of the present invention will be further described below in section 3.5.

[0187] In other embodiments of vector power amplifier 700, process detectors are employed to compensate for any process variations in circuitry of the amplifier. In the embodiment of FIG. 7A for example, process detectors 791-793 are

optionally added to monitor variations in PA drivers **794-797** and phase splitter **750**. In further embodiments, frequency compensation circuitry **799** may be employed to compensate for frequency variations.

[0188] FIG. 7B is a block diagram that illustrates another exemplary embodiment of vector power amplifier **700**. Optional components are illustrated with dashed lines, although other embodiments may have more or less optional components.

[0189] The embodiment illustrates a multiple-input single-output (MISO) implementation of the amplifier of FIG. 7A. In the embodiment of FIG. 7B, constant envelope signals **761**, **763**, **765** and **767**, output from vector modulators **760**, **762**, **764**, and **766**, are input into MISO PAs **784** and **786**. MISO PAs **784** and **786** are two-input single-output power amplifiers. In an embodiment, MISO PAs **784** and **786** include elements **770**, **772**, **774**, **776**, **794-797** as shown in the embodiment of FIG. 7A or functional equivalence thereof. In another embodiment, MISO PAs **784** and **786** may include other elements, such as optional pre-drivers and optional process detection circuitry. Further, MISO PAs **784** and **786** are not limited to being two-input PAs as shown in FIG. 7B. In other embodiments as will be described further below with reference to FIGS. 51A-H, PAs **784** and **786** can have any number of inputs and outputs.

[0190] FIG. 8A is a block diagram that illustrates another exemplary embodiment **800A** of a vector power amplifier according to the Cartesian 4-Branch VPA method shown in FIG. 6. Optional components are illustrated with dashed lines, although other embodiments may have more or less optional components.

[0191] In the embodiment of FIG. 8A, a DAC **830** of sufficient resolution and sample rate replaces DACs **730**, **732**, **734**, and **736** of the embodiment of FIG. 7A. DAC **830**'s sample rate is controlled by a DAC clock signal **826**.

[0192] DAC **830** receives in-phase and quadrature information signals **810** and **820** from I Data Transfer Function module **710** and Q Data Transfer Function module **712**, respectively, as described above. In an embodiment, an input selector **822** selects the order of signals **810** and **820** being input into DAC **830**.

[0193] DAC **830** may output a single analog signal at a time. In an embodiment, a sample and hold architecture may be used to ensure proper signal timing to the four branches of the amplifier, as shown in FIG. 8A.

[0194] DAC **830** sequentially outputs analog signals **832**, **834**, **836**, **838** to a first set of sample-and-hold circuits **842**, **844**, **846**, and **848**. In an embodiment, DAC **830** is clocked at a sufficient rate to emulate the operation of DACs **730**, **732**, **734**, and **736** of the embodiment of FIG. 7A. An output selector **824** determines which of output signals **832**, **834**, **836**, and **838** should be selected for output.

[0195] DAC **830**'s DAC clock signal **826**, output selector signal **824**, input selector **822**, and sample-and-hold clocks **840A-D**, and **850** are controlled by a control module that can be independent or integrated into transfer function modules **710** and/or **712**.

[0196] In an embodiment, sample-and-hold circuits (S/H) **842**, **844**, **846**, and **848** sample and hold the received analog values from DAC **830** according to a clock signals **840A-D**. Sample-and-hold circuits **852**, **854**, **856**, and **858** sample and hold the analog values from sample and hold circuits **842**, **844**, **846**, and **848** respectively. In turn, sample-and-hold circuits **852**, **854**, **856**, and **858** hold the received analog values,

and simultaneously release the values to vector modulators **760**, **762**, **764**, and **766** according to a common clock signal **850**. In another embodiment, sample-and-hold circuits **852**, **854**, **856**, and **858** release the values to optional interpolation filters **731**, **733**, **735**, and **737** which are also anti-aliasing filters. In an embodiment, a common clock signal **850** is used in order to ensure that the outputs of S/H **852**, **854**, **856**, and **858** are time-aligned.

[0197] Other aspects of vector power amplifier **800A** substantially correspond to those described above with respect to vector power amplifier **700**.

[0198] FIG. 8B is a block diagram that illustrates another exemplary embodiment **800B** of a vector power amplifier according to the Cartesian 4-Branch VPA method shown in FIG. 6. Optional components are illustrated with dashed lines, although other embodiments may have more or less optional components.

[0199] Embodiment **800B** illustrates another single DAC implementation of the vector power amplifier. However, in contrast to the embodiment of FIG. 8A, the sample and hold architecture includes a single set of sample-and-hold (S/H) circuits. As shown in FIG. 8B, S/H **842**, **844**, **846**, and **848** receive analog values from DAC **830**, illustrated as signals **832**, **834**, **836**, and **838**. Each of S/H circuits **842**, **844**, **846** and **848** release its received value according to a different clock **840A-D** as shown. The time difference between analog samples used for to generate signals **740**, **741**, **742**, **744**, **745**, and **746** can be compensated for in transfer functions **710** and **712**. According to the embodiment of FIG. 8B, one level of S/H circuitry can be eliminated relative to the embodiment of FIG. 8A, thereby reducing the size and the complexity of the amplifier.

[0200] Other aspects of vector power amplifier **800B** substantially correspond to those described above with respect to vector power amplifiers **700** and **800A**.

[0201] FIG. 8C is a block diagram that illustrates another exemplary embodiment **800C** of vector power amplifier **700**. Optional components are illustrated with dashed lines, although other embodiments may have more or less optional components. The embodiment of FIG. 8C illustrates a multiple-input single-output (MISO) implementation of the amplifier of FIG. 8A. In the embodiment of FIG. 8C, constant envelope signals **761**, **763**, **765** and **767**, output from vector modulators **760**, **762**, **764**, and **766**, are input into MISO PAs **860** and **862**. MISO PAs **860** and **862** are two-input single-output power amplifiers. In an embodiment, MISO PAs **860** and **862** include elements **770**, **772**, **774**, **776**, **794-797** as shown in the embodiment of FIG. 7A or functional equivalence thereof. In another embodiment, MISO PAs **860** and **862** may include other elements, such as optional pre-drivers and optional process detection circuitry. In another embodiment, MISO PAs **860** and **862** may include other elements, such as pre-drivers, not shown in the embodiment of FIG. 7A. Further, MISO PAs **860** and **862** are not limited to being two-input PAs as shown in FIG. 8C. In other embodiments as will be described further below with reference to FIGS. 51A-H, PAs **860** and **862** can have any number of inputs and outputs.

[0202] Other aspects of vector power amplifier **800C** substantially correspond to those described above with respect to vector power amplifiers **700** and **800A**.

[0203] FIG. 8D is a block diagram that illustrates another exemplary embodiment **800D** of vector power amplifier **700**. Optional components are illustrated with dashed lines,

although other embodiments may have more or less optional components. The embodiment of FIG. 8D illustrates a multiple-input single-output (MISO) implementation of the amplifier of FIG. 8B. In the embodiment of FIG. 8D, constant envelope signals 761, 763, 765 and 767, output from vector modulators 760, 762, 764, and 766, are input into MISO PAs 870 and 872. MISO PAs 870 and 872 are two-input single-output power amplifiers. In an embodiment, MISO PAs 870 and 872 include elements 770, 772, 774, 776, 794-797 as shown in the embodiment of FIG. 7A or functional equivalence thereof. In another embodiment, MISO PAs 870 and 872 may include other elements, such as optional pre-drivers and optional process detection circuitry. In another embodiment, MISO PAs 870 and 872 may include other elements, such as pre-drivers, not shown in the embodiment of FIG. 7A. Further, MISO PAs 870 and 872 are not limited to being two-input PAs as shown in FIG. 8D. In other embodiments as will be described further below with reference to FIGS. 51A-H, PAs 870 and 872 can have any number of inputs and outputs.

[0204] Other aspects of vector power amplifier 800D substantially correspond to those described above with respect to vector power amplifiers 700 and 800B.

3.2) Cartesian-Polar-Cartesian-Polar 2-Branch Vector Power Amplifier

[0205] A Cartesian-Polar-Cartesian-Polar (CPCP) 2-Branch VPA embodiment shall now be described (The name of this embodiment is provided for ease of reference, and is not limiting).

[0206] According to the Cartesian-Polar-Cartesian-Polar (CPCP) 2-Branch VPA method, a time-varying complex envelope signal is decomposed into 2 substantially constant envelope constituent signals. The constituent signals are individually amplified, and then summed to construct an amplified version of the original time-varying complex envelope signal. In addition, the phase angle of the time-varying complex envelope signal is determined and the resulting summation of the constituent signals are phase shifted by the appropriate angle.

[0207] In one embodiment of the CPCP 2-Branch VPA method, a magnitude and a phase angle of a time-varying complex envelope signal are calculated from in-phase and quadrature components of a signal. Given the magnitude information, two substantially constant envelope constituents are calculated from a normalized version of the desired time-varying envelope signal, wherein the normalization includes implementation specific manipulation of phase and/or amplitude. The two substantially constant envelope constituents are then phase shifted by an appropriate angle related to the phase shift of the desired time-varying envelope signal. The substantially constant envelope constituents are then individually amplified substantially equally, and summed to generate an amplified version of the original desired time-varying envelope signal.

[0208] FIGS. 9A and 9B conceptually illustrate the CPCP 2-Branch VPA embodiment using a phasor signal representation. In FIG. 9A, phasor \vec{R}_{in} represents a time-varying complex envelope input signal $r(t)$. At any instant of time, \vec{R}_{in} reflects a magnitude and a phase shift angle of signal $r(t)$. In the example shown in FIG. 9A, \vec{R}_{in} is characterized by a

magnitude R and a phase shift angle θ . As described above, the phase shift angle is measured relative to a reference signal.

[0209] Referring to FIG. 9A, \vec{R}' represents the relative amplitude component of \vec{R}_{in} generated by \vec{U}' and \vec{L}' .

[0210] Still referring to FIG. 9A, it is noted that, at any time instant, \vec{R}' can be obtained by the sum of an upper phasor \vec{U}' and a lower phasor \vec{L}' . Further, \vec{U}' and \vec{L}' can be maintained to have substantially constant magnitude. The phasors, \vec{U}' and \vec{L}' , accordingly, represent two substantially constant envelope signals. $r'(t)$ can thus be obtained, at any time instant, by the sum of two substantially constant envelope signals that correspond to phasors \vec{U}' and \vec{L}' .

[0211] The phase shifts of phasors \vec{U}' and \vec{L}' relative to \vec{R}' are set according to the desired magnitude R of \vec{R}' . In the simplest case, when upper and lower phasors \vec{U}' and \vec{L}' are selected to have equal magnitude, upper and lower phasors \vec{U}' and \vec{L}' are substantially symmetrically shifted in phase relative to \vec{R}' . This is illustrated in the example of FIG. 9A. It is noted that terms and phrases indicating or suggesting orientation, such as but not limited to "upper and lower" are used herein for ease of reference and are not functionally or structurally limiting.

[0212] It can be verified that, for the case illustrated in FIG. 9A, the phase shift of \vec{U}' and \vec{L}' relative to \vec{R}' , illustrated as angle

$$\frac{\phi}{2}$$

in FIG. 9A, is related to the magnitude of \vec{R}' as follows:

$$\frac{\phi}{2} = \cot^{-1} \left(\frac{R}{2\sqrt{1 - \frac{R^2}{4}}} \right) \quad (7)$$

where R represents a normalized magnitude of phasor \vec{R}' .

[0213] Equation (7) can further be reduced to

$$\frac{\phi}{2} = \cos^{-1} \left(\frac{R}{2} \right) \quad (7.10)$$

where R represents a normalized magnitude of phasor \vec{R}' .

[0214] Alternatively, any substantially equivalent mathematical equations or other substantially equivalent mathematical techniques such as look up tables can be used.

[0215] It follows from the above discussion that, in phasor representation, any phasor \vec{R}' of variable magnitude and phase can be constructed by the sum of two constant magnitude phasor components:

$$\vec{R}' = \vec{U}' + \vec{L}'$$

$$|\vec{U}'| = |\vec{L}'| = A = \text{constant} \quad (8)$$

[0216] Correspondingly, in the time domain, a time-varying envelope sinusoidal signal $r'(t) = R(t) \times \cos(\omega t)$ is constructed by the sum of two constant envelope signals as follows:

$$r'(t) = U'(t) + L'(t); \quad (9)$$

$$U'(t) = A \times \cos\left(\omega t + \frac{\phi}{2}\right);$$

$$L'(t) = A \times \cos\left(\omega t - \frac{\phi}{2}\right);$$

where A is a constant and

$$\frac{\phi}{2}$$

is as shown in equation (7).

[0217] From FIG. 9A, it can be farther verified that equations (9) can be rewritten as:

$$r'(t) = U''(t) + L''(t);$$

$$U''(t) = C \cos(\omega t) + \alpha \sin(\omega t);$$

$$L''(t) = C \cos(\omega t) - \beta \sin(\omega t); \quad (10)$$

where C denotes the real part component of phasors \vec{U}' and \vec{L}' and is equal to

$$A \times \cos\left(\frac{\phi}{2}\right).$$

Note that C is a common component of \vec{U}' and \vec{L}' . α and β denote the imaginary part components of phasors \vec{U}' and \vec{L}' , respectively,

$$\alpha = \beta = A \times \sin\left(\frac{\phi}{2}\right).$$

Accordingly, from equations (12),

$$r'(t) = 2C \times \cos(\omega t) = 2A \times \cos\left(\frac{\phi}{2}\right) \times \cos(\omega t).$$

As understood by a person skilled in the art based on the teachings herein, other equivalent and/or simplified representations of the above representations of the quantities A, B, and C may also be used, including look up tables, for example.

[0218] Note that \vec{R}_{in} is shifted by θ degrees relative to \vec{R}' . Accordingly, using equations (8), it can be deduced that:

$$\vec{R}_{in} = \vec{R}' e^{j\theta} = (\vec{U}' + \vec{L}') e^{j\theta} = \vec{U}' e^{j\theta} + \vec{L}' e^{j\theta} \quad (11)$$

[0219] Equations (11) imply that a representation of \vec{R}_{in} can be obtained by summing phasors \vec{U}' and \vec{L}' , described above, shifted by θ degrees. Further, an amplified output version, \vec{R}_{out} , of \vec{R}_{in} can be obtained by separately amplifying substantially equally each of the θ degrees shifted versions of phasors \vec{U}' and \vec{L}' , and summing them. FIG. 9B illustrates this concept. In FIG. 9B, phasors \vec{U} and \vec{L} represent θ degrees shifted and amplified versions of phasors \vec{U}' and \vec{L}' . Note that, since \vec{U}' and \vec{L}' are constant magnitude phasors, \vec{U} and \vec{L} are also constant magnitude phasors. Phasors \vec{U} and \vec{L} sum, as shown FIG. 9B, to phasor \vec{R}_{out} , which is a power amplified version of input signal \vec{R}_{in} .

[0220] Equivalently, in the time domain, it can be shown that:

$$r_{out}(t) = U(t) + L(t);$$

$$U(t) = K[C \cos(\omega t + \theta) + \alpha \sin(\omega t + \theta)];$$

$$L(t) = K[C \cos(\omega t + \theta) - \beta \sin(\omega t + \theta)]. \quad (12)$$

where $r_{out}(t)$ corresponds to the time domain signal represented by phasor \vec{R}_{out} , $U(t)$ and $L(t)$ correspond to the time domain signals represented by phasors \vec{U} and \vec{L} , and K is the power amplification factor.

[0221] A person skilled in the art will appreciate that, whereas the time domain representations in equations (9) and (10) have been provided for the case of a sinusoidal waveform, equivalent representations can be developed for non-sinusoidal waveforms using appropriate basis functions.

[0222] FIG. 10 is a block diagram that conceptually illustrates an exemplary embodiment 1000 of the CPCP 2-Branch VPA embodiment. An output signal $r(t)$ of desired power level and frequency characteristics is generated from in-phase and quadrature components according to the CPCP 2-Branch VPA embodiment.

[0223] In the example of FIG. 10, a clock signal 1010 represents a reference signal for generating output signal $r(t)$. Clock signal 1010 is of the same frequency as that of desired output signal $r(t)$.

[0224] Referring to FIG. 10, an Iclk_phase signal 1012 and a Qclk_phase signal 1014 represent amplitude analog values that are multiplied by the in-phase and quadrature components of Cclk signal 1010 and are calculated from the baseband I and Q signals.

[0225] Still referring to FIG. 10, clock signal 1010 is multiplied with Iclk_phase signal 1012. In parallel, a 90° degrees shifted version of clock signal 1010 is multiplied with Qclk_phase signal 1014. The two multiplied signals are combined to generate Rclk signal 1016. Rclk signal 1016 is of the same frequency as clock signal 1010. Further, Rclk signal 1016 is characterized by a phase shift angle according to the ratio of Q(t) and I(t). The magnitude of Rclk signal 1016 is such that $R^2_{clk} = I^2_{clk_phase} + Q^2_{clk_phase}$. Accordingly, Rclk signal 1016 represents a substantially constant envelope signal having the phase characteristics of the desired output signal $r(t)$.

[0226] Still referring to FIG. 10, Rclk signal 1016 is input, in parallel, into two vector modulators 1060 and 1062. Vector modulators 1060 and 1062 generate the $U(t)$ and $L(t)$ substantially constant envelope constituents, respectively, of the

desired output signal $r(t)$ as described in (12). In vector modulator **1060**, an in-phase Rclk signal **1020**, multiplied with Common signal **1028**, is combined with a 900 degree shifted version **1018** of Rclk signal, multiplied with first signal **1026**. In parallel, in vector modulator **1062**, an in-phase Rclk signal **1022**, multiplied with Common signal **1028**, is combined with a 900 degrees shifted version **1024** of Rclk signal, multiplied with second signal **1030**. Common signal **1028**, first signal **1026**, and second signal **1030** correspond, respectively, to the real part C and the imaginary parts a and β described in equation (12).

[0227] Output signals **1040** and **1042** of respective vector modulators **1060** and **1062** correspond, respectively, to the $U(t)$ and $L(t)$ constant envelope constituents of input signal $r(t)$.

[0228] As described above, signals **1040** and **1042** are characterized by having substantially equal and constant magnitude envelopes. Accordingly, when signals **1040** and **1042** are input into corresponding power amplifiers (PA) **1044** and **1046**, corresponding amplified signals **1048** and **1050** are substantially constant envelope signals.

[0229] Power amplifiers **1044** and **1046** apply substantially equal power amplification to signals **1040** and **1042**, respectively. In an embodiment, the power amplification level of PAs **1044** and **1046** is set according to the desired power level of output signal $r(t)$. Further, amplified signals **1048** and **1050** are in-phase relative to each other. Accordingly, when summed together, as shown in FIG. 10, resulting signal **1052** corresponds to the desired output signal $r(t)$.

[0230] FIG. 10A is another exemplary embodiment **1000A** of the CPCP 2-Branch VPA embodiment. Embodiment **1000A** represents a Multiple Input Single Output (MISO) implementation of embodiment **1000** of FIG. 10.

[0231] In embodiment **1000A**, constant envelope signals **1040** and **1042**, output from vector modulators **1060** and **1062**, are input into MISO PA **1054**. MISO PA **1054** is a two-input single-output power amplifier. In an embodiment, MISO PA **1054** may include various elements, such as pre-drivers, drivers, power amplifiers, and process detectors (not shown in FIG. 10A), for example. Further, MISO PA **1054** is not limited to being a two-input PA as shown in FIG. 10A. In other embodiments, as will be described further below with reference to FIGS. 51A-H, PA **1054** can have any number of inputs.

[0232] Operation of the CPCP 2-Branch VPA embodiment is depicted in the process flowchart **1100** of FIG. 11.

[0233] The process begins at step **1110**, which includes receiving a baseband representation of the desired output signal. In an embodiment, this involves receiving in-phase (I) and quadrature (Q) components of the desired output signal. In another embodiment, this involves receiving magnitude and phase of the desired output signal.

[0234] Step **1120** includes receiving a clock signal set according to a desired output signal frequency of the desired output signal. In the example of FIG. 10, step **1120** is achieved by receiving clock signal **1010**.

[0235] Step **1130** includes processing the clock signal to generate a normalized clock signal having a phase shift angle according to the received I and Q components. In an embodiment, the normalized clock signal is a constant envelope signal having a phase shift angle according to a ratio of the I and Q components. The phase shift angle of the normalized clock is relative to the original clock signal. In the example of FIG. 10, step **1130** is achieved by multiplying clock signal

1010's in-phase and quadrature components with I_{clk_phase} **1012** and Q_{clk_phase} **1014** signals, and then summing the multiplied signal to generate Rclk signal **1016**.

[0236] Step **1140** includes the processing of the I and Q components to generate the amplitude information required to produce first and second substantially constant envelope constituent signals.

[0237] Step **1150** includes processing the amplitude information of step **1140** and the normalized clock signal Rclk to generate the first and second constant envelope constituents of the desired output signal. In an embodiment, step **1150** involves phase shifting the first and second constant envelope constituents of the desired output signal by the phase shift angle of the normalized clock signal. In the example of FIG. 10, step **1150** is achieved by vector modulators **1060** and **1062** modulating Rclk signal **1016** with first signal **1026**, second signal **1030**, and common signal **1028** to generate signals **1040** and **1042**.

[0238] Step **1160** includes individually amplifying the first and second constant envelope constituents, and summing the amplified signals to generate the desired output signal. In an embodiment, the amplification of the first and second constant envelope constituents is substantially equal and according to a desired power level of the desired output signal. In the example of FIG. 10, step **1160** is achieved by PAs **1044** and **1046** amplifying signals **1040** and **1042** to generate amplified signals **1048** and **1050**.

[0239] FIG. 12 is a block diagram that illustrates an exemplary embodiment of a vector power amplifier **1200** implementing the process flowchart **1100**. Optional components are illustrated with dashed lines, although in other embodiments more or less components may be optional.

[0240] Referring to FIG. 12, in-phase (I) and quadrature (Q) information signal **1210** is received by an I and Q Data Transfer Function module **1216**. In an embodiment, I and Q Data Transfer Function **1216** samples signal **1210** according to a sample clock **1212**. I and Q information signal **1210** includes baseband I and Q information of a desired output signal $r(t)$.

[0241] In an embodiment, I and Q Data Transfer Function module **1216** processes information signal **1210** to generate information signals **1220**, **1222**, **1224**, and **1226**. The operation of I and Q Data Transfer Function module **1216** is further described below in section 3.4.

[0242] Referring to FIG. 12, information signal **1220** includes quadrature amplitude information of first and second constant envelope constituents of a baseband version of desired output signal $r(t)$. With reference to FIG. 9A, for example, information signal **1220** includes the α and β quadrature components. Referring again to FIG. 12, information signal **1226** includes in-phase amplitude information of the first and second constant envelope constituents of the baseband version of signal $r(t)$. With reference to FIG. 9A, for example, information signal **1226** includes the common C in-phase component.

[0243] Still referring to FIG. 12, information signals **1222** and **1224** include normalized in-phase I_{clk_phase} and quadrature Q_{clk_phase} signals, respectively. I_{clk_phase} and Q_{clk_phase} are normalized versions of the I and Q information signals included in signal **1210**. In an embodiment, I_{clk_phase} and Q_{clk_phase} are normalized such that that $(I^2_{clk_phase} + Q^2_{clk_phase} = \text{constant})$. It is noted that the phase of signal **1250** corresponds to the phase of the desired output

signal and is created from I_{clk_phase} and Q_{clk_phase} . Referring to FIG. 9B, I_{clk_phase} and Q_{clk_phase} are related to I and Q as follows:

$$\theta = \tan^{-1}\left(\frac{Q}{I}\right) = \tan^{-1}\left(\frac{Q_{clk_phase}}{I_{clk_phase}}\right) \quad (12.1)$$

where θ represents the phase of the desired output signal, represented by phasor \vec{R}_{out} in FIG. 9B. The sign information of the baseband I and Q information must be taken into account to calculate θ for all four quadrants.

[0244] In the exemplary embodiment of FIG. 12, information signals 1220, 1222, 1224, and 1226 are digital signals. Accordingly, each of signals 1220, 1222, 1224, and 1226 is fed into a corresponding digital-to-analog converter (DAC) 1230, 1232, 1234, and 1236. The resolution and sample rate of DACs 1230, 1232, 1234, and 1236 is selected according to specific signaling schemes. DACs 1230, 1232, 1234, and 1236 are controlled by DAC clock signals 1221, 1223, 1225, and 1227, respectively. DAC clock signals 1221, 1223, 1225, and 1227 may be derived from a same clock signal or may be independent.

[0245] In other embodiments, information signals 1220, 1222, 1224, and 1226 are generated in analog format and no DACs are required.

[0246] Referring to FIG. 12, DACs 1230, 1232, 1234, and 1236 convert digital information signals 1220, 1222, 1224, and 1226 into corresponding analog signals, and input these analog signal into optional interpolation filters 1231, 1233, 1235, and 1237, respectively. Interpolation filters 1231, 1233, 1235, and 1237, which also serve as anti-aliasing filters, shape the DACs output signals to produce the desired output waveform. Interpolation filters 1231, 1233, 1235, and 1237 generate signals 1240, 1244, 1246, and 1248, respectively. Signal 1242 represents the inverse of signal 1240.

[0247] Still referring to FIG. 12, signals 1244 and 1246, which include I_{clk_phase} and Q_{clk_phase} information, are input into a vector modulator 1238. Vector modulator 1238 multiplies signal 1244 with a channel clock signal 1214. Channel clock signal 1214 is selected according to a desired output signal frequency. In parallel, vector modulator 1238 multiplies signal 1246 with a 90° shifted version of channel clock signal 1214. In other words, vector modulator 1238 generates an in-phase component having amplitude of I_{clk_phase} and a quadrature component having amplitude of Q_{clk_phase} .

[0248] Vector modulator 1238 combines the two modulated signals to generate Rclk signal 1250. Rclk signal 1250 is a substantially constant envelope signal having the desired output frequency and a phase shift angle according to the I and Q data included in signal 1210.

[0249] Still referring to FIG. 12, signals 1240, 1242, and 1248 include the U, L, and Common C amplitude components, respectively, of the complex envelope of signal $r(t)$. Signals 1240, 1242, and 1248 along with Rclk signal 1250 are input into vector modulators 1260 and 1262.

[0250] Vector modulator 1260 combines signal 1240, multiplied with a 90° shifted version of Rclk signal 1250, and signal 1248, multiplied with a 0° shifted version of Rclk signal 1250, to generate output signal 1264. In parallel, vector modulator 1262 combines signal 1242, multiplied with a 90°

shifted version of Rclk signal 1250, and signal 1248, modulated with a 0° shifted version of Rclk signal 1250, to generate output signal 1266.

[0251] Output signals 1264 and 1266 represent substantially constant envelope signals. Further, phase shifts of output signals 1264 and 1266 relative to Rclk signal 1250 are determined by the angle relationships associated with the ratios α/C and β/C , respectively. In an embodiment, $\alpha = -\beta$ and therefore output signals 1264 and 1266 are symmetrically phased relative to Rclk signal 1250. With reference to FIG. 9B, for example, output signals 1264 and 1266 correspond, respectively, to the \vec{U} and \vec{L} constant magnitude phasors.

[0252] A sum of output signals 1264 and 1266 results in a channel-clock-modulated signal having the I and Q characteristics of baseband signal $r(t)$. To achieve a desired power level at the output of vector power amplifier 1200, however, signals 1264 and 1266 are amplified to generate an amplified output signal. In the embodiment of FIG. 12, signals 1264 and 1266 are, respectively, input into power amplifiers (PAs) 1270 and 1272 and amplified. In an embodiment, PAs 1270 and 1272 include switching power amplifiers. Autobias circuitry 1218 controls the bias of PAs 1270 and 1272 as further described below in section 3.5.2. In the embodiment of FIG. 12, for example, autobias circuitry 1218 provides a bias voltage 1228 to PAs 1270 and 1272.

[0253] In an embodiment, PAs 1270 and 1272 apply substantially equal power amplification to respective constant envelope signals 1264-1266. In an embodiment, the power amplification is set according to the desired output power level. In other embodiments of vector power amplifier 1200, PA drivers and/or pre-drivers are additionally employed to provide additional power amplification capability to the amplifier. In the embodiment of FIG. 12, for example, PA drivers 1284 and 1286 are optionally added, respectively, between vector modulators 1260 and 1262 and subsequent PAs 1270 and 1272.

[0254] Respective output signals 1274 and 1276 of PAs 1270 and 1272 are substantially constant envelope signals. Further, when output signals 1274 and 1276 are summed, the resulting signal has minimal non-linear distortion. In the embodiment of FIG. 12, output signals 1274 and 1276 are coupled together to generate output signal 1280 of vector power amplifier 1200. In an embodiment, no isolation is used in coupling the outputs of PAs 1270 and 1272. Accordingly, minimal power loss is incurred by the coupling. In an embodiment, the outputs of PAs 1270 and 1272 are directly coupled together using a wire. Direct coupling in this manner means that there is minimal or no resistive, inductive, or capacitive isolation between the outputs of PAs 1270 and 1272. In other words, outputs of PAs 1270 and 1272 are coupled together without intervening components. Alternatively, in an embodiment, the outputs of PAs 1270 and 1272 are coupled together indirectly through inductances and/or capacitances that result in low or minimal impedance connections, and/or connections that result in minimal isolation and minimal power loss. Alternatively, outputs of PAs 1270 and 1272 are coupled using well known combining techniques, such as Wilkinson, hybrid combiners, transformers, or known active combiners. In an embodiment, the PAs 1270 and 1272 provide integrated amplification and power combining in a single operation. In an embodiment, one or more of the power amplifiers and/or drivers described herein are implemented using multiple input, single output power amplification techniques, examples of which are shown in FIGS. 12A, 12B, and 51A-H.

[0255] Output signal **1280** represents a signal having the I and Q characteristics of baseband signal $r(t)$ and the desired output power level and frequency. In embodiments of vector power amplifier **1200**, a pull-up impedance **1288** is coupled between the output of vector power amplifier **1200** and a power supply. In other embodiments, an impedance matching network **1290** is coupled at the output of vector power amplifier **1200**. Output stage embodiments according to power amplification methods and systems of the present invention will be further described below in section 3.5.

[0256] In other embodiments of vector power amplifier **1200**, process detectors are employed to compensate for any process variations in circuitry of the amplifier. In the exemplary embodiment of FIG. 12, for example, process detector **1282** is optionally added to monitor variations in PA drivers **1284** and **1286**.

[0257] FIG. 12A is a block diagram that illustrates another exemplary embodiment of a vector power amplifier **1200A** implementing the process flowchart **1100**. Optional components are illustrated with dashed lines, although in other embodiments more or less components may be optional.

[0258] Embodiment **1200A** illustrates a multiple-input single-output (MISO) implementation of embodiment **1200**. In embodiment **1200A**, constant envelope signals **1261** and **1263**, output from vector modulators **1260** and **1262**, are input into MISO PA **1292**. MISO PA **1292** is a two-input single-output power amplifier. In an embodiment, MISO PA **1292** includes elements **1270**, **1272**, **1282**, **1284**, and **1286** as shown in the embodiment of FIG. 12. In another embodiment, MISO PA **1292** may include other elements, such as pre-drivers, not shown in the embodiment of FIG. 12. Further, MISO PA **1292** is not limited to being a two-input PA as shown in FIG. 12A. In other embodiments as will be described further below with reference to FIGS. 51A-H, PA **1292** can have any number of inputs and outputs.

[0259] Still referring to FIG. 12A, embodiment **1200A** illustrates one implementation for delivering autobias signals to MISO PA **1292**. In the embodiment of FIG. 12A, Autobias signal **1228** generated by Autobias circuitry **1218**, has one or more signals derived from it to bias different stages of MISO PA **1292**. As shown in the example of FIG. 12A, three bias control signals Bias A, Bias B, and Bias C are derived from Autobias signal **1228**, and then input at different stages of MISO PA **1292**. For example, Bias C may be the bias signal to the pre-driver stage of MISO PA **1292**. Similarly, Bias B and Bias A may be the bias signals to the driver and PA stages of MISO PA **1292**.

[0260] In another implementation, shown in embodiment **1200B** of FIG. 12 B, Autobias circuitry **1218** generates separate Autobias signals **1295**, **1296**, and **1297**, corresponding to Bias A, Bias B, and Bias C, respectively. Signals **1295**, **1296**, and **1297** may or may not be generated separately within Autobias circuitry **1218**, but are output separately as shown. Further, signals **1295**, **1296**, and **1297** may or may not be related as determined by the biasing of the different stages of MISO PA **1294**.

[0261] Other aspects of vector power amplifiers **1200A** and **1200B** substantially correspond to those described above with respect to vector power amplifier **1200**.

[0262] FIG. 13 is a block diagram that illustrates another exemplary embodiment **1300** of a vector power amplifier according to the CPCP 2-Branch VPA embodiment. Optional

components are illustrated with dashed lines, although in other embodiments more or less components may be optional.

[0263] In the exemplary embodiment of FIG. 13, a DAC of sufficient resolution and sample rate **1320** replaces DACs **1230**, **1232**, **1234** and **1236** of the embodiment of FIG. 12. DAC **1320** is controlled by a DAC clock **1324**.

[0264] DAC **1320** receives information signal **1310** from I and Q Data Transfer Function module **1216**. Information signal **1310** includes identical information content to signals **1220**, **1222**, **1224** and **1226** in the embodiment of FIG. 12.

[0265] DAC **1320** may output a single analog signal at a time. Accordingly, a sample-and-hold architecture may be used as shown in FIG. 13.

[0266] DAC **1320** sequentially outputs analog signals **1332**, **1334**, **1336**, **1336** to a first set of sample-and-hold circuits **1342**, **1344**, **1346**, and **1348**. In an embodiment, DAC **1230** is clocked at a sufficient rate to replace DACs **1230**, **1232**, **1234**, and **1236** of the embodiment of FIG. 12. An output selector **1322** determines which of output signals **1332**, **1334**, **1336**, and **1338** should be selected for output.

[0267] DAC **1320**'s DAC clock signal **1324**, output selector signal **1322**, and sample-and-hold clocks **1340A-D** and **1350** are controlled by a control module that can be independent or integrated into transfer function module **1216**.

[0268] In an embodiment, sample-and-hold circuits (S/H **1342**, **1344**, **1346**, and **1348** hold the received analog values and, according to a clock signal **1340A-D**, release the values to a second set of sample-and-hold circuits **1352**, **1354**, **1356**, and **1358**. For example, S/H **1342** release its value to S/H **1352** according to a received clock signal **1340A**. In turn, sample-and-hold circuits **1352**, **1354**, **1356**, and **1358** hold the received analog values, and simultaneously release the values to interpolation filters **1231**, **1233**, **1235**, and **1237** according to a common clock signal **1350**. A common clock signal **1350** is used in order to ensure that the outputs of S/H **1352**, **1354**, **1356**, and **1358** are time-aligned.

[0269] In another embodiment, a single layer of S/H circuitry that includes S/H **1342**, **1344**, **1346**, and **1348** can be employed. Accordingly, S/H circuits **1342**, **1344**, **1346**, and **1348** receive analog values from DAC **1320**, and each releases its received value according to a clock independent of the others. For example, S/H **1342** is control led by clock **1340A**, which may not be synchronized with clock **1340B** that controls S/H **1344**. To ensure that outputs of S/H circuits **1342**, **1344**, **1346**, and **1348** are time-aligned, delays between clocks **1340A-D** are pre-compensated for in prior stages of the amplifier. For example, DAC **1320** outputs signal **1332**, **1334**, **1336**, and **1338** with appropriately selected delays to S/H circuits **1342**, **1344**, **1346**, and **1348** in order to compensate for the time differences between clocks **1340A-D**.

[0270] Other aspects of vector power amplifier **1300** are substantially equivalent to those described above with respect to vector power amplifier **1200**.

[0271] FIG. 13A is a block diagram that illustrates another exemplary embodiment **1300A** of a vector power amplifier according to the CPCP 2-Branch VPA embodiment. Optional components are illustrated with dashed lines, although in other embodiments more or less components may be optional. Embodiment **1300A** is a MISO implementation of embodiment **1300** of FIG. 13.

[0272] In the embodiment of FIG. 13A, constant envelope signals **1261** and **1263** output from vector modulators **1260** and **1262** are input into MISO PA **1360**. MISO PA **1360** is a

two-input single-output power amplifier. In an embodiment, MISO PA 1360 includes elements 1270, 1272, 1282, 1284, and 1286 as shown in the embodiment of FIG. 13. In another embodiment, MISO PA 1360 may include other elements, such as pre-drivers, not shown in the embodiment of FIG. 13, or functional equivalents thereof. Further, MISO PA 1360 is not limited to being a two-input PA as shown in FIG. 13A. In other embodiments as will be described further below with reference to FIGS. 51A-H, PA 1360 can have any number of inputs.

[0273] The embodiment of FIG. 13A further illustrates two different sample and hold architectures with a single or two levels of S/H circuitry as shown. The two implementations have been described above with respect to FIG. 13.

[0274] Embodiment 1300A also illustrates optional bias control circuitry 1218 and associated bias control signal 1325, 1326, and 1327. Signals 1325, 1326, and 1327 may be used to bias different stages of MISO PA 1360 in certain embodiments.

[0275] Other aspects of vector power amplifier 1300A are equivalent to those described above with respect to vector power amplifiers 1200 and 1300.

3.3) Direct Cartesian 2-Branch Vector Power Amplifier

[0276] A Direct Cartesian 2-Branch VPA embodiment shall now be described. This name is used herein for reference purposes, and is not functionally or structurally limiting.

[0277] According to the Direct Cartesian 2-Branch VPA embodiment, a time-varying envelope signal is decomposed into two constant envelope constituent signals. The constituent signals are individually amplified equally or substantially equally, and then summed to construct an amplified version of the original time-varying envelope signal.

[0278] In one embodiment of the Direct Cartesian 2-Branch VPA embodiment, a magnitude and a phase angle of a time-varying envelope signal are calculated from in-phase and quadrature components of an input signal. Using the magnitude and phase information, in-phase and quadrature amplitude components are calculated for two constant envelope constituents of the time-varying envelope signal. The two constant envelope constituents are then generated, amplified equally or substantially equally, and summed to generate an amplified version of the original time-varying envelope signal R_m .

[0279] The concept of the Direct Cartesian 2-Branch VPA will now be described with reference to FIGS. 9A and 14.

[0280] As described and verified above with respect to FIG.

9A, the phasor \vec{R}' can be obtained by the sum of an upper phasor \vec{U}' and a lower phasor \vec{L}' appropriately phased to produce \vec{R}' . \vec{R}' is calculated to be proportional to the magnitude R_m . Further, \vec{U}' and \vec{L}' can be maintained to have substantially constant magnitude. In the time domain, \vec{U}' and \vec{L}' represent two substantially constant envelope signals. The time domain equivalent $r'(t)$ of \vec{R}' can thus be obtained, at any time instant, by the sum of two substantially constant envelope signals.

[0281] For the case illustrated in FIG. 9A, the phase shift of \vec{U}' and \vec{L}' relative to \vec{R}' , illustrated as angle

$$\frac{\phi}{2}$$

in FIG. 9A, is related to the magnitude of \vec{R}' as follows:

$$\frac{\phi}{2} = \cot^{-1} \left(\frac{R}{2\sqrt{1 - \frac{R^2}{4}}} \right) \quad (13)$$

where R represents the normalized magnitude of phasor \vec{R}' .

[0282] In the time domain, it was shown that a time-varying envelope signal, $r'(t) = R(t) \cos(\omega t)$ for example, can be constructed by the sum of two constant envelope signals as follows:

$$\begin{aligned} r'(t) &= U'(t) + L'(t); \\ U'(t) &= C \times \cos(\omega t) + \alpha \times \sin(\omega t); \\ L'(t) &= C \times \cos(\omega t) - \beta \times \sin(\omega t). \end{aligned} \quad (14)$$

where C denotes the in-phase amplitude component of phasors \vec{U}' and \vec{L}' and is equal or substantially equal to

$$A \times \cos\left(\frac{\phi}{2}\right)$$

(A being a constant). α and β denote the quadrature amplitude components of phasors \vec{U}' and \vec{L}' , respectively.

$$\alpha = \beta = A \times \sin\left(\frac{\phi}{2}\right).$$

Note that equations (14) can be modified for non-sinusoidal signals by changing the basis function from sinusoidal to the desired function.

[0283] FIG. 14 illustrates phasor \vec{R} and its two constant magnitude constituent phasors \vec{U} and \vec{L} . \vec{R} is shifted by θ degrees relative to \vec{R}' in FIG. 9A. Accordingly, it can be verified that:

$$\begin{aligned} \vec{R} &= \vec{R}' \times e^{j\theta} = (\vec{U}' + \vec{L}') \times e^{j\theta} = \vec{U} + \vec{L}; \\ \vec{U} &= \vec{U}' \times e^{j\theta}; \\ \vec{L} &= \vec{L}' \times e^{j\theta}. \end{aligned} \quad (15)$$

[0284] From equations (15), it can be farther shown that:

$$\begin{aligned} \vec{U} &= \vec{U}' \times e^{j\theta} = (C + j\alpha) \times e^{j\theta}; \\ \Rightarrow \vec{U} &= (C + j\alpha)(\cos\theta + j\sin\theta) \\ &= (C\cos\theta - \alpha\sin\theta) + j(C\sin\theta + \alpha\cos\theta). \end{aligned} \quad (16)$$

[0285] Similarly, it can be shown that:

$$\begin{aligned}\vec{L} &= \vec{L}' \times e^{j\theta} \\ &= (C + j\beta) \times e^{j\theta}; \\ \Rightarrow \vec{L} &= (C + j\beta)(\cos\theta + j\sin\theta) \\ &= (C\cos\theta - \beta\sin\theta) + j(C\sin\theta + \beta\cos\theta).\end{aligned}\quad (17)$$

[0286] Equations (16) and (17) can be re-written as:

$$\begin{aligned}\vec{U} &= (C \cos \theta - \alpha \sin \theta) + j(C \sin \theta + \alpha \cos \theta) = U_x + jU_y; \\ \vec{L} &= (C \cos \theta - \beta \sin \theta) + j(C \sin \theta + \beta \cos \theta) = L_x + jL_y.\end{aligned}\quad (18)$$

[0287] Equivalently, in the time domain:

$$\begin{aligned}U(t) &= U_x \phi_1(t) + U_y \phi_2(t); \\ L(t) &= L_x \phi_1(t) + L_y \phi_2(t);\end{aligned}\quad (19)$$

[0288] where $\phi_1(t)$ and $\phi_2(t)$ represent an appropriately selected orthogonal basis functions.

[0289] From equations (18) and (19), it is noted that it is sufficient to calculate the values of α , β , C and $\sin(\Theta)$ and $\cos(\Theta)$ in order to determine the two constant envelope constituents of a time-varying envelope signal $r(t)$. Further, α , β and C can be entirely determined from magnitude and phase information, equivalently I and Q components, of signal $r(t)$.

[0290] FIG. 15 is a block diagram that conceptually illustrates an exemplary embodiment 1500 of the Direct Cartesian 2-Branch VPA embodiment. An output signal $r(t)$ of desired power level and frequency characteristics is generated from in-phase and quadrature components according to the Direct Cartesian 2-Branch VPA embodiment.

[0291] In the example of FIG. 15, a clock signal 1510 represents a reference signal for generating output signal $r(t)$. Clock signal 1510 is of the same frequency as that of desired output signal $r(t)$.

[0292] Referring to FIG. 15, exemplary embodiment 1500 includes a first branch 1572 and a second branch 1574. The first branch 1572 includes a vector modulator 1520 and a power amplifier (PA) 1550. Similarly, the second branch 1574 includes a vector modulator 1530 and a power amplifier (PA) 1560.

[0293] Still referring to FIG. 15, clock signal 1510 is input, in parallel, into vector modulators 1520 and 1530. In vector modulator 1520, an in-phase version 1522 of clock signal 1510, multiplied with U_x signal 1526, is summed with a 90° degrees shifted version 1524 of clock signal 1510, multiplied with U_y signal 1528. In parallel, in vector modulator 1530, an in-phase version 1532 of clock signal 1510, multiplied with L_x signal 1536, is summed with a 90° degrees shifted version 1534 of clock signal 1510, multiplied with L_y signal 1538. U_x signal 1526 and U_y signal 1528 correspond, respectively, to the in-phase and quadrature amplitude components of the $U(t)$ constant envelope constituent of signal $r(t)$ provided in equation (19). Similarly, L_x signal 1536, and L_y signal 1538 correspond, respectively, to the in-phase and quadrature amplitude components of the $L(t)$ constant envelope constituent of signal $r(t)$ provided in equation (19).

[0294] Accordingly, respective output signals 1540 and 1542 of vector modulators 1520 and 1530 correspond, respectively, to the $U(t)$ and $L(t)$ constant envelope constituents of signal $r(t)$ as described above in equations (19). As

described above, signals 1540 and 1542 are characterized by having equal and constant or substantially equal and constant magnitude envelopes.

[0295] Referring to FIG. 15, to generate the desired power level of output signal $r(t)$, signals 1540 and 1542 are input into corresponding power amplifiers 1550 and 1560.

[0296] In an embodiment, power amplifiers 1550 and 1560 apply equal or substantially equal power amplification to signals 1540 and 1542, respectively. In an embodiment, the power amplification level of PAs 1550 and 1560 is set according to the desired power level of output signal $r(t)$.

[0297] Amplified output signals 1562 and 1564 are substantially constant envelope signals. Accordingly, when summed together, as shown in FIG. 15, resulting signal 1570 corresponds to the desired output signal $r(t)$.

[0298] FIG. 15A is another exemplary embodiment 1500A of the Direct Cartesian 2-Branch VPA embodiment. Embodiment 1500A represents a Multiple Input Signal Output (MISO) implementation of embodiment 1500 of FIG. 15.

[0299] In embodiment 1500A, constant envelope signals 1540 and 1542, output from vector modulators 1520 and 1530, are input into MISO PA 1580. MISO PA 1580 is a two-input single-output power amplifier. In an embodiment, MISO PA 1580 may include various elements, such as pre-drivers, drivers, power amplifiers, and process detectors (not shown in FIG. 15A), for example. Further, MISO PA 1580 is not limited to being a two-input PA as shown in FIG. 15A. In other embodiments, as will be described further below with reference to FIGS. 51A-H, PA 1580 can have any number of inputs.

[0300] Operation of the Direct Cartesian 2-Branch VPA embodiment is depicted in the process flowchart 1600 of FIG. 16. The process begins at step 1610, which includes receiving a baseband representation of a desired output signal. In an embodiment, the baseband representation includes I and Q components. In another embodiment, the I and Q components are RF components that are down-converted to baseband.

[0301] Step 1620 includes receiving a clock signal set according to a desired output signal frequency of the desired output signal. In the example of FIG. 15, step 1620 is achieved by receiving clock signal 1510.

[0302] Step 1630 includes processing the I and Q components to generate in-phase and quadrature amplitude information of first and second constant envelope constituent signals of the desired output signal. In the example of FIG. 15, the in-phase and quadrature amplitude information is illustrated by U_x , U_y , L_x , and L_y .

[0303] Step 1640 includes processing the amplitude information and the clock signal to generate the first and second constant envelope constituent signals of the desired output signal. In an embodiment, the first and second constant envelope constituent signals are modulated according to the desired output signal frequency. In the example of FIG. 15, step 1640 is achieved by vector modulators 1520 and 1530, clock signal 1510, and amplitude information signals 1526, 1528, 1536, and 1538 to generate signals 1540 and 1542.

[0304] Step 1650 includes amplifying the first and second constant envelope constituents, and summing the amplified signals to generate the desired output signal. In an embodiment, the amplification of the first and second constant envelope constituents is according to a desired power level of the desired output signal. In the example of FIG. 15, step 1650 is achieved by PAs 1550 and 1560 amplifying respective signals

1540 and 1542 and, subsequently, by the summing of amplified signals 1562 and 1564 to generate output signal 1574.

[0305] FIG. 17 is a block diagram that illustrates an exemplary embodiment of a vector power amplifier 1700 implementing the process flowchart 1600. Optional components are illustrated with dashed lines, although other embodiments may have more or less optional components.

[0306] Referring to FIG. 17, in-phase (I) and quadrature (Q) information signal 1710 is received by an I and Q Data Transfer Function module 1716. In an embodiment, I and Q Data Transfer Function module 1716 samples signal 1710 according to a sample clock 1212. I and Q information signal 1710 includes baseband I and Q information.

[0307] In an embodiment, I and Q Data Transfer Function module 1716 processes information signal 1710 to generate information signals 1720, 1722, 1724, and 1726. The operation of I and Q Data Transfer Function module 1716 is further described below in section 3.4.

[0308] Referring to FIG. 17, information signal 1720 includes vector modulator 1750 quadrature amplitude information that is processed through DAC 1730 to generate signal 1740. Information signal 1722 includes vector modulator 1750 in-phase amplitude information that is processed through DAC 1732 to generate signal 1742. Signals 1740 and 1742 are calculated to generate a substantially constant envelope signal 1754. With reference to FIG. 14, for example, information signals 1720 and 1722 include the upper quadrature and in-phase components U_y and U_x , respectively.

[0309] Still referring to FIG. 17, information signal 1726 includes vector modulator 1752 quadrature amplitude information that is processed through DAC 1736 to generate signal 1746. Information signal 1724 includes vector modulator 1752 in-phase amplitude information that is processed through DAC 1734 to generate signal 1744. Signals 1744 and 1746 are calculated to generate a substantially constant envelope signal 1756. With reference to FIG. 14, for example, information signals 1724 and 1726 include the lower in-phase and quadrature components L_x and L_y , respectively.

[0310] In the exemplary embodiment of FIG. 17, information signals 1720, 1722, 1724 and 1726 are digital signals. Accordingly, each of signals 1720, 1722, 1724 and 1726 is fed into a corresponding digital-to-analog converter (DAC) 1730, 1732, 1734, and 1736. The resolution and sample rates of DACs 1730, 1732, 1734, and 1736 are selected according to the specific desired signaling schemes. DACs 1730, 1732, 1734, and 1736 are controlled by DAC clock signals 1721, 1723, 1725, and 1727, respectively. DAC clock signals 1721, 1723, 1725, and 1727 may be derived from a same clock or may be independent of each other.

[0311] In other embodiments, information signals 1720, 1722, 1724 and 1726 are generated in analog format and no DACs are required.

[0312] Referring to FIG. 17, DACs 1730, 1732, 1734, and 1736 convert digital information signals 1720, 1722, 1724, and 1726 into corresponding analog signals, and input these analog signals into optional interpolation filters 1731, 1733, 1735, and 1737, respectively. Interpolation filters 1731, 1733, 1735, and 1737, which also serve as anti-aliasing filters, shape the DACs output signals to produce the desired output waveform. Interpolation filters 1731, 1733, 1735, and 1737 generate signals 1740, 1742, 1744, and 1746, respectively.

[0313] Still referring to FIG. 17, signals 1740, 1742, 1744, and 1746 are input into vector modulators 1750 and 1752. Vector modulators 1750 and 1752 generate first and second

constant envelope constituents. In the embodiment of FIG. 17, channel clock 1714 is set according to a desired output signal frequency to thereby establish the frequency of the output signal 1770.

[0314] Referring to FIG. 17, vector modulator 1750 combines signal 1740, multiplied with a 90° shifted version of channel clock signal 1714, and signal 1742, multiplied with a 0° shifted version of channel clock signal 1714, to generate output signal 1754. In parallel, vector modulator 1752 combines signal 1746, multiplied with a 90° shifted version of channel clock signal 1714, and signal 1744, multiplied with a 0° shifted version of channel clock signal 1714, to generate output signal 1756.

[0315] Output signals 1754 and 1756 represent constant envelope signals. A sum of output signals 1754 and 1756 results in a carrier signal having the I and Q characteristics of the original baseband signal. In embodiments, to generate a desired power level at the output of vector power amplifier 1700, signals 1754 and 1756 are amplified and then summed. In the embodiment of FIG. 17, for example, signals 1754 and 1756 are, respectively, input into corresponding power amplifiers (PAs) 1760 and 1762. In an embodiment, PAs 1760 and 1762 include switching power amplifiers. Autobias circuitry 1718 controls the bias of PAs 1760 and 1762. In the embodiment of FIG. 17, for example, autobias circuitry 1718 provides a bias voltage 1728 to PAs 1760 and 1762.

[0316] In an embodiment, PAs 1760 and 1762 apply equal or substantially equal power amplification to respective constant envelope signals 1754 and 1756. In an embodiment, the power amplification is set according to the desired output power level. In other embodiments of vector power amplifier 1700, PA drivers are additionally employed to provide additional power amplification capability to the amplifier. In the embodiment of FIG. 17, for example, PA drivers 1774 and 1776 are optionally added, respectively, between vector modulators 1750 and 1752 and subsequent PAs 1760 and 1762.

[0317] Respective output signals 1764 and 1766 of PAs 1760 and 1762 are substantially constant envelope signals. In the embodiment of FIG. 17, output signals 1764 and 1766 are coupled together to generate output signal 1770 of vector power amplifier 1700. In embodiments, it is noted that the outputs of PAs 1760 and 1762 are directly coupled. Direct coupling in this manner means that there is minimal or no resistive, inductive, or capacitive isolation between the outputs of PAs 1760 and 1762. In other words, outputs of PAs 1760 and 1762 are coupled together without intervening components. Alternatively, in an embodiment, the outputs of PAs 1760 and 1762 are coupled together indirectly through inductances and/or capacitances that result in low or minimal impedance connections, and/or connections that result in minimal isolation and minimal power loss. Alternatively, outputs of PAs 1760 and 1762 are coupled using well known combining techniques, such as Wilkinson, hybrid couplers, transformers, or known active combiners. In an embodiment, the PAs 1760 and 1762 provide integrated amplification and power combining in a single operation. In an embodiment, one or more of the power amplifiers and/or drivers described herein are implemented using multiple input, single output (MISO) power amplification techniques, examples of which are shown in FIGS. 17A, 17B, and 51A-H.

[0318] Output signal 1770 represents a signal having the desired I and Q characteristics of the baseband signal and the desired output power level and frequency. In embodiments of

vector power amplifier 1700, a pull-up impedance 1778 is coupled between the output of vector power amplifier 1700 and a power supply. In other embodiments, an impedance matching network 1780 is coupled at the output of vector power amplifier 1700. Output stage embodiments according to power amplification methods and systems of the present invention will be further described below in section 3.5.

[0319] In other embodiments of vector power amplifier 1700, process detectors are employed to compensate for any process and/or temperature variations in circuitry of the amplifier. In the exemplary embodiment of FIG. 17, for example, process detector 1772 is optionally added to monitor variations in PA drivers 1774 and 1776.

[0320] FIG. 17A is a block diagram that illustrates another exemplary embodiment 1700A of a vector power amplifier implementing process flowchart 1600. Optional components are illustrated with dashed lines, although other embodiments may have more or less optional components. Embodiment 1700A illustrates a multiple-input single-output (MISO) implementation of the amplifier of FIG. 17. In the embodiment of FIG. 17A, constant envelope signals 1754 and 1756, output from vector modulators 1750 and 1760, are input into MISO PA 1790. MISO PA 1790 is a two-input single-output power amplifier. In an embodiment, MISO PA 1790 include elements 1760, 1762, 1772, 1774, and 1776 as shown in the embodiment of FIG. 17, or functional equivalents thereof. In another embodiment, MISO PA 1790 may include other elements, such as pre-drivers, not shown in the embodiment of FIG. 17. Further, MISO PA 1790 is not limited to being a two-input PA as shown in FIG. 17A. In other embodiments, as will be described further below with reference to FIGS. 51A-H, PA 1790 can have any number of inputs.

[0321] In another embodiment of embodiment 1700, shown as embodiment 1700B of FIG. 17B, optional Autobias circuitry 1218 generates separate bias control signals 1715, 1717, and 1719, corresponding to Bias A, Bias B, and Bias C, respectively. Signals 1715, 1717, and 1719 may or may not be generated separately within Autobias circuitry 1718, but are output separately as shown. Further, signals 1715, 1717, and 1719 may or may not be related as determined by the biasing required for the different stages of MISO PA 1790.

[0322] FIG. 18 is a block diagram that illustrates another exemplary embodiment 1800 of a vector power amplifier according to the Direct Cartesian 2-Branch VPA embodiment of FIG. 16. Optional components are illustrated with dashed lines, although other embodiments may have more or less optional components.

[0323] In the exemplary embodiment of FIG. 18, a DAC 1820 of sufficient resolution and sample rate replaces DACs 1730, 1732, 1734, and 1736 of the embodiment of FIG. 17. DAC 1820 is controlled by a DAC clock 1814.

[0324] DAC 1820 receives information signal 1810 from I and Q Data. Transfer Function n module 1716. Information signal 1810 includes identical information content to signals 1720, 1722, 1724, and 1726 in the embodiment of FIG. 17.

[0325] DAC 1820 may output a single analog signal at a time. Accordingly, a sample-and-hold architecture may be used as shown in FIG. 18.

[0326] In the embodiment of FIG. 18, DAC 1820 sequentially outputs analog signals 1822, 1824, 1826, and 1828 to sample-and-hold circuits 1832, 1834, 1836, and 1838, respectively. In an embodiment, DAC 1820 is of sufficient resolution and sample rate to replace DACs 1720, 1722, 1724, and 1726 of the embodiment of FIG. 17. An output selector

1812 determines which of output signals 1822, 1824, 1826, and 1828 are selected for output.

[0327] DAC 1820's DAC clock signal 1814, output selector signal 1812, and sample-and-hold clocks 1830A-D, and 1840 are controlled by a control module that can be independent or integrated into transfer function module 1716.

[0328] In an embodiment, sample-and-hold circuits 1832, 1834, 1836, and 1838 sample and hold their respective values and, according to a clock signal 1830A-D, release the values to a second set of sample-and-hold circuits 1842, 1844, 1846, and 1848. For example, S/H 1832 release's its value to S/H 1842 according to a received clock signal 1830A. In turn, sample-and-hold circuits 1842, 1844, 1846, and 1848 hold the received analog values, and simultaneously release the values to interpolation filters 1852, 1854, 1856, and 1858 according to a common clock signal 1840.

[0329] In another embodiment, a single set of S/H circuitry that includes S/H 1832, 1834, 1836, and 1838 can be employed. Accordingly, S/H circuits 1832, 1834, 1836, and 1838 receive analog values from DAC 1820, and each samples and holds its received value according to independent clocks 1830A-D. For example, S/H 1832 is controlled by clock 1830A, which may not be synchronized with clock 1830B that controls S/H 1834. For example, DAC 1820 outputs signals 1822, 1824, 1826, and 1828 with appropriately selected analog values calculated by transfer function module 1716 to S/H circuits 1832, 1834, 1836, and 1838 in order to compensate for the time differences between clocks 1830A-D.

[0330] Other aspects of vector power amplifier 1800 correspond substantially to those described above with respect to vector power amplifier 1700.

[0331] FIG. 18A is a block diagram that illustrates another exemplary embodiment 1800A of a vector power amplifier according to the Direct Cartesian 2-Branch VPA embodiment. Optional components are illustrated with dashed lines, although in other embodiments more or less components may be optional. Embodiment 1800A is a Multiple Input Single Output (MISO) implementation of embodiment 1800 of FIG. 18.

[0332] In the embodiment of FIG. 18A, constant envelope signals 1754 and 1756, output from vector modulators 1750 and 1752, are input into MISO PA 1860. MISO PA 1860 is a two-input single-output power amplifier. In an embodiment, MISO PA 1860 includes elements 1744, 1746, 1760, 1762, and 1772 as shown in the embodiment of FIG. 18, or functional equivalents thereof. In another embodiment, MISO PA 1860 may include other elements, such as pre-drivers, not shown in the embodiment of FIG. 17. Further, MISO PA 1860 is not limited to being a two-input PA as shown in FIG. 18A. In other embodiments as will be described further below with reference to FIGS. 51A-H, PA 1860 can have any number of inputs.

[0333] The embodiment of FIG. 18A further illustrates two different sample and hold architectures with a single or two levels of S/H circuitry as shown. The two implementations have been described above with respect to FIG. 18.

[0334] Other aspects of vector power amplifier 1800A are substantially equivalent to those described above with respect to vector power amplifiers 1700 and 1800.

3.4) I and Q Data to Vector Modulator Transfer Functions

[0335] In some of the above described embodiments, I and Q data transfer functions are provided to transform received I

and Q data into amplitude information inputs for subsequent stages of vector modulation and amplification. For example, in the embodiment of FIG. 17, I and Q Data Transfer Function module 1716 processes I and Q information signal 1710 to generate in-phase and quadrature amplitude information signals 1720, 1722, 1724, and 1726 of first and second constant envelope constituents 1754 and 1756 of signal $r(t)$. Subsequently, vector modulators 1750 and 1752 utilize the generated amplitude information signals 1720, 1722, 1724, and 1726 to create the first and second constant envelope constituent signals 1754 and 1756. Other examples include modules 710, 712, and 1216 in FIGS. 7, 8, 12, and 13. These modules implement transfer functions to transform I and/or Q data into amplitude information inputs for subsequent stages of vector modulation and amplification.

[0336] According to the present invention, I and Q Data Transfer Function modules may be implemented using digital circuitry, analog circuitry, software, firmware or any combination thereof.

[0337] Several factors affect the actual implementation of a transfer function according to the present invention, and vary from embodiment to embodiment. In one aspect, the selected VPA embodiment governs the amplitude information output of the transfer function and associated module. It is apparent, for example, that I and Q Data Transfer Function module 1216 of the PCP 2-Branch VPA embodiment 1200 differs in output than I and Q Data Transfer Function module 1716 of the Direct Cartesian 2-Branch VPA embodiment 1700.

[0338] In another aspect, the complexity of the transfer function varies according to the desired modulation scheme (s) that need to be supported by the VPA implementation. For example, the sample clock, the DAC sample rate, and the DAC resolution are selected in accordance with the appropriate transfer function to construct the desired output waveform (s).

[0339] According to the present invention, transfer function embodiments may be designed to support one or more VPA embodiments with the ability to switch between the supported embodiments as desired. Further, transfer function embodiments and associated modules can be designed to accommodate a plurality of modulation schemes. A person skilled in the art will appreciate, for example, that embodiments of the present invention may be designed to support a plurality of modulation schemes (individually or in combination) including, but not limited to, BPSK, QPSK, OQPSK, DPSK, CDMA, WCDMA, W-CDMA, GSM, EDGE, MPSK, MQAM, MSK, CPFSK, PM, FM, OFDM, and multi-tone signals. In an embodiment, the modulation scheme(s) may be configurable and/or programmable via the transfer function module.

3.4.1 Cartesian 4-Branch VPA Transfer Function

[0340] FIG. 19 is a process flowchart 1900 that illustrates an example I and Q transfer function embodiment according to the (Cartesian 4-Branch VPA embodiment. The process begins at step 1910, which includes receiving an in-phase data component and a quadrature data component. In the Cartesian 4-Branch VPA embodiment of FIG. 7A, for example, this is illustrated by I Data Transfer Function module 710 receiving I information signal 702, and Q Data Transfer Function module 712 receiving Q information signal 704. It is noted that, in the embodiment of FIG. 7A, I and Q Data Transfer Function modules 710 and 712 are illustrated as separate components.

In implementation, however, I and Q Data Transfer Function modules 710 and 712 may be separate or combined into a single module.

[0341] Step 1920 includes calculating a phase shift angle between first and second substantially equal and constant envelope constituents of the I component. In parallel, step 1920 also includes calculating a phase shift angle between first and second substantially equal and constant envelope constituents of the Q component. As described above, the first and second constant envelope constituents of the I components are appropriately phased relative to the I component. Similarly, the first and second constant envelope constituents of the Q components are appropriately phased relative to the Q component. In the embodiment of FIG. 7A, for example, step 1920 is performed by I and Q Data Transfer Function modules 710 and 712.

[0342] Step 1930 includes calculating in-phase and quadrature amplitude information associated with the first and second constant envelope constituents of the I component. In parallel, step 1930 includes calculating in-phase and quadrature amplitude information associated with the first and second constant envelope constituents of the Q component. In the embodiment of FIG. 7A, for example, step 1930 is performed by I and Q Data Transfer Function modules 710 and 712.

[0343] Step 1940 includes outputting the calculated amplitude information to a subsequent vector modulation stage. In the embodiment of FIG. 7A, for example, I and Q Transfer Function modules 710 and 712 output amplitude information signals 722, 724, 726, and 728 to vector modulators 760, 762, 764, and 766 through DACs 730, 732, 734, and 736.

[0344] FIG. 20 is a block diagram that illustrates an exemplary embodiment 2000 of a transfer function module, such as transfer function modules 710 and 712 of FIG. 7A, implementing the process flowchart 1900. In the example of FIG. 20, transfer function module 2000 receives I and Q data signals 2010 and 2012. In an embodiment, I and Q data signals 2010 and 2012 represent I and Q data components of a baseband signal, such as signals 702 and 704 in FIG. 7A.

[0345] Referring to FIG. 20, in an embodiment, transfer function module 2000 samples I and Q data signals 2010 and 2012 according to a sampling clock 2014. Sampled I and Q data signals are received by components 2020 and 2022, respectively, of transfer function module 2000. Components 2020 and 2022 measure, respectively, the magnitudes of the sampled I and Q data signals. In an embodiment, components 2020 and 2022 are magnitude detectors.

[0346] Components 2020 and 2022 output the measured I and Q magnitude information to components 2030 and 2032, respectively, of transfer function module 2000. In an embodiment, the measured I and Q magnitude information is in the form of digital signals. Based on the I magnitude information, component 2030 calculates a phase shift angle ϕ_I between first and second equal and constant or substantially equal and constant envelope constituents of the sampled I signal. Similarly, based on the Q magnitude information, component 2032 calculates phase shift angle ϕ_Q between a first and second equal and constant or substantially equal and constant envelope constituents of the sampled Q signal. This operation shall now be further described.

[0347] In the embodiment of FIG. 20, ϕ_I and ϕ_Q are illustrated as functions $f(I\vec{I})$ and $f(Q\vec{Q})$ of the I and Q magnitude signals. In embodiments, functions $f(I\vec{I})$ and $f(Q\vec{Q})$ are set

according to the relative magnitudes of the baseband I and Q signals respectively. $f(|\vec{I}|)$ and $f(|\vec{Q}|)$ according to embodiments of the present invention will be further described below in section 3.4.4.

[0348] Referring to FIG. 20, components 2030 and 2032 output the calculated phase shift information to components 2040 and 2042, respectively. Based on phase shift angle ϕ_I , component 2040 calculates in-phase and quadrature amplitude information of the first and second constant envelope constituents of the sampled I signal. Similarly, based on phase shift angle ϕ_Q , component 2042 calculates in-phase and quadrature amplitude information of the first and second constant envelope constituents of the sampled Q signal. Due to symmetry, in embodiments of the invention, calculation is required for 4 values only. In the example of FIG. 20, the values are illustrated as $\text{sgn}(I) \times I_{UX}$, I_{UY} , Q_{UX} , and $\text{sgn}(Q) \times Q_{UY}$, as provided in FIG. 5.

[0349] Components 2040 and 2042 output the calculated amplitude information to subsequent stages of the vector power amplifier. In embodiments, each of the four calculated values is output separately to a digital-to-analog converter. As shown in the embodiment of FIG. 7A for example, signals 722, 724, 726, and 728 are output separately to DACs 730, 732, 734, and 736, respectively. In other embodiments, signals 722, 724, 726, and 728 are output into a single DAC as shown in FIGS. 800A and 800B.

3.4.2) CPCP 2-Branch VPA Transfer Function

[0350] FIG. 21 is a process flowchart 2100 that illustrates an example I and Q transfer function embodiment according to the CPCP 2-Branch VPA embodiment. The process begins at step 2110, which includes receiving in-phase (I) and quadrature (Q) data components of a baseband signal. In the CPCP 2-Branch VPA embodiment of FIG. 12, for example, this is illustrated by I and Q Data Transfer Function module 1216 receiving I and Q information signal 1210.

[0351] Step 2120 includes determining the magnitudes $|I|$ and $|Q|$ of the received I and Q data components.

[0352] Step 2130 includes calculating a magnitude $|R|$ of the baseband signal based on the measured $|I|$ and $|Q|$ magnitudes. In an embodiment, $|R|$ is such that $|R|^2 = |I|^2 + |Q|^2$. In the embodiment of FIG. 12, for example, steps 2120 and 2130 are performed by I and Q Data Transfer Function module 1216 based on received information signal 1210.

[0353] Step 2140 includes normalizing the measured $|I|$ and $|Q|$ magnitudes. In an embodiment, $|I|$ and $|Q|$ are normalized to generate an I_{clk_phase} and Q_{clk_phase} signals (as shown in FIG. 10) such that $|I_{clk_phase}|^2 + |Q_{clk_phase}|^2 = \text{constant}$. In the embodiment of FIG. 12, for example, step 2140 is performed by I and Q Data Transfer Function module 1216 based on received information signal 1210.

[0354] Step 2150 includes calculating in-phase and quadrature amplitude information associated with first and second constant envelope constituents. In the embodiment of FIG. 12, for example, step 2150 is performed by I and Q Data Transfer Function module 1216 based on the envelope magnitude $|R|$.

[0355] Step 2160 includes outputting the generated I_{clk_phase} and Q_{clk_phase} (from step 2140) and the calculated amplitude information (from step 2150) to appropriate vector modulators. In the embodiment of FIG. 12, for example, I and Q Data Transfer Function module 1216 output information

signals 1220, 1222, 1224, and 1226 to vector modulators 1238, 1260, and 1262 through DACs 1230, 1232, 1234, and 1236.

[0356] FIG. 22 is a block diagram that illustrates an exemplary embodiment 2200 of a transfer function module (such as module 1216 of FIG. 12) implementing the process flowchart 2100. In the example of FIG. 22, transfer function module 2200 receives I and Q data signal 2210. In an embodiment, I and Q data signal 2210 includes I and Q components of a baseband signal, such as signal 1210 in the embodiment of FIG. 12, for example.

[0357] In an embodiment, transfer function module 2200 samples I and Q data signal 2210 according to a sampling clock 2212. Sampled I and Q data signals are received by component 2220 of transfer function module 2200. Component 2220 measures the magnitudes $|\vec{I}|$ and $|\vec{Q}|$ of the sampled I and Q data signals.

[0358] Based on the measured $|\vec{I}|$ and $|\vec{Q}|$ magnitudes, component 2230 calculates the magnitude $|\vec{R}|$ of the baseband signal. In an embodiment, $|\vec{R}|$ is such that $|\vec{R}|^2 = |\vec{I}|^2 + |\vec{Q}|^2$.

[0359] In parallel, component 2240 normalizes the measured $|\vec{I}|$ and $|\vec{Q}|$ magnitudes. In an embodiment, $|\vec{I}|$ and $|\vec{Q}|$ are normalized to generate I_{clk_phase} and Q_{clk_phase} signals such that $|I_{clk_phase}|^2 + |Q_{clk_phase}|^2 = \text{constant}$, where $|I_{clk_phase}|$ and $|Q_{clk_phase}|$ represent normalized magnitudes of $|\vec{I}|$ and $|\vec{Q}|$. Typically, given that the constant has a value A, the measured $|\vec{I}|$ and $|\vec{Q}|$ magnitudes are both divided by the quantity

$$\frac{A}{\sqrt{|\vec{I}|^2 + |\vec{Q}|^2}}$$

[0360] Component 2250 receives the calculated $|\vec{R}|$ magnitude from component 2230, and based on it calculates a phase shift angle ϕ between first and second constant envelope constituents. Using the calculated phase shift angle ϕ , component 2050 then calculates in-phase and quadrature amplitude information associated with the first and second constant envelope constituents.

[0361] In the embodiment of FIG. 22, the phase shift angle ϕ is illustrated as a function $f(|\vec{R}|)$ of the calculated magnitude $|\vec{R}|$.

[0362] Referring to FIG. 22, components 2240 and 2250 output the normalized I_{clk_phase} and Q_{clk_phase} magnitude information and the calculated amplitude information to DAC's for input into the appropriate vector modulators. In embodiments, the output values are separately output to digital-to-analog converters. As shown in the embodiment of FIG. 12, for example, signals 1220, 1222, 1224, and 1226 are output separately to DACs 1230, 1232, 1234, and 1236, respectively. In other embodiments, signals 1220, 1222, 1224, and 1226 are output into a single DAC as shown in FIGS. 13 and 13A.

3.4.3) Direct Cartesian 2-Branch Transfer Function

[0363] FIG. 23 is a process flowchart 2300 that illustrates an example I and Q transfer function embodiment according

to the Direct Cartesian 2-Branch VPA embodiment. The process begins at step **2310**, which includes receiving in-phase (I) and quadrature (Q) data components of a baseband signal. In the Direct Cartesian 2-Branch VPA embodiment of FIG. **17**, for example, this is illustrated by I and Q Data Transfer Function module **1716** receiving I and Q information signal **1710**.

[**0364**] Step **2320** includes determining the magnitudes $|I|$ and $|Q|$ of the received I and Q data components.

[**0365**] Step **2330** includes calculating a magnitude $|R|$ of the baseband signal based on the measured $|I|$ and $|Q|$ magnitudes. In an embodiment, $|R|$ is such that $|R|^2 = |I|^2 + |Q|^2$. In the embodiment of FIG. **17**, for example, steps **2320** and **2330** are performed by I and Q Data Transfer Function module **1716** based on received information signal **1710**.

[**0366**] Step **2340** includes calculating a phase shift angle θ of the baseband signal based on the measured $|I|$ and $|Q|$ magnitudes. In an embodiment, θ is such that

$$\theta = \tan^{-1} \left(\frac{|Q|}{|I|} \right),$$

and wherein the sign of I and Q determine the quadrant of θ . In the embodiment of FIG. **17**, for example, step **2340** is performed by I and Q Data Transfer Function module **1216** based on I and Q data components received in information signal **1210**.

[**0367**] Step **2350** includes calculating in-phase and quadrature amplitude information associated with a first and second constant envelope constituents of the baseband signal. In the embodiment of FIG. **17**, for example, step **2350** is performed by I and Q Data Transfer Function module **1716** based on previously calculated magnitude $|R|$ and phase shift angle θ .

[**0368**] Step **2360** includes outputting the calculated amplitude information to DAC's for input into the appropriate vector modulators. In the embodiment of FIG. **17**, for example, I and Q Data Transfer Function module **1716** output information signals **1720**, **1722**, **1724**, and **1726** to vector modulators **1750** and **1752** through DACs **1730**, **1732**, **1734**, and **1736**. In other embodiments, signals **1720**, **1722**, **1724**, and **1726** are output into a single DAC as shown in FIGS. **18** and **18A**.

[**0369**] FIG. **24** is a block diagram that illustrates an exemplary embodiment **2400** of a transfer function module implementing the process flowchart **2300**. In the example of FIG. **24**, transfer function module **2400** (such as transfer function module **1716**) receives I and Q data signal **2410**, such as signal **1710** in FIG. **17**. In an embodiment, I and Q data signal **2410** includes I and Q data components of a baseband signal.

[**0370**] In an embodiment, transfer function module **2400** samples I and Q data signal **2410** according to a sampling clock **2412**. Sampled I and Q data signals are received by component **2420** of transfer function module **2200**. Component **2420** measures the magnitudes $|\vec{I}|$ and $|\vec{Q}|$ of the sampled I and Q data signals.

[**0371**] Based on the measured $|\vec{I}|$ and $|\vec{Q}|$ magnitudes, component **2430** calculates the magnitude $|\vec{R}|$. In an embodiment, $|\vec{R}|$ is such that $|\vec{R}|^2 = |\vec{I}|^2 + |\vec{Q}|^2$.

[**0372**] In parallel, component **2240** calculates the phase shift angle θ of the baseband signal. In an embodiment, θ is such that

$$\theta = \tan^{-1} \left(\frac{|\vec{Q}|}{|\vec{I}|} \right),$$

where the sign of I and Q determine the quadrant of θ .

[**0373**] Component **2450** receives the calculated $|\vec{R}|$ magnitude from component **2430**, and based on it calculates a phase shift angle ϕ between first and second constant envelope constituent signals. In the embodiment of FIG. **24**, the phase shift angle ϕ is illustrated as a function $f_3(|\vec{R}|)$ of the calculated magnitude $|\vec{R}|$. This is further described in section 3.4.4.

[**0374**] In parallel, component **2450** receives the calculated phase shift angle θ from component **2440**. As functions of ϕ and θ , component **2450** then calculates in-phase and quadrature amplitude information for the vector modulator inputs that generate the first and second constant envelope constituents. In an embodiment, the in-phase and quadrature amplitude information supplied to the vector modulators are according to the equations provided in (18).

[**0375**] Component **2450** outputs the calculated amplitude information to subsequent stages of the vector power amplifier. In embodiments, the output values are separately output to digital-to-analog converters. As shown in the embodiment of FIG. **17**, for example, signals **1720**, **1722**, **1724**, and **1726** are output separately to DACs **1730**, **1732**, **1734**, and **1736**, respectively. In other embodiments, signals **1720**, **1722**, **1724**, and **1726** are output into a single DAC as shown in FIGS. **18** and **18A**.

3.4.4) Magnitude to Phase Shift Transform

[**0376**] Embodiments of $f(|I|)$, $f(|Q|)$ of FIG. **20** and $f(|R|)$ of FIGS. **22** and **24** shall now be further described.

[**0377**] According to the present invention, any periodic waveform that can be represented by a Fourier series and a Fourier transform can be decomposed into two or more constant envelope signals.

[**0378**] Below are provided two examples for sinusoidal and square waveforms.

3.4.4.1) Magnitude to Phase Shift Transform for Sinusoidal Signals:

[**0379**] Consider a time-varying complex envelope sinusoidal signal $r(t)$. In the time domain, it can be represented as:

$$r(t) = R(t) \sin(\omega t + \delta(t)) \quad (20)$$

where $R(t)$ represents the signal's envelope magnitude at time t , $\delta(t)$ represents the signal's phase shift angle at time t , and ω represents the signal's frequency in radians per second.

[**0380**] It can be verified that, at any time instant t , signal $r(t)$ can be obtained by the sum of two appropriately phased equal and constant or substantially equal and constant envelope signals. In other words, it can be shown that:

$$R(t) \sin(\omega t + \delta(t)) = A \sin(\omega t) + A \sin(\omega t + \phi(t)) \quad (21)$$

for an appropriately chosen phase shift angle $\phi(t)$ between the two constant envelope signals. The phase shift angle $\phi(t)$ will be derived as a function of $R(t)$ in the description below. This is equivalent to the magnitude to phase shift transform for sinusoidal signals.

[0381] Using a sine trigonometric identity, equation (21) can be re-written as:

$$\begin{aligned} R(t)\sin(\omega t + \delta(t)) &= A\sin(\omega t) + A\sin(\omega t)\cos\phi(t) + A\sin(\phi(t))\cos\omega t; \\ \Rightarrow R(t)\sin(\omega t + \delta(t)) &= A\sin(\phi(t))\cos\omega t + A(1 + \cos\phi(t))\sin\omega t. \end{aligned} \quad (22)$$

[0382] Note, from equation (22), that signal $r(t)$ is written as a sum of an in-phase component and a quadrature component. Accordingly, the envelope magnitude $R(t)$ can be written as:

$$\begin{aligned} R(t) &= \sqrt{(A\sin(\phi(t)))^2 + (A(1 + \cos(\phi(t))))^2}; \\ \Rightarrow R(t) &= \sqrt{2A(A + \cos(\phi(t)))}. \end{aligned} \quad (23)$$

[0383] Equation (23) relates the envelope magnitude $R(t)$ of signal $r(t)$ to the phase shift angle $\phi(t)$ between two constant envelope constituents of signal $r(t)$. The constant envelope constituents have equal or substantially equal envelope magnitude A , which is typically normalized to 1.

[0384] Inversely, from equation (23), the phase shift angle $\phi(t)$ can be written as a function of $R(t)$ as follows:

$$\phi(t) = \arccos\left(\frac{R(t)^2}{2A^2} - 1\right). \quad (24)$$

[0385] Equation (24) represents the magnitude to phase shift transform for the case of sinusoidal signals, and is illustrated in FIG. 26.

3.4.4.2) Magnitude to Phase Shift Transform for Square Wave Signals:

[0386] FIG. 28 illustrates a combination of two constant envelope square wave signals according to embodiments of the present invention. In FIG. 28, signals 2810 and 2820 are constant envelope signals having a period T , a duty cycle γT ($0 < \gamma < 1$), and envelope magnitudes $A1$ and $A2$, respectively.

[0387] Signal 2830 results from combining signals 2810 and 2820. According to embodiments of the present invention, signal 2830 will have a magnitude equal or substantially equal to a product of signals 2810 and 2820. In other words, signal 2830 will have a magnitude of zero whenever either of signals 2810 or 2820 has a magnitude of zero, and a non-zero magnitude when both signals 2810 and 2820 have non-zero magnitudes.

[0388] Further, signal 2830 represents a pulse-width-modulated signal. In other words, the envelope magnitude of signal 2830 is determined according to the pulse width of signal 2830 over one period of the signal. More specifically, the envelope magnitude of signal 2830 is equal or substantially to the area under the curve of signal 2830.

[0389] Referring to FIG. 28, signals 2810 and 2820 are shown time-shifted relative to each other by a time shift t' . Equivalently, signals 2810 and 2820 are phase-shifted relative to each other by a phase shift angle

$$\phi = \left(\frac{t'}{T}\right) \times 2\pi$$

radians.

[0390] Still referring to FIG. 28, note that the envelope magnitude R of signal 2830, in FIG. 28, is given by:

$$R = A_1 \times A_2 \times (\gamma T - t') \quad (25)$$

[0391] Accordingly, it can be deduced that ϕ is related to R according to:

$$\phi = \left[\gamma - \frac{R}{T(A_1 A_2)}\right] \times (2\pi). \quad (26)$$

[0392] Note, from equation (26), that R is at a maximum of $\gamma A_1 A_2$ when $\phi = 0$. In other words, the envelope magnitude is at a maximum when the two constant envelope signals are in-phase with each other.

[0393] In typical implementations, signals 2810 and 2820 are normalized and have equal or substantially equal envelope magnitude of 1. Further, signals 2810 and 2820 typically have a duty cycle of 0.5. Accordingly, equation (28) reduces to:

$$\phi = \left[0.5 - \frac{R}{T}\right] \times (2\pi). \quad (27)$$

[0394] Equation (27) illustrates the magnitude to phase shift transform for the case of normalized and equal or substantially equal envelope magnitude square wave signals. Equation (27) is illustrated in FIG. 26.

3.4.5 Waveform Distortion Compensation

[0395] In certain embodiments, magnitude to phase shift transforms may not be implemented exactly as theoretically or practically derived. In fact, several factors may exist that require adjustment or tuning of the derived transform for optimal operation. Waveform distortion compensation is one factor that may require adjustment or tuning of the magnitude to phase shift transform. Waveform distortion compensation is now described below.

[0396] In practice, several factors may cause waveform distortion of constant envelope constituents of a desired output signal $r(t)$. Furthermore, it is expected that waveform distortion in the constituents translates into waveform distortion in the desired output signal when the constituents are combined. FIG. 25 illustrates the effect of waveform distortion on a signal using phasor signal representation. In FIG. 25, \vec{R} represents a phasor representation of a desired signal $r(t)$. In reality, waveform distortion can cause the actual phasor representation of $r(t)$ to fall anywhere within a maximum error vector magnitude from \vec{R} . In the example of FIG. 25, this is illustrated using a circle centered at \vec{R} and having a radius equal or substantially equal to the maximum error vector magnitude. Phasors \vec{R}_1 and \vec{R}_2 represent examples of actual phasor representations of the desired signal $r(t)$.

[0397] According to embodiments of the present invention, expected waveform distortion to a desired output signal can be estimated. In some embodiments, the expected waveform

distortion is compensated for at the vector modulation stage of the power amplifier. In other embodiments, the expected waveform distortion is compensated for at the transfer function stage of the power amplifier.

[0398] In the former approach, compensation is achieved by applying appropriate magnitude and phase shift tuning at the vector modulation stage outputs. Accordingly, waveform distortion is removed by waveshaping of the constituent signals of the desired output signal.

[0399] In the latter approach, the transfer function is designed to factor in and cancel or at least reduce the effects of the expected waveform distortion. As can be understood from the above description of transfer functions, waveform distortion compensation can be introduced at different positions within a transfer function stage. In some embodiments, compensation is applied at the output stage of the transfer function. For example, referring to FIG. 17, transfer function module outputs 1720, 1722, 1274 and 1726 may be tuned prior to being input into DACs 1730, 1732, 1734, and 1736. In other embodiments, compensation is applied at the magnitude to phase shift transform stage of the transfer function. Referring to FIG. 24, for example, magnitude to phase shift transform $\phi=f(|R|)$ may be adjusted appropriately to compensate for the expected waveform distortion.

3.5) Output Stage

[0400] An aspect of embodiments of the present invention lies in summing constituent signals at the output stage of a vector power amplifier (VPA). This is shown, for example, in FIG. 7 where the outputs of PAs 770, 772, 774, and 776 are summed. This is similarly shown in FIGS. 8, 12, 13, 17, and 18, for example. Various embodiments for combining the outputs of VPAs are described herein. While the following is described in the context of VPAs, it should be understood that the following teachings generally apply to coupling or summing the outputs of any active devices in any application.

[0401] FIG. 29 illustrates a vector power amplifier output stage embodiment 2900 according to an embodiment of the present invention. Output stage 2900 includes a plurality of vector modulator signals 2910- $\{1, \dots, n\}$ being input into a plurality of corresponding power amplifiers (PAs) 2920- $\{1, \dots, n\}$. As described above, signals 2910- $\{1, \dots, n\}$ represent constituent signals of a desired output signal of the vector power amplifier.

[0402] In the example of FIG. 29, PAs 2910- $\{1, \dots, n\}$ equally amplify or substantially equally amplify input signals 2910- $\{1, \dots, n\}$ to generate amplified output signals 2930- $\{1, \dots, n\}$. Amplified output signals 2930- $\{1, \dots, n\}$ are coupled together directly at summing node 2940. According to this example embodiment of the present invention, summing node 2940 includes no coupling or isolating element, such as a power combiner, for example. In the embodiment of FIG. 29, summing node 2940 is a zero-impedance (or near-zero impedance) conducting wire. Accordingly, unlike in conventional systems that employ combining elements, the combining of output signals according to this embodiment of the present invention incurs minimal power loss.

[0403] In another aspect, output stage embodiments of the present invention can be implemented using multiple-input single-output (MISO) power amplifiers.

[0404] In another aspect, output stage embodiments of the present invention can be controlled to increase the power efficiency of the amplifier by controlling the output stage current according to the desired output power level.

[0405] In what follows, various output stage embodiments according to VPA embodiments of the present invention are provided in section 3.5.1. In section 3.5.2, embodiments of output stage current shaping functions, for increasing the power efficiency of certain VPA embodiments of the present invention, are presented. Section 3.5.3 describes embodiments of output stage protection techniques that may be utilized for certain output stage embodiments of the present invention.

3.5.1) Output Stage Embodiments

[0406] FIG. 30 is a block diagram that illustrates a power amplifier (PA) output stage embodiment 3000 according to an embodiment of the present invention. Output stage embodiment 3000 includes a plurality of PA branches 3005- $\{1, \dots, n\}$. Signals 3010- $\{1, \dots, n\}$ incoming from respective vector modulators represent inputs for output stage 3000. According to this embodiment of the present invention, signals 3010- $\{1, \dots, n\}$ represent equal and constant or substantially equal and constant envelope constituent signals of a desired output signal of the power amplifier.

[0407] PA branches 3005- $\{1, \dots, n\}$ apply equal or substantially equal power amplification to respective signals 3010- $\{1, \dots, n\}$. In an embodiment, the power amplification level through PA branches 3005- $\{1, \dots, n\}$ is set according to a power level requirement of the desired output signal.

[0408] In the embodiment of FIG. 30, PA branches 3005- $\{1, \dots, n\}$ each includes a power amplifier 3040- $\{1, \dots, n\}$. In other embodiments, drivers 3030- $\{1, \dots, n\}$ and pre-drivers 3020- $\{1, \dots, n\}$, as illustrated in FIG. 30, may also be added in a PA branch prior to the power amplifier element. In embodiments, drivers and pre-drivers are employed whenever a required output power level may not be achieved in a single amplifying stage.

[0409] To generate the desired output signal, outputs of PA branches 3005- $\{1, \dots, n\}$ are coupled directly at summing node 3050. Summing node 3050 provides little or no isolation between the coupled outputs. Further, summing node 3050 represents a relatively lossless summing node. Accordingly, minimal power loss is incurred in summing the outputs of PAs 3040- $\{1, \dots, n\}$.

[0410] Output signal 3060 represents the desired output signal of output stage 3000. In the embodiment of FIG. 30, output signal 3060 is measured across a load impedance 3070.

[0411] FIG. 31 is a block diagram that illustrates another power amplifier (PA) output stage embodiment 3100 according to the present invention. Similar to the embodiment of FIG. 30, output stage 3100 includes a plurality of PA branches 3105- $\{1, \dots, n\}$. Each of PA branches 3105- $\{1, \dots, n\}$ may include multiple power amplification stages represented by a pre-driver 3020- $\{1, \dots, n\}$, driver 3030- $\{1, \dots, n\}$, and power amplifier 3040- $\{1, \dots, n\}$. Output stage embodiment 3100 further includes pull-up impedances coupled at the output of each power amplification stage to provide biasing of that stage. For example, pull-up impedances 3125- $\{1, \dots, n\}$ and 3135- $\{1, \dots, n\}$, respectively, couple the pre-driver and driver stage outputs to power supply or independent bias power supplies. Similarly, pull-up impedance 3145 couples the PA stage outputs to the power supply or an independent bias power supply. According to this embodiment of the present invention, pull-up impedances represent optional components that may affect the efficiency but not necessarily the operation of the output stage embodiment.

[0412] FIG. 32 is a block diagram that illustrates another power amplifier (PA) output stage embodiment 3200 according to the present invention. Similar to the embodiment of FIG. 30, output stage 3200 includes a plurality of PA branches 3205- $\{1, \dots, n\}$. Each of PA branches 3205- $\{1, \dots, n\}$ may include multiple power amplification stages represented by a pre-driver 3020- $\{1, \dots, n\}$, driver 3030- $\{1, \dots, n\}$, and power amplifier 3040- $\{1, \dots, n\}$. Output stage embodiment 3200 also includes pull-up impedances coupled at the output of each power amplification stage to achieve a proper biasing of that stage. Further, output stage embodiment 3200 includes matching impedances coupled at the outputs of each power amplification stage to maximize power transfer from that stage. For example, matching impedances 3210- $\{1, \dots, n\}$ and 3220- $\{1, \dots, n\}$, are respectively coupled to the pre-driver and driver stage outputs. Similarly, matching impedance 3240 is coupled at the PA stage output. Note that matching impedance 3240 is coupled to the PA output stage subsequent to summing node 3250.

[0413] In the above-described embodiments of FIGS. 30-32, the PA stage outputs are combined by direct coupling at a summing node. For example, in the embodiment of FIG. 30, outputs of PA branches 3005- $\{1, \dots, n\}$ are coupled together at summing node 3050. Summing node 3050 is a near zero-impedance conducting wire that provides minimal isolation between the coupled outputs. Similar output stage coupling is shown in FIGS. 31 and 32. It is noted that in certain embodiments of the present invention, output coupling, as shown in the embodiments of FIGS. 30-32 or embodiments subsequently described below, may utilize certain output stage protection measures. These protection measures may be implemented at different stages of the PA branch. Further, the type of protection measures needed may be PA implementation-specific. A further discussion of output stage protection according to an embodiment of the present invention is provided in section 3.5.3.

[0414] FIG. 33 is a block diagram that illustrates another power amplifier (PA) output stage embodiment 3300 according to the present invention. Similar to the embodiment of FIG. 30, output stage 3300 includes a plurality of PA branches 3305- $\{1, \dots, n\}$. Each of PA branches 3305- $\{1, \dots, n\}$ may include multiple power amplification stages represented by a pre-driver 3020- $\{1, \dots, n\}$, driver 3030- $\{1, \dots, n\}$, and power amplifier 3040- $\{1, \dots, n\}$. Output stage embodiment 3300 may also include pull-up impedances 3125- $\{1, \dots, n\}$, 3135- $\{1, \dots, n\}$, and 3145 coupled at the output of each power amplification stage to achieve a proper biasing of that stage. Additionally, output stage embodiment 3300 may include matching impedances 3210- $\{1, \dots, n\}$, 3220- $\{1, \dots, n\}$, and 3240 coupled at the output of each power amplification stage to maximize power transfer from that stage. Further, output stage embodiment 3300 receives an autobias signal 3310, from an Autobias module 3340, coupled at the PA stage input of each PA branch 3305- $\{1, \dots, n\}$. Autobias module 3340 controls the bias of PAs 3040- $\{1, \dots, n\}$. In an embodiment, autobias signal 3340 controls the amount of current flow through the PA stage according to a desired output power level and signal envelope of the output waveform. A further description of the operation of autobias signal and the autobias module is provided below in section 3.5.2.

[0415] FIG. 34 is a block diagram that illustrates another power amplifier (PA) output stage embodiment 3400 according to the present invention. Similar to the embodiment of FIG. 30, output stage 3400 includes a plurality of PA branches

3405- $\{1, \dots, n\}$. Each of PA branches 3405- $\{1, \dots, n\}$ may include multiple power amplification stages represented by a pre-driver 3020- $\{1, \dots, n\}$, driver 3030- $\{1, \dots, n\}$, and power amplifier 3040- $\{1, \dots, n\}$. Output stage embodiment 3400 may also include pull-impedances 3125- $\{1, \dots, n\}$, 3135- $\{1, \dots, n\}$, and 3145 coupled at the output of each power amplification stage to achieve desired biasing of that stage. Additionally, output stage embodiment 3400 may include matching impedances 3210- $\{1, \dots, n\}$, 3220- $\{1, \dots, n\}$, and 3240 coupled at the output of each power amplification stage to maximize power transfer from that stage. Further, output stage embodiment 3400 includes a plurality of harmonic control circuit networks 3410- $\{1, \dots, n\}$ coupled at the PA stage input of each PA branch $\{1, \dots, n\}$. Harmonic control circuit networks 3410- $\{1, \dots, n\}$ may include a plurality of resistance, capacitance, and/or inductive elements and/or active devices coupled in series or in parallel. According to an embodiment of the present invention, harmonic control circuit networks 3410- $\{1, \dots, n\}$ provide harmonic control functions for controlling the output frequency spectrum of the power amplifier. In an embodiment, harmonic control circuit networks 3410- $\{1, \dots, n\}$ are selected such that energy transfer to the fundamental harmonic in the summed output spectrum is increased while the harmonic content of the output waveform is decreased. A further description of harmonic control according to embodiments of the present invention is provided below in section 3.6.

[0416] FIG. 35 is a block diagram that illustrates another power amplifier (PA) output stage embodiment 3500 according to the present invention. Output stage embodiment 3500 represents a differential output equivalent of output stage embodiment 3200 of FIG. 32. In embodiment 3500, PA stage outputs 3510- $\{1, \dots, n\}$ are combined successively to result in two aggregate signals. The two aggregate signals are then combined across a loading impedance, thereby having the output of the power amplifier represent the difference between the two aggregate signals. Referring to FIG. 35, aggregate signals 3510 and 3520 are coupled across loading impedance 3530. The output of the power amplifier is measured across the loading impedance 3530 as the voltage difference between nodes 3540 and 3550. According to embodiment 3500, the maximum output of the power amplifier is obtained when the two aggregate signals are 180 degrees out-of-phase relative to each other. Inversely, the minimum output power results when the two aggregate signals are in-phase relative to each other.

[0417] FIG. 36 is a block diagram that illustrates another output stage embodiment 3600 according to the present invention. Similar to the embodiment of FIG. 30, output stage 3600 includes a plurality of PA branches 3605- $\{1, \dots, n\}$. Each of PA branches $\{1, \dots, n\}$ may include multiple power amplification stages represented by a pre-driver 3020- $\{1, \dots, n\}$, a driver 3030- $\{1, \dots, n\}$, and a power amplifier (PA) 3620- $\{1, \dots, n\}$.

[0418] According to embodiment 3600, PA's 3620- $\{1, \dots, n\}$ include switching power amplifiers. In the example of FIG. 36, power amplifiers 3620- $\{1, \dots, n\}$ include npn bipolar junction transistor (BJT) elements Q1, ..., Qn. BJT elements Q1, ..., Qn have common collector nodes. Referring to FIG. 36, collector terminals of BJT elements Q1, ..., Qn are coupled together to provide summing node 3640. Emitter terminals of BJT elements Q1, ..., Qn are coupled to

a ground node, while base terminals of BJT elements Q1, . . . , Qn provide input terminals into the PA stage.

[0419] FIG. 37 is an example (related to FIG. 36) that illustrates an output signal of the PA stage of embodiment 3600 in response to square wave input signals. For ease of illustration, a two-branch PA stage is considered. In the example of FIG. 37, square wave signals 3730 and 3740 are input, respectively, into BJT elements 3710 and 3720. Note that when either of BJT elements 3710 or 3720 turns on, summing node 3750 is shorted to ground. Accordingly, when either of input signals 3730 or 3740 is high, output signal 3780 will be zero. Further, output signal 3780 will be high only when both input signals 3730 and 3740 are zero. According to this arrangement, PA stage 3700 performs pulse-width modulation, whereby the magnitude of the output signal is a function of the phase shift angle between the input signals.

[0420] Embodiments are not limited to npn BJT implementations as described herein. A person skilled in the art will appreciate, for example, that embodiments of the present invention may be implemented using pnp BJTs, CMOS, NMOS, PMOS, or other type of transistors. Further, embodiments can be implemented using GaAs and/or SiGe transistors with the desired transistor switching speed being a factor to consider.

[0421] Referring back to FIG. 36, it is noted that while PAs 3620- $\{1, \dots, n\}$ are each illustrated using a single BJT notation, each PA 3620- $\{1, \dots, n\}$ may include a plurality of series-coupled transistors. In embodiments, the number of transistors included within each PA is set according to a required maximum output power level of the power amplifier. In other embodiments, the number of transistors in the PA is such that the numbers of transistors in the pre-driver, driver, and PA stages conform to a geometric progression.

[0422] FIG. 38 illustrates an exemplary PA embodiment 3800 according to an embodiment of the present invention. PA embodiment 3800 includes a BJT element 3870, a LC network 3860, and a bias impedance 3850. BJT element 3870 includes a plurality of BJT transistors Q1, . . . , Q8 coupled in series. As illustrated in FIG. 38, BJT transistors Q1, . . . , Q8 are coupled together at their base, collector, and emitter terminals. Collector terminal 3880 of BJT element 3870 provides an output terminal for PA 3800. Emitter terminal 3890 of BJT element 3870 may be coupled to substrate or to an emitter terminal of a preceding amplifier stage. For example, emitter terminal 3890 is coupled to an emitter terminal of a preceding driver stage.

[0423] Referring to FIG. 38, LC network 3860 is coupled between PA input terminal 3810 and input terminal 3820 of BJT element 3870. LC network 3860 includes a plurality of capacitive and inductive elements. Optionally, a Harmonic Control Circuit network 3830 is also coupled at input terminal 3820 of BJT element 3870. As described above, the HCC network 3830 provides a harmonic control function for controlling the output frequency spectrum of the power amplifier.

[0424] Still referring to FIG. 38, bias impedance 3850 couples Iref signal 3840 to input terminal 3820 of BJT element 3870. Iref signal 3840 represents an autobias signal that controls the bias of BJT element 3870 according to a desired output power level and signal envelope characteristics.

[0425] It is noted that, in the embodiment of FIG. 38, BJT element 3870 is illustrated to include 8 transistors. It can be appreciated by a person skilled in the art, however, that BJT

element 3870 may include any number of transistors as required to achieve the desired output power level of the power amplifier.

[0426] In another aspect, output stage embodiments can be implemented using multiple-input single-output (MISO) power amplifiers. FIG. 51A is a block diagram that illustrates an exemplary MISO output stage embodiment 5100A. Output stage embodiment 5100A includes a plurality of vector modulator signals 5110- $\{1, \dots, n\}$ that are input into MISO power amplifier (PA) 5120. As described above, signals 5110- $\{1, \dots, n\}$ represent constant envelope constituents of output signal 5130 of the power amplifier. MISO PA 5120 is a multiple input single output power amplifier. MISO PA 5120 receives and amplifies signals 5110- $\{1, \dots, n\}$ providing a distributed multi signal amplification process to generate output signal 5130.

[0427] It is noted that MISO implementations, similar to the one shown in FIG. 51A, can be similarly extended to any of the output stage embodiments described above. More specifically, any of the output stage embodiments of FIGS. 29-37 can be implemented using a MISO approach. Additional MISO embodiments will now be provided with reference to FIGS. 51B-I. It is noted that any of the embodiments described above can be implemented using any of the MISO embodiments that will now be provided.

[0428] Referring to FIG. 51A, MISO PA 5120 can have any number of inputs as required by the substantially constant envelope decomposition of the complex envelope input signal. For example, in a two-dimensional decomposition, a two-input power amplifier can be used. According to embodiments of the present invention, building blocks for creating MISO PAs for any number of inputs are provided. FIG. 51B illustrates several MISO building blocks according to an embodiment of the present invention. MISO PA 5110B represents a two-input single-output PA block. In an embodiment, MISO PA 5110B includes two PA branches. The PA branches of MISO PA 5110B may be equivalent to any PA branches described above with reference to FIGS. 29-37, for example. MISO PA 5120B represents a three-input single-output PA block. In an embodiment, MISO PA 5120B includes three PA branches. The PA branches of MISO PA 5120B may be equivalent to any PA branches described above with reference to FIGS. 29-37, for example.

[0429] Still referring to FIG. 51B, MISO PAs 5110B and 5120B represent basic building blocks for any multiple-input single-output power amplifier according to embodiments of the present invention. For example, MISO PA 5130B is a four-input single-output PA, which can be created by coupling together the outputs of two two-input single-output PA blocks, such as MISO PA 5110B, for example. This is illustrated in FIG. 51C. Similarly, it can be verified that MISO PA 5140B, an n-input single-output PA, can be created from the basic building blocks 5110B and 5120B.

[0430] FIG. 51D illustrates various embodiments of the two-input single output PA building block according to embodiments of the present invention.

[0431] Embodiment 5110D represents an npn implementation of the two-input single output PA building block. Embodiment 5110D includes two npn transistors coupled together using a common collector node, which provides the output of the PA. A pull-up impedance (not shown) can be coupled between the common collector node and a supply node (not shown).

[0432] Embodiment **5130D** represents a pnp equivalent of embodiment **5110D**. Embodiment **5130D** includes two pnp transistors coupled at a common collector node, which provides the output of the PA. A pull-down impedance (not shown) can be coupled between the common collector node and a ground node (not shown).

[0433] Embodiment **5140D** represents a complementary npn/pnp implementation of the two-input single output PA building block. Embodiment **5140D** includes an npn transistor and a pnp transistor coupled at a common collector node, which provides the output of the PA.

[0434] Still referring to FIG. **51D**, embodiment **5120D** represents a NMOS implementation of the two-input single output PA building block. Embodiment **5120D** includes two NMOS transistors coupled at a common drain node, which provides the output of the PA.

[0435] Embodiment **5160D** represents a PMOS equivalent of embodiment **5120D**. Embodiment **5120D** includes two PMOS transistors coupled at a common drain node, which provides the output of the PA.

[0436] Embodiment **5150D** represents a complementary MOS implementation of the two-input single-output PA building block. Embodiment **5150D** includes a PMOS transistor and an NMOS transistor coupled at common drain node, which provides the output of the PA.

[0437] Two-input single-output embodiments of FIG. **51D** can be further extended to create multiple-input single-output PA embodiments. FIG. **51E** illustrates various embodiments of multiple-input single-output PAs according to embodiments of the present invention.

[0438] Embodiment **5150E** represents an npn implementation of a multiple-input single-output PA. Embodiment **5150E** includes a plurality of npn transistors coupled together using a common collector node, which provides the output of the PA. A pull-up impedance (not shown) can be coupled between the common collector node and a supply voltage (not shown). Note that an n-input single-output PA according to embodiment **5150E** can be obtained by coupling additional npn transistors to the two-input single-output PA building block embodiment **5110D**.

[0439] Embodiment **5170E** represents a pnp equivalent of embodiment **5150E**. Embodiment **5170E** includes a plurality of pnp transistors coupled together using a common collector node, which provides the output of the PA. A pull-down impedance (not shown) may be coupled between the common collector node and a ground node (not shown). Note that an n-input single-output PA according to embodiment **5170E** can be obtained by coupling additional pnp transistors to the two-input single-output PA building block embodiment **5130D**.

[0440] Embodiments **5110E** and **5130E** represent complementary npn/pnp implementations of a multiple-input single-output PA. Embodiments **5110E** and **5130E** may include a plurality of npn and/or pnp transistors coupled together using a common collector node, which provides the output of the PA. Note that an n-input single-output PA according to embodiment **5110E** can be obtained by coupling additional npn and/or pnp transistors to the two-input single-output PA building block embodiment **5140D**. Similarly, an n-input single-output PA according to embodiment **5130E** can be obtained by coupling additional npn and/or pnp transistors to the two-input single-output PA building block embodiment **5130D**.

[0441] Embodiment **5180E** represents an PMOS implementation of a multiple-input single-output PA. Embodiment **5180E** includes a plurality of PMOS transistors coupled together using a common drain node, which provides the output of the PA. Note that an n-input single-output PA according to embodiment **5180E** can be obtained by coupling additional NMOS transistors to the two-input single-output PA building block embodiment **5160D**.

[0442] Embodiment **5160E** represents a NMOS implementation of multiple-input single-output PA. Embodiment **5160E** includes a plurality of NMOS transistors coupled together using a common drain node, which provides the output of the PA. Note that an n-input single-output PA according to embodiment **5160E** can be obtained by coupling additional PMOS transistors to the two-input single-output PA building block embodiment **5120D**.

[0443] Embodiments **5120E** and **5140E** complementary MOS implementations of a multiple-input single-output PA. Embodiments **5120E** and **5140E** include a plurality of npn and pnp transistors coupled together using a common drain node, which provides the output of the PA. Note that a n-input single-output PA according to embodiment **5120E** can be obtained by coupling additional NMOS and/or PMOS transistors to the two-input single-output PA building block **5150D**. Similarly, an n-input single-output PA according to embodiment **5140E** can be obtained by coupling additional NMOS and/or PMOS transistors to the two-input single-output PA building block **5160D**.

[0444] FIG. **51F** illustrates further multiple-input single-output PA embodiments according to embodiments of the present invention. Embodiment **5110F** represents a complementary npn/pnp implementation of a multiple-input single-output PA. Embodiment **5110F** can be obtained by iteratively coupling together embodiments of PA building block **5140D**. Similarly, embodiment **5120F** represents an equivalent NMOS/PMOS complementary implementation of a multiple-input single-output PA. Embodiment **5120F** can be obtained by iteratively coupling together embodiments of PA building block **5150D**.

[0445] It must be noted that the multiple-input single-output embodiments described above may each correspond to a single or multiple branches of a PA. For example, referring to FIG. **29**, any of the multiple-input single-output embodiments may be used to replace a single or multiple PAs **2920**-{**1**, . . . , **n**}. In other words, each of PAs **2920**-{**1**, . . . , **n**} may be implemented using any of the multiple-input single-output PA embodiments described above or with a single-input single-output PA as shown in FIG. **29**.

[0446] It is further noted that the transistors shown in the embodiments of FIGS. **51D**, **51E**, and **51F** may each be implemented using a series of transistors as shown in the exemplary embodiment of FIG. **38**, for example.

[0447] FIG. **51G** illustrates further embodiments of the multiple-input single-output PA building blocks. Embodiment **5110G** illustrates an embodiment of the two-input single-output PA building block. Embodiment **5110G** includes two PA branches that can each be implemented according to single-input single-output or multiple-input single-output PA embodiments as described above. Further, embodiment **5110G** illustrates an optional bias control signal **5112G** that is coupled to the two branches of the PA embodiment. Bias control signal **5112G** is optionally employed in embodiment **5110G** based on the specific implementation of the PA branches. In certain implementations, bias control will

be required for proper operation of the PA. In other implementations, bias control is not required for proper operation of the PA, but may provide improved PA power efficiency, output circuit protection, or power on current protection.

[0448] Still referring to FIG. 51G, embodiment 5120G illustrates an embodiment of the three-input single-output PA building block. Embodiment 5120G includes three PA branches that can each be implemented according to single-input single-output or multiple-input single-output PA embodiments as described above. Further, embodiment 5120G illustrates an optional bias control signal 5114G that is coupled to the branches of the PA embodiment. Bias control signal 5114G is optionally employed in embodiment 5120G based on the specific implementation of the PA branches. In certain implementations, bias control will be required for proper operation of the PA. In other implementations, bias control is not required for proper operation of the PA, but may provide improved PA power efficiency.

[0449] FIG. 51H illustrates a further exemplary embodiment 5100H of the two-input single-output PA building block. Embodiment 5100H includes two PA branches that can each be implemented according to single-input single-output or multiple-input single-output PA embodiments as described above. Embodiment 5100H further includes optional elements, illustrated using dashed lines in FIG. 51H, that can be additionally employed in embodiments of embodiment 5100H. In an embodiment, PA building block 5100H may include a driver stage and/or pre-driver stage in each of the PA branches as shown in FIG. 51H. Process detectors may also be optionally employed to detect process and temperature variations in the driver and/or pre-driver stages of the PA. Further, optional bias control may be provided to each of the pre-driver, driver, and/or PA stages of each branch of the PA embodiment. Bias control may be provided to one or more the stages based on the specific implementation of that stage. Further, bias control may be required for certain implementations, while it can be optionally employed in others.

[0450] FIG. 51I illustrates a further exemplary embodiment 5100I of a multiple-input single-output PA. Embodiment 5100I includes at least two PA branches that can each be implemented according to single-input single-output or multiple-input single-output PA embodiments as described above. Embodiment 5100I further includes optional elements that can be additionally employed in embodiments of embodiment 5100I. In an embodiment, the PA may include driver and/or pre-driver stages in each of the PA branches as shown in FIG. 51I. Process detectors may also be optionally employed to detect process and temperature variations in the driver and/or pre-driver stages of the PA. Further, optional bias control may be provided to each of the pre-driver, driver, and/or PA stages of each branch of the PA embodiment. Bias control may be provided to one or more the stages based on the specific implementation of that stage. Further, bias control may be required for certain implementations, while it can be optionally employed in others.

3.5.2) Output Stage Current Control—Autobias Module

[0451] Embodiments of the output stage and optional pre-driver and driver stage bias and current control techniques according to embodiments of the present invention are described below. In certain embodiments, output stage current control functions are employed to increase the output stage efficiency of a vector power amplifier (VPA) embodi-

ment. In other embodiments, output stage current control is used to provide output stage protection from excessive voltages and currents which is further described in section 3.5.3. In embodiments, output stage current control functions are performed using the Autobias module described above with reference to FIG. 33. A description of the operation of the Autobias module in performing these current control functions is also presented below according to an embodiment of the present invention.

[0452] According to embodiments of the present invention, power efficiency of the output stage of a VPA can be increased by controlling the output stage current of the VPA as a function of the output power and the envelope of the output waveform.

[0453] FIG. 37, illustrates a partial schematic of a Multiple Input Single Output amplifier comprised of two NPN transistors with input signals S1 and S2. When S1 and S2 are designed to be substantially similar waveforms and substantially constant envelope signals, any time varying complex-envelope output signal can be created at circuit node 3750 by changing the phase relationship of S1 and S2.

[0454] FIG. 39 illustrates an example time varying complex-envelope output signal 3910 and its corresponding envelope signal 3920. Note that signal 3910 undergoes a reversal of phase at an instant of time t_0 . Correspondingly, envelope signal 3920 undergoes a zero crossing at time t_0 . Output signal 3910 exemplifies output signals according to typical wireless signaling schemes such as W-CDMA, QPSK, and OFDM, for example.

[0455] FIG. 40 illustrates example diagram FIG. 37's output stage current in response to output signal 3910. I_{out} signal 4010 represents output stage current without autobias control, and I_{out} signal 4020 represents output stage current with autobias control. Without autobias control, as the phase shift between S1 and S2 changes from 0 to 180 degrees, the output current I_{out} increases. With autobias control, the output current I_{out} decreases and can be minimized when at or near t_0 of FIG. 39.

[0456] Note that I_{out} signal 4020 varies as a function of envelope signal 3920. Accordingly, I_{out} signal 4020 is at the maximum when a maximum output power is required, but decreases as the required output power goes down. Particularly, I_{out} signal 4020 approaches zero as the associated output power goes to zero. Accordingly, a person skilled in the art will appreciate that output stage current control, according to embodiments of the present invention, results in significant power savings and increases the power efficiency of the power amplifier.

[0457] According to embodiments of the present invention, output stage current control may be implemented according to a variety of functions. In an embodiment, the output stage current can be shaped to correspond to the desired output power of the amplifier. In such an embodiment, the output stage current is a function that is derived from the envelope of the desired output signal, and the power efficiency will increase.

[0458] FIG. 41 illustrates exemplary autobias output stage current control functions 4110 and 4120 according to embodiments of the present invention. Function 4110 may represent a function of output power and signal envelope as described above. On the other hand, function 4120 may represent a simple shaping function that goes to a minimum value for a pre-determined amount of time when the output power is below a threshold value. Accordingly, functions

4110 and **4120** represent two cases of autobias output stage current control functions with autobias control signal **4110** resulting in I_{out} response **4130** and autobias control signal **4120** resulting in I_{out} response **4140**. The invention, however, is not limited to those two exemplary embodiments. According to embodiments of the present invention, output stage autobias current control functions may be designed and implemented to accommodate the efficiency and current consumption requirements of a particular vector power amplifier design.

[**0459**] In implementation, several approaches exist for performing output stage current control. In some embodiments, output stage current shaping is performed using the Autobias module. The Autobias module is illustrated as autobias circuitry **714** and **716** in the embodiments of FIGS. **7** and **8**. Similarly, the Autobias module is illustrated as autobias circuitry **1218** in the embodiments of FIGS. **12** and **13**, and as autobias circuitry **1718** in the embodiments of FIGS. **17** and **18**.

[**0460**] Output stage current control using Autobias is depicted in process flowchart **4800** of the embodiment of FIG. **48**. The process begins in step **4810**, which includes receiving output power and output signal envelope information of a desired output signal of a vector power amplifier (VPA). In some embodiments, implementing output stage current control using Autobias requires a priori knowledge of the desired output power of the amplifier. Output power information may be in the form of envelope and phase information. For example, in the embodiments of FIGS. **7**, **8**, **12**, **13**, **17**, and **18**, output power information is included in I and Q data components received by the VPA embodiment. In other embodiments, output power information may be received or calculated using other means.

[**0461**] Step **4820** includes calculating a signal according to the output power and output envelope signal information. In embodiments, an Autobias signal is calculated as a function of some measure of the desired output power. For example, the Autobias signal may be calculated as a function of the envelope magnitude of the desired output signal. Referring to the embodiments of FIGS. **7**, **8**, **12**, **13**, **17**, and **18**, for example, it is noted that the Autobias signal (signals **715** and **717** in FIGS. **7** and **8**, signal **1228** in FIGS. **12** and **13**, and signals **1728** in FIGS. **17** and **18**) is calculated according to received I and Q data components of a desired output signal. In certain embodiments, such as the ones described in FIGS. **7**, **8**, **12**, **13**, **17**, and **18**, the Autobias signal is calculated by an Autobias module being provided output power information. In other embodiments, the Autobias signal may be calculated by the I and Q Data Transfer Function module(s) of the VPA. In such embodiments, an Autobias module may not be required in implementation. In embodiments, the I and Q Data Transfer Function module calculates a signal, outputs the signal to a DAC which output signal represents the Autobias signal.

[**0462**] Step **4830** includes applying the calculated signal at an output stage of the VPA, thereby controlling a current of the output stage according to the output power of the desired output signal. In embodiments, step **4830** includes coupling the Autobias signal at the PA stage input of the VPA. This is illustrated, for example, in the embodiments of FIGS. **33** and **42** where Autobias signal **3310** is coupled at the PA stage input of the VPA embodiment. In these embodiments, Autobias signal **3310** controls the bias of the PA stage transistors according to the output power of the desired output signal of

the VPA embodiment. For example, Autobias signal **3310** may cause the PA stage transistors to operate in cutoff state when the desired output power is minimal or near zero, thereby drawing little or no output stage current. Similarly, when a maximum output power is desired, Autobias signal **3310** may bias the PA stage transistors to operate in class C,D,E, etc. switching mode. Autobias signal **3310** may also cause the PA stage transistors or FETs to operate in forward or reverse biased states according to the desired output power and signal envelope characteristics.

[**0463**] In other embodiments, step **4830** includes coupling the Autobias signal using pull-up impedances at the PA stage input and optionally the inputs of the driver and pre-driver stages of the VPA. FIGS. **38** and **43** illustrate such embodiments. For example, in the embodiment of FIG. **38**, bias impedance **3850** couples Autobias Iref signal **3840** to input terminal **3820** of BJT element **3870**. BJT element **3870** represents the PA stage of one PA branch of an exemplary VPA embodiment. Similarly, in the embodiment of FIG. **43**, Autobias signal **4310** is coupled to transistors **Q1**, . . . , **Q8** through corresponding bias impedances **Z1**, . . . , **Z8**. Transistors **Q1**, . . . , **Q8** represent the PA stage of one branch of an exemplary VPA embodiment.

[**0464**] Embodiments for implementing the Autobias circuitry described above will now be provided. FIG. **27** illustrates three embodiments **2700A**, **2700B**, and **2700C** for implementing the Autobias circuitry. These embodiments are provided for illustrative purposes, and are not limiting. Other embodiments will be apparent to persons skilled in the art(s) based on the teachings contained herein.

[**0465**] In embodiment **2700A**, Autobias circuitry **2700A** includes an Autobias Transfer Function module **2712**, a DAC **2714**, and an optional interpolation filter **2718**. Autobias circuitry **2700A** receives an I and Q Data signal **2710**. Autobias Transfer Function module **2712** processes the received I and Q Data signal **2710** to generate an appropriate bias signal **2713**. Autobias Transfer Function module **2712** outputs bias signal **2713** to DAC **2714**. DAC **2714** is controlled by a DAC clock **2716** which may be generated in Autobias transfer module **2712**. DAC **2714** converts bias signal **2713** into an analog signal, and outputs the analog signal to interpolation filter **2718**. Interpolation filter **2718**, which also serves as an anti-aliasing filter, shapes the DAC's output to generate Autobias signal **2720**, illustrated as Bias A in embodiment **5112G**. Autobias signal **2720** may be used to bias the PA stage and/or the driver stage, and/or the pre-driver stage of the amplifier. In an embodiment, Autobias signal **2720** may have several other Autobias signals derived therefrom to bias different stages within the PA stage. This can be done using additional circuitry not included in embodiment **2700A**.

[**0466**] In contrast, embodiment **2700B** illustrates an Autobias circuitry embodiment in which multiple Autobias signals are derived within the Autobias circuitry. As shown in embodiment **2700B**, circuit networks **2722**, **2726**, and **2730**, illustrated as circuit networks A, B, and C in embodiment **2700B**, are used to derive Autobias signals **2724** and **2728** from Autobias signal **2720**. Autobias signals **2720**, **2724**, and **2728** are used to bias different amplification stages.

[**0467**] Embodiment **2700C** illustrates another Autobias circuitry embodiment in which multiple Autobias signals are generated independently within the Autobias Transfer Function module **2712**. In embodiment **2700C**, Autobias Transfer Function module **2712** generates multiple bias signals according to the received I and Q Data signal **2710**. The bias

signals may or may not be related. Autobias Transfer Function module 2712 outputs the generated bias signals to subsequent DACs 2732, 2734, and 2736. DACs 2732, 2734, and 2736 are controlled by DAC clock signals 2733, 2735, and 2737, respectively. DACs 2732, 2734, and 2736 convert the received bias signals into analog signals, and output the analog signals to optional interpolation filters 2742, 2744, and 2746. Interpolation filters 2742, 2744, and 2746, which also serve as anti-aliasing filters, shape the DACs outputs to generate Autobias signals 2720, 2724, and 2728. Similar to embodiment 2700B, Autobias signals 2720, 2724, and 2728 are used to bias different amplification stages such as the pre-driver, driver, and PA.

[0468] As noted above, Autobias circuitry embodiments according to the present invention are not limited to the ones described in embodiments 2700A, 2700B, and 2700C. A person skilled in the art will appreciate, for example, that Autobias circuitry can be extended to generate any number of bias control signals as required to control the bias of various stages of amplification, and not just three as shown in embodiments 5200B and 5200C, for example.

3.5.3) Output Stage Protection

[0469] As described above, output stage embodiments according to embodiments of the present invention are highly power efficient as a result of being able to directly couple outputs at the PA stage using no combining or isolating elements. Certain output stage embodiments in certain circumstances and/or applications, however, may require additional special output stage protection measures in order to withstand such direct coupling approach. This may be the case for example for output stage embodiments such as 5110D, 5120D, 5130D, 5160D, 5150E, 5160E, 5170E, and 5180E illustrated in FIGS. 51D and 51E. Note that, generally, complementary output stage embodiments, such as embodiments 5140D, 5150D, 5110E, 5120E, 5130E, and 5140E of FIGS. 51D and 51E, do not require (but may optionally use) the same output stage protection measures as will be described herein in this section. Output stage protection measures and embodiments to support such measures are now provided.

[0470] In one aspect, transistors of distinct branches of a PA stage should generally not simultaneously be in opposite states of operation for extended periods of time. Following a restart or power on with no inputs being supplied to the final PA stages, transients within the PA branches may cause this mode to occur resulting in the PA stage transistors potentially damaging one another or circuit elements connected to the output. Accordingly, embodiments of the present invention further constrain the Autobias module to limit the output current in the PA stage.

[0471] In another aspect, it may be desired to ensure that the Autobias module limits the output voltages below the breakdown voltage specification of the PA stage transistors. Accordingly, in embodiments of the present invention, such as the one illustrated in FIG. 42 for example, a feedback element 4210 is coupled between the common collector node of the PA stage and the Autobias module. Feedback element 4210 monitors the collector to base voltage of the PA stage transistors, and may constrain the Autobias signal as necessary to protect the transistors and/or circuit elements.

[0472] A person skilled in the art will appreciate that other output stage protection techniques may also be implemented. Furthermore, output stage protection techniques may be

implementation specific. For example, depending on the type of PA stage transistors (npn, pnp, NMOS, PMOS, npn/pnp, NMOS/PMOS), different protection functions may be required.

3.6) Harmonic Control

[0473] According to embodiments of the present invention, an underlying principle for each branch PA is to maximize the transfer of power to a fundamental harmonic of the output spectrum. Typically, each branch PA may be multi-stage giving rise to a harmonically rich output spectrum. In one aspect, transfer of real power is maximized for the fundamental harmonic. In another aspect, for non-fundamental harmonics, real power transfer is minimized while imaginary power transfer may be tolerated. Harmonic control, according to embodiments of the present invention, may be performed in a variety of ways.

[0474] In one embodiment, real power transfer onto the fundamental harmonic is maximized by means of wave-shaping of the PA stage input signals. In practice, several factors play a role in determining the optimal wave shape that results in a maximum real power transfer onto the fundamental harmonic. Embodiment 3400 of the present invention, described above, represents one embodiment that employs waveshaping of PA stage input signals. In embodiment 3400, a plurality of harmonic control circuitry (HCC) networks 3410-{1, . . . , n} are coupled at the PA stage input of each PA branch {1, . . . , n}. HCC networks 3410-{1, . . . , n} have the effect of waveshaping the PA stage inputs, and are typically selected so as to maximize real power transfer to the fundamental harmonic of the summed output spectrum. According to embodiments of the present invention, waveshaping can be used to generate variations of harmonically diverse waveforms. In other embodiments, as can be apparent to a person skilled in the art, waveshaping can be performed at the pre-driver and/or the driver stage.

[0475] In another embodiment, harmonic control is achieved by means of waveshaping of the PA stage output. FIG. 43 illustrates an exemplary PA stage embodiment 4300 of the present invention. In embodiment 4300, Autobias signal 4310 is coupled to transistors Q1, . . . , Q8 through corresponding bias impedances Z1, . . . , Z8. Notice that when impedances Z1, . . . , Z8 have different values, transistors Q1, . . . , Q8 have different bias points and can be turned on at different times. This approach of biasing transistors Q1, . . . , Q8 is referred to as staggered bias. Note that using staggered bias, the PA output waveform can be shaped in a variety of ways depending on the values assigned to bias impedances Z1, . . . , Z8.

[0476] Harmonic control using staggered bias is depicted in process flowchart 4900 of the embodiment of FIG. 49. The process begins in step 4910, which includes coupling an input signal at first ports of a plurality of transistors of a power amplifier (PA) switching stage. In the example embodiment of FIG. 43, for example, step 4910 corresponds to coupling PA_IN signal 4310 at base terminals of the plurality of transistors Q1, . . . , Q8.

[0477] Step 4920 includes coupling a plurality of impedances between the first ports of the plurality of transistors and a bias signal. In the example embodiment of FIG. 43, for example, step 4920 is achieved by coupling impedances Z1, . . . , Z8 between base terminals of respective transistors Q1, . . . , Q8 and Iref signal. In an embodiment, values of the plurality of impedances are selected to cause a time-staggered

switching of the input signal, thereby harmonically shaping an output signal of the PA stage. In embodiments, a multi-stage staggered output may be generated by selecting multiple distinct values of the plurality of impedances. In other embodiments, switching is achieved by selecting the plurality of impedances to have equal or substantially equal value.

[0478] FIG. 44 illustrates an exemplary wave-shaped PA output using a two-stage staggered bias approach. In a two-stage staggered bias approach, a first set of the PA transistors is first turned on before a second set is turned on. In other words, the bias impedances take two different values. Waveform 4410 represents an input waveform into the PA stage. Waveform 4420 represents the wave-shaped PA output according to a two-stage staggered bias. Notice that output waveform 4420 slopes twice as it transitions from 1 to 0, which corresponds to the first and second sets of transistors turning on successively.

[0479] According to embodiments of the present invention, a variety of multi-stage staggered bias approaches may be designed. Bias impedance values may be fixed or variable. Furthermore, bias impedance values may be equal or substantially equal, distinct, or set according to a variety of permutations. For example, referring to the example of FIG. 43, one exemplary permutation might set $Z1=Z2=Z3=Z4$ and $Z5=Z6=Z7=Z8$ resulting in a two-stage staggered bias.

3.7) Power Control

[0480] Vector power amplification embodiments of the present invention intrinsically provide a mechanism for performing output power control.

[0481] FIG. 45 illustrates one approach for performing power control according to an embodiment of the present invention. In FIG. 45, phasors \vec{U}_1 and \vec{L}_1 represent upper and lower constituents of a first phasor \vec{R}_1 . \vec{U}_1 and \vec{L}_1 are constant magnitude and are symmetrically shifted in phase relative to \vec{R}_1 by a phase shift angle $\phi/2$. Phasors \vec{U}_2 and \vec{L}_2 represent upper and lower constituents of a second phasor \vec{R}_2 . \vec{U}_2 and \vec{L}_2 are constant magnitude and are symmetrically shifted in phase relative to \vec{R}_2 by a phase shift angle

$$\frac{\phi}{2} + \phi_{off}.$$

[0482] It is noted, from FIG. 45, that \vec{R}_1 and \vec{R}_2 are in-phase relative to each other but only differ in magnitude. Furthermore, \vec{U}_2 and \vec{L}_2 are equally or substantially equally phased shifted relative to \vec{U}_1 and \vec{L}_1 , respectively. Accordingly, it can be inferred that, according to the present invention, a signal's magnitude can be manipulated without varying its phase shift angle by equally or substantially equally shifting symmetrically its constituent signals.

[0483] According to the above observation, output power control can be performed by imposing constraints on the phase shift angle of the constituent signals of a desired output signal. Referring to FIG. 45, for example, by constraining the range of values that phase shift angle

$$\frac{\phi}{2}$$

can take, magnitude constraints can be imposed on phasor \vec{R}_1 .

[0484] According to embodiments of the present invention, a maximum output power level can be achieved by imposing a minimum phase shift angle condition. For example, referring to FIG. 45, by setting a condition such that

$$\frac{\phi}{2} \geq \phi_{off},$$

the magnitude of phasor \vec{R}_1 is constrained not to exceed a certain maximum level. Similarly, a maximum phase shift angle condition imposes a minimum magnitude level requirement.

[0485] In another aspect of power control, output power resolution is defined in terms of a minimum power increment or decrement step size. According to an embodiment of the present invention, output power resolution may be implemented by defining a minimum phase shift angle step size. Accordingly, phase shift angle values are set according to a discrete value range having a pre-determined step size. FIG. 46 illustrates an exemplary phase shift angle spectrum, whereby phase shift angle

$$\frac{\phi}{2}$$

is set according to a pre-determined value range having a minimum step ϕ_{step} .

[0486] A person skilled in the art will appreciate that a variety of power control schemes may be implemented in a fashion similar to the techniques described above. In other words, various power control algorithms can be designed, according to the present invention, by setting corresponding constraints on phase shift angle values. It is also apparent, based on the description above of data transfer functions, that power control schemes can be naturally incorporated into a transfer function implementation.

3.8) Exemplary Vector Power Amplifier Embodiment

[0487] FIG. 47 illustrates an exemplary embodiment 4700 of a vector power amplifier according to the present invention. Embodiment 4700 is implemented according to the Direct Cartesian 2-Branch VPA method.

[0488] Referring to FIG. 47, signals 4710 and 4712 represent incoming signals from a transfer function stage. The transfer function stage is not shown in FIG. 47. Block 4720 represents a quadrature generator which may be optionally implemented according to an embodiment of the present invention. Quadrature generator 4720 generates clock signals 4730 and 4732 to be used by vector modulators 4740 and 4742, respectively. Similarly, signals 4710 and 4712 are input into vector modulators 4740 and 4742. As described above, vector modulators 4740 and 4742 generate constant envelope constituents that are, subsequently, processed by a PA stage. In embodiment 4700, the PA stage is multi-stage, whereby

each PA branch includes a pre-driver stage **4750-4752**, a driver stage **4760-4762**, and a power amplifier stage **4770-4772**.

[0489] Further illustrated in FIG. **47** are Autobias signals **4774** and **4776**, and terminals **4780** and **4782** for coupling harmonic control circuitry and networks. Terminal node **4780** represents the output terminal of the vector power amplifier, and is obtained by direct coupling of the two PA branches' outputs.

4. SUMMARY

[0490] Mathematical basis for a new concept related to processing signals to provide power amplification and up-conversion is provided herein. These new concepts permit arbitrary waveforms to be constructed from sums of waveforms which are substantially constant envelope in nature. Desired output signals and waveforms may be constructed from substantially constant envelope constituent signals which can be created from the knowledge of the complex envelope of the desired output signal. Constituent signals are summed using new, unique, and novel techniques not available commercially, not taught or found in literature or related art. Furthermore, the blend of various techniques and circuits provided in the disclosure provide unique aspects of the invention which permits superior linearity, power added efficiency, monolithic implementation and low cost when compared to current offerings. In addition, embodiments of the invention are inherently less sensitive to process and temperature variations. Certain embodiments include the use of multiple input single output amplifiers described herein.

[0491] Embodiments of the invention can be implemented by a blend of hardware, software and firmware. Both digital and analog techniques can be used with or without microprocessors and DSP's.

[0492] Embodiments of the invention can be implemented for communications systems and electronics in general. In addition, and without limitation, mechanics, electro mechanics, electro optics, and fluid mechanics can make use of the same principles for efficiently amplifying and transducing signals.

5. CONCLUSION

[0493] The present invention has been described above with the aid of functional building blocks illustrating the performance of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries can be defined so long as the specified functions and relationships thereof are appropriately performed. Any such alternate boundaries are thus within the scope and spirit of the claimed invention. One skilled in the art will recognize that these functional building blocks can be implemented by discrete components, application specific integrated circuits, processors executing appropriate software and the like and combinations thereof.

[0494] While various embodiments of the present invention have been described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of the present invention should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

What is claimed is:

1. A method of amplification, comprising:
 - determining an in-phase (I) component and a quadrature (Q) component of a desired output signal based on a reference signal;
 - generating first and second signals having a desired output signal frequency from the received I component;
 - generating third and fourth signals having the desired output signal frequency from the received Q component;
 - amplifying each of the first, second, third, and fourth signals individually; and
 - generating the desired output signal by summing the amplified first, second, third, and fourth signals.
2. The method of claim 1, wherein the first and second signals have substantially constant and equal magnitude envelopes and a sum equal to the I component.
3. The method of claim 1, wherein the third and fourth signals have substantially constant and equal magnitude envelopes and a sum equal to the Q component.
4. The method of claim 1, further comprising receiving a clock signal set according to the desired output signal frequency.
5. The method of claim 1, wherein the amplifying comprises amplifying the first, second, third, and fourth signals substantially equally according to a desired power level of the desired output signal.
6. The method of claim 1, further comprising determining a relative phase angle and magnitude of the I and Q components.
7. The method of claim 6, further comprising generating a set of I and Q phase control signals based on the determined relative phase angle and magnitude of the I and Q components.
8. The method of claim 6, wherein the determining comprises determining a phase shift relative to the reference signal and determining a complex envelope.
9. The method of claim 8, further comprising determining a first phase shift angle using the complex envelope, wherein the first phase shift angle is the phase difference between the first and second substantially constant envelope signals.
10. The method of claim 9, further comprising determining a second phase shift angle using the complex envelope, wherein the second phase shift angle is the phase difference between the third and fourth substantially constant envelope signals.
11. A vector power amplifier, comprising:
 - one or more phase splitters configured to determine an in-phase (I) component and a quadrature (Q) component of a desired output signal based on a reference signal;
 - one or more vector modulators configured to generate first and second signals having a desired output signal frequency from the received I component;
 - one or more vector modulators configured to generate third and fourth signals having the desired output signal frequency from the received Q component;
 - one or more amplifiers configured to amplify each of the first, second, third, and fourth signals individually; and
 - a summer configured to generate the desired output signal by summing the amplified first, second, third, and fourth signals.
12. The amplifier of claim 11, wherein the one or more vector modulators are configured to generate the first and

second signals so that they have substantially constant and equal magnitude envelopes and a sum equal to the I component.

13. The amplifier of claim **11**, wherein the one or more vector modulators are configured to generate the third and fourth signals so that they have substantially constant and equal magnitude envelopes and a sum equal to the Q component.

14. The amplifier of claim **11**, further comprising a clock configured to generate a clock signal according to the desired output signal frequency.

15. The amplifier of claim **11**, wherein the one or more amplifiers are configured to amplify the first, second, third, and fourth signals substantially equally according to a desired power level of the desired output signal.

16. The amplifier of claim **11**, further comprising determining a relative phase angle and magnitude of the I and Q components.

17. The amplifier of claim **11**, wherein the one or more amplifiers comprise one or more multiple input single output (MISO) amplifiers.

* * * * *