



US010359147B1

(12) **United States Patent**
Johnson, Sr.

(10) **Patent No.:** **US 10,359,147 B1**
(45) **Date of Patent:** ***Jul. 23, 2019**

(54) **REMOVABLE TRIPOD WITH SECUREMENT**

(71) Applicant: **Really Right Stuff, LLC**, Lehi, UT
(US)

(72) Inventor: **Joseph M. Johnson, Sr.**, Lehi, UT
(US)

(73) Assignee: **Really Right Stuff, LLC**, Lehi, UT
(US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **16/294,137**

(22) Filed: **Mar. 6, 2019**

Related U.S. Application Data

(63) Continuation of application No. 16/101,848, filed on Aug. 13, 2018, now Pat. No. 10,267,452, which is a continuation of application No. 15/782,167, filed on Oct. 12, 2017, now Pat. No. 10,054,256, which is a continuation of application No. 15/605,511, filed on May 25, 2017, now Pat. No. 9,816,662, which is a continuation of application No. 15/293,764, filed on Oct. 14, 2016, now Pat. No. 9,689,525, which is a continuation of application No. 13/366,080, filed on Feb. 3, 2012, now Pat. No. 9,494,276.

(60) Provisional application No. 61/489,179, filed on May 23, 2011.

(51) **Int. Cl.**
A47B 91/00 (2006.01)
F16M 11/36 (2006.01)
F16B 7/18 (2006.01)
G03B 17/56 (2006.01)

(52) **U.S. Cl.**

CPC **F16M 11/36** (2013.01); **F16B 7/182** (2013.01); **G03B 17/561** (2013.01); **F16M 2200/08** (2013.01)

(58) **Field of Classification Search**

CPC ... A45F 3/44; E04H 12/2223; E04H 12/2215; F16M 11/32; F16M 11/36; A47B 91/00; A47B 13/021; A47B 1/024
USPC 248/545, 688, 530, 156, 159, 163.1, 188, 248/188.8, 188.9; 108/156
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,654,620 A * 10/1953 Tinnerman A47B 91/06
138/89
2,868,602 A * 1/1959 Drezner F16B 12/48
248/188.8
4,079,908 A * 3/1978 Davis A45F 3/44
248/156
5,046,693 A * 9/1991 Browne F16B 9/023
248/159
6,629,506 B2 * 10/2003 Park A47B 9/18
108/156
6,669,153 B1 * 12/2003 Allan A47B 91/00
248/188.9
6,908,067 B2 * 6/2005 Clasen E04H 12/2223
248/533


(Continued)

Primary Examiner — Bradley Duckworth
(74) *Attorney, Agent, or Firm* — Chernoff, Vilhauer, McClung & Stenzel, LLP

(57) **ABSTRACT**

Installation of a removable tripod foot is facilitated by a cross-axis aperture in the foot and loosening of the threaded connection of the foot and the tripod's leg is resisted by a resilient element engaging interfacing surfaces of the foot and the leg.

14 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,264,210	B2 *	9/2007	Yu	A45F 3/44 135/16
7,520,485	B1 *	4/2009	Giannetto	A01K 97/10 173/91
8,398,037	B2 *	3/2013	Johnson	F16M 11/32 248/163.2
10,054,256	B2 *	8/2018	Johnson, Sr.	F16M 11/36
2002/0109053	A1 *	8/2002	Lemieux	F16M 11/14 248/187.1
2004/0227040	A1 *	11/2004	Crain	F16B 7/1463 248/188.8
2005/0161560	A1 *	7/2005	Kjellman	F16M 11/16 248/163.1
2008/0251663	A1 *	10/2008	Tracy	A47B 91/00 248/188.8
2009/0278020	A1 *	11/2009	Marcil	A45F 3/44 248/545
2010/0005701	A1 *	1/2010	Santiago	A01K 97/10 43/21.2

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

REMOVABLE TRIPOD WITH SECUREMENT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 16/101,848, filed Aug. 13, 2018, which application is a continuation of U.S. patent application Ser. No. 15/782,167, filed Oct. 12, 2017, now U.S. Pat. No. 10,054,256, issued Aug. 21, 2018, which application is a continuation of U.S. patent application Ser. No. 15/605,511, filed May 25, 2017, now U.S. Pat. No. 9,816,662, issued Nov. 14, 2017, which application is a continuation of U.S. patent application Ser. No. 15/293,764, filed Oct. 14, 2016, now U.S. Pat. No. 9,689,525, issued Jun. 27, 2017, which application is a continuation of U.S. patent application Ser. No. 13/366,080, filed Feb. 3, 2012, now U.S. Pat. No. 9,494,276, issued Nov. 15, 2016, which application claims the benefit of U.S. Provisional App. No. 61/489,179, filed May 23, 2011.

BACKGROUND OF THE INVENTION

The present invention relates to a removable foot for a tripod and, more particularly, to a mechanism to aid in tightening and to resist loosening of a threaded connection between a foot and a leg of a tripod.

tripods are used for both still and motion photography to provide stability and prevent unintended movement of the camera. A tripod reduces camera movement to enable the sharpest image and is especially useful when using a telephoto lens or longer exposure time because any camera movement while the shutter is open will blur the image. A tripod also aids in framing an image or in capturing multiple images of the same scene, for example when bracketing an exposure. A tripod enables controlled movement of the camera when panning, facilitating tracking a moving subject with a motion video camera or capturing multiple stills for a panoramic image.

Removable feet can increase the utility of a tripod by enabling use of specialized feet for particular surfaces and conditions. However, removable feet are commonly attached to a tripod's legs by screw threads which can be difficult to tighten and may loosen making the tripod unstable and increasing the likelihood that a foot will be lost. What is desired, therefore, is a removable tripod foot that is easy to install and resists loosening.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is perspective view of a tripod.

FIG. 2 is a perspective view of a claw-type tripod foot.

FIG. 3 is a perspective view of the underside to the claw-type foot of FIG. 2.

FIG. 4 is a perspective view of a spike tripod foot.

FIG. 5 is an elevation view of a portion of a tripod leg and a removable foot.

FIG. 6 is a section view of a portion of a tripod leg and a removable foot.

FIG. 7 is an elevation view of a portion of a tripod leg and a removable foot of a second embodiment.

FIG. 8 is an enlarged view of a portion of the section of FIG. 6.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

Referring in detail to the drawings where similar parts are identified by like reference numerals, and, more particularly

to FIG. 1, a tripod 20 is useful for both still and motion photography. Typically, a tripod comprises an apex mount 22 including a mechanism, such as a threaded stud 24, for securing a camera or an intermediate interface, such as a ball head or panoramic element, to which a camera can be secured. The apex mount 22 is secured to an apex structure 26 which is also the anchor point for the three legs 28 of the tripod. Each of the legs is typically secured to the apex structure 26 by a pivot joint 30 enabling the legs to be pivoted toward each other for transport and pivoted apart when the tripod is deployed for use. The legs 28 commonly comprise a plurality of leg sections, such as the three leg sections 32, 34, and 36, that telescope together to reduce the length of the collapsed tripod for transport or to enable adjustment of the height of the deployed tripod or compensation for an irregular supporting surface. A locking mechanism 38 which may be actuated by twisting secures the relative positions of the telescoping tube sections. Photographic tripods are preferably light weight and compact to facilitate transportation and the leg sections commonly comprise tubes of light weight materials such as aluminum or carbon fiber.

Tripod feet 40 provide the interface between the legs of the tripod and the surface on which the tripod will be supported. The tripod feet commonly have a curved lower surface 42 which is often covered with rubber or plastic to resist sliding on a floor or other supporting surface. While the feet may be permanently affixed to the legs of the tripod, the feet are often removable enabling more specialized feet to be substituted when desired. Referring FIGS. 2 and 3, for example, one type specialized tripod foot is a claw foot 50 having body 52 comprising a crenated wall 54 with a plurality of facets 56 along the lower edge. The sharp edges 58 at the intersections of the facets are intended to bite into a hard, rough surface and secure the tripod even if the surface is wet. Referring to FIG. 4, another type of specialized tripod foot is a spike foot 70. The pointed end portion 72 of the foot's spike-like body 76 is intended to penetrate loose surface material providing additional support on shifting surfaces or in strong winds.

Referring to also FIGS. 5 and 6, replaceable tripod feet are commonly affixed to the leg of the tripod by screwing a threaded stud 80 projecting from the foot into a threaded aperture 82 in a ferrule 84 which is secured to the end of a tubular leg section 86. On the other hand, referring to FIG. 7, the gender of the threads in the ferrule and the foot may be reversed with male threads of a threaded stud 90 projecting from the ferrule to engage female threads in an aperture 92 in the foot. While a threaded connection makes replacement straight forward, it can be difficult to fully tighten the threaded connection. The feet can also loosen as a result of cyclic loads and vibration as the tripod is repeatedly deployed or moved across a supporting surface; a condition that is exacerbated by the difficulty in tightening the feet. When the threaded feet loosen, the tripod becomes unstable and the feet may eventually become detached from the tripod. To prevent the removable feet from loosening, a liquid thread locker is commonly applied to the threads but this is time consuming and the container may leak damaging other equipment in a camera bag. On the other hand, threaded connections with prevailing torque features increase the torque required to tighten, as well as loosen, the connection making tightening and removal more difficult and the features may wear and become ineffective with repeated use. The applicants concluded that a mechanism that would permit removable tripod feet to be easily tight-

3

ened but would reliably resist loosening would substantially improve the utility of a tripod.

The removable feet **50**, **70** for use with the tripod **20** include a resilient element **94** at the interface between the foot and the ferrule **84** secured to the end of the tripod's leg **28**. As illustrated in FIG. **5**, the resilient element **94** may be supported by the leg engaging surface **60** of the removable foot, but, referring to FIG. **7**, the resilient element **94** could be applied to the foot engaging surface **96** of the ferrule **84**. The resilient element increases friction between the interfacing surfaces of the foot and the ferrule to resist loosening of the threaded connection. While the elastomeric element could have any shape and could be applied to the respective surface, it is, preferably, a toroidal element, and, more preferably, an elastomeric o-ring installed in a groove **98** in one of the interfacing surfaces **60**, **96**. Referring also to FIG. **8**, the groove **98** has an inner wall **99** which is undercut at an angle **101**. The diameter of the groove at the point of intersection of the inner wall with the interfacing surface **60** is slightly greater than the inner diameter of the resilient element **94**. When the resilient element is installed in the groove it must be stretched slightly. When the resilient element is released in the groove, it returns to its original size and is trapped in the groove against the sloping inner wall. On the other hand, the resilient element could be retained in the groove by an outer wall that sloped to a diameter, at the interfacing surface, that is slightly smaller than the outer diameter of the resilient element. A portion of the resilient element projects proud of the respective leg engaging surface **60** or foot engaging surface **96** so that the resilient element is compressed when the threaded connection is tightened. While an o-ring is inexpensive, the dimensions and characteristics of o-rings are carefully controlled and the force exerted by the o-ring is predictable enabling the foot to be tightened so that the interfacing surfaces **60** and **96** come in contact. Contact between the rigid leg engaging and foot engaging surfaces enhances the stability of the foot and the tripod and increases friction in the threaded connection which resists loosening. The compressed resilient element exerts a resilient separating force at the interfacing surfaces maintaining friction in the engaged screw threads during vibration and cyclic loading and resisting loosening of the threaded connection. Since the resilient element **94** does not come in contact with both of the interfacing surfaces until the surfaces are proximate each other, the foot screws easily into the ferrule for a major portion of the length of the threaded connection.

To compress the resilient element and bring the leg engaging surface into contact with the foot engaging surface, an aperture(s) **74** which extends substantially normal to the longitudinal axis of the threaded element in the foot is provided in the body of the foot. A tool, such as a rod, an Allen wrench **100** or the shank of a screw driver can be inserted into the aperture providing the necessary leverage to fully tighten the threaded connection.

The resilient element at the interfacing surfaces of a removable foot and a tripod leg and a cross-axis aperture facilitates installation of the foot and resists loosening of the threaded connection.

The detailed description, above, sets forth numerous specific details to provide a thorough understanding of the present invention. However, those skilled in the art will appreciate that the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuitry have not been described in detail to avoid obscuring the present invention.

4

All the references cited herein are incorporated by reference.

The terms and expressions that have been employed in the foregoing specification are used as terms of description and not of limitation, and there is no intention, in the use of such terms and expressions, of excluding equivalents of the features shown and described or portions thereof, it being recognized that the scope of the invention is defined and limited only by the claims that follow.

I claim:

1. A foot for a tripod comprising:

- (a) a body including an interface surface including a portion arranged to engage a terminal portion of a leg of a tripod and an elongate threaded portion arranged substantially normal to the portion of the interface surface;
- (b) a resilient element engaging the interface surface;
- (c) wherein said resilient element extends proud of the portion of said interface surface arranged to engage the leg of the tripod;
- (d) wherein said interface surface includes an outer peripheral edge and said resilient element is sized such that at least a portion is within said outer peripheral edge of said interface surface when engaged therewith;
- (e) wherein said resilient element has an outer diameter and further said body includes a body outer peripheral surface with an outer diameter proximate said outer peripheral edge, where the resilient element outer diameter extends proud of the body outer peripheral surface;
- (f) said body defining an opening extending completely there through at a location between said interface surface and an end of said body furthest distant from said terminal portion of said leg of said tripod when said body is engaged with said terminal portion of said leg of said tripod.

2. The foot for said tripod of claim **1** wherein said body includes a crenated wall defining a plurality of facets arranged to engage a surface supporting said tripod, wherein each of said facets has an elongate portion perpendicular to the axis of said elongate threaded portion.

3. The foot for said tripod of claim **2** wherein a respective arc is defined in said crenated wall extending the entire distance between each of said plurality of facets, where each of said respective arc does not define a discontinuity therein between each of said plurality of facets.

4. The foot for said tripod of claim **3** wherein said body defines said opening in said body at a location directly above a first said facet at an elevation above the upper portion of each of said arc defined on either side of said first facet.

5. The foot for said tripod of claim **4** wherein said body defines said opening in said body at a location directly above a second said facet at an elevation above the upper portion of each of said arc defined on either side of said second facet.

6. The foot for said tripod of claim **5** wherein said opening is aligned with said elongate threaded portion.

7. The foot for said tripod of claim **6** wherein said body defines an upper exterior surface at an elevation above said upper portion of each of said arc defined on either side of said first facet, and at an elevation above said upper portion of each of said arc defined on either side of said second facet.

8. The foot for said tripod of claim **7** wherein said body defines a lower exterior surface at an elevation below said upper exterior surface and adjacent thereto.

9. The foot for said tripod of claim **8** wherein said first opening is defined in part of said upper exterior surface and in part of said lower exterior surface, said second opening is

defined in part of said upper exterior surface and in part of said lower exterior surface, and wherein said upper exterior surface and said lower exterior surface define a discontinuity therein around said body.

10. The foot for said tripod of claim 1 wherein the interface surface includes a portion defining a circular groove and the resilient element comprises an elastomeric toroid retained in the groove with a portion of a surface of the resilient element projecting proud of the portion of the interface surface arranged to engage the leg of a tripod. 10

11. The foot for said tripod of claim 1 wherein said body further comprises an elongate spike portion for engaging a surface supporting said tripod.

12. The foot for said tripod of claim 1 wherein said elongate threaded portion of said body comprises a stud projecting from said surface. 15

13. The foot for said tripod of claim 1 wherein said elongate threaded portion of said body comprises a portion defining a threaded aperture.

14. The foot for said tripod of claim 1 further comprising said tripod. 20

* * * * *