TOTAL NO OF SHEET: 03. TOTAL NO OF FIG:03



Fig.1: Concrete Production by adding fibre as Reinforced Material flow.

Dated this 24th day of August, 2022

S.B.Patil college of Engineering

Prof. R.B. Ghogare

Prof.M.V.Gaikwad

Prof.P.R.Admile

Prof. S. M. Baral

Prof. M. B. Katkar

Prof. S .M. Kale

Prof. S. V. Bankar

Prof.V.S.Bere

Prof.A.B.Rupnawar



Fig.2: Concrete Production by adding fibre as Reinforced Material block.

Dated this 24th day of August, 2022

S.B.Patil college of Engineering

Prof. R.B. Ghogare

Prof.M.V.Gaikwad

Prof.P.R.Admile

Prof. S. M. Baral

Prof. M. B. Katkar

Prof. S .M. Kale

Prof. S. V. Bankar

Prof.V.S.Bere

Prof.A.B.Rupnawar

TOTAL NO OF SHEET: 03. TOTAL NO OF FIG:03



Fig.3: Concrete Production by adding fibre as Reinforced Material.

Dated this 24th day of August, 2022

S.B.Patil college of Engineering

Prof. R.B. Ghogare

Prof.M.V.Gaikwad

Prof.P.R.Admile

Prof. S. M. Baral

Prof. M. B. Katkar

Prof. S .M. Kale

Prof. S. V. Bankar

Prof.V.S.Bere

Prof.A.B.Rupnawar

FORM 2
THE PATENT ACT 1970 &
The Patents Rules, 2003
COMPLETE SPECIFICATION
(See section 10 and rule 13)
Indian Patent office. /Delhi/ Mumbai/ Chennai/ Kolkata

TITLE OF THE INVENTION:

Concrete Production by adding fibre as Reinforced Material.

Name	Nationality	Address
Applicants		
S.B.Patil college of Engineering	AN INDIAN NATIONAL	Solapur-Pune highway, Vangali, Tal: Inadapur, Dist: Pune,Pin:413 Pin:413106
Prof. R.B. Ghogare	AN INDIAN NATIONAL	S.B.Patil college of Engineering staff quarters,Solapur-pune highway,Vangali,Tal:Inadapur,Dist:Pune, Pin:413106
Prof.M.V.Gaikwad	AN INDIAN NATIONAL	S.B.Patil college of Engineering staff quarters,Solapur-pune highway,Vangali,Tal:Inadapur,Dist:Pune, Pin:413106
Prof.P.R.Admile	AN INDIAN NATIONAL	S.B.Patil college of Engineering staff quarters,Solapur-pune highway,Vangali,Tal:Inadapur,Dist:Pune, Pin:413106
Prof. S. M. Baral	AN INDIAN NATIONAL	A/P Nimgao Ketaki, Tal- Indapur, Dist-Pune Pin:413120
Prof. M. B. Katkar	AN INDIAN NATIONAL	At-Bhagatwadi, Post-Sarati, Tal_ Indapur, Dist-Pune ,Pin:413103
Prof. S .M. Kale	AN INDIAN NATIONAL	A/P - Agoti No.2, Tal-Indapur Dist-Pune Pin:413106
Prof. S. V. Bankar	AN INDIAN NATIONAL	A/P- Malewadi (Akluj) Tal- Malshiras Dist-Solapur Pin- 413101
Prof.V.S.Bere	AN INDIAN NATIONAL	A/P- Ambikanagar, Indapur, Tal- Indapur Dist-Pune, Pin-413106
Prof.A.B.Rupnawar	AN INDIAN NATIONAL	A/P Mahatma Phule Nagar Bijawadi Tal Indapur Dist Pune, Pin:413106
Inventors		
Prof. R.B. Ghogare	AN INDIAN NATIONAL	S.B.Patil college of Engineering staff quarters, Solapur-pune highway,Vangali, Tal:Inadapur,Dist:Pune, Pin:413106
Prof.M.V.Gaikwad	AN INDIAN NATIONAL	S.B.Patil college of Engineering staff quarters, Solapur-pune highway,Vangali, Tal:Inadapur,Dist:Pune, Pin:413106
Prof.P.R.Admile	AN INDIAN NATIONAL	S.B.Patil college of Engineering staff quarters, Solapur-pune highway,Vangali, Tal:Inadapur,Dist:Pune, Pin:413106

Prof. S. M. Baral	AN INDIAN NATIONAL	A/P Nimgao Ketaki, Tal- Indapur, Dist-Pune Pin:413120
Prof. M. B. Katkar	AN INDIAN NATIONAL	At-Bhagatwadi, Post-Sarati, Tal_ Indapur, Dist-Pune ,Pin:413103
Prof. S .M. Kale	AN INDIAN NATIONAL	A/P - Agoti No.2, Tal-Indapur Dist-Pune Pin:413106
Prof. S. V. Bankar	AN INDIAN NATIONAL	A/P- Malewadi (Akluj) Tal- Malshiras Dist-Solapur Pin- 413101
Prof.V.S.Bere	AN INDIAN NATIONAL	A/P- Ambikanagar, Indapur, Tal- Indapur Dist-Pune, Pin-413106
Prof.A.B.Rupnawar	AN INDIAN NATIONAL	A/P Mahatma Phule Nagar Bijawadi Tal Indapur Dist Pune, Pin:413106

Complete Specification

ABSTRACT

Our Invention "Concrete Production by adding fibre as Reinforced Material" is a Concrete is one of the most broadly perceived advancement material generally conveyed by using locally available fixings. The current pattern in substantial innovation is towards expanding the strength and sturdiness of cement to fulfill the needs of the cutting edge development. The primary point of the review is to concentrate on the impact of glass fiber and steel strands in the substantial. FRC has the high elasticity and heat proof properties in this way decreasing the deficiency of harm during fire mishaps. In the current work the strength studies are done to analyze the glass and steel fiber concrete. The FRC is added 0.5, 1, 2 and 3% are added for M20 grade concrete. Result shows the rate expansion in compressive strength, flexural strength and split rigidity for 28days. The current development gives a manufactured fiber mix and techniques for its utilization containing a first fiber part framed of a homopolymeric polypropylene fiber and a second fiber part being a copolymer shaped of a polypropylene and a high thickness polyethylene. The principal fiber part is fibrillated and the second fiber part is a wound group included various strands of a no fibrillating monofilament. The manufactured fiber mix grants further developed support properties to the structure materials to which they are added. Specifically, the manufactured fiber mix when integrated into a structure material gives decreased penetrability, expanded weariness strength, further developed durability, and diminished plastic shrinkage. The one of a kind mix of the bent second fiber part mixed with the primary fiber part gives further developed blend capacity and uniform dissemination of the manufactured fiber mix in cementitious materials.

FILED OF INVENTION:

Civil Engineering

BACKGROUND OF THE INVENTION

Concrete is one of the most broadly perceived advancement material generally conveyed by using locally available fixings. The advancement of cement has achieved the fundamental requirement for added substances both compound and mineral to work on the exhibition of cement.

Subsequently assortments of admixtures, for example, fly debris, coconut fiber have been utilized up to this point. Glass fiber has involved more than 30 years in a few development components, essentially non constructional ones, as façade boards, channeling for sterilization, improving non recoverable structure work and different items. Concrete is one of the most tough structure materials.

It furnishes predominant imperviousness to fire contrasted and wooden development and gains strength over the long haul. Structures made of cement can have a long help life. Concrete is utilized more than some other artificial material on the planet Concrete, has moderately high compressive strength, however much lower elasticity.

Concrete has an extremely low coefficient of warm extension and therapists as it develops. The utilization of admixtures is predominantly to adjust the setting and solidifying of concrete by impacting the rate hydration of concrete. Various sorts of admixtures are there to diminish the water content by lessening the surface strain of water;

OBJECTIVES OF THE INVENTION

1) The objective is to provide a "Concrete Production by adding fibre as Reinforced Material" is a Concrete is one of the most broadly perceived advancement material generally conveyed by using locally available fixings.
2) The other objective is to provide a current pattern in substantial innovation is towards expanding the strength and sturdiness of cement to fulfill the needs of the cutting edge development. The primary point of the review is to concentrate on the impact of glass fiber and steel strands in the substantial.
3) The other objective is to provide a FRC has the high elasticity and heat proof properties in this way decreasing the deficiency of harm during fire mishaps. In the current work the strength studies are done to analyze the glass and steel fiber concrete. The FRC is added 0.5, 1, 2 and 3% are added for M20 grade concrete.
4) The other objective is to provide a the rate expansion in compressive strength, flexural strength and split rigidity for 28days. The current development gives a manufactured fiber mix and techniques for its utilization containing a first fiber part framed of a homopolymeric polypropylene fiber and a second fiber part being a copolymer shaped of a polypropylene and a high thickness polyethylene.
5) The other objective is to provide a principal fiber part is fibrillated and the second fiber part is a wound group included various strands of a no fibrillating monofilament. The manufactured fiber mix grants further developed support properties to the structure materials to which they are added.
6) The other objective is to provide a manufactured fiber mix when integrated into a structure material gives decreased penetrability, expanded weariness strength, further developed durability, and diminished plastic shrinkage.
7) The other objective is to provide a kind mix of the bent second fiber part mixed with the primary fiber part gives further developed blend capacity and uniform dissemination of the manufactured fiber mix in cementitious materials.

SUMMARY OF THE INVENTION

The materials utilized are concrete, coarse total sand as fine total, water and steel filaments

• Cement: Ordinary Portland concrete of 53 Grade

• Fine Aggregate (sand): Locally accessible zone II sand with explicit gravity 2.6 affirming with code book IS 393-1970.

• Coarse Aggregate: Crushed stone of 10mm size having explicit gravity 2.76 affirming code book IS 393-1970.

• Water: Potable water for Experiments.

• Steel Fibers: In this Experiment Hook tain steel strands are utilized with various angle proportions 50, 60 and 67 having lengths 35, 30 and 20mm with distance across 0.7, 0.5 and 0.4.

• Glass Fiber: It is the material produced using incredibly fine strands of glass. It is a light weight, areas of strength for incredibly vigorous material. There are unmistakable kinds of fiber anyway in these we have taken E-glass fiber to show better obstruction and an awesome protection to power.

The current creation gives a manufactured fiber mix that incorporates a first fiber part shaped of a homopolymeric polypropylene fiber, and a second fiber part. The second fiber part is a copolymer, shaped of a polypropylene and a high thickness polyethylene.

The polypropylene piece of the second fiber part is ideally present in a significant sum, generally ideally around 70 to 80 percent by weight, and the high thickness polyethylene segment is ideally present in a minor sum comparative with the polypropylene, generally ideally around 20 to 30 percent by weight.

In the favored encapsulation of the engineered fiber mix, the main fiber part is fibrillated and the second fiber part is available as a wound heap of no fibrillating monofilaments.

The turned pack is included different strands of the no fibrillating monofilament. Every one of the first and second fiber parts ideally has a fiber length of around 19 to around 60 mm, and most ideally, has significantly a similar fiber length. The principal fiber part is ideally around 100 to around 20,000 denier for each fiber and is ideally present in the engineered fiber mix in sums going from around 5 to around 50 by absolute weight percent, and all the more ideally around 6.7 percent by complete weight percent.

The second fiber part is ideally around 350 to around 6000 denier for every fiber, and is ideally present in sums going from around 50 to around 95, and all the more ideally around 93.3, percent by complete weight percent.

The current development likewise gives a built up cementitious material, like cement, including the manufactured fiber mix disseminated through a grid of the

cementitious material. The engineered fiber mix might be available in the cementitious material in sums going from around 0.1 to around 2.0 percent by volume, and ideally in sums going from around 0.3 to around 2.0 percent by volume, and most ideally from 0.5 to around 2.0 percent by volume.

BRIEF DESCRIPTION OF THE DIAGRAM

Fig.1: Concrete Production by adding fibre as Reinforced Material flow.
Fig.2: Concrete Production by adding fibre as Reinforced Material block.
Fig.3: Concrete Production by adding fibre as Reinforced Material.

DESCRIPTION OF THE INVENTION

It is notable that the expansion of a support part to building materials like cementitious materials, block, black-top, and such works on the primary honesty of the material and diminishes the probability of breaking. When integrated into cementitious materials like cement, for instance, the support part is added to lessen the impact of two primary underlying lacks:

1) low elasticity;

2) low resist crack. The rigidity of cement is moderately low since concrete, when shaped, typically contains various miniature breaks. It is the quick proliferation of these miniature breaks under applied pressure that is liable for the low rigidity of the material. On account of the broad use and relevance of concrete, extensive examination has been embraced to diminish the impacts of its inadequate underlying properties.

Regular support materials that are added to cementitious materials incorporate, for instance, different checks of wire cross section or support strands. An assortment of support fiber added substances are known in the workmanship that give strength qualities to building materials.

Common support filaments incorporate asbestos strands, glass strands, steel filaments, mineral filaments, and cellulose strands. Some support filaments are more qualified for specific applications than others. For instance, asbestos filaments are known to give compelling support however, due to ecological and wellbeing concerns, are not broadly utilized.

What's more, glass strands and steel filaments are somewhat costly, and tend to disintegrate in cementitious materials. Steel filaments normally decay at the outer layer of the fiber built up material, while glass strands constantly go through disintegration because of the basic idea of concrete. Likewise, because of the physical and substance attributes of steel strands, there is some trouble in consistently dispersing the steel fiber all through the blend. Besides, there are sure physical and functional lacks built into steel fiber that diminish its viability. Such lacks incorporate, for instance, bounce back in air-set substantial applications, and generally high hardware costs because of gear wear from contact with the steel filaments.

In this current work M20 grade of cement is chosen for the extents of 1:1.96:2.63 and water concrete proportion of 0.45 and different examinations are directed to notice the reactions. Notwithstanding broad fixings steel and glass filaments are added of rates 0, 0.5,1,2 and 3.

The ends are drawn from the experimental outcomes • In compressive strength, flexural strength and split elasticity, the expansion of Steel fiber the strength is expanding directly, yet in glass fiber up to 1% it is expanding and from 2% it is diminishing. • It is presumed that the strength is expanding while at the same time expanding the level of steel fiber. Be that as it may, on account of glass filaments, the strength is expanding up to 1%. After 1% the strength is lessening. • Finally inferred that glass fiber can be amount to the 1%.

WE CLAIMS

1. Our Invention "Concrete Production by adding fibre as Reinforced Material" is a Concrete is one of the most broadly perceived advancement material generally conveyed by using locally available fixings. The current pattern in substantial innovation is towards expanding the strength and sturdiness of cement to fulfill the needs of the cutting edge development. The primary point of the review is to concentrate on the impact of glass fiber and steel strands in the substantial. FRC has the high elasticity and heat proof properties in this way decreasing the deficiency of harm during fire mishaps. In the current work the strength studies are done to analyze the glass and steel fiber concrete. The FRC is added 0.5, 1, 2 and 3% are added for M20 grade concrete. Result shows the rate expansion in compressive strength, flexural strength and split rigidity for 28days. The current development gives a manufactured fiber mix and techniques for its utilization containing a first fiber part framed of a homopolymeric polypropylene fiber and a second fiber part being a copolymer shaped of a polypropylene and a high thickness polyethylene. The principal fiber part is fibrillated and the second fiber part is a wound group included various strands of a no fibrillating monofilament. The manufactured fiber mix grants further developed support properties to the structure materials to which they are added. Specifically, the manufactured fiber mix when integrated into a structure material gives decreased penetrability, expanded weariness strength, further developed durability, and diminished plastic shrinkage. The one of a kind mix of the bent second fiber part mixed with the primary fiber part gives further developed blend capacity and uniform dissemination of the manufactured fiber mix in cementitious materials.
2. According to clime 1# the Invention is a "Concrete Production by adding fibre as Reinforced Material" is a Concrete is one of the most broadly perceived advancement material generally conveyed by using locally available fixings.
3. According to claim 1# the Invention is a current pattern in substantial innovation is towards expanding the strength and sturdiness of cement to fulfill the needs of the cutting edge development. The primary point of the review is to concentrate on the impact of glass fiber and steel strands in the substantial.
4. According to claim 1,2# the Invention is a FRC has the high elasticity and heat proof properties in this way decreasing the deficiency of harm during fire mishaps. In the current work the strength studies are done to analyze the glass and steel fiber concrete. The FRC is added 0.5, 1, 2 and 3% are added for M20 grade concrete.

5. According to claim 1,3,4# the Invention is a the rate expansion in compressive strength, flexural strength and split rigidity for 28days. The current development gives a manufactured fiber mix and techniques for its utilization containing a first fiber part framed of a homopolymeric polypropylene fiber and a second fiber part being a copolymer shaped of a polypropylene and a high thickness polyethylene.
6. According to claim 1,2,5# the Invention is a principal fiber part is fibrillated and the second fiber part is a wound group included various strands of a no fibrillating monofilament. The manufactured fiber mix grants further developed support properties to the structure materials to which they are added.
7. According to claim 1,3,5,6# the Invention is a manufactured fiber mix when integrated into a structure material gives decreased penetrability, expanded weariness strength, further developed durability, and diminished plastic shrinkage.
8. According to claim 1,3,5,6,7# the Invention is a kind mix of the bent second fiber part mixed with the primary fiber part gives further developed blend capacity and uniform dissemination of the manufactured fiber mix in cementitious materials.

Dated this 24th day of August, 2022

S.B.Patil college of Engineering

Prof. R.B. Ghogare

Prof.M.V.Gaikwad

Prof.P.R.Admile

Prof. S. M. Baral

Prof. M. B. Katkar

Prof. S .M. Kale

Prof. S. V. Bankar

Prof.V.S.Bere

Prof.A.B.Rupnawar