



US010285688B2

(12) **United States Patent**
Hess et al.

(10) **Patent No.:** **US 10,285,688 B2**
(45) **Date of Patent:** **May 14, 2019**

(54) **SURGICAL ACCESS DEVICES THAT INCLUDE AN ELONGATE OPENING WITH AN ADJUSTABLE ENTRY PORT DISPOSED IN THE OPENING**

(58) **Field of Classification Search**
CPC A61B 17/0057; A61B 17/0482; A61B 17/0469; A61B 17/34; A61B 2017/00637;
(Continued)

(71) Applicant: **Ethicon Endo-Surgery, LLC**,
Guaynabo, PR (US)

(56) **References Cited**

(72) Inventors: **Christopher J. Hess**, Blue Ash, OH (US); **Frederick E. Shelton, IV**, Hillsboro, OH (US); **Jerome R. Morgan**, Cincinnati, OH (US); **Ryan A. Bledsoe**, Cincinnati, OH (US); **Douglas E. Withers**, Cincinnati, OH (US); **Craig T. Gates**, West Chester, OH (US)

U.S. PATENT DOCUMENTS

5,391,182 A 2/1995 Chin
5,476,470 A 12/1995 Fitzgibbons, Jr.
(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion dated Jun. 19, 2017 for Application No. PCT/US2017/024691, 17 pgs.

(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 100 days.

Primary Examiner — Lynnsy M Summitt

(74) *Attorney, Agent, or Firm* — Frost Brown Todd LLC

(21) Appl. No.: **15/274,209**

(57) **ABSTRACT**

(22) Filed: **Sep. 23, 2016**

(65) **Prior Publication Data**

US 2017/0281229 A1 Oct. 5, 2017

Related U.S. Application Data

(63) Continuation of application No. 15/088,723, filed on Apr. 1, 2016.

(51) **Int. Cl.**

A61B 17/04 (2006.01)

A61B 17/02 (2006.01)

(Continued)


(52) **U.S. Cl.**

CPC **A61B 17/0469** (2013.01); **A61B 17/0057** (2013.01); **A61B 17/0218** (2013.01);

(Continued)

Surgical access devices having wound closure features incorporated as part of the device are provided. The devices allow suture to be inserted directly into the device and operated to close an opening through which the device is disposed as or shortly after the device is removed from the surgical site. Further, the wound closure features allow for various orientations of wound closure to be achieved by adjusting an angle at which the suture enters tissue surrounding the opening to be closed. Some of the wound closure features provided for include openings formed in both the housing and cannula of the surgical access device, multiple openings formed in one or both the housing and cannula, locations of the openings being adjustable or otherwise movable, and various flexible seals. Other features, as well as methods of closing an opening through which the surgical access device was disposed, are also provided.

35 Claims, 23 Drawing Sheets



(51)	Int. Cl. <i>A61B 17/34</i> <i>A61B 17/00</i> <i>A61M 39/04</i>	(2006.01) (2006.01) (2006.01)	8,915,932 B2	12/2014	Pipenhagen et al.
			8,926,639 B2	1/2015	Bagaoisan et al.
			8,979,747 B2	3/2015	Auerbach et al.
			8,992,549 B2	3/2015	Bennett, III
(52)	U.S. Cl. CPC <i>A61B 17/0482</i> (2013.01); <i>A61B 17/3417</i> (2013.01); <i>A61B 17/3421</i> (2013.01); <i>A61B</i> <i>17/3423</i> (2013.01); <i>A61B 17/3439</i> (2013.01); <i>A61B 17/3462</i> (2013.01); <i>A61M 39/04</i> (2013.01); <i>A61B 2017/00637</i> (2013.01); <i>A61B</i> <i>2017/00663</i> (2013.01); <i>A61B 2017/0225</i> (2013.01); <i>A61B 2017/3441</i> (2013.01); <i>A61B</i> <i>2017/3445</i> (2013.01); <i>A61B 2017/3464</i> (2013.01)		9,011,319 B2	4/2015	Norton et al.
			9,033,872 B2	5/2015	Mohajer-Shojaee
			9,066,717 B2	6/2015	Sherts et al.
			9,149,272 B2	10/2015	Sherts et al.
			9,510,823 B2	12/2016	Malkowski
			9,636,104 B2	5/2017	Mohajer-Shojaee
			9,687,270 B2 *	6/2017	Gaiselmann A61B 17/3417
			9,700,303 B2 *	7/2017	Prior A61M 5/329
			2004/0068273 A1	4/2004	Fariss et al.
			2007/0203507 A1	8/2007	McLaughlin et al.
			2008/0033459 A1	2/2008	Shafi et al.
			2008/0097485 A1	4/2008	Shpaichler et al.
			2010/0228198 A1 *	9/2010	Widenhouse A61B 17/3423 604/167.01
			2011/0082475 A1 *	4/2011	Smith A61B 17/0057 606/144
			2011/0112557 A1 *	5/2011	Beeley A61B 17/0057 606/148
			2013/0035699 A1	2/2013	Heneveld et al.
			2013/0035700 A1	2/2013	Heneveld
			2013/0035701 A1	2/2013	Heneveld et al.
			2013/0035702 A1 *	2/2013	Heneveld A61B 17/0057 606/144
			2013/0103057 A1 *	4/2013	Keating A61B 17/0401 606/146
(56)	References Cited U.S. PATENT DOCUMENTS 5,507,755 A * 4/1996 Gresl A61B 17/0469 606/139 5,507,758 A 4/1996 Thomason et al. 5,562,688 A * 10/1996 Riza A61B 17/0469 606/139 5,716,369 A 2/1998 Riza 5,782,845 A 7/1998 Shewchuk 5,830,232 A 11/1998 Hasson 5,984,948 A 11/1999 Hasson 5,993,471 A 11/1999 Riza et al. 6,183,485 B1 2/2001 Thomason et al. 7,981,092 B2 7/2011 Duke 8,177,762 B2 5/2012 Beasley et al. 8,465,476 B2 6/2013 Rogers et al. 8,475,490 B2 7/2013 Hess 8,518,059 B2 8/2013 Ringley 8,545,522 B2 10/2013 Shpaichler et al. 8,568,362 B2 10/2013 Moreno, Jr. et al. 8,579,807 B2 11/2013 Moreno, Jr. et al. 8,622,970 B2 1/2014 Wingardner, III et al. 8,623,028 B2 1/2014 Rogers et al. 8,636,686 B2 1/2014 Minnelli et al. 8,690,831 B2 4/2014 Duke 8,906,042 B2 12/2014 Hodgkinson et al.		2015/0035702 A1 *	2/2013	Heneveld A61B 17/0057 606/144
			2013/0103057 A1 *	4/2013	Keating A61B 17/0401 606/146
			2013/0253543 A1	9/2013	Heneveld
			2015/0038793 A1	2/2015	Prior et al.
			2015/0038994 A1 *	2/2015	Prior A61M 5/329 606/147
			2015/0038997 A1	2/2015	Malkowski et al.
			2015/0094741 A1	4/2015	Hodgkinson et al.
			2015/0119906 A1	4/2015	Bagaoisan et al.
			2015/0238184 A1 *	8/2015	Mohajer-Shojaee A61B 17/0057 600/204
			2016/0045224 A1	2/2016	Hendershot, III
			2017/0258466 A1	9/2017	Prior et al.
			OTHER PUBLICATIONS		
			U.S. Appl. No. 15/088,723.		
			U.S. Appl. No. 15/274,182.		
			U.S. Appl. No. 15/274,198.		
			U.S. Appl. No. 15/274,237.		
			European Search Report and Written Opinion dated Aug. 23, 2017 for Application No. EP 17164122.8, 7 pgs.		
			* cited by examiner		

FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 4E




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 5E




FIG. 6




FIG. 7




FIG. 8




FIG. 9





FIG. 10









FIG. 13






FIG. 15A




FIG. 15B




FIG. 16




FIG. 17




FIG. 18A




FIG. 18B




FIG. 19A




FIG. 19B




FIG. 20A




FIG. 20B




FIG. 21




FIG. 22A




FIG. 22B




FIG. 22C




FIG. 23




FIG. 24





FIG. 25



1

**SURGICAL ACCESS DEVICES THAT
INCLUDE AN ELONGATE OPENING WITH
AN ADJUSTABLE ENTRY PORT DISPOSED
IN THE OPENING**

**CROSS REFERENCE TO RELATED
APPLICATIONS**

The present application claims priority to and is a continuation of U.S. patent application Ser. No. 15/088,723 filed on Apr. 1, 2016, published as U.S. Pub. No. 2017/0281154 on Oct. 5, 2017, and entitled "Surgical Access Devices with Integrated Wound Closure Features," which is hereby incorporated by reference in its entirety.

FIELD

The present disclosure relates to surgical access devices, and more particularly provides for features incorporated into surgical access devices that assist in closing an opening in which the surgical access device is disposed while or shortly after the surgical access device is removed from the surgical site. The disclosure also pertains to methods related to the same.

BACKGROUND

Surgical procedures often require a surgeon to gain access to a cavity in a patient's body. Generally, when such a procedure is required, an incision is made in an exterior wall of the cavity and an instrument is inserted into the working channel created by the incision. One common instrument used in such a procedure is a trocar assembly. Trocar assemblies include a variety of components, but generally can include a trocar cannula, a trocar obturator, and a trocar housing. In many designs, in order to access the body cavity, the trocar cannula is directed through the skin and the trocar obturator is inserted through an interior lumen defined by the cannula. The trocar obturator is then used to penetrate the skin, which has often already had an incision made in it with a scalpel or similar device, and access the body cavity. More specifically, in some designs, applying pressure against a proximal end of the trocar obturator allows a sharp point at a distal end of the trocar obturator to be forced through the skin until it enters the body cavity. Then, the trocar cannula is inserted through the perforation made by the trocar obturator and the trocar obturator is withdrawn, leaving the inner lumen of the trocar cannula as a path to access the body cavity from outside of the body.

The trocar housing can be joined to a proximal end portion of the trocar cannula, and further, the housing can define a working chamber with an open distal end portion that is in communication with the interior lumen of the cannula. Just as the interior lumen can receive the obturator, it can also receive other elongated surgical instruments such that the instruments can be axially extended into and withdrawn from the cannula through the proximal end portion of the working chamber defined by the trocar housing. For example, in order to allow a surgeon to more easily see during a procedure, an endoscope can be inserted through the cannula and proximal or into the body cavity. Further, it is common for one or more seals to be disposed within the housing and/or the cannula to help prevent fluid or gas from escaping during surgical procedures. Such prevention is needed, especially during certain minimally invasive surgical procedures, in which an insufflation gas is used to expand a body cavity. In many instances, at least two seals

2

are used to help maintain a seal while instruments are passed into and out of the working channel.

Once a procedure is completed, the trocar is removed and the opening (sometimes referred to herein as a wound) that was formed through which the trocar is inserted is typically closed. The size of the opening will depend on the size of the trocar. Some common trocar sizes include trocars identified as 5 millimeter trocars, 8 millimeter trocars, 12 millimeter trocars, and 15 millimeter trocars, with the size correlating approximately to the inner diameter of the cannula. At least for openings that are 8 millimeters wide or larger, suture is typically used to close the opening to prevent herniations after surgery. The stitching of the opening is typically done after the trocar is removed, or at least a housing portion of the trocar, and thus the ability to insufflate at that point is lost. The stitching up process typically involves using additional tools and performing several extra steps after the primary surgical method has already been completed. This leads to increased difficulty in closing the opening, an increased amount of time to perform the surgery, and a greater likelihood for unnecessary trauma to the tissue surrounding the opening. It can be particularly tough to stitch the opening when the cavity wall in which the opening is formed is thick, e.g., approximately equal to or greater than three-quarters of an inch, as is often the case for abdominal walls.

Accordingly, there is a need to reduce or eliminate the need for extra tools to be used to close an opening through which a trocar is passed during a surgical procedure, and to reduce the amount of steps required to close the opening. The solution should provide for a more convenient and easier way for surgeons to close the opening and reduce possible trauma to the surround tissue and the patient generally.

SUMMARY

Surgical access devices that incorporate wound closure features (or opening closure features) to allow an opening through which the surgical access device is passed to be closed while or shortly after the surgical access device is withdrawn from the opening are provided for in the present disclosure. Various configurations provide for sealed openings associated with a housing or proximal end of a surgical access device, as well as sealed openings associated with a cannula of the surgical access device. There can be multiple openings associated with each of the housing and the cannula, which thus make the wound closure feature adjustable. By passing a suture through different openings, the angle at which a suture passes through tissue can be changed. As this angle, referred to herein as a bite angle, is adjusted, it impacts the amount of tissue through which the suture passes and provides for various configurations to close the opening. The adjustability of the bite angle can be further enhanced by providing for openings that are movable or are otherwise adjustable as provided for in the present disclosure. For example, one or more of the openings can be rotated around a central longitudinal axis of the surgical access device, and/or the opening itself can provide for some adjustability by being flexible and/or by providing for an instrument-receiving opening that is smaller than the opening itself. When the instrument-receiving opening is smaller than the opening itself, the instrument-receiving opening can be moved with respect to the opening itself to adjust the angle at which an instrument disposed in the instrument-receiving opening passes through the opening. Still further, the present disclosure also provides for seals that include a

3

patterned guide surface conducive to both position and locate a surgical instrument passed therethrough to a desired position. The seals are also resistant to tearing, thereby preventing undesirable remnants of the seal from entering the body.

In one exemplary embodiment, a surgical access device includes a housing and a cannula extending distally from the housing. The housing has a central lumen extending through it and a sidewall disposed around the central lumen, while the cannula is in fluid communication with the central lumen to define a working channel that is sized and configured to receive a surgical instrument. The sidewall of the housing has at least one opening extending through it, with that opening having an opening seal associated with it, and the cannula has at least one sealed opening extending through a sidewall of the cannula. A seal is disposed within the working channel. The seal is configured to seal the working channel when no surgical instrument is disposed through the seal. The opening(s) extending through the sidewall of the housing and the sealed opening(s) extending through the sidewall of the cannula are configured to form a suture path(s). A suture path allows a suture to be passed from an outside environment, through the at least opening of the housing, through the at least one sealed opening of the cannula, and to a surgical site.

The at least one opening that extends through the housing sidewall and the at least one sealed opening that extends through the cannula sidewall can be configured such that an angle formed between a central longitudinal axis extending through the cannula and an axis extending between the at least one opening extending through the housing sidewall and the at least one sealed opening extending through the cannula sidewall is adjustable. A variety of different features that permit the adjustability of this angle, sometimes referred to as a bite angle, are provided for in the present disclosure. For example, the housing sidewall can include a plurality of openings that extend through the housing sidewall, with each opening having a seal associated with it. In such instances, the angle is adjustable at least by virtue of the axis extending between the openings of the housing sidewall and the cannula sidewall passing through different openings of the plurality of openings that extend through the housing sidewall. For instance, in a first position, the axis extending between the openings of the housing sidewall and the cannula sidewall can extend between a first opening of the plurality of openings extending through the housing sidewall and an opening of the at least one sealed opening extending through the cannula sidewall, and in a second position the same axis can extend between a second opening of the plurality of openings extending through the housing sidewall and the opening of the at least one sealed opening extending through the cannula sidewall.

By way of further example, adjustability of the bite angle can be provided for by the cannula sidewall including a plurality of sealed openings that extend through the cannula sidewall. In such instances, the angle is adjustable at least by virtue of the axis extending between the openings of the housing sidewall and the cannula sidewall passing through different sealed openings of the plurality of sealed openings that extend through the cannula sidewall. For instance, in a first position, the axis extending between the openings of the housing sidewall and the cannula sidewall can extend between an opening of the at least one opening extending through the housing sidewall and a first sealed opening of the plurality of sealed openings extending through the cannula sidewall, and in a second position the same axis can extend between the opening of the at least one opening

4

extending through the housing sidewall and a second sealed opening of the plurality of sealed openings extending through the cannula sidewall.

By way of still further example, adjustability of the bite angle can be provided for by one or more elongate openings. The at least one opening extending through the housing sidewall can include an elongate opening having an elongate length that extends substantially parallel to the central longitudinal axis. The elongate opening can further include an adjustable entry point that is movable along the elongate length to adjust the angle formed between the central longitudinal axis and the axis extending between the elongate opening and the at least one sealed opening of the cannula sidewall.

By way of yet another example, adjustability of the bite angle can be provided by a housing that includes a first rotary disc and a second rotary disc that are each configured to rotate about the central longitudinal axis extending through the cannula. Further, each disc can include one or more openings of the opening(s) that extend through the housing sidewall disposed on the respective discs, with the opening disposed on the first disc being referred to at least in this instance as a first opening and the opening disposed on the second disc being referred to at least in this instance as a second opening. The first and second openings can be movable, e.g., by rotating them about the central longitudinal axis, to adjust the angle formed between the central longitudinal axis extending through the cannula and the axis extending between the openings of the housing sidewall and the cannula sidewall.

In some embodiments that include the first and second rotary discs, the first and second openings can be configured to be moved to an alignment position in which the first and second openings are aligned to form an elongate opening having an elongate length that extends substantially parallel to the central longitudinal axis. The elongate opening can be configured to allow for multiple entry points of a surgical instrument to provide the adjustable angle formed between the central longitudinal axis and the axis extending between the openings of the housing sidewall and the cannula sidewall.

By way of another example, adjustability of the bite angle can be controlled by a rotary dial. The rotary dial can be configured to move the at least one opening extending through the housing sidewall. The movement of this opening adjusts the angle formed between the central longitudinal axis and the axis extending between the openings extending through the housing sidewall and the cannula sidewall.

The various embodiments described with respect to the adjustability of the bite angle can be combined. By way of non-limiting example, both the housing sidewall and the cannula sidewall can include multiple openings, any of which can be elongate openings that do or do not have adjustable entry points. By way of further non-limiting example, any number of openings formed in the sidewall of the housing can be formed on one or more rotary discs. By way of still a further non-limiting example, a rotary dial can be used to control components such as rotary discs and/or adjustable entry points of elongate openings, among other features. The angle formed by the central longitudinal axis and the axis extending between the openings of the housing sidewall and the cannula sidewall in any of the provided for embodiments can be adjusted between values approximately in the range of about 15 degrees to about 60 degrees. The angle formed allows different wall thicknesses to be passed through. Accordingly, in view of the present disclosures, a range of wall thicknesses through which an instrument

5

and/or a suture can be passed in view of the provided for surgical access devices is approximately in the range of about 1 centimeter to about 5 centimeters.

In some embodiments, the at least one sealed opening of the cannula sidewall can include a seal having a patterned guide surface that faces towards the working channel. The patterned guide surface can be configured to direct a surgical instrument through one or more pre-defined resealable openings of the seal. The patterned guide surface can include a slidable, floating instrument that allows an angle formed between a central longitudinal axis extending through the cannula and an axis extending between the at least one opening of the housing sidewall and the at least one sealed opening of the cannula sidewall to be adjustable.

A proximal portion of the cannula can have a portion of its sidewall that is thinner than surrounding portions of the cannula sidewall. Further, the thinner portion can have at least one sealed opening that extends through the cannula sidewall. In such embodiments, a sealing sleeve that is sized to be disposed over the thinner portion can be included. The sealing sleeve can be sized such that an outer diameter of the combination of the thinner portion of the sidewall and the sealing sleeve is substantially similar to an outer diameter of the surrounding portions of the cannula sidewall. The sealing sleeve can then provide the sealable nature of the at least one sealed opening of the surgical access device.

In another exemplary embodiment, a surgical access device includes a housing, a cannula extending distally from the housing, a seal, at least one entry port, and at least one sealed exit port. The housing and the cannula define a working channel that extends through the two components, with the working channel being sized and configured to receive a surgical instrument. The seal is disposed within the working channel, and is configured to seal the working channel when no instrument is disposed in it. The at least one entry port is disposed in or proximate to the housing, and has a seal associated with the entry port. The at least one sealed exit port extends through a sidewall of the cannula. Further, the entry and exit ports are configured such that an angle formed between a central longitudinal axis that extends through the cannula and an axis that extends between the ports, i.e., the bite angle, is adjustable.

The angle formed between the central longitudinal axis and the axis that extends between the ports can be adjustable approximately between the values of about 15 degrees to about 60 degrees. The angle formed allows different wall thicknesses to be passed through. Accordingly, in view of the present disclosures, a range of wall thicknesses through which an instrument and/or a suture can be passed in view of the provided for surgical access devices is approximately in the range of about 1 centimeter to about 5 centimeters. In some embodiments, the at least one entry port can include a plurality of entry ports disposed in or proximate to the housing, with each opening having a seal associated with it. In such instances, the angle is adjustable at least by virtue of the axis extending between the entry and exit ports passing through different entry ports of the plurality of entry ports. For instance, in a first position, the axis extending between the entry and exit ports can extend between a first entry port of the plurality of entry ports and an exit port of the at least one sealed exit port, and in a second position the same axis can extend between a second entry port of the plurality of entry ports and the exit port of the at least one sealed exit port.

In some embodiments, the at least one sealed exit port can include a plurality of sealed exit ports that extend through the sidewall of the cannula. In such instances, the angle is

6

adjustable at least by virtue of the axis extending between the entry and exit ports passing through different sealed exit ports of the plurality of sealed exits ports. For instance, in a first position, the axis extending between the entry and exit ports can extend between an entry port of the at least one entry port and a first sealed exit port of the plurality of sealed exit ports, and in a second position the same axis can extend between the entry port of the at least one sealed entry port and a second sealed exit port of the plurality of sealed exit ports.

The at least one entry port can include an elongate opening having an elongate length that extends substantially parallel to the central longitudinal axis. The elongate opening can further include an adjustable entry point that is movable along the elongate length to adjust the angle formed between the central longitudinal axis and the axis extending between the elongate opening and the at least one sealed exit port.

The housing can sometimes include both a first rotary disc and a second rotary disc, with each disc being configured to rotate about the central longitudinal axis that extends through the cannula. The first rotary disc can have disposed on it a first entry port of the at least one entry port that is disposed in or proximate to the housing, and the second rotary disc can likewise have disposed on it a second entry port of the at least one entry port that is disposed in or proximate to the housing. The first and second entry ports can be movable to adjust the angle formed between the central longitudinal axis and the axis extending between the entry and exit ports.

In some embodiments that include the first and second rotary discs, the first and second entry ports can be moved to an alignment position in which the first and second entry ports are aligned to form an elongate opening having an elongate length that extends substantially parallel to the central longitudinal axis. The elongate opening can be configured to allow for multiple entry points of a surgical instrument to provide the adjustable angle formed between the central longitudinal axis and the axis extending between the entry and exit ports.

In some embodiments, a rotary dial can be included to assist in adjusting the bite angle. The rotary dial can be configured to move the at least one entry port. The movement of the entry port adjusts the angle formed between the central longitudinal axis and the axis extending between the entry and exit ports.

Again, the various embodiments described with respect to different ways by which the bite angle can be adjusted can be combined. By way of non-limiting example, there can be multiple entry ports and exit ports, any of which can include elongate openings that do or do not have adjustable entry points. By way of further non-limiting example, any number of entry ports can be formed on one or more rotary discs. By way of still a further non-limiting example, a rotary dial can be used to control components such as rotary discs and/or adjustable entry points of elongate openings, among other features.

In some embodiments, the at least one sealed exit port can include a seal having a patterned guide surface that faces towards the working channel. The patterned guide surface can be configured to direct a surgical instrument through one or more pre-defined resealable openings of the seal. The patterned guide surface can include a slidable, floating instrument entrance that allows an angle formed between the central longitudinal axis and the axis extending between the entry and exit ports to be adjustable.

A proximal portion of the cannula can have a portion of its sidewall that is thinner than surrounding portions of the cannula sidewall. Further, the thinner portion can have at least one sealed exit port that extends through the cannula sidewall. In such embodiments, a sealing sleeve that is sized to be disposed over the thinner portion can be included. The sealing sleeve can be sized such that an outer diameter of the combination of the thinner portion of the sidewall and the sealing sleeve is substantially similar to the outer diameter of the surrounding portions of the cannula sidewall. The sealing sleeve can then provide the sealable nature of the at least one sealed exit port of the surgical access device.

An exemplary embodiment of a surgical method includes passing a first filament tail through a first opening extending through a sidewall of a housing of a surgical access device, through a first opening extending through a sidewall of a cannula that extends distally from the housing, and through tissue adjacent to an opening in tissue. The method further includes passing a second filament tail through a second opening extending through the sidewall of the housing of the surgical access device, through a second opening extending through the sidewall of the cannula, and through tissue adjacent to the opening in the tissue. Tension is applied to at least one of the first and second filament tails, which in turn decreases a size of the opening in the tissue.

In some embodiments, the steps of passing the first and second filament tails through first and second openings extending through the housing sidewall, respectively, can include selecting one opening of a plurality of openings that extend through the housing sidewall and are proximate to each other to be the respective first or second opening based on the desired angle at which the respective first or second filament tail is to be passed through the tissue. Likewise, in some embodiments, the steps of passing the first and second filament tails through first and second openings extending through the cannula sidewall, respectively, can include selecting one opening of a plurality of openings that extend through the cannula sidewall to be the respective first or second opening based on the desired angle at which the respective first or second filament tail is to be passed through the tissue.

The at least one of the first and second openings that extend through the housing sidewall can include an elongate opening having an elongate length that extends substantially parallel to a central longitudinal axis that extends through the cannula. The elongate opening can further include an adjustable entry point that is movable along the elongate length. In such embodiments, the method can include moving the adjustable entry point longitudinally to adjust an angle at which the respective first or second filament tail is directed to enter the tissue. Further, the surgical method can include moving at least one of the first and second openings that extend through the housing sidewall to adjust an angle at which the respective first or second filament tail is directed to enter the tissue.

In one exemplary embodiment, a surgical access device that includes a first suture path extending across a working channel of the surgical access device such that one entrance of the first suture path is associated with a housing of the surgical access device and the other entrance of the first suture path is associated with a cannula that extends distally from the housing, the other entrance being located approximately on an opposed side of the device in comparison to the entrance associated with the housing. The device further includes a second suture path extending across the working channel of the surgical access device such that one entrance of the second suture path is associated with a housing of the

surgical access device at a location that is approximately opposed to the entrance of the housing associated with the first suture path, and the other entrance of the second suture path being associated with the cannula at a location that is approximately opposed to the entrance of the cannula associated with the first suture path. The first and second suture paths are configured to allow an angle formed by a central axis extending through at least one of the paths and a central longitudinal axis of the surgical access device is adjustable. As a result, an angle at which a suture insertion or implant instrument that extends through the path, and thus a suture associated with such an instrument, can be adjusted to better configure the instrument and/or suture to pass through a particular thickness of tissue that is disposed adjacent to the surgical device.

The present disclosure provides a wide variety of ways by which the aforementioned angle can be adjusted with respect to one or both paths. Some non-limiting examples of such features include: multiple openings being formed in one or both of the housing and the cannula, one or more rotary discs having one or more openings of the housing formed in the disc(s); one or more elongate seals; rotary dials to control, by way of non-limiting example, an adjustable entry point that moves along an elongate length of the elongate seal(s); a slidable, floating instrument entrance that is included as part of a seal disposed within the opening(s) of the cannula to permit bite angle adjustment; a seal having a patterned guide surface that faces towards a working channel of the device and is configured to direct a surgical instrument through one or more pre-defined resealable openings of the seal; a sealing sleeve; and, in embodiments that include a sealing sleeve, a portion of the cannula having a thinner portion so that a diameter formed by the cannula and sealing sleeve is substantially similar to an outer diameter of the remainder of the cannula. A person skilled in the art, in view of the present disclosure, will understand how such features can be selectively combined and/or used independent of all other features to adjust a bite angle without departing from the spirit of the present disclosure. Further, in some embodiments, a seal (e.g., a duckbill seal) can be disposed within the working channel and can be configured to seal the working channel when no surgical instrument is disposed in the working channel. Further, the angle that is being adjusted can be adjusted between values of about 15 degrees to about 60 degrees.

In another exemplary embodiment, a surgical access device includes a housing having a central lumen that extends through it and a cannula that extends distally from the housing and is in fluid communication with the central lumen to define a working channel that is sized and configured to receive a surgical instrument. The housing further includes a sidewall disposed around the central lumen. A suture path is formed between a suture insertion entrance associated with the housing and a suture insertion exit associated with the cannula. An angle at which the path extends with respect to a central longitudinal axis extending through the cannula is selectably adjustable. More particularly, the device includes a suture path adjusting element that is configured to control the angle at which the path extends with respect to the central longitudinal axis. As a result, a user can adjust the aforementioned angle, which in turn allows a user to change the angle at which a suture disposed through the suture path enter tissue disposed proximate to the cannula.

The suture path adjusting element can have a variety of configurations based on the present disclosures. By way of two non-limiting examples, the suture path adjusting ele-

ment can be a rotary dial that controls an adjustable entry port that is a suture insertion entrance disposed within an elongate opening associated with the housing, and/or one or more rotary discs of the housing having one or more openings that serve as suture insertion entrances that can be rotated to adjust the angle. In some embodiments, a second suture path can be provided. The second suture path can be controlled by the suture path adjusting element such that both paths are adjusted at the same time, or it can be independently adjustable, for instance by a second suture path adjusting element. In other embodiments the suture path adjusting element can be configured to control both suture paths independently of each other. The angle that is being adjusted can be adjusted between values of about 15 degrees to about 60 degrees.

Other features that can be incorporated in the embodiment focused on selectably adjustable suture path(s) include a slidable, floating instrument entrance that is included as part of a seal disposed within the opening(s) of the cannula to permit bite angle adjustment; a seal having a patterned guide surface that faces towards a working channel of the device and is configured to direct a surgical instrument through one or more pre-defined resealable openings of the seal; a sealing sleeve; and, in embodiments that include a sealing sleeve, a portion of the cannula having a thinner portion so that a diameter formed by the cannula and sealing sleeve is substantially similar to an outer diameter of the remainder of the cannula. A person skilled in the art, in view of the present disclosure, will understand how such features can be selectively combined and/or used independent of all other features without departing from the spirit of the present disclosure. Further, in some embodiments, a seal (e.g., a duckbill seal) can be disposed within the working channel and can be configured to seal the working channel when no surgical instrument is disposed in the working channel.

In still another exemplary embodiment, a surgical access device includes a cannula configured to be disposed in an opening in tissue, the cannula having an inner lumen extending therethrough to provide for a working channel of the surgical access device. The cannula includes a sidewall extending radially around a central longitudinal axis of the device, which can help define the inner lumen. One or more openings are formed in the sidewall such that the opening forms a passageway between the inner lumen and an outside environment. Each such opening can include a seal disposed therein. The seal can include a patterned guide surface that faces towards the inner lumen, and can be configured to direct a surgical instrument through one or more pre-defined resealable openings of the seal. The pre-defined resealable openings can also be referred to as a pre-defined rupture location. Such openings or locations can minimize or eliminate tear remnants that may result from passing an instrument through the seal, and can reduce an amount of load to be applied to an instrument being inserted through the seal to pass the instrument through the seal.

In some embodiments, the surgical access device can include some or all of the other components provided for herein, including but not limited one or more of the following features: a housing from which the cannula can extend distally, with the housing having a central lumen that extends through the housing such that the central lumen is in fluid communication with the inner lumen of the cannula to define the working channel; a seal disposed within the working channel of the surgical access device that is configured to seal the working channel when no surgical instrument is disposed through the seal; one or more openings formed in a sidewall of the housing, which in turn can define

a suture path between opening(s) in the housing and opening(s) in the cannula; and one or more features configured to allow a bite angle to be adjusted. Some non-limiting examples of features configured to allow a bite angle to be adjusted are multiple openings being formed in one or both of the housing and the cannula, one or more rotary discs having one or more openings of the housing formed in the disc(s); one or more elongate seals; rotary dials to control, by way of non-limiting example, an adjustable entry point that moves along an elongate length of the elongate seal(s); a slidable, floating instrument entrance that is included as part of the patterned guide surface of the seal to permit bite angle adjustment; and a sealing sleeve that includes the patterned guide surface to help form the sealed opening of the cannula, and in some instances, a portion of the cannula has a thinner portion so that a diameter formed by the cannula and sealing sleeve is substantially similar to an outer diameter of the remainder of the cannula. A person skilled in the art, in view of the present disclosure, will understand how such features can be selectively combined and/or used independent of all other features to adjust a bite angle without departing from the spirit of the present disclosure.

BRIEF DESCRIPTION OF DRAWINGS

This disclosure will be more fully understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

FIGS. 1A-1D are schematic illustrations of an opening formed in tissue;

FIG. 2A is a front view of one exemplary embodiment of a surgical access device;

FIG. 2B is a perspective view of the surgical access device of FIG. 2A;

FIG. 2C is a perspective cross-sectional view of the surgical access device of FIG. 2B taken along line C-C;

FIG. 2D is a perspective, partially transparent view of the surgical access device of FIG. 2B, with a portion of the housing removed;

FIG. 3 is a perspective view of one exemplary embodiment of a suture implant device having a suture associated therewith;

FIG. 4A is a perspective, partially transparent view of the surgical access device of FIG. 2A having the suture implant device and suture of FIG. 3 disposed therethrough;

FIG. 4B is a front view of the surgical access device of FIG. 4A with the suture implant device removed from the surgical access device;

FIG. 4C is a front view of the surgical access device of FIG. 4B with a second suture disposed therethrough;

FIG. 4D is a front view of the surgical access device of FIG. 4C having the first and second sutures coupled together to form a loop;

FIG. 4E is a front view of the surgical access device of FIG. 4D illustrating the loop being collapsed;

FIG. 5A is a perspective view of another exemplary embodiment of a surgical access device and a portion of another exemplary embodiment of a suture implant device;

FIG. 5B is a detailed perspective view of the surgical access device and a portion of the suture implant device of FIG. 5A;

FIG. 5C is a perspective view of the surgical access device and the entire suture implant device of FIG. 5A with the suture implant device being disposed through the surgical access device;

FIG. 5D is a perspective view of the surgical access device and suture implant device of FIG. 5C with the suture

11

implant device being removed from the surgical access device and located adjacent to an opposite side of the surgical access device;

FIG. 5E is a perspective view of the surgical access device and suture implant device of FIG. 5D with the suture implant device disposed through the surgical access device;

FIG. 6 is a perspective view of yet another exemplary embodiment of a surgical access device, the device having multiple ports associated with each of a housing and a cannula of the surgical access device;

FIG. 7 is a perspective view of another exemplary embodiment of a surgical access device having multiple ports associated with each of a housing and a cannula of the device, as well as a portion of a suture implant device disposed through the surgical access device;

FIG. 8 is a perspective view of still another exemplary embodiment of a surgical access device, the device including multiple elongate ports associated with each of a housing and a cannula of the device, and at least one of the elongate ports of the housing including an adjustable entry point that is controllable with a rotary dial;

FIG. 9 is a perspective view of the rotary dial of FIG. 8, the rotary dial having multiple suture implant devices disposed therethrough;

FIG. 10 is a perspective cross-sectional view of the surgical access device of FIG. 8 taken along line D-D, the surgical access device having the suture implant devices of FIG. 9 disposed therethrough;

FIG. 11 is a front view of the surgical access device of FIG. 8 illustrating a suture implant device in two different locations;

FIGS. 12A and 12B are schematic illustrations of the suture implant device of FIG. 11 disposed at the two different locations, respectively;

FIG. 13 is a perspective view of another exemplary embodiment of a surgical access device having multiple ports associated with each of a housing and a cannula of the device, as well as a portion of a suture implant device disposed therethrough;

FIG. 14 is a front view of the surgical access device of FIG. 13 illustrating the suture implant device of FIG. 13 in two different locations;

FIGS. 15A and 15B are schematic illustrations of the suture implant device of FIG. 14 disposed at the two different locations, respectively;

FIG. 16 is a perspective view of yet another exemplary embodiment of a surgical access device having multiple ports associated with each of a housing and a cannula of the device, as well as a portion of a suture implant device disposed therethrough;

FIG. 17 is a perspective view of another exemplary embodiment of a surgical access device, the device including multiple elongate ports associated with a cannula of the device;

FIG. 18A is front view of a seal associated with the elongate ports of FIG. 17;

FIG. 18B is a side view of the seal of FIG. 18A;

FIG. 19A is front view of one exemplary embodiment of a seal that can be used in conjunction with the elongate ports of FIG. 17;

FIG. 19B is a side view of the seal of FIG. 19A;

FIG. 20A is front view of another exemplary embodiment of a seal that can be used in conjunction with the elongate ports of FIG. 17;

FIG. 20B is a side view of the seal of FIG. 20A;

FIG. 21 is a front view of still another exemplary embodiment of a surgical access device, the device including a

12

slidable, floating seal associated with a cannula of the device and having a suture implant device disposed therein in two different locations;

FIG. 22A is a schematic side view of the slidable, floating seal and the suture implant device of FIG. 21, the suture implant device being disposed in a resting position;

FIG. 22B is a schematic side view of the slidable, floating seal and the suture implant device of FIG. 22A, the suture implant device being disposed in a first position;

FIG. 22C is a schematic side view of the slidable, floating seal and the suture implant device of FIG. 22A, the suture implant device being disposed in a second position;

FIG. 23 is a side view of another exemplary embodiment of a surgical access device, the device including a sleeve that is used to provide a seal associated with a cannula of the device;

FIG. 24 is a perspective view of the surgical access device of FIG. 23, the device having the sleeve removed from the cannula to expose an opening formed in the cannula; and

FIG. 25 is a perspective view of the sleeve of FIG. 23.

DETAILED DESCRIPTION

Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those skilled in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the present disclosure is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present disclosure. Further, in the present disclosure, like-number components of the various embodiments generally have similar features when those components are of a similar nature and/or a similar purpose. Additionally, to the extent features, sides, directions, steps, etc. are described herein as being a "first feature" or "first direction" or a "second feature" or "second direction," such numerical ordering is generally arbitrary, and thus such numbering can be interchangeable.

The terms "proximal" and "distal" are used herein with reference to a location of a clinician with respect to a surgical site, with the term "proximal" referring to the portion closest to the clinician and the term "distal" referring to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as "vertical," "horizontal," "up," and "down" may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute. Further, in some instances, components are referred to interchangeably with and without the term "assembly," e.g., a trocar and a trocar assembly. There is no particular intention for the terms to refer to different components. Likewise, terms such as "instrument" and "device" may be used interchangeably.

The present disclosure generally provides for a surgical access device or system that incorporates features to improve wound (or opening) closure capabilities directly into the device or system. More particularly, the surgical access devices and systems provided for are generally described as trocars having both a housing and a cannula,

13

with the cannula extending distally from the housing. One or more openings are associated with the housing such that an instrument, device, or suture passed through the opening also passes through the housing and into a working channel defined by the housing and the cannula. Likewise, one or more openings are associated with a sidewall of the cannula such that an instrument, device, or suture that passes through the one or more openings associated with the housing and into the working channel can be passed out of the working channel to an environment outside of the cannula via the one or more openings of the cannula sidewall. The passageway or path (sometimes referred to herein as a suture path) extending between the opening(s) associated with the housing and the opening(s) associated with the cannula can be sealed such that when no instrument, device, or suture is passed therethrough, fluid is prevented from passing between an environment outside of the surgical access device and the working channel. Suture passed through the surgical access device via the openings associated with the housing and the cannula can be passed into tissue that is proximate to the opening into which the surgical access device is disposed and subsequently cinched to close the opening while or after the surgical access device is removed from the opening.

The present disclosure also provides for a number of adjustable features that can be incorporated into the surgical access device to allow for suture that is disposed through the passageway to be passed into tissue at different angles as desired. These features include using multiple openings associated with either or both of the housing and the cannula, using components that can adjust a position of the openings with respect to a central longitudinal axis of the surgical access device, using elongate openings, rotary dials, and/or using flexible seals or sealing components, among other features. FIGS. 1A-1D provide some exemplary illustrations of potential desired stitching paths for a suture when closing an opening formed in tissue. Notably, although in each of the illustrated configurations of FIGS. 1A-1D the openings terminate and thus do not extend fully through tissue, such stitching patterns are equally applicable to openings that do extend fully through tissue, such as openings through which a trocar assembly is typically disposed.

FIG. 1A provides for one example of a potential desired stitching path for closing an opening 6 in tissue 8. As shown, there are two potential suture paths 1, 2 that extend proximally to distally from a first (as shown left) side E of a surgical access device (not shown) to a second (as shown right) side F of the surgical access device. A suture can be passed along one or both paths 1, 2. Further, one or both paths 1, 2 can be used in combination with two other paths 3, 4 also provided for that extend proximally to distally from the second side F to the first side E. As shown, the angles α_1 , α_2 , α_3 , α_4 at which the paths are positioned with respect to a central longitudinal axis A that extends through the opening 6 (and would extend through a surgical access device when disposed through an opening), referred to herein as a bite angle, is different for different paths. This is why the ability to adjust the bite angle when the surgical access device is still disposed in the opening is desirable. By being able to adjust the bite angle defined by the locations of the opening(s) associated with the housing and cannula of the surgical access device, the different paths illustrated can be followed by sutures while the device remains in the opening. Prior to the present disclosure, these varied angles would be created by removing the surgical access device and then passing the suture through tissue at the desired angles completely independent of the surgical access device. A

14

person skilled in the art will recognize that bite angles can be measured between any two sides of the paths and axes, and thus the illustrated configurations of the bite angles are by no means limiting to defining from where a bite angle is measured.

FIGS. 1B, 1C, and 1D likewise illustrated alternative path options for an opening formed in tissue. More particularly, FIG. 1B illustrates two paths 1', 2' that extend proximally to distally from a first (as shown left) side E' of a surgical access device (not shown) to a second (as shown right) side F' of the surgical access device, and two paths 3', 4' that extend from the second side F' to the first side E' to create bite angles α_1' , α_2' , α_3' , α_4' with respect to a central longitudinal axis A' that extends through an opening 6' in tissue 8', while FIG. 1C illustrates two paths 1'', 2'' that extend proximally to distally from a first (as shown left) side E'' of a surgical access device (not shown) to a second (as shown right) side F'' of the surgical access device, and one path 3'' that extends from the second side F'' to the first side E''. Further, FIG. 1D illustrates one path 1''' that extends from a first (as shown left) side E''' of a surgical access device (not shown) to a second (as shown right) side F''' of the surgical access device, and a single path 2''' that extends from the second side F''' to the first side E''' to create bite angles α_1'' , α_2'' , α_3'' , α_4'' with respect to a central longitudinal axis A'' that extends through an opening 6'' in tissue 8''. In the FIG. 1D embodiment, the two paths 1''', 2''' from a perfect perpendicular angle with respect to each other, and an approximately 45 degree bite angle α_1''' , α_2''' with respect to a central longitudinal axis A''' that extends through an opening 6''' in tissue 8'''. A person having skill in the art will recognize a myriad of paths that can be formed to close openings or wounds in tissue, and such paths are generally achievable in view of the disclosures provided for herein.

Trocar Assemblies

FIGS. 2A-2D illustrate one exemplary embodiment of a surgical access device, as shown a trocar or trocar assembly 100. The trocar 100 can generally include a trocar cannula 102 and a trocar housing (or handle) 104. A number of configurations are available for the housing 104. In the illustrated embodiment, the housing 104 has a generally cylindrical shape having a proximal removable cap portion 105 and a distal chamber portion 107, with the cap portion 105 being selectively attachable and detachable from the distal chamber portion 107. FIG. 2D illustrates an instance in which the proximal cap portion 105 has been detached from the distal chamber portion 107. The trocar housing 104 more generally is defined by a sidewall 108 that extends circumferentially around a central longitudinal axis L extending through the trocar assembly 100, and thus the trocar cannula 102. The housing 104 includes a central lumen 110 extending from an open proximal end portion 104p to a distal end portion 104d. The housing 104 can have a variety of components disposed therein, as described below. As shown the cap portion 105 selectively mates with distal chamber portion 107 by way of male mating members, as shown tabs 112 (FIG. 2C), on the cap portion 105 engaging complementary female mating members, as shown slots 114 (FIG. 2C), formed in the distal chamber portion 107. Further, the cap portion 105 also provides for female mating members, as shown slots 116, at its proximal end for receiving various components, such as an obturator (not shown).

The trocar cannula 102 extends distally from the housing 104, and is also generally defined by a sidewall 118 that extends circumferentially around the central longitudinal axis L. A diameter of the cannula 102 is generally smaller

15

than a diameter of the housing **104**. Further, the trocar cannula **102** can define an interior lumen **120** with an open proximal end portion **102p** and an open distal end portion **102d**. As shown by way of FIGS. **2A** and **2C**, the proximal end portion **102p** can extend into and be mounted in the distal end portion **104d** of the trocar housing **104**, thus defining a working channel **122** of the surgical access device **100** that extends from the proximal end portion **104p** to the open distal end portion **102d** of the cannula **102**. As a result, the housing **104** is in fluid communication with the interior lumen **120** of the trocar cannula **102**. Further, an insufflation port **124** can be associated with the housing **104**, as shown the distal chamber portion **107**, to control the flow of an insufflation fluid or gas, e.g., carbon dioxide, to a surgical site. More particularly, the insufflation port **124** can include a stop cock valve **126** and a cock valve lever **128**, which can work together to allow and/or prevent passage of an insufflation fluid or gas through flexible tubing into a portion of the trocar housing **104** and the trocar cannula **102**.

One or more seal assemblies can be at least partially positioned within the working channel. As shown in FIG. **2C**, a first, proximal seal assembly **130** and a second, distal seal assembly **132** are both disposed in the housing and are both positioned within the working channel **122**. The first, proximal seal assembly **130**, also referred to as an instrument seal, is provided for in the illustrated embodiment as part of the cap portion **105**. The instrument seal **130** can be adapted to cooperate with an exterior of any instrument inserted at least partially through the trocar cannula **102** such that it can sealingly engage the exterior of the instrument and thus can prevent the passage of fluids through the trocar housing **104** when the instrument is present within the trocar assembly **100**. All sorts of instruments, although primarily surgical instruments, can be inserted at least partially through the trocar cannula **102**. One example of such an instrument is an endoscope or a similar device that enables visualization during minimally invasive surgical procedures. One skilled in the art will recognize that many other instruments are known for insertion into at least a portion of the trocar cannula **102**, and accordingly, that the proximal seal assembly **130** can likewise sealingly engage the exterior of those instruments as well.

The second, distal seal assembly **132**, also referred to as a zero-closure or duckbill seal, is provided for in the illustrated embodiment as part of the chamber portion **107**. The duckbill seal **132** can be configured to form a seal in the working channel **122** when no instrument is disposed therethrough to thus prevent the leakage of insufflation gases delivered through the trocar housing **104** to the body cavity. As a result, the insufflation port **124** is configured to be in fluid communication with a portion of the working channel **122** that is disposed distal of the duckbill seal **132**. As shown, the duckbill seal **132** has a generally circular flange **134** with a sidewall **136** extending distally therefrom. The shape of the sidewall **136** can vary, but in the illustrated embodiment, the sidewall **136** includes opposed flaps **135** (only one is illustrated) that extend at an angle toward one another in a distal direction and that come together at a distal end to form a seal face **138**. The opposed flaps **135** are movable relative to one another to allow the seal face **138** to move between a closed position, in which no instrument is disposed therethrough and the seal face **138** seals the working channel **122** of the trocar assembly **100**, and an open position in which an instrument is disposed therethrough.

A person skilled in the art will recognize a variety of ways by which the seal assemblies **130**, **132** can be disposed in the housing **104**, as well as other locations at which one or more

16

of the sealing assemblies can be disposed, including within the cannula **102**. Further, a person skilled in the art will recognize that while in an exemplary embodiment two seal assemblies are provided in the working channel **122**, in other embodiments one seal assembly, or more than two seal assemblies, can also be used in the trocar assembly **100**. Still further, a person skilled in the art will recognize other components and features that can be included as part of a trocar assembly that can be included as part of the present trocar assembly **100**, or other trocar assemblies, without negatively impacting the adjustability features provided for herein.

The illustrated embodiment of the trocar assembly **100**, as well as other embodiments of trocar assemblies provided for herein, are exemplary, non-limiting embodiments of trocar assemblies with which the features related to wound closure can be used. A wide variety of trocar assemblies can be easily adapted in view of the present disclosures without departing from the spirit of the present disclosure. Some exemplary embodiments of trocar assemblies, and components thereof, are provided for in U.S. Pat. Nos. 7,981,092, 8,579,807, 8,568,362, 8,636,686, 8,690,831, U.S. Patent Application Publication No. 2015/0038793, and U.S. Patent Application Publication No. 2015/0038994, issued as U.S. Pat. No. 9,700,303 on Jul. 11, 2017, the content of each which is hereby incorporated by reference in its entirety. Further, a person having skill in the art will recognize typical materials used to form the various components of a trocar assembly, and the various sizes of trocar assemblies that can be used. By way of non-limiting examples, trocar assembly sizes with which the present disclosures can be used include $\frac{2}{3}$ millimeter, 5 millimeter, 8 millimeter, $\frac{10}{12}$ millimeter, 15 millimeter, and 18 millimeter trocar assemblies. A person skilled in the art will recognize that these trocar sizes generally delineate a size of an inner diameter of the cannula of the trocar, thus informing a user a size of an instrument that can be disposed through the cannula. An outer diameter of the trocar is thus larger. By way of non-limiting examples, an outer diameter of a 5 millimeter trocar is typically about 8.0 millimeters, and an outer diameter of a $\frac{10}{12}$ trocar is typically about 15.15 millimeters.

Openings or Ports Formed in Housing and Cannula

As shown best in FIGS. **2B-2D**, opposed openings or ports **140** are disposed in the housing **104**. The openings **140** can be formed in the sidewall **108** of the housing **104**, and can extend therethrough, creating a channel **142** through which fluid can flow through. In the illustrated embodiment, the opening **140** is substantially circular and the channel **142** substantially cylindrical, although other shapes and configurations are possible without departing from the spirit of the present disclosure. A seal **144** is disposed somewhere along a length of the channel **142**. In the illustrated embodiment, the seal **144** is disposed at the opening **140**, which serves as a proximal entrance to the channel **142**. In other embodiments, the seal **144** can be disposed further distally along a path through the channel **142**, i.e., closer to the central longitudinal axis **L**. In the illustrated embodiment, the entrance into the channel **142** is approximately flush with the outer sidewall **108**, and the channel **142** that extends into the working channel **122** is disposed at an oblique angle β with respect to the central longitudinal axis **L** such that the channel terminates distal of the distal-most seal, i.e., the duckbill seal **132**, thereby forming a suture path between an outside environment and a surgical site. The present configuration allows insufflation to be substantially maintained even as an instrument or suture is passed through the channel **142**. As shown, the proximal end of the channel **142** is

disposed approximately in the same horizontal plane as a portion of the distal-most seal **132**, but it does not have to be so disposed. The openings **140** promote fluid communication between an outside environment and the working channel when the seal **144** associated with the channel **142** is open.

FIGS. 2A-2D illustrate opposed openings or ports **160** disposed in the cannula **102** as well. The openings **160** can be formed, and extend through, the sidewall **118** of the cannula **102**. A seal **164** is associated with the opening **160**, for instance by sitting within the opening **160**, or as described in later embodiments, by having a sleeve that serves as a seal disposed around the cannula at the opening. In some instances, the openings **160** can be referred to as sealed openings or ports because of the proximity of the seal **164** with respect to the opening **160**. The openings **160** formed in the cannula **102** are accessible by an instrument, device, or suture that is passed through the housing opening **140** and through the working channel **122**. Thus, a plurality of paths can be formed between the opening(s) **140** of the housing **104** and the opening(s) **160** of the cannula **102**, the paths passing across the working channel **122** of the device **100**. The sealed openings or ports **160** can have a variety of shapes and configurations, but in the illustrated embodiment both openings **160** are elongate, having a substantially elliptical shape. The elongate nature of the ports **160** allows for different bite angles to be achieved, and can be used in conjunction with other adjustability features and particularly configured seals to achieve desired results as described herein. The inclusion of openings or ports **140**, **160** in association with both the housing **104** and the cannula **102** is one particularly useful and independently novel aspect of the present disclosure. Another separate, but also particularly useful and independently novel aspect of the present disclosure, is the ability for bite angles to be adjusted across one or more suture paths that are formed through a surgical access device like the trocar assembly **100**.

The materials used to form the seals **164**, as well as the seals **144** associated with the housing **104**, can be any materials known to those skilled in the art, including but not limited to various elastomers and rubbers, such as polyisoprene, Butyl rubber, anionically polymerized isoprene (e.g., Kraton® as manufactured by Kraton Polymers of Houston, Tex.), polyurethane, silicone, and other similar materials. Some seals can be manufactured from more than one of these materials. In the illustrated embodiment, the openings **140** formed in the housing **104** and the openings **160** formed in the cannula **102** are substantially aligned such that longitudinally extending planes that pass through an approximate entirety of the respective openings **160** are substantially parallel to longitudinally extending planes that extend through an approximate entirety of the respective openings **140** in the housing **104**. However, the openings **140**, **160** can generally be disposed at any location around the circumference of the respective housing **104** and cannula **102** as desired, and as described below, their locations can be manipulated.

Suture Insertion Devices and Use of the Same with Trocar Assemblies

FIG. 3 provides for one exemplary embodiment of a suture insertion device **1000**, also referred to as a suture implant device, that can be used in conjunction with the surgical access devices provided for herein. Such devices are known to those skilled in the art, and thus a detailed explanation as to how they work is unnecessary. Generally, the device **1000** includes a proximal handle or gripping portion **1002**, an elongate shaft **1004** extending from the

proximal handle portion **1002**, and a distal tip or needle **1006** that is configured to puncture tissue and/or hold a suture at a position relative to the device **1000** to aid in passing the suture into and through a surgical access device and then into tissue disposed proximate to that surgical access device. In the illustrated embodiment, a suture **1010** is coupled to a connecting anchor or member **1012**, and the connecting anchor **1012** is coupled to the distal tip **1006** of the device **1000** to secure the suture relative to the device. More particularly, the connecting anchor **1012** has a lumen (not shown) extending through a portion thereof, and the distal tip **1006** of the device **1000** and inner walls of the anchor **1012** surrounding the lumen of the anchor **1012** are configured to be removably coupled together. Other mechanisms and manners for connecting the suture **1010** to the device **1000** are possible. By way of non-limiting example, a spring-biased stylet having a tip needle can be used, such as an Endo Close™ insertion device, as manufactured by Medtronic of Dublin, Republic of Ireland. Further, as described below, the connecting anchor **1012** can be disconnected from the suture insertion device **1000** and subsequently coupled with a second connecting anchor to form a single suture.

One exemplary embodiment of using the suture insertion device **1000** with the surgical access device **100** is illustrated in FIGS. 4A-4E. As shown, the suture insertion device **1000** can be passed through the opening **140** (identified for purposes of FIGS. 4A-4E as **140a** to distinguish it from the opposed opening **140**, which is identified for purposes of FIGS. 4A-4E as **140b**) in the housing **104**, through the working channel **122**, and through the sealed opening **160** (identified for purposes of FIGS. 4A-4E as **160b** to distinguish it from the opposed opening **160**, which is identified for purposes of FIGS. 4A-4E as **160a**) in the cannula **102** that is opposed to the opening **140a** so that the connecting anchor **1012** and at least a portion of the suture insertion device **1000** is disposed outside of the surgical access device **100**, proximate to tissue in which the surgical access device **100** is disposed. The suture **1010** can be coupled to the suture insertion device **1000**, for instance by way of the connecting anchor **1012**, and upon exiting the opening **160b**, can be passed through tissue proximate to an opening in which the surgical access device **100** is disposed for future closure of the opening. The connecting anchor **1012**, and thus the suture **1010**, can be disconnected from the suture insertion device, and the suture insertion device removed, thereby leaving the suture **1010** and connecting anchor **1012** in the configuration illustrated in FIG. 4B.

The suture insertion device **1000**, or another suture insertion device, can also be operated to pass a second suture **1010'** into and through the surgical access device **100**. For example, the device **1000** can be passed into the other housing opening **140b**, through the working channel **122**, and through the other sealed opening **160a** so that a connecting anchor or member **1012'** associated with the second suture **1010'** and at least a portion of the suture insertion device **1000** is disposed outside of the surgical access device **100**, proximate to tissue in which the surgical access device **100** is disposed. Subsequent removal of the suture insertion device **1000** can result in the configuration illustrated in FIG. 4C.

As shown in FIG. 4D, the two connecting members **1012**, **1012'** can be coupled together so that the first and second sutures **1010**, **1010'** form a single suture loop **1014**. In the illustrated embodiment, the members **1012**, **1012'** are passed through sealed openings **180** located at a distal end **102d** of the cannula **102**. The sealed openings **180** can have at least

19

some of the same characteristics described above with respect to the sealed openings **160a**, **106b**, thus preventing fluid from unnecessarily passing between the working channel **122** and the outside environment. In other embodiments, the connecting members **1012**, **1012'** can be coupled outside of the surgical access device **100**, or alternatively, the two sutures **1010**, **1010'**, and/or additional sutures passed through openings **140**, **160** of the surgical access device **100**, can be operated independently to close the opening through which the surgical access device **100** is disposed. Turning back to the illustrated embodiment, the formed loop **1014** can then be closed, for instance by applying tension in direction P and Q to proximal ends **1010p**, **1010p'** of one or both sutures **1010**, **1010'**, respectively, as shown in FIG. 4E. The tension can be applied as the surgical access device **100** is being removed from the opening in tissue, or after it has been removed, to quickly and efficiently close the opening through which the surgical access device **100** was disposed.

Alternative Embodiment of Surgical Access Device and Suture Insertion Device

FIGS. 5A-5E illustrate another exemplary embodiment of a surgical access device, as shown a trocar assembly **200**, as well as another exemplary embodiment of a suture insertion device **2000**. The trocar **200** generally includes a trocar cannula **202** and a trocar housing (or handle) **204**, and has similar features and components as the trocar assembly **100**. Accordingly, it is unnecessary to discuss in any detail components such as a removable cap portion **205**, distal chamber portion **207**, central lumen **210**, interior lumen **220**, working channel **222** formed by the central and interior lumens **210**, **220**, insufflation port **224**, and seals (not shown), among other components. The construction and operation of such components are understood by a person skilled in the art in view of the disclosures provided for herein related to such components amongst the various provided for embodiments.

One illustrated difference between the trocar **100** and the trocar **200** is the location of the openings or ports **240** that are associated with the housing **204**. While the openings or ports **240** of the trocar **200** include channels **242** that extend between an outside environment and the working channel **222**, and seals **244** (FIG. 5C) associated therewith, an entrance of the channel **242** in FIGS. 5A-5E is not flush with respect to a sidewall **208** of the housing **204**. As shown, the opposed channels **242** extend separate from the sidewall **208**, and entrances of the channels **242** are further away radially from a central longitudinal axis L' of the device **200** than the outer sidewall **208** is located. Further, as illustrated in FIG. 5E, the entrances are angled with respect to the central longitudinal axis L'. More particularly, as shown, an angle γ formed by a plane J that extends substantially across the entrance of the channel **242** and the central longitudinal axis L' is oblique. The channel **242** still communicates with the working channel **222** and an opposed sealed opening **260** formed in a sidewall **218** of the cannula **202** as provided for with respect to the sealed opening **160** of the trocar **100**, as shown in FIGS. 5C and 5E. Further, the path formed by the opposed openings **240** and **260** is sealed at both ends, for example by providing for a seal **244** proximate to the entrance of the channel **242** and a seal **264** associated with the opening **260** extending through the cannula **202**. In the illustrated embodiment, the sealed openings **260** of the cannula **202** are formed by openings (not shown) formed in the sidewall **218** and a sleeve **270** disposed around the cannula **202**, the sleeve **270** having pre-formed seals **264** formed therein that are complementary in shape to the openings **260** such that the combination of the openings **260**

20

and the seals **264** form sealed openings of the cannula **202**. As shown, the sleeve **270** increases a diameter of the cannula **202**, but in other embodiments, as described below for instance with respect to FIGS. 23-25, the cannula and/or sleeve can be configured such that the diameter of the combination of the cannula and the sleeve is approximately equal to the diameter of the cannula at locations where the sleeve is not disposed.

Further, the suture insertion or implant device **2000** provided for in FIGS. 5A-5E is an alternative arrangement of a suture insertion device. The device **2000** generally includes a proximal handle portion **2002**, an elongate shaft **2004**, and a distal tip or needle **2006**, all of which are similarly constructed as the suture insertion device **1000**. One illustrated difference is that the proximal handle portion **2002** includes a spring-loaded actuator **2003**, which is spring-biased into a retaining position to maintain a location of a suture **2010** (FIG. 5B) with respect to the device **2000**. Pressing the actuator **2003** can release the suture **2010** from the device **2000**, thus allowing the device **2000** to be removed and the suture **2010** used to complete the surgical repair. In some embodiments, a connecting anchor or member **2012** can be used to assist in associating the suture **2010** with the device **2000**, as shown in FIG. 5B.

In use, the suture insertion device **2000** having the suture **2010** associated therewith is passed from an outside environment, into the opening **240** through the entrance into the channel **242**, through the working channel **222**, and out of the sealed opening **260** to the surgical site. The suture **2010** is decoupled from the insertion device **2000** and the insertion device **2000** is removed. The suture insertion device **2000** then has a second suture associated therewith (or, alternatively, a second suture insertion device is used in conjunction with a second suture), is passed from an outside environment, into the opposed opening **240** through the entrance into the opposed channel **242**, through the working channel **222**, and out of the other sealed opening **260** to the surgical site. The suture is again decoupled from the insertion device **2000** (or second suture insertion device) and the insertion device **2000** removed. The sutures can then be operated to close the opening through which the trocar **200** is disposed as or after the trocar **200** is removed from the opening.

Surgical Access Devices with Multiple Openings Proximate to Each Other

FIGS. 6 and 7 provide two alternative embodiments of surgical access devices having multiple openings associated with each of a housing and a cannula, with the openings in each of the housing and cannula being proximate to each other. In other words, while previous embodiments included multiple openings formed in a housing and multiple openings formed in a cannula, those openings were generally opposed to each other so that one opening in a housing and one opening on an opposed side of the cannula formed a suture path. There were not multiple openings formed on the same side of a housing or a cannula to provide various suture path options having forming different bite angles. The embodiments of FIGS. 6 and 7, however, provide multiple openings in the same component that are proximate to each other, which provides the ability for different bite angles to be achieved depending on through which openings a suture insertion device and/or a suture are passed.

As shown in FIG. 6, a trocar **300** having both a housing **304** and a cannula **302** extending distally therefrom includes a port extension **301** extending radially from the otherwise cylindrically-shaped housing **304**. The extension **301** includes a plurality of openings or ports **340** formed therein,

each port or opening serving as an entrance to a channel 342 that extends through the extension 301, through the housing 304, and into a working channel 322 extending through the trocar 300. As with other embodiments, the working channel 322 is formed by a central lumen 310 extending through the housing 304 and an interior lumen 320 extending through the cannula 302. Each opening 340 can have a seal 344 associated therewith, either at the entrance or further in the channel 342, between the entrance and the working channel 322. The openings 340 can be formed in any pattern, but in the illustrated embodiment there are three openings 340 having a triangular pattern formed between the three openings. The extension 301 can be any size and shape, depending, at least in part, on the desired bite angle, the number of desired openings 340, and the components and methods with which the trocar 300 is designed to be used. In the illustrated embodiment, the extension 301 has a substantially pyramidal shape with the openings 340 being formed in a substantially flat, proximal-facing surface 301_f, and an angled side 301_s that extends radially from the sidewall 308 to lead to an outer-most wall 301_w of the substantially flat, proximal-facing surface 301_f. Although not illustrated, a complementary extension, along with one or more openings or ports, can be formed on an opposed side of the device 300, or at any other location along a circumference of the housing 304.

Multiple openings or ports 360 can also be formed in a sidewall 318 of the cannula 302, with the multiple openings 360 being proximate to each other. Similar to the openings 340 of the housing 304, the openings 360 can be formed in any pattern, but in the illustrated embodiment there are three openings 360 having a triangular pattern formed between the three openings 360, with one opening, a central vertex 360_c (i.e., the opening that is approximately equidistantly spaced from the other two openings), being more proximal than the other two, which are substantially aligned with respect to a longitudinal axis L" extending through the device 300. Each of the openings 360 can be sealed in manners similar to those described elsewhere herein as it pertains to openings or ports associated with the cannula, and thus in some embodiments can include a seal 364 disposed within each opening 360. Additionally, although not illustrated, openings 360 of the nature illustrated with respect to FIG. 6 can also be formed on an opposed side of the cannula 302, or at any other location along its circumference. Further, any one of the openings 360 formed in the cannula 302 can be used in conjunction with any one of the openings 340 formed in the extension 301. Each different combination of openings 340, 360 in the housing 304 and cannula 302 can provide for a different bite angle.

FIG. 7 provides for another configuration of a trocar 400 having multiple openings 440, 460 proximate to each other in both a housing 404 and a cannula 402 extending distally from the housing 404, respectively, to allow for multiple bite angles. In the illustrated embodiment, the trocar 400 is disposed in an opening 6''' formed in tissue 8'''. The openings or ports 440 associated with the housing 404 of the illustrated embodiment are configured in a manner similar to the openings 240 of the trocar 200 of FIGS. 5A-5E, and can be used in conjunction with the openings 460 to pass a suture along a path extending therebetween and into tissue to close the opening 6''' as or shortly after the trocar 400 is removed from the opening 6'''.

As shown, three openings or ports 440 extend radially from a sidewall 408 of the housing 404, with each port 440 being more distal than an adjacent port. In the illustrated embodiment, the three ports 440 are substantially aligned along a longitudinal axis M that is substantially parallel to a

central longitudinal axis L''' of the device 400. In other embodiments, one or more of the ports 440 can be located in a position that is at a location other than substantially longitudinally aligned with one or more of the other ports 440. Each port 440 can include a channel 442 that extends from an outside environment, through the housing 404 and into a working channel 422 extending through the device that is defined by a central lumen 410 of the housing and an inner lumen 420 of the cannula 402. In the illustrated embodiment, an entrance of each channel 442 is disposed radially further away from the central longitudinal axis L''' than the sidewall 408 is located with respect to the central longitudinal axis L'''. Each channel 442 includes a seal 444 associated therewith, either at the entrance or disposed further distally along the channel 442 so that the outside environment is sealed from the working channel 422. A plane J' extending substantially through the entrance of the channel 442 can form an oblique angle δ with respect to the central longitudinal axis L'''.

Multiple openings or ports 460 can also be formed in a sidewall 418 of the cannula 402, with the multiple openings 460 being proximate to each other. Similar to the openings 440 of the housing 404, the openings 460 can be formed in any pattern, but in the illustrated embodiment there are three openings 460 having a triangular pattern formed between the three openings, with one opening, a central vertex 460_c (i.e., the opening that is approximately equidistantly spaced from the other two openings), being disposed to the right of the other two co-aligned vertices as shown. One of the two c-aligned vertices, a proximal-most vertex 460_p, is more proximal than the other two vertices. Each of the openings 460 can be sealed in manners similar to those described elsewhere herein as it pertains to openings or ports form in the cannula, and thus in some embodiments can include a seal 464 disposed within each opening 460. Additionally, although not illustrated, openings 460 of the nature illustrated with respect to FIG. 7 can also be formed on an opposed side of the cannula 402, or at any other location along its circumference. Further, any one of the openings 460 formed in the cannula 402 can be used in conjunction with any one of the openings 440 extending from the housing 404. Each different combination of openings 440, 460 in the housing 404 and cannula 402 can provide for a different bite angle. Further, in some embodiments, either or both of the openings associated with the housing 404 and the openings 460 associated with the cannula 402 can be labeled to help users identify the bite angles that are achieved. The markings can be formed on the sidewalls 408 and 418 at locations visible to a user and/or visible using an endoscope or other viewing instrument to view the markings.

In the illustrated embodiment, a suture insertion or implant device 4000 is illustrated passing through a proximal-most opening 440_p of the housing openings 440 and the proximal-most opening 460_p of the cannula openings 460. While the location of an opening 440 in the housing 404 through which a suture insertion device can be similar to the location of an opening 460 in cannula through which the same device is inserted, i.e., the device passing through the proximal-most openings of both the housing and cannula, a suture insertion device and/or suture can be passed from any of the openings of the housing to any of the openings of the cannula. Accordingly, a first position can be in which a device and/or suture passes through the proximal-most housing opening and the proximal-most cannula opening, a second position can be in which a device and/or suture passes through the proximal-most housing opening and one of the distal-most cannula openings, a third position can be

in which a device and/or suture passes through the proximal-most housing opening and the other of the distal-most cannula openings, a fourth position can be in which a device and/or suture passes through the middle housing opening and the proximal-most cannula opening, and so forth. Any number of positions can be achieved depending, at least in part, on the number of openings provided in the housing and cannula, the adjustability of those openings (as described below), and the size and shape of the openings and instruments used in conjunction therewith. In use, a person skilled in the art, in view of the present disclosures, will recognize how to select different openings to pass an insertion instrument and/or suture through to achieve desired bite angles. The various bite angles can be used to pass suture into the tissue 8''' in various configurations to allow the opening 6''' to be closed while or shortly after the trocar 400 is removed from the opening 6'''. A person skilled in the art will recognize that while some other surgical access device embodiments provided for herein are not illustrated with respect to a tissue or an opening or wound formed in the tissue, the other embodiments can be used to close openings in which the surgical access device is disposed while or shortly after the device is removed from such an opening or wound in view of the present disclosures.

Surgical Access Device Having Elongate, Adjustable Openings

FIGS. 8-11 illustrate one exemplary embodiment of a surgical access device, e.g., a trocar 500, having an elongate opening or slot 540 formed in a housing 504 of the device 500, with the elongate opening 540 including an adjustable entry port 541 that is movable along a length of the slot 540 to adjust an angle of a suture insertion or implant device or suture that passes therethrough with respect to a central longitudinal axis L''' of the device 500. As shown, the housing 504 includes an elongate opening or slot 540 formed in an extension 501 that extends radially away from a sidewall 508 of the housing 504, although in other embodiments the slot 540 can be formed in the sidewall 508 itself and/or the extension 501 can be considered to be part of the sidewall 508. The opening 540 can have a variety of shapes and configurations, but in the illustrated embodiment the opening 540 is elongate, having a substantially elliptical shape. An adjustable entry port 541, alternatively referred to herein as an instrument receiving opening or an adjustable sealable opening, is disposed within the elongate opening 540 and has a seal 544 associated therewith. The seal 544 can be disposed at the surface of the extension 501 as shown, or it can be disposed at a location more proximate to the central longitudinal axis L'''. The seal 544 provides a seal between the outside environment and a working channel 522 of the device 500 that is defined by a central lumen 510 of the housing 504 and an interior lumen 520 of the cannula 502. While in earlier embodiments a channel was associated with the various openings 140, 240, 340, 440 that extends through the respective housings 104, 204, 304, 404, no such channel is provided for the trocar 500 so that the rotation of the openings 540 can be more easily achieved. Instead, the openings 540 extend a distance into the housing before opening to openings formed in the rotary disc 590, as described in greater detail below.

The adjustable entry port 541 is configured to receive a suture insertion or implant device and/or suture therethrough, which in turn can be passed through the working channel 522, a sealed opening 560 formed in a sidewall 518 of the cannula 502 that extends distally from the housing 504, and to a surgical site. The sealed opening 560 can be sealed, for example, by having a seal 564 disposed within

the opening 560. As described below, the adjustable entry port 541 is movable along a length of the opening 540 to adjust a bite angle at which the insertion device and/or suture disposed therethrough passes through the working channel 522 and into tissue. Although not illustrated, a complementary extension having an elongate opening or slot and an adjustable entry port, can be formed on an opposed side of the device 500, or at any other location along a circumference of the housing 504.

The adjustable entry port 541 can be moved through the opening 540 using a variety of different techniques, and in the illustrated embodiment a rotary dial 590 is provided to move the adjustable entry port 541. The rotary dial 590, which is illustrated in FIGS. 9 and 10, can be disposed distal of an entrance of the adjustable entry point 541 and distal of a distal-most seal 532 (typically a duckbill or zero-closure seal) disposed in the housing 504, as best seen in FIG. 10. The rotary dial 590 can include one or more receiving openings 592 formed therein for receiving an instrument to pass from the adjustable entry port 541 to the working channel 522. The receiving openings 592 can have diameters or widths that are approximately greater than half a radius of the rotary dial 590 so that a device passing therethrough can be moved through a variety of angles. As shown in FIG. 10, an instrument 5000 can extend from the adjustable entry port 541, through the receiving opening 592, and into the working channel 522.

Turning back to FIG. 9, the rotary dial 590 can further include opposed cams 594 that are disposed on a surface 596 of the rotary dial 590, the cams 594 being ramped to allow for adjustability. A seal spring (not shown) can further be disposed therein to bias the rotary dial 590. In one embodiment, the spring can be biased towards a bottom part of the receiving opening 592 so that rotation of the cam 594 in a direction R biases the rotary dial 590 upward in a direction S, as shown in FIG. 9. Accordingly, as the rotary dial 590 is turned, for example, counterclockwise in the direction R, an instrument 5000 disposed in the opening 592 can slide up the cam 594 in the direction S. Notably, the instrument 5000 is not necessarily disposed in the opening 592 when the dial 590 is rotated, and in such instances, when the device 5000 is eventually passed through the dial 590, then it attains the illustrated configuration set by the rotation of the dial 590.

As shown in FIG. 8, the rotary dial can be rotated in either direction, which in turn causes the adjustable entry port 541 to move up and down through the elongate opening 540 to establish a bite angle for the suture insertion device and associated suture. Further, the aggressiveness of the curve of the cam 594 can impact the bite angle that is created, with the more aggressive curve creating a greater variation in bite angle. In the illustrated embodiment, the curves of the cams 594 yield a change in bite angle approximately in the range of about 15 degrees to about 45 degrees, and in one non-limiting exemplary embodiment the change in bite angle is about 30 degrees. Further, an outer edge of the rotary dial 590 can include one or more gripping features 598, e.g., ridges, grooves, or the like, to assist a user in being able to easily rotate the dial. In some embodiments, the dial 590 can be configured to have distinct set positions keyed into it such that as the dial 590 is rotated, it moves between various preset, keyed configurations that result in different bite angles.

FIG. 11 depicts the adjustable entry point 541 (not visible) being moved by rotation of the rotary dial 590 in the counterclockwise direction R. As shown, as the dial 590 is rotated in the counterclockwise direction R, the portion of the instrument 5000 located proximate to the adjustable

25

entry port **541** moves in a downward direction T, while the portion of the instrument **5000** located proximate to sealed openings **560** of the cannula **502** move in an upward direction U, thereby decreasing the bite angle associated with the instrument **5000**. The two different bite angles with respect to tissue **9** are more clearly illustrated in FIGS. **12A** and **12B**, with an angle decreasing in FIG. **12B** as the rotary dial **590** is moved in the counterclockwise direction R and the adjustable entry point **541** moves distally through the opening **540** (not visible). In particular, the illustrated embodiment in FIG. **12A** is related to the instrument **5000** being disposed in a first position G, and the illustrated embodiment in FIG. **12B** being related to the instrument **5000** being disposed in a second position H, with both positions being identified in FIG. **11**.

A person skilled in the art will recognize that the components of the surgical access device **500** can be altered to achieve a variety of other configurations, such as rotation in either direction being able to achieve larger and smaller bite angles, having additional openings formed in any of the housing **504**, the rotary dial **590**, and/or the cannula **502** to provide further flexibility and adjustability, etc. In the illustrated embodiment, an angle of adjustment is approximately in the range of about 15 degrees to about 60 degrees, although smaller and larger angles can be achieved without departing from the spirit of the present disclosure. The angle formed allows different wall thicknesses to be passed through. Accordingly, in view of the present disclosures, a range of wall thicknesses through which an instrument and/or a suture can be passed in view of the provided for surgical access devices is approximately in the range of about 1 centimeter to about 5 centimeters.

Surgical Access Devices with Openings that Rotate with Respect to a Central Longitudinal Axis

FIGS. **13** and **14** and FIG. **16** provide two additional embodiments of surgical access devices that both provide multiple openings to achieve different bite angles, and also provide for movement of the openings with respect to respective central longitudinal axes of the surgical access devices to provide additional adjustability options for achieving a variety of bite angles. More particularly, the openings are configured to be rotated about a central longitudinal axis of the surgical access device.

FIGS. **13** and **14** illustrate one exemplary embodiment of a surgical access device, as shown a trocar **600**, having openings **640** formed in a housing **604** of the trocar **600** that are adjustable. As shown, the housing **604** includes a plurality of rotatable discs **609a**, **609b** associated with a distal chamber portion **607** of the housing **604**, with a cap portion **605** being removably and replaceably attachable to the distal chamber portion **607**. In the illustrated embodiment, an insufflation port **624** is associated with the cap portion (FIG. **14**), and the two rotatable discs **609a**, **609b** are associated with the distal chamber portion **607**. Each disc **609a**, **609b** can include one or more openings **640** formed therein. The openings **640** can extend towards a central longitudinal axis L''' in a manner similar to the openings **540** described above with respect to the device of FIGS. **8-11**. Although not illustrated, a rotary disc can be provided below the rotary discs **609a**, **609b** and can operate in a manner similar to the rotary disc **590** described above, and thus a channel or path can be formed between the openings **640**, through the openings formed in such a rotary disc, and to a working channel **622** of the trocar, the working channel **622** being defined by a central lumen **610** of the housing **604** and an inner lumen **620** of the cannula **602**.

26

In view of the present disclosures, any of the plurality of housing openings **640** can be rotated and used in conjunction with any of the plurality of cannula openings **660** to achieve various bite angles. FIG. **14** provides one illustration of an insertion instrument **6000** having a different bite angle by virtue of being disposed in openings **640** of different rotary discs **609a**, **609b**. However, a person skilled in the art will also recognize that as any of the discs **609a**, **609b** rotates, and the instrument **6000** can be used in conjunction with other openings **660** in the cannula **602**, the same housing opening **640** can be used to create a different bite angle as well just by virtue of the disc **609a**, **609b** in which the instrument **6000** is disposed rotating. As shown, the instrument **6000** has a first bite angle when the instrument **6000** is disposed in an opening disposed in the top rotary disc **609a** and is passed through an elongate sealed opening **660** formed in the cannula **602**, while the instrument **6000** has a second bite angle when the device **6000** is disposed in an opening **640** disposed in the bottom rotary disc **609b** and is passed through a different elongate sealed opening **660** formed in the cannula **602**. Notably, the elongate sealed openings **660** provided for in a sidewall **618** of the cannula **602** of FIG. **14** are elongate along a width rather than a length, although as described above, either configuration is acceptable. Seals **664** can be associated with the openings **660** as described in greater detail in other embodiments. The achieved bite angles θ of both configurations are illustrated with respect to tissue **9'** in FIGS. **15A** and **15B**, with the illustrated embodiment in FIG. **15A** being related to the instrument **6000** being disposed in a first position G', and the illustrated embodiment in FIG. **15B** being related to the instrument **6000** being disposed in a second position H', with both positions being identified in FIG. **14**.

FIG. **16** depicts an alternative embodiment of a surgical access device, as shown a trocar **700**, having rotary discs **709a**, **709b**. Similar to the surgical access device of FIGS. **13** and **14**, a plurality of discs, as shown the two discs **709a**, **709b**, are included as part of a housing **704** of the trocar **700**, and each disc **709a**, **709b** includes a plurality of openings **740** formed therein. In the embodiment illustrated in FIGS. **13** and **14**, the openings **740** formed in the discs **609a**, **609b** had a portion of an outer wall of the respective discs **609a**, **609b** disposed around an entirety of each opening **640**. In contrast, the openings **740** formed in the discs **709a**, **709b** include at least one opening **740** that is open-ended such that the open-ended openings **740** can be moved to an alignment position in which one opening **740** associated with one disc **709a** is aligned with one opening **740** associated with the other disc **709b** to form an elongate opening **740C**. A suture insertion or implant instrument **7000** and/or suture can then be passed through any portion of the formed elongate opening **740C**, into a working channel **722** of the trocar **700** that is formed by a central lumen **710** of the housing **704** and an interior lumen **720** of the cannula **702**, through openings **760** formed in a sidewall **718** of the cannula **702**, and to a surgical site.

In the illustrated embodiment, multiple elongate openings **740C** are formed at the same time, although the openings **740** on each disc **709a**, **709b** do not need to be spaced in such a manner. In some instances, only a single elongate opening **740C** is formed when two openings **740** are disposed in an alignment position with respect to each other. Further, when an opening **740** formed in one disc **709a** is not aligned with an opening **740** formed in an adjacent disc **709b**, a surface of the adjacent disc **709b** closes the opening **740** of the first disc **709a** such that the opening **740** can be used to receive a suture insertion or implant instrument

and/or suture as described herein. Either or both of the discs **709a**, **709b** can rotate about a central longitudinal axis L'''''' of the surgical access device **700** to selectively move one or more openings **740** of a disc **709a**, **709b** into and out of an alignment position.

Similar to other embodiments, the one or more sealed openings **760** can be formed in a sidewall **718** of the cannula **702**. In the illustrated embodiment, there are three openings **760** illustrated, each being elongate along a horizontal plane that is substantially perpendicular to the central longitudinal axis L'''''' (the plane going into and out of the paper as shown), with a central vertex **760c** being more distal than two aligned proximal vertices of a sealed opening triangular configuration. Seals **764** can be associated with the openings **760** as described in greater detail in other embodiments. Further, although the illustrated embodiments provide for two rotary discs having openings associated therewith, fewer or more rotary discs can be incorporated into the housing of any surgical access device without departing from the spirit of the present disclosure.

One useful and independently novel aspect of the present disclosure is the ability it provides a user to selectably adjust a bite angle formed between a suture path extending between one or more openings associated with a housing of a surgical access device and one or more openings associated with a cannula of the surgical access device. Whether the ability to adjust is a result of the inclusion of multiple openings in association with the housing or cannula, the ability to move the openings with respect to a central longitudinal axis of the surgical access device (e.g., rotate about the central longitudinal axis by way of one or more rotary discs), the ability to move an adjustable entry port within an elongate seal, the ability to operate a rotary dial to move an adjustable entry port or openings more generally, or any other adjustable feature afforded by the present disclosures, the selectable adjustment enhances a surgical procedure because it allows a user to manipulate the angle at which a suture will enter tissue so that the opening in which the surgical device is inserted can be closed in a desirable manner.

Seals and Sealed Openings of the Cannula

FIG. **17** provides for another exemplary embodiment of a surgical access device, as shown a trocar **800**. Similar to previous embodiments, the trocar **800** includes a housing **804** having a cannula **802** extending distally therefrom, and one or more openings **840**, **860** are associated with each of the housing **804** and cannula **802**, respectively, to allow for a path to be formed through which a suture insertion or implant instrument and/or suture can travel from an outside environment, through the housing **804**, through a working channel **822** of the device **800** defined by a central lumen **810** of the housing **804** and an interior lumen **820** of the cannula **802**, through the cannula **802**, and to a surgical site. The focus of this embodiment is on the sealed openings **860** formed in the cannula **802**, which are illustrated in greater detail in FIGS. **18A** and **18B**. As shown in FIG. **17**, two opposed sealed openings **860** are formed in a sidewall **818** of the cannula **802**. Each opening **860** is elongate and generally elliptical in shape. A length l of the sealed openings **860** in a direction substantially along an axis Y that is parallel to a central longitudinal axis L'''''' of the device is greater than a width of the sealed openings **860**. Each sealed opening **860** is formed by forming a lumen in the sidewall **818** and associating a seal **864** with the lumen. In various embodiments the seal **864** can be positioned within the lumen or overtop of the lumen. As shown, the seal **864** is sized to sit snugly within the lumen so that fluid does not

generally pass between the seal **864** and the portion of the sidewall **818** that defines the lumen.

As shown in FIGS. **17**, **18A**, and **18B**, the seal **864** includes a plurality of ridges **863** formed in a surface that faces towards the working channel **822** of the trocar **800**. The ridges **863** are in a criss cross pattern such that openings **865**, also referred as pre-defined tear zones, are formed between the ridges **863**. One or more of the openings **865** can be configured to have an instrument, e.g., a suture insertion or implant device, and/or suture passed there-through and seal around the instrument and/or suture to maintain a seal between the working channel **822** and a surgical site. The ridges **863** provide both a pre-defined path to which the instrument and/or suture can be directed, and also provide reinforcement for the seal so that remnants of the seal **864** are not separated from the rest of the seal as an instrument and/or seal are passed through the seal. Further, as illustrated best by FIG. **18B**, the ridges **863** form individual pockets **867** along a length of the seal **864** with narrowed neck portions **869** between each pocket **867**, thus providing individual, predefined openings **865** through which instruments and/or sutures can be disposed. Additionally, the preformed patterns minimize an amount of load that needs to be applied to an instrument and/or suture being passed through the seal **864**.

FIGS. **19A-20B** illustrate two further, non-limiting embodiments of seals **864'**, **864''** having patterned guide surfaces that can be associated with the elongate openings **860** of FIG. **17**. The seal **864'** of FIGS. **19A** and **19B** includes a patterned guide surface that has a plurality of pre-formed openings or tear zones **865'** centrally disposed along a longitudinal axis N of the seal **864'**. As with the seal **864**, the patterned guide surfaces minimize an amount of load that needs to be applied to an instrument and/or suture being passed through the seal **864'**. The longitudinal axis N is substantially parallel to the central longitudinal axis L'''''' of the surgical access device **800** when the seal **864'** is disposed within the opening **860**. Each of the four pre-formed openings **865'** is configured to be closed when no instrument or suture is disposed therethrough, and is configured to seal around an instrument and/or suture that is disposed therethrough. Each pre-formed opening **865'** can independently open and close apart from the other pre-formed openings **865'**. Similar to the seal **864** as best shown in FIG. **19B**, a narrowed neck portion **869'** can extend between each of the openings **865'** to provide individual, predefined openings through which instruments and/or sutures can be disposed. The material disposed around each opening can help reinforce the seal so that portions surrounding each opening **865'** do not break away from the seal **864'** when an instrument is passed therethrough. Further, the seal **864'** can be generally flexible in six degrees, thereby allowing an instrument disposed through one opening **865'** to be moved with some level of freedom in two directions longitudinally, horizontally, and through the seal **864'**. Accordingly, while the selection of which opening **865'** an instrument and/or suture is passed can impact the associated bite angle, the bite angle can also be adjusted when such instrument and/or suture is disposed in a single opening **865'** due to the flexibility of the seal **864'**.

FIGS. **20A** and **20B** illustrate an alternative embodiment of a seal **864''** that includes a patterned guide surface with at least one pre-formed opening **865''** formed therein. As shown, a preformed opening or tear zone **865''** can be formed centrally in the seal **864''**, with a plurality of radial arcs **861''** disposed above and below the preformed opening **864''**. The seal **864''** is generally configured to allow an

instrument and/or suture associated with the instrument to be passed through the central opening **865**", and the arcs **861**" can provide flexibility to allow the instrument and/or suture passing therethrough to be manipulated to achieve various bite angles. The arcs **861**" also provide reinforcement for the seal **864**" so that portions surrounding the opening **865**" do not break away from the seal **864**" when an instrument is passed therethrough. A longitudinal slit **871**" can extend along a length of the seal **864**", thereby providing the ability to insert an instrument and/or a suture through any of the arcs **861**" as well. Slits **863**" disposed between each arc **861**" can help form individual pockets **867**" through which an instrument and/or suture can be disposed, as illustrated in FIG. 20B.

FIGS. 21-22C illustrate an exemplary embodiment of a movable seal associated with a sidewall of a cannula of a surgical access device. As shown in FIG. 21, a surgical access device, e.g., a trocar assembly **900**, includes a housing **904** and a cannula **902** extending distally therefrom. One or more openings **940**, **960** are associated with each of the housing **904** and the cannula **902**. Further, a movable seal **964** is disposed within one opening **960** formed in a sidewall **918** of the cannula **902**. The movable seal **964** includes a slidable, floating instrument entrance **965** that allows a bite angle to be adjusted when a suture insertion or implant instrument and/or suture is disposed therethrough. In an unengaged state, the slidable, floating resealable instrument entrance **965** can be substantially centered with respect to the seal **964**, and thus the opening **960**. When no instrument is disposed therethrough, the slidable, floating resealable instrument entrance **965** maintains a seal between a working channel **922** defined by a central lumen **910** of the housing **904** and an inner lumen **920** of the cannula **902**, and an outside environment. A plurality of slits **963** can be formed in a surface of the seal **964** to assist in providing flexibility in the seal **964**. An instrument **9000** can be passed into the instrument entrance **965**, as shown in FIG. 22A, such that the seal **964** forms a seal around the instrument **9000**. The instrument can be manipulated between first and second positions V and W as labeled in FIG. 21 and as illustrated in FIGS. 22B and 22C, respectively. During manipulation, a seal is maintained around the instrument **9000**, as shown in FIGS. 22B and 22C, so that fluid does not pass across the seal **964**. Similar to the earlier embodiments, the pre-defined, pre-formed nature of the slidable, floating instrument entrance **965** and associated seal **964** minimizes an amount of load that needs to be applied to an instrument and/or suture being passed through the seal **964**, while also minimizing the risk of a remnant of the seal body becoming dislodged from the seal **964**.

While the construction of the seals provided for herein can themselves lead to flexible seals that permit a bite angle to be adjusted while reducing the risk of remnants becoming separated from the seal, the materials used to form the seals can also assist in providing flexibility and a decreased risk of remnant dislodging. Thus, materials that are stretchable and tear-resistant are well-suited for use in formed sealed openings in the cannula and/or the housing. Some non-limiting examples of materials that can be used to form the seals include various elastomers and rubbers, such as polyisoprene, Butyl rubber, anionically polymerized isoprene (e.g., Kraton® as manufactured by Kraton Polymers of Houston, Tex.), polyurethane, silicone, and other similar materials. One or more materials can be used to form any of the seals provided for herein.

The particular seal constructions provided for herein are useful and independently novel aspects of the present dis-

closure. The seals provide pre-defined rupture locations that minimize tear remnants that are left behind, which is particularly useful for seals formed in a sidewall of a cannula of a surgical access device. A person skilled in the art will recognize that the seals provided for herein can also be used effectively in other types or portions of medical devices, as well as other fields that use seals in which the present disclosures will prove useful.

Seal Sleeve

The surgical access device **200** of FIGS. 5A-5E includes a seal sleeve **270** disposed around openings **260** formed in the sidewall **218** of the cannula **202** to create a sealed opening. In that embodiment, however, the thickness of the sleeve **270** causes a diameter of the cannula **202** as a whole to be greater at the location of the sleeve **270** than elsewhere along a length of the cannula **202**. FIGS. 23-25 provide for an alternative embodiment in which a cannula **202'** of a surgical access device, e.g., a trocar assembly **200'**, is modified to accommodate a thickness of a sleeve **270'** so that a diameter of the cannula **202'** is not necessarily greater at the portion of the cannula **202'** that includes the sealed openings **260'** and sleeve **270'**.

As shown in FIGS. 23 and 24, a surgical access device, e.g., a trocar assembly **200'**, includes a housing **204'** and a cannula **202'** extending distally therefrom. Each of the housing **204'** and cannula **202'** can include at least one opening **240'**, **260'**, respectively, associated therewith for passing a suture insertion or implant instrument and/or suture therethrough as described above. The opening(s) **260'** in the cannula **202'** can be formed in a proximal portion **202p'** of the cannula **202'**. In the illustrated embodiment, there are two opposed openings **260'** formed in the cannula **202'**, although only one is visible. Like the other embodiments provided for, however, any number of openings **260'** can be formed in a sidewall **218'** of the cannula **202'**, at most any location and in any number of configurations or patterns.

As described at least with respect to FIGS. 5A-5E, a seal sleeve **270'** having one or more pre-formed seals **274'** can be used in conjunction with the openings **260'** to form a sealed opening that is configured to prevent fluid from passing through the opening **260'** when no instrument or the like is disposed in the seal **264'**, and which can seal around an instrument or the like passed through the seal **264'**. In other embodiments of a sleeve, no pre-formed seal is formed and the sleeve itself is configured to generally form a seal around an instrument and/or suture passing therethrough, but maintain a seal when nothing is passed therethrough.

One exemplary embodiment of a seal sleeve **270'** is illustrated in FIG. 25. The seal sleeve **270'** is generally cylindrical in shape and includes a lumen **273'** extending therethrough. The lumen **273'** is generally sized to allow the sleeve **270'** to be elastically coupled to the cannula **202'** when the sleeve **270'** is disposed around or on the cannula **202'**. In particular, the seal sleeve **270'** can be configured to stretch and snap along any portion of the cannula **202'** wherein openings **260'** designed to have seals associated therewith are disposed on the cannula **202'**. The sleeve **270'** can have any number of configurations associated with it, including the pre-formed openings **264'** and/or patterned surfaces described above, and it can be made from materials known to those skilled in the art for providing sealing characteristics, e.g., various elastomers and rubbers, such as polyisoprene, Butyl rubber, anionically polymerized isoprene (e.g., Kraton® as manufactured by Kraton Polymers of Houston, Tex.), polyurethane, silicone, and other similar materials. One or more materials can be used to form any of the seals provided for herein.

As shown in FIG. 24, a portion of the proximal portion 202p' can have a portion 219' of the sidewall 218' removed to accommodate placement of the seal sleeve 270' over the openings 260' without increasing a diameter of the device 200' at the portion that includes both the cannula 202' and the sleeve 270'. As shown in FIG. 25, the sealing sleeve 270' has a thickness t, and as shown in FIG. 24, the portion 219' of the sidewall 218' that is removed results in a recess 215' disposed between two ledges 217', each ledge 217' being sized to approximately have the same thickness t as the sleeve 270'. The shape of the recess 215' is such that it is complimentary to the shape of the seal sleeve 270', and thus in the illustrated embodiment it is substantially cylindrical in shape. When the seal sleeve 270' is placed in the recess 215', the seal sleeve 270' can sit approximately flush with the rest of the cannula 202' such that an outer wall of the seal sleeve 270' is approximately aligned with the outer sidewall 218' of the cannula 202'. While the thickness t of the seal sleeve 270', and thus the thickness t of the ledges 217', can depend on a variety of factors, including the size of the cannula (e.g., a thickness of the cannula, which in some embodiments is about 0.8 millimeters), the patient, and the preferences of the surgeon, in some exemplary embodiments the thickness t can be approximately in the range of about 0.05 millimeters to about 0.5 millimeters, more specifically in some embodiments approximately in the range of about 0.1 millimeters to about 0.3 millimeters, and in one non-limiting embodiment the thickness t is about 0.4 millimeters.

A person skilled in the art will recognize that the various features provided for across the various embodiments can be used interchangeably across other embodiments without departing from the spirit of the present disclosure. By way of non-limiting example, to the extent one embodiment includes an elongate opening and another embodiment does not, the elongate opening can be easily incorporated into the other embodiment. The ability to transpose one or more features from one embodiment to any other embodiment is readily understandable in view of the present disclosures. In no way is the depiction of one feature in one embodiment limiting of that feature only being able to be implemented in that embodiment.

Further, a person skilled in the art will appreciate that the present invention has application in conventional endoscopic and open surgical instrumentation as well application in robotic-assisted surgery.

The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

Preferably, the devices described herein will be processed before surgery. First, a new or used instrument is obtained and if necessary cleaned. The instrument can then be sterilized. In one sterilization technique, the instrument is placed

in a closed and sealed container, such as a plastic or TYVEK® bag. The container and its contents are then placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, or high-energy electrons. The radiation kills bacteria on the instrument and in the container. The sterilized instrument can then be stored in the sterile container. The sealed container keeps the instrument sterile until it is opened in the medical facility.

It is preferred that device is sterilized. This can be done by any number of ways known to those skilled in the art including beta or gamma radiation, ethylene oxide, steam.

One skilled in the art will appreciate further features and advantages of the disclosure based on the above-described embodiments. Accordingly, the disclosure is not to be limited by what has been particularly shown and described, except as indicated by the appended claims. Additionally, while the present disclosures generally discuss passing suture insertion or implant devices and sutures through the paths formed between openings of the housing and openings of the cannula, a person skilled in the art, in view of the present disclosures, would understand that other devices, instruments, and the like can be passed between the openings and other features of the surgical access device without departing from the spirit of the present disclosure. All publications and references cited herein are expressly incorporated herein by reference in their entirety.

What is claimed is:

1. A surgical access device, comprising:

(a) a housing having at least one elongate opening formed therein;

(b) a cannula extending distally from the housing along a central longitudinal axis and having at least one sealed opening extending through a sidewall thereof, wherein the cannula communicates with an interior of the housing to define a working channel sized to receive a surgical instrument therethrough; and

(c) an adjustable entry port disposed within the at least one elongate opening, the adjustable entry port and the at least one sealed opening of the cannula being configured to form a suture path such that a suture can be passed from an outside environment, through the adjustable entry port, through the at least one sealed opening of the cannula, and to a surgical site,

wherein the adjustable entry port is moveable within the at least one elongate opening in a direction parallel to the central longitudinal axis to a plurality of locations within the at least one elongate opening to vary an angle that is formed by the suture path and the central longitudinal axis.

2. The surgical access device of claim 1, further comprising a rotary dial configured to move the adjustable entry port with respect to the at least one elongate opening.

3. The surgical access device of claim 2, wherein the rotary dial is disposed between a proximal end of the housing and a proximal end of the cannula and has a portion thereof that extends radially outward from a sidewall of the housing such that the portion can be operable to move the adjustable entry port with respect to the at least one elongate opening.

4. The surgical access device of claim 2, wherein the rotary dial further comprises at least one opening extending from a proximal end of the rotary dial through to a distal end of the rotary dial, the opening intersecting the suture path so that it receives a suture passed through the adjustable entry port and into the cannula.

5. The surgical access device of claim 4, wherein a diameter of the at least one opening extending from a

33

proximal end of the rotary dial through to a distal end of the rotary dial is greater than at least half of a radius of the rotary dial.

6. The surgical access device of claim 4, wherein the rotary dial further comprises at least one cam disposed on a surface of the rotary dial, the cam having a ramped configuration that impacts a location of the adjustable entry port with respect to the at least one elongate opening.

7. The surgical access device of claim 1, wherein a value of the angle that is formed by the suture path and the central longitudinal axis extending through the cannula impacts a value of a bite angle at which a suture passed through the suture path and into tissue surrounding the cannula enters the tissue, and wherein the adjustable entry port is configured to change a value of the bite angle.

8. The surgical access device of claim 1, wherein the plurality of locations that the adjustable entry port moves with respect to the at least one elongate opening further comprises a plurality of pre-set, keyed positions, the plurality of pre-set, keyed positions providing for different values of the angle that is formed by the suture path and the central longitudinal axis extending through the cannula.

9. The surgical access device of claim 1, the device further comprising a seal disposed within the working channel and configured to seal the working channel when no instrument is disposed therethrough.

10. The surgical access device of claim 9, wherein the at least one elongate opening formed in the housing is disposed proximal of the seal and the at least one sealed opening formed in the cannula is disposed distal of the seal, the at least one elongate opening further being disposed on an opposed side of the device in comparison to the at least one sealed opening.

11. The surgical access device of claim 9, wherein the at least one elongate opening formed in the housing comprises a first elongate opening and a second elongate opening both disposed proximal of the seal, with the adjustable entry port being disposed within the first elongate opening, and the device further comprising a second adjustable entry port that is disposed within the second elongate opening,

wherein the at least one sealed opening extending through a sidewall of the cannula further comprises a first sealed opening and a second sealed opening both disposed distal of the seal, with the adjustable entry port and the second sealed opening being configured to form the suture path and the second adjustable entry port and the first sealed opening being configured to form a second suture path such that a suture can be passed from an outside environment, through the second adjustable entry port, through the first sealed opening of the cannula, and to a surgical site, and the second adjustable entry port being configured to move within the second elongate opening to a plurality of locations with respect to the second elongate opening such that different locations of the plurality of locations result in different values of an angle that is formed by the second suture path and the central longitudinal axis extending through the cannula, and

wherein the first elongate opening formed in the housing is disposed on an opposed side of the device in comparison to the second sealed opening in the cannula, and the second elongate opening formed in the housing is disposed on an opposed side of the device in comparison to the first sealed opening in the cannula.

34

12. The surgical access device of claim 11, further comprising:

a rotary dial configured to move the adjustable entry port with respect to the at least one elongate opening, the rotary dial having at least two openings extending from a proximal end of the rotary dial through to a distal end of the rotary dial, with a first opening of the at least two openings intersecting the suture path so that it receives a suture passed through the adjustable entry port and into the cannula, and a second opening of the at least two openings intersecting the suture path so that it receives a suture passed through the second adjustable entry port and into the cannula.

13. The surgical access device of claim 12, wherein the rotary dial further comprises at least two cams disposed on a surface of the rotary dial, opposed to each other, each cam having a ramped configuration that impacts a location of the respective adjustable entry ports with respect to the elongate openings of the suture paths that the openings intersect.

14. The surgical access device of claim 1, wherein the adjustable entry port is movable along a length of the at least one elongate opening.

15. The surgical access device of claim 1, further comprising an actuator operatively coupled with the adjustable entry port, wherein the actuator is operable to move the adjustable entry port within the at least one elongate opening.

16. A surgical access device, comprising:

(a) a housing having at least one elongate opening formed therein;

(b) a cannula extending distally from the housing and having at least one sealed opening extending through a sidewall thereof, the at least one elongate opening of the housing and the at least one sealed opening of the cannula being configured to form a suture path such that a suture can be passed from an outside environment, through the at least one elongate opening, through the at least one sealed opening of the cannula, and to a surgical site; and

(c) a rotary dial disposed between a proximal end of the housing and a proximal end of the cannula, the rotary dial being configured to adjust an angle formed by the suture path and a central longitudinal axis extending through the cannula by changing a location of entry of the at least one elongate opening.

17. The surgical access device of claim 16, wherein the housing and the cannula define a working channel extending therethrough that is sized and configured to receive a surgical instrument, the device further comprising a seal disposed within the working channel and configured to seal the working channel when no instrument is disposed therethrough.

18. The surgical access device of claim 17, wherein the at least one elongate opening formed in the housing is disposed proximal of the seal and the at least one sealed opening formed in the cannula is disposed distal of the seal, the at least one elongate opening further being disposed on an opposed side of the device in comparison to the at least one sealed opening.

19. The surgical access device of claim 18, wherein the at least one elongate opening formed in the housing comprises a first elongate opening and a second elongate opening both disposed proximal of the seal,

wherein the at least one sealed opening extending through a sidewall of the cannula further comprises a first sealed opening and a second sealed opening both

35

disposed distal of the seal, with the first elongate opening and the second sealed opening being configured to form the suture path and the second elongate opening and the first sealed opening being configured to form a second suture path such that a suture can be passed from an outside environment, through the second elongate opening, through the first sealed opening of the cannula, and to a surgical site,

wherein the first elongate opening formed in the housing is disposed on an opposed side of the device in comparison to the second sealed opening in the cannula, and the second elongate opening formed in the housing is disposed on an opposed side of the device in comparison to the first sealed opening in the cannula, and wherein the rotary dial is further configured to adjust an angle formed by the second suture path and the central longitudinal axis extending through the cannula by changing a location of entry of the second elongate opening.

20. The surgical access device of claim 19, wherein the rotary dial further comprises at least two openings extending from a proximal end of the rotary dial through to a distal end of the rotary dial, with a first opening of the at least two openings intersecting the suture path so that it receives a suture passed through the first elongate opening and into the cannula, and a second opening of the at least two openings intersecting the suture path so that it receives a suture passed through the second elongate opening and into the cannula.

21. The surgical access device of claim 20, wherein the rotary dial further comprises at least two cams disposed on a surface of the rotary dial, opposed to each other, each cam having a ramped configuration that correlates to the respective angles formed by the suture paths and the central longitudinal axis extending through the cannula.

22. The surgical access device of claim 16, wherein the rotary dial further comprises at least one opening extending from a proximal end of the rotary dial through to a distal end of the rotary dial, the opening intersecting the suture path so that it receives a suture passed through the at least one elongate opening and into the cannula.

23. The surgical access device of claim 22, wherein a diameter of the at least one opening extending from a proximal end of the rotary dial through to a distal end of the rotary dial is greater than at least half of a radius of the rotary dial.

24. The surgical access device of claim 22, wherein the rotary dial further comprises at least one cam disposed on a surface of the rotary dial, the cam having a ramped configuration that correlates to the angle formed by the suture path and the central longitudinal axis extending through the cannula.

25. The surgical access device of claim 16, wherein a value of the angle that is formed by the suture path and the central longitudinal axis extending through the cannula impacts a value of a bite angle at which a suture passed through the suture path and into tissue surrounding the cannula enters the tissue, and wherein the rotary dial is configured to change a value of the bite angle.

36

26. The surgical access device of claim 16, wherein the rotary dial further comprises a plurality of pre-set, keyed positions that provide for different values of the angle that is formed by the suture path and the central longitudinal axis extending through the cannula.

27. A surgical access device, comprising:

(a) a housing, wherein the housing includes:

(i) a housing side surface, and

(ii) a first opening extending through the housing side surface;

(b) a cannula extending distally from the housing along a central axis, wherein the cannula includes:

(i) a cannula side surface,

(ii) a central lumen, wherein the central lumen communicates with an interior of the housing to define a working channel sized to receive a surgical instrument therethrough, and

(iii) a second opening extending through the cannula side surface, wherein the second opening cooperates with the first opening to define a suture path that extends across the working channel; and

(c) an adjustment element coupled to the housing, wherein the adjustment element is selectively movable to adjust a suture path angle defined between the suture path and the central axis while the suture path remains configured to receive an instrument therethrough.

28. The surgical access device of claim 27, wherein the first opening comprises an elongate first opening, wherein the surgical access device further comprises an adjustable entry port disposed within the elongate first opening, wherein the adjustable entry port is configured to move along a length of the elongate first opening in response to movement of the adjustment element.

29. The surgical access device of claim 28, wherein the adjustable entry port is moveable in a direction parallel to the central axis.

30. The surgical access device of claim 28, wherein the adjustable entry port is moveable proximally within the elongate first opening to decrease the suture path angle, wherein the adjustable entry port is movable distally within the elongate first opening to increase the suture path angle.

31. The surgical access device of claim 28, wherein the second opening comprises an elongate second opening.

32. The surgical access device of claim 27, wherein the adjustment element comprises a rotating element operable to rotate relative to at least a portion of the housing.

33. The surgical access device of claim 32, wherein the rotating element is configured to rotate about the central axis.

34. The surgical access device of claim 32, further comprising an adjustable entry port disposed within the first opening, wherein the rotating element includes a cam feature operable to move the adjustable entry port within the first opening in response to rotation of the rotating element to thereby adjust the suture path angle.

35. The surgical access device of claim 27, wherein the adjustment element comprises a user-engageable portion that protrudes radially from the housing.

* * * * *