



- (51) International Patent Classification:
G01D 21/00 (2006.01) *G01M 3/00* (2006.01)
- (21) International Application Number:
PCT/US2016/067544
- (22) International Filing Date:
19 December 2016 (19.12.2016)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
14/984,088 30 December 2015 (30.12.2015) US
- (71) Applicant: ITRON, INC. [US/US]; 2111 N. Molter Road, Liberty Lake, WA 99019 (US).
- (72) Inventor: CORNWALL, Mark, K.; 2111 N. Molter Road, Liberty Lake, WA 99019 (US).
- (74) Agent: DESANTIS, Luanne, M.; ITRON, INC., 2111 N. Molter Road, Liberty Lake, WA 99019 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

- (54) Title: GAS LEAK DETECTION AND LOCATION DETERMINATION




FIG. 1

(57) Abstract: A method of gas detection includes receiving, by a data collection device, reports of detected concentrations of a particular gas from one or more gas sensing devices having one or more associated gas sensors, receiving an alarm from a gas sensing device indicating a detected concentration greater than a predetermined threshold, and receiving concentration updates from the alarming device at a rate faster than that provided by its predetermined reporting schedule. The method may further include sending a command to one or more gas sensing devices nearby the alarming device to send concentration updates. The method may further include determining a location of a gas leak by triangulating the received updates from the alarming device and the nearby devices based on their locations and/or creating and displaying a gas concentration map based on the received updates from the alarming device and the nearby devices and their locations.

GAS LEAK DETECTION AND LOCATION DETERMINATION

5

RELATED APPLICATIONS

[0001] This PCT international application is a continuation of U.S. Pat. Appl. No. 14/984,088, filed December 30, 2015, entitled "Gas Leak Detection and Location Determination."

10

FIELD OF THE DISCLOSURE

[0002] This disclosure relates generally to gas sensing and leak detection in a communications network.

15

BACKGROUND

[0003] Natural gas (i.e., methane (CH₄)) is considered one of the cleanest, safest, and most useful of energy sources. When burned, it produces a great deal of energy with fewer emissions than many other energy sources, and therefore it has many uses in residential, commercial, and industrial applications. One reason that natural gas is considered safe is its narrow combustion limits, which ensures predictability in use. Natural gas will only ignite when air contains between five and fifteen percent natural gas. Due to its combustible nature, however, there is still a risk of explosion when using natural gas, which makes it very important to quickly determine where gas leaks may be occurring. Other gases have similar properties and risks. There are some gas detection sensors currently available and/or currently being developed. However, these sensors are either high in power consumption, high in cost, or both. Widespread application of such sensors (e.g., one or more at every home, business, etc.) could be quite costly, and in some applications (e.g., for use with gas utility meters, which typically run on battery power) may not even be feasible.

30

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 is an illustration of a network environment in which example methods, apparatus, and articles of manufacture disclosed herein may be implemented, according to
5 embodiments of this disclosure.'

[0005] FIG. 2 is a flow diagram of an example gas leak detection process from the perspective of a gas sensing device, according to embodiments of this disclosure.

[0006] FIG. 3 is a flow diagram of an example leak rate tracking process from the perspective of a gas sensing device, according to embodiments of this disclosure.

10 [0007] FIG. 4 is a flow diagram of an example leak detection process from the perspective of a data collection device, according to embodiments of this disclosure.

[0008] FIG. 5 is a flow diagram of an example leak location determination process from the perspective of a data collection device, according to embodiments of this disclosure.

[0009] FIGs. 6A and 6B are block diagrams of example gas concentration maps, according
15 to embodiments of the present disclosure.

[0010] FIG. 7 is a flow diagram of an example leak rate tracking process from the perspective of a data collection device, according to embodiments of this disclosure.

[0011] FIG. 8 is a block diagram of an example gas sensing device, according to an embodiment of the present disclosure.

20 [0012] FIG. 9 is a block diagram of an example data collection device, according to an embodiment of the present disclosure.

[0013] In the drawings, the leftmost digit(s) of a reference number may identify the drawing in which the reference number first appears.

25

DETAILED DESCRIPTION

[0014] As lower cost, low power-consumption sensors (e.g., micro-electro-mechanical systems (MEMS) sensors), including some gas sensors, are being developed, useful applications for such sensors are needed. The following description discloses gas leak
30 detection applications in a communication system environment that may provide swift pinpointing of a location of a gas leak as well as other information that may minimize the risk of explosion and help save both lives and property.

[0015] Embodiments are now described with reference to the figures, where like reference numbers may indicate identical or functionally similar elements. While specific configurations and arrangements are discussed, it should be understood that this is done for illustrative purposes only. A person skilled in the relevant art will recognize that other configurations and arrangements can be used without departing from the spirit and scope of the description. It will be apparent to a person skilled in the relevant art that the technology disclosed herein can also be employed in a variety of other systems and applications other than what is described herein.

[0016] FIG. 1 illustrates an example data collection network 100 (e.g., an advanced meter reading (AMR) network or other similar network), according to embodiments. The network 100 may include a central office 102, which may be associated with a data collection/processing entity (e.g., a utility company in the case of an AMR network). The central office may communicate with network nodes through one or more networks 104, which may be the Internet or other network having widespread or local functionality. Network nodes may include nodes 106-114, which may include, for example, endpoint devices such as utility meters or other devices that may comprise sensors, actuators, etc. (e.g., gas sensing devices). These nodes/devices may be located at various locations (e.g., homes, businesses, etc.). Nodes/devices 106-114 may be configured in a mesh network, star network or other configuration. One or more of the network nodes (e.g., device 106) may be a data collector and/or concentrator that may be configured for communication (e.g., radio frequency (RF) communication, cellular communication, etc.) with a plurality of downstream devices 108-114, which may also be configured for similar communications. In an example operation, data collector 106 may receive data or other communications from endpoint devices 108-114 to be provided to a data collection device 116, (which may be located at central office 102) and/or a mobile data collection device 118, and vice versa. For example, for an AMR network, the collected data may include consumption data or other information associated with a utility meter (e.g., a gas utility meter), such as detected concentration amounts of a particular gas in the air. Additionally, data collector 106 may send software updates, firmware updates, instructions or other information (which may have been communicated to data collector 106 from data collection device 116 or 118, for example) to one or more of the endpoint devices 108-114. In an embodiment, one or more network nodes (e.g., devices 106-114) may be battery-operated devices.

[0017] In an expanded view, data collection device 116 (and/or mobile data collection device 118) may include, among other components, one or more controllers or processors 120, a memory 122, a communication system 124 (e.g., configured for RF communications, cellular communications, or another type of communications), and a display 126. Devices 106-114
5 may include, among other components, one or more controllers or processors 130, a memory 132, a communication system 134 (e.g., configured for RF communications, cellular communications, or another type of communications), and one or more sensors 138, which may include at least one gas sensor 140. Devices 106-114 may also include a global positioning system (GPS) and/or an altimeter device 142 to determine the location and/or altitude of the
10 device.

[0018] FIG. 2 is a flow diagram of an example gas leak detection process 200 from the perspective of a gas sensing device (e.g., devices 106-114), according to embodiments. At 202, a detected concentration amount (e.g., in parts per million (ppm) or as a percentage of the surrounding air) of a particular gas (e.g., methane) may be received from a gas sensor
15 associated with the gas sensing device. (In embodiments discussed herein, a detected concentration amount may be alternatively measured and/or presented as a percentage of the Lower Explosive Level (LEL) of the gas, at which 100% LEL is an amount at which there will be an explosion if a spark is present, and at about 10% LEL, the measured gas concentration may be considered great enough to indicate presence of the gas with a need to alarm and/or
20 prompt an investigation.) At 204, it may be determined whether the detected concentration is greater than a predetermined threshold. For example, for methane, which may ignite at 5%, the predetermined threshold may be set at a value lower than 5% (e.g., 0.5% or 5000 ppm). If the detected concentration is greater than the threshold, at 212, an alarm may be sent to a data collection device (e.g., device 116 and/or 118). A detected concentration greater than the
25 threshold may indicate a possible (and potentially dangerous) gas leak and is reported as it may warrant further investigation. Due to potential urgency, updated gas concentration reports may be sent to the data collection device at a faster rate than its normal reporting schedule at 216. This may be done automatically by the gas sensing device, or in an alternative embodiment, this may be done in response to receiving a command (at 214) from the data collection device
30 to send updates of detected concentration at the faster rate. Referring back to decision block 204, if the detected concentration is not greater than the predetermined threshold, at 206, the detected concentration may be provided to the data collection device (e.g., per its normal reporting schedule), and processing may return to 202, where the next gas concentration report

may be received. In an embodiment, the gas sensing device may receive a command from the data collection device to send updates of detected concentration at a faster rate than its normal reporting schedule (at 208). This command may have been sent by the data collection device in response to the data collection device receiving an alarm from another (e.g., neighboring or nearby) gas sensing device that its detected concentration of the gas was greater than the predetermined threshold. In response to the command at 208, the gas sensing device may send updates of detected concentration to the data collection device at the faster rate at 210. In an alarm situation, it may be very useful for investigative purposes to also collect data from neighboring or nearby gas sensing devices in order to more quickly identify the location of a possible (and potentially dangerous) gas leak. An alarm may be cleared, or cancelled, by the data collection device, or by the gas sensing device, if there is no longer any safety risk, for example. Once an alarm is cancelled, the gas sensing device may go back to its normal reporting schedule.

[0019] FIG. 3 is a flow diagram of an example leak rate tracking process 300 from the perspective of a gas sensing device (e.g. any of devices 106-114), according to embodiments. Process 300 begins from block 216 of process 200 of FIG. 2. At 302, the gas sensing device may track a rate that the concentration of the gas is increasing or decreasing. At 304, the tracked rate may be sent to the data collection device (device 116 and/or 118). In an embodiment, the data collection device may determine from the tracked rate that the concentration of the gas is decreasing at a rate such that it no longer presents a safety concern. This may occur, for example, if a leak was repaired, if the gas was shut off in the location of the leak, or if the gas was detected due to the gas supply system providing temporary (usually very brief) venting in order to relieve built-up pressure in the system. If the data collection device determines there is no longer a safety risk, it may send a command to the gas sensing device to clear the alarm. Thus, at 306, a clear alarm command may be received from the data collection device. In an embodiment, the gas sensing device itself may determine that the tracked rate does not pose, or no longer poses, a safety concern and may clear the error itself and/or send a message to the data collection device that the alarm has been cancelled. In an embodiment, the tracked rate may be determined prior to an alarm being sent to the data collection device. If the tracked rate shows that the concentration of the gas is decreasing at a rate such that it does not present, or no longer presents, a safety concern, an alarm may not need to be sent to the data collection device.

[0020] FIG. 4 is a flow diagram of an example leak detection process 400 from the perspective of a data collection device (e.g., device 116 or 118), according to embodiments. At 402, the data collection device may receive reports of detected concentration (e.g., in parts per million (ppm) or as a percentage of the surrounding air, or as a percentage of LEL, etc.) of a particular gas (e.g., methane) from one or more gas sensing devices (e.g. devices 106-114, which may be located at various locations (e.g., homes, businesses, etc.)). The gas concentration reports may be received from each sending gas sensing device on a predetermined schedule respectively associated with each gas sensing device. At 404, an alarm may be received from one of the gas sensing devices indicating that a detected concentration of the gas is greater than a predetermined threshold. This may indicate a possible (and potentially dangerous) gas leak and is reported as it may warrant further investigation. In an embodiment, the data collection device, in response to receiving the alarm and due to potential urgency, may send, at 406, a command to the alarming gas sensing device to send updated gas concentration reports at a faster rate than its normal reporting schedule. At 408, the data collection device may receive updated gas concentration reports from the alarming gas sensing device at the faster rate. In an embodiment, the gas sensing device may automatically send updated reports without a request from the data collection device. Once there is no longer a safety concern, at 410, the data collection device may send a command to the alarming gas sensing device to clear the alarm. In an embodiment, the alarming gas sensing device may clear the alarm automatically once the detected concentration of the gas is no longer greater than the predetermined threshold.

[0021] FIG. 5 is a flow diagram of an example leak location determination process 500 from the perspective of a data collection device (e.g., device 116 or 118), according to embodiments. Process 500 begins from block 408 of process 400 of FIG. 4. At 502, a command may be sent from the data collection device to one or more gas sensing devices that are neighboring, or nearby, the alarming gas sensing device to send reports/updates of detected concentrations of the gas at a faster rate than their normal reporting schedules. At 504, the reports/updates may be received from the nearby gas sensing device(s) at the faster rate. At 506, the data collection device may determine a probable location of a gas leak. In an embodiment, the location of the gas sensing device with the highest reading may be a good indication of a location of a gas leak. In another embodiment, the location of a gas leak may be determined by triangulating the received updates from the alarming gas sensing device and the nearby gas sensing device(s) based on the device locations, weighting of received gas

concentration data, etc. The device locations may be determined in various ways known to a person of ordinary skill in the relevant arts (e.g., via cellular triangulation, a GPS and/or altimeter associated with each device, etc.). For example, latitude and longitude values for each gas sensing device may be known or recorded at the time of installation, and these values may be averaged to determine a possible location of a gas leak. For a more accurate location determination, the latitude and longitude values may be weighted by the level of concentration measured at each device. The triangulation may also be based on other factors, including wind speed and direction, street layout, building topology (e.g., tallness/configurations of buildings), etc. Optionally, at 508, the data collection device may create and display a gas concentration map based on the received updates from the alarming gas sensing device and the nearby gas sensing device(s) and on the device locations. The gas concentration map may be further based on wind speed/direction, street layout, building topology, etc. The gas concentration map may help a user (e.g., utility/field technician) to visually identify a probable location of a gas leak in an expedient manner. Once there is no longer a need for data from the nearby gas sending device(s), at 510, the data collection device may send a command to the nearby gas sensing device(s) to go back to reporting per predetermined reporting schedule(s). At 512, the process may continue at 410 of FIG. 4.

[0022] Two examples of gas concentration maps are shown in FIGs. 6A and 6B, according to embodiments. FIG. 6A includes a gas concentration map 646 that depicts a housing community, showing locations of houses along neighborhood streets. The houses may be equipped with gas sensing devices, such as devices 106-114 of FIG. 1. The gas sensing devices may have been included in conjunction with gas metering devices installed at each house, for example. The houses on map 646 show readings of the respective gas sensing devices (i.e., detected concentrations of the gas) at each location. The readings may be updated on a predetermined basis to show reading changes (e.g., every 20 seconds or other set interval, which may be user selectable). In the embodiment shown, the readings are shown as a concentration or volume percentage of the surrounding air. In other embodiments, readings may be shown in other units (e.g., parts per million (ppm)). In an embodiment, a user may be able to choose what units are shown. According to the example shown in FIG. 6A, the gas sensing device at house 648 is showing the highest reading, which may indicate the location of a gas leak. Based on the readings at the other houses, it appears that there may be wind coming from the northwest that may be blowing the gas in a southeast direction. In an example, if triangulation is used based on the shown data, and taking the wind into account, the results of

the triangulation analysis may indicate that a gas leak may be occurring in the vicinity of houses 648, 650, and 652, for example. As can be seen in FIG. 6A, house 654 is not showing a reading. This may be because there is no gas sensing device at that location, or it may indicate that the gas sensing device at that location is faulty or not operational. Thus, while gas concentration map 646 may primarily be used to pinpoint a location of a possible gas leak, it may also indicate other problems in the system that may warrant repair or correction.

[0023] FIG. 6B includes a gas concentration map 656 that depicts a layout of an example multi-floor building having a parking level (which may be underground), a lobby level (e.g., as a first floor), and four additional floor levels. One or more gas sensing devices may be installed on one or more levels. As gas metering devices for a multi-floor building are normally banked together in one or more locations, the gas sensing devices may not be associated with a particular metering device, or any metering device. In the example shown, two gas sensing devices are located on each of the parking and lobby levels, and one gas sensing device is located on each of the additional floor levels. This is by way of example and not limitation, as any number of gas sensing devices may be used at any locations (e.g., in each individual apartment or business office, etc.). As in the example shown, each depicted level of the building may show readings of the respective gas sensing devices at each location. The readings may be updated on a predetermined basis to show reading changes (e.g., every 20 seconds or other set interval, which may be user selectable). In the embodiment shown, the readings are shown as a concentration or volume percentage of the surrounding air. In other embodiments, readings may be shown in other units (e.g., parts per million (ppm)). In an embodiment, a user may be able to choose what units are shown. The exact global positions of the gas sensing devices may be very close, as they are all located in the same multi-floor building. However, their altitudes within the building may be distinguishably different. In the example shown, the gas sensing device on Floor 2 indicates the highest concentration of a gas in the air, and the gas sensing device on the east side of the lobby indicates the next highest concentration. This data (e.g., when triangulated) may indicate the presence of a gas leak somewhere between Floor 2 and the lobby, likely on the east side. With this information, if an evacuation is warranted, it would likely be safest to have occupants evacuate using stairwells located on the west side of the building. Thus, a concentration map may be useful in determining public safety options as well as determining a location of a possible gas leak.

[0024] While gas concentration maps 646 and 656 may be used by both a data collection device 116 (e.g., located at a central office) and/or a mobile data collection device 118 (e.g., a

mobile or handheld device used by a field technician), these maps may be especially useful, and quite important, when used on a mobile data collection device 118 in the field, because having this data in real time in the vicinity of a potential gas leak may help a field technician make quick decisions regarding whether, and how, an immediate evacuation of the area needs to occur and/or whether it is safe enough to allow technicians to be working in the area. Having this capability may allow for real-time crisis management of a potentially very dangerous situation that may not be as efficient if managed solely by a remote central office.

[0025] FIG. 7 is a flow diagram of an example leak rate tracking process 700 from the perspective of a data collection device, according to embodiments. Process 700 begins from block 408 of process 400 of FIG. 4. At 702, a rate that the detected concentration of the gas at the alarming sensing device is increasing or decreasing may be tracked, or received from the alarming sensing device. At 704, a clear alarm command may be sent to the alarming gas sensing device when the tracked rate is decreasing at a rate that indicates no safety concern. This may occur, for example, if a leak was repaired, if the gas was shut off in the location of the leak, or if the gas was detected due to the gas supply system providing temporary (usually very brief) venting in order to relieve built-up pressure in the system.

[0026] One or more features disclosed herein may be implemented in hardware, software, firmware, and/or combinations thereof, including discrete and integrated circuit logic, application specific integrated circuit (ASIC) logic, and microcontrollers, and may be implemented as part of a domain-specific integrated circuit package, or a combination of integrated circuit packages. The terms software and firmware, as used herein, refer to a computer program product including at least one computer readable medium having computer program logic, such as computer-executable instructions, stored therein to cause a computer system to perform one or more features and/or combinations of features disclosed herein. The computer readable medium may be transitory or non-transitory. An example of a transitory computer readable medium may be a digital signal transmitted over a radio frequency or over an electrical conductor, through a local or wide area network, or through a network such as the Internet. An example of a non-transitory computer readable medium may be a compact disk, a flash memory, SRAM, DRAM, a hard drive, a solid state drive, or other data storage device.

[0027] A processing platform of a data collection device (e.g., data collection device 116 or mobile data collection device 118 of FIG. 1), and/or a gas sensing device (e.g., any of devices 106-114) may be embodied in any type of mobile and/or non-mobile computing device. Examples of mobile devices may include, but are not to be limited to, laptop computers, ultra-

laptop computers, tablets, touch pads, portable computers, handheld computers, palmtop computers, personal digital assistants (PDAs), e-readers, cellular telephones, combination cellular telephone/PDAs, mobile smart devices (e.g., smart phones, smart tablets, etc.), mobile internet devices (MIDs), mobile messaging devices, mobile data communication devices, mobile media playing devices, cameras, mobile gaming consoles, wearable devices, mobile industrial field devices, etc. Examples of non-mobile devices may include, but are not to be limited to, servers, personal computers (PCs), Internet appliances, televisions, smart televisions, data communication devices, media playing devices, gaming consoles, industrial field devices, etc.

[0028] FIG. 8 is a block diagram of an example gas sensing device, according to embodiments. Processing platform 800 may include one or more processors 830, memory 832, one or more secondary storage devices 874, one or more input/output devices 872, and/or one or more communication interfaces 834, in communication via a bus, line, or similar implementation (not shown). Processing platform 800 may also include a power supply 884, which may include an interface to an electricity source and/or may include one or more batteries. Platform 800 may also include one or more sensors 838, including at least one gas sensor, for example. In an embodiment, platform 800 may also include a GPS (for location determination) and/or an altimeter (for altitude determination (e.g., which floor(s) of a building)) device 842. In an example where a gas sensing device is incorporated into a utility meter, platform 800 may also include one or more registers 882 for flow measurement, for example.

[0029] Processor(s) 830 may be implemented by, for example but not limitation, one or more integrated circuits, logic circuits, microprocessors, controllers, etc. Processor(s) 830 may include a local memory 876 (e.g., a cache). Memory 832 may include a volatile and/or a non-volatile memory. Volatile memory may be implemented by, for example but not limitation, Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS Dynamic Random Access Memory (RDRAM) and/or any other type of random access memory device. Non-volatile memory may be implemented by flash memory and/or any other desired type of memory device. Access to memory 832 may be controlled by a memory controller (not shown). Data stored in local memory 876 and/or memory 832 may be used by processor(s) 830 to facilitate sensor data collection functions, metering functions if embodied in a utility meter, and/or communications, according to embodiments of this disclosure.

[0030] Input/output device(s) 872 may allow a user to interface with processor(s) 830. Input devices may allow a user to enter data and/or commands for processor(s) 830. Input devices may include, for example, an audio sensor, a microphone, a camera (e.g., still, video, etc.), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint, a voice
5 recognition system, etc. Output devices may provide or present information to a user. Output devices may include, for example, display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display, a cathode ray tube display (CRT), a touchscreen, a tactile output device, a printer, speakers, etc.). The input/output device(s) 872 may be connected to processor(s) 830, for example, with an interface circuit (not shown). The
10 interface circuit may be implemented by any type of interface standard, such as, for example, an Ethernet interface, a universal serial bus (USB), a PCI express interface, etc. For use with an output device, the interface circuit may include a graphics driver card, chip, and/or processor.

[0031] Communication interface(s) 834 may be implemented in hardware or a combination
15 of hardware and software, and may provide wired or wireless network interface(s) to one or more networks, such as network(s) 104 of FIG. 1. Communication interface(s) 834 may be a part of, or connected with, the interface circuit discussed above, and/or may include or connect with communication devices such as a transmitter, a receiver, a transceiver, a modem and/or network interface card to facilitate exchange of data with external devices (e.g., computing
20 devices of any kind) via a network, such as network(s) 104.

[0032] Secondary storage device(s) 874 may store processing logic 878 (e.g., software) to be executed by processor(s) 830, and/or may store data 880. Processing logic 878 and data 880 may be used by processor(s) 830 to facilitate sensor data collection functions, metering functions if embodied in a utility meter, and/or communications between devices, according to
25 embodiments of this disclosure. Processing logic 878 may include instructions for executing the methodology described herein for a gas sensing device, for example. Examples of secondary storage device(s) 874 may include one or more hard drive disks, compact disk (CD) drives, digital versatile disk (DVD) drives, Blu-ray disk drives, redundant array of independent disks (RAID) systems, floppy disk drives, flash drives, etc. Data and/or processing logic may
30 be stored on a removable tangible computer readable storage medium (e.g., a floppy disk, a CD, a DVD, a Blu-ray disk, etc.) using one or more of the secondary storage device(s) 874.

[0033] FIG. 9 is a block diagram of an example mobile or non-mobile device data collection device, according to embodiments. Processing platform 900 may include one or

more processors 920, memory 922, one or more secondary storage devices 974, one or more input/output devices 972, and/or one or more communication interfaces 924, in communication via a bus, line, or similar implementation (not shown). Processing platform 900 may also include a power supply (not shown), which may include an interface to an electricity source and/or may include one or more batteries.

[0034] Processor(s) 920 may be implemented by, for example but not limitation, one or more integrated circuits, logic circuits, microprocessors, controllers, etc. Processor(s) 920 may include a local memory 976 (e.g., a cache). Memory 922 may include a volatile and/or a non-volatile memory. Volatile memory may be implemented by, for example but not limitation, Synchronous Dynamic Random Access Memory (SDRAM), Dynamic Random Access Memory (DRAM), RAMBUS Dynamic Random Access Memory (RDRAM) and/or any other type of random access memory device. Non-volatile memory may be implemented by flash memory and/or any other desired type of memory device. Access to memory 922 may be controlled by a memory controller (not shown). Data stored in local memory 976 and/or memory 922 may be used by processor(s) 920 to facilitate data collection functions and/or communications, according to embodiments of this disclosure.

[0035] Input/output device(s) 972 may allow a user to interface with processor(s) 920. Input devices may allow a user to enter data and/or commands for processor(s) 920. Input devices may include, for example, an audio sensor, a microphone, a camera (e.g., still, video, etc.), a keyboard, a button, a mouse, a touchscreen, a track-pad, a trackball, isopoint, a voice recognition system, etc. Output devices may provide or present information to a user. Output devices may include, for example, display devices (e.g., a light emitting diode (LED), an organic light emitting diode (OLED), a liquid crystal display, a cathode ray tube display (CRT), a touchscreen, a tactile output device, a printer, speakers, etc.). The input/output device(s) 972 may be connected to processor(s) 920, for example, with an interface circuit (not shown). The interface circuit may be implemented by any type of interface standard, such as, for example, an Ethernet interface, a universal serial bus (USB), a PCI express interface, etc. For use with an output device, the interface circuit may include a graphics driver card, chip, and/or processor.

[0036] Communication interface(s) 924 may be implemented in hardware or a combination of hardware and software, and may provide wired or wireless network interface(s) to one or more networks, such as network(s) 104 of FIG. 1. Communication interface(s) 924 may be a part of, or connected with, the interface circuit discussed above, and/or may include or connect

with communication devices such as a transmitter, a receiver, a transceiver, a modem and/or network interface card to facilitate exchange of data with external devices (e.g., computing devices of any kind) via a network, such as network(s) 104.

5 [0037] Secondary storage device(s) 974 may store processing logic 978 (e.g., software) to be executed by processor(s) 920, and/or may store data 980. Processing logic 978 and data 980 may be used by processor(s) 920 to facilitate data collection functions and/or communications between devices, according to embodiments of this disclosure. Processing logic 978 may include instructions for executing the methodology described herein for a data collection device, for example. Examples of secondary storage device(s) 974 may include one or more
10 hard drive disks, compact disk (CD) drives, digital versatile disk (DVD) drives, Blu-ray disk drives, redundant array of independent disks (RAID) systems, floppy disk drives, flash drives, etc. Data and/or processing logic may be stored on a removable tangible computer readable storage medium (e.g., a floppy disk, a CD, a DVD, a Blu-ray disk, etc.) using one or more of the secondary storage device(s) 974.

15 [0038] The embodiments described herein provide quick detection and location identification of gas leaks, using a low-cost, low-power-consumption solution that may contribute to public safety and possibly save lives. The particular examples and scenarios used in this document are for ease of understanding and are not to be limiting. Though described for use with data collection from battery-powered devices used for gas utility metering, features
20 described herein may be used in many other contexts and situations that may or may not involve battery power or gas utility metering. The power/cost-saving features discussed herein may be beneficial in many other systems involving sensing devices of many types, including other utility metering systems and other types of systems.

[0039] Although certain example methods, apparatus and articles of manufacture have
25 been disclosed herein, the scope of coverage of this patent is not limited thereto. On the contrary, this patent covers all methods, apparatus and articles of manufacture fairly falling within the scope of the claims of this patent.

What Is Claimed Is:

1. A data collection device (116, 118, 900), comprising:
 - at least one processor (120, 920);
 - 5 a communications system (124, 924) communicably coupled with the at least one processor, the communications system capable of communicating with one or more gas sensing devices (106, 108, 110, 112, 114, 800), over a network (104); and
 - a memory (122, 922) communicably coupled with the at least one processor, the memory configured to store detected concentrations of a particular gas reported by gas sensors
 - 10 (140) associated with the one or more gas sensing devices,
 - wherein the at least one processor is configured to:
 - receive reports of detected concentrations of the gas from the one or more gas sensing devices in accordance with one or more predetermined schedules respectively associated with the one or more gas sensing devices;
 - 15 receive an alarm from an alarming gas sensing device of the one or more gas sensing devices indicating that a detected concentration the gas is greater than a predetermined threshold; and
 - receive updated reports of detected concentrations of the gas from the alarming gas sensing device at a rate faster than that provided by the predetermined schedule
 - 20 respectively associated with the alarming gas sensing device.
2. The data collection device (116, 118, 900) of claim 1, wherein the at least one processor (120, 920) is further configured to:
 - send a command to the alarming gas sensing device (106, 108, 110, 112, 114, 800) to
 - 25 send the updated reports at the faster rate.

3. The data collection device (116, 118, 900) of claim 1, wherein the at least one processor (120, 920) is further configured to:

send a command to one or more gas sensing devices (106, 108, 110, 112, 114, 800) nearby the alarming gas sensing device to send updated reports of detected concentrations of the gas at respective rates that are faster than that provided by the predetermined schedules respectively associated with the one or more gas sensing devices nearby the alarming gas sensing device; and

receive the updated reports of detected concentrations of the gas from the gas sensing devices nearby the alarming gas sensing device at the faster rates.

10

4. The data collection device (116, 118, 900) of claim 3, wherein the at least one processor (120, 920) is further configured to:

determine a location of a gas leak by triangulating the received updated reports from the alarming gas sensing device (106, 108, 110, 112, 114, 800) and the nearby gas sensing devices based on the locations of the alarming gas sensing device and the nearby gas sensing devices.

15

5. The data collection device (116, 118, 900) of claim 3, further comprising a display (972), and wherein the at least one processor is further configured to:

create and display a gas concentration map (646, 656) based on the received updated reports from the alarming gas sensing device (106, 108, 110, 112, 114, 800) and the nearby gas sensing devices and on the locations of the alarming gas sensing device and the nearby gas sensing devices.

20

6. The data collection device (116, 118, 900) of claim 5, wherein the gas concentration map (646, 656) takes into account one or more of wind speed and direction, street layout, or building topology.

25

7. The data collection device (116, 118, 900) of claim 1, wherein the at least one processor (120, 920) is further configured to at least one of:

receive, from the alarming gas sensing device (106, 108, 110, 112, 114, 800), a tracked rate that the detected concentration of the gas at the alarming gas sensing device is increasing or decreasing; or

track the rate that the detected concentration of the gas at the alarming gas sensing device is increasing or decreasing.

8. The data collection device (116, 118, 900) of claim 7, wherein the at least one processor (120, 920) is further configured to:

send a clear alarm command to the alarming gas sensing device (106, 108, 110, 112, 114) when the tracked rate at the alarming gas sensing device is decreasing at a rate that indicates no safety concern.

9. The data collection device (116, 118, 900) of claim 1, wherein the data collection device is a computing device (116) at a central utility office (102).

10. The data collection device (116, 118, 900) of claim 1, wherein the data collection device is a mobile field computing device (118), and wherein the at least one processor (120, 920) is further configured to:

poll one or more of the gas sensing devices (106, 108, 110, 112, 114, 800) for detected concentrations of the gas.

11. A method of gas detection, comprising:

receiving, by a processor (120, 920) of a data collection device (116, 118, 900), reports of detected concentrations of a particular gas from one or more gas sensing devices (106, 108, 110, 112, 114, 800) having one or more associated gas sensors (140), the reports received in
5 accordance with one or more predetermined schedules respectively associated with the one or more gas sensing devices;

receiving, by the processor, an alarm from an alarming gas sensing device of the one or more gas sensing devices indicating that a detected concentration of the gas is greater than a predetermined threshold; and

10 receiving updated reports of detected concentrations of the gas from the alarming gas sensing device at a rate faster than that provided by the predetermined schedule respectively associated with the alarming gas sensing device.

12. The method of claim 11, further comprising:

15 sending, by the processor (120, 920), a command to the alarming gas sensing device (106, 108, 110, 112, 114, 800) to send the updated reports at the faster rate.

13. The method of claim 11, further comprising:

20 sending, by the processor (120, 920), a command to one or more gas sensing devices (106, 108, 110, 112, 114, 800) nearby the alarming gas sensing device to send updated reports of detected concentrations of the gas at respective rates that are faster than that provided by the predetermined schedules respectively associated with the one or more gas sensing devices nearby the alarming gas sensing device; and

25 receiving the updated reports of detected concentrations of the gas from the gas sensing devices nearby the alarming gas sensing device at the faster rates.

14. The method of claim 13, further comprising at least one of:

determining a location of a gas leak by triangulating the received updated reports from the alarming gas sensing device (106, 108, 110, 112, 114, 800) and the nearby gas sensing devices based on the locations of the alarming gas sensing device and the nearby gas sensing
5 devices; or

creating and displaying a gas concentration map (646, 656) based on the received updated reports from the alarming gas sensing device and the nearby gas sensing devices and on the locations of the alarming gas sensing device and the nearby gas sensing devices.

10 15. The method of claim 11, further comprising at least one of:

receiving, by the processor (120, 920), from the alarming gas sensing device (106, 108, 110, 112, 114, 800), a tracked rate that the detected concentration of the gas at the alarming gas sensing device is increasing or decreasing;

tracking, by the processor, the rate that the detected concentration of the gas at the
15 alarming gas sensing device is increasing or decreasing; or

sending, by the processor, a clear alarm command to the alarming gas sensing device when the tracked rate is decreasing at a rate that indicates no safety concern.

16. A computer-readable medium (974) having computer program logic (978) stored
20 thereon, the computer program logic including instructions to cause a processor (120, 920) of a data collection device (116, 118, 900) to execute the method of any of claims 11-15.

17. A gas sensing device (106, 108, 110, 112, 114, 800), comprising:

at least one processor (130, 830);

25 a communications system (134, 834) communicably coupled with the at least one processor, the communications system capable of communicating with at least one other device, including a data collection device (116, 118, 900), over a network (104); and

a memory (132, 832) communicably coupled with the at least one processor, the memory configured to store detected concentrations of a particular gas detected by at least one
30 associated gas sensor (140),

wherein the at least one processor is configured to send reports of the detected concentrations of the gas to the data collection device per a predetermined schedule or in response to an unscheduled request, and

wherein the at least one processor is further configured to, when a detected concentration of the gas is greater than a predetermined threshold,

trigger and send an alarm to the data collection device; and

5 send updated reports of the detected concentrations of the gas to the data collection device at a rate faster than that provided by the predetermined schedule.

18. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the gas sensor (140) is a micro-electro-mechanical systems (MEMS) sensor.

10 19. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the at least one processor (130, 830) is further configured to send the updated reports to the data collection device (116, 118, 900) at the faster rate automatically upon the triggering of the alarm.

15 20. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the at least one processor (130, 830) is further configured to send the updated reports to the data collection device (116, 118, 900) at the faster rate based on a command from the data collection device in response to the data collection device receiving the alarm.

20 21. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the at least one processor (130, 830) is further configured to track a rate that the detected concentration of the gas is increasing or decreasing.

25 22. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 21, wherein the at least one processor (130, 830) is further configured to receive a clear alarm command from the data collection device (116, 118, 900) when the data collection device determines that the tracked rate is decreasing at a rate that indicates no safety concern.

30 23. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the at least one processor (130, 830) is further configured to send the reports of detected concentrations of the gas to the data collection device (116, 118, 900) at a faster rate than that of the predetermined schedule in response to an alarm received by the data collection device indicating a possible gas leak detected by a nearby gas sensing device.

24. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the data collection device (116, 118, 900) is a computing device at a central utility office (102).

25. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the data
5 collection device (116, 118, 900) is a mobile field computing device (118).

26. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the gas sensing device is part of a gas metering device.

10 27. The gas sensing device (106, 108, 110, 112, 114, 800) of claim 17, wherein the gas is methane.

28. A method of gas detection, comprising:

15 sending, by a processor (130, 830) of a gas sensing device (106, 108, 110, 112, 114, 800) to a data collection device (116, 118, 900), reports of detected concentrations of a particular gas by an associated gas sensor (140) in communication with the processor, the sending being per a predetermined schedule or in response to an unscheduled request by the data collection device; and

20 when a detected concentration of the gas is greater than a predetermined threshold, triggering and sending, by the processor, an alarm to the data collection device; and

25 sending, by the processor, updated reports of detected concentrations of the gas to the data collection device at a rate faster than that provided by the predetermined schedule.

29. The method of claim 28, wherein the sending of the updated reports is automatic upon the triggering of the alarm.

30 30. The method of claim 28, wherein the sending of the updated reports is based on a command received from the data collection device (116, 118, 900) in response to the data collection device receiving the alarm.

31. The method of claim 28, further comprising:
tracking a rate that the detected concentration of the gas is increasing or decreasing;
and
providing the tracked rate to the data collection device (116, 118, 900).

5

32. The method of claim 31, further comprising:
receiving a clear alarm command from the data collection device (116, 118, 900) when
the data collection device determines that the tracked rate is decreasing at a rate that indicates
no safety concern.

10

33. The method of claim 28, further comprising:
sending the reports of detected concentrations of the gas at a rate faster than that of the
predetermined schedule in response to a command received from the data collection device
(116, 118, 900) that was sent in response to the data collection device receiving an alarm
15 indicating a possible gas leak detected by a nearby gas sensing device (106, 108, 110, 112, 114,
800).

34. A computer-readable medium (874) having computer program logic (878) stored
thereon, the computer program logic including instructions to cause a processor (130, 830) of
20 a gas sensing device (106, 108, 110, 112, 114, 800) to execute the method of any of claims 28-
33.




FIG. 1

2 / 9




FIG. 2

3 / 9




FIG. 3

4 / 9




FIG. 4

5 / 9




FIG. 5




FIG. 6A




FIG. 6B

7 / 9




FIG. 7




FIG. 8




FIG. 9

INTERNATIONAL SEARCH REPORT

International application No

PCT/US2016/067544

A. CLASSIFICATION OF SUBJECT MATTER

INV. G01D21/00 G01M3/00
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G01D G01M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 2 661 093 A2 (ITRON INC [US]) 6 November 2013 (2013-11-06)	1-16
A	figures 1, 14-16, 21,22 claims abstract paragraphs [0048] - [0052], [0096] - [0126]	17-34
A	----- US 2004/173006 A1 (MCCOY FRED GRANT [US] ET AL) 9 September 2004 (2004-09-09) figures claims abstract ----- -/-	1-34



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

29 March 2017

Date of mailing of the international search report

13/04/2017

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Moulara, Guilhem

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2016/067544

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2007/000310 A1 (YAMARTINO STEPHEN J [US] ET AL) 4 January 2007 (2007-01-04) figures claims paragraphs [0024] - [0032] -----	1-34
A	US 2008/168826 A1 (SAIDI ALI [US] ET AL) 17 July 2008 (2008-07-17) abstract paragraphs [0016] - [0027] claims -----	1-34
A	WO 2006/099632 A2 (QUALCOMM INC [US]; PERSICO CHARLES J [US]) 21 September 2006 (2006-09-21) abstract -----	1-34

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2016/067544

Patent document cited in search report		Publication date		Patent family member(s)		Publication date
EP 2661093	A2	06-11-2013	EP	2661093	A2	06-11-2013
			US	2013297771	A1	07-11-2013
			WO	2013165814	A1	07-11-2013

US 2004173006	A1	09-09-2004	CN	1784594	A	07-06-2006
			US	2004173006	A1	09-09-2004
			US	2004221642	A1	11-11-2004
			US	2004226345	A1	18-11-2004

US 2007000310	A1	04-01-2007	CA	2612778	A1	11-01-2007
			CN	101223431	A	16-07-2008
			EP	1896819	A1	12-03-2008
			JP	2009501319	A	15-01-2009
			KR	20080021713	A	07-03-2008
			TW	200702651	A	16-01-2007
			US	2007000310	A1	04-01-2007
			WO	2007005188	A1	11-01-2007

US 2008168826	A1	17-07-2008	US	2008168826	A1	17-07-2008
			WO	2008088664	A1	24-07-2008

WO 2006099632	A2	21-09-2006	AU	2006225107	A1	21-09-2006
			CA	2601203	A1	21-09-2006
			EP	1859294	A2	28-11-2007
			TW	200644654	A	16-12-2006
			US	2006211430	A1	21-09-2006
			US	2011070896	A1	24-03-2011
			WO	2006099632	A2	21-09-2006
