




(86) Date de dépôt PCT/PCT Filing Date: 2007/12/20
 (87) Date publication PCT/PCT Publication Date: 2008/07/03
 (45) Date de délivrance/Issue Date: 2012/03/27
 (85) Entrée phase nationale/National Entry: 2009/06/22
 (86) N° demande PCT/PCT Application No.: DK 2007/000559
 (87) N° publication PCT/PCT Publication No.: 2008/077403
 (30) Priorités/Priorities: 2006/12/22 (DK PA 2006 01705);
 2007/08/10 (DK PA 2007 01142)

(51) Cl.Int./Int.Cl. *F03D 1/06* (2006.01),
F03D 11/00 (2006.01)
 (72) Inventeurs/Inventors:
 GODSK, KRISTIAN BALSCHMIDT, DK;
 NIELSEN, THOMAS STEINICHE BJERTRUP, DK
 (73) Propriétaire/Owner:
 VESTAS WIND SYSTEMS A/S, DK
 (74) Agent: BERESKIN & PARR LLP/S.E.N.C.R.L.,S.R.L.

(54) Titre : EOLIENNE MUNIE DE PALES DE ROTOR EQUIPEES D'AILETTES ET PALES POUR UN TEL ROTOR
 (54) Title: WIND TURBINE WITH ROTOR BLADES EQUIPPED WITH WINGLETS AND BLADES FOR SUCH ROTOR



(57) Abrégé/Abstract:

A wind turbine is disclosed comprising a rotor with wind turbine blades each having a root end connected to a hub of the wind turbine and a tip end, the tip end of each of which being equipped with a winglet extending a distance in a direction perpendicularly

(57) **Abrégé(suite)/Abstract(continued):**

to a longitudinal direction of the blade. A new and much more slim design of the outer part of the wind turbine blade is disclosed, i.e. with a shorter chord length designed within a narrow band of values defined with respect to the length of the winglet, i.e. the extension in the direction transverse to the longitudinal direction of the blade.

COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
3 July 2008 (03.07.2008)

PCT

(10) International Publication Number
WO 2008/077403 A3

(51) International Patent Classification:
F03D 1/06 (2006.01) F03D 11/00 (2006.01)

(74) Agent: PATENTGRUPPEN A/S; Arosgården, Aaboulevarden 31, DK-8000 Aarhus C (DK).

(21) International Application Number:
PCT/DK2007/000559

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AB, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(22) International Filing Date:
20 December 2007 (20.12.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PA 2006 01705 22 December 2006 (22.12.2006) DK
PA 2007 01142 10 August 2007 (10.08.2007) DK

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): VESTAS WIND SYSTEMS A/S [DK/DK]; Alsvej 21, DK-8940 Randers SV (DK).

(72) Inventors; and

(75) Inventors/Applicants (for US only): GODSK, Kristian, Balschmidt [DK/DK]; Blegdamsvej 22, 3. th., DK-2200 Kobenhavn (DK). NIELSEN, Thomas, Steiniche, Bjertrup [DK/DK]; Vorup Kirkevej 31, DK-8900 Randers (DK).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv))


Published:

— with international search report

[Continued on next page]

WO 2008/077403 A3

(54) Title: WIND TURBINE WITH ROTOR BLADES EQUIPPED WITH WINGLETS AND BLADES FOR SUCH ROTOR



(57) Abstract: A wind turbine is disclosed comprising a rotor with wind turbine blades each having a root end connected to a hub of the wind turbine and a tip end, the tip end of each of which being equipped with a winglet extending a distance in a direction perpendicularly to a longitudinal direction of the blade. A new and much more slim design of the outer part of the wind turbine blade is disclosed, i.e. with a shorter chord length designed within a narrow band of values defined with respect to the length of the winglet, i.e. the extension in the direction transverse to the longitudinal direction of the blade.

WIND TURBINE WITH ROTOR BLADES EQUIPPED WITH WINGLETS AND
BLADES FOR SUCH ROTOR

The present invention relates to a wind turbine having a rotor with wind turbine
5 blades equipped with winglets and having a particular airfoil design to improve the
performance of the wind turbine

BACKGROUND OF THE INVENTION

10 It has for a number of years been common practice in air craft wing design to arrange
different types of winglets or other means at the wing tip for reducing or preventing
the spanwise flow of air from the pressure (lower) side of the wing profile to the
suction (upper) side of the profile around the tip, which results in the creation of the
tip vortex and a decreased lift coefficient at the tip section of the wing, mainly due to
15 the reduced suction at the suction side. Wind turbine rotors having blades equipped
with winglets are also known in the art, mainly for the purpose of reducing noise
emission from the wind turbine due to the presence of the tip vortices but also to
improve the overall performance of the wind turbine.

20 WO 2004/061298 A2 discloses such blade for a wind turbine, where a particular
design of the winglet itself is disclosed.

EP 1 500 814 A1 shows a wind turbine blade with an end projection having an
aerodynamic cross-sectional profile, which lies in a plane extending at an angle to
25 the rotor blade plane. The end projection is asymmetric to the central longitudinal
axis of the rotor blade, with a progressive or stepped reduction in the blade thickness
at the transition between the end projection and the remainder of the rotor blade.

WO 2005/078277 A2 relates to a rotor blade for a wind turbine with a drag ratio, in
30 particular in the central or main board region of said rotor, whose value exceeds 80

% and preferably 90 % of the maximum value of said ratio in the range of $\pm 2^\circ$ of the optimum pitch of said rotor

5 One of the consequences of producing lift on a finite wing is the generation of spanwise flow around the tip which influences the flow pattern in the whole tip region. In particular, the pressure gradients caused by the lower pressures on the upper surface relative to the higher pressures on the lower surface lead to inward spanwise flow (toward the hub) on the upper surface and outward spanwise flow (toward the tip) on the lower surface. At the trailing edge, the merging of these two
10 flows having different directions generates the vorticity that is shed from a finite wing and is the origin of induced drag as well as aerodynamic noise.

An endplate at the tip of a finite wing can reduce the spanwise flow and thereby reduce the induced drag. Unfortunately, to be effective, the endplate must be so large
15 that the increase in wetted area drag far outweighs any drag reduction. A winglet, rather than being a simple fence which limits the spanwise flow, carries an aerodynamic load that produces a flow field i.e. an inward side force that allows its own induced velocity field to partially cancel that of the main wing, thereby reducing the amount of spanwise flow. In essence, the winglet diffuses or spreads out the
20 influence of the tip vortex such that the downwash and, in turn the induced drag, are reduced. In this way, the winglet acts like an endplate in reducing the spanwise flow but, by carrying the proper aerodynamic loading, it accomplishes this with much less wetted area.

25 The displacement of the wing tip out and away from the main wing planform reduces the effect of the shed vorticity on the wing by displacing the concentrated vorticity away from the wing. In this manner, the winglet emulates the effect of a planar span extension and an increase in the length of the load perimeter.

The diffusion process is also realized as an expansion of the wake in the far field due to induced velocities from the non-planar components of the winglet. The out of plane bound vortex on an upward winglet induces horizontal velocities on the free wake that cause a spanwise spreading of the wake field. This also emulates the effect
5 of a span increase.

Another benefit of winglets, which is not achieved by a simple span extension, is the effect on the spanwise lift distribution, particularly in the region of the wing tip. The influence of the winglet effectively loads the planform in the tip region, increasing
10 the local lift coefficients and filling out the spanwise lift distribution. Planform efficiencies greater than those of an elliptical wing are possible. This occurs because, as evidenced by the extension of the roughly constant lift coefficients to beyond the actual tip location, the tip loaded spanwise lift distribution is, in fact, behaving like that of a nearly elliptically loaded planform of a greater span. When referenced to the
15 actual span, the resulting efficiency is greater than that of an elliptical loading.

Summing up the overall benefits of winglet vs. tip extension is:

1. Installation of winglets is found to cause a larger increase in the power coefficient and a smaller increase in the flap bending moment than radially
20 extended rotor blades
2. The smaller turbine diameter for the same tip velocity results in smaller gear ratio.
3. On some sites the local regulations dictates maximum wind turbine height (tower + blade tip in highest position).
- 25 4. Decrease noise from tip vortices.

BRIEF DESCRIPTION OF THE INVENTION

The advantages discussed above of the application of winglets on wind turbine
30 blades have lead to design trend where the blade part extending from the hub and to

the tip end of the blades immediately adjacent the winglet, i.e. at the winglet root, is designed as the inner part of a longer wind turbine blade because the presence of the winglet reduces the adverse tip effects on the lift coefficient at the outer part of the blade near the tip and a higher performance of that part of the blade may be achieved, which is particularly interesting because this part sweeps a large section of the total area swept by the rotor. This design leads to relatively large chord lengths at the outer part of the blade, i.e. the outer about 5% of the complete rotor radius.

It is an object of the present invention to provide an improved design of a wind turbine blade with a winglet that results in an improved performance of the wind turbine with respect to yearly production and preferably also reduced noise emission.

It has been found by the present invention that an optimisation of the performance of the wind turbine may be achieved by designing the outer part of the blade much more slim, i.e. with a shorter chord length designed within a narrow band of values defined with respect to the length of the winglet, i.e. the extension in the direction transverse to the longitudinal direction of the blade. The reduction in chord length has shown to reduce the actual drag more than the reduction in lift and results in an improved performance. Thus, the present invention relates to a wind turbine comprising a rotor with wind turbine blades each having a root end connected to a hub of the wind turbine and a tip end, the tip end of each of which being equipped with a winglet extending a distance in a direction perpendicularly to a longitudinal direction of the blade, wherein the combined radius specific solidity (SoI_r) of the rotor at the tip end of the blades immediately adjacent the winglet is 0.085 times the extension of the winglet divided by the radius of the rotor, plus a value within the range of 0.0012 and 0.0048. However, for an optimum effect of the winglet, the inventor's studies indicates that said value preferably is within the range of 0.0016 and 0.0042, and most preferred within the range of 0.0024 and 0.0040. The extension of the winglet and the radius of the rotor are taken in absolute values, so that their ratio, i.e. the extension of the winglet divided by the radius of the rotor, will be a fraction,

typically in the order of 0.01 to 0.04. Thus, an example of a typical calculation of the combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades immediately adjacent the winglet is for a blade where the ratio of the winglet extension and the rotor radius is 0.025 and said value is selected as a medial value of the last mentioned range: $(0.085 \text{ times } 0.025) + 0.0032 = 0.0053$.

The solidity of a wind turbine rotor is the ratio between the area of the blades projected into the rotor plane and the total area covered by the rotating blades, A_{blade} . The combined solidity, i.e. the sum of solidities of the blades, is hence:

$$Sol = \frac{n \cdot A_{blade}}{\pi R^2}$$

Where n is the number of wind turbine blades, e.g. 2, 3 or 4.

Solidity may also be established for a specific radius, r , from the centre of the rotor plane. The radius specific solidity of the wind turbine blade decreases as a function of the specific radius, r , and the combined radius specific solidity Sol_r . The combined radius specific solidity (Sol_r) of the rotor is defined as

$$Sol_r = \frac{n \cdot c_r}{2\pi R}$$

where n is the number of blades in the rotor, normally 2 or 3, c_r the chord length at the distance r from the hub and R the radius of the rotor.

20

In a preferred embodiment of the present invention, the outer end of the blades are designed so that the combined radius specific solidity (Sol_r) of the rotor increases continuously from the tip end of the blade and to a value in the range of 0.0065 to 0.013 at a position 5% of the rotor radius R from the tip in the direction of the hub, preferably in the range of 0.008 to 0.011 and most preferred within a range of 0.0085 to 0.01. It is particularly preferred that the combined radius specific solidity of the rotor increases substantially linearly, i.e. within a deviation of +/- 5-8% from a linear increase as a function of distance from the tip.

According to another preferred embodiment of the present invention, the whole outer part of the blades of the rotor is designed in a particular manner to improve the overall performance of the rotor. It has been found that the optimal design depends strongly on the height of the winglet, and the invention further relates to a wind turbine comprising a rotor with wind turbine blades each having a root end connected to a hub of the wind turbine and a tip end, the tip end of each of which being equipped with a winglet extending a distance X_{height} in a direction perpendicularly to a longitudinal direction of the blade, wherein the combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades substantially is designed in accordance with the formula

$$Sol_r = -0.34087 \cdot \left(\frac{r}{R}\right)^2 + 0.6004 \cdot \left(\frac{r}{R}\right) - 1.236 \cdot \left(\frac{X_{\text{height}}}{R}\right)^2 + 0.12548 \cdot \left(\frac{X_{\text{height}}}{R}\right) - 0.25276 + C$$

r being the distance to the hub and R the radius of the rotor, wherein C is defined as a constant for the rotor and is chosen within the range of -0.006 and 0.006, the combined radius specific solidity (Sol_r) of the rotor being defined as

$$Sol_r = \frac{n \cdot c_r}{2\pi R}$$

n being the number of blades in the rotor, c_r the chord length at the distance r from the hub.

The wide range of the design reflects the fact that wind turbine rotors are designed for the type of wind the individual wind turbine will be subjected to, i.e. the expected distribution of wind velocities.

25

This blade tip design may advantageously be combined with the aforementioned design according to the present invention.

It is preferred that C is chosen within the range of -0.004 and 0.004, preferably within the range of -0.003 and 0.003.

In a preferred embodiment of the present invention, said tip part being designed according to said formula constitutes at least the outer 5% of the blade length of each of the blades of the rotor, preferably at least the outer 8% of the blade length of each of the blades of the rotor, and most preferred at least the outer 10% of the blade length.

10 The combined radius specific solidity (Sol_r) of said tip part is designed substantially in accordance with the formula, which in a preferred embodiment means that it deviates less than 12% from the combined radius specific solidity (Sol_r) defined by said formula, preferably less than 8% and most preferred less than 6%.

15 The extension of the winglet may with the present invention exceed the commonly applied 1.2% to 1.5% of the rotor radius with improved performance of the wind turbine. Thus, the winglet extends preferably in the range of 0.5% to 5% of the radius R of the rotor, and most preferred in the range of 2% to 4% of the radius.

20 It is preferred that the maximum lift coefficient $C_{l,max}$ of the blades, where $C_{l,max}$ is valid for a two-dimensional flow passing a smooth profile surface, at the outer 10% of the radius R of the rotor is within the range of 0.9 and 2.0, and it is furthermore preferred that the maximum lift coefficient $C_{l,R}$ at the tip end of blades is within the range of 0.2 and 1.4. For a further discussion of the maximum lift coefficient, please refer to WO 2006/090215.

With respect to the design of the winglet, it is preferred that the combined radius specific solidity of the winglet tip chord is within the range of 0.0 and 0.02 for blade radius r taken as the rotor radius R , and the maximum lift coefficient ($C_{l,max}$) for the winglet tip chord is within the range of 0.0 and 0.4. It is furthermore preferred that

30

the combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades immediately adjacent the winglet is substantially equal to the combined radius specific solidity at the winglet root chord, and that the combined radius specific solidity decreases substantially continuously, more preferably linearly with the
5 distance to the tip, from the winglet root chord to the winglet tip chord.

The winglet may extend to the pressure side, which is the most common in order to avoid interference with the wind turbine tower, or the winglet may extend to the pressure side as well as to the suction side of the blade. However, it is preferred that
10 the winglets extend said distance (X_{height}) to the suction side of the blades of the rotor as it in combination with the present invention has shown to provide an improved performance of the wind turbine.

It is furthermore preferred that the winglet inflow angle of attack α_{A0A} is in the range
15 of -5 to 10° , preferably in the range of -2 to 8° and most preferred in the range of 0 to 5° .

It is also a preferred embodiment of the present invention that the winglet inclination angle of attack to blade is within the range of 70 to 150° , preferably in the range of
20 80 to 120° and most preferred in the range of 90 to 100° .

It is a further preferred embodiment of the present invention that the winglet leading edge displacement X_{LED} is less than the winglet root chord, preferably within the range of 5% to 75% thereof and most preferred with the range of 10% to 50%
25 thereof.

It is a yet further preferred embodiment of the present invention that the winglet trailing edge displacement X_{TED} is less than plus or minus 30% of winglet root chord, i.e. that the trailing edge of the winglet at very tip of the winglet may be
30 displaced in front of or behind the trailing edge of the main wing, preferably in the

range of plus or minus 2% to plus or minus 20% thereof and most preferred within the range of plus or minus 5% to plus or minus 10% thereof.

The present invention also relates to wind turbine blades having a root end with means for coupling said root end to a hub of a wind turbine and a tip end having a winglet, the blade being suitable for use in a wind turbine having the characteristics as described above, wherein the number of wind turbine blades is $n=2$ or $n=3$.

BRIEF DESCRIPTION OF FIGURES

10

The enclosed figures illustrates terms and effects related to the present invention:

- Fig. 1 illustrates the inclination of the winglet to the blade,
Fig. 2 illustrates the winglet height, the winglet root chord, the winglet tip
15 chord, the leading edge displacement and the trailing edge displacement,
Fig. 3 illustrates the winglet angle of attack,
Fig. 4 shows a preferred combined radius specific solidity of the outer 10% of a
wing turbine rotor having a 1% winglet height,
Fig. 5 shows a preferred combined radius specific solidity of the outer 10% of a
20 wing turbine rotor having a 2% winglet height, and
Fig. 6 shows a preferred combined radius specific solidity of the outer 10% of a
wing turbine rotor having a 4% winglet height.

DETAILED DESCRIPTION OF TERMS AND EMBODIMENTS

25

In Fig. 1, the tip end of a blade is shown as seen in perspective with the winglet pointing upwards, and the inclination of the winglet to the blade is shown as the winglet inclination angle to blade, $\alpha_{\text{inclination}}$, defined as the angle between the main wing centre line and the winglet centre line.

30

In Fig. 2 the tip end of a blade is shown as seen from the end thereof, i.e. the blade itself extends away from the viewer of Fig. 3. The winglet height, X_{height} , is defined as the distance from the main wing chord line at the very tip to the chord line of the very tip of the winglet. The winglet root chord, $X_{\text{rootchord}}$, is defined as the distance from the leading edge to the trailing edge of the main wing at the very tip where the winglet is attached. The winglet tip chord, X_{tipchord} , is defined as the distance from the leading edge to the trailing edge of the winglet at the very tip of the winglet. The winglet leading edge displacement, X_{LED} , is defined as the distance from the leading edge of the main wing at the very tip to the leading edge of the winglet at very tip of the winglet. The winglet trailing edge displacement, X_{TED} , is defined as the distance from the trailing edge of the main wing at the very tip to the trailing edge of the winglet at very tip of the winglet.

In Fig. 3 the tip end of a blade is shown as seen from the side to which the winglet tip points, i.e. the tip of the winglet of Fig. 3 points towards the viewer. The winglet angle of attack, α_{A0A} , is defined as the angle between the line parallel to the main wing chord plane at the tip and the winglet root chord plane

Modifying the blade with different winglets has shown to increase the efficiency of the rotor i.e. the amount of energy that the rotor extracts from the wind.

The annual increase in production for a turbine with an average wind speed of 8.5 m/s for a standard wind turbine rotor has been calculated theoretically for various extensions of the winglet:

25

	original	1 % Winglet	2 % Winglet	4 % Winglet
Percent increase in annual production for an average wind speed of 8.5 m/s	0.0	0.9	1.5	2.4

It is observed that the main effect of the blade design according to the invention arise for wind speeds between 5 - 11 m/s. This is highly advantageous, as for higher wind

speed, the maximum production is already reached and for smaller wind speeds, radial movement of the wind has limited effect. It appears that the increase tends to be larger for larger heights of the winglets, but a practical limit with respect to mechanical construction and forces on the tip part of the blades due to the presence
5 of the winglet is about 5% of the radius of the wind turbine.

The combined radius specific solidity of the outer 10% of wind turbine blades has been calculated for three different examples of blade designs according to the present invention and are shown in Figs. 4-6.

10

In Fig. 4, a design with a winglet height of 1% of the rotor radius is shown. The combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades immediately adjacent the winglet is chosen to be 0.00435 which results in a constant $C = -0.00355$ for the above formula. For a 3-bladed wind turbine with a rotor
15 diameter of 90 meter this equals a winglet height of 45 cm, a tip chord length of about 41 cm and a chord length at radius $r = 90\%$ of the rotor radius of 45 meter of about 92 cm.

In Fig. 5, a design with a winglet height of 2% of the rotor radius is shown. The
20 combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades immediately adjacent the winglet is chosen to be 0.0057 which results in a constant $C = -0.003085$ for the above formula. For a 3-bladed wind turbine with a rotor diameter of 90 meter this equals a winglet height of 90 cm, a tip chord length of about 54 cm and a chord length at radius $r = 90\%$ of the rotor radius of 45 meter of about 98 cm.

25

In Fig. 6, a design with a winglet height of 4% of the rotor radius is shown. The combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades immediately adjacent the winglet is chosen to be 0.0057 which results in a constant $C = -0.003212$ for the above formula. For a 3-bladed wind turbine with a rotor diameter

of 90 meter this equals a winglet height of 180 cm, a tip chord length of about 62 cm and a chord length at radius $r = 90\%$ of the rotor radius of 45 meter of about 107 cm.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A wind turbine comprising a rotor with wind turbine blades each having a root end connected to a hub of the wind turbine and a tip end, the tip end of each of which being equipped with a winglet extending a distance (X_{height}) in a direction perpendicularly to a longitudinal direction of the blade;

wherein the combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades immediately adjacent the winglet is 0.085 times the extension of the winglet (X_{height}) divided by the radius (R) of the rotor plus a value within the range of 0.0012 and 0.0048, plus, the combined radius specific solidity (Sol_r) of the rotor being defined as

$$Sol_r = \frac{n \cdot c_r}{2\pi R}$$

n being the number of blades in the rotor, c_r the chord length at the distance r from the hub and R the radius of the rotor.

2. A wind turbine according to claim 1, wherein said combined radius specific solidity (Sol_r) of the rotor at the tip end of the blade is within the range of 0.0016 and 0.0042, plus 0.085 times the extension of the winglet (X_{height}) divided by the radius (R) of the rotor.

3. A wind turbine according to claim 1, wherein said combined radius specific solidity (Sol_r) of the rotor at the tip end of the blade is within the range of 0.0024 and 0.0040, plus 0.085 times the extension of the winglet (X_{height}) divided by the radius (R) of the rotor.

4. A wind turbine according to any one of claims 1 to 3, wherein the combined radius specific solidity (Sol_r) of the rotor increases continuously from the tip end of the blade and to a value in the range of 0.0065 to 0.013 at a position 5% of the rotor radius R from the tip in the direction of the hub.

5. A wind turbine according to any one of claims 1 to 3, wherein the combined radius specific solidity (Sol_r) of the rotor increases continuously from the tip end of the

blade and to a value in the range of 0.008 to 0.011 at a position 5% of the rotor radius R from the tip in the direction of the hub.

6. A wind turbine according to any one of claims 1 to 3, wherein the combined radius specific solidity (Sol_r) of the rotor increases continuously from the tip end of the blade and to a value in the range of 0.0085 to 0.01 at a position 5% of the rotor radius R from the tip in the direction of the hub.

7. A wind turbine according to claim 4, 5 or 6, wherein the combined radius specific solidity (Sol_r) of the rotor increases substantially linearly from the tip end of the blade and to a position 5% of the rotor radius (R) from the tip in the direction of the hub.

8. A wind turbine comprising a rotor with wind turbine blades each having a root end connected to a hub of the wind turbine and a tip end, the tip end of each of which being equipped with a winglet extending a distance (X_{height}) in a direction perpendicularly to a longitudinal direction of the blade;

wherein the combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades substantially is designed in accordance with the formula

$$Sol_r = -0.34087 \cdot \left(\frac{r}{R}\right)^2 + 0.6004 \cdot \left(\frac{r}{R}\right) - 1.236 \cdot \left(\frac{X_{\text{height}}}{R}\right)^2 + 0.12548 \cdot \left(\frac{X_{\text{height}}}{R}\right) - 0.25276 + C$$

r being the distance to the hub and R the radius of the rotor, wherein C is defined as a constant for the rotor and is chosen within the range of -0.006 and 0.006, the combined radius specific solidity (Sol_r) of the rotor being defined as

$$Sol_r = \frac{n \cdot c_r}{2\pi R}$$

n being the number of blades in the rotor, c_r the chord length at the distance r from the hub.

9. A wind turbine according to claim 8, wherein C is chosen within the range of -0.004 and 0.004.

10. A wind turbine according to claim 8, wherein C is chosen within the range of -0.003 and 0.003.

11. A wind turbine according to claim 8, 9 or 10, wherein said tip end being designed according to said formula constitutes at least the outer 5% of the blade length of each of the blades of the rotor.
12. A wind turbine according to claim 11, wherein said tip end being designed according to said formula constitutes at least the outer 8% of the blade length of each of the blades of the rotor.
13. A wind turbine according to claim 11, wherein said tip end being designed according to said formula constitutes at least the outer 10% of the blade length of each of the blades of the rotor.
14. A wind turbine according to any one of claims 8 to 13, wherein the combined radius specific solidity (Sol_r) of said tip end deviates less than 12% from the combined radius specific solidity (Sol_r) defined by said formula.
15. A wind turbine according to any one of claims 8 to 13, wherein the combined radius specific solidity (Sol_r) of said tip end deviates less than 8% from the combined radius specific solidity (Sol_r) defined by said formula.
16. A wind turbine according to any one of claims 8 to 13, wherein the combined radius specific solidity (Sol_r) of said tip end deviates less than 6% from the combined radius specific solidity (Sol_r) defined by said formula.
17. A wind turbine according to any one of claims 1 to 16, wherein the extension of the winglet (X_{height}) constitutes in the range of 0.5% to 5% of the radius (R) of the rotor.
18. A wind turbine according to any one of claims 1 to 16, wherein the extension of the winglet (X_{height}) constitutes in the range of 2% to 4% of the radius (R) of the rotor.
19. A wind turbine according to any one of claims 1 to 18, wherein the maximum lift coefficient $C_{1,\text{max}}$ of the blades where $C_{1,\text{max}}$ is valid for a two-dimensional flow passing a

smooth profile surface, at the outer 10% of the radius R of the rotor is within the range of 0.9 and 2.0.

20. A wind turbine according to any one of claims 1 to 19, wherein the maximum lift coefficient $C_{l,R}$ at the tip end of blades is within the range of 0.2 and 1.4.

21. A wind turbine according to any one of claims 1 to 20, wherein the combined radius specific solidity of the winglet tip chord (Sol_r) is within the range of 0.0 and 0.02 for blade radius r taken as the rotor radius R , and the maximum lift coefficient ($C_{l,max}$) for the winglet tip chord is within the range of 0.0 and 0.4.

22. A wind turbine according to claim 21, wherein the combined radius specific solidity (Sol_r) of the rotor at the tip end of the blades immediately adjacent the winglet is substantially equal to the combined radius specific solidity at the winglet root chord, and the combined radius specific solidity decreases substantially continuously from the winglet root chord to the winglet tip chord.

23. A wind turbine according to claim 22, wherein the combined radius specific solidity decreases substantially linearly between the winglet root chord and the winglet tip chord.

24. A wind turbine according to any one of claims 1 to 23, wherein the winglets extend said distance (X_{height}) to the suction side of the blades of the rotor.

25. A wind turbine according to any one of claims 1 to 24, wherein the winglet inflow angle of attack α_{AoA} is in the range of -5 to 10° .

26. A wind turbine according to any one of claims 1 to 24, wherein the winglet inflow angle of attack α_{AoA} is in the range of -2 to 8° .

27. A wind turbine according to any one of claims 1 to 24, wherein the winglet inflow angle of attack α_{AoA} is in the range of 0 to 5° .

28. A wind turbine according to any one of claims 1 to 27, wherein the winglet inclination angle of attack to blade is within the range of 70 to 150°.
29. A wind turbine according to any one of claims 1 to 27, wherein the winglet inclination angle of attack to blade is within the range of 80 to 120°.
30. A wind turbine according to any one of claims 1 to 27, wherein the winglet inclination angle of attack to blade is within the range of 90 to 100°.
31. A wind turbine according to any one of claims 1 to 28, wherein the winglet leading edge displacement X_{LED} is less than the winglet root chord within the range of 5% to 75% thereof.
32. A wind turbine according to any one of claims 1 to 28, wherein the winglet leading edge displacement X_{LED} is less than the winglet root chord within the range of 10% to 50% thereof.
33. A wind turbine according to any one of claims 1 to 32, wherein the winglet trailing edge displacement X_{TED} is less than plus or minus 30 % of the winglet root chord.
34. A wind turbine according to any one of claims 1 to 32, wherein the winglet trailing edge displacement X_{TED} is plus or minus 2% to plus or minus 20% thereof of the winglet root chord.
35. A wind turbine according to any one of claims 1 to 32, wherein the winglet trailing edge displacement X_{TED} is plus or minus 5% to plus or minus 10% thereof of the winglet root chord.
36. A wind turbine blade having a root end with means for coupling said root end to a hub of a wind turbine and a tip end having a winglet, the blade being suitable for use in a wind turbine as defined in any one of claims 1 to 35, wherein the number of wind turbine blades is $n=2$ or $n=3$.

1/4




Fig. 1




Fig. 2






Fig. 3


2/4


**Fig. 4**

3/4

*Fig. 5*

4/4

**Fig. 6**



$\alpha_{\text{inclination}}$