

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2013/058896 A1

(43) International Publication Date

25 April 2013 (25.04.2013)

WIPO | PCT

(51) International Patent Classification:

G06F 3/01 (2006.01) *G06F 3/14* (2006.01)
G06F 3/048 (2013.01) *G06F 9/44* (2006.01)
G06F 3/041 (2006.01)

(74) Agent: **CHOI, Hogene, L.**; Baker Botts L.L.P., 2001 Ross Avenue, Suite 600, Dallas, TX 75201 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:

PCT/US2012/054973

(22) International Filing Date:

13 September 2012 (13.09.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13/275,095 17 October 2011 (17.10.2011) US

(71) Applicant (for all designated States except US): **FACEBOOK, INC.** [US/US]; 1601 Willow Road, Menlo Park, CA 94025 (US).


(72) Inventors; and

(75) Inventors/Applicants (for US only): **PAPAKIPOS, Matthew, Nicholas** [US/US]; 1601 Willow Road, Menlo Park, CA 94025 (US). **CAHILL, Matthew** [US/US]; 1601 Willow Road, Menlo Park, CA 94025 (US).

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

[Continued on next page]

(54) Title: NAVIGATING APPLICATIONS USING SIDE-MOUNTED TOUCHPAD



(57) Abstract: In one embodiment, a user of a mobile device navigates between application user interface layers by using touch inputs to the mobile device's side-mounted touchpad.



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

Declarations under Rule 4.17:

- *as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))*

NAVIGATING APPLICATIONS USING SIDE-MOUNTED TOUCHPAD

TECHNICAL FIELD

The present disclosure relates generally to touch-based user interfaces, and more particularly to, navigating between user interface layers of an application hosted by a computing device having a side-mounted touchpad.

5

BACKGROUND

A touchpad is an input device including a surface that detects touch-based inputs of users. A touch screen is an electronic visual display that detects the presence and location of user touch inputs. Mobile devices such as a mobile phone, a tablet computer, and a laptop computer often incorporate a touch screen or a touchpad to facilitate user interactions with application programs running on the mobile device.

10 SUMMARY

Particular embodiments relate to touch-based user interfaces that allow a user of a computing device to navigate between application user interface layers by using touch inputs to a side-mounted touchpad. These and other features, aspects, and advantages of the disclosure are described in more detail below in the detailed description and in conjunction with the following figures.

15 20 BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates an example touch screen of a mobile phone that hosts a browser client displaying a web page.

Figure 2 illustrates an example processing stack of a mobile device with touch-based input device(s).

25 Figure 3A-3C illustrate an example method of navigating between user interface layers of an application hosted on a touch-screen device.

Figure 4 illustrates an example application user interface hierarchy of an application hosted on a touch-screen device.

Figure 5 illustrates a front view and a side view of an example mobile device with a

front-mounted touch screen and a side-mounted touchpad.

Figure 5A illustrates another example of the mobile device of Figure 5.

Figure 5B illustrates an example mobile device with a back-mounted touch surface.

Figures 5C-5F illustrate example touch events associated with the one or more side-mounted touchpads of the example mobile device of Figure 5.

Figures 5G-5I illustrate example touch events associated with a back-mounted touch surface of the example mobile device of Figure 5B.

Figure 6 illustrates an example method of navigating between user interface layers of an application using side-mounted touchpads.

10 Figure 7 illustrates an example mobile device platform.

DETAILED DESCRIPTION

The invention is now described in detail with reference to a few embodiments thereof as illustrated in the accompanying drawings. In the following description, numerous specific details are set forth in order to provide a thorough understanding of the 15 present disclosure. It is apparent, however, to one skilled in the art, that the present disclosure may be practiced without some or all of these specific details. In other instances, well known process steps and/or structures have not been described in detail in order not to unnecessarily obscure the present disclosure. In addition, while the disclosure is described in conjunction with the particular embodiments, it should 20 be understood that this description is not intended to limit the disclosure to the described embodiments. To the contrary, the description is intended to cover alternatives, modifications, and equivalents as may be included within the spirit and scope of the disclosure as defined by the appended claims.

A touchpad is an input device including a surface that detects touch-based inputs of 25 users. Similarly, a touch screen is an electronic visual display that detects the presence and location of user touch inputs. So-called dual touch or multi-touch displays or touchpads refer to devices that can identify the presence, location and movement of more than one touch input, such as two or three finger touches. A system incorporating one or more touch-based input devices may monitor one or more touch-sensitive surfaces for one or more touch or near touch inputs from a user. When one 30

or more such user inputs occur, the system may determine the distinct area(s) of contact and identify the nature of the touch or near touch input(s) via geometric features and geometric arrangements (e.g., location, movement), and determine if they correspond to various touch events (e.g., tap, drag, swipe, pinch). These touch events 5 may then be processed by handler functions that register or subscribe as listeners to such events, as illustrated in Figure 1. Figure 1 illustrates an example touch screen of a mobile phone that hosts a browser client displaying a web page. In the example of Figure 1, touch screen 101 of mobile phone 100 displays an HTML/JavaScript code snippet displaying a text string “Tap on this text”, as listed below.

10

15

20

```
<html>
  <!-- pseudo-code to include a touch event listener from a touch
       events library
  library TouchEventsLibrary
  function onTapEvent
  -->
  <body>
    <h1  onTapEvent="this.innerHTML='Boo!'">Click  on  this
        text</h1>
  </body>
</html>
```

As a user taps on the text string “Tap on this text.” (102), a touch event listener “onTouchEvent” can trigger an action of changing the text string from “Tap on this text.” to “Boo!” (103).

25 Recognition of touch events by a system with one or more touch-based input devices--i.e., identifying one or more touch inputs by a user and determining corresponding touch event(s)-- may be implemented by a combination of hardware, software, and/or firmware (or device drivers). Figure 2 illustrates an example processing stack of a mobile device (e.g., a smart phone) with touch-based input device(s). Hardware layer 30 201 can include one or more processors and various hardware input/output devices such as camera, communication interface, and touch-based input device (e.g., touch screen, touchpad). Drivers layer 202 includes one or more drivers that communicate

and control hardware layer 200, for example, a driver receiving and processing touch input signals generated by a touch-screen display. Operating system 203 runs computing programs and manages hardware layer 201 via one or more drivers in driver layer 202. Libraries 204 include one or more libraries used by one or more application programs in applications 205 (e.g., web browser, address book, etc.). For example, touch events library 210 can contain codes that interpret touch inputs to touch events or gestures, and a web browser application program can access touch event library 210 (e.g., via function calls) and process a web page with touch event handlers embedded within the page, as illustrated in Figure 1 and in the 10 HTML/JavaScript code snippet above.

User interface layers of application programs hosted by a computing device, including user interface layers of the computing device's operating system, are generally arranged in a hierarchy, such as a hierarchical tree structure. A root node of the tree structure may correspond to a home user interface layer or home screen of an 15 application, including icons, buttons, pull-down menus, hypertext links or other controls that allow users to navigate to child user interface layers. Child user interface layers may include icons or buttons that allow users to navigate back to parent user interface layers by selecting an icon or button. Many such buttons are displayed on the top of a menu bar, but there are a lot of exceptions.

20 With a touch-screen device, a user can often navigate between user interface layers of an application hosted on the touch-screen device by touching one or more selectable elements within the application's user graphic interface displayed with the touch-screen, as illustrated in Figures 3A-3C. The particular application shown in Figures 3A-3C is a Facebook(r) client hosted by a mobile phone with a touch screen (e.g., an 25 iPhone(r) smartphone offered by Apple, Inc. of Cupertino, California). When a user launches the application, the application shows a home screen 301 (Figure 3A), or an interface displaying home user interface layer of the application. The home screen 301 may include user interface elements such as icons or buttons for navigating to other layers, for example, News Feed icon 310, Photos icon 330, or Friends icon 340.

30 Figure 4 illustrates an example application user interface hierarchy 400 of the application illustrated in Figures 3A-3C. The application user interface hierarchy includes home layer 401 and one or more sub-layers 402, such as News Feed 410,

Profile 420, Photos 430, Friends 440, and the like. In addition, Photos layer 430 itself has a sub-layer of Album list 432 which in turn has a sub-layer Photo list 434, and so on. Not all layers have sub-layers, such as News Feed content 412, Self Profile content 422, “Photo 1” 436, which are leaf layers. In the example of Figure 4, the 5 nodes of the hierarchy represent different user interface layers provided by the application, while the edges between the nodes illustrate a potential navigation flow. Additionally, the application may allow for navigation among the nodes in a way that does not observe a hierarchical model, such as navigating directly between sibling node layers, traversing more than one hop directly between layers, and the like.

10 For example, from home layer 401, the user can navigate to Friends layer 440 by touching Friends icon 340 within home screen 301, the current screen will change to a screen 341 for Friends layer 440, as illustrated in Figure 3B. The screen 341 for Friends layer 440 comprises a list of friends wherein each friend is represented by a selectable icon (e.g., a profile picture). The user can navigate to a particular friend 15 layer “Laura” 442 by touching a corresponding icon (342), the current screen will change to a screen for the particular friend (343), as illustrated in Figure 3C. From the particular friend layer “Laura” 442 or from the screen for the particular friend 343 illustrated in Figure 3C, the user can look up additional information (e.g., an email address, a phone number) of the particular friend by touching “info” icon 344, 20 navigate back to Friends layer by touching “Friends” icon 345, or navigating to home layer by touching home icon 346.

Particular embodiments herein relate to a computing device (such as a mobile phone, netbook, smartphone, tablet, or other portable device) with a touch screen and one or more side-mounted touchpads and methods of allowing users to use the one or more 25 side-mounted touchpads to navigate between application user interface layers. Particular embodiments can improve user experience associated with mobile devices as the side-mounted touchpad(s) can offload user interaction to the side-mounted touchpad(s) and yield better usage of the touch screen (e.g., a less congested graphic user interface with less navigation elements or icons). Figure 5 illustrates a front view 30 and a side view of an example mobile device with a front-mounted touch screen and a side-mounted touchpad. In particular embodiments, mobile device 500 may comprise a housing with multi-touch touch screen 501 disposed on a front face of the housing.

The mobile device 500 may also include a side-mounted multi-touch touchpad 502 and a side-mounted single-touch touchpad 503, both disposed on a lateral face or edge of the device 500. In particular embodiments, mobile device 500 may include hardware and/or software that supports or implements a variety of functions. For 5 example, mobile device 500 may support telephony functions, chat and/or email functions. Mobile device 500 may also support network data communications and include a web browser for accessing and displaying web pages. Mobile device 500 may also support or incorporate, a Wi-Fi base station functions, a digital media player functions, and/or a gaming device functions. In one embodiment, the side-mounted 10 touchpad 503 may be replaced by a clickable button or keypad device. In another embodiment, the side-mounted touchpad 503 may be a multi-touch touchpad. In some implementations, the touchpad 402 may be a single- or multi-touch device. In some embodiments, side-mounted touchpad 502 may comprise a slightly concave multi-touch surface, as illustrated in Figure 5A. The touch screen 501 and side-mounted 15 touchpad 503 may be single-touch, dual-touch or multi-touch devices. In addition, implementations of the invention can operate without a touch screen device, relying instead on a regular display device and a pointer device, such as a trackball or trackpad. In other embodiments, mobile device 500 may include a back-mount touch surface 505 on a back-side of mobile device 500. The back-mounted touch 505 may 20 cover substantially all or a portion of a back side of mobile device 500, as illustrated in Figure 5B. The back-mounted touch surface 505 may comprise a multi-touch touchpad or a multi-touch touch screen.

Mobile device 500 may recognize touch inputs, and determine one or more corresponding touch events or gestures. One or more applications hosted on mobile 25 device 500 may be configured to register a handler function that responds to the one or more touch events. In particular embodiments, mobile device 500 may recognize one or more user touch inputs performed on touch screen 501, touchpad 502, touchpad 503, and/or back-mounted touch surface 505, and determine one or more corresponding touch events. In particular embodiments, mobile device 500 may 30 determine a forward lateral flick event associated with touchpad 502, as illustrated in Figure 5C. In the example of Figure 5C, a user touches touchpad 502 in a quick motion in forward lateral direction (indicated by the arrow 510), and a gesture

recognition library of mobile device 500 can access data generated by touchpad 502 and determine the touch input corresponding to a forward lateral flick event or gesture associated with touchpad 502. In particular embodiments, mobile device 500 may determine a backward lateral flick event associated with touchpad 502, as illustrated

5 in Figure 5D. In the example of Figure 5D, a user touches touchpad 502 in a quick motion in backward lateral direction (indicated by the arrow 512), and a gesture recognition library of mobile device 500 can access data generated by touchpad 502 and determine the touch input corresponding to a backward lateral flick event or gesture associated with touchpad 502.

10 In particular embodiments, mobile device 500 may identify a tap event. In some embodiments, mobile device 500 may determine a tap event associated with touchpad 502, as illustrated in Figure 5E. In the example of Figure 5E, a user taps or strikes lightly on touchpad 502 (indicated by the arrow 514), and a gesture recognition library of mobile device 500 can interpret the user's touch input and identify the touch

15 input corresponding to a tap event. In other embodiments, mobile device 500 may identify a tap event associated with touchpad 503, as illustrated in Figure 5F. In the example of Figure 5F, a user taps or strikes lightly on touchpad 503 (indicated by the arrow 516), and a gesture recognition library of mobile device 500 can interpret the user's touch input and identify the touch input corresponding to a tap event. In one

20 embodiments, mobile device 500 may identify a tap event associated with touchpad 503 if touchpad 503 is a clickable button and a user clicks on the clickable button.

In other embodiments, mobile device 500 may identify touch events associated with back-mounted touch surface 505, as illustrated in Figures 5G-5I. In the example of Figure 5G, a user touches back-mounted touch surface 505 in a quick motion in an

25 upward direction (indicated by the arrow 531). A gesture recognition library of mobile device 500 can interpret the user's touch input and identify the touch input corresponding to an upward flick event or gesture associated with back-mounted touch surface 505. In the example of Figure 5H, a user touches back-mounted touch surface 505 in a quick motion in a downward direction (indicated by the arrow 532).

30 A gesture recognition library of mobile device 500 can interpret the user's input and identify the touch input corresponding to a downward flick event or gesture associated with back-mounted touch surface 505. In the example of Figure 5I, a user taps or

strikes lightly on back-mounted touch surface 505 (as indicated by the arrow 533). A gesture recognition library of mobile device 500 can interpret the user's input and identify the touch input corresponding to a tap event associated with back-mounted touch surface 505.

- 5 In contrast to navigating between user interface layers of an application by touch inputs to a touch screen as illustrated in the example in Figures 3A-3C, Figure 6 illustrates an example method of navigating between user interface layers of an application using side-mounted touchpads. Specifically, the example method of Figure 6 may enable a user to navigate between user interface layers by flicking
- 10 across a side-mounted touchpad, to jump to the application's home screen by tapping or clicking a side-mounted "home button". As a listener for touch events (601), the handler function can, responsive to a touch event, cause an application to navigate to a different user interface layer. In particular embodiments, when a touch event occurs (601), the handler function may determine a current application layer corresponding
- 15 to the touch event. In particular embodiments, the application may store a navigation history that tracks the layers to which the user has navigated. In particular embodiments, the handler function may determine if the touch event is a forward lateral flick event (602). In particular embodiments, if the touch event is a forward lateral flick event, and if the forward navigation history identifies a next layer for the
- 20 current layer, the handler function may cause the application navigate to the next layer (603). In particular embodiments, the handler function may determine if the touch event is a backward lateral flick event (604). In particular embodiments, if the touch event is a backward lateral flick event, and if the backward navigation history identifies a previous layer for the current layer, the handler function may cause the application navigate to the previous layer (605). In particular embodiments, the handler function may determine if the touch event is a tap event in connection with
- 25 input device 503 (606). In particular embodiments, if the touch event is a tap event, and if the current layer is not a home layer, the handler function may cause the application navigate to the home layer (607).
- 30 Additionally, particular embodiments may enable navigating between user interface layers of an application using the back-mounted touch surface described earlier. For example, as a listener for touch events, the handler function can, responsive to a touch

event, cause an application to navigate to a different user interface layer. When a touch event occurs, the handler function may determine a current application layer corresponding to the touch event. The application may store a navigation history that tracks the layers to which the user has navigated. The handler function may 5 determine if the touch event is an upward flick event associated with back-mounted touch surface 505. If the touch event is an upward flick event associated with back-mounted touch surface 505, and if the forward navigation history identifies a next layer for the current layer, the handler function may cause the application to navigate to the next layer. The hander function may determine if the touch event is a 10 downward flick event associated with back-mounted touch surface 505. If the touch event is a downward flick event associated with back-mounted touch surface 505, and if the backward navigation history identifies a previous layer for the current layer, the handler function may cause the application navigate to the previous layer. The handler function may determine if the touch event is a tap event associated with back-mounted touch surface 505. If the touch event is a tap event associated with back-mounted touch surface 505, and if the current layer is not a home layer, the handler 15 function may cause the application to navigate to the home layer.

The forward and back gestures, as well as the home control input, described above can be utilized in connection with a variety of applications and computing devices. 20 For example, as discussed above, the forward and back gestures, as well as the home control input, may be used in connection with a special-purpose client application in order to facilitate navigation of the various application layers. In such an implementation, the home input causes navigation back to the home or root layer of the application. The forward and back gestures, as well as the home control input, 25 may also be used in connection with a browser client to facilitate navigation of a series of web pages provided by one or more domains. In such an implementation, the home input may cause navigation back to a home page, while the forward and back gestures may implement corresponding forward and backward navigation functions common to browser client applications. In addition, the forward and back 30 gestures, as well as the home control input, can be used in connection with a graphical user interface shell of an operating system. In such an implementation, the home input may cause navigation back to the home screen of the operating system, while

the forward and back gestures may implement corresponding forward and backward navigation functions across various layers provided by the operating system shell.

The application and functionality described above can be implemented as a series of

instructions stored on a computer-readable storage medium that, when executed,

5 cause a programmable processor to implement the operations described above. While

the mobile device 500 may be implemented in a variety of different hardware and computing systems, FIGURE 7 shows a schematic representation of the main components of an example computing platform of a client or mobile device, according to various particular embodiments. In particular embodiments, computing

10 platform 702 may comprise controller 704, memory 706, and input output subsystem

710. In particular embodiments, controller 704 which may comprise one or more processors and/or one or more microcontrollers configured to execute instructions and to carry out operations associated with a computing platform. In various

embodiments, controller 704 may be implemented as a single-chip, multiple chips

15 and/or other electrical components including one or more integrated circuits and printed circuit boards. Controller 704 may optionally contain a cache memory unit for temporary local storage of instructions, data, or computer addresses. By way of example, using instructions retrieved from memory, controller 704 may control the reception and manipulation of input and output data between components of

20 computing platform 702. By way of example, controller 704 may include one or more processors or one or more controllers dedicated for certain processing tasks of computing platform 702, for example, for 2D/3D graphics processing, image processing, or video processing.

Controller 704 together with a suitable operating system may operate to execute

25 instructions in the form of computer code and produce and use data. By way of example and not by way of limitation, the operating system may be Windows-based,

Mac-based, or Unix or Linux-based, Symbian-based, or Android-based among other

suitable operating systems. The operating system, other computer code and/or data

may be physically stored within memory 706 that is operatively coupled to controller

30 704.

Memory 706 may encompass one or more storage media and generally provide a place to store computer code (e.g., software and/or firmware) and data that are used

by computing platform 702. By way of example, memory 706 may include various tangible computer-readable storage media including Read-Only Memory (ROM) and/or Random-Access Memory (RAM). As is well known in the art, ROM acts to transfer data and instructions uni-directionally to controller 704, and RAM is used 5 typically to transfer data and instructions in a bi-directional manner. Memory 706 may also include one or more fixed storage devices in the form of, by way of example, hard disk drives (HDDs), solid-state drives (SSDs), flash-memory cards (e.g., Secured Digital or SD cards, embedded MultiMediaCard or eMMC cards), among other suitable forms of memory coupled bi-directionally to controller 704. 10 Information may also reside on one or more removable storage media loaded into or installed in computing platform 702 when needed. By way of example, any of a number of suitable memory cards (e.g., SD cards) may be loaded into computing platform 702 on a temporary or permanent basis.

Input output subsystem 710 may comprise one or more input and output devices 15 operably connected to controller 704. For example, input-output subsystem may include keyboard, mouse, one or more buttons, thumb wheel, and/or display (e.g., liquid crystal display (LCD), light emitting diode (LED), Interferometric modulator display (IMOD), or any other suitable display technology). Generally, input devices are configured to transfer data, commands and responses from the outside world into 20 computing platform 702. The display is generally configured to display a graphical user interface (GUI) that provides an easy to use visual interface between a user of the computing platform 702 and the operating system or application(s) running on the mobile device. Generally, the GUI presents programs, files and operational options with graphical images. During operation, the user may select and activate various 25 graphical images displayed on the display in order to initiate functions and tasks associated therewith. Input output subsystem 710 may also include touch based devices such as touchpad and touch screen. A touchpad is an input device including a surface that detects touch-based inputs of users. Similarly, a touch screen is a display that detects the presence and location of user touch inputs. Input output system 710 30 may also include dual touch or multi-touch displays or touchpads that can identify the presence, location and movement of more than one touch inputs, such as two or three finger touches.

In particular embodiments, computing platform 702 may additionally comprise audio subsystem 712, camera subsystem 712, wireless communication subsystem 716, sensor subsystems 718, and/or wired communication subsystem 720, operably connected to controller 704 to facilitate various functions of computing platform 702.

5 For example, Audio subsystem 712, including a speaker, a microphone, and a codec module configured to process audio signals, can be utilized to facilitate voice-enabled functions, such as voice recognition, voice replication, digital recording, and telephony functions. For example, camera subsystem 712, including an optical sensor (e.g., a charged coupled device (CCD), or a complementary metal-oxide 10 semiconductor (CMOS) image sensor), can be utilized to facilitate camera functions, such as recording photographs and video clips. For example, wired communication subsystem 720 can include a Universal Serial Bus (USB) port for file transferring, or a Ethernet port for connection to a local area network (LAN). Additionally, computing platform 702 may be powered by power source 732.

15 Wireless communication subsystem 716 can be designed to operate over one or more wireless networks, for example, a wireless PAN (WPAN) (such as, for example, a BLUETOOTH WPAN, an infrared PAN), a WI-FI network (such as, for example, an 802.11a/b/g/n WI-FI network, an 802.11s mesh network), a WI-MAX network, a cellular telephone network (such as, for example, a Global System for Mobile 20 Communications (GSM) network, an Enhanced Data Rates for GSM Evolution (EDGE) network, a Universal Mobile Telecommunications System (UMTS) network, and/or a Long Term Evolution (LTE) network). Additionally, wireless communication subsystem 716 may include hosting protocols such that computing platform 702 may be configured as a base station for other wireless devices.

25 Sensor subsystem 718 may include one or more sensor devices to provide additional input and facilitate multiple functionalities of computing platform 702. For example, sensor subsystems 718 may include GPS sensor for location positioning, altimeter for altitude positioning, motion sensor for determining orientation of a mobile device, light sensor for photographing function with camera subsystem 714, temperature 30 sensor for measuring ambient temperature, and/or biometric sensor for security application (e.g., fingerprint reader). Other input/output devices may include an accelerometer that can be used to detect the orientation of the device.

In particular embodiments, various components of computing platform 702 may be operably connected together by one or more buses (including hardware and/or software). As an example and not by way of limitation, the one or more buses may include an Accelerated Graphics Port (AGP) or other graphics bus, an Enhanced

5 Industry Standard Architecture (EISA) bus, a front-side bus (FSB), a HYPERTRANSPORT (HT) interconnect, an Industry Standard Architecture (ISA) bus, an INFINIBAND interconnect, a low-pin-count (LPC) bus, a memory bus, a Micro Channel Architecture (MCA) bus, a Peripheral Component Interconnect (PCI) bus, a PCI-Express (PCI-X) bus, a serial advanced technology attachment (SATA)

10 bus, a Video Electronics Standards Association local (VLB) bus, a Universal Asynchronous Receiver/Transmitter (UART) interface, a Inter-Integrated Circuit (I²C) bus, a Serial Peripheral Interface (SPI) bus, a Secure Digital (SD) memory interface, a MultiMediaCard (MMC) memory interface, a Memory Stick (MS) memory interface, a Secure Digital Input Output (SDIO) interface, a Multi-channel

15 Buffered Serial Port (McBSP) bus, a Universal Serial Bus (USB) bus, a General Purpose Memory Controller (GPMC) bus, a SDRAM Controller (SDRC) bus, a General Purpose Input/Output (GPIO) bus, a Separate Video (S-Video) bus, a Display Serial Interface (DSI) bus, an Advanced Microcontroller Bus Architecture (AMBA) bus, or another suitable bus or a combination of two or more of these.

20 Herein, reference to a computer-readable storage medium encompasses one or more non-transitory, tangible computer-readable storage media possessing structure. As an example and not by way of limitation, a computer-readable storage medium may include a semiconductor-based or other integrated circuit (IC) (such, as for example, a field-programmable gate array (FPGA) or an application-specific IC (ASIC)), a hard

25 disk, an HDD, a hybrid hard drive (HHD), an optical disc, an optical disc drive (ODD), a magneto-optical disc, a magneto-optical drive, a floppy disk, a floppy disk drive (FDD), magnetic tape, a holographic storage medium, a solid-state drive (SSD), a RAM-drive, a SECURE DIGITAL card, a SECURE DIGITAL drive, a MultiMediaCard (MMC) card, an embedded MMC (eMMC) card, or another suitable

30 computer-readable storage medium or a combination of two or more of these, where appropriate. Herein, reference to a computer-readable storage medium excludes any medium that is not eligible for patent protection under 35 U.S.C. § 101. Herein,

reference to a computer-readable storage medium excludes transitory forms of signal transmission (such as a propagating electrical or electromagnetic signal per se) to the extent that they are not eligible for patent protection under 35 U.S.C. § 101.

This disclosure contemplates one or more computer-readable storage media 5 implementing any suitable storage. In particular embodiments, a computer-readable storage medium implements one or more portions of controller 704 (such as, for example, one or more internal registers or caches), one or more portions of memory 705, or a combination of these, where appropriate. In particular embodiments, a computer-readable storage medium implements RAM or ROM. In particular 10 embodiments, a computer-readable storage medium implements volatile or persistent memory. In particular embodiments, one or more computer-readable storage media embody software. Herein, reference to software may encompass one or more applications, bytecode, one or more computer programs, one or more executables, one or more instructions, logic, machine code, one or more scripts, or source code, and 15 vice versa, where appropriate. In particular embodiments, software includes one or more application programming interfaces (APIs). This disclosure contemplates any suitable software written or otherwise expressed in any suitable programming language or combination of programming languages. In particular embodiments, software is expressed as source code or object code. In particular embodiments, 20 software is expressed in a higher-level programming language, such as, for example, C, Perl, JavaScript, or a suitable extension thereof. In particular embodiments, software is expressed in a lower-level programming language, such as assembly language (or machine code). In particular embodiments, software is expressed in JAVA. In particular embodiments, software is expressed in Hyper Text Markup 25 Language (HTML), Extensible Markup Language (XML), or other suitable markup language

The present disclosure encompasses all changes, substitutions, variations, alterations, and modifications to the example embodiments herein that a person having ordinary skill in the art would comprehend. Similarly, where appropriate, the appended claims 30 encompass all changes, substitutions, variations, alterations, and modifications to the example embodiments herein that a person having ordinary skill in the art would comprehend.

CLAIMS

What is claimed is:

1. A method, comprising:
 - in response to a touch event generated during execution of an application, the application comprising one or more user interface layers arranged in a navigation hierarchy:
 - determining an application layer corresponding to the touch event;
 - if the touch event is a forward lateral flick event:
 - navigating to a next layer identified in a navigation history, if the navigation history identifies the next layer; and
 - if the touch event is a backward lateral flick event:
 - navigating to a previous layer identified in a navigation history, if the navigation history identifies the previous layer.
- 15 2. The method of Claim 1, further comprising:
 - if the touch event is a tap event:
 - navigating to a home layer if the determined application layer is not the home layer.
- 20 3. The method of Claim 1 wherein the application is a web browser.
4. The method of Claim 1 wherein the application is an operating system.
5. An apparatus, comprising:
 - 25 a memory;
 - one or more processors;
 - a display;
 - a first side-mounted touchpad;
 - a second side-mounted input device;
- 30 a program comprising computer-readable instructions operative, when executed, to cause the one or more processors to:
 - in response to a touch event generated during execution of an

application running on the apparatus, the application comprising one or more user interface layers arranged in a navigation hierarchy:

 determine an application layer corresponding to the touch event;

5 if the touch event is a forward lateral flick event associated with the first side-mounted touchpad:

 navigate to a next layer identified in a navigation history, if the navigation history identifies the next layer; and

 if the touch event is a backward lateral flick event associated with the first die-mounted touchpad:

10 navigate to a previous layer identified in a navigation history, if the navigation history identifies the previous layer.

6. The apparatus of Claim 5 wherein the program further comprises instructions operative to cause the one or more processors to:

15 if the touch event is a tap event associated with the second side-mounted input device:

 navigate to a home layer if the determined application layer is not the home layer

20 7. The apparatus of Claim 5 wherein the display is a touch screen.

8. The apparatus of Claim 5 wherein the first side-mounted touchpad comprises a concave surface.

25 9. The apparatus of Claim 5 wherein the second side-mounted input device is a touchpad.

10. The apparatus of Claim 5 wherein the second side-mounted input device is a clickable button.

30 11. The apparatus of Claim 5 wherein the application is a web browser client application hosted by the apparatus.

12. The apparatus of Claim 5 wherein the application is an operating system of the apparatus.

5 13. One or more computer-readable tangible storage media embodying software operable when executed by a computing device to:

in response to a touch event generated during execution of an application running on the computing device, the application comprising one or more user interface layers arranged in a navigation hierarchy:

determine an application layer corresponding to the touch event;

10 if the touch event is a forward lateral flick event:

navigating to a next layer identified in a navigation history, if the navigation history identifies the next layer; and

if the touch event is a backward lateral flick event:

navigating to a previous layer identified in a navigation history, if the navigation history identifies the previous layer.

15

14. The media of Claim 13, further comprising software operable when executed by one or more computing devices to:

if the touch event is a tap event:

20

navigate to a home layer if the determined application layer is not the home layer.

15. The media of Claim 13, wherein the application is a web browser.

25

16. The media of Claim 13, wherein the application is an operating system.




FIGURE 1




FIGURE 2




FIGURE 3A




FIGURE 3C




FIGURE 3B





FIGURE 4






FIGURE 5A




FIGURE 5B




FIGURE 5D




FIGURE 5C







FIGURE 5F

FIGURE 5E






FIGURE 6




FIGURE 7

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US2012/054973**A. CLASSIFICATION OF SUBJECT MATTER****G06F 3/01(2006.01)i, G06F 3/048(2006.01)i, G06F 3/041(2006.01)i, G06F 3/14(2006.01)i, G06F 9/44(2006.01)i**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

G06F 3/01; G06F 3/048; G06F 3/033; G06F 3/00; G06F 3/045; G06F 3/041; G09G 5/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
Korean utility models and applications for utility models
Japanese utility models and applications for utility modelsElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
eKOMPASS(KIPO internal) & Keywords: lateral, side, touch, navigation, forward, backward, application, layer, user interface**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	US 2010-0079395 A1 (KYUNG JIN KIM et al.) 1 April 2010 See abstract, paragraphs [0053], [0058], [0134]–[0147], [0166], [0177], claim 1, and figures 1, 4–11	1,3–5,7–13,15,16
A		2,6,14
Y	US 2011-0179368 A1 (NICHOLAS V. KING et al.) 21 July 2011 See abstract, paragraphs [0003], [0040], [0074], [0075], claim 1, and figures 1, 8–12	1,3–5,7–13,15,16
A	US 2010-0315356 A1 (BRAN FERREN et al.) 16 December 2010 See abstract, paragraphs [0015]–[0035], claim 1, and figures 1–4	1–16
A	US 2007-0288856 A1 (STEFAN GEOFFREY BUTLIN et al.) 13 December 2007 See abstract, paragraphs [0003]–[0022], and figures 3–5	1–16

 Further documents are listed in the continuation of Box C. See patent family annex.

* Special categories of cited documents:
 "A" document defining the general state of the art which is not considered to be of particular relevance
 "E" earlier application or patent but published on or after the international filing date
 "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)
 "O" document referring to an oral disclosure, use, exhibition or other means
 "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
 "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
 "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
 "&" document member of the same patent family

Date of the actual completion of the international search
26 FEBRUARY 2013 (26.02.2013)

Date of mailing of the international search report

27 FEBRUARY 2013 (27.02.2013)

Name and mailing address of the ISA/KR



Facsimile No. 82-42-472-7140

Authorized officer

LEE, Chang Yong

Telephone No. 82-42-481-5398



INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2012/054973

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US20100079395 A1	01.04.2010	KR 10-2010-0035475 A KR 10-2010-0038528 A WO 2010-036050 A2	05.04.2010 15.04.2010 01.04.2010
US20110179368 A1	21.07.2011	None	
US20100315356 A1	16.12.2010	CN 101924786 A CN 101925034 A CN 101925152 A CN 101968694 A CN 101969511 A CN 102012625 A CN 102393808 A CN 102404510 A CN 102414698 A CN 102414995 A CN 102415204 A CN 102422246 A CN 102428405 A CN 102428432 A CN 102447836 A CN 102447837 A CN 102447838 A CN 102523381 A CN 102546927 A CN 102567665 A CN 102572097 A CN 102594978 A DE 102010018864 A1 EP 2431782 A1 EP 2434372 A2 EP 2434427 A2 EP 2434427 A3 EP 2437213 A1 EP 2442167 A2 EP 2442167 A3 EP 2443511 A1 EP 2443532 A1 EP 2443536 A1 EP 2443540 A2 EP 2443591 A1 EP 2443902 A1 EP 2444930 A1 EP 2450782 A1 EP 2450783 A1 EP 2452441 A2 EP 2495594 A2 EP 2495594 A3 EP 2509021 A1	22.12.2010 22.12.2010 22.12.2010 09.02.2011 09.02.2011 13.04.2011 28.03.2012 04.04.2012 11.04.2012 11.04.2012 11.04.2012 18.04.2012 25.04.2012 25.04.2012 09.05.2012 09.05.2012 09.05.2012 27.06.2012 04.07.2012 11.07.2012 11.07.2012 18.07.2012 03.03.2011 21.03.2012 28.03.2012 28.03.2012 06.06.2012 04.04.2012 18.04.2012 17.10.2012 25.04.2012 25.04.2012 25.04.2012 25.04.2012 25.04.2012 25.04.2012 25.04.2012 09.05.2012 09.05.2012 16.05.2012 05.09.2012 28.11.2012 10.10.2012

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2012/054973

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		EP 2509022 A1	10.10.2012
		EP 2509023 A1	10.10.2012
		GB 201009712 D0	21.07.2010
		GB 2471175 A	22.12.2010
		GB 2471176 A	22.12.2010
		GB 2471177 A	22.12.2010
		GB 2471178 A	22.12.2010
		GB 2471178 B	04.01.2012
		GB 2471179 A	22.12.2010
		JP 2011-004397 A	06.01.2011
		JP 2011-008767 A	13.01.2011
		JP 2011-027718 A	10.02.2011
		JP 2011-040045 A	24.02.2011
		JP 2011-041258 A	24.02.2011
		JP 2011-070643 A	07.04.2011
		JP 2012-104124 A	31.05.2012
		JP 2012-104125 A	31.05.2012
		JP 2012-104126 A	31.05.2012
		JP 2012-104127 A	31.05.2012
		JP 2012-108515 A	07.06.2012
		JP 2012-108919 A	07.06.2012
		JP 2012-108920 A	07.06.2012
		JP 2012-109976 A	07.06.2012
		JP 2012-109977 A	07.06.2012
		JP 2012-118985 A	21.06.2012
		JP 2012-120171 A	21.06.2012
		KR 10-1093845 B1	13.12.2011
		KR 10-1095151 B1	16.12.2011
		KR 10-1156238 B1	13.06.2012
		KR 10-1194124 B1	24.10.2012
		KR 10-2010-0135196 A	24.12.2010
		KR 10-2010-0135202 A	24.12.2010
		KR 10-2012-0003936 A	11.01.2012
		KR 10-2012-0003937 A	11.01.2012
		KR 10-2012-0003963 A	11.01.2012
		KR 10-2012-0006064 A	17.01.2012
		KR 10-2012-0006065 A	17.01.2012
		KR 10-2012-0006066 A	17.01.2012
		KR 10-2012-0006067 A	17.01.2012
		KR 10-2012-0012805 A	10.02.2012
		KR 10-2012-0012806 A	10.02.2012
		KR 10-2012-0013409 A	14.02.2012
		KR 10-2012-0013410 A	14.02.2012
		KR 10-2012-0013412 A	14.02.2012
		KR 10-2012-0014010 A	15.02.2012
		KR 10-2012-0014012 A	15.02.2012
		KR 10-2012-0014013 A	15.02.2012
		KR 10-2012-0015314 A	21.02.2012
		KR 10-2012-0016087 A	22.02.2012
		KR 10-2012-0018308 A	02.03.2012

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2012/054973

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		KR20100135194A	24.12.2010
		TW 201101019 A	01.01.2011
		TW 201101812 A	01.01.2011
		TW 201104543 A	01.02.2011
		TW 201105097 A	01.02.2011
		TW 201108082 A	01.03.2011
		US 2010-0315337 A1	16.12.2010
		US 2010-0316282 A1	16.12.2010
		US 2010-0317327 A1	16.12.2010
		US 2010-0317336 A1	16.12.2010
		US 2010-0317341 A1	16.12.2010
		US 2010-0317407 A1	16.12.2010
		US 2010-0317408 A1	16.12.2010
		US 2010-0318656 A1	16.12.2010
		US 2010-0318903 A1	16.12.2010
		US 2010-0319052 A1	16.12.2010
		US 8229463 B2	24.07.2012
		US 8254957 B2	28.08.2012
		WO 2010-147609 A1	23.12.2010
		WO 2010-147610 A1	23.12.2010
		WO 2010-147611 A1	23.12.2010
		WO 2010-147704 A1	23.12.2010
		WO 2010-147704 A9	23.12.2010
		WO 2010-147821 A2	23.12.2010
		WO 2010-147821 A3	23.12.2010
		WO 2010-147823 A1	23.12.2010
		WO 2010-147823 A9	23.12.2010
		WO 2010-147824 A2	23.12.2010
		WO 2010-147824 A3	23.12.2010
US20070288856 A1	13.12.2007	AR047814A1	22.02.2006
		AR047883A1	01.03.2006
		AR047884A1	01.03.2006
		AR047885A1	01.03.2006
		AR047888A1	01.03.2006
		AR048022A1	22.03.2006
		AU 2005-214401 A1	01.09.2005
		AU 2005-214404 A1	01.09.2005
		AU 2005-214405 A1	01.09.2005
		AU 2005-214406 A1	01.09.2005
		AU 2005-215457 A1	01.09.2005
		AU 2005-215465 A1	01.09.2005
		BR P10507699A	24.07.2007
		BR P10507700A	03.07.2007
		BR P10507701A	03.07.2007
		BR P10507706A	03.07.2007
		BR P10507707A	03.07.2007
		BR P10507709A	03.07.2007
		CA 2555102 A1	01.09.2005
		CA 2555557 A1	01.09.2005

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2012/054973

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		CA 2555995 A1	01.09.2005
		CA 2556284 A1	01.09.2005
		CA 2556285 A1	01.09.2005
		CA 2556294 A1	01.09.2005
		CN 100462917 C	18.02.2009
		CN 100549948 C	14.10.2009
		CN 1914596 A	14.02.2007
		CN 1922573 A	28.02.2007
		CN 1922608 A	28.02.2007
		CN 1922608 B	26.05.2010
		CN 1922609 A	28.02.2007
		CN 1922852 A	28.02.2007
		CN 1989762 A	27.06.2007
		CN 1989762 B	02.03.2011
		EP 1721241 A2	15.11.2006
		EP 1721269 A1	15.11.2006
		EP 1721443 A1	15.11.2006
		EP 1723517 A2	22.11.2006
		EP 1723520 A2	22.11.2006
		EP 1723563 A1	22.11.2006
		EP 2249250 A2	10.11.2010
		EP 2249250 A3	08.12.2010
		GB 0403709 D0	24.03.2004
		GB 2411331 A	24.08.2005
		IL 177205D0	10.12.2006
		IL 177206D0	10.12.2006
		IL 177207D0	10.12.2006
		IL 177208D0	10.12.2006
		IL 177209D0	10.12.2006
		IL 177210D0	10.12.2006
		JP 04-891094 B2	22.12.2011
		JP 04-943865 B2	09.03.2012
		JP 2007-523417 A	16.08.2007
		JP 2007-523417 T	16.08.2007
		JP 2007-523417 T	16.08.2007
		JP 2007-523418 A	16.08.2007
		JP 2007-523418 T	16.08.2007
		JP 2007-523419 A	16.08.2007
		JP 2007-523419 A6	16.08.2007
		JP 2007-523419 T	16.08.2007
		JP 2007-523420 A	16.08.2007
		JP 2007-523420 T	16.08.2007
		JP 2007-523421 A	16.08.2007
		JP 2007-523421 T	16.08.2007
		JP 2007-535025 A	29.11.2007
		JP 2007-535025 T	29.11.2007
		JP 2011-248909 A	08.12.2011
		JP 2012-155728 A	16.08.2012
		KR 10-1105176 B1	12.01.2012
		KR 10-1105177 B1	12.01.2012

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/US2012/054973

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
		KR 10-1111943 B1	13.03.2012
		KR 10-1146159 B1	25.05.2012
		KR 10-1164833 B1	11.07.2012
		KR 10-2007-0008564 A	17.01.2007
		KR20060127207A	11.12.2006
		KR20060134109A	27.12.2006
		KR20070007106A	12.01.2007
		KR20070008564A	17.01.2007
		PE00362006A1	01.03.2006
		PE00372006A1	11.02.2006
		PE00872006A1	20.03.2006
		PE00882006A1	20.03.2006
		PE00892006A1	23.03.2006
		RU 2363039 C2	27.07.2009
		RU 2383919 C2	10.03.2010
		US 2007-0266316 A1	15.11.2007
		US 2007-0283280 A1	06.12.2007
		US 2007-0300217 A1	27.12.2007
		US 2008-0037452 A1	14.02.2008
		US 2008-0282142 A1	13.11.2008
		US 8327289 B2	04.12.2012
		WO 2005-081094 A2	01.09.2005
		WO 2005-081101 A2	01.09.2005
		WO 2005-081130 A1	01.09.2005
		WO 2005-081131 A1	01.09.2005
		WO 2005-081132 A1	01.09.2005
		WO 2005-081505 A1	01.09.2005
		WO 2005-081505 A8	28.09.2006
		WO 2005-081551 A2	01.09.2005