



AU9463020

(12) PATENT ABRIDGMENT (11) Document No. AU-B-63020/94
(19) AUSTRALIAN PATENT OFFICE (10) Acceptance No. 667167

- (54) Title
ROTATING TOOL
- International Patent Classification(s)
(51)⁵ **A47C 001/024 A47C 001/121**
- (21) Application No. : **63020/94** (22) Application Date : **11.05.94**
- (30) Priority Data
- | | | |
|------------------|-----------------|-----------------|
| (31) Number | (32) Date | (33) Country |
| TO93A0363 | 27.05.93 | IT ITALY |
- (43) Publication Date : **01.12.94**
- (44) Publication Date of Accepted Application : **07.03.96**
- (71) Applicant(s)
PRO-CORD S.R.L.
- (72) Inventor(s)
GIANCARLO PIRETTI
- (74) Attorney or Agent
PHILLIPS ORMONDE & FITZPATRICK , 367 Collins Street, MELBOURNE VIC 3000
- (56) Prior Art Documents
US 5203853
US 4938532
EP 131553
- (57) Claim

1. A chair including a base structure, a seat supported by the base structure and a backrest having a support structure which is pivotally mounted on the base structure around a transverse horizontal axis and movable between a relatively upright position and a backwardly reclined position, and spring means biasing the backrest towards its upright position,

wherein said spring means includes a leaf spring arranged along said transverse horizontal axis of the backrest support structure and having a central portion operatively connected to said base structure and opposite ends connected to said backrest support structure, and

wherein said base structure includes a tubular cross member inside which said leaf spring is arranged, said tubular cross member extending the entire length of said leaf spring and having at its central portion at least an inner stop element adapted to cooperate with said leaf spring to limit rotation of the latter.

AUSTRALIA

Patents Act

667167

COMPLETE SPECIFICATION
(ORIGINAL)

Application Number:
Lodged:

Class

Int. Class

Complete Specification Lodged:
Accepted:
Published:

Priority

Related Art:

Name of Applicant:

Pro-Cord S.r.l.

Actual Inventor(s):

Giancarlo Piretti

Address for Service:

PHILLIPS ORMONDE & FITZPATRICK
Patent and Trade Mark Attorneys
367 Collins Street
Melbourne 3000 AUSTRALIA

Invention Title:

CHAIR WITH TILTING BACKREST

Our Ref : 368116
POF Code: 192558/228094

The following statement is a full description of this invention, including the best method of performing it known to applicant(s):

Chair with tilting backrest.

The present invention relates to chairs of the type comprising a base structure, a seat supported by the base structure and a backrest having a support structure pivotally mounted on said base structure around a transverse horizontal axis and movable between a relatively upright position and a backwardly reclined position, and spring means biasing said backrest towards its upright position.

In recent years, there has been more and more research in order to provide chairs characterized by a sitting posture which is ergonomically proper and of maximum comfort even in the field of chairs to be used in public places, such as cinemas, theatres, auditoriums or meeting and conference rooms and the like. Naturally, the structure of a chair of this type must be necessarily simple and of low cost. Therefore, the designers have been compelled to seek for compromise solutions between the opposite needs which have been mentioned above, no completely satisfactory solution being found to date.

The applicant started from considering that even a chair to be used in a public place must be provided, in a way similar to what usually happens for office chairs, with a tilting backrest biased elastically towards its upright position.

Therefore, the object of the invention is that of providing a chair of the type indicated at the beginning of the present description which on one hand ~~minimizes~~ ~~solves~~ the above mentioned problems satisfactorily, so as to have a particularly advantageous application in the field of seats of chairs for public use and, on the other hand, is able to be used advantageously even in different fields, such as in the field of office chairs or house chairs.



The invention accordingly provides a chair including a base structure, a seat supported by the base structure and a backrest having a support structure which is pivotally mounted on the base structure around a transverse horizontal axis and movable between a relatively upright position and a backwardly reclined position, and spring means biasing the backrest towards its upright position,

wherein said spring means includes a leaf spring arranged along said transverse horizontal axis of the backrest support structure and having a central portion operatively connected to said base structure and opposite ends connected to said backrest support structure, and

wherein said base structure includes a tubular cross member inside which said leaf spring is arranged, said tubular cross member extending the entire length of said leaf spring and having at its central portion at least an inner stop element adapted to cooperate with said leaf spring to limit rotation of the latter.

Each half portion of said leaf spring acts as a torsion bar rigidly connected to the base structure at the centre of the leaf spring and connected to said backrest at the respective end of the leaf spring. Therefore, this arrangement provides the effects of two torsion bars respectively associated with the two sides of the backrest, with the advantage however of having a structure extremely simple and of low costs, as well as easy and quick to be mounted.

In the preferred embodiment of the present invention, the backrest support structure includes two side arms comprising two coaxial pins rotatably mounted within the opposed ends of said tubular cross member, each pin and the respective end of the tubular cross member being provided with stop means cooperating with each other so as to limit the tilting angular movement of said pins with respect to the tubular cross member



between two end positions corresponding to the upright position and the backward reclined position of the backrest respectively, said arrangement being such that when the backrest is in its upright position, each half portion of the leaf spring is subject to a torsion load which tends to hold the backrest in such position.

Also in said preferred embodiment, the tubular cross member comprises a sheet metal tube having at its centre two diametrically opposed areas which are inwardly deformed, against which the central part of the leaf spring abuts when the backrest is reclined backwardly. Furthermore, said stop means interacting between the ends of the tubular cross members and the respective pins which are rotatably mounted within such ends, comprises for each end of the tubular cross member a transverse member carried by said pin and having each end engaged within a circumferential slot formed in the wall of the tubular cross member.

Naturally, the above described mechanism can be applied to chairs of many different types.

Further embodiments and details of construction will become apparent from the following description with reference to the annexed drawings, given purely by way of non limiting example, in which:

figure 1 is a side elevational view of a first embodiment of a chair according to the invention,

figure 2 is a partial bottom view and on an enlarged scale of the chair of figure 1,

figure 2a is a cross sectional view taken along line II-II of figure 2,

figure 3 is a cross sectional partial view and on an enlarged scale taken along line III-III of figure 1,

figure 4 is a partially sectioned view taken along line IV-IV of figure 3,

figure 5 is an elevational side view of a second embodiment of the chair according to the invention,

figures 6, 7 show a front and a plan view of the chair of figure 5,

figure 8 shows the chair of figure 5 in a different operative condition,

figure 9 is a partial view on an enlarged scale and in cross section taken along line IX-IX of figure 5,

figures 10, 11 show cross sectional views taken along lines X-X and XI-XI of figure 9,

figure 12 is a partial cross sectional view taken along line XII-XII of figure 10,

figures 13, 14 are cross sectional views taken along lines XIII-XIII and XIV-XIV of figure 10,

figures 15 - 17 show two chairs of the type of figure 5 stacked on each other, respectively in a side, front and plan view, and

figures 18, 19 are a side view and a plan view of two chairs arranged side by side.

With reference to figures 1, 2, numeral 1 generally designates a chair comprising a base structure 2 which supports a seat 3 and a backrest 4. The base structure 2 comprises two bent tubular elements 5, 6, welded to each other and defining respectively the two front legs 7 and the two rear legs 8. Each of the two tubular elements 5, 6 has a general U-shaped configuration. Element 5 has two wings which define the front legs 7 of the chair and a central portion 9 (figure 2) which on its turn is U-bent in a horizontal plane, on which the seat 3 is fixed. The U-shaped element 6 has two wings which define the rear legs 8 and a central straight portion 10 welded to element 5 at its ends 11, one of which is visible in figure 2. The central straight portion 10 rigidly supports in a cantilever fashion two end bushes 12 (figures 3, 4) inside which

there are welded the ends of a tubular cross member of sheet metal 13 which therefore is rigidly connected to the base structure of the chair.

The backrest 4 of the chair is provided with a support structure comprising two side arms 4a each of which ends with a cylindrical pin 14 which is rotatably mounted within the respective end of the tubular cross member 13 with the interposition of a bush 15 of plastics material having a low friction. Each pin 14 is crossed by a transverse member 16 having each of its two ends engaged within a circumferential slot 17 formed in the respective bush 12, so that the angular tilting movement of the backrest 4 around axis 18 of the tubular cross member 13 is limited between two end positions respectively corresponding to a relatively upright position and a backwardly reclined position of the backrest, respectively shown with undotted line and with dotted line in figure 1. In figure 3, reference numeral 9 designates a screw for locking the transverse member 16, engaged within each side arm 4a of the backrest.

The spring bias of the backrest 4 towards its upright position is obtained by spring means comprising a leaf spring 20 arranged within the tubular cross member 13 and having its ends received within a slot 21 formed axially within pin 14 from its end surface. The central part of the sheet metal tubular cross member 13 has two areas deformed radially inwardly, diametrically opposed to each other, designated by reference numeral 22 in figure 2a, against which the central part of leaf 20 abuts when backrest 4 is reclined backwardly. The arrangement of each transverse member 16 in the respective circumferential slot 17 is such that the leaf spring 20 is subjected to a load which tends to hold the backrest 4 in its raised



position. When the seated person leans against the backrest 4, he exerts a thrust tending to recline the backrest backwardly, against the action of the leaf spring 20. This leaf spring behaves as a pair of torsion bars rigidly connected to the base structure at the centre of the leaf spring and respectively connected to the two side arms 4a which support the backrest 4.

As it is clearly apparent from the foregoing description, the chair is characterized by an extremely simple structure, which can be manufactured at low cost, easy and quick to be mounted, while ensuring at the same time a very good comfort and an ergonomically proper posture.

Figures 5-14 show a further embodiment of the chair according to the invention. In these figures, those parts which correspond to those of the chair of figures 1-4 are indicated by the same reference numerals. In the case of this embodiment, the base structure of the chair comprises two side uprights 30 provided at their lower ends with two side feet 31 defining a generally inverted T-shaped configuration and connected to each other at their upper ends by a cross member 33. As visible in figures 9, 11, uprights 30 and cross member 33 are formed by sheet metal tubes with an oval and flattened cross section. Cross member 33 is provided with two appendages 34 projecting in a cantilever fashion from two areas adjacent to the ends of the cross member which support bushes 12 (similar to those illustrated with reference to figures 1-4) within which there are welded the ends of the tubular cross member 13. The arrangement of the side arms 4a which support the backrest 4, the leaf spring 20 inside the tubular cross member 13, and the pins 14 on arms 4a which are rotatably mounted within the ends of tubular cross

member 13, is similar to that described with reference to figures 1-4.

In the case of the embodiment shown in figures 5-19, also, the structure of the seat 3 is pivotally mounted on the intermediate portion of the tubular cross member 13, so that the seat 3 may be moved between a position of normal use (figure 5) and a raised substantially vertical position (figure 8) to make the passage easier for people walking between two adjacent rows of chairs of the same type, in a public place or a conference room. The operation of the chair is absolutely similar to that described with reference to the chair of figures 1-4.

Figures 15-19 of the annexed drawings show the possibility of stacking a number of chairs of the same type above each other, while occupying a minimum space, or arranging a number of chairs of the same type in front of each other, with the seats arranged in their raised positions.

From the foregoing description, it is clearly apparent that the mechanism forming the subject of the present invention may be adapted easily to various types of chairs and allows particularly the production of chairs having on one side very good performances from the standpoint of comfort and on the other side a structure which is very simple and of low cost.

THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A chair including a base structure, a seat supported by the base structure and a backrest having a support structure which is pivotally mounted on the base structure around a transverse horizontal axis and movable between a relatively upright position and a backwardly reclined position, and spring means biasing the backrest towards its upright position,

wherein said spring means includes a leaf spring arranged along said transverse horizontal axis of the backrest support structure and having a central portion operatively connected to said base structure and opposite ends connected to said backrest support structure, and

wherein said base structure includes a tubular cross member inside which said leaf spring is arranged, said tubular cross member extending the entire length of said leaf spring and having at its central portion at least an inner stop element adapted to cooperate with said leaf spring to limit rotation of the latter.

2. A chair according to claim 1, wherein said backrest support structure includes two side arms including two coaxial pins which are rotatably mounted within the opposite ends of said tubular cross member each said pin and the respective end of said tubular cross member being provided with stop means cooperating with each other to limit the angular tilting movement of said pins with respect to the tubular cross member between two end positions corresponding respectively to the upright position and the backwardly reclined position of said backrest, said arrangement being such that, when the backrest is in its upright position, each half portion of said leaf spring is subject to a torsion load which tends to hold said backrest in said upright position.

3. A chair according to claim 2, wherein said stop element of the tubular cross member includes a radially inwardly deformed portion of the wall of the tubular cross member.



4. A chair according to claim 3, wherein the tubular cross member has at its centre two radially inwardly deformed portions, which are diametrically opposite to each other.
- 5 5. A chair according to claim 4, wherein said stop means limiting rotation of said pins with respect to said tubular cross member includes at least a transverse member mounted on each pin and having at least one end engaged within a circumferential slot formed in said tubular cross member.
- 10 6. A chair according to claim 5, wherein each of said pins has an axial slot which extends from its end surface within which there is received the respective end of said leaf spring.
7. A chair substantially as herein described with reference to the
- 15 accompanying drawings.

DATED: 3 January, 1996.

PHILLIPS ORMONDE & FITZPATRICK

20 Attorneys for:


PRO-CORD S.r.l.



ABSTRACT

In a chair (1) having a backrest (4) which can be reclined backwardly against the action of spring means, the latter comprises a leaf spring (20) having its central portion operatively connected to the base structure (2) of the chair and its ends connected to two side arms (4a) which support the backrest (4).

(Figures 1, 3)



1/6

Fig. 1




Fig. 3





Fig. 4



2/6 Fig. 2




Fig. 6

3/6




Fig. 5




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 12




Fig. 11




Fig. 13




Fig. 14




Fig. 16

5/6




Fig. 15




Fig. 17




Fig. 18




Fig. 19

