

(No Model.)

C. W. GREGG.
CORSET.

No. 567,855.

Patented Sept. 15, 1896.

Fig. 1.





Fig. 2.



Witnesses:

V. H. Bantlett
A. L. Hobby

Inventor:

Charles W. Gregg,

By Howard Sprague
Attorneys.

UNITED STATES PATENT OFFICE.

CHARLES W. GREGG, OF DETROIT, MICHIGAN, ASSIGNOR, BY MESNE ASSIGNMENTS, OF ONE-HALF TO SAMUEL H. CAMP, OF JACKSON, MICHIGAN.

CORSET.

SPECIFICATION forming part of Letters Patent No. 567,855, dated September 15, 1896.

Application filed February 18, 1896. Serial No. 579,700. (No model.)

To all whom it may concern:

Be it known that I, CHARLES W. GREGG, a citizen of the United States, residing at Detroit, in the county of Wayne and State of Michigan, have invented certain new and useful Improvements in Corsets, of which the following is a specification, reference being had therein to the accompanying drawings.

The invention consists in the construction of a corset, and particularly relates to the construction of the back, which is provided with lacing-apertures, a lacing-cord, and flaps to cover the lacing-apertures and the cord, so that the cord, even in well-fitting dresses, does not show through.

The invention further consists in the construction, arrangement, and combination of the various parts, all as more fully herein-after described.

In the drawings, Figure 1 is an elevation of the back edges of a corset, partly broken away, and Fig. 2 is a cross-section through the same.

A is the back of the corset. To each edge thereof is secured the back-section B, looped as shown at C, to embrace in the edge of the loop the edge stay D.

E is a stay parallel to the stay D, separated therefrom, and which is preferably held between the section B and the flap F, a pocket

therefor being formed by sewing through both of these sections on each side of the stay. Between the stays are the eyelets G, through which the lacing-cord, preferably a flat cord, is adapted to be laced. The flap F is of sufficient width to cover the eyelets and the edge or back stay and such portion of the lacing-cord as passes through the eyelets and over this stay. The result is that where the corset is used under a close-fitting dress the lacing-cord is covered by the flap and cannot be seen through the dress in the shape of ridges, as is the case with the construction which does not employ such covering-flaps.

What I claim as my invention is—

In a corset, the combination with the back, of a back-section secured thereto and formed with a loop and lacing-apertures, a lacing-stay secured in said loop, a flap of substantially the width of said back-section secured to the back and to the back-section and forming with said back-section a pocket, and a second stay in said pocket, substantially as described.

In testimony whereof I affix my signature in presence of two witnesses.

CHAS. W. GREGG.

Witnesses:

J. L. FOUNTAIN,
L. C. CHANDLER.