



US011962901B2

(12) **United States Patent**
Cohen et al.

(10) **Patent No.:** **US 11,962,901 B2**

(45) **Date of Patent:** ***Apr. 16, 2024**

(54) **SYSTEMS AND METHODS FOR OBTAINING A SUPER MACRO IMAGE**

(71) Applicant: **Corephotonics Ltd.**, Tel Aviv (IL)

(72) Inventors: **Noy Cohen**, Tel Aviv (IL); **Gal Shabtay**, Tel Aviv (IL); **Ephraim Goldenberg**, Tel Aviv (IL); **Nadav Geva**, Tel Aviv (IL); **Udi Yakir**, Tel Aviv (IL); **Sagi Habani**, Tel Aviv (IL); **Dolev Danino**, Tel Aviv (IL)

(73) Assignee: **Corephotonics Ltd.**, Tel Aviv (IL)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **18/346,243**

(22) Filed: **Jul. 2, 2023**

(65) **Prior Publication Data**

US 2023/0353871 A1 Nov. 2, 2023

Related U.S. Application Data

(63) Continuation of application No. 17/600,341, filed as application No. PCT/IB2021/054186 on May 15, 2021, now Pat. No. 11,770,609.

(Continued)

(51) **Int. Cl.**
H04N 23/67 (2023.01)
G02B 3/14 (2006.01)

(Continued)

(52) **U.S. Cl.**
CPC **H04N 23/67** (2023.01); **G02B 3/14** (2013.01); **G03B 13/36** (2013.01); **G06T 7/50** (2017.01); **H04N 23/69** (2023.01); **H04N 23/698** (2023.01)

(58) **Field of Classification Search**
CPC H04N 23/67; H04N 23/69; H04N 23/698; G02B 3/14; G02B 15/15; G03B 13/36;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,106,752 A 2/1938 Land
2,354,503 A 7/1944 Arthur
(Continued)

FOREIGN PATENT DOCUMENTS

CN 101276415 A 10/2008
CN 101634738 A 1/2010
(Continued)

OTHER PUBLICATIONS

Statistical Modeling and Performance Characterization of a Real-Time Dual Camera Surveillance System, Greienhagen et al., Publisher: IEEE, 2000, 8 pages.

(Continued)



Primary Examiner — Shahbaz Nazrul

(74) *Attorney, Agent, or Firm* — Nathan & Associates; Menachem Nathan

(57) **ABSTRACT**

Systems comprising a Wide/Ultra-Wide camera, a folded Tele camera comprising an optical path folding element and a Tele lens module, a lens actuator for moving the Tele lens module for focusing to object-lens distances between 3.0 cm and 35 cm with an object-to-image magnification between 1:5 and 25:1, and an application processor (AP), wherein the AP is configured to analyze image data from the UW camera to define a Tele capture strategy for a sequence of Macro images with a focus plane slightly shifted from one captured Macro image to another and to generate a new Macro image from this sequence, and wherein the focus plane and a depth of field of the new Macro image can be controlled continuously.

20 Claims, 26 Drawing Sheets



Related U.S. Application Data				
(60)	Provisional application No. 63/177,427, filed on Apr. 21, 2021, provisional application No. 63/173,446, filed on Apr. 11, 2021, provisional application No. 63/164,187, filed on Mar. 22, 2021, provisional application No. 63/119,853, filed on Dec. 1, 2020, provisional application No. 63/110,057, filed on Nov. 5, 2020, provisional application No. 63/070,501, filed on Aug. 26, 2020, provisional application No. 63/032,576, filed on May 30, 2020.	6,222,359 B1	4/2001	Duesler et al.
		6,268,611 B1	7/2001	Pettersson et al.
		6,549,215 B2	4/2003	Jouppi
		6,611,289 B1	8/2003	Yu et al.
		6,643,416 B1	11/2003	Daniels et al.
		6,650,368 B1	11/2003	Doron
		6,654,180 B2	11/2003	Ori
		6,680,748 B1	1/2004	Monti
		6,714,665 B1	3/2004	Hanna et al.
		6,724,421 B1	4/2004	Glatt
		6,738,073 B2	5/2004	Park et al.
		6,741,250 B1	5/2004	Furlan et al.
		6,750,903 B1	6/2004	Miyatake et al.
		6,778,207 B1	8/2004	Lee et al.
		7,002,583 B2	2/2006	Rabb, III
		7,015,954 B1	3/2006	Foote et al.
		7,038,716 B2	5/2006	Klein et al.
		7,187,504 B2	3/2007	Horiuchi
		7,199,348 B2	4/2007	Olsen et al.
		7,206,136 B2	4/2007	Labaziewicz et al.
		7,248,294 B2	7/2007	Slatter
		7,256,944 B2	8/2007	Labaziewicz et al.
		7,305,180 B2	12/2007	Labaziewicz et al.
		7,339,621 B2	3/2008	Fortier
		7,346,217 B1	3/2008	Gold, Jr.
		7,365,793 B2	4/2008	Cheatle et al.
		7,411,610 B2	8/2008	Doyle
		7,424,218 B2	9/2008	Baudisch et al.
		7,509,041 B2	3/2009	Hosono
		7,515,351 B2	4/2009	Chen et al.
		7,533,819 B2	5/2009	Barkan et al.
		7,564,635 B1	7/2009	Tang
		7,619,683 B2	11/2009	Davis
		7,643,225 B1	1/2010	Tsai
		7,660,049 B2	2/2010	Tang
		7,684,128 B2	3/2010	Tang
		7,688,523 B2	3/2010	Sano
		7,692,877 B2	4/2010	Tang et al.
		7,697,220 B2	4/2010	Iyama
		7,738,016 B2	6/2010	Toyofuku
		7,738,186 B2	6/2010	Chen et al.
		7,773,121 B1	8/2010	Huntsberger et al.
		7,777,972 B1	8/2010	Chen et al.
		7,809,256 B2	10/2010	Kuroda et al.
		7,813,057 B2	10/2010	Lin
		7,821,724 B2	10/2010	Tang et al.
		7,826,149 B2	11/2010	Tang et al.
		7,826,151 B2	11/2010	Tsai
		7,869,142 B2	1/2011	Chen et al.
		7,880,776 B2	2/2011	LeGall et al.
		7,898,747 B2	3/2011	Tang
		7,916,401 B2	3/2011	Chen et al.
		7,918,398 B2	4/2011	Li et al.
		7,957,075 B2	6/2011	Tang
		7,957,076 B2	6/2011	Tang
		7,957,079 B2	6/2011	Tang
		7,961,406 B2	6/2011	Tang et al.
		7,964,835 B2	6/2011	Olsen et al.
		7,978,239 B2	7/2011	Deever et al.
		8,000,031 B1	8/2011	Tsai
		8,004,777 B2	8/2011	Sano et al.
		8,077,400 B2	12/2011	Tang
		8,115,825 B2	2/2012	Culbert et al.
		8,149,327 B2	4/2012	Lin et al.
		8,149,523 B2	4/2012	Ozaki
		8,154,610 B2	4/2012	Jo et al.
		8,218,253 B2	7/2012	Tang
		8,228,622 B2	7/2012	Tang
		8,233,224 B2	7/2012	Chen
		8,238,695 B1	8/2012	Davey et al.
		8,253,843 B2	8/2012	Lin
		8,274,552 B2	9/2012	Dahi et al.
		8,279,537 B2	10/2012	Sato
		8,363,337 B2	1/2013	Tang et al.
		8,390,729 B2	3/2013	Long et al.
		8,391,697 B2	3/2013	Cho et al.
		8,395,851 B2	3/2013	Tang et al.
		8,400,555 B1	3/2013	Georgiev et al.
		8,400,717 B2	3/2013	Chen et al.
(51)	Int. Cl.			
	G03B 13/36 (2021.01)			
	G06T 7/50 (2017.01)			
	H04N 23/69 (2023.01)			
	H04N 23/698 (2023.01)			
(58)	Field of Classification Search			
	CPC G03B 30/00; G03B 37/02; G03B 17/12; G06T 7/50			
	See application file for complete search history.			
(56)	References Cited			
	U.S. PATENT DOCUMENTS			
	2,378,170 A	6/1945	Aklin	
	2,441,093 A	5/1948	Aklin	
	3,085,354 A	4/1963	Rasmussen et al.	
	3,388,956 A	6/1968	Eggert et al.	
	3,524,700 A	8/1970	Eggert et al.	
	3,558,218 A	1/1971	Grey	
	3,584,513 A	6/1971	Gates	
	3,864,027 A	2/1975	Harada	
	3,941,001 A	3/1976	LaSarge	
	3,942,876 A	3/1976	Betensky	
	4,134,645 A	1/1979	Sugiyama et al.	
	4,199,785 A	4/1980	McCullough et al.	
	4,338,001 A	7/1982	Matsui	
	4,465,345 A	8/1984	Yazawa	
	4,792,822 A	12/1988	Akiyama et al.	
	5,000,551 A	3/1991	Shibayama	
	5,005,083 A	4/1991	Grage et al.	
	5,032,917 A	7/1991	Aschwanden	
	5,041,852 A	8/1991	Misawa et al.	
	5,051,830 A	9/1991	von Hoessle	
	5,099,263 A	3/1992	Matsumoto et al.	
	5,248,971 A	9/1993	Mandl	
	5,287,093 A	2/1994	Amano et al.	
	5,327,291 A	7/1994	Baker et al.	
	5,331,465 A	7/1994	Miyano	
	5,394,520 A	2/1995	Hall	
	5,436,660 A	7/1995	Sakamoto	
	5,444,478 A	8/1995	Lelong et al.	
	5,459,520 A	10/1995	Sasaki	
	5,502,537 A	3/1996	Utagawa	
	5,657,402 A	8/1997	Bender et al.	
	5,682,198 A	10/1997	Katayama et al.	
	5,768,443 A	6/1998	Michael et al.	
	5,892,855 A	4/1999	Kakinami et al.	
	5,926,190 A	7/1999	Turkowski et al.	
	5,940,641 A	8/1999	McIntyre et al.	
	5,969,869 A	10/1999	Hirai et al.	
	5,982,951 A	11/1999	Katayama et al.	
	6,014,266 A	1/2000	Obama et al.	
	6,035,136 A	3/2000	Hayashi et al.	
	6,101,334 A	8/2000	Fantone	
	6,128,416 A	10/2000	Oura	
	6,147,702 A	11/2000	Smith	
	6,148,120 A	11/2000	Sussman	
	6,169,636 B1	1/2001	Kreitzer	
	6,201,533 B1	3/2001	Rosenberg et al.	
	6,208,765 B1	3/2001	Bergen	
	6,211,668 B1	4/2001	Duesler et al.	
	6,215,299 B1	4/2001	Reynolds et al.	

(56)

References Cited

U.S. PATENT DOCUMENTS

8,439,265	B2	5/2013	Ferren et al.	2004/0017386	A1	1/2004	Liu et al.
8,446,484	B2	5/2013	Muukki et al.	2004/0027367	A1	2/2004	Pilu
8,451,549	B2	5/2013	Yamanaka et al.	2004/0061788	A1	4/2004	Bateman
8,483,452	B2	7/2013	Ueda et al.	2004/0141065	A1	7/2004	Hara et al.
8,503,107	B2	8/2013	Chen et al.	2004/0141086	A1	7/2004	Mihara
8,514,491	B2	8/2013	Duparre	2004/0239313	A1	12/2004	Godkin
8,514,502	B2	8/2013	Chen	2004/0240052	A1	12/2004	Minefuji et al.
8,547,389	B2	10/2013	Hoppe et al.	2005/0013509	A1	1/2005	Samadani
8,553,106	B2	10/2013	Scarff	2005/0041300	A1	2/2005	Oshima et al.
8,570,668	B2	10/2013	Takakubo et al.	2005/0046740	A1	3/2005	Davis
8,587,691	B2	11/2013	Takane	2005/0062346	A1	3/2005	Sasaki
8,619,148	B1	12/2013	Watts et al.	2005/0128604	A1	6/2005	Kuba
8,718,458	B2	5/2014	Okuda	2005/0134697	A1	6/2005	Mikkonen et al.
8,752,969	B1	6/2014	Kane et al.	2005/0141103	A1	6/2005	Nishina
8,780,465	B2	7/2014	Chae	2005/0141390	A1	6/2005	Lee et al.
8,803,990	B2	8/2014	Smith	2005/0157184	A1	7/2005	Nakanishi et al.
8,810,923	B2	8/2014	Shinohara	2005/0168834	A1	8/2005	Matsumoto et al.
8,854,745	B1	10/2014	Chen	2005/0168840	A1	8/2005	Kobayashi et al.
8,896,655	B2	11/2014	Mauchly et al.	2005/0185049	A1	8/2005	Iwai et al.
8,958,164	B2	2/2015	Kwon et al.	2005/0200718	A1	9/2005	Lee
8,976,255	B2	3/2015	Matsuoto et al.	2005/0248667	A1	11/2005	Schweng et al.
9,019,387	B2	4/2015	Nakano	2005/0270667	A1	12/2005	Gurevich et al.
9,025,073	B2	5/2015	Attar et al.	2006/0054782	A1	3/2006	Olsen et al.
9,025,077	B2	5/2015	Attar et al.	2006/0056056	A1	3/2006	Ahiska et al.
9,041,835	B2	5/2015	Honda	2006/0067672	A1	3/2006	Washisu et al.
9,137,447	B2	9/2015	Shibuno	2006/0102907	A1	5/2006	Lee et al.
9,185,291	B1	11/2015	Shabtay et al.	2006/0125937	A1	6/2006	LeGall et al.
9,215,377	B2	12/2015	Sokeila et al.	2006/0126737	A1	6/2006	Boice et al.
9,215,385	B2	12/2015	Luo	2006/0170793	A1	8/2006	Pasquarette et al.
9,229,194	B2	1/2016	Yoneyama et al.	2006/0175549	A1	8/2006	Miller et al.
9,235,036	B2	1/2016	Kato et al.	2006/0181619	A1	8/2006	Liow et al.
9,241,111	B1*	1/2016	Baldwin H04N 23/45	2006/0187310	A1	8/2006	Janson et al.
9,270,875	B2	2/2016	Brisedoux et al.	2006/0187322	A1	8/2006	Janson et al.
9,279,957	B2	3/2016	Kanda et al.	2006/0187338	A1	8/2006	May et al.
9,286,680	B1	3/2016	Jiang et al.	2006/0227236	A1	10/2006	Pak
9,344,626	B2	5/2016	Silverstein et al.	2006/0238902	A1	10/2006	Nakashima et al.
9,360,671	B1	6/2016	Zhou	2006/0275025	A1	12/2006	Labaziewicz et al.
9,369,621	B2	6/2016	Malone et al.	2007/0024737	A1	2/2007	Nakamura et al.
9,413,930	B2	8/2016	Geerds	2007/0126911	A1	6/2007	Nanjo
9,413,984	B2	8/2016	Attar et al.	2007/0127040	A1	6/2007	Davidovici
9,420,180	B2	8/2016	Jin	2007/0159344	A1	7/2007	Kisacanan
9,438,792	B2	9/2016	Nakada et al.	2007/0177025	A1	8/2007	Kopet et al.
9,485,432	B1	11/2016	Medasani et al.	2007/0188653	A1	8/2007	Pollock et al.
9,488,802	B2	11/2016	Chen et al.	2007/0189386	A1	8/2007	Imagawa et al.
9,568,712	B2	2/2017	Dror et al.	2007/0229983	A1	10/2007	Saori
9,578,257	B2	2/2017	Attar et al.	2007/0247726	A1	10/2007	Sudoh
9,618,748	B2	4/2017	Munger et al.	2007/0253689	A1	11/2007	Nagai et al.
9,678,310	B2	6/2017	Iwasaki et al.	2007/0257184	A1	11/2007	Olsen et al.
9,681,057	B2	6/2017	Attar et al.	2007/0285550	A1	12/2007	Son
9,723,220	B2	8/2017	Sugie	2008/0017557	A1	1/2008	Witdouck
9,736,365	B2	8/2017	Laroia	2008/0024614	A1	1/2008	Li et al.
9,736,391	B2	8/2017	Du et al.	2008/0025634	A1	1/2008	Border et al.
9,768,310	B2	9/2017	Ahn et al.	2008/0030592	A1	2/2008	Border et al.
9,800,798	B2	10/2017	Ravirala et al.	2008/0030611	A1	2/2008	Jenkins
9,817,213	B2	11/2017	Mercado	2008/0056698	A1	3/2008	Lee et al.
9,851,803	B2	12/2017	Fisher et al.	2008/0084484	A1	4/2008	Ochi et al.
9,894,287	B2	2/2018	Qian et al.	2008/0088942	A1	4/2008	Seo
9,900,522	B2	2/2018	Lu	2008/0094730	A1	4/2008	Toma et al.
9,927,600	B2	3/2018	Goldenberg et al.	2008/0094738	A1	4/2008	Lee
2002/0005902	A1	1/2002	Yuen	2008/0094738	A1	4/2008	Lee
2002/0030163	A1	3/2002	Zhang	2008/0106629	A1	5/2008	Kurtz et al.
2002/0054214	A1	5/2002	Yoshikawa	2008/0117316	A1	5/2008	Orimoto
2002/0063711	A1	5/2002	Park et al.	2008/0129831	A1	6/2008	Cho et al.
2002/0075258	A1	6/2002	Park et al.	2008/0218611	A1	9/2008	Parulski et al.
2002/0118471	A1	8/2002	Imoto	2008/0218612	A1	9/2008	Border et al.
2002/0122113	A1	9/2002	Foote	2008/0218613	A1	9/2008	Janson et al.
2002/0167741	A1	11/2002	Koiwai et al.	2008/0219654	A1	9/2008	Border et al.
2003/0030729	A1	2/2003	Prentice et al.	2008/0291531	A1	11/2008	Heimer
2003/0048542	A1	3/2003	Enomoto	2008/0304161	A1	12/2008	Souma
2003/0093805	A1	5/2003	Gin	2009/0002839	A1	1/2009	Sato
2003/0156751	A1	8/2003	Lee et al.	2009/0067063	A1	3/2009	Asami et al.
2003/0160886	A1	8/2003	Misawa et al.	2009/0086074	A1	4/2009	Li et al.
2003/0202113	A1	10/2003	Yoshikawa	2009/0102948	A1	4/2009	Scherling
2004/0008773	A1	1/2004	Itokawa	2009/0109556	A1	4/2009	Shimizu et al.
2004/0012683	A1	1/2004	Yamasaki et al.	2009/0122195	A1	5/2009	Van Baar et al.
				2009/0122406	A1	5/2009	Rouvinen et al.
				2009/0122423	A1	5/2009	Park et al.
				2009/0128644	A1	5/2009	Camp et al.
				2009/0135245	A1	5/2009	Luo et al.
				2009/0141365	A1	6/2009	Jannard et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2009/0147368	A1	6/2009	Oh et al.	2012/0196648	A1	8/2012	Havens et al.
2009/0168135	A1	7/2009	Yu et al.	2012/0229663	A1	9/2012	Nelson et al.
2009/0200451	A1	8/2009	Connors	2012/0229920	A1	9/2012	Otsu et al.
2009/0219547	A1	9/2009	Kauhanen et al.	2012/0249815	A1	10/2012	Bohn et al.
2009/0225438	A1	9/2009	Kubota	2012/0262806	A1	10/2012	Lin et al.
2009/0234542	A1	9/2009	Orlewski	2012/0287315	A1	11/2012	Huang et al.
2009/0252484	A1	10/2009	Hasuda et al.	2012/0320467	A1	12/2012	Baik et al.
2009/0279191	A1	11/2009	Yu	2013/0002928	A1	1/2013	Imai
2009/0295949	A1	12/2009	Ojala	2013/0002933	A1	1/2013	Topliss et al.
2009/0303620	A1	12/2009	Abe et al.	2013/0016427	A1	1/2013	Sugawara
2009/0324135	A1	12/2009	Kondo et al.	2013/0057971	A1	3/2013	Zhao et al.
2010/0013906	A1	1/2010	Border et al.	2013/0063629	A1	3/2013	Webster et al.
2010/0020221	A1	1/2010	Tupman et al.	2013/0076922	A1	3/2013	Shihoh et al.
2010/0033844	A1	2/2010	Katano	2013/0088788	A1	4/2013	You
2010/0060746	A9	3/2010	Olsen et al.	2013/0093842	A1	4/2013	Yahata
2010/0060995	A1	3/2010	Yumiki et al.	2013/0094126	A1	4/2013	Rappoport et al.
2010/0097444	A1	4/2010	Lablans	2013/0113894	A1	5/2013	Mirlay
2010/0103194	A1	4/2010	Chen et al.	2013/0135445	A1	5/2013	Dahi et al.
2010/0134621	A1	6/2010	Namkoong et al.	2013/0148215	A1	6/2013	Mori et al.
2010/0165131	A1	7/2010	Makimoto et al.	2013/0148854	A1	6/2013	Wang et al.
2010/0165476	A1	7/2010	Eguchi	2013/0155176	A1	6/2013	Paripally et al.
2010/0196001	A1	8/2010	Ryynänen et al.	2013/0163085	A1	6/2013	Lim et al.
2010/0202068	A1	8/2010	Ito	2013/0182150	A1	7/2013	Asakura
2010/0214664	A1	8/2010	Chia	2013/0201360	A1	8/2013	Song
2010/0238327	A1	9/2010	Griffith et al.	2013/0202273	A1	8/2013	Ouedraogo et al.
2010/0246024	A1	9/2010	Aoki et al.	2013/0208178	A1	8/2013	Park
2010/0259836	A1	10/2010	Kang et al.	2013/0229544	A1	9/2013	Bando
2010/0265331	A1	10/2010	Tanaka	2013/0235224	A1	9/2013	Park et al.
2010/0277813	A1	11/2010	Ito	2013/0250150	A1	9/2013	Malone et al.
2010/0283842	A1	11/2010	Guissin et al.	2013/0258044	A1	10/2013	Betts-LaCroix
2010/0321494	A1	12/2010	Peterson et al.	2013/0258048	A1	10/2013	Wang et al.
2011/0001838	A1	1/2011	Lee	2013/0270419	A1	10/2013	Singh et al.
2011/0032409	A1	2/2011	Rossi et al.	2013/0271852	A1	10/2013	Schuster
2011/0058320	A1	3/2011	Kim et al.	2013/0278785	A1	10/2013	Nomura et al.
2011/0063417	A1	3/2011	Peters et al.	2013/0279032	A1	10/2013	Suigetsu et al.
2011/0063446	A1	3/2011	McMordie et al.	2013/0286221	A1	10/2013	Shechtman et al.
2011/0064327	A1	3/2011	Dagher et al.	2013/0286488	A1	10/2013	Chae
2011/0080487	A1	4/2011	Venkataraman et al.	2013/0321668	A1	12/2013	Kamath
2011/0080655	A1	4/2011	Mori	2014/0009631	A1	1/2014	Topliss
2011/0102667	A1	5/2011	Chua et al.	2014/0022436	A1	1/2014	Kim et al.
2011/0102911	A1	5/2011	Iwasaki	2014/0049615	A1	2/2014	Uwagawa
2011/0115965	A1	5/2011	Engelhardt et al.	2014/0063616	A1	3/2014	Okano et al.
2011/0121666	A1	5/2011	Park et al.	2014/0092487	A1	4/2014	Chen et al.
2011/0128288	A1	6/2011	Petrou et al.	2014/0118584	A1	5/2014	Lee et al.
2011/0149119	A1	6/2011	Matsui	2014/0139719	A1	5/2014	Fukaya et al.
2011/0157430	A1	6/2011	Hosoya et al.	2014/0146216	A1	5/2014	Okumura
2011/0164172	A1	7/2011	Shintani et al.	2014/0160311	A1	6/2014	Hwang et al.
2011/0188121	A1	8/2011	Goring et al.	2014/0160581	A1	6/2014	Cho et al.
2011/0221599	A1	9/2011	Högasten	2014/0192224	A1	7/2014	Laroia
2011/0229054	A1	9/2011	Weston et al.	2014/0192238	A1	7/2014	Attar et al.
2011/0234798	A1	9/2011	Chou	2014/0192253	A1	7/2014	Laroia
2011/0234853	A1	9/2011	Hayashi et al.	2014/0204480	A1	7/2014	Jo et al.
2011/0234881	A1	9/2011	Wakabayashi et al.	2014/0218587	A1	8/2014	Shah
2011/0242286	A1	10/2011	Pace et al.	2014/0240853	A1	8/2014	Kubota et al.
2011/0242355	A1	10/2011	Goma et al.	2014/0285907	A1	9/2014	Tang et al.
2011/0249347	A1	10/2011	Kubota	2014/0293453	A1	10/2014	Ogino et al.
2011/0285714	A1	11/2011	Swic et al.	2014/0313316	A1	10/2014	Olsson et al.
2011/0298966	A1	12/2011	Kirschstein et al.	2014/0362242	A1	12/2014	Takizawa
2012/0014682	A1	1/2012	David et al.	2014/0362274	A1	12/2014	Christie et al.
2012/0026366	A1	2/2012	Golan et al.	2014/0376090	A1	12/2014	Terajima
2012/0044372	A1	2/2012	Cote et al.	2014/0379103	A1	12/2014	Ishikawa et al.
2012/0062780	A1	3/2012	Morihisa	2015/0002683	A1	1/2015	Hu et al.
2012/0062783	A1	3/2012	Tang et al.	2015/0002684	A1	1/2015	Kuchiki
2012/0069235	A1	3/2012	Imai	2015/0022896	A1	1/2015	Cho et al.
2012/0069455	A1	3/2012	Lin et al.	2015/0029601	A1	1/2015	Dror et al.
2012/0075489	A1	3/2012	Nishihara	2015/0042870	A1	2/2015	Chan et al.
2012/0092777	A1	4/2012	Tochigi et al.	2015/0070781	A1	3/2015	Cheng et al.
2012/0105579	A1	5/2012	Jeon et al.	2015/0086127	A1	3/2015	Camilus et al.
2012/0105708	A1	5/2012	Hagiwara	2015/0092066	A1	4/2015	Geiss et al.
2012/0124525	A1	5/2012	Kang	2015/0103147	A1	4/2015	Ho et al.
2012/0147489	A1	6/2012	Matsuoka	2015/0110345	A1	4/2015	Weichselbaum
2012/0154547	A1	6/2012	Aizawa	2015/0116569	A1	4/2015	Mercado
2012/0154614	A1	6/2012	Moriya et al.	2015/0124059	A1	5/2015	Georgiev et al.
2012/0154929	A1	6/2012	Tsai et al.	2015/0138381	A1	5/2015	Ahn
2012/0194923	A1	8/2012	Um	2015/0138431	A1	5/2015	Shin et al.
				2015/0145965	A1	5/2015	Livyatan et al.
				2015/0153548	A1	6/2015	Kim et al.
				2015/0154776	A1	6/2015	Zhang et al.
				2015/0162048	A1	6/2015	Hirata et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS

CN	102739949	A	10/2012	JP	2013148823	A	8/2013
CN	102147519	B	1/2013	JP	2014142542	A	8/2014
CN	102982518	A	3/2013	JP	2016105577	A	6/2016
CN	103024272	A	4/2013	JP	2017116679	A	6/2017
CN	203406908	U	1/2014	JP	2017146440	A	8/2017
CN	103576290	A	2/2014	JP	2018059969	A	4/2018
CN	103698876	A	4/2014	JP	2019113878	A	7/2019
CN	103841404	A	6/2014	KR	20070005946	A	1/2007
CN	104297906	A	1/2015	KR	20090019525	A	2/2009
CN	104407432	A	3/2015	KR	20090058229	A	6/2009
CN	105467563	A	4/2016	KR	20090131805	A	12/2009
CN	105657290	A	6/2016	KR	20100008936	A	1/2010
CN	205301703	U	6/2016	KR	20110058094	A	6/2011
CN	105827903	A	8/2016	KR	20110080590	A	7/2011
CN	105847662	A	8/2016	KR	20110115391	A	10/2011
CN	106680974	A	5/2017	KR	20120068177	A	6/2012
CN	104570280	B	6/2017	KR	20140135909	A	5/2013
CN	107608052	A	1/2018	KR	20130104764	A	9/2013
CN	107682489	A	2/2018	KR	1020130135805	A	11/2013
CN	109729266	A	5/2019	KR	20140014787	A	2/2014
EP	1536633	A1	6/2005	KR	20140023552	A	2/2014
EP	1780567	A1	5/2007	KR	101428042	B1	8/2014
EP	2523450	A1	11/2012	KR	101477178	B1	12/2014
JP	S54157620	A	12/1979	KR	20140144126	A	12/2014
JP	S59121015	A	7/1984	KR	20150118012	A	10/2015
JP	S59191146	A	10/1984	KR	20160000759	A	1/2016
JP	6165212	A	4/1986	KR	101632168	B1	6/2016
JP	S6370211	A	3/1988	KR	20160115359	A	10/2016
JP	H0233117	A	2/1990	KR	20170105236	A	9/2017
JP	04211230	A	8/1992	KR	20180120894	A	11/2018
JP	406059195	A	3/1994	KR	20130085116	A	6/2019
JP	H07318864	A	12/1995	TW	M602642	U	10/2020
JP	H07325246	A	12/1995	WO	2000027131	A2	5/2000
JP	H07333505	A	12/1995	WO	2004084542	A1	9/2004
JP	08271976	A	10/1996	WO	2006008805	A1	1/2006
JP	H09211326	A	8/1997	WO	2010122841	A1	10/2010
JP	H11223771	A	8/1999	WO	2013058111	A1	4/2013
JP	3210242	B2	9/2001	WO	2013063097	A1	5/2013
JP	2002010276	A	1/2002	WO	2014072818	A2	5/2014
JP	2003298920	A	10/2003	WO	2017025822	A1	2/2017
JP	2003304024	A	10/2003	WO	2017037688	A1	3/2017
JP	2004056779	A	2/2004	WO	2018130898	A1	7/2018
JP	2004133054	A	4/2004				
JP	2004245982	A	9/2004				
JP	2004334185	A	11/2004				
JP	2005099265	A	4/2005				
JP	2005122084	A	5/2005				
JP	2005321592	A	11/2005				
JP	2006195139	A	7/2006				
JP	2006237914	A	9/2006				
JP	2006238325	A	9/2006				
JP	2007133096	A	5/2007				
JP	2007164065	A	6/2007				
JP	2007219199	A	8/2007				
JP	2007228006	A	9/2007				
JP	2007306282	A	11/2007				
JP	2008076485	A	4/2008				
JP	2008111876	A	5/2008				
JP	2008191423	A	8/2008				
JP	2008271026	A	11/2008				
JP	2010032936	A	2/2010				
JP	2010164841	A	7/2010				
JP	2010204341	A	9/2010				
JP	2011055246	A	3/2011				
JP	2011085666	A	4/2011				
JP	2011138407	A	7/2011				
JP	2011145315	A	7/2011				
JP	2011203283	A	10/2011				
JP	2012132739	A	7/2012				
JP	2012203234	A	10/2012				
JP	2013003317	A	1/2013				
JP	2013003754	A	1/2013				
JP	2013101213	A	5/2013				
JP	2013105049	A	5/2013				
JP	2013106289	A	5/2013				

OTHER PUBLICATIONS

A 3MPixel Multi-Aperture Image Sensor with 0.7 μ m Pixels in 0.11 μ m CMOS, Fife et al., Stanford University, 2008, 3 pages.

Dual camera intelligent sensor for high definition 360 degrees surveillance, Scotti et al., Publisher: IET, May 9, 2000, 8 pages.

Dual-sensor foveated imaging system, Hua et al., Publisher: Optical Society of America, Jan. 14, 2008, 11 pages.

Defocus Video Matting, McGuire et al., Publisher: ACM SIG-GRAPH, Jul. 31, 2005, 11 pages.

Compact multi-aperture imaging with high angular resolution, Santacana et al., Publisher: Optical Society of America, 2015, 10 pages.

Multi-Aperture Photography, Green et al., Publisher: Mitsubishi Electric Research Laboratories, Inc., Jul. 2007, 10 pages.

Multispectral Bilateral Video Fusion, Bennett et al., Publisher: IEEE, May 2007, 10 pages.

Super-resolution imaging using a camera array, Santacana et al., Publisher: Optical Society of America, 2014, 6 pages.

Optical Splitting Trees for High-Precision Monocular Imaging, McGuire et al., Publisher: IEEE, 2007, 11 pages.

High Performance Imaging Using Large Camera Arrays, Wilburn et al., Publisher: Association for Computing Machinery, Inc., 2005, 12 pages.

Real-time Edge-Aware Image Processing with the Bilateral Grid, Chen et al., Publisher: ACM SIGGRAPH, 2007, 9 pages.

Superimposed multi-resolution imaging, Carles et al., Publisher: Optical Society of America, 2017, 13 pages.

Viewfinder Alignment, Adams et al., Publisher: Eurographics, 2008, 10 pages.

Dual-Camera System for Multi-Level Activity Recognition, Bodor et al., Publisher: IEEE, Oct. 2014, 6 pages.

Engineered to the task: Why camera-phone cameras are different,

(56)

References Cited

OTHER PUBLICATIONS

Giles Humpston, Publisher: Solid State Technology, Jun. 2009, 3 pages.

A compact and cost effective design for cell phone zoom lens, Chang et al., Sep. 2007, 8 pages.

Consumer Electronic Optics: How small a lens can be? The case of panomorph lenses, Thibault et al., Sep. 2014, 7 pages.

Optical design of camera optics for mobile phones, Steinich et al., 2012, pp. 51-58 (8 pages).

The Optics of Miniature Digital Camera Modules, Bareau et al., 2006, 11 pages.

Modeling and measuring liquid crystal tunable lenses, Peter P. Clark, 2014, 7 pages.

Mobile Platform Optical Design, Peter P. Clark, 2014, 7 pages.

Boye et al., "Ultrathin Optics for Low-Profile Innocuous Imager", Sandia Report, 2009, pp. 56-56.

"Cheat sheet: how to understand f-stops", Internet article, Digital Camera World, 2017.

Office action in related Chinese patent application No. 202180002905.0, dated Apr. 18, 2023.

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 1C




FIG. 1D




FIG. 1E




FIG. 1F




FIG. 1G

130







FIG. 1H





170




FIG. 1L




FIG. 1M




FIG. 1N




FIG. 1O




FIG. 1P




FIG. 1Q






FIG. 1R








FIG. 1U






FIG. 2C






FIG. 2D



KNOWN ART

FIG. 3A



KNOWN ART

FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 5D




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10

SYSTEMS AND METHODS FOR OBTAINING A SUPER MACRO IMAGE

CROSS REFERENCE TO RELATED APPLICATIONS

This application is a continuation from U.S. patent application Ser. No. 17/600,341 filed Sep. 30, 2021 (now allowed), which was a 371 application from international application PCT/IB2021/054186 filed May 15, 2021, and is related to and claims priority from U.S. Provisional patent Applications No. 63/032,576 filed May 30, 2020, No. 63/070,501 filed on Aug. 26, 2020, No. 63/110,057 filed Nov. 5, 2020, No. 63/119,853 filed Dec. 1, 2020, No. 63/164,187 filed Mar. 22, 2021, No. 63/173,446 filed Apr. 11, 2021 and No. 63/177,427 filed Apr. 21, 2021, all of which are expressly incorporated herein by reference in their entirety.

FIELD

The subject matter disclosed herein relates in general to macro images and in particular to methods for obtaining such images with mobile telephoto (“Tele” or “T”) cameras.

BACKGROUND

Multi-cameras (of which a “dual-camera” having two cameras is an example) are now standard in portable electronic mobile devices (“mobile devices”, e.g. smartphones, tablets, etc.). A multi-camera usually comprises a wide field-of-view (or “angle”) FOV_w camera (“Wide” or “W” camera), and at least one additional camera, with a narrower (than FOV_w) FOV (Tele camera with FOV_T), or with an ultra-wide field of view FOV_{uw} (wider than FOV_w, “UW” camera). A known dual camera including a W camera and a folded T camera is shown in FIG. 10.

A “Macro-photography” mode is becoming a popular differentiator. “Macro-photography” refers to photographing objects that are close to the camera, so that an image recorded on the image sensor is nearly as large as the actual object photographed. The ratio of object size over image size is the object-to-image magnification. For system cameras such as digital single-lens reflex camera (DSLR), a Macro image is defined by having an object-to-image magnification of about 1:1 or larger, e.g. 1:1.1. In the context of mobile devices this definition is relaxed, so that also an image with an object-to-image magnification of about 10:1 or even 15:1 is referred to as “Macro image”. Known mobile devices provide Macro-photography capabilities which are usually provided by enabling very close focusing with a UW camera, which has a relatively short effective focal length (EFL) of e.g. EFL=2.5 mm.

An UW camera can focus to close range required for Macro photography (e.g., 1.5 cm to 15 cm), but its spatial resolution is poor. For example, an UW camera with EFL=2.5 mm focused to an object at 5 cm (lens-object distance) will have approximately 19:1 object-to-image magnification. This according to the thin lens equation:

$$\frac{1}{EFL} = \frac{1}{u} + \frac{1}{v}$$

with EFL=2.5 mm, a lens-image distance v=2.6 mm and an object-lens distance of u=50 mm. Even when focused as close as 1.5 cm, the object-to-image magnification of the

UW camera will be approximately 5:1. Capturing objects in Macro images from these short object-lens distances of e.g. u=5 cm or less is very challenging for a user—e.g. it may make framing of the image very hard, it may prohibit taking image of popular Macro objects such as living subjects (e.g. insects), and it may introduce shadows and obscure the lighting in the scene

A dedicated Macro camera may be realized with a smartphone’s Tele camera. Tele cameras focused to close objects have a very shallow depth of field (DOF). Consequently, capturing Macro images in Macro-photography mode is very challenging. Popular Macro objects such as flowers or insects exhibit a significant variation in depth, and cannot be imaged all-in-focus in a single capture. It would be beneficial to have a multi camera in mobile devices that capture Macro images (i) from a larger lens-object distance (e.g. 3.0-35 cm) and (ii) with larger object-to-image magnification (e.g. 1:5-25:1).

SUMMARY

In the following and for simplicity, the terms “UW image” and “W image”, “UW camera” and “W camera”, “UW FOV” (or FOV_{uw}) and “W FOV” (or FOV_w) etc. may be used interchangeably. A W camera may have a larger FOV than a Tele camera or a Macro-capable Tele camera, and a UW camera may have a larger FOV than a W camera. Typically but not limiting, FOV_T may be 15-40 degrees, FOV_w may be 60-90 degrees and FOV_{uw} may be 90-130 degrees. A W camera or a UW camera may be capable to focus to object-lens distances that are relevant for Macro photography and that may be in the range of e.g. 2.5-15 cm. In some cases (e.g. between W and UW), FOV ranges given above may overlap to a certain degree.

In various embodiments, there are provided systems, comprising: a Wide camera for providing at least one Wide image; a Tele camera comprising a Tele lens module; a lens actuator for moving the Tele lens module for focusing to any distance or set of distances between 3.0 cm and 35 cm with an object-to-image magnification between 1:5 and 25:1; and an application processor (AP) configured to analyse image data from the Wide camera to define a capture strategy for capturing with the Tele camera a sequence of Macro images with a focus plane shifted from one captured Macro image to another captured Macro image, and to generate a new Macro image from this sequence. The focus plane and the DOF of the new Macro image can be controlled continuously. In some embodiments, the continuous control may be post-capture.

In some embodiments, the Tele camera may be a folded Tele camera comprising an optical path folding element (OPFE). In some embodiments, the Tele camera may be a double-folded Tele camera comprising two OPFEs. In some embodiments, the Tele camera may be a pop-out Tele camera comprising a pop-out lens

In some embodiments, the focusing may be to object-lens distances of 3.0-25 cm, of 3.0-15 cm, or of 10-35 cm.

In some embodiments, the Tele camera may have an EFL of 7-10 mm, of 10-20 mm, or of 20-40 mm.

In some embodiments, the Tele capture strategy may be adjusted during capture of the sequence of Macro images based on information from captured Macro images.

In some embodiments, the information from captured Macro images is processed by a Laplacian of Gaussian analysis.

In some embodiments, the image data from the UW camera is phase detection auto-focus (PDAF) data.

In some embodiments, generation of the new Macro image may use a UW image as reference image.

In some embodiments, the generation of the new Macro image may use a video stream of UW images as reference image.

In some embodiments, the AP may be configured to automatically detect objects of interests (OOIs) in the sequence of captured Macro images and to generate the new Macro image when the OOIs are entirely in-focus.

In some embodiments, the AP may be configured to automatically detect OOIs in the UW image data and to generate the new Macro image when the OOIs are entirely in-focus.

In some embodiments, the AP may be configured to automatically detect OOIs in the sequence of input Macro images and to generate the new Macro image when specific image segments of the OOIs have a specific amount of forward de-focus blur and a specific amount of backward de-focus blur.

In some embodiments, the AP may be configured to automatically detect OOIs in the UW image data and to generate the new Macro image when specific image segments of the OOIs have a specific amount of forward de-focus blur and a specific amount of backward de-focus blur.

In some embodiments, the AP may be configured to calculate a depth map from the sequence of captured Macro images and to use the depth map to generate the new Macro image.

In some embodiments, the AP may be configured to provide the new Macro image with realistic artificial lighting scenarios.

In some embodiments, the AP may be configured to analyse of image data from the Wide camera to automatically select an object and to define the capture strategy for capturing the object with the Tele camera. In some embodiments, a focus peaking map may be displayed to a user for selecting an object which is captured with the Tele camera.

In some embodiments, the AP may be configured to calculate a depth map from the PDAF data and to use the depth map to generate the new Macro image.

In some embodiments, the Tele lens module may include one or more D cut lenses.

In some embodiments, a system may further comprise a liquid lens used for focusing to the object-lens distances of 4-15 cm. In some embodiments, the power of the liquid lens can be changed continuously in a range of 0-30 dioptre. In some embodiments, the liquid lens may be located on top of the folded Tele camera's OPFE. In some embodiments, the liquid lens may be located between the folded Tele camera's OPFE and the Tele lens module.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting examples of embodiments disclosed herein are described below with reference to figures attached hereto that are listed following this paragraph. The drawings and descriptions are meant to illuminate and clarify embodiments disclosed herein, and should not be considered limiting in any way. Like elements in different drawings may be indicated by like numerals. Elements in the drawings are not necessarily drawn to scale.

FIG. 1A shows a perspective view of an embodiment of a folded Tele lens and sensor module in a Tele lens state with focus on infinity;

FIG. 1B shows a perspective view of the Tele lens and sensor module of FIG. 1A in a Macro lens state with focus on a close object;

FIG. 1C shows in cross section another continuous zoom Tele lens and sensor module disclosed herein in a minimum zoom state;

FIG. 1D shows the module of FIG. 1C in an intermediate zoom state;

FIG. 1E shows the module of FIG. of FIG. 1C in a maximum zoom state;

FIG. 1F shows in cross section yet another continuous zoom Tele lens and sensor module disclosed herein in a minimum zoom state;

FIG. 1G shows the module of FIG. 1F in an intermediate zoom state;

FIG. 1H shows the module of FIG. of FIG. 1F in a maximum zoom state;

FIG. 1I shows an embodiment of a folded Tele camera disclosed herein;

FIG. 1J shows a pop-out camera in an operational or "pop-out" state;

FIG. 1K shows the pop-out camera of FIG. 1J in a non-operational or "collapsed" state;

FIG. 1L shows an exemplary Tele-Macro camera lens system disclosed herein in a cross-sectional view in a collapsed state;

FIG. 1M shows the lens system of FIG. 1L in a first Tele state having a first EFL and a first zoom factor;

FIG. 1N shows the lens system of FIG. 1L in a second Tele state having a second EFL and a second zoom factor;

FIG. 1O shows the lens system of FIG. 1L in a Tele-Macro state having a third EFL and a third zoom factor;

FIG. 1P shows schematically another exemplary Tele-Macro camera lens system disclosed herein in a cross-sectional view in pop-out state;

FIG. 1Q shows the lens system of FIG. 1P in a first collapsed state;

FIG. 1R shows the lens system of FIG. 1P in a second collapsed state;

FIG. 1S shows schematically yet another exemplary Tele-Macro camera lens system disclosed herein in a cross-sectional view in pop-out state;

FIG. 1T shows the lens system of FIG. 1S in a collapsed state;

FIG. 1U shows schematically dual-camera output image sizes and ratios between an ultra-wide FOV and a Macro FOV;

FIG. 2A illustrates an embodiment of a folded Tele digital camera with Macro capabilities disclosed herein;

FIG. 2B illustrates another embodiment of a folded Tele digital camera with Macro capabilities disclosed herein;

FIG. 2C shows in cross section yet another continuous zoom Tele lens and sensor module disclosed herein in a first zoom state;

FIG. 2D shows the module of FIG. 2C in a second zoom state;

FIG. 2E shows the module of FIG. 2C in a third zoom state;

FIG. 3A shows a point object in focus, with a micro-lens projecting the light from the object onto the center of two sub-pixels, causing zero-disparity;

FIG. 3B shows light-rays from the point object in FIG. 3A out of focus;

FIG. 4A illustrates a method of capturing a Macro focus stack disclosed herein;

FIG. 4B illustrates another method of generating a focus stack disclosed herein;

FIG. 5A shows an exemplary Macro object and setup for capturing the Macro object;

FIG. 5B shows an output graph for the Macro setup of FIG. 5A;

FIG. 5C shows another exemplary Macro object and setup for capturing the Macro object;

FIG. 5D shows an output graph for the Macro setup of FIG. 5C;

FIG. 6 illustrates a method of generating single Macro images from a plurality of images of a focus stack;

FIG. 7 shows a graphic user interface (GUI) that a user may use to transmit a command to modify the appearance of the output image;

FIG. 8A shows a symmetric blur function;

FIG. 8B shows an asymmetric blur function with functionality as described in FIG. 8A;

FIG. 9 shows a system for performing methods disclosed herein;

FIG. 10 shows an exemplary dual-camera.

DETAILED DESCRIPTION

Tele cameras with a Macro-photography mode can switch to a Macro state by performing movements within the lens of the Tele camera, thus changing the lens's properties. Cameras with such capability are described for example in co-owned international patent applications PCT/IB2020/051405 and PCT/IB2020/058697. For example, FIGS. 19A and 19B in PCT/IB2020/051405 show two folded Tele camera states: one with the Tele lens in a first "Tele lens" state and the other with the Tele lens in a second "Macro lens" state. Because of the large EFL of a Tele camera and an image region of the image sensor that is smaller in the Macro mode than it is in the Tele mode, a "Macro lens" state may come with a small Macro FOV like FOV 198 below.

In the following, images are referred to as "Macro images", if they fulfil both of the two criteria:

Object-to-image magnification of 1:5-25:1.

Captured at an object-lens distance in the range of 30 mm-350 mm with a camera having an EFL in the range of 7 mm-40 mm.

FIGS. 1A and 1B show schematically an embodiment of a folded Tele lens and sensor module disclosed herein and numbered 100. FIG. 1A shows module 100 in a Tele lens state with focus on infinity from a top perspective view, and FIG. 1B shows module 100 in a Macro lens state with maximum object-to-image magnification (M_{max}) with a focus on a (close) object at about 4 cm from the camera from the same top perspective view.

Module 100 further comprises a first lens group (G1) 104, a second lens group (G2) 106 and a third lens group (G3) 108, a module housing 102 and an image sensor 110. In this embodiment, lens groups 104, 106 and 108 are fixedly coupled, i.e. the distances between lens groups do not change. Lens groups 104, 106 and 108 together may form a lens with an EFL=13 mm. Lens groups 104, 106 and 108 share a lens optical axis 112. For focusing, lens groups 104, 106 and 108 are actuated together by a VCM mechanism (not shown) along lens optical axis 112. A VCM mechanism (not shown) can also be used for changing between lens focus states.

With reference to FIG. 1B and to an optical design detailed in Example 6 in Table 25 of PCT/IB2020/051405, $M_{max}=2.3:1$ may be achieved (for objects at 4.2 cm). This according to a thin lens approximation with EFL=13 mm, a lens-image distance $v=19$ mm, and an object-lens distance of $u=42$ mm. M_{max} may be achieved with the lens configuration

as shown in FIG. 1B, where lens groups G1+G2+G3 are moved together as far as possible towards the object (i.e. away from sensor 110).

A smaller object-to-image magnification M may be selected continuously by capturing the object from a larger distance. A magnification of zero (for objects at infinity) is obtained with the lens configuration of FIG. 1A and with lens groups G1+G2+G3 moved together as far as possible towards image sensor 110. For magnifications between zero and M_{max} , lens groups G1+G2+G3 are moved together between the limits stated above. For example, a magnification $M=4.3:1$ may be desired. To switch from a M_{max} state to $M=4.3:1$, the lenses G1+G2+G3 must be moved together about 3 mm towards the image sensor.

In another embodiment a Macro camera may have an EFL of 25 mm and may be compared to a UW camera with EFL=2.5 mm described above. Both cameras may include a same image sensor, e.g., with 4 mm active image sensor width. When focused to 5 cm, the Macro camera with EFL=25 mm will have 1:1 object-to-image magnification and will capture an object width of 4 mm (same as the sensor width). In comparison, the UW camera with approximately 19:1 object-to-image magnification will capture an object width of 76 mm.

A Tele camera with an EFL=7-40 mm may be beneficial for Macro photography, as it can provide large image magnification. However, focusing a Tele camera to short object-lens distances is not trivial and requires large lens strokes that must support optics specifications such as limiting de-center deviations (with respect to a plane normal to an optical path) between lens and image sensor to 25 μ m or less, e.g. to 5 μ m. As an example, for focusing the Macro camera having EFL=25 mm to 10 cm (compared to focus on infinity), a lens stroke of about 6.3 mm is required. For an upright (non-folded) Tele camera, lens strokes of 2 mm or more are incompatible with mobile device (and thus camera) height constraints. However, in folded camera designs (described in FIGS. 1A-1B and FIGS. 2A-2B) or "pop-out" camera designs (described in FIGS. 1J-1K and for example in co-owned international patent application PCT/IB2020/058697) a smartphone's height does not limit such lens strokes.

In other embodiments, a folded or non-folded Tele camera for capturing Macro images may have an EFL of 7-40 mm, for example 18 mm. For Macro capability, the folded or non-folded Tele camera may be able to focus continuously to objects having an object-lens distance of e.g. 30-350 mm.

FIG. 1C-E shows an embodiment of a continuous zoom Tele lens and sensor module disclosed herein and numbered 120 in different zoom states. FIG. 1C shows module 120 in its minimum zoom state, having an EFL=15 mm, FIG. 1D shows module 120 in an intermediate zoom state, having an EFL=22.5 mm, and FIG. 1E shows module 120 in its maximum zoom state, having an EFL=30 mm.

Module 120 comprises a lens 122 with 8 single lens elements L1-L8, an image sensor 124 and, optionally, an optical window 126. The optical axis is indicated by 128. Module 120 is included in a folded Tele camera such as camera 1000. Module 120 has a continuous zoom range that can be switched continuously between a minimum zoom state and a maximum zoom state. The EFL of the maximum zoom state EFL_{MAX} and the EFL of the minimum zoom state EFL_{MIN} fulfil EFL_{MAX}=2×EFL_{MIN}. Lens 122 is divided into three lens groups, group 1 ("G1"), which is closest to an object, group 2 ("G2") and group 3 ("G3"), which is closest to sensor 124. For changing a zoom state, G1 and G3 are moved together as one group ("G13" group) with respect to

G2 and to sensor 124. For focusing, G1+G2+G3 move together as one group with respect to sensor 124.

FIG. 1F-H shows another embodiment of a continuous zoom Tele lens and sensor module disclosed herein and numbered 130 in different zoom states. FIG. 1F shows module 130 in its minimum zoom state, having an EFL=10 mm, FIG. 1G shows module 130 in an intermediate zoom state, having an EFL=20 mm, and FIG. 1H shows module 130 in its maximum zoom state, having an EFL=30 mm.

Module 130 comprises a lens 132 with 10 single lens elements L1-L10, an image sensor 134 and optionally an optical window 136. Module 130 is included in a folded Tele camera such as camera 1000. Module 130 has a continuous zoom range that can be switched continuously between a minimum zoom state and a maximum zoom state. The EFL of the maximum zoom state EFL_{MAX} and the EFL of the minimum zoom state EFL_{MIN} fulfil: $EFL_{MAX}=3 \times EFL_{MIN}$. Lens 132 is divided into four lens groups, group 1 ("G1"), which is closest to an object, group 2 ("G2"), group 3 ("G3") and group 4 ("G4") which is closest to sensor 134. For changing a zoom state, G1 and G3 are moved together as one group ("G13" group) with respect to G2, G4 and to sensor 134. For focusing, G13+G2+G4 move together as one group with respect to sensor 134.

FIG. 1I shows an embodiment of a folded Tele camera disclosed herein and numbered 140. In general, folded Tele cameras are based on one optical path folding element (OPFE). Such scanning folded Tele cameras are described for example in the co-owned international patent application PCT/IB2016/057366. Camera 140 is based on two OPFEs, so that one may refer to a "double-folded" Tele camera. Module 140 comprises a first "Object OPFE" 142, an Object OPFE actuator 144, an "Image OPFE" 146 and an Image OPFE actuator 148. A lens (not shown) is included in a lens barrel 150. Camera 140 further includes an image sensor 151 and a focusing actuator 153.

Module 140 is a scanning folded Tele camera. By rotational movement of Object OPFE 142 and Image OPFE 146, the native (diagonal) FOV (FOV_N) of camera 140 can be steered for scanning a scene. FOV_N may be 10-40 degrees, and a scanning range of FOV_N may be ± 5 deg- ± 35 deg. For example, a scanning folded Tele camera with 20 deg FOV_N and ± 20 FOV_N scanning covers a Tele FOV of 60 deg.

FIG. 1J-K shows exemplarily a pop-out Tele camera 160 which is described for example in co-owned international patent application PCT/IB2020/058697. FIG. 1J shows pop-out camera 160 in an operational or "pop-out" state. Pop-out camera 160 comprises an aperture 152, a lens barrel 154 including a lens (not shown), a pop-out mechanism 156 and an image sensor 158. FIG. 1K shows pop-out camera 160 in a non-operational or "collapsed" state. By means of pop-out mechanism 156, camera 160 is switched from a pop-out state to the collapsed state. In some dual-camera embodiments, both the W camera and the T camera may be pop-out cameras. In other embodiments, only one of the W or T cameras may be a pop-out camera, while the other (non-pop-out) camera may be a folded or a non-folded (upright) camera.

FIGS. 1L-O show schematically an exemplary pop-out Tele-Macro camera lens system 170 as disclosed herein in a cross-sectional view. Lens system 170 may be included in a pop-out camera as described in FIGS. 1J-K. FIG. 1L shows lens system 170 in a collapsed state.

FIG. 1M shows lens system 170 in a first Tele state having a first EFL (EFL1) and a first zoom factor (ZF1). FIG. 1N shows lens system 170 in a second Tele state having a second EFL (EFL2) and a second ZF2, wherein $EFL1 < EFL2$

and $ZF1 < ZF2$. FIG. 1O shows lens system 170 in a Tele-Macro state having a third EFL3 and a third ZF3. In the Tele-Macro state, a camera including lens system 170 can focus to close objects at < 350 mm object-lens distance for capturing Macro images.

FIGS. 1P-R show schematically another exemplary pop-out Tele-Macro camera lens system 180 as disclosed herein in a cross-sectional view. Lens system 180 includes a lens 182 and an image sensor 184. Lens system 180 may be included in a pop-out camera as described in FIGS. 1J-K. FIG. 1P shows lens system 180 in pop-out state. In a pop-out state, a camera including lens system 180 can focus to close objects at < 350 mm object-lens distance for capturing Macro images. FIG. 1Q shows lens system 180 in a first collapsed state. FIG. 1R shows lens system 180 in a second collapsed state.

FIGS. 1S-T show schematically another exemplary pop-out Tele-Macro camera lens system 190 as disclosed herein in a cross-sectional view. Lens system 190 includes a lens 192 and an image sensor 194. Lens system 190 may be included in a pop-out camera as described in FIGS. 1J-K. FIG. 1S shows lens system 190 in pop-out state. In a pop-out state, a camera including lens system 190 can focus to close objects at less than 350 mm object-lens distance for capturing Macro images. FIG. 1T shows lens system 190 in a collapsed state.

Modules 100, 120, 130, 140, 150, 170, 180, 190 and 220 or cameras including modules 100, 120, 130, 140, 150, 170, 180, 190 and 220 may be able/used to capture Macro images with a Macro camera module such as Macro camera module 910.

FIG. 1U illustrates in an example 195 exemplary triple camera output image sizes of, and ratios between an Ultra-Wide (UW) FOV 196, a Wide (W) FOV 197 and a Macro FOV 198. With respect to a Tele camera used for capturing objects at lens-object distances of e.g. 1 m or more, in a Macro mode based on a Tele camera, a larger image is formed at the image sensor plane. Thus an image may cover an area larger than the active area of an image sensor so that only a cropped FOV of the Tele camera's FOV may be usable for capturing Macro images. As an example, consider a Macro camera that may have an EFL of 30 mm and an image sensor with 4 mm active image sensor width. When focused to an object at 5 cm (lens-object distance) a lens-image distance of $v=77$ mm is required for focusing and an object-to-image magnification of about 1:1.5 is achieved. A Macro FOV of about 43% of the actual Tele FOV may be usable for capturing Macro images.

The following description refers to W cameras, assuming that a UW camera could be used instead.

FIG. 2A illustrates an embodiment of a folded Tele camera with Macro capabilities disclosed herein, numbered 200. Camera 200 comprises an image sensor 202, a lens 204 with an optical axis 212, and an OPFE 206, exemplarily a prism. Camera 200 further comprises a liquid lens (LL) 208 mounted on a top side (surface facing an object, which is not shown) of prism 206, in a direction 214 perpendicular to optical axis 212. The liquid lens has optical properties that can be adjusted by electrical voltage supplied by a LL actuator 210. In this embodiment, LL 208 may supply a dioptr range of 0 to 35 dioptr continuously. In a Macro photography state, the entire lens system comprising LL 208 and lens 204 may have an EFL of 7-40 mm. The DOF may be as shallow as 0.01-2 mm. In this and following embodiments, the liquid lens has a mechanical height H_{LL} and an optical height (clear height) CH. CH defines a respective height of a clear aperture (CA), where CA defines the area

of the lens surface that meets optical specifications. That is, CA is the effective optical area and CH is the effective height of the lens, see e.g. co-owned international patent application PCT/IB2018/050988.

For regular lenses with fixed optical properties (in contrast with a LL with adaptive optical properties), the ratio between the clear height and a lens mechanical height H (CH/H) is typically 0.9 or more. For a liquid lens, the CH/H ratio is typically 0.9 or less, e.g. 0.8 or 0.75. Because of this and in order to exploit the CH of the optical system comprising the prism and lens, H_{LL} may be designed to be 15% larger or 20% larger than the smallest side of the prism top surface. In embodiment 200, LL actuator **210** is located along optical axis **212** of the lens, i.e. in the -X direction in the X-Y-Z coordinate system shown. Lens **204** may be a D cut lens with a lens width W that is larger than lens height H. In an example, a width/height W/H ratio of a D cut lens may be 1.2.

FIG. 2B illustrates yet another embodiment of a folded Tele camera with Macro capabilities disclosed herein, numbered **200'**. Camera **200'** comprises the same elements as cameras **200**, except that in camera **200'** LL **208** is located between prism **206** and lens **204**. As in camera **200**, lens **204** may be a D cut lens with a lens width W that is larger than a lens height H. In an example, a width/height W/H ratio of a D cut lens may be 1.2. As in camera **200**, in a Macro photography state, the entire lens system comprising of LL **208** and lens **204** may have an EFL of 7 mm-40 mm and a DOF may be as shallow as 0.01-7.5 mm.

FIGS. 2C-2E show schematically another embodiment of a continuous zoom Tele lens and sensor module disclosed herein and numbered **220** in different zoom states. Module **220** is included in a folded Tele camera such as camera **1000**. Module **220** comprises a lens **222**, an (optional) optical element **224** and an image sensor **226**. FIGS. 2C-2E show 3 fields with 3 rays for each: the upper marginal-ray, the lower marginal-ray and the chief-ray. Lens **222** includes 6 single lens elements L1-L6. The optical axis is indicated by **228**.

FIG. 2C shows module **220** focused to infinity, FIG. 2D shows module **220** focused to 100 mm and FIG. 2E shows module **220** focused to 50 mm.

Lens **220** is divided into two lens groups G1 (includes lens elements L_1 and L_2) and G2 (includes L_3 , L_4 , L_5 and L_6) which move relative to each other and additionally together as one lens with respect to the image sensor for focusing. Because of the very shallow DOF that comes with these cameras, capturing a focus stack and building a good image out of it is not trivial. However, methods described below allow to do so.

Some multi-cameras are equipped with a W camera and a Tele camera with Macro capabilities both (or only one of the cameras) having a Phase-Detection Auto-Focus (PDAF) sensor such as a 2 PD sensor, i.e. a sensor in which each sensor pixel is divided into two or more sub-pixels and supports depth estimation via calculation of disparity. PDAF sensors take advantage of multiple micro-lenses ("ML"), or partially covered MLs to detect pixels in and out of focus. MLs are calibrated so that objects in focus are projected onto the sensor plane at the same location relative to the lens, see FIG. 3A.

FIG. 3A shows a point object **302** in focus, with a MLs projecting the light from the object onto the center of two sub-pixels, causing zero-disparity. FIG. 3B shows light-rays from a point object **304** out of focus. "Main-lens" "ML", and "Sub-pixels pair" are illustrated the same way in both FIGS. 3A and 3B. In FIG. 3B, a left ML projects the light from object **304** onto the center of a left sub-pixel. A right ML

projects the same object onto a right sub-pixel, causing a positive disparity value of 2. Objects before/after the focal plane (not shown) are projected to different locations relative to each lens, creating a positive/negative disparity between the projections. The PDAF disparity information can be used to create a "PDAF depth map". Note that this PDAF depth map is both crude (due to a very small baseline) and relative to the focal plane. That is, zero-disparity is detected for objects in focus, rather than for objects at infinity. In other embodiments, a depth map may be created based on image data from a stereo camera, a Time-of-Flight (ToF) or by methods known in the art for monocular depth such as e.g. depth from motion.

FIG. 4A illustrates a method of capturing a Macro focus stack (or "defining a Tele capture strategy") as disclosed herein. The term "focus stack" refers to a plurality of images that are captured in identical imaging conditions (i.e. camera and object are not moving during the capturing of the focus stack but the focus of the lens is moving in defined steps between consecutive image captures). An application controller (AP), for example AP **940** shown in FIG. 9, may be configured to perform the steps of this method. An object is brought into focus in step **402**. In some embodiments and for bringing an object or region into focus, a focus peaking map as known in the art may be displayed to a user. If a scanning Tele camera such as camera **140** is used, an object may be brought into focus by detecting the object in the W camera FOV and automatically steering the scanning Tele camera FOV towards this object. An object in the W camera FOV may be selected for focusing automatically by an algorithm, or manually by a human user. For example, a saliency algorithm providing a saliency map as known in the art may be used for automatic object selection by an algorithm. The user gives a capture command in step **404**. A first image is captured in the step **406**. In step **408**, the image is analysed according to methods described below and shown in FIG. 5A and FIG. 5B. In some embodiments, only segments of the image (instead of the entire image) may be analysed. The segments that are analysed may be defined by an object detection algorithm running on the image data from the Macro camera or on the image data of the W camera. Alternatively, the segments of the image that are analysed (i.e. OOIs) may be marked manually by a user. According to the results of this analysis, the lens is moved in defined steps for focusing forward (i.e. the focus moves a step away from the camera) in step **410**, or for focusing backward (i.e. the focus moves a step towards the camera) in step **412**. The forward or backward focus may depend on a command generated in step **408**. A backward focusing command may, for example, be triggered when a plateau A (A') in FIG. 5B (or FIG. 5D) is detected. A forward focusing command may, for example, be triggered when no plateau A (A') in FIG. 5B (or FIG. 5D) is detected. An additional image is captured in step **414**. These steps are repeated until the analysis in step **408** outputs a command for reversing the backward focusing or an abort command to abort focus stack capturing. An abort command may, for example, be triggered when a plateau A (A') or E (E') in FIG. 5B (or FIG. 5D) is detected. The abort command ends the focus stack capture in step **416**. In another embodiment, step **410** may be replaced by step **412** and step **412** may be replaced by step **410**, i.e. first the backward focusing may be performed and then the forward focusing may be performed.

If a scanning Tele camera such as camera **140** is used for capturing a Macro focus stack and defining a Tele capture strategy, an object that covers a FOV segment which is larger than the native Tele FOV ("object FOV") can be

captured by multiple focus stacks that cover a different FOV segment of the object FOV each. For example, W camera image data may be used to divide the object FOV in a multitude of smaller (than the Tele FOV_N) FOVs with which are captured consecutively with the focus stack capture process as described above, and stitched together after capturing the multitude of FOVs.

If a continuous zoom Tele camera such as camera 120 or camera 130 is used for capturing a Macro focus stack and defining a Tele capture strategy, e.g. depending on the size or content or color of the object FOV, a specific zoom factor may be selected. For example, W camera image data can be used to analyze a Macro object. Based on this analysis, a suitable zoom factor for the continuous zoom Tele camera may be selected. A selection criterion may be that the FOV of the continuous zoom Tele camera fully covers the Macro object. Other selection criteria may be that the FOV of the continuous zoom Tele camera not just fully covers the Macro object, but covers additionally a certain amount of background FOV, e.g. for aesthetic reasons. Yet other selection criteria may be to select a FOV so that the images captured by the continuous zoom Tele camera may have a certain DOF. As a first example, a larger DOF may be beneficial for capturing an object with a focus stack including a smaller number of single images. As a second example, a specific DOF may be beneficial, e.g. as of the Macro image's aesthetic appearance.

FIG. 4B illustrates another method of capturing a focus stack (or defining a Tele capture strategy). An AP (e.g. AP 940 shown in FIG. 9) may be configured to perform the steps of this method. In step 452, a PDAF map is captured with the W camera. In step 454, a depth map is calculated from the PDAF map as known in the art. Focus stack parameters such as focus step size and focus stack brackets are derived in step 456 from the depth map. The focus stack brackets are the upper and lower limits of the focus stack, i.e. they include two planes, a first in-focus plane with the largest object-lens distance in the focus stack, and a second in-focus plane with the smallest object-lens distance in the focus stack. A plurality of images with shifted focus is captured between these two limits. The focus step size defines the distance between two consecutive in-focus planes that were captured in the focus stack. A focus plane may have a specific depth defined by the DOF (focus plane located in center). The parameters defined in step 456 may be used to control the camera. For example, the parameters may be fed into a standard Burst mode feature for focus stack capture, as supplied for example on Android smartphones. In step 458, the focus stack is captured according to the parameters. In other embodiments, the PDAF map in step 452 may be captured not by a W camera, but by a Macro capable Tele camera. The PDAF map of the Tele camera may exhibit a higher spatial resolution, which may be desirable, and a stronger blurring of out-of-focus areas, which may be desirable or not. The stronger blurring of out-of-focus areas may be desirable for an object having a shallow depth, e.g. a depth of <1 mm. The stronger blurring of out-of-focus areas may not be desirable for an object having a larger depth, e.g. a depth of >2.5 mm. A strong blurring may render a depth calculation as performed in step 454 impossible.

In some embodiments, in step 452, PDAF image data may be captured from specific scene segments only, e.g. for a ROI only. In other embodiments, in step 452, PDAF image data may be captured from the entire scene, but depth map calculation in step 454, may be performed for segments only. The specific scene segments may be identified by image analysis performed on image data from a UW or a W or the

Tele camera. PDAF maps may be captured in step 452 not only from single images, but also from a video stream.

In some embodiments, instead of calculating a depth map in step 454, a depth map or image data for calculating a depth map may be provided by an additional camera.

In some embodiments, a different analysis method may be applied in order to analyse the entire Macro scene at only one (or only a few) focus position(s). From this analysis, a preferred focus stack step size and focus stack range may be derived. These values are then feed into a standard Burst mode feature for focus stack capture.

In some embodiments, for focus stack capture in step 458, imaging settings such as the values for white-balance and exposure time may be kept constant for all images captured in the focus stack.

Capturing a focus stack comprising Macro images with shallow DOF may require actuation of the camera's lens with high accuracy, as the DOF defines a minimum accuracy limit for the focusing process. The requirements for actuation accuracy may be derived from the images' DOF. For example, an actuation accuracy may be required that allows for controlling the location of the focus plane with an accuracy that is larger than the DOF by a factor of 2-15. As an example, consider a focus stack including Macro images having a DOF of 50 μm , i.e. segments of the scene that are located less than 25 μm distance from the focus plane are in-focus. The minimum accuracy for focusing would accordingly be 25 μm -3 μm .

Optical image stabilization (OIS) as known in the art may be used during focus stack capturing. OIS may be based on actuating the lens or the image sensor or the OPFE of camera 910. In some embodiments, depth data of the Macro scene may be used for OIS.

FIG. 5A shows exemplarily a Macro object (here Flower) and a camera for capturing the Macro object (not in scale). The flower is captured from a top position (marked by "camera").

FIG. 5B shows an exemplary output graph for the Macro setup of FIG. 5A obtained using a method described in FIG. 4A. The dots in the graph represent the results of the analysis for a specific image of the focus stack, i.e. each image in the focus stack is analysed during focus stack capturing as described above, where the analysis provides a number (sum of pixels in focus) for each image. These numbers may be plotted as illustrated here. The analysis may use functions as known in the art such as e.g. Laplacian of Gaussians, or Brenner's focus measure. An overview of suitable functions may be found in Santos et al., "Evaluation of autofocus functions in molecular cytogenetic analysis", 1997, Journal of Microscopy, Vol. 188, Pt 3, December 1997, pp. 264-272.

The analysis output is a measure for the amount of pixels in each image that are in-focus. The larger the number output for a specific image, the higher the overall number of pixels in the image that are in focus. The assumption of the focus stack analysis is that a major part of Macro objects exhibits an analysis curve characterized by common specific features. The curve is characterized (starting from a left image side, i.e. from a camera-scene setup where the focus is farther away than the Macro object) by a plateau A (focus farther away than object, so almost no pixel is in-focus and there is a small output number), followed by a positive gradient area B (where first the farthest parts of the Macro objects are in-focus and then larger parts of the Macro object are in-focus), followed by a plateau C (where for example the center of the Macro object and large parts of the object are in-focus), which is followed by a negative gradient D (where the focus moves away from Macro object center),

followed by a plateau E. The abort command as described in FIG. 4A is triggered by detecting plateau A or plateau E. Depending on which focus position the focus stack capture was started, the focus stack capture will be aborted or the direction of focus shifting will be switched (from towards the camera to away from the camera or the other way around). In general, focus stack capture may be started with a focus position where a part or point of the Macro object is in focus. The analysis will output a high number for the first image. Then focus is moved away from the camera, which means that analysis output moves on the plateau C (towards the left in the graph), until it reaches the gradient area B in the graph and in the end the plateau area A. If there is no further increase in the number outputted from the analysis, the focus is moved back to the first position (at plateau C) and focus is shifted towards the camera. The same steps as described above are performed till in the end plateau E is reached. Here the focus stack capture process is finished.

FIG. 5C shows another exemplary Macro object (here a bee) and another camera for capturing the Macro object (not in scale). FIG. 5D shows another exemplary output graph for the Macro setup of FIG. 5C using a method described in FIG. 4. Although varying in details because of the different object depth distribution, features A'-E' here are similar to features A-E in FIG. 5B.

The Tele images of the focus stack captured according to methods described e.g. in FIG. 4A, FIG. 4B and FIG. 5A-D are the input Macro images that may be further processed, e.g. by the method described in FIG. 6.

FIG. 6 illustrates a method of generating single Macro images from a plurality of images of a focus stack. An AP such as AP 940 may be configured to perform the steps of this method. Suitable images of the focus stack are selected by analysis methods known in the art in step 602. Criteria that may disqualify an image as "suitable" image may include: significant motion blur (e.g. from handshake) in an image, redundancy in captured data, or bad focus. Only selected suitable images are used further in the process. The suitable images are aligned with methods as known in the art in step 604. Suitable image regions in the aligned images are selected in step 606. Selection criteria for "suitable" regions may include the degree of focus of an area, e.g. whether an area is in focus or has a certain degree of defocus blur. The choice of selection criteria depends on the input of a user or program. A user may wish an output image with a Macro object that is all-in-focus (i.e. image with a depth of field larger than the depth of the Macro object), meaning that all the parts of the Macro object are in focus simultaneously. However, the all-in-focus view generally does not represent the most pleasant image for a human observer (as human perception comes with certain amount of blurring by depth, too), so an image with a certain focus plane and a certain amount of blurred area may be more appealing. "Focus plane" is the plane formed by all points of an un-processed image that are in focus. Images from a focus stack generated as described in FIG. 4A-B and a selection of suitable images in step 606 may allow to choose any focus plane and any amount of blurring in the output image 612 continuously. The amount of blurring of image segments that are not in focus may depend on their location in a scene. The amount of blurring may be different for image segments of object segments that are further away from the camera by some distance d with respect to the focus plane, than for image segments that are closer to the camera than the focus plane by the same distance d . The continuous control of the focus plane's position and the depth of field of the new Macro image may be performed after capturing the focus stack

("post-capture"). In some embodiments, continuous control of the focus plane's position and the depth of field of the new Macro image may be performed before capturing the focus stack ("pre-capture") as well and e.g. enabled by showing a preview video stream to a user. The selected images are fused into a single image with methods known in the art in step 608. In some embodiments and optionally, the fusion in step 608 may use depth map information, estimated e.g. using depth from focus or depth from defocus methods known in the art. In other embodiments, depth map information from PDAF (see FIG. 3A-B) may be used. The PDAF information may be provided from the image sensor of the UW camera or from the W camera or from the Tele camera with Macro capability. In some embodiments, PDAF data may be captured by the Tele camera simultaneously with capturing the Tele focus stack images, i.e. a stack of PDAF images is captured under identical focus conditions as the focus stack image. From this PDAF image stack a depth map may be calculated. E.g. one may use in-focus image segments from a single PDAF image only, as they can be assigned to a specific depth with high accuracy. By fusing the depth estimation data from all the in-focus image segments of the PDAF image stack a high-quality depth map may be generated.

In some embodiments, both Tele image data and Wide image data may be fused to one image in step 608.

In other embodiments, only a subset of the images selected in step 602 may be fused into a single image in step 608 and output in step 612. For example, a subset of only 1, only 2, or only 3, or only 4, or only 5 images may be fused into one single image in step 608 and output in step 612. In yet another embodiment, only one of the images selected in step 602 may be output in step 612. The single output image is fine-tuned in step 610 to finalize results by, e.g. reduce noise. The fine tuning may include smoothening images seams, enhancements, filters like radial blur, chroma fading, etc. The image is output in step 612.

In other embodiments, selection of suitable image regions in step 606 may be based on an image analysis performed on images from a W camera. Because of the wider FOV and larger DOF of a W camera (with respect to a Macro capable Tele camera), it may be beneficial to additionally use W image data for generating the single Macro images, e.g. for object identification and segmentation. For example, a Macro region of interest (ROI) or object of interest (OOI) may be detected in FOV_W before or during focus stack capturing with the Macro capable Tele camera. The ROI or OOI may be segmented according to methods known in the art. Segmentation means identification of coordinates of the FOV segment that contains the ROI or OOI. Via calibration of the FOV_W and FOV_T , these coordinates are translated to the FOV_T coordinates. The coordinates of ROIs or OOIs may be used for selection of suitable image regions in step 606. In some embodiments, the segmentation analysis may be performed on single images. In other embodiments, the segmentation analysis may be performed on a video stream, i.e. on a sequence of single images.

In some embodiments, image information of the W camera may be used for further tasks. One or more W images may be used as a ground truth "anchor" or reference image in the Macro image generation process. Ground truth refers here to W image information about a scene segment that is significantly more complete than the Tele image information of the same scene segment. A single W image provides significantly more information about a Macro object than a single Tele image. As an example one may think of an ROI or OOI that is mostly in-focus and fully visible in a single

15

W image but only partly visible in a single Tele image, e.g. because of the significantly shallower Tele DOF. The W ground truth or reference image may be used as ground truth anchor in the following steps of the method described in FIG. 6:

In step 602, a W image may be used for selection of suitable images. The ground truth may e.g. allow to identify Tele images that exceed a certain threshold of focus blur or motion blur.

In step 604, a W image may be used as a reference image for aligning images. In one example the Tele images of the focus stack may all be aligned with reference to the W reference image. In another example, the Tele images of the focus stack may first all be aligned with reference to the W reference image, and for more detailed alignment the Tele images may be aligned with reference to other Tele images of the focus stack.

In step 606, a W image may be used for defining suitable image regions as described above.

In step 608, a W image may be used for correction of fusion artifacts. Fusion artifacts are defined as visual features that are not present in the actual scene but that are an undesired byproduct of the image fusion process.

In step 610, a W image may be used to identify image segments in the fused image that exhibit undesired features and that may be corrected. Such undesired features may e.g. be misalignments of images, unnatural color differences or blurring caused by e.g. de-focus or motion. De-focus blur may e.g. be induced by estimation errors in the depth map used in image fusion step 608.

In yet another embodiment, the method described above may not involve any image processing such as described in steps 608-612, but may be used to select a single image from the focus stack. The selection may be performed automatically (e.g. by analyzing the focus stack for the sharpest, most clear and well-composed image with a method as described in FIG. 5A-5D) or manually by a human user. FIG. 7 shows a graphical user interface (GUI) that a user may use to transmit a command to modify the appearance of the output image, e.g. a user may transmit a command (e.g. “forward blur” and “backward blur”) for a more blurred image or an image where larger parts are in focus. “Background blur” and “forward blur” refer to the blur options as described in FIGS. 8A, 8B. In one embodiment, in case the user command is to modify the appearance of an image, the method will be re-performed from step 606 on, however with a different set of selection criteria. In another embodiment, in case the user command is to modify the appearance of an image, a blurring algorithm (artificial blurring) may be applied to the output image to form another output image. The focus plane may be changed by marking a new image segment that should be in-focus by touching the device screen. The blur may be changed according to the wishes of the user. The user may wish to modify the DOF of the displayed image, e.g. from an all-in-focus image (i.e. infinite DOF) to a more shallow DOF. A user may wish to modify the focus plane of an image that is not all-in-focus. A user may modify the image, and a pre-view image generated by an estimation indicating a projected output image may be displayed. If a user performs a click on “Apply”, a full algorithm may be applied as described in FIG. 6.

FIG. 8A shows a symmetric blur function. By moving the sliders (forward/backward blur) in FIG. 8A, a user may move linearly on the X axis, with blur applied to the image as indicated on the Y axis. FIG. 8B shows an asymmetric blur function with functionality as described in FIG. 8A.

16

Application of the blur function enables the user to blur differently the foreground and the background. For example, there are cases where forward blur may be unwanted at all, from an artistic point of view. Asymmetric blur enables this possibility.

In some embodiments, further image features such as e.g. artificial lightning may be provided. Artificial lightning means that the lightning scenario in the scene can be changed by a user or a program, e.g. by artificially moving a light source within a scene. For artificial lightning, the presence of a depth map may be beneficial.

FIG. 9 shows a system 900 for performing methods as described above. System 900 comprises a first Tele camera module (or simply “Tele camera”) 910. Tele camera 910 may be a Macro capable folded Tele camera, a double-folded Tele camera, a pop-out Tele camera, a scanning folded Tele camera, or an upright (non-folded) Tele camera. If camera 910 is a folded camera, it comprises an optical path folding element (OPFE) 912 for folding an optical path by 90 degrees, a lens module 914 and an image sensor 916. A lens actuator 918 performs a movement of lens module 914 to bring the lens to different lens states for focusing and optionally for OIS. System 910 may comprise an additional, second camera module 930, and an application processor (AP) 940. The second camera module 930 may be a W camera or a UW camera. In some embodiments, both a W camera and a UW camera may be included. AP 940 comprises an image generator 942 for generating images, and an image analyzer 946 for analyzing images as described above, as well as an object detector 944. A human machine interface (HMI) 950 such as a smartphone screen allows a user to transmit commands to the AP. A memory element 970 may be used to store image data. Calibration data for calibration between camera 910 and second camera module 930 may be stored in memory element 970 and/or in additional memory elements (not shown). The additional memory elements may be integrated in the camera 910 and/or in the second camera module 930. The additional memory elements may be EEPROMs (electrically erasable programmable read-only memory). Memory element 970 may e.g. be a NVM (non-volatile memory).

FIG. 10 illustrates a dual-camera (which may be part of a multi-camera with more than two cameras) known in the art and numbered 1000, see e.g. co-owned international patent application PCT/IB2015/056004. Dual-camera 1000 comprises a folded Tele camera 1002 and a Wide camera 1004. Tele camera 1002 comprises an OPFE 1006, a lens 1008 that may include a plurality of lens elements (not visible in this representation, but visible e.g. in FIG. 1C-H) with an optical axis 1010 and an image sensor 1012. Wide camera 1004 comprises a lens 1014 with an optical axis 1016 and an image sensor 1018. OPFE 1006 folds the optical path from a first optical path 1020 which is substantially parallel to optical axis 1016 to a second optical path which is substantially parallel optical axis 1010.

While this disclosure has been described in terms of certain embodiments and generally associated methods, alterations and permutations of the embodiments and methods will be apparent to those skilled in the art. The disclosure is to be understood as not limited by the specific embodiments described herein, but only by the scope of the appended claims.

Furthermore, for the sake of clarity the term “substantially” is used herein to imply the possibility of variations in values within an acceptable range. According to one example, the term “substantially” used herein should be interpreted to imply possible variation of up to 5% over or

under any specified value. According to another example, the term “substantially” used herein should be interpreted to imply possible variation of up to 2.5% over or under any specified value. According to a further example, the term “substantially” used herein should be interpreted to imply possible variation of up to 1% over or under any specified value.

All references mentioned in this specification are herein incorporated in their entirety by reference into the specification, to the same extent as if each individual reference was specifically and individually indicated to be incorporated herein by reference. In addition, citation or identification of any reference in this application shall not be construed as an admission that such reference is available as prior art to the present application.

What is claimed is:

1. A system, comprising:
 - a Wide camera for providing at least one Wide image;
 - a Tele camera comprising a Tele lens module;
 - a lens actuator for moving the Tele lens module for focusing to any distance or set of distances between 3.0 cm and 35 cm with an object-to-image magnification between 1:5 and 25:1; and
 - an application processor (AP) configured to analyse image data from the Wide camera to automatically select an object and to define a capture strategy for capturing the object with the Tele camera a sequence of Macro images with a focus plane shifted from one captured Macro image to another captured Macro image, and to generate a new Macro image from this sequence, wherein the system is included in a mobile electronic device.
2. The system of claim 1, wherein the focus plane and a depth of field of the new Macro image can be controlled continuously post-capture.
3. The system of claim 1, wherein the focusing is to object-lens distances of 3.0-25 cm.
4. The system of claim 1, wherein the focusing is to object-lens distances of 3.0-15 cm.
5. The system of claim 1, wherein the Tele camera is a folded Tele camera comprising an optical path folding element.
6. The system of claim 1, wherein the Tele camera is a double-folded Tele camera comprising two optical path folding elements.
7. The system of claim 1, wherein the Tele camera is a pop-out Tele camera comprising a pop-out lens.
8. The system of claim 1, wherein the AP is configured to calculate a depth map from Wide image data or Wide phase detection auto-focus (PDAF) image data and to use the

depth map to define the capture strategy for capturing with the Tele camera a sequence of Macro images or to generate the new Macro image.

9. The system of claim 1, wherein the Tele camera has an EFL of EFL=10-20 mm.
10. The system of claim 1, wherein the Tele camera has an EFL of EFL=20-40 mm.
11. The system of claim 1, wherein instead of a Wide camera an Ultra-Wide camera is used for providing at least one Ultra-Wide image.
12. The system of claim 1, wherein the Tele camera can be switched between two or more discrete zoom states.
13. The system of claim 12, wherein the AP is configured to analyse image data from the Wide camera to switch the Tele camera to a specific zoom state for capturing Macro images which have a specific magnification and a specific field of view.
14. The system of claim 12, wherein a zoom factor of a maximum zoom state is 2×larger than a zoom factor of a minimum zoom state.
15. The system of claim 13, wherein the analysis of image data from the Wide camera includes use of a saliency map.
16. The system of claim 1, wherein the generation of the new Macro image uses a Wide image as a reference image.
17. The system of claim 1, wherein the Tele capture strategy is adjusted during capture of the sequence of Macro images based on information from captured Macro images.
18. The system of claim 1, wherein the mobile electronic device is a smartphone.
19. The system of claim 1, wherein the mobile electronic device is a tablet.
20. A method, comprising: in a mobile electronic device comprising a Wide camera and a Tele camera:
 - using the Wide camera to provide at least one Wide image;
 - focusing the Tele camera to any distance or set of distances between 3.0 cm and 35 cm with an object-to-image magnification between 1:5 and 25:1;
 - based on image data from the Wide camera, automatically selecting an object and defining a capture strategy for capturing the object with the Tele camera a sequence of Macro images with a focus plane shifted from one captured Macro image to another captured Macro image; and
 - generating a new Macro image from the sequence of Macro images.

* * * * *