

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization

International Bureau



(10) International Publication Number

WO 2014/161629 A1

(43) International Publication Date
9 October 2014 (09.10.2014)

(51) International Patent Classification:

H04L 12/70 (2013.01)

(21) International Application Number:

PCT/EP2014/000661

(22) International Filing Date:

12 March 2014 (12.03.2014)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

13305447.8 5 April 2013 (05.04.2013) EP

(71) Applicant: ALCATEL LUCENT [FR/FR]; 148/152, route de la Reine, F-92100 Boulogne-Billancourt (FR).

(72) Inventor: WORRALL, Chandrika K.; Alcatel-Lucent Telecom Ltd, The Quadrant, Stonehill Green, Westlea, Swindon SN5 7DJ (GB).

(74) Agent: SARUP, David Alexander; Alcatel-Lucent Telecom Ltd., Intellectual Property Business Group, Christchurch Way, Greenwich, London SE10 0AG (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,


AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: DUAL CONNECTIVITY NETWORK



Long BSR MAC control element

FIG. 3

(57) Abstract: A method of transmitting an indication of user equipment uplink buffer status in a wireless communications network in which user equipment is configured to communicate with one or more base stations using dual connectivity techniques, a computer program product and user equipment operable to perform that method. The method comprises: receiving an indication of a dual connectivity configuration to be used by the user equipment for uplink transmission; structuring an uplink buffer status report to group uplink buffer status by one or more scheduler to be used by the user equipment according to the received indication of a dual connectivity configuration; and transmitting the structured uplink buffer status report to the one or more base stations. Aspects and embodiments provide a method for providing buffer status reports in a network offering dual connectivity functionality according to which user equipment is served by multiple independent schedulers which may be connected via a non-ideal backhaul link.

WO 2014/161629 A1

DUAL CONNECTIVITY NETWORK

FIELD OF THE INVENTION

The present invention relates to a method of transmitting an indication of user

- 5 equipment uplink buffer status in a wireless communications network in which user equipment is configured to communicate with one or more base stations using dual connectivity techniques; a computer program product and user equipment operable to perform that method.

10 BACKGROUND

Wireless telecommunication systems are known. In such systems, mobile

10 communication devices (for example, mobile telephones) are operable to communicate with base stations provided by network providers.

- 15 In known wireless telecommunication systems, radio coverage is provided to network connectable devices, such as mobile telephones, or wireless devices such as iPads or other similar tablets, within areas known as cells. A base station is located in each cell to provide radio coverage. Typically, network connectable devices in each cell are operable to receive information and data from a base station and to transmit
- 20 information and data to a base station.

User equipment roam through a wireless communications system. Base stations are

typically provided which support areas of radio coverage. A number of such base

25 stations are provided and are distributed geographically in order to provide a wide area of coverage to user equipment.

When user equipment is within an area served by a base station, communications may

be established between the user equipment and the base station over associated radio

30 links. Each base station typically supports a number of sectors within the geographical area of service. Typically, a different antenna within a base station supports each associated sector. Each base station has multiple antennas.

Traditional base stations provide coverage in relatively large geographical areas and

those cells are often referred to as macro cells. It is possible to provide a heterogeneous

35 network (hetnet) where smaller sized cells are provided within macro cells. Such

smaller sized cells are sometimes referred to as micro cells, pico cells or femto cells.

One way to establish a small cell is to provide a small cell base station that provides

coverage having a relatively limited range within the coverage area of the macro cell. The transmission power of a small cell base station is relatively low and, hence, each small cell provides a small coverage area compared to that of a macro cell and covers, for example, an office or a home.

5

Such small cells are typically provided where the communications coverage provided by the macro cell is poor or where a user wishes to use an alternative communications link provided locally, by the small cell base station, to communicate with the core network, and/or to increase capacity within a network.

10

Deployment of small cells in a wireless communication network can assist a network in relation to handling capacity in high traffic areas, for example, so-called hot spot areas. An ability to offload traffic to a small cell or cells located in a high traffic area of a network may be particularly useful to a network operator. In some cases, “dual connectivity” may be offered such that a user and a network are configured to allow communication with a macro cell base station and a small cell base station. A number of dual connectivity implementations can be configured, each may offer different benefits.

20 Although dual connectivity HetNet deployments may offer advantages, unexpected consequences of such deployments may occur. It is desired to address those consequences.

SUMMARY

25 A first aspect provides a method of transmitting an indication of user equipment uplink buffer status in a wireless communications network in which user equipment is configured to communicate with one or more base stations using dual connectivity techniques, the method comprising: receiving an indication of a dual connectivity configuration to be used by the user equipment for uplink transmission; structuring an 30 uplink buffer status report to group uplink buffer status by one or more scheduler to be used by the user equipment according to the received indication of a dual connectivity configuration; and transmitting the structured uplink buffer status report to the one or more base stations.

35 The first aspect recognizes that dual connectivity offers a way to offload data traffic in a network to a small cell as required. In a dual connectivity scenario user equipment is connected to more than one cell at a given time and the user equipment is served by more than one cell.

The first aspect recognizes that a scheduling request mechanism is likely to be required to support all dual connectivity scenarios. Typical network configuration assumes that user equipment is served by single scheduling base station or network control node and 5 therefore a single scheduling request mechanism is used.

In a typical network deployment, backhaul communication between small cell base stations and between small cell base stations and macrocell base stations is non-ideal. That is to say, rather than offering immediate communication, there may be one way 10 latency in the order of a few milliseconds to a few tens of milliseconds. In order for the small cell and macro base station to operate in a network to provide dual connectivity functionality with such backhaul latency, an independent scheduler is provided at each serving node. The provision of multiple independent schedulers, results in a need for an adapted scheduling request mechanism to allow efficient operation in a network in 15 which multiple independent schedulers are provided to support dual connectivity to user equipment.

Traffic offloading may occur in relation to both downlink and uplink traffic in a network. Uplink dual connectivity operation with independent schedulers, requires 20 that both independent schedulers are aware of a buffer status report of each user equipment. In a case where dual connectivity is implemented in the uplink, some data flows can be offloaded to the small cell base station. The offloaded traffic is scheduled by the corresponding small cell scheduler. The scheduler located at the small cell needs to be informed of the buffer status report corresponding to the offloaded traffic to be 25 routed to the small cell.

Aspects and embodiments relate to a method of providing a suitable buffer status report to each serving schedulers supporting a dual connectivity configuration of a network. Furthermore, aspects and embodiments described herein provide a method 30 to extract or construct a buffer status report to enable traffic offloading by a scheduler. The method may also be such that a buffer status report provides a scheduler with suitable data flow information directly from user equipment or from another cell.

Offloading uplink traffic in a dual connectivity capable network can be implemented, 35 for example, using one of the following configurations:

- In one configuration, user equipment may be operable to transmit all uplink traffic to one cell, for example, the small cell. In a co-channel deployment with dual connectivity, the user equipment may have strong downlink signal from a macro cell, whilst having low path loss in relation to uplink transmissions directed towards the small cell. In such a scenario, all uplink traffic can be transmitted from user equipment to the small cell. As a result, an uplink scheduling grant will originate from the small cell and the small cell requires a buffer status report relating to all the uplink traffic bearers.
- 5 10 In another configuration in a co-channel deployment with dual connectivity, some uplink data flows (radio bearers) can be offloaded to a small cell. According to such a configuration, the small cell is in charge of scheduling the offloaded traffic bearers and therefore the buffer status report relating to the offloaded traffic bearers needs to be known by the small cell.
- 15 20 In another configuration in a co-channel deployment with dual connectivity, uplink data can belong to a radio bearer which is scheduled and received by both macro and small cell, for example, in a network capable to implement multi flow or multi streaming techniques. In such a configuration, the buffer status report of the relevant radio bearer needs to be known by both the macro and small cell.

Aspects and embodiments provide a buffer status reporting mechanism designed to handle all the described configurations whilst maintaining a common buffer status report reporting mechanism.

- 25 In one embodiment, structuring the uplink buffer status report comprises constructing an independent uplink buffer status report for each scheduler to be used by the user equipment. Accordingly, user equipment is operable to format a buffer status report intended for schedulers at the macro and the small cell independently. According to 30 such an embodiment, the resulting transmission considers and creates a different buffer status report MAC control element (buffer status report MAC CE) in relation to each serving scheduler. An indication of the identity of the intended scheduler (cell) is also included in the buffer status report MAC CE as a cell ID index. In an alternative embodiment, an indication of a cell ID is implicitly indicated via the LCID included in 35 the MAC PDU sub-header. Such embodiments require transmission of a buffer status report MAC CE per serving cell. In a further embodiment, user equipment may be operable to map a buffer status report MAC PDU corresponding to granted uplink resources on a cell by cell basis and the uplink resource(s) used to transmit the buffer

status report MAC is used as an implicit indication of which cell the buffer status report is intended for.

In one embodiment, structuring the uplink buffer status report comprises constructing
5 a single uplink buffer status report including grouped buffer status information for
each scheduler to be used by the user equipment. Accordingly, a single buffer status
report MAC CE is designed to be used in relation to all serving cells. According to such
an embodiment, an indication of serving cell identity is explicitly or implicitly included
in a MAC CE. In case of an implicit indication, a buffer status report is formatted
10 according to a cell order. Upon reception of the buffer status report MAC CE, a
scheduler is operable to decode the buffer status report field corresponding to the cell it
supports. According to some embodiments, the buffer status report MAC CE may be
transmitted on any uplink resource granted by any cell. According to such an
embodiment, a user equipment specific scrambling code used as user equipment
15 "identification" is known by both macro and small cells participating in a dual
connectivity arrangement.

In a further embodiment, user equipment is operable to transmit buffer status report
information towards a macro cell. In such an embodiment, LC Groups are configured
20 in such a way to ensure that offloaded radio bearers belong to different LCGs to the
bearers served by the macro cell. Upon reception of a buffer status report MAC CE, the
macro cell is operable to extract the buffer status report corresponding to offloaded
traffic and forward that information to the relevant small cell using the X2 interface. In
such an embodiment, the buffer status report experiences backhaul latency. However, if
25 only delay tolerant traffic is offloaded to the small cell, such a backhaul delay on the
buffer status report may be tolerated by the small cell scheduler. In such an
embodiment, the buffer status report information can be transmitted only on resource
granted to a user by the macro cell.

30 In one embodiment, the grouped buffer status information includes an indication of a
scheduler to which the information contained therein is of relevance. the user
equipment may be configured to transmit buffer status report information to any cell
(using resources granted by any cell). Upon reception of the buffer status report
information, the cell extracts the buffer status report information corresponding to the
35 traffic (radio bearers) being served by the cell and remaining buffer status report
information is forwarded to the other cell over the X2 interface.

In one embodiment, the grouped buffer status information is encoded such that it can only be decoded by a scheduler to which the information is of relevance. In some embodiments, radio bearers which are served by the macro cell may not be revealed to the other cell, particularly in the case of inter vendor operation, and in such cases, the 5 buffer status report information for each cell can be protected with cell specific coding.

In one embodiment, transmitting the structured uplink buffer status report comprises transmitting one of the independent uplink buffer status reports to each scheduler.

10 In one embodiment, transmitting the structured uplink buffer status report comprises using resource granted by the one or more base stations. Accordingly, use of granted resource may be utilised by user equipment to implicitly convey information to a scheduler. For example, in one embodiment the method further comprises choosing granted resource for transmission of the structured uplink buffer status report in 15 dependence upon a scheduler to which the information is of relevance.

A second aspect provides a computer program product operable, when executed on a computer, to perform the method of the first aspect.

20 A third aspect provides user equipment operable to transmit an indication of user equipment uplink buffer status in a wireless communications network in which the user equipment is configured to communicate with one or more base stations using dual connectivity techniques, the user equipment comprising: reception logic operable to receive an indication of a dual connectivity configuration to be used by the user 25 equipment for uplink transmission; buffer status logic operable to structure an uplink buffer status report to group uplink buffer status by one or more scheduler to be used by the user equipment according to the received indication of a dual connectivity configuration; and communication logic operable to transmit the structured uplink buffer status report to the one or more base stations.

30 In one embodiment, the buffer status logic is operable to structure the uplink buffer status report by constructing an independent uplink buffer status report for each scheduler to be used by the user equipment.

35 In one embodiment, the buffer status logic is operable to structure the uplink buffer status report by constructing a single uplink buffer status report including grouped buffer status information for each scheduler to be used by the user equipment.

In one embodiment, the grouped buffer status information includes an indication of a scheduler to which the information contained therein is of relevance.

5 In one embodiment, the grouped buffer status information is encoded such that it can only be decoded by a scheduler to which the information is of relevance.

In one embodiment, the transmission logic is operable to transmit one of the independent uplink buffer status reports to each scheduler.

10

In one embodiment, the transmission logic is operable to transmit the structured uplink buffer status report using resource granted by the one or more base stations.

15

In one embodiment, the transmission logic is operable to choose granted resource for transmission of the structured uplink buffer status report in dependence upon a scheduler to which the information is of relevance.

A fourth aspect provides a method of receiving an indication of user equipment uplink buffer status at a base station in a wireless communications network in which user

20

equipment is configured to communicate with one or more base stations using dual connectivity techniques, the method comprising: determining a dual connectivity configuration being used by user equipment for uplink transmission; receiving a structured uplink buffer status report; and extracting information from the structured uplink buffer status report relevant to a scheduler at the base station. Accordingly a base station and/or associated scheduler in a network may be operable to receive and understand a newly structured buffer status report. That buffer status report may have a familiar format, or may require some adjustment to allow decoding of a new format of message.

25

30 In one embodiment, the method further comprises: determining that the structured uplink buffer status report includes information relevant to a scheduler at another of the one or more base stations; and forwarding the information relevant to a scheduler at another of the one or more base stations to said another of the one or more base stations. Accordingly, in some implementations, use of X2 signalling may replace increased direct network signalling from a user to each scheduler of interest in a dual signalling scenario.

In one embodiment, the structured uplink buffer status report comprises an independent uplink buffer status report for each scheduler to be used by the user equipment.

5 In one embodiment, the structured uplink buffer status report includes grouped buffer status information for each scheduler to be used by the user equipment.

In one embodiment, the grouped buffer status information includes an indication of a scheduler to which the information contained therein is of relevance.

10 In one embodiment, the grouped buffer status information is encoded such that it can only be decoded by a scheduler to which the information is of relevance.

15 A fifth aspect provides a computer program product operable, when executed on a computer, to perform the method of the fourth aspect.

A sixth aspect provides a base station operable to receive an indication of user equipment uplink buffer status in a wireless communications network in which user equipment is configured to communicate with one or more base stations using dual connectivity techniques, the base station comprising: configuration logic operable to determine a dual connectivity configuration being used by user equipment for uplink transmission; reception logic operable to receive a structured uplink buffer status report from user equipment; and extraction logic operable to extract information from the structured uplink buffer status report relevant to a scheduler at the base station.

20

25 In one embodiment, the base station further comprises: determination logic operable to determine that the structured uplink buffer status report includes information relevant to a scheduler at another of the one or more base stations; and forward the information relevant to a scheduler at another of the one or more base stations to the another of the one or more base stations.

30

In one embodiment, the structured uplink buffer status report comprises an independent uplink buffer status report for each scheduler to be used by the user equipment.

35 In one embodiment, the structured uplink buffer status report includes grouped buffer status information for each scheduler to be used by the user equipment.

In one embodiment, the grouped buffer status information includes an indication of a scheduler to which the information contained therein is of relevance.

- 5 In one embodiment, the grouped buffer status information is encoded such that it can only be decoded by a scheduler to which the information is of relevance.
- 10 Further particular and preferred aspects are set out in the accompanying independent and dependent claims. Features of the dependent claims may be combined with features of the independent claims as appropriate, and in combinations other than those explicitly set out in the claims.
- 15 Where an apparatus feature is described as being operable to provide a function, it will be appreciated that this includes an apparatus feature which provides that function or which is adapted or configured to provide that function.

BRIEF DESCRIPTION OF THE DRAWINGS

- 20 Embodiments of the present invention will now be described further, with reference to the accompanying drawings, in which:
Figure 1 illustrates the main components of a telecommunications network;
Figure 2 and Figure 3 illustrate schematically a known buffer status report format; and
Figures 4 and 5 illustrate schematically a scheduling request trigger and transmission
25 according to one embodiment.

DESCRIPTION OF THE EMBODIMENTS

- Figure 1 illustrates schematically the main components of a wireless telecommunications network 10. In the UMTS network architecture illustrated user equipment 50 roam through the wireless telecommunications system. Base stations 20 are provided which support areas of radio coverage 30. A number of such base stations 20 are provided and are distributed geographically in order to provide a wide area of coverage to user equipment 50.
- 35 When user equipment is within an area served by a base station 30, communications may be established between the user equipment and the base station over associated

radio links. Each base station typically supports a number of sectors within the geographical area of service 30.

Typically, a different antenna within a base station supports each associated sector.

5 Each base station 20 has multiple antennas. It will be appreciated that Figure 1 illustrates a small subset of a total number of user equipment and base stations that may be present in a typical communication network. It will also be appreciated that different network architectures may be implemented, including, for example a Long Term Evolution (LTE) network in which the functionality provided by network nodes 10 described above is provided by network nodes which are named differently but have analogous functionality.

In a typical network a centralized scheduler is used to schedule single uplink and downlink traffic flows for each user equipment. As a result, there is no need to

15 distribute any buffer status reports to different schedulers. A typical buffer status report simply indicates the buffer status of established radio bearers. Dual connectivity data flow offloading techniques within a HetNet requires a change to typical operation, since separate schedulers are provided in relation to each cell serving a user and a typical buffer status report includes no information in relation to how to differentiate 20 information in a buffer status report corresponding to traffic offloaded to a small cell scheduler.

Overview

Before discussing the embodiments in any more detail, first an overview will be

25 provided.

Aspects and embodiments described herein provide a method to extract or construct a buffer status report to enable traffic offloading by a scheduler. The method may also be such that a buffer status report provides a scheduler with suitable data flow

30 information directly from user equipment or from another cell.

Offloading uplink traffic in a dual connectivity capable network can be implemented, for example, using one of the following configurations:

35 In one configuration, user equipment may be operable to transmit all uplink traffic to one cell, for example, the small cell. In a co-channel deployment with dual connectivity, the user equipment may have strong downlink signal from a macro cell,

whilst having low path loss in relation to uplink transmissions directed towards the small cell. In such a scenario, all uplink traffic can be transmitted from user equipment to the small cell. As a result, an uplink scheduling grant will originate from the small cell and the small cell requires a buffer status report relating to all the uplink traffic 5 bearers.

In another configuration in a co-channel deployment with dual connectivity, some uplink data flows (radio bearers) can be offloaded to a small cell. According to such a configuration, the small cell is in charge of scheduling the offloaded traffic bearers and 10 therefore the buffer status report relating to the offloaded traffic bearers needs to be known by the small cell.

In another configuration in a co-channel deployment with dual connectivity, uplink data can belong to a radio bearer which is scheduled and received by both macro and 15 small cell, for example, in a network capable to implement multi flow or multi streaming techniques. In such a configuration, the buffer status report of the relevant radio bearer needs to be known by both the macro and small cell.

Aspects and embodiments provide a buffer status reporting mechanism designed to 20 handle all the described configurations whilst maintaining a common buffer status report reporting mechanism.

Figure 2 and Figure 3 illustrate schematically a known buffer status report format. The current LTE standard defines two buffer status report formats named: short buffer 25 status report (or truncated buffer status report) and long buffer status report. In order to reduce signaling in a network, logical channels are grouped into 4 groups and buffer statuses are transmitted per logical channel group (LCG). According to the short buffer status report format, a buffer status can be signaled for one LCG. According to the long buffer status report format, buffer status is reported for all four LCGs. The report 30 format is shown schematically in Figures 2 and 3. The transmission of buffer status report in a Medium Access Control Control Element MAC CE is identified by the associated logical channel ID for a truncated, short or long buffer status report included in a MAC PDU (Protocol Data Unit) sub-header.

35 Aspects and embodiments described herein follow similar principles, and recognize that it is possible to place information relating to a logical channel such that it is grouped into a number of groups in order to reduce signaling overhead and to report a buffer status per LCG.

In one embodiment, user equipment is operable to format a buffer status report intended for schedulers at the macro and the small cell independently. According to such an embodiment, the resulting transmission considers and creates a different 5 buffer status report MAC control element (buffer status report MAC CE) in relation to each serving scheduler. An indication of the identity of the intended scheduler (cell) is also included in the buffer status report MAC CE as a cell ID index. In an alternative embodiment, an indication of a cell ID is implicitly indicated via the LCID included in the MAC PDU sub-header. Such embodiments require transmission of a buffer status 10 report MAC CE per serving cell.

In a further embodiment, user equipment may be operable to map a buffer status report MAC PDU corresponding to granted uplink resources on a cell by cell basis and the uplink resource(s) used to transmit the buffer status report MAC is used as an 15 implicit indication of which cell the buffer status report is intended for.

In one embodiment, a single buffer status report MAC CE is designed to be used in relation to all serving cells. According to such an embodiment, an indication of serving cell identity is explicitly or implicitly included in a MAC CE. In case of an implicit 20 indication, a buffer status report is formatted according to a cell order. Upon reception of the buffer status report MAC CE, a scheduler is operable to decode the buffer status report field corresponding to the cell it supports. According to some embodiments, the buffer status report MAC CE may be transmitted on any uplink resource granted by any cell. According to such an embodiment, a user equipment specific scrambling code 25 used as user equipment “identification” is known by both macro and small cells participating in a dual connectivity arrangement.

In a further embodiment, user equipment is operable to transmit buffer status report information towards a macro cell. In such an embodiment, LC Groups are configured 30 in such a way to ensure that offloaded radio bearers belong to different LCGs to the bearers served by the macro cell. Upon reception of a buffer status report MAC CE, the macro cell is operable to extract the buffer status report corresponding to offloaded traffic and forward that information to the relevant small cell using the X2 interface. In such an embodiment, the buffer status report experiences backhaul latency. However, if 35 only delay tolerant traffic is offloaded to the small cell, such a backhaul delay on the buffer status report may be tolerated by the small cell scheduler. In such an embodiment, the buffer status report information can be transmitted only on resource granted to a user by the macro cell.

In a further embodiment, the user equipment may be configured to transmit buffer status report information to any cell (using resources granted by any cell). Upon reception of the buffer status report information, the cell extracts the buffer status report information corresponding to the traffic (radio bearers) being served by the cell and remaining buffer status report information is forwarded to the other cell over the X2 interface.

5 In some embodiments, radio bearers which are served by the macro cell may not be revealed to the other cell, particularly in the case of inter vendor operation, and in such cases, the buffer status report information for each cell can be protected with cell specific coding.

10 Aspects and embodiments provide a method for providing buffer status reports in a network offering dual connectivity functionality according to which user equipment is served by multiple independent schedulers which may be connected via a non-ideal backhaul link.

15 Further considerations relate to a method relating to scheduling request triggers and transmission of scheduling requests to corresponding serving schedulers in a dual connectivity deployment scenario.

20 Existing scheduling request mechanisms typically only work for single or multiple schedulers connected via an ideal backhaul. There is no mechanism which is operable to support multiple schedulers connected via a non-ideal backhaul, which could have up to 60ms one way latency.

25 Further aspects and embodiments allow conveyance of scheduling request information intended for different schedulers by means of a single scheduling request message or multiple scheduling requests messages, depending on a scheduling request trigger event, D-SR configuration. A pending scheduling request cancellation may also be configured such that depends on the nature of the transmission.

Scheduling Request Procedure:

30 35 Scheduling request (SR) transmission is typically triggered when data arrives at an uplink transmission buffer belonging to a radio bearer on which scheduling request masking is not enabled and there is no uplink grant available for a transmission. Data “arrival” at an uplink transmission buffer is defined either as: arrival of data at an

PDCP buffer or at an RLC buffer. In each case a radio bearer is mapped to a logical channel (one to one mapping), therefore data arrival at PDCP and RLC buffer can be considered equivalent with regards to a scheduling request trigger.

5 For the transmission of a scheduling request, dedicated scheduling request (D-SR) resources are configured by the network on a per user equipment basis. However, if no D-SR are configured, user equipment are allowed to request an uplink grant using RACH. Typically only one D-SR configuration per user equipment is performed.

10 Dual Connectivity Support

In a network operable to offload uplink traffic according to dual connectivity methods, it will be appreciated that various scenarios are possible. For example:

Scenario 1

15 Dual connectivity may be implemented such that there is an uplink/downlink split where uplink traffic is served by a small cell whilst downlink traffic is served by a macro cell. Such an implementation can be particularly useful in co-channel deployments.

Scenario 2

20 Similarly, dual connectivity may be used to offer multi-streaming support, according to which a radio bearer is served by more than one cell in order to achieve transmission diversity and load balancing gain.

Scenario 3

25 Furthermore, dual connectivity can be used to implement a radio bearer level traffic split according to which some bearers are served by a macro whilst other bearers are offloaded to a small cell.

Scheduling Request Procedure:

30 Trigger, transmission and cancellation of pending scheduling requests

In Scenario 1, the scheduling request is required by the small cell, since the small cell is in charge of the scheduling of uplink traffic. In scenario 2, the scheduling request is required by schedulers located at both the macro and small cell, assuming both schedulers are involved in uplink traffic scheduling. However, at the user equipment typically one scheduling request is triggered due to the uplink data arrival on a corresponding uplink buffer. Scenario 3 requires a scheduling request at the macro and the small cell depending on which radio bearer triggers the scheduling request.

Transmission of a scheduling request intended for different schedulers can be handled by configuring multiple D-SR resources to the user equipment. The user equipment is then required to map the scheduling request trigger to the corresponding D-SR

5 resources. The multiple D-SR is configured independently with varying periodicity to match a required QoS in relation to each of the bearers. Unnecessary allocation of multiple D-SR resource per user equipment is costly to the network, given that dedicated resources are simply to be used for scheduling request transmissions. Therefore allocation of D-SR on a per cell or per scheduler basis should be avoided.

10

In relation to the dual connectivity deployment scenarios set out above, scenario 1 and 2 require the transmission of single scheduling request by the user equipment.

In scenario 3, in a typical deployment, only non-delay critical traffic is offloaded to the small cell, as a result of backhaul latency. Thus the backhaul latency is likely to also be 15 tolerated if a scheduling request is forwarded over a backhaul link. Therefore, a single D-SR configuration can be used even in relation to scenario 3. The scheduling request should indicate an intended scheduler. Thus, according to some embodiments, upon reception of a scheduling request, a receiving base station, for example, a macro base station, is operable to identify that the scheduling request is intended for a different 20 base station, for example, the small cell and forward the corresponding request to the small cell using the X2 interface.

If a macro eNB is unaware that the scheduling request is intended for the small cell, the macro may be operable to allocate radio resources for buffer status report transmission 25 to the macro cell. However, if the macro cell is aware the scheduling request is intended for the small cell, the macro cell does not grant uplink resources for the user equipment in macro cell.

In some embodiments, if a scheduling request transmission is intended for both 30 schedulers at the same time, user equipment may be operable to transmit the scheduling request only to, for example, a macro cell. From a buffer status report transmitted over granted uplink resources in the macro cell, a macro base station may be operable to identify the need to forward the buffer status report to, for example, the small cell.

35

In some embodiments, an identification of an intended scheduling cell in relation to a transmitted scheduling request can be performed by means of either an implicit or

explicit indication. Indication of an intended scheduling cell may be performed by user equipment based on timings or based on decisions made in the frequency domain.

5 Figure 4 and 5 illustrate schematically a scheduling request trigger and transmission according to one embodiment. As shown in Figures 4 and 5, if both scheduling request1 and scheduling request2 are triggered, only scheduling request1 is transmitted. The transmission of scheduling request1 “cancels” both pending scheduling request1 and scheduling request2.

10 Figure 4 illustrates schematically a scheduling request trigger and transmission according to one embodiment. In the embodiment of Figure 4, a scheduling request is transmitted on D-SR when multiple D-SR are configured for a given user. According to Figure 4(a) both scheduling request1 and scheduling request2 are triggered at the same time. Scheduling request1 is transmitted on D-SR1 and scheduling request2 is transmitted on D-SR2. According to Figure 4(b) both scheduling request1 and scheduling request2 are triggered, but only scheduling request1 is transmitted on D-SR1. According to Figure 4(c) only scheduling request2 is triggered, and scheduling request2 is transmitted on D-SR2.

15

20 Figure 5 illustrates schematically a scheduling request trigger and transmission according to one embodiment. According to the arrangement of Figure 5, the scheduling request trigger and transmission is implemented using D-SR in a scenario where a single D-SR is configured for a user. Figure 5(a) shows a case where both scheduling request1 and scheduling request2 are triggered at the same time and scheduling request1 is transmitted on D-SR. Figure 5(b) shows a case where scheduling request2 is triggered, and scheduling request2 is transmitted on D-SR.

25

In some embodiments, the scheduling request can be performed via RACH access. According to those embodiments, a user may not be configured to have D-SR resource.

30 If no D-SR is configured in relation to a user for either cell participating in dual connectivity methods, user equipment may use RACH access for transmission of a scheduling request.

35 In one embodiment, if scheduling request1(for macro) and scheduling request2 (for small cell) are triggered, RACH is performed for scheduling request only on the macro. The network is able to identify scheduling request1 and scheduling request2 from a later buffer status report. The user equipment is operable to cancel both pending

scheduling requests on transmission of the request to the macro. If only scheduling request2 (small cell) is triggered, immediate RACH access is not necessary and RACH for scheduling request on small cell can be performed with low urgency.

5 If D-SR is only configured for one cell, both scheduling request triggers can be communicated to the network over the allocated D-SR. If D-SR with long periodicity is configured for small cell and no D-SR is configured for macro and there is no D-SR opportunity within a configured time window, a scheduling request1 (macro) trigger may initiate a RACH access for scheduling request on the macro.

10

In some embodiments, a similar scheduling request procedure modification can be implemented if resources become available for a new transmission whilst a scheduling request is triggered. For example, if uplink resources become available on the small cell and scheduling request1 (macro) is triggered, scheduling request1 can be transmitted on configured D-SR on the macro. In such a case, latency over the backhaul link is not tolerable by the scheduling request triggered, due to high priority traffic on macro, for example, measurement reports.

20 The invention provides a method for providing scheduling request to the network in a scenario that the user equipment is served by multiple independent schedulers which are connected via non-ideal backhaul link.

25 A person of skill in the art would readily recognize that steps of various above-described methods can be performed by programmed computers. Herein, some embodiments are also intended to cover program storage devices, e.g., digital data storage media, which are machine or computer readable and encode machine-executable or computer-executable programs of instructions, wherein said instructions perform some or all of the steps of said above-described methods. The program storage devices may be, e.g., digital memories, magnetic storage media such as a magnetic disks 30 and magnetic tapes, hard drives, or optically readable digital data storage media. The embodiments are also intended to cover computers programmed to perform said steps of the above-described methods.

35 The functions of the various elements shown in the Figures, including any functional blocks labelled as “processors” or “logic”, may be provided through the use of dedicated hardware as well as hardware capable of executing software in association with appropriate software. When provided by a processor, the functions may be provided by

a single dedicated processor, by a single shared processor, or by a plurality of individual processors, some of which may be shared. Moreover, explicit use of the term “processor” or “controller” or “logic” should not be construed to refer exclusively to hardware capable of executing software, and may implicitly include, without limitation,

5 digital signal processor (DSP) hardware, network processor, application specific integrated circuit (ASIC), field programmable gate array (FPGA), read only memory (ROM) for storing software, random access memory (RAM), and non volatile storage. Other hardware, conventional and/or custom, may also be included. Similarly, any switches shown in the Figures are conceptual only. Their function may be carried out

10 through the operation of program logic, through dedicated logic, through the interaction of program control and dedicated logic, or even manually, the particular technique being selectable by the implementer as more specifically understood from the context.

15 It should be appreciated by those skilled in the art that any block diagrams herein represent conceptual views of illustrative circuitry embodying the principles of the invention. Similarly, it will be appreciated that any flow charts, flow diagrams, state transition diagrams, pseudo code, and the like represent various processes which may be substantially represented in computer readable medium and so executed by a

20 computer or processor, whether or not such computer or processor is explicitly shown.

The description and drawings merely illustrate the principles of the invention. It will thus be appreciated that those skilled in the art will be able to devise various arrangements that, although not explicitly described or shown herein, embody the principles of the invention and are included within its spirit and scope. Furthermore,

25 all examples recited herein are principally intended expressly to be only for pedagogical purposes to aid the reader in understanding the principles of the invention and the concepts contributed by the inventor(s) to furthering the art, and are to be construed as being without limitation to such specifically recited examples and conditions.

30 Moreover, all statements herein reciting principles, aspects, and embodiments of the invention, as well as specific examples thereof, are intended to encompass equivalents thereof.

CLAIMS

1. A method of transmitting an indication of user equipment uplink buffer status in a wireless communications network in which said user equipment is configured to communicate with one or more base stations using dual connectivity techniques, said method comprising:
 - 5 receiving an indication of a dual connectivity configuration to be used by said user equipment for uplink transmission;
 - 10 structuring an uplink buffer status report to group uplink buffer status by one or more scheduler to be used by said user equipment according to said received indication of a dual connectivity configuration; and
 - 15 transmitting said structured uplink buffer status report to said one or more base stations.
- 15 2. A method according to claim 1, wherein structuring said uplink buffer status report comprises constructing an independent uplink buffer status report for each scheduler to be used by said user equipment.
- 20 3. A method according to claim 1, wherein structuring said uplink buffer status report comprises constructing a single uplink buffer status report including grouped buffer status information for each scheduler to be used by said user equipment.
- 25 4. A method according to claim 3, wherein said grouped buffer status information includes an indication of a scheduler to which the information is of relevance.
5. A method according to claim 3 or claim 4, wherein said grouped buffer status information is encoded such that it can only be decoded by a scheduler to which the information is of relevance.
- 30 6. A method according to any preceding claim, wherein transmitting said structured uplink buffer status report comprises transmitting one of said independent uplink buffer status reports to each scheduler.
7. A method according to any preceding claim, wherein transmitting said structured uplink buffer status report comprises using resource granted by said one or more base stations.

8. A method according to claim 7, comprising choosing granted resource for transmission of said structured uplink buffer status report in dependence upon a scheduler to which the information is of relevance.

5 9. A computer program product operable, when executed on a computer, to perform the method of any one of claims 1 to 8.

10. 10. User equipment operable to transmit an indication of user equipment uplink buffer status in a wireless communications network in which said user equipment is configured to communicate with one or more base stations using dual connectivity techniques, said user equipment comprising:
reception logic operable to receive an indication of a dual connectivity configuration to be used by said user equipment for uplink transmission;
buffer status logic operable to structure an uplink buffer status report to group uplink buffer status by one or more scheduler to be used by said user equipment according to said received indication of a dual connectivity configuration; and
communication logic operable to transmit said structured uplink buffer status report to said one or more base stations.

20 11. 11. A method of receiving an indication of user equipment uplink buffer status at a base station in a wireless communications network in which said user equipment is configured to communicate with one or more base stations using dual connectivity techniques, said method comprising:
determining a dual connectivity configuration being used by said user equipment for uplink transmission;
receiving a structured uplink buffer status report; and
extracting information from said structured uplink buffer status report relevant to a scheduler at said base station.

30 12. 12. A method according to claim 11, comprising: determining that said structured uplink buffer status report includes information relevant to a scheduler at another of said one or more base stations; and
forwarding said information relevant to a scheduler at another of said one or more base stations to said another of said one or more base stations.

35 13. 13. A computer program product operable, when executed on a computer, to perform the method of any one of claim 11 or claim 12.

14. A base station operable to receive an indication of user equipment uplink buffer status in a wireless communications network in which said user equipment is configured to communicate with one or more base stations using dual connectivity

5 techniques, said base station comprising:

configuration logic operable to determine a dual connectivity configuration being used by said user equipment for uplink transmission;

reception logic operable to receive a structured uplink buffer status report; and

10 extraction logic operable to extract information from said structured uplink buffer status report relevant to a scheduler at said base station.

1/4






FIG. 1

2/4



Short BSR and Truncated BSR MAC control element


FIG. 2



Long BSR MAC control element

FIG. 3

3/4



SR trigger and transmission of SR on D-SR when multiple D-SR are configured for the UE.


(a) Both SR1 and SR2 triggered at the same time and SR1 is transmitted on D-SR1 and SR2 is transmitted on D-SR2

(b) both SR1 and SR2 are triggered, only SR1 is transmitted on D-SR1

(c) only SR2 is triggered, SR2 is transmitted on D-SR2

FIG. 4

4/4



SR trigger and transmission of SR on D-SR when single D-SR is configured for the UE.

(a) both SR1 and SR2 triggered at the same time and SR1 is transmitted on D-SR

(b) both SR2 is triggered, SR2 is transmitted on D-SR

FIG. 5

INTERNATIONAL SEARCH REPORT

International application No
PCT/EP2014/000661

A. CLASSIFICATION OF SUBJECT MATTER
INV. H04L12/70
ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
H04L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>NOKIA: "Buffer reporting for E-UTRAN", 3GPP TSG-RAN WG2 MEETING #52, ATHENS GREECE, 27-31 MARCH 2006; 20060327 - 20060330</p> <p>, vol. R2-060829 31 March 2006 (2006-03-31), pages 1-5, XP002503218, Retrieved from the Internet: URL:www.3gpp.org [retrieved on 2006-03-01] the whole document</p> <p>----- -/-</p>	1-14

Further documents are listed in the continuation of Box C.

See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance
"E" earlier application or patent but published on or after the international filing date
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
"O" document referring to an oral disclosure, use, exhibition or other means
"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

Date of mailing of the international search report

4 April 2014

23/04/2014

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Schrembs, Gerd

INTERNATIONAL SEARCH REPORT

International application No PCT/EP2014/000661

C(Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>JOHN L TOMICI ET AL: "Multi-RAT traffic offloading solutions for the bandwidth crunch problem", SYSTEMS, APPLICATIONS AND TECHNOLOGY CONFERENCE (LISAT), 2011 IEEE LONG ISLAND, IEEE, 6 May 2011 (2011-05-06), pages 1-6, XP031880722, DOI: 10.1109/LISAT.2011.5784243 ISBN: 978-1-4244-9878-9 the whole document</p> <p>-----</p> <p>EP 2 568 759 A1 (ALCATEL LUCENT [FR]) 13 March 2013 (2013-03-13) abstract paragraph [0001] - paragraph [0009] paragraph [0012] claims 1,6-7,9 figures 1-3</p> <p>-----</p> <p>MOTOROLA: "Comparison of UL buffer reporting/scheduling schemes in LTE", 3GPP TSG-RAN-WG2 LTE, AD HOC MEETING, CANNES FRANCE, 27-30 JUNE 2006; 20060627 - 20060630 , vol. R2-061915 30 June 2006 (2006-06-30), pages 1-4, XP002503219, Retrieved from the Internet: URL:www.3gpp.org [retrieved on 2008-11-10] the whole document</p> <p>-----</p>	1-14
A		1-14
A		1-14

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/EP2014/000661

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
EP 2568759	A1	13-03-2013	CN 102783234 A	14-11-2012
			EP 2568759 A1	13-03-2013
			JP 2013526223 A	20-06-2013
			KR 20130014586 A	07-02-2013
			US 2013114445 A1	09-05-2013
			WO 2011137576 A1	10-11-2011