



- (51) **International Patent Classification:**  
BOW 53/14 (2006.01) BOW 53/18 (2006.01)
- (21) **International Application Number:**  
PCT/US201 1/02063 1
- (22) **International Filing Date:**  
10 January 201 1 (10.01 .201 1)
- (25) **Filing Language:** English
- (26) **Publication Language:** English
- (30) **Priority Data:**  
61/294,971 14 January 2010 (14.01 .2010) US  
12/985,6 13 6 January 201 1 (06.01 .201 1) US
- (71) **Applicant (for all designated States except US):** ALSTOM TECHNOLOGY LTD [CH/CH]; Brown Boveri Strasse 7, CH-5400 Baden (CH).
- (72) **Inventor:** PONTBRIAND, Michael W.; 315 Hummingbird Drive, Yonore, Tennessee 37885 (US).

- (72) **Inventor; and**
- (75) **Inventor/Applicant (for US only):** BABURAO, Barath [IN/US]; 200 Kelso Way, Apt. 128, Knoxville, Tennessee 37923 (US).
- (74) **Agents:** OLSON, Timothy J. et al; ALSTOM POWER INC., 200 Great Pond Drive, P.O. Box 500, Windsor, CT 06095-0500 (US).
- (81) **Designated States (unless otherwise indicated, for every kind of national protection available):** AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) **Designated States (unless otherwise indicated, for every kind of regional protection available):** ARIPO (BW, GH,

[Continued on next page]

(54) **Title:** WATER WASH METHOD AND SYSTEM FOR A CARBON DIOXIDE CAPTURE PROCESS




FIG. 1

(57) **Abstract:** A system and method for recovering a solvent from a decarbonated flue gas in an absorption column (100), the decarbonated flue gas (120) having had carbon dioxide absorbed and removed by vapor-liquid contact with a carbon dioxide absorbing solution (119) containing the solvent. The system includes an emission control section (114) configured to bring a water stream (122) substantially free of the solvent into contact with the decarbonated flue gas (120) to recover the solvent from the decarbonated flue gas (120) and to form a solvent containing wash water (160) and a reduced solvent containing flue gas (124) and a flue gas cooling section (116) configured to bring cooled wash water (132) into contact with the reduced solvent containing flue gas (124) to cool the reduced solvent containing flue gas (124) and condense water from the decarbonated flue gas thereby forming a cooled flue gas (125) and used wash water.

W<sup>o</sup> 2011/087972 A1

GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG,  
ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,  
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,  
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU,  
LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK,

SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,  
GW, ML, MR, NE, SN, TD, TG).

**Published:**

— with international search report (Art. 21(3))

## **WATER WASH METHOD AND SYSTEM FOR A CARBON DIOXIDE CAPTURE PROCESS**

### **CROSS REFERENCE TO RELATED APPLICATIONS**

[0001] This application claims priority to U.S. Provisional Patent Application No. 61/294,971 filed on January 14, 2010, the contents of which are incorporated in their entirety herein.

### **TECHNICAL FIELD**

[0002] The present disclosure relates to a water wash system for a carbon dioxide (CO<sub>2</sub>) capture process. More particularly, the present disclosure relates to a method and system of washing flue gas after CO<sub>2</sub> absorption to reduce solvent emissions and maintain water neutrality.

### **BACKGROUND**

[0003] From the point of view of air pollution control and environmental concerns, there is seen a need to decrease the quantities and concentrations of carbon dioxide (CO<sub>2</sub>) emissions resulting from the combustion of coal, oil, and other carbon fuels. For this purpose, methods for removing carbon dioxide from the flue gas (also commonly referred to as "exhaust gas") resulting from such combustion are presently being developed. One such method employs absorption of CO<sub>2</sub> from flue gases using aqueous solutions of solvents. Examples of solvents include amine-containing solutions. Examples of amines include, but are not limited to, for example, alkanolamine, monoethanolamine and the like, and combinations and/or mixtures thereof, which are hereinafter referred to as "amines" or "amine compounds."

[0004] An example of a solvent-based method for removing CO<sub>2</sub> with the use of amines is provided in U.S. Pat. No. 5,318,758, which is incorporated by reference herein in its entirety. The '758 patent proposes a method which performs decarbonation by using an aqueous solution of an amine compound as a solution for absorbing carbon dioxide from the flue gas within an absorber column.

[0005] In general, a solvent-based method for removing CO<sub>2</sub> from a flue gas includes a flue gas supplied by a combustion gas supply blower, which is cooled by a cooling tower, and then fed to an absorption column. In the CO<sub>2</sub> absorption section of the absorption column, the fed flue gas is brought into countercurrent contact with an absorbing solution supplied through an absorbing solution supply port via at least one nozzle. As a result, CO<sub>2</sub> in the flue gas is absorbed and removed by the absorbing solution. The loaded absorbing solution, which has absorbed CO<sub>2</sub>, is sent to a regeneration tower by the absorbing solution discharge pump through an absorbing solution discharge port. In the regeneration tower, the loaded absorbing solution is regenerated, and fed again to the absorption tower through the absorbing solution supply port.

[0006] Most solvent-based CO<sub>2</sub> capture processes involve an exothermic reaction between the solvent and the flue gas, which leads to a temperature profile in the absorption column. Depending upon the process parameters, the maximum temperature (also known as "temperature bulge") in the column could be in the top, bottom or middle section of the absorber column. Owing to this temperature increase, there are some solvent losses that occur in the process along the column. These solvent losses occur mainly through the decarbonated flue gas that is leaving the top of the absorber column.

[0007] In a CO<sub>2</sub> capture process with a chemical solvent, such as amines, a wash section may be included on top of the absorber column to reduce this emission loss. The decarbonated flue gas contacts the wash water in the wash section on top of the absorber, which captures some of the solvent from the gas phase and is recovered in the liquid phase. This recovered solvent in the liquid phase can be either used directly in the CO<sub>2</sub> absorption process or sent to a solvent make-up section.

[0008] Depending upon the gas separation processes upstream of the CO<sub>2</sub> absorber column, the flue gas entering the absorber column is mostly saturated. In order to maintain the solvent capacity, it is important to run the process without any solvent losses as well as water accumulation. Any accumulation of excess water in the absorber column will lead to the dilution of the solvent concentration, which will impact its mass transfer characteristics and variation of partial pressures along the column. Hence it is important to ensure that the amount of water entering and leaving the process is very close, which is called "water neutrality". Previously known and described wash sections have not provided reduced

solvent neutrality. The processes and systems described herein are seen to address at least these issues.

### **SUMMARY**

[0009] According to aspects illustrated herein, there is provided a method for recovering a solvent from a decarbonated flue gas in a water wash section of an absorption column, the decarbonated flue gas having had carbon dioxide absorbed and removed by vapor-liquid contact with a carbon dioxide absorbing solution containing the solvent in the absorption column, the method comprising: bringing a water stream substantially free of the solvent into counter-current contact with the decarbonated flue gas in an emission control section of the absorption column to recover the solvent from the decarbonated flue gas to form a solvent containing wash water and a reduced solvent containing flue gas; and bringing a cooled wash water into counter-current contact with the reduced solvent containing flue gas in a flue gas cooling section of the absorption column to cool the reduced solvent containing flue gas, thereby forming a cooled flue gas and a used wash water.

[0010] According to another aspect illustrated herein, there is provided a system for recovering a solvent from a decarbonated flue gas in an absorption column, the decarbonated flue gas having had carbon dioxide absorbed and removed by vapor-liquid contact with a carbon dioxide absorbing solution containing the solvent, the system comprising: an emission control section configured to bring a water stream substantially free of the solvent into contact with the decarbonated flue gas to recover the solvent from the decarbonated flue gas and to form a solvent containing wash water and a reduced solvent containing flue gas; and a flue gas cooling section configured to bring cooled wash water into contact with the reduced solvent containing flue gas to cool the reduced solvent containing flue gas and condense water from the decarbonated flue gas thereby forming a cooled flue gas and used wash water.

[0011] The above described and other features are exemplified by the following figures and detailed description.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

[0012] Referring to the drawings, wherein like items are numbered alike in the various Figures:

[0013] FIG. 1 depicts a CO<sub>2</sub>-absorption column having a water wash section in accordance with an embodiment described herein; and

[0014] FIG.2 depicts a CO<sub>2</sub>-absorption column having a water wash section in accordance with an embodiment described herein.

### **DETAILED DESCRIPTION**

[0015] FIG. 1 illustrates an absorption column 100 having at least one absorber bed 110 and a water wash section 112. In this arrangement, the water wash section 112 is divided in to at least two sections, namely, an emission control section 114 and a flue gas cooling section 116.

[0016] A flue gas 118 provided to the absorption column 100 and ascends at least a portion of a length L of the absorption column. In at least one absorber bed 110, carbon dioxide (CO<sub>2</sub>) present in the flue gas 118 is absorbed by contacting the flue gas with a CO<sub>2</sub>-absorbing solution 119 in a countercurrent fashion. In one embodiment, the CO<sub>2</sub>-absorbing solution 119 is an amine-containing solution. Examples of amines include, but are not limited to, for example, alkanolamine, monoethanolamine and the like, and combinations and/or mixtures thereof, which are hereinafter referred to as "amines" or "amine compounds." The amine-containing solution may also include a promoter to enhance the chemical reaction kinetics involved in the capture of CO<sub>2</sub> by the ammoniated solution. For example, the promoter may include an amine (e.g. piperazine) or an enzyme (e.g., carbonic anhydrase or its analogs), which may be in the form of a solution or immobilized on a solid or semi-solid surface.

[0017] Removal of CO<sub>2</sub> from the flue gas 118 creates a decarbonated flue gas 120. The decarbonated flue gas 120 contains, for example, an amount of the CO<sub>2</sub>-absorbing solution in vapor form, (hereinafter "a solvent"). For example, the decarbonated flue gas 120 may contain an amount of amine solvent in vapor form.

[0018] To absorb, and thereby remove or reduce the amount of the solvent in the decarbonated flue gas 120, the decarbonated flue gas 120 ascends at least a portion of the length L of the absorption column 100 and encounters the water wash section 112. As shown

in FIG. 1, the decarbonated flue gas 120 encounters the emission control section 114, which facilitates the reduction or removal of the solvent from the decarbonated flue gas.

[0019] The emission control section 114 includes a water stream 122 (also referred to as "make-up water"). The water stream 122 is relatively free of contaminants and impurities, such as, for example, the solvent, and facilitates the absorption of the solvent from the decarbonated flue gas 120. While not shown on the figure, it is contemplated that the water stream 122 can be used from anywhere within the process itself, *e.g.*, regenerator condensate, and the like.

[0020] The decarbonated flue gas 120 comes into contact with water stream 122 in a countercurrent fashion as the decarbonated flue gas ascends up at least a portion of the length L of the absorption column 100 and the water stream descends at least a portion of the absorption column.

[0021] Since the water stream 122 is relatively free of contaminants and impurities, the concentration gradient of solvent (*e.g.*, amine) between the decarbonated flue gas 120 and the water stream is high, resulting in solvent absorption from the decarbonated flue gas and formation of a reduced solvent containing flue gas 124. The reduced solvent containing flue gas 124 leaving the emission control section 114 is almost free of any solvent, therefore vapor phase solvent losses are reduced. Owing to this high concentration gradient, the water circulation rate for the emission control section 114 is very low. This in turn affects the temperature of the flue gas 124 exiting the emission control section 114.

[0022] There are minimal changes between the entrance temperature of the decarbonated flue gas 120 and the exit temperature of the reduced solvent containing flue gas 124 in the emission control section 114. Accordingly, to cool the temperature of the reduced solvent containing flue gas 124, and to remove excess water, therefrom, the flue gas 124 is provided to the flue gas cooling section 116, which contacts the flue gas 124 with water to form a cooled flue gas 125. Maintenance of water neutrality, *i.e.*, keeping the amount of water leaving the absorption column 100 the same as or similar to the amount of water introduced to the absorption column, is also facilitated by the flue gas cooling section 116. The flue gas 124 is provided to the flue gas cooling section 116 by ascending at least a portion of the length L of the absorption column 100.

[0023] In the flue gas cooling section 116, the solvent emissions control is very minimal, and therefore, the used wash water 126 from the flue gas cooling section 116 may be used elsewhere in the absorption column 100 or within the overall process of removing contaminants from a flue gas.

[0024] Still referring to FIG. 1, in one embodiment the flue gas cooling section 116 includes a liquid distributor 128. The liquid distributor 128 may include, for example, a manifold 130 having nozzles or the like to disperse a wash water 132 within the absorption column 100, and a liquid distribution plate 134 or the like, to further distribute the wash water within the absorption column.

[0025] The flue gas cooling section 116 may also include a mass transfer device 136, such as packing trays, plates, or the like, disposed beneath the liquid distributor 128. As shown in FIG. 1, the mass transfer device 136 is positioned beneath the liquid distribution plate 134. The flue gas cooling section 116 may also include a collection device 138, such as a liquid collector plate, disposed beneath the mass transfer device 136, which acts to collect wash water 132 that has descended at least a portion of the length L of the absorption column 100. The collection device 138 provides the wash water to a sump 140, where the wash water is withdrawn as used wash water 126.

[0026] A pump 142 is in fluid communication (e.g., by piping, tubing, ductwork, or the like) with the sump 140 of the collection device 128. The pump 142 facilitates removal of the water collected by the collection device 138 and provided to the sump 140.

[0027] A heat exchanger 144 is in fluid communication with the pump 142 and is configured to reduce the temperature of the used wash water 126 to form a cooled liquid 145. As shown in FIG. 1, at least a portion of the cooled liquid 145 is recirculated within the flue gas cooling section 116. In one embodiment, as shown in FIG. 1, the cooled liquid supplements wash water 132 that is provided to the flue gas cooling section 116. The system is not limited in this regard since it is contemplated that the wash water 132 may consist entirely of the cooled liquid 145.

[0028] Continuing to refer to FIG. 1, a branch line 146 is disposed in fluid communication with the pump 142 and the collection device 138. The branch line 146 is arranged so less than all of the used wash water 126 may be cooled and returned to the flue gas cooling section 116. For example, a portion of the used wash water 126 may be provided to the heat

exchanger 144, and a portion of the withdrawn liquid may be provided to the branch line 146. In one example, 50% of the used wash water 126 is provided to the heat exchanger 144 and 50 % of the used wash water is provided to the branch line 146.

[0029] The branch line 146 may include one or more control valves 148 or other flow control devices, to adjust an amount of used wash water 126 removed from the water wash system 112 or to adjust an amount of used wash water that flows through the branch line. The used wash water 126 provided to branch line 146 may be sent to a lean solvent make-up tank (not shown) or to the top of the absorption column 100 (not shown). The used wash water 126, because it contains little to no amine solvent, may also be used elsewhere within the overall flue gas treatment system.

[0030] Similar to the flue gas cleaning section 116, the emission control section 114 also includes a collection device 150 for collecting wash water in the emission control section. The collection device 150 is disposed between a material transfer device 152 and an absorbing solution distributor 154. The absorbing solution distributor 154 facilitates the distribution of the CO<sub>2</sub>-absorbing solution 119 throughout the absorber bed 110. The CO<sub>2</sub>-absorbing solution 119 contacts the flue gas 118 in a countercurrent manner as the flue gas 118 ascends at least to a portion of a length L of the absorption column 100 and the CO<sub>2</sub>-absorbing solution travels in an opposite direction.

[0031] Still referring to the emission control section 114 in FIG. 1, a liquid distributor 156 (also referred to as a fluid distribution device) is disposed within the absorption column 100 and is in fluid communication with the source of the water stream 122. The liquid distributor 156 is configured to distribute the water stream 122 within the emission control section 114.

[0032] A branch line 158 is disposed in fluid communication with a sump 160 of the collection device 150. The branch line 158 may be in fluid communication with branch line 146, and may include one or more control valves 162 or of the flow control devices, to adjust an amount of solvent containing 161 wash water that is withdrawn from the emissions control section 114. Solvent containing wash water 161 from the emission control system 114 may be sent to a lean solvent make-up tank (not shown) or to the top of the absorption columns 100, or used within the overall system for removing contaminants from the flue gas.

[0033] A controller 164 may be in communication with one or more components described above. The controller 164 may be, for example, a general purpose computer, an

application-specific integrated circuit, or a pneumatic, electric or mechanical controller. The controller 164 maybe configured to automatically adjust one or more system parameters to control solvent emissions and maintain water neutrality in the wash water system 112 or the entire CO<sub>2</sub> removal system. For example, as shown in FIG.1, the controller 164 may be in communication with the heat exchanger 144, the pump 142 or the flow control valves 148, 162. The system is not limited in this regard as the controller 164 may be in communication with other components.

**[0034]** In one embodiment, the controller 164 can be configured to adjust an amount of solvent, *e.g.*, amine, that is recovered by the wash water system 112 by adjusting an amount of the water stream 122 that is brought into contact with decarbonated flue gas 120. For example, if the controller 164 determines that solvent emission or system solvent losses meet or exceed a predetermined threshold, the controller 164 may act to increase the amount of water stream 122 added to the emission control section 114.

**[0035]** In another embodiment, the controller 164 can also be configured to control water neutrality by adjusting a temperature of the wash water 132 brought into contact with the decarbonated flue gas 120 in the flue gas cooling section 116, thereby adjusting the amount of water removed from the reduced solvent containing flue gas 124. Water neutrality can also be controlled, for example, by assessing or determining the amount of water stream 122 added to the water wash section 112 (for water wash neutrality) or the entire CO<sub>2</sub> system (for system neutrality) and compared to the amount of water removed from the flue gas cooling section 116 (*e.g.*, by pump 142 or branch line 146).

**[0036]** Depending on the comparison performed by the controller 164, the controller may increase or decrease the temperature of the wash water 132 (*e.g.*, by adjusting the flow of the wash water to the heat exchanger 144) to adjust an amount of water removed from the reduced solvent containing flue gas 124, and thereby maintain water neutrality within a desired range. The controller 164 may be capable of measuring or determining a solvent concentration, collected in the absorption column 100, for example, and adjust the temperature of the wash water if the solvent concentration meets certain thresholds.

**[0037]** In another embodiment, the controller 164 may also control the amount of the used wash water 126 provided to branch line 146 by adjusting one or more of the flow control valve 148 or the pump 142.

**[0038]** The liquid distributor 156 of the emission control section 114 may comprise, for example, a manifold 166 with nozzles or the like to disperse the water stream 122 within the column, and a liquid distribution plate 168 or the like to further distribute the wash water within the column 100.

**[0039]** In another embodiment, as shown in FIG. 2, the absorption column 100, which includes the wash section 112 and related components as described in detail above, is configured to recirculate at least a portion of the used wash water to the flue gas cooling section 116 and provide at least a portion of the withdrawn liquid to the emission control section 114.

**[0040]** As shown in FIG. 2, the sump 140 is in fluid communication with the pump 142. The pump 142 withdraws the used wash water 126 from the sump 140. After being withdrawn, at least a portion of the used wash water 126 is provided to the heat exchanger 144 as described in more detail above. Another portion of the used wash water 126 is provided to the emission control section 114.

**[0041]** The amount of used wash water 126 is provided to the emission control section 114 may be controlled by opening or closing a control valve 170 that is positioned between the flue gas cooling section 116 and the emission control section 114. Control valve 170 may be operated manually or automatically. Control valve 170 may be in communication with the controller 164, which may close or open control valve 170 based on information, readings, or signals concerning amounts of wash water provided to the emission control section 114 by other sources as described herein.

**[0042]** Since the reduced solvent containing flue gas 124 has very little to no solvent, the used wash water 126, which has contacted the flue gas 124, will have a very low concentration of solvent. Thus, the used wash water 126 may be recirculated for re-use in the flue gas cooling section 116 or provided to the emission control section 114. Re-use of the used wash water 126 may reduce the amount of fresh water provided to the absorption tower in the form of water stream 122 and wash water 132.

**[0043]** Increasing an amount of water provided to the emission control section 114 facilitates proper circulation and distribution of water that comes into countercurrent contact with the decarbonated flue gas 120. By maintaining proper circulation and distribution of water in the emission control section 114, the desired amount of solvent can be removed from

the decarbonated flue gas 120. Maintenance or proper circulation of water in the emission control section 114 can be achieved by providing the used wash water 126 to the emission control section. These efforts do not increase the costs associated with providing fresh water, *e.g.*, water stream 122, to the emission control section.

**[0044]** To further reduce the amount of the water stream 122 provided to the emission control section 114, at least a portion of the solvent containing wash water 161 withdrawn from sump 160 by a pump 172 into a branch line 158 may be recirculated and provided to the top of the emission control section.

**[0045]** As shown in FIG. 2, at least a portion of the solvent containing wash water 161 in branch line 158 is directed by line 174 to join with at least a portion of used wash water 126 to form a recycle liquid 176. Recycle liquid 176 is introduced to the top of the emission control section 114 via the manifold 166. Once introduced to the emission control section 114, the recycle liquid 176, along with water stream 122, descends at least a length L of the absorption tower 100, thereby absorbing the solvent from the decarbonated flue gas 120 to form flue gas 124.

**[0046]** The amount of the solvent containing wash water 161 provided to the emission control section 114 may be regulated by a control valve 178. As shown in FIG. 2, the control valve 178 is disposed in line 174, however, it is contemplated that the control valve 178 may be disposed in the branch line 158. The control valve 178 may be in communication with the controller 164, which may close or open the control valve 178 based on information, readings or signals concerning amounts of the wash water provided to the emission control section 114 by other sources described herein.

**[0047]** The foregoing embodiments are exemplified in the Examples included below, which are provided to exemplify certain aspects of the disclosed embodiments. The Examples are not provided to limit the embodiments in any manner.

ExamplesEXAMPLE 1

[0048] To illustrate the effectiveness of the system shown in FIG. 1, a simulation was run to show the impact on the solvent emissions as well as water neutrality. A flue gas with 90% of CO<sub>2</sub> removed from a ~260 Mwe (megawatt of electrical energy) lignite fired power plant was used in this simulation. It was assumed the required solvent emissions are ~2 parts per million by volume (ppmv). Based on the inlet flue gas conditions, the flue gas exit temperatures are calculated to be ~ 112 degrees Fahrenheit (°F) in order to obtain water neutrality. The simulation included an amine-containing absorbing solution.

[0049] The tabulation below illustrates the impact of the system shown in FIG. 1 in comparison with the conventional method, *i.e.*, having only one wash water bed. With the conventional method (case 1, below), if the circulation is adjusted to provide water neutrality by maintaining closer exit gas temperatures, the solvent emissions control is not achieved (9 ppmv vs 2 ppmv). On the other hand, if the circulation rates are adjusted to give ~ 7 ppmv solvent emissions (case 3), the exit temperatures does not satisfy the water neutrality constraints. Both solvent emission control and water neutrality are achieved in the system illustrated in FIG. 1.

Table 1: Comparison of conventional and new water wash scheme

Case #	Cases type	Solvent Emissions, ppmv	Clean Flue Gas Exit Temperature, deg F	Water Circulation Rate, Gpm
1	Conventional	9.2	112.40	6100
2	System of FIG. 1	2.0	111.75	6100 + 20 (makeup)
3	Conventional 2	7.1	98.85	8000

EXAMPLE 2

[0050] To illustrate the effectiveness of the system shown in FIG. 2, a simulation was run to show the impact on the solvent emissions as well as water neutrality. The system of FIG. 2

was compared to a conventional system, *i.e.*, having only one wash water bed as well as a system according to FIG. 1.

[0051] With the convention flow scheme (case 4, below), if the circulation is adjusted to provide water neutrality by maintaining closer exit flue gas temperatures, the solvent emissions control is not achieved (9 ppmv v. 2 ppmv). If the circulation rates are adjusted to give ~7ppmv solvent emissions (case 5), the exit temperature of the flue gas does not satisfy the water neutrality constraints. While both emission control and water neutrality are achieved by utilizing a system according to FIG. 1 (case 6), solvent emission rates can be lowered further by utilizing a system according to FIG. 2 (case 7).

Table 2: Comparison of Conventional Systems to Systems Illustrated in FIGS. 1 and 2

Case #	Case Type	Solvent Emissions, ppmv	Clean Flue Gas Exit Temperature, °F	Water Circulation Rate, Gpm
4	Conventional	9.2	112.40	6100
5	Conventional 2	7.1	98.85	8000
6	System of FIG. 1	2.0	111.75	6100 + 20 (make up)
7	System of FIG. 2	0.46	111.70	6100 + 10 (make up) + 1800 (re-circulation)

[0052] While the invention has been described with reference to various exemplary embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiment disclosed as the best mode contemplated for carrying out this invention, but that the invention will include all embodiments falling within the scope of the appended claims.

CLAIMS:

What is claimed is:

1. A method for recovering a solvent from a decarbonated flue gas in a water wash section of an absorption column, the decarbonated flue gas having had carbon dioxide absorbed and removed by vapor-liquid contact with a carbon dioxide absorbing solution containing the solvent in the absorption column, the method comprising:

bringing a water stream substantially free of the solvent into counter-current contact with the decarbonated flue gas in an emission control section of the absorption column to recover the solvent from the decarbonated flue gas to form a solvent containing wash water and a reduced solvent containing flue gas; and

bringing a cooled wash water into counter-current contact with the reduced solvent containing flue gas in a flue gas cooling section of the absorption column to cool the reduced solvent containing flue gas, thereby forming a cooled flue gas and a used wash water.

2. A method according to claim 1, wherein the solvent is an amine-containing solution.

3. A method according to claim 1, further comprising:

adjusting an amount of solvent absorbed by the wash water section by adjusting an amount of the water stream contacted with the decarbonated flue gas; and

adjusting an amount of water removed from the reduced solvent containing flue gas by adjusting a temperature of the cooled wash water contacted with the reduced solvent containing flue gas.

4. A method according to claim 1, further comprising:
  - collecting the used wash water with a collection device disposed between the flue gas cooling section and the emission control section;
  - removing the collected used wash water from the collection device;
  - cooling at least a portion of the removed used wash water to form cooled wash water; and
  - returning at least a portion of the cooled wash water to the flue gas cooling section.
  
5. A method according to claim 4, further comprising:
  - adjusting an amount of used wash water removed from the flue gas section by adjusting an amount of cooled wash water returned to the flue gas cooling section.
  
6. A method according to claim 5, further comprising:
  - adjusting an amount of water removed from the decarbonated flue gas in the flue gas cooling section by adjusting a temperature of the cooled wash water brought into contact with the reduced solvent containing flue gas.
  
7. A method according to claim 1, further comprising:
  - collecting the used wash water with a collection device disposed between the flue gas cooling section and the emission control section;
  - removing the collected used wash water from the collection device; and
  - providing at least a portion of the removed used wash water to the emission control section.
  
8. A method according to claim 7, further comprising:
  - providing a remainder of the removed used wash water to a heat exchanger;
  - cooling the removed used wash water to form a cooled wash water; and
  - providing the cooled wash water to the flue gas cooling section.
  
9. A method according to claim 7, further comprising:
  - contacting the decarbonated flue gas with the removed used wash water and the water stream in a countercurrent manner in the emission to form a solvent containing wash water.

10. A method according to claim 9, further comprising:
  - collecting the solvent containing wash water in a collection device within the emission control section; and
  - reutilizing at least a portion of the solvent containing wash water in the emission control section.
  
11. A method according to claim 10, wherein the portion of the solvent containing wash water reutilized in the emission control section is combined with the used wash water from the flue gas cooling section; and
  - providing the combined solvent containing wash water and used wash water to the emission control section.
  
12. A method according to claim 10, further comprising:
  - providing at least a portion of the solvent containing wash water to an absorber bed in the absorption column.
  
13. A system for recovering a solvent from a decarbonated flue gas in an absorption column, the decarbonated flue gas having had carbon dioxide absorbed and removed by vapor-liquid contact with a carbon dioxide absorbing solution containing the solvent, the system comprising:
  - an emission control section configured to bring a water stream substantially free of the solvent into contact with the decarbonated flue gas to recover the solvent from the decarbonated flue gas and to form a solvent containing wash water and a reduced solvent containing flue gas; and
  - a flue gas cooling section configured to bring cooled wash water into contact with the reduced solvent containing flue gas to cool the reduced solvent containing flue gas and condense water from the decarbonated flue gas thereby forming a cooled flue gas and used wash water.
  
14. A system according to claim 13, wherein the solvent is an amine compound.

15. A system according to claim 13, further comprising:  
a controller configured to adjust an amount of solvent absorbed in the emission control section by adjusting an amount of the water stream contacted with the decarbonated flue gas.
16. A system according to claim 15, wherein the controller is configured to adjust an amount of water removed from the reduced solvent containing flue gas by adjusting a temperature of the cooled wash water contacted with the reduced solvent containing flue gas.
17. A system according to claim 13, further comprising:  
a collection device disposed between the flue gas cooling section and the emission control section, the collection device configured to collect the used wash water from the flue gas cooling section;  
a pump in fluid communication with a sump of the collection device to remove the collected used wash water from the collection device;  
a heat exchanger in fluid communication with the pump to cool at least a portion of the removed used wash water to form a cooled wash water; and  
a liquid distributor disposed in the absorption column and in fluid communication with the heat exchanger, the liquid distributor configured to distribute the cooled wash water in the flue gas cooling section.
18. A system according to claim 17, further comprising:  
a second liquid distributor disposed in the absorption column and in fluid communication with the pump, the second liquid distributor configured to distribute at least a portion of the removed used wash water in the emission control section.
19. A system according to claim 18, further comprising:  
a collection device disposed between the emission control section and an absorber bed, the collection device configured to collect the solvent containing wash water from the emission control section;  
a pump in fluid communication with a sump of the collection device to remove the collected solvent containing wash water from the emission control section; and  
a line to direct at least a portion of the removed solvent containing wash water to the second liquid distributor.

20. A system according to claim 19, further comprising:
- a recycle liquid provided to the second liquid distributor, wherein the recycle liquid includes at least a portion of the removed solvent containing wash water from the emission control section and at least a portion of the used wash water from the flue gas cooling section.





INTERNATIONAL SEARCH REPORT

International application No  
PCT/US2011/02Q631

**A. CLASSIFICATION OF SUBJECT MATTER**  
INV. B01D53/14 B01D53/18  
ADD.  
According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**  
Minimum documentation searched (classification system followed by classification symbols)  
B01D  
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)  
EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 2003/045756 A1 (MIMURA TOMIO [JP] ET AL) 6 March 2003 (2003-03-06) paragraphs [0055], [0056], [0057], [0060], [0061], [0062]; figure 1 -----	1-20
X	US 5 378 442 A (FUJII MASUMI [JP] ET AL) 3 January 1995 (1995-01-03) column 9, line 64 - column 10, line 54; figure 3 -----	1-6, 13-16
A	W0 2008/108657 A1 (AKER CLEAN CARBON AS [NO]; LUND RAND I [NO]; SANDEN KNUT [NO]; HAALAND) 12 September 2008 (2008-09-12) page 5, line 16 - page 7, line 32; figures -----	1-20
A	US 3 435 590 A (SMITH CALVIN S) 1 April 1969 (1969-04-01) figures -----	1-20

Further documents are listed in the continuation of Box C.

See patent family annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier document but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search 5 April 2011	Date of mailing of the international search report 12/04/2011
---	--

Name and mailing address of the ISA/ European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Fax: (+31-70) 340-3016	Authorized officer  Persichini, Carlo
--	---

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No PCT/US201 1/02Q63 1
---

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2003045756	AI	06-03 -2003	AU 772954 B2 13-05 -2004
			AU 1092402 A 06-05 -2002
			CA 2393626 AI 02-05 -2002
			DK 1334759 T3 12-07 -20 10
			EP 1334759 AI 13-08-2003
			Wo 0234369 AI 02-05 -2002
			JP 3969949 B2 05-09 -2007
			JP 2002 126439 A 08-05 -2002
			NO 20023053 A 14-08-2002
			RU 2230599 C2 20-06-2004
US 5378442	A	03-01 - 1995	DE 693 18433 D1 18-06- 1998
			DE 693 18433 T2 17- 12 - 1998
			EP 0553643 A2 04-08- 1993
W0 2008108657	AI	12-09 -2008	EP 2 13 1943 AI 16- 12 -2009
			US 2010061904 AI 11-03 -20 10
US 3435590	A	01-04- 1969	NONE