



US 20040153142A1

(19) **United States**(12) **Patent Application Publication****Klumb et al.**(10) **Pub. No.: US 2004/0153142 A1**(43) **Pub. Date: Aug. 5, 2004**(54) **EXPANDABLE COIL ENDOLUMINAL PROSTHESIS**(75) Inventors: **Katherine J. Klumb**, Los Altos, CA (US); **Thomas J. Fogarty**, Portola Valley, CA (US); **Kirti P. Kamdar**, Sunnyvale, CA (US); **Bradley B. Hill**, Portola Valley, CA (US)

Correspondence Address:


HAYNES BEFFEL & WOLFELD LLP
P O BOX 366
HALF MOON BAY, CA 94019 (US)(73) Assignee: **VASCULAR ARCHITECTS, INC., A Delaware corporation**, San Jose, CA (US)(21) Appl. No.: **10/731,737**(22) Filed: **Dec. 9, 2003****Related U.S. Application Data**

(63) Continuation of application No. 09/834,145, filed on Apr. 12, 2001, now Pat. No. 6,660,032, which is a

continuation of application No. 09/400,955, filed on Sep. 22, 1999, now Pat. No. 6,645,237, which is a continuation-in-part of application No. 09/258,542, filed on Feb. 26, 1999, now Pat. No. 6,248,122.

Publication Classification(51) **Int. Cl.⁷** **A61F 2/06**(52) **U.S. Cl.** **623/1.22**(57) **ABSTRACT**

A coiled stent (196) has a coiled stent body with a main body portion (106) and end portions (108). The end portions may be substantially less stiff than the body portion to help prevent tissue trauma. A graft material (124) may be used to cover at least the main body portion to create a coiled stent graft (122) in which adjacent turns (128) have gaps defined therebetween to create a generally helical gap (130). The coiled stent may have side elements (10) separated by connector elements (112) and be placeable in a contracted, reduced diameter state and in a relaxed, expanded diameter state. The connector elements are preferably generally parallel to the stent axis when placed in the contracted, reduced-diameter state, typically tightly wrapped around a placement catheter (136).






FIG. 1.




FIG. 1B.



FIG. 2A.




FIG. 2B.




FIG. 2C.




FIG. 2D.




FIG. 2E.








FIG. 2F.






FIG. 4D.




FIG. 4E.




FIG. 4C.




FIG. 5.




FIG. 6.




FIG. 7.




FIG. 7A.




FIG. 8.




FIG. 9.




FIG. 10.




FIG. 11.




FIG. 12.



FIG. 13A.




FIG. 14.




FIG. 13.




FIG. 15.




FIG. 16A.




FIG. 16B.




FIG. 16C.




FIG. 16D.




FIG. 16E.




FIG. 16F.




FIG. 16G.






FIG. 17A.






FIG. 18.




FIG. 19.



FIG. 20.




FIG. 21.

EXPANDABLE COIL ENDOLUMINAL PROSTHESIS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This is a continuation of U.S. patent application Ser. No. 09/834,145 filed 12 Apr. 2001, now U.S. Pat. No. 6,660,032, which is a continuation of U.S. patent application Ser. No. 09/400,955 filed 22 Sep. 1999, now U.S. Pat. No. 6,645,237, which is a continuation-in-part of U.S. patent application Ser. No. 09/258,542 filed 26 Feb. 1999, now U.S. Pat. No. 6,248,122. This is related to U.S. patent application Ser. No. 09/400,952 entitled Catheter With Controlled Release Endoluminal Prosthesis and Method For Placing, filed 22 Sep. 1999, now U.S. Pat. No. 6,238,430.

BACKGROUND OF THE INVENTION

[0002] The present invention provides devices and methods for the endoluminal placement of prostheses, particularly within the vascular system for the treatment of cardiovascular disease, such as vascular stenoses, dissections, aneurysms, and the like. The apparatus and methods, however, are also useful for placement in other body lumens, such as the ureter, urethra, biliary tract, gastrointestinal tract and the like, for the treatment of other conditions which may benefit from the introduction of a reinforcing or protective structure within the body lumen. The prostheses will be placed endoluminally. As used herein, "endoluminally" will mean placement by percutaneous or cutdown procedures, wherein the prosthesis is transluminally advanced through the body lumen from a remote location to a target site in the lumen. In vascular procedures, the prostheses will typically be introduced "endovascularly" using a catheter over a guidewire under fluoroscopic guidance. The catheters and guidewires may be introduced through conventional access sites to the vascular system, such as through the femoral artery, or brachial and subclavian arteries, for access to the target site.

[0003] An endoluminal prosthesis typically comprises at least one radially expansible, usually cylindrical, body segment. By "radially expansible," it is meant that the body segment can be converted from a small diameter configuration (used for endoluminal placement) to a radially expanded, usually cylindrical, configuration which is achieved when the prosthesis is implanted at the desired target site. The prosthesis may be non-resilient, e.g., malleable, thus requiring the application of an internal force to expand it at the target site. Typically, the expansive force can be provided by a balloon catheter, such as an angioplasty balloon for vascular procedures. Alternatively, the prosthesis can be self-expanding. Such self-expanding structures are provided by a temperature-sensitive superelastic material, such as Nitinol, which naturally assumes a radially expanded condition once an appropriate temperature has been reached. The appropriate temperature can be, for example, a temperature slightly below normal body temperature; if the appropriate temperature is above normal body temperature, some method of heating the structure must be used. Another type of self-expanding structure uses resilient material, such as a stainless steel or superelastic alloy, and forming the body segment so that it possesses its desired, radially-expanded diameter when it is unconstrained, e.g., released from radially constraining forces a

sheath. To remain anchored in the body lumen, the prosthesis will remain partially constrained by the lumen. The self-expanding prosthesis can be delivered in its radially constrained configuration, e.g. by placing the prosthesis within a delivery sheath or tube and retracting the sheath at the target site. Such general aspects of construction and delivery modalities are well-known in the art and do not comprise part of the present invention.

[0004] The dimensions of a typical endoluminal prosthesis will depend on its intended use. Typically, the prosthesis will have a length in the range from 0.5 cm to 10 cm, usually being from about 0.8 cm to 5 cm, for vascular applications. The small (radially collapsed) diameter of cylindrical prostheses will usually be in the range from about 1 mm to 10 mm, more usually being in the range from 1.5 mm to 6 mm for vascular applications. The expanded diameter will usually be in the range from about 2 mm to 42 mm, preferably being in the range from about 3 mm to 15 mm for vascular applications.

[0005] One type of endoluminal prosthesis includes both a stent component and a graft component. These endoluminal prostheses are often called stent grafts. A stent graft is typically introduced using a catheter with both the stent and graft in contracted, reduced-diameter states. Once at the target site, the stent and graft are expanded. After expansion, the catheter is withdrawn from the vessel leaving the stent graft at the target site.

[0006] Grafts are used within the body for various reasons, such as to repair damaged or diseased portions of blood vessels such as may be caused by injury, disease, or an aneurysm. It has been found effective to introduce pores into the walls of the graft to provide ingrowth of tissue onto the walls of the graft. With larger diameter grafts, woven graft material is often used. In small diameter vessels, porous fluoropolymers, such as PTFE, have been found useful.

[0007] Coil-type stents can be wound about the catheter shaft in torqued compression for deployment. The coil-type stent can be maintained in this torqued compression condition by securing the ends of the coil-type stent in position on a catheter shaft. The ends are released by, for example, pulling on wires once at the target site. See, for example, U.S. Pat. Nos. 5,372,600 and 5,476,505. Alternatively, the endoluminal prosthesis can be maintained in its reduced-diameter condition by a sleeve; the sleeve can be selectively retracted to release the prosthesis. A third approach is the most common. A balloon is used to expand the prosthesis at the target site. The stent is typically extended past its elastic limit so that it remains in its expanded state after the balloon is deflated. One balloon expandable stent is the PALMAZ-SHAITZ stent available from the CORDIS Division of Johnson & Johnson. Stents are also available from Arterial Vascular Engineering of Santa Rosa, Calif. and Guidant Corporation of Indianapolis, Ind.

SUMMARY OF THE INVENTION

[0008] The present invention is directed to an endoluminal prosthesis configured to help avoid trauma to a patient's tissue.

[0009] One aspect of the invention is directed to a coiled stent having a coiled stent body with a main body portion and end portions. The end portions are substantially less stiff than the body portion to help prevent tissue trauma.

[0010] The main body portion may include a ladder-like stent having edge elements separated by connector elements. The end portions may have inwardly-tapering portions with blunt tips. The inwardly-tapering portions may have lengths greater than the widths. The main body portion may also be designed to have longitudinal sections with different radial stiffnesses.

[0011] A graft material may be used to cover at least the main body portion to create a coiled stent graft in which adjacent turns have gaps defined therebetween to create a generally helical gap. The generally helical gap helps to promote a helical pattern of tissue ingrowth so that even if substantial tissue ingrowth occurs, the vessel will be much less likely to be sealed off than if the exposed tissue defined a circular pattern. The use of the generally helical gap may help speed up healing because the generally helical gap may help cells to proliferate more evenly between the coils and may enhance non-turbulent flow to help reduce restenosis.

[0012] Further aspects of the invention relates to an endoluminal prosthesis having a body with side elements separated by connector elements and a placement method therefore. The body is placeable in a contracted, reduced diameter state and a relaxed, expanded state. The connector elements are generally parallel to the axis of the body when placed in the contracted, reduced-diameter state, typically surrounding a placement catheter.

[0013] According to another aspect of the invention the endoluminal prosthesis includes a coiled body having first and second ends and a main portion therebetween. The main portion has an average cross-sectional dimension of x . At least one of the first and second ends has a maximum cross-sectional dimension of about $5x$ to $25x$ and a blunt tip to avoid trauma to the patient's tissue. The tip typically has a flattened, generally oval shape while the main body portion typically has a rectangular cross-sectional shape.

[0014] Other features and advantages of the invention will appear from the following description in which the preferred embodiments have been set forth in detail in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0015] FIG. 1 is an overall view of a catheter assembly using a straight stent embodiment;

[0016] FIG. 1A is an enlarged cross-sectional view taken along line 1A-1A of FIG. 1;

[0017] FIG. 1B is an enlarged simplified partial cross-sectional view of the distal portion of the catheter of FIG. 1, with the addition of a general tubular external graft, to illustrate the relative relationship between the various components;

[0018] FIG. 2A illustrates the catheter of FIG. 1A introduced into a blood vessel at a target site after the sheath has been pulled back to expose the stent and balloon at the target site, the graft of FIG. 1B being omitted from FIGS. 2A-2G for clarity of illustration;

[0019] FIG. 2B is similar to FIG. 2A with the distal portion of the balloon partially inflated to cause the first, distal stent portion to disengage from the first stent portion holder;

[0020] FIG. 2C is similar to FIG. 2B but after the balloon has been deflated which permits the distal portion of the stent to spin relatively freely and thus expand to press against the inside wall of the blood vessel;

[0021] FIG. 2D illustrates the balloon fully reinflated and showing the second, proximal end of the stent disengaged from the second stent end holder;

[0022] FIG. 2E is similar to FIG. 2D but with the balloon fully deflated;

[0023] FIG. 2F shows the stent in its second, expanded-diameter state after withdrawal of the distal portion of the catheter shaft;

[0024] FIG. 3A is an enlarged view illustrating a push wire extending along the catheter shaft, passing through a push wire tube to permit the second, proximal end of the stent to be disengaged from the catheter shaft;

[0025] FIG. 3B illustrates the first stent end holder and the first, distal end of the stent which slidably engages an opening formed in the first stent end holder;

[0026] FIG. 4A illustrates the stent of FIG. 2G with the external graft of FIG. 1B surrounding the stent and held against the inner wall of the blood vessel by the stent;

[0027] FIG. 4B illustrates the stent of FIG. 2G with an internal graft;

[0028] FIG. 4C illustrates fastening an internal graft to an external stent using strips of graft material creating pathways for the stent;

[0029] FIG. 4D illustrates an alternative coil-type stent in which the stent comprises a pair of spaced-apart coiled stent wires;

[0030] FIG. 4E illustrates a stent graft in which parallel stent wires are kept in a spaced-apart relationship by spacers, the coiled stent wires being covered on both the inside and the outside by graft material, only a portion of the stent of FIG. 4A shown covered by the graft material to illustrate the arrangement of the coiled stent wires and spacers;

[0031] FIG. 5 shows a bifurcated version of the catheter and balloon allowing for deployment of a bifurcated prosthesis, the prosthesis not shown;

[0032] FIG. 6 illustrates a bifurcated stent;

[0033] FIG. 7 shows the bifurcated stent of FIG. 6 loaded onto the bifurcated catheter of FIG. 5 with the balloon deflated;

[0034] FIG. 7A is an enlarged cross sectional view taken along line 7A-7A of FIG. 7;

[0035] FIG. 8 shows the bifurcated stent of FIG. 7 deployed in a bifurcated vessel with the balloon inflated;

[0036] FIG. 9 shows the stent of FIG. 8 deployed in the vessel and the withdrawal of the catheter;

[0037] FIG. 10 shows a bifurcated catheter with a spring member used to keep the catheter shaft arms apart;

[0038] FIG. 11 illustrates a stent blank used to create a coiled stent similar to that shown in FIG. 4E;

[0039] FIG. 12 illustrates a stent blank similar to that of FIG. 11 but having different thickness along its length;

[0040] FIG. 13 illustrates a stent graft in a radially expanded condition, the stent graft including a stent similar to that shown in FIG. 11 covered with a sleeve of porous graft material, the stent graft having a central turn with a greatly increased pitch for placement at a branching intersection;

[0041] FIG. 14 illustrates a stent graft similar to that of FIG. 13 but in which one end of the stent graft has much greater radially expanded diameter than the other portion to accommodate a vessel having different internal diameters;

[0042] FIG. 15 illustrates an alternative embodiment to the stent graft of FIG. 13 in which the stent graft has a large expanded diameter and also has the one turn with the greater pitch at one end of the stent graft;

[0043] FIG. 15A shows a stent graft similar to that of FIG. 13 but with generally evenly-spaced turns;

[0044] FIG. 16A is an overall view of the distal end of a three-shaft deployment catheter used to deploy the stent grafts of FIGS. 13-15;

[0045] FIG. 16B is an end view of the shafts of 16A;

[0046] FIG. 16C is an embodiment similar to the catheter of FIG. 16A but including only inner and outer shafts;

[0047] FIG. 16D illustrates a proximal end adapter mounted to the proximal end of the catheter of FIG. 16C;

[0048] FIG. 16E illustrates an alternative embodiment of the catheter of FIG. 16C;

[0049] FIGS. 16F and 16G are simplified side and cross-sectional views of a further alternative embodiment of the catheter of FIGS. 16A and 16B;

[0050] FIG. 17A illustrates the stent graft of FIG. 13 tightly wrapped about the distal end of the catheter of FIGS. 16A and 16B and placed within a vessel with the intermediate portion of the stent graft at the intersection of the main and branching vessels;

[0051] FIG. 17B illustrates the release of the proximal half of the stent graft;

[0052] FIG. 17C illustrates the release of the distal half of the stent graft prior to the removal of the catheter shafts;

[0053] FIGS. 18 and 19 illustrate the placement of radiopaque marks at different positions along a coiled ladder-type stent having a central turn with a greatly increased pitch;

[0054] FIG. 20 illustrates one example of a radiopaque marker shaped to permit the determination of the orientation of the prosthesis as well as its location; and

[0055] FIG. 21 illustrates a coiled prosthesis having enlarged blunt ends to help prevent tissue trauma.

DESCRIPTION OF THE SPECIFIC EMBODIMENTS

[0056] FIG. 1 illustrates a catheter assembly 2 including broadly a catheter 4 extending from a proximal end adaptor 6, the catheter having an introducer sheath 8 slidably mounted over the catheter. Proximal end adaptor 6 includes a body 10 to which a push wire manipulator 14 is slidably mounted. Proximal end adaptor 6 also includes an inflation

port 16, to permit a balloon, discussed below, to be inflated and deflated during use, and a guidewire port 17.

[0057] Catheter 4 includes elongate catheter shaft 18 defining three lumens therein. FIG. 1A illustrates an inflation lumen 20, coupled to inflation port 16, a guidewire lumen 22 housing a guidewire 24, the proximal end of the guidewire passing through guidewire port 17. The catheter shaft 18 also includes a push wire lumen 26 housing a push wire tube 28, a push wire 30 being housed within push wire tube 28. Push wire 30 is connected to push wire manipulator 14 and is pushed and pulled through push wire tube 28 by the movement of manipulator 14. Push wire tube 28 is used to help prevent push wire 30 from buckling, which may occur during use due to the relatively thin diameter of the push wire, typically about 0.10 to 0.76 mm (0.004 to 0.030 inch). The distal end of guidewire 24, not shown, is positioned near the tip 32 of catheter shaft 18 and is used to help guide tip 32 through the body, typically through blood vessels, as is conventional. During the typically percutaneous introduction of the distal portion 34 of catheter 4 into the vasculature, sheath 8 is in the distal position shown in FIG. 1 to cover up the balloon 36, stent 38, and graft 40 as shown in FIG. 1B.

[0058] Once in position at the target site 42 in blood vessel 44, see FIG. 2A, handle 46 of introducer sheath 8 is pulled in a proximal direction to expose graft 40, stent 38, and balloon 36. Note that in FIGS. 2A-2F, graft 40 is not shown for clarity of illustration.

[0059] Stent 38 is a coil-type of stent typically made of 0.10 to 0.76 mm (0.004 to 0.030 inch) diameter Nitinol wire. Stent 38 may be made of other materials including stainless steel, Elgiloy®, a cobalt-chromium-nickel alloy made by Elgiloy Inc., and polymers. Stent 38, when in a relaxed state, typically has a diameter of about 2 to 30 mm to accommodate blood vessel 44 having an internal diameter of about 2 to 30 mm. The wire diameter, coil diameter, and other properties of stent 38 may vary according to the particular body region to be accessed and the procedure to be conducted. In FIGS. 1B and 2A, balloon 36 is in a deflated condition while stent 38 is in a first, reduced-diameter state with the coil-type stent 38 in torqued compression onto catheter shaft 18 and balloon 36. Stent 38 includes a proximal end 48, shown also in FIG. 3A, which is housed within a hollow interior of a stent end holder 50. Proximal end 48 of stent 38 can be selectively dislodged from proximal stent end holder 50 by the distal movement of push wire 30 through push wire tube 28. In this embodiment, proximal stent end holder 50 is an extension of push wire tube 28 as suggested in FIG. 3A. Instead of push wire 30, push wire tube 28 could be pulled into catheter shaft 18 to release proximal end 48 of stent 38.

[0060] It may be desired that the length of stent 34 be about the same when in the reduced-diameter state as when in the relaxed, enlarged-diameter state. This is desirable to minimize shifting of the stent at the target site during deployment. The use of a coil-type stent helps to achieve this by permitting the appropriate spacing the turns of the stent onto the balloon-covered catheter shaft when in a reduced-diameter state. For example, stent 38 having a relaxed diameter of 6 mm, a relaxed length of 5 cm and 10 turns in a relaxed state, can be wound onto the balloon-covered catheter shaft to assume a reduced-diameter state with about

30 turns, a diameter of about 2.5 mm and the same length of about 5 cm. The results will vary depending on various factors, such as the pitch of the coil.

[0061] A proximal end 52 of balloon 36 is spaced-apart from stent end holder 50 by a distance sufficient to permit at least one turn, and preferably one-and-a-half to two turns, of stent 38 to be wrapped directly around catheter shaft 18 without any of balloon 38 being between stent 38 and catheter shaft 18. The purpose of this is to inhibit the dislodgment of proximal end 48 from stent end holder 50 upon the initial inflation of balloon 36 as will be discussed in more detail below. Thus, the initial turn or turns of stent 38 are in effective contact with catheter shaft 18 because there is no portion of balloon 36 between the turn or turns of the stent and the catheter shaft.

[0062] The distal end 54 of balloon 36 is positioned near the distal stent end holder 56. Accordingly, when the distal stent end 58 is engaged within distal stent end holder 56, stent 38 quickly starts wrapping around balloon 36. Thus, upon inflation of balloon 36, distal stent end 58 is pulled from distal end holder 56 as shown in FIG. 2B. Note that in FIG. 2B, balloon 36 is only partly inflated. Inflation of distal end 54 of balloon 36 is aided in this embodiment by somewhat more loosely wrapping stent 38 around the balloon at distal end 54 than over the remainder of the balloon. This reduces the resistance to inflation of the balloon at distal end 54 thus permitting the expansion of the distal end of stent 38 before expansion at its proximal end. Other ways to promote this initial expansion of distal end 54 of balloon 36, such as making distal end 54 easier to expand than the remainder of the balloon or only partially retracting sleeve 8 or using a balloon with separately inflatable proximal and distal portions, can be used.

[0063] After this partial expansion of balloon 36, the balloon is deflated as shown in FIG. 2C. This permits stent 38 to more freely expand within blood vessel 44 so that a greater portion of the stent is in its expanded state in FIG. 2C than in FIG. 2B. FIG. 2D illustrates balloon 36 after having been fully inflated and the dislodgment of proximal end 48 of stent 38 from proximal end stent holder 50 by moving push wire 30 distally through the manipulation of push wire manipulator 14. This dislodgment of proximal end 48 preferably occurs after the full inflation of balloon 36; it could also occur before the full inflation of the balloon as well.

[0064] FIG. 2E illustrates balloon 36 deflated leaving stent 38 in its expanded-diameter state pressing graft 40, not shown in FIGS. 2A-2F but shown in FIG. 4A, against the inner wall of blood vessel 44. Though not always necessary, it may be desired to move sheath 40 in a distal direction to cover balloon 36 prior to removing the distal portion of the catheter shaft. FIG. 2F illustrates stent 38 in its expanded-diameter state after removal of catheter shaft 18 and sheath 8. It can be noted that in FIGS. 1B and 4A the length of graft 40 is shorter than the length of stent 38; this helps to ensure that the ends of graft 40 are pressed against the interior of blood vessel 44.

[0065] In use, the user introduces distal portion 34 of catheter 4 into, for example, a suitable blood vessel 44 and directs tip 32 of catheter shaft 18 to a target site 42 using guidewire manipulator 12 and appropriate visualization techniques as is conventional. Balloon 36 is partially inflated

through inflation port 16 to the condition of FIG. 2B causing distal stent end 58 to be dislodged from distal stent end holder 56. Balloon 36 is then deflated to permit a distal portion of stent 38 to more fully expand within blood vessel 44. Balloon 36 is then fully expanded as shown in FIG. 2D and push wire 30 is extended by moving push wire manipulator 14 in a distal direction causing proximal end 48 of stent 36 to be dislodged from proximal stent end holder 50; alternatively, push wire 30 could be extended to first dislodge proximal end 48 of stent 38B from proximal end stent holder 50 and then balloon 36 could be fully expanded. The inflation of balloon 36 also expands graft 40. Balloon 36 is then deflated as shown in FIG. 2E and withdrawn into sheath 8. A distal portion of catheter shaft 18 and balloon 36 therewith are then withdrawn from target site 42 in blood vessel 44 (see FIG. 2F) leaving stent 38 and graft 40, which together constitute a stent graft 59, in place as shown in FIG. 4A.

[0066] FIG. 4B illustrates an alternative embodiment in which graft 40A is an internal graft coupled to stent 38. One method of coupling internal graft 40A to stent 38 is through the use of one or more strips 60 of graft material. Pockets, not shown, are created between stent 40A and strips 60 to permit stent 38 to pass between the two. The gaps are relatively large to prevent graft 40A from being overly deformed during the deployment of the stent and graft.

[0067] FIG. 4D illustrates a stent 38A made up of a pair of spaced-apart coiled stent wires joined together at their ends. To permit the ends of stent 38 to be secured to catheter shaft 18, the stent end holders could, for example, be modified to accommodate the generally U-shaped ends or the ends could be squeezed together or otherwise made to form a pointed end as suggested by the dashed lines at one end of stent end 38A.

[0068] FIG. 4E illustrates a presently preferred embodiment in which a stent 38B is made up of a pair of coiled stent wires 62 joined together and maintained in a spaced-apart relationship by spacer wires 64 to create a ladder-like stent 38B. A strip 66 of graft material is secured to coiled stent wire 62 to form a spiral graft 40B surrounding stent 38B to lie on both the inside and the outside of the stent. Only a portion of stent 38B is covered with strip 66 to illustrate the construction of the stent. Strip 66 of graft material can be adhered to stent 38B in a variety of ways including use of an adhesive, heat welding, or making strip 66 in the form of a tube or a double-sided strip with a hollow interior which encases coiled stent wires 62. It can be seen that only one of the two coiled stent wires 62 extend outwardly at each end of stent 38B to form the proximal end 48B and the distal end 58B of stent 38B.

[0069] Ladder-like stent 38B could also be made from a tube or sheet of stent material by, for example, stamping, laser cutting, waterjet cutting or other suitable processes. It is expected that processes which do not overly heat the stent material, such as waterjet cutting, may be preferred. The graft material can be in the form of a tube of graft material which is slid over ladder-like stent 38B and secured in place by, for example, suturing the ends of the graft material.

[0070] FIG. 5 shows a distal portion 34D of a bifurcated catheter made according to the invention with like reference numerals referring to like elements. Catheter shaft 18D includes first and second arms 70, 72 terminating at first and

second tips **74, 76**. In **FIG. 5** neither a stent, shown in **FIG. 6**, nor graft material is illustrated for clarity of illustration. Balloon **36D** is a bifurcated balloon having a first portion **78** extending along first arm **70** and a second portion **80** extending along second arm **72**. Proximal stent end holder **50** is carried on catheter shaft **50D** while distal stent end holder **56D** is positioned along first arm **70D**. The stent end holders **50D, 56D** are similar to stent end holders **50, 56** illustrated in **FIGS. 3A and 3B** with the hollow tubular members extending distally for proximal stent end holder **50** and proximally for distal stent end holder **56D**. A second distal stent end holder **82** is carried along second arm **72** and has a distally extending open-ended tube **84** corresponding to push wire tube **28D** in that it also extends in a distal direction and uses a push wire to disengage the end of a stent from within the push wire tube **84**. As discussed above, other methods for removing the ends of the stents from push wire tubes **28D, 84** such as retracting the push wire tubes proximally, could also be used.

[0071] **FIG. 6** illustrates a bifurcated stent **38D** having a main portion **86** and first and second arms **88, 90** which are wrapped around main portion of catheter shaft **18D** and first and second arms **70, 72** respectively. Arm **88** is an extension of main portion **86**; arm **90** is joined to arm **88** and main portion **86** at junction **102**. Proximal end **48D** of stent **38D** corresponds to proximal end **48** of stent **38** as shown in **FIG. 3A** while distal end **58D** of stent **38D** corresponds to distal stent end **58** of stent **38** shown in **FIG. 3D**. Proximal and distal ends **48D, 58D** engage proximal and distal stent end holders **50D, 56D** in manner similar to those of **FIGS. 3A and 3B**. However, the distal end **92** of second arm **90** may have a reverse bend.

[0072] As shown in **FIG. 7A**, catheter shaft **18D** defines three lumens, inflation lumen **20D**, guidewire lumen **22D**, housing tube guidewires **24D**, one for each arm **70, 72**, and a push wire lumen **26D** housing push wire tubes **28, 84** with push wires **30D** slidably passing within the push wire tubes **28D, 84**.

[0073] **FIG. 7** illustrates distal catheter portion **34D** with balloon **36D** in a collapsed state, stent **38D** wrapped around both balloon **36D** and distal portion **34D**, and showing the outline of a branched vessel **44D** shown in dashed lines. Again, as with **FIGS. 2A-2F**, graft material is not shown for ease of illustration. However, as with the embodiments of **FIGS. 1-4**, graft material is typically used with stent **38D**. Of course other types of stents, other than the coiled bifurcated stent shown in **FIG. 6**, could be used as well. The placement of stent **38D** occurs in substantially the same fashion as can occur with the straight stent described above. The main difference is that proximal ends **48D** and **92** of stent **38D** are both released using push wires **30D** while distal stent end **58D** is released by the partial inflation of balloon **36D**. **FIG. 8** illustrates the result of having gone through the stent end release cycle, that is typically partial inflation, which releases stent end **58D**, deflation and then the full inflation and release of stent ends **48D, 92**. After stent **38D** has been expanded, distal catheter portion **34D** and balloon **36D** therewith are removed from the bifurcated target site as suggested in **FIG. 9**. Again, graft material is not shown for clarity of illustration. As with the above embodiments, graft material may not be, but often is, used with the stent or other prosthesis.

[0074] **FIG. 10** illustrates a distal catheter portion **34E** similar to that shown in **FIG. 5** in which the first and second arms **70, 72** are biased outwardly at their junction **94** by a biasing element **96** which tends to separate arms **70, 72** from one another. Biasing element may be made of a variety of materials, such as a leaf spring or, as illustrated, a triangular section of a resilient spongy material such as silicone or polyurethane. Using biasing element **96** helps to ensure arms **70, 72** are directed down different vascular segments **98, 100**. To do so distal catheter portion **34E** is typically housed within sheath **8** until just above the target site. At that point, distal portion **34E** is extended out through the open distal end of introducer sheath **8** permitting arms **70, 72** to move freely into vascular segments **98, 100**. This movement may be aided using guidewires **24D** in addition to biasing element **96**.

[0075] Modifications and variation may be to the above-described catheter assembly and method may be made. For example, it may not be necessary to only partly inflate the balloon as indicated in **FIG. 2B**; rather, it may be desired to fully inflate the balloon to release distal stent end **58** from distal stent end holder **56**. Also, it may not be necessary to deflate the balloon after the full or partial inflation of the balloon as shown in **FIG. 2C**. In a preferred embodiment, a coiled stent is placed in torqued compression onto the catheter shaft and balloon. Other types of radially expanding stents, which may or may not be self-expanding, can be used as well. For example, tubes of stent material having numerous axially extending slits which permit the tube to be expanded radially in a diamond-like pattern using the balloon can be used. The stent could also be made of a temperature-sensitive shape-memory material. In the preferred embodiment, balloon **36** is necessary to expand graft **40** from its reduced-diameter state of **FIG. 1B** to its expanded-diameter state of **FIG. 4A**; graft material may be used which does not require a balloon to place it into its fully expanded condition. In the preferred embodiment, graft **40** is an expandable, porous PTFE graft material such as that available from IMPRA, Baxter, W. L. Gore or Atrium. Other types of graft material, such as polyester or polyurethane, can be used. Instead of mechanically releasing proximal end **48** of stent **38**, the proximal end can be held and selectively released by electrolytic methods as shown in U.S. Pat. No. 5,122,136 to Guglielmi, et al. Distal stent end **58** could be releasably coupled to catheter shaft **18** for release by inflation of balloon **36** by other than holder **56**, such as through a releasable or breakable tether, a clip or other fastener, adhesive or other releasable or breakable structure. The holding and selective release of proximal stent end **48** could be by using a range of conventional or unconventional holders; for example, the distal end of sheath **8** could be left to cover the proximal end **52** of balloon **36** during the initial inflation of balloon and then pulled back to uncover the proximal balloon end for the subsequent inflation of the balloon. Pull or push wires could be used to actuate a catch to release proximal stent end **48**. Conventional techniques, such as those shown in U.S. Pat. Nos. 5,372,600; 5,476,505; 5,683,451; 5,443,500; 4,913,141; 5,246,445; 5,360,401; 5,201,757; 4,875,480; 4,848,343; 4,732,152; and 4,665,918, and those shown in WO 97/07756 and WO 94/16629, may also be used to release proximal stent end **48**.

[0076] Bifurcated embodiments have been shown illustrating use of a single balloon. If desired, a number of separate balloons could be used instead of a single balloon.

For example, three separate balloons could be used, one for each branch of the stent. The three balloons could be all coupled to a single inflation lumen; in such case the three separate balloons would act similarly to the single balloon. However, if each balloon were separately inflatable, more than one of the stent ends could be released through the inflation of the various balloons. Stent 38D is shown with main portion 86 and first and second arms 88, 90 secured together at a common location 102. It may be desired to have, for example, second arm 90 be joined to a section of stent 38D between main portion 86 and first arm 88 by a sliding connection; this may be useful to help properly seat or orient the stent or a stent graft within the bifurcated vessel. First arm 88 is shown as a single continuous coil in FIG. 6. If desired, first arm 88 could include one or more separate sections of stent to create the first arm. Instead of having a single catheter split into two catheter arms, second arm 72 could actually be a separate catheter extending through the interior of catheter shaft 18D; this would facilitate inflating a balloon associated with the second arm separately from the one or more other balloons associated with the main portion of the catheter shaft and the first arm. It may also permit the second arm of the catheter shaft to move longitudinally relative to the main catheter shaft and the first arm of the catheter shaft.

[0077] FIG. 11 illustrates a stent blank 104 used to create a coiled stent similar to that shown in FIG. 4E. Stent blank 104 includes a main body portion 106 and first and second end portions 108. Main body portion 106 includes side edge or rail elements 110 connected by connector or rung elements 112. Rung elements 112 are, as shown in FIG. 11, at an angle to rail elements 110 so that when stent blank 104 is formed into a coiled stent and tightly wrapped about an introducer catheter, such as in FIG. 17A, rung elements 112 are axially-extending so that they lie flat for a tighter wrap.

[0078] End portions 108 are thinner and thus more flexible than main body portion 106. In addition, end portions 108 have an inwardly tapering portion 114 terminating at a blunt tip 115. The shape of end portions 108 and the lessened stiffness of the end portions, compared to body portion 106, help to prevent tissue trauma during use. This type of coiled stent in which the end portions 108 are less stiff than the main body portion 106 can find particular utility in stabilizing a traumatic injury site within a patient, such as in the case of a dissection, flap or false lumen. End portion 108 could also be stiffer than main body portion; this embodiment may be useful, for example, when treating occlusive disease on either side of a branch vessel.

[0079] FIG. 12 illustrates a stent blank 104A similar to stent blank 104 of FIG. 11 but in which main body portion 106A has three different radial stiffnesses. That is, main body portion 106A has a first, central longitudinal section 116 of a first, greater stiffness, and second and third longitudinal sections 118, 120 on either side of first section 116. Sections 118, 120 are successively thinner and thus have successively lower radial stiffnesses when stent blank 104A is formed into a coiled stent. End portion 108A acts as the fourth longitudinal section with the least radial stiffness of any of the sections in this embodiment. Instead of a set of generally discrete radial stiffnesses, the radial stiffness could vary continuously along at least part of the length of stent blank 104A, and then along the resulting stent body.

[0080] In addition to providing less traumatic end portions 108, 108A, a coiled prosthesis formed from either of stent blanks 104, 104A, when uncoiling, will have a tendency to open up first in the center, because of the greater stiffness at the center, followed by the ends. This helps to reduce the degree to which the end portions 108, 108A are dragged along the surface of the vessel or other hollow body structure as the prosthesis is released.

[0081] FIGS. 13, 14, 15 and 15A illustrate four stent graft embodiments 122, 122A, 122B, 122C. Stent graft 122 includes a ladder-type coiled stent formed from stent blank 104 and covered with tubular graft material 124. Graft material 124 is preferably porous PTFE or ePTFE. The ends 126 of graft material 124 are sealed, or for example, by using an adhesive or by placing a suitable heat seal material, such as FEP (fluorinated ethylene propylene) or other thermoplastic materials, between the layers of the graft material 124 and applying heat and pressure. The porous nature of the graft material permits sealing in this manner in spite of the inert nature of PTFE. In addition, a direct bond of the PTFE to itself, via a process known as sintering, may be employed. Other methods for sealing ends 126 could also be used. Coiled stent graft 122 includes a number of spaced apart turns 128 defining a generally helical gap 130 therebetween. The helical nature of the gap 130 is believed to help prevent restenosis in two ways. First, the helical nature of stent graft 122 and of gap 130 is expected to help induce a blood flow pattern which helps to reduce plaque build up. Second, if plaque build up does occur along the edges of helical gap 13, the helical nature of gap 13 is expected to help cells to proliferate more evenly between adjacent turns 128 and may enhance non-turbulent flow to help reduce restenosis.

[0082] The average width of helical gap 130 is equal to about 0% to 1200% of the average width of turns 128. More typically the average width of gap of 130 is about 50% to 800% of the average width of turns 128 when stent graft 122 is deployed. Also, stent graft 122 has a generally constant pitch except at its central region. The pitch of a central turn 132 of stent graft 122 is substantially greater than the pitch of its adjacent turns 128 to accommodate placement of stent graft 122 at the intersection of a main or first vessel and a branching vessel as will be discussed in more detail with reference to FIGS. 17A-17C.

[0083] FIG. 14 illustrates a stent graft 122A in which a central turn 132A also has an increased pitch as opposed to adjacent turns 128A. However, the turns on one side of central turn 132A have a larger fully-expanded diameter than turns on the other side to accommodate transition between smaller and larger diameter vessels.

[0084] FIG. 15 illustrates a stent graft 122B designed for placement with the end turn 134 having a substantially greater pitch than its adjacent turn 128B. Stent graft 122B is used when one end of the stent graft is to be positioned at the intersection and main and branching vessels so that the stent graft extends to one side of the intersection as opposed to both sides as in the embodiments of FIGS. 13 and 14. FIG. 15A illustrates stent graft 122C, which may be used at locations other than bifurcations, having generally uniformly spaced turns 128C.

[0085] FIGS. 16A-16B illustrate a catheter 136 used for deploying the stent grafts of FIGS. 13 and 14. Catheter 136 includes outer, intermediate and inner rotating, telescoping

shafts **138, 140, 142** each having a distal end **144, 146, 148**. Each of the shafts has a prosthesis portion holder **150, 150A, 150B** at its distal end **144, 146, 148**. Prosthesis portion holders **150, 150A, 150B** include pull wires **152, 152A, 152B** which pass along axially-extending lumens **154, 154A, 154B** formed in the body of shafts **138, 140, 142**, out of exit holes **156, 156A, 156B**, across gaps **158, 158A, 158B** and back into reinsertion openings **160, 160A, 160B**. Pull wires **152, 152A, 152B** pass through and engage different portions of, for example, stent graft **122** and secure those portions of the stent graft to shafts **138, 140, 142**. As shown in **FIG. 17A**, prosthesis portion holder **150B** at distal end **148** of inner shaft **142** engages the distal end **166** of stent graft **122**. Holders **150, 150A** at distal ends **144, 144A** of outer and intermediate shafts **138, 140** engage proximal end **168** and central turn **132** of stent graft **122**, respectively. One or more of shafts **138, 140, 142** may be braided to enhance torquing stiffness to aid rotation.

[0086] **FIG. 16C** illustrates the distal end of a catheter **136A** including only two shafts, outer shaft **138A** and inner shaft **142A**. Catheter **136A** is typically used when placing an endoluminal prosthesis of the type which does not have a central turn with an increased pitch, such as those of **FIGS. 15 and 15A**, and thus does not need a catheter with an intermediate shaft.

[0087] **FIG. 16D** illustrates, in a simplified form, a proximal end adapter **170** mounted to the proximal end of catheter **136A** of **FIG. 16C**. Proximal end adapter **170** includes distal and proximal portions **172, 176** through which catheter **136A** passes. Proximal end adapter **170** provides for the rotation of either or both shafts **138A, 142A** through the manipulation of thumb wheel **174** mounted to portion **176**. A flip lever **175** extends from distal portion **172** and is movable between secured and released positions to either secure shafts **138A, 142A** to one another or to permit shafts **138A, 142A** to move axially relative to one another. Pull wires **152, 152B** are normally secured to their respective shafts **138A, 142A** by deployment knobs **178, 180**; pulling on deployment knobs **178, 180** releases pull wires **152, 152B**, respectively to permit the pull wires to be pulled to release the endoluminal prosthesis from the appropriate holder **150, 150B**.

[0088] **FIGS. 16F and 16G** illustrate a further three-shaft embodiment of the invention similar to the three-shaft embodiment of **FIGS. 16A and 16B**. Instead of using lumens **154** to house pull wires **152**, tubular members **162, 162A, 162B**, typically hypotubes, could be secured to the outside of the shafts **138B, 140B, 142B**. Gaps or breaks are provided at the distal ends of hypotubes **162, 162A, 162B** to define the gaps **158, 158A, 158B**.

[0089] **FIG. 17A** shows stent graft **122** of **FIG. 13** tightly wrapped about catheter **136**. Distal end **166**, proximal end **168** and central turn **132** of stent graft **122** are secured to distal ends **148, 144** and **146** of inner, outer and intermediate shafts **142, 138, 140** by prosthesis portions holders **150**. Stent graft **122** is housed within a main vessel **182** with central turn **132** aligned with the intersection **184** of main vessel **182** and branching vessel **186**. To help ensure proper placement of central turn **132** at intersection **184**, stent graft **122** has one or more remote visualization markers at or adjacent to turn **132**. Radiopaque markers **188, 190, 192** are shown in **FIG. 18** at distal, intermediate and proximal portions of the

central turn **194** of stent **196**. Radiopaque markers may be shaped to provide information as to both location and orientation of stent **196** on the catheter. For example, radiopaque marker **190A** of **FIG. 19** has a broad central portion **190B** extending between rail elements **110** and arm portions **190C** extending along rail elements **110**; this permits marker **190A** to provide both location and orientation information about stent **196A**. Orientation marker **190A** is configured so that the viewer can determine whether the turn is facing the viewer or is away from the viewer based upon the marker's orientation. Various other marker shapes to provide both location and orientation can also be used.

[0090] Radiopaque markers may also be used on the placement catheter itself. For example, radiopaque markers **191, 193, 195** are used on shafts **138B, 140B, 142B** aligned with their respective holders **150, 150A, 150B**, as shown in **FIG. 16F**, to indicate the location of the holders. Radiopaque marker **193** is shown to be configured as an orientation specific marker to help in the proper placement of the prosthesis. **FIG. 20** illustrates the shape of an orientation-specific radiopaque marker **197** which could be placed, for example, on shafts **138, 140, 142** at one or more of the holders **150** of the embodiments of **FIGS. 16A, 16C and 16E**. Radiopaque or other remote visualization markers may also be used at other positions along the endoluminal prosthesis, such as at each end, or along the placement catheter.

[0091] **FIG. 17B** illustrates the release of proximal end **168** of stent graft **122** while **FIG. 17C** illustrates the subsequent release of distal end **166** of stent graft **122**. It should be noted that central turn **132** remains secured to intermediate shaft **140** while the distal and proximal ends **166, 168** of stent graft **122** are released to ensure that the open region of central turn **122** remains facing intersection **184** to help ensure substantially unrestricted fluid flow between main vessel **182** and branching vessel **186**. It should also be noted that prior to releasing the stent graft, the number of turns can be increased or decreased by the relative rotation of shafts **138, 140** and **142**. Also, the length of stent graft **122** can be changed by the relative axial sliding motion among outer, intermediate and inner shafts **138, 140, 142**. For example, instead of simply releasing proximal end **168** of stent graft **122** to the position shown in **FIG. 17B**, it may be desired to rotate outer shaft relative to intermediate shaft **140**, keeping intermediate and inner shafts **140, 142** stationary so to unwind the proximal half of the stent graft to ensure that the stent graft is properly positioned prior to releasing the stent graft. Similarly, both outer shaft and inner shafts can be rotated while maintaining intermediate shaft stationary to create the expanded diameter condition of **FIG. 17** prior to releasing any portion of the stent graft. In this way the physician can ensure that stent graft **122** is properly positioned, especially with respect to central turn **132**. If necessary or desired, intermediate shaft **140** could be, for example, rotated relative to outer and inner shafts **138, 142** to help properly position or reposition central turn **132**.

[0092] **FIG. 17A** also shows how by properly selecting the angle of connector elements **112** relative to side elements **110** for a placement catheter of a particular outside diameter, connector elements **112**, indicated by dashed lines in **FIG. 17A**, will lie generally parallel to the axis of stent graft **122**. This permits connector element **112** to lie closer to catheter **136**, to provide a much smoother wrap when in its con-

tracted, reduced-diameter state, than would result if connector elements were not generally parallel to the axis in such a state. This axial orientation can be contrasted with the off-axis orientation of connectors **112** when in the expanded diameter state of **FIG. 17C**. The smoother outer surface of stent graft **122** enhances the ease of insertion of the stent graft within a hollow body organ, such as blood vessel **182**.

[0093] As discussed above with reference to **FIGS. 11 and 12**, end portions **108, 108A** of sent blanks **104, 104A** are less stiff than main body portion **106, 106A**, as well as having rounded, blunt tips **116, 116A**. **FIG. 21** illustrates a coiled prosthesis **198** in which the main body **200** has an average cross-sectional dimension of x while the enlarged blunt ends **202** have a maximum cross-sectional dimension **204** of $5x$ to $25x$, and more preferably $5x$ to $10x$. In one example main body **200** has a rectangular cross-sectional shape with a minimum width of 0.025 mm (0.001 in) and a maximum width of 1 mm (0.040 in); enlarged blunt end has a thickness of 0.025 mm (0.001 in) and a maximum cross-sectional dimension **204** of 1 cm (0.4 in). This configuration of the ends **202** of prosthesis **198** helps reduce trauma to the patient's tissue by making the ends of the prosthesis less stiff and also by providing a much greater surface area so to reduce the pressure exerted against the tissue, as opposed to what could be exerted by a coiled prosthesis having a constant cross-sectional dimension. The example of **FIG. 21** could be modified so that ends **202**, rather being solid, are made from loops of wire with open centers.

[0094] Modification and variation can be made to the above described inventions without departing from the subject of the inventions as defined in the following claims. For example, connectors **112** could be oriented perpendicular to rail elements **110**, graft material **124** could be placed upon only a portion of the underlying stent or on only one side of the underlying stent. Placement catheter **136** could include fewer or additional telescoping rotatable shafts. The telescoping shafts may not need to be coaxial shafts slidable within or over one another; the telescoping shafts could be, for example, solid and/or tubular elongate members positioned side-by-side. Holders **150** could be constructed differently; for example, if the sequence of releasing the prosthesis is known it may be possible to use a single pull wire instead of three separate pull wires.

[0095] Any and all patents, applications, and printed publications referred to above are incorporated by reference.

What is claimed is:

1. A coiled endoluminal prosthesis comprising:
 - a body comprising a coiled ribbon of material;
 - the body comprising a main body portion and first and second end portions, the main body portion comprising first and second edge elements separated by connector elements, at least substantially all of the elements between the first and second edge elements being said connector elements;
 - the main body portion having a maximum width and the end portions having a maximum width no greater than the maximum width of the main body portion;
 - said body movable between a reduced diameter state, extending along a body axis, and an expanded diameter state; and
 - all said connector elements being at an acute angle to the edge elements when in the expanded diameter state, said angle chosen so that all of said connector elements lie generally parallel to the body axis when in the reduced diameter state so to provide a smoother appearance when in the reduced diameter state.
2. A coiled endoluminal prosthesis according to claim 1 wherein the end portions are substantially less stiff than the main body portion.
3. A coiled endoluminal prosthesis according to claim 1 wherein said end portions each have an inwardly-tapering portion with a blunt tip.
4. A coiled endoluminal prosthesis according to claim 1 wherein the main body portion comprises first, second and third longitudinal sections each having a different radial stiffness.
5. A coiled endoluminal prosthesis according to claim 1 wherein the stiffness of the main body portion continuously varies along at least part of its length.
6. The coiled endoluminal prosthesis according to claim 1 further comprising an orientation-specific marker carried by the body so to aid proper rotary orientation and longitudinal placement of the prosthesis.
7. The coiled endoluminal prosthesis according to claim 1 wherein the end portions comprise generally U-shaped members, said generally U-shaped members being thinner and more flexible than the edge and connector elements of the main body portion.
8. The coiled endoluminal prosthesis according to claim 1 wherein the end portions have a longitudinally-extending length and a laterally-extending width, said length being greater than said width.

* * * * *