

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
1 October 2009 (01.10.2009)

(10) International Publication Number  
WO 2009/120852 A2

(51) International Patent Classification:

A61B 17/58 (2006.01)

CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(21) International Application Number:

PCT/US2009/038376

(22) International Filing Date:

26 March 2009 (26.03.2009)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/039,464 26 March 2008 (26.03.2008) US

(71) Applicant and

(72) Inventor: SEVRAIN, Lionel, C. [US/US]; 1219 Avondale Lane, West Palm Beach, FL 33409 (US).

(74) Agent: SISTRUNK, Melissa, L.; 1301 McKinney Ste 5100, Houston, TX 77010 (US).


(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: UNIVERSAL ANCHOR FOR ATTACHING OBJECTS TO BONE TISSUE



(57) Abstract: An anchoring device and method for attaching an object to a bone comprises an anchoring member having proximal and distal ends, with the proximal end being adapted to hold the object to the bone while the distal end is in the bone, and a locking member having proximal and distal ends, with the proximal end adapted to secure the anchoring member into the bone and oppose its pull-out or loosening by stopping its backing or preventing its unscrewing while the distal end is in the bone. Also provided are first and second fasteners, with the first fastener adapted to fit to the proximal end of the anchoring member, and the second fastener adapted to fit to the proximal end of the locking member. The end of the second fastener can have an angle that matches an angle of the locking member.

## UNIVERSAL ANCHOR FOR ATTACHING OBJECTS TO BONE TISSUE

**[0001]** The present invention claims priority to U.S. Provisional Application Serial No. 61/039,464, filed March 26, 2008, which is incorporated by reference herein in its entirety.

### FIELD OF THE INVENTION

**[0002]** The present invention relates to devices for attaching various objects, such as prostheses or implants, to bones, and in certain cases for anchoring spinal instruments to the vertebrae of the human rachis.

### BACKGROUND OF THE INVENTION

**[0003]** The fast-growing aging population represents an important orthopedic market with a very specific need related to its low-quality cancellous or spongy bone (osteoporosis). Osteosynthesis procedures in such people are jeopardized by the risk of loosening in relation with the pullout or back-out of anchors in the bone. The reliability of an anchoring system depends on its ability to resist pulling out of the bone. Removal of an anchor may lead to extrusion, or even worse, loosening of any object attached to the bone. Known anchoring systems propose several solutions: Divergent or convergent screws have been proposed to oppose to pull out forces by increasing the grip. Locking mechanisms intended to secure the anchor within the object (such as locking screw or anti-reverse systems) avoid the pull out of the anchor but not the extrusion of the entire construct. Bicortical screwing may be dangerous and can make the construct too rigid. This can lead to the breakage of the implant itself. Special features like conical core, self-tapping profile and roughened surfaces of the anchor have been developed to increase the grip to the cancellous bone. Expandable mechanisms (such as threaded peg expanded with a coaxial inner member or "Molly screw") crush and split fragile bone tissue and then creates an empty room around the buried part of the anchor. This can lead the construct to toggle and therefore to a condition for pull out or loosening in response to physiological micro-motions.

**[0004]** U.S. Patent 6,695,844 to Bramlet et al discloses an expandable-winged fastener made up of an outer member and an inner mechanism able to protract or retract wings intended not only to increase the interface between the bone and the device but also to expand within the cancellous bone. Although the wings are blunted, the bone-implant interface is

weakened as the wings expand or retract because the expanded wings broach through the bone as they pivot and therefore require the bone to remodel.

**[0005]** Other solutions use an interlocking mechanism, such as a K-wire which intersect a bone screw (“An Interlocking Screw for Fixation in Osteoporotic Bone” described by McKoy and al. in “internal fixation in osteoporotic bone” authored by Yuehuei H. An in 2002) or two members connected by their ends through a threaded connection (“Anchoring System for Fixing Object to bones” US Patent Application Serial No. 10/275,710 to Lionel Sevrain).

**[0006]** Connecting solutions address some of the problems, and provide increased strength and reliability, but require an aiming system that may represent a hurdle not only from a marketing standpoint but also from an anatomical standpoint. There is therefore a need for an improved anchoring system and installation method for anchoring an object to bone.

**[0007]** It would be desirable to provide a novel anchoring system for securing various objects to bones, such as spinal devices or instrumentations to the rachis, and to provide an anchoring system well adapted to prevent a pull out of the anchor and therefore the extrusion and/or the loosening of the object over time. It would also be desirable to provide an anchoring system to bring the needed reliability in such osteoporotic bone, without the hassle of an additional aiming guide.

## SUMMARY OF THE INVENTION

**[0008]** Therefore, in accordance with a first aspect, there is provided an anchoring device for attaching an object to a bone, comprising an anchoring member having proximal and distal ends, the proximal end being adapted to hold the object to the bone while the distal end is in the bone, and a locking member having proximal and distal ends, with the proximal end adapted to secure the anchoring member into the bone and oppose its pull-out or loosening by stopping its backing or preventing its unscrewing, while the distal end is in the bone.

**[0009]** Also in accordance with another aspect, there is provided first and second fasteners, the first fastener being adapted to fit to the proximal end of the anchoring member, and the second fastener being adapted to fit to the proximal end of the locking member. More specifically, the second fastener is adequately designed to match the angulation of the locking member.

**[0010]** Further in accordance with another aspect, there is provided a method for mounting an object to a bone, comprising the steps of: (a) providing anchoring member and locking member each having proximal and distal ends, (b) introducing the anchoring member in the bone wherein said proximal end holds an object to the bone, (c) positioning the locking member into the proximal end of the anchoring member, and (d) preventing the anchoring member of loosening.

**[0011]** In one embodiment of the invention, there is a system for attaching one or more objects to bone tissue, comprising: an anchoring member having proximal and distal ends, wherein the proximal end comprises a socket and an aperture, wherein the aperture is oblique to the axis of the length of the anchoring member; and a locking member having proximal and distal ends, wherein the proximal end comprises a socket; wherein the aperture of the anchoring member is adapted for insertion of the locking member therethrough. In a specific embodiment, the system further comprises at least one fastener, wherein the fastener is adapted to fit to a socket in the proximal end of the anchoring member, adapted to fit to a socket in the proximal end of the locking member, or both. In one specific embodiment, the system further comprises first and second fasteners, wherein the first fastener is adapted to fit to a socket in the proximal end of the anchoring member and the second fastener is adapted to fit to a socket in the proximal end of the locking member.

**[0012]** In another embodiment of the invention, the angle on the head of the second fastener corresponds to the angulation of the locking member inserted into the anchoring member. In other specific embodiments, the anchoring member, the locking member, or both have a rough surface. In certain aspects, the surface of the inner wall of the aperture is smooth, rough, or threaded. In particular aspects of the invention, the angle between the axis of the length of the anchoring member and the axis of the length of the locking member is between 1 and 89 degrees, between 10 and 75 degrees, between 10 and 50 degrees, between 10 and 35 degrees, or between 25 and 30 degrees.

**[0013]** In a specific embodiment of the invention, the shape of the socket of the anchoring member and/or the shape of the socket of the locking member is hexagonal, pentagonal, square, triangular, cross-shaped, plus sign-shaped, linear, or star-shaped. In a particular aspects of the invention, the second fastener is a ball end hexagonal fastener.

**[0014]** In one embodiment of the invention, there is a method of affixing one or more objects to bone, comprising the step of anchoring the object to the bone using the system(s) or composition(s) of the invention. In another embodiment of the invention, there is a kit comprising the system(s) or composition(s) of the invention.

**[0015]** The foregoing has outlined rather broadly the features and technical advantages of the present invention in order that the detailed description of the invention that follows may be better understood. Additional features and advantages of the invention will be described hereinafter which form the subject of the claims of the invention. It should be appreciated by those skilled in the art that the conception and specific embodiment disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present invention. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the invention as set forth in the appended claims. The novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present invention.

#### **BRIEF DESCRIPTION OF THE DRAWINGS**

**[0016]** Having thus generally described the nature of the invention, reference will now be made to the accompanying drawings, showing by way of illustration a particular embodiment thereof.

**[0017]** Fig. 1 is a schematic perspective view of an anchoring member in accordance with the present invention.

**[0018]** Fig. 2a is a schematic cross-sectional plan view of an anchoring member.

**[0019]** Fig. 2b is a top plan schematic view of the proximal end of the anchoring member.

**[0020]** Fig. 3 is a schematic perspective view of an anchoring member with the locking member.

**[0021]** Fig. 4 is a schematic cross-sectional plan view of an anchoring member with the locking member

**[0022]** Fig. 5 is a perspective view of an anchoring member holding an object (plate).

**[0023]** Fig. 6a is a cross-sectional view of the shaft (Hex Key) of one embodiment of the first fastener F1.

**[0024]** Fig. 6b is a schematic perspective view of the distal end (ball end hex tool) of the first fastener F1.

**[0025]** Fig. 6c is a lateral view of the first fastener F1.

**[0026]** Fig. 7 is a schematic perspective view of a differential that can be used for the second fastener F2.

**[0027]** Fig. 8a is an enlarged perspective view of the distal end (ball end hex tool) of the first fastener F1.

**[0028]** Fig. 8b is an enlarged lateral view of the distal end (ball end hex tool) showing a 25 to 30 degree angle entry to the hex tool.

**[0029]** Fig. 8c is an example of oblique insertion.

**[0030]** Fig. 8d is a lateral view of the first fastener F1 engaged within a hex screw.

**[0031]** Fig. 9a is a lateral view of a cortical-type locking member L.

**[0032]** Fig. 9b is a lateral view of a cancellous-type locking member L.

**[0033]** Fig. 9c is a lateral view of a headless-type locking member L.

**[0034]** Fig. 10 illustrates various angulation patterns of the interlocking anchor and locking members.

**[0035]** Fig. 11 illustrates one embodiment of a locking member within an anchoring member, in addition to the respective fastener having a corresponding angulation to the angulation of the locking member within the anchoring member.

**[0036]** Fig. 12 illustrates an exemplary embodiment of a fastener and its corresponding locking member within the anchoring member.

**[0037]** From the foregoing disclosure and the following more detailed description of various particular embodiments it will be apparent to those skilled in the art that the present invention provides a significant advance in the art of bone anchoring devices. Additional features and advantages of various particular embodiments will be better understood in view of the detailed description provided below.

## **DETAILED DESCRIPTION OF THE INVENTION**

**[0038]** The present invention incorporates by reference herein in its entirety U.S. Provisional Patent Application Serial No. 60/896,960, filed March 26, 2007.

**[0039]** The term "a" or "an" as used herein in the specification may mean one or more. As used herein in the claim(s), when used in conjunction with the word "comprising", the words "a" or "an" may mean one or more than one. As used herein "another" may mean at least a second or more. Some embodiments of the invention may consist of or consist essentially of one or more elements, method steps, methods and/or systems of the invention. It is contemplated that any system, method, or composition described herein can be implemented with respect to any other method or composition described herein.

### **I. The Present Invention**

**[0040]** It will be apparent to those skilled in the art, that is, to those who have knowledge or experience in this area of technology, that many variations are possible for the system for anchoring bone disclosed herein. The following detailed discussion of various and particular features and embodiments will illustrate the general principles of the invention with reference to an improved bone anchoring device for use in mammalian bone, including vertebrae, for example. Other embodiments suitable for other applications will be apparent to those skilled in the art given the benefit of this disclosure.

**[0041]** Any mammalian bone, including human bone, may have the inventive systems, methods, and/or compositions of the present invention applied thereto. Examples include long, short, flat, irregular, accessory, and sesamoid bones. Particular examples include but are not limited to vertebrae, femur, humerus, radius, ulna, femur, tibia, fibula, clavicle, rib, metacarpals, metatarsals, phalanges, skull bones, sternum, scapulae, innominate, vertebrae, maxillae, sphenoid, carpus, tarsus, patella, interfrontal bone, epipteris bone, coronal ossicle, bregmatic ossicle, sagittal ossicle, lambdoid ossicle, and squame-parietal ossicle.

**[0042]** The materials of the components of the present invention may be of any suitable kind. Materials of the anchor and locking member are biocompatible, in certain embodiments. Examples of materials include biomedical metallic materials, including stainless steel; alloys (Al, Co, Ni, Ta, W, V, *etc.*); cobalt-based alloys; or titanium and its alloys. Other examples of materials include polymeric biomaterials, such as synthetic non-biodegradable polymers: polyethylene (high density polyethylene –HDPE-, ultrahigh molecular weight polyethylene –UHMWPE-), poly (ether ether ketone) or PEEK. Polymer matrix composite biomaterials may be employed and include fiber-reinforced composites (for example, carbon fiber or kevlar).

**[0043]** The shape, diameter, length, and any associated angles of the anchor, locking member, and, by extrapolation, fastener(s) of the invention maybe of any kind, so long as the locking member is able to be positioned within the anchor at an angle to generate a V-shaped (or L-shaped, in a 90 degree configuration) configuration and so long as the corresponding fastener(s) can be inserted in the respective socket **104** in the head of anchor and/or locking member to apply torque for affixing them into bone.

**[0044]** Referring now to Figs. 1 to 9, in accordance with an illustrative embodiment of the present invention, an anchoring device or implant, generally referred to using the numeral **100**, will now be described. The anchoring system **100** is generally comprised of an anchoring member A and a locking member L (see Fig. 3)


**[0045]** Fig. 1 illustrates an anchoring member A in accordance with a certain embodiment. The anchoring member A generally has cancelous screws' features such as a 2-portion shaft comprising an optionally coarse, self-tapping thread **103**, designed to anchor in the softer medullary or cancelous bone, and topped by a smooth unthreaded portion **101** that allows

it to act as a lag screw. The unthreaded upper portion **101** presents an oblique aperture **102** having an angle (for example, of about 25°) with respect to an axial plane of the anchoring member's shaft. The proximal end of the anchoring member A has a proximal end socket **104** such that it can be engaged by a fastener like a key, screwdriver, or wrench (see Fig. 2b). In specific embodiments, the proximal end of the anchoring member A has a Hex (hexagonal) type's proximal end socket **104** such that it can be engaged by a Hex tip fastener like a key or wrench (see Fig. 2b).

**[0046]** The term "fastener" as used herein refers to a tool, such as a wrench, key, or screwdriver, that is employed to insert the corresponding anchor in the bone *via* the head of the anchor and/or to insert the corresponding locking member in the anchor *via* the socket **104** of the head of the locking member.

**[0047]** Although the socket **104** of the head of the anchor or locking member may be of any shape, the embodiment presented herein wherein both heads are hexagonal is merely illustrative. That is, the shape of the socket **104** for insertion of the respective fastener in the anchor or locking member may be of any shape, including hexagonal, pentagonal, square, triangular, cross-shaped, plus sign-shaped, linear, star-shaped, and so forth, for example. In a specific embodiment, the head of the locking member is smaller than the head of the anchor, although in other embodiments the head of the locking member is the same size as the head of the anchor. In another specific embodiment, the socket **104** of the proximal end of the anchor and the socket **104** of the proximal end of the locking member are identical in shape and/or size, whereas in other specific embodiments the socket **104** of the proximal end of the anchor and the socket **104** of the proximal end of the locking member are not identical in shape and/or size.

**[0048]** Fig. 2 shows a cross-sectional view of the anchoring member (Fig. 2a) and a top plan of the proximal end of the anchoring member (Fig. 2b). The shape of the socket **104** for insertion of the respective fastener in the anchor or locking member may be of any shape, including hexagonal, pentagonal, square, triangular, cross-shaped, plus sign-shaped, linear, star-shaped, and so forth, for example (see below); these may be referred to as slotted, Phillips, Pozidriv, torx, Hex key, Robertson, Tri-Wing, Torq-Set, or Spanner, for example.



[0050] However, an exemplary hexagonal (Hex) socket in the head (104) of the anchoring member brings the following advantage: a ball end hex key (or wrench) can be used for angulated screwing and insertion, the contact surfaces of the screw are protected from external damage, the tool can be used with a headless screw, there are six contact surfaces between screw and driver, the socket's depth are less prone to stripping, and this room can be used for cannulation, for example.

[0051] Fig. 3 illustrates the anchoring system 100 comprising the anchoring member A and the locking member L. The angle  $\alpha$  between the two members is fixed and set up at 25 degrees in a certain embodiment. This angle allows using a standard hex second fastener F2 (wherein F1 fastener refers to the fastener for the anchor and F2 fastener refers to the fastener for the locking member) equipped with an end ball hex end since it can be used with an angulation up to 30 degrees. In other embodiments, the angle can be set up to another value comprised between 1 to 90 degrees. In a specific embodiment, the angle can be 15-25 degrees. Beyond 30 degrees angulation, another embodiment of the second fastener F2 with an inclinable hex tip end may be used (differential inner mechanism).

[0052] Fig. 4 is a schematic cross-sectional plan view of the anchoring system 100. In this representation, a headless locking member L is engaged into a oblique aperture (111) within the exemplary hex-shaped socket (104) of the head of the anchoring member A. The surface of the inner wall of the aperture may be threaded, smooth, or rough. One end of the aperture is at the proximal head of the anchor, and the opposite end is on one side of the anchor.

[0053] Fig. 5 is a perspective view of an anchoring member holding an exemplary object (plate) P.

**[0054]** Fig. 6 illustrates the first fastener F1 with its Hex type tip (112). In this representation, the fastener comprises a head or tip that engages with the socket of the anchor to apply torque by rotating the tip, such as but not limited to a screwdriver, key or wrench. The tip is not limited to hex type. The second fastener F2 in certain aspects comprises a ball end hex type end to allow screwing of the locking member. The second fastener F2 can have the same features as the first fastener F1 when used in a particular embodiment *e.g.* with an angle  $\alpha$  between the two members equal at 25 degrees, or inferior at 30 degrees at the maximum, in accordance with the working angle (25 to 30 degrees) of such ball end hex tip. In this case, only the size differs from the first fastener F1, the second fastener F2 being thinner than the first fastener F1 in order to be able to slide within the inner socket 104 of the first fastener F1, in particular embodiments.

**[0055]** In another embodiment an angle  $\beta$ , higher than the angle  $\alpha$ , *e.g.* superior at 30 degrees between the two members A and L, is set up. In this embodiment, the second fastener F2 presents an inclinable tip able to match the angle  $\beta$  and is equipped with an inner mechanism applying the torque in accordance with an oblique transmission of the rotating motion imparted to the handle of the fastener. Such mechanism can be but is not limited to a differential, a screw gear, or a set of gears. Fig. 7 illustrates the principle of such mechanism and shows a schematic conceptual view of a differential. Such a fastener can be rotated manually or by an electric or other motor.

**[0056]** Whatever the mechanism can be, it is intended to allow an oblique screwing while the handle of the fastener remains straight forward, in certain embodiments. Such a feature is useful when the local anatomical requirements forbid the tool to be tilted. For example, when a surgery using a minimally invasive approach through a small incision is performed, the instruments must go through this small cutaneous aperture, and therefore can not be angulated in order to avoid damaging soft tissue.

**[0057]** Fig. 8a is an enlarged perspective view of the distal end (ball end hex tool) of the fastener. The concept by which ball ends slide into a screw head is known as funnel insertion. Basically, it means that the sides of the ball end direct (funnel) it into place. This allows fast funnel entry, eliminates wasted time even in blind applications, and the full depth engagement reduces "stripping" problems.

**[0058]** Fig. 8b is an enlarged lateral view of the distal end (ball end hex tool) showing a 25 to 30 degree angle entry to hex. As maximum allowable angle increases, neck size decreases, and strength also decreases. By contrast, increasing the strength of a ball-end tool requires a corresponding increase in neck size and decrease in maximum allowable angle. Designing the perfect ball-end tool means choosing the ideal balance between strength and allowable angle. Fig. 8c is an example of oblique insertion. Fig. 8d is a lateral view of the first fastener F1 engaged within a hex screw.

**[0059]** Fig. 9 illustrates the three possible designs of the locking member L. In certain embodiments, the locking member L is thinner than the anchoring member A so that it can be slid through the oblique aperture and positioned within the empty room of the hexagonal socket of the anchoring member. Its length can be smaller, equal or bigger than the anchoring member. Its proximal end can be equipped with a head (105) or be wide-mouthed (106) to block within the anchoring member's head, or be headless (107). Whatever the type of the locking member L can be (headed 105, wide-mouthed 106 or headless 107), the socket has a hex type shape, in certain embodiments. The locking member can be a cortical type screw (Fig. 9a) with a fine thread (108) all along its shaft and therefore screwed into an oblique threaded canal within the anchoring member's head, or a cancelous type screw (Fig. 9b) with a coarser thread (109), designed to anchor the bone and a smooth, unthreaded portion (110), designed to slid within an oblique unthreaded canal within the anchoring member's head. Depending of its type, the locking member L can just act as an anti-rotational device and prevent the unscrewing of the anchoring member A in the cortical type design, or be both a blocking system as described above and an additional fastening device intended to secure and reinforce the grip within the medullary bone in the cancelous type design. Moreover, due to its divergent positioning, it brings to the construct a V-shaped design which opposes to pull-out forces. Whatever cancelous or cortical type design be used, the adjunction of a second divergent member (locking member L) advantageously increases both the grip and the purchase within the bone, especially in cancelous and/or osteoporotic bone and therefore opposes to pull-out and secures the fixation of any object to the bone.

**[0060]** Fig. 10 illustrates various angulation patterns of the interlocking anchor and locking members. Upon certain angulations of the locking member within the anchoring member, and therefore, certain angulations required for the corresponding fastener to screw the

locking member, the proximal end of the anchoring member requires a cavity at its socket to allow the fastener access to the locking member.

**[0061]** Fig. 11 illustrates one embodiment of a locking member within an anchoring member, in addition to the respective fastener having a corresponding angulation to the angulation of the locking member within the anchoring member. In this specific embodiment, the proximal end of the anchoring member has a cavity that allows insertion of the fastener for the locking member.

**[0062]** Fig. 12 illustrates an exemplary embodiment of a fastener and its corresponding locking member within the anchoring member. The proximal end of the anchoring member comprises a cavity that allows insertion of the fastener for the locking member.

**[0063]** In certain embodiments, the anchor and locking member are coated with antibiotic or other medicine useful upon implantation of an implant on and/or in a bone. In other embodiments, the surface of the anchor and/or locking member is rough for a better grip within the bone.

**[0064]** Any of the compositions described herein may be comprised in a kit. Where there are more than one components in the kit, the kit also may contain a second, third or other additional container into which the additional components may be separately placed. The kits of the present invention may include a means for containing the invention component(s) in close confinement for commercial sale. Such containers may include injection or blow molded plastic containers into which the components are retained, for example.

**[0065]** The kit may comprise the anchor, locking member, and/or fastener(s). In some cases, all components are sold separate, whereas in other cases all or a subset of components are sold together. Irrespective of the number and/or type of containers, the kits of the invention may also comprise, and/or be packaged with, an instrument other than a fastener(s) of the invention for assisting with placing the anchor/locking member within the body of an animal.

**[0066]** In particular embodiments of the invention, a variety of anchors, locking members, and/or fasteners may be provided in a kit. For example, a variety of lengths,

diameters, socket shapes, and/or angles of the corresponding anchors, locking members, and/or fastener(s) may be provided in a kit.

**[0067]** From the foregoing disclosure and detailed description of certain embodiments, it will be apparent that various modifications, additions and other alternative embodiments are possible without departing from the true scope and spirit of the invention. The embodiments discussed were chosen and described to provide the best illustration of the principles of the invention and its practical application to thereby enable one of ordinary skill in the art to use the invention in various embodiments and with various modifications as are suited to the particular use contemplated. All such modifications and variations are within the scope of the invention as determined by the appended claims when interpreted in accordance with the breadth to which they are fairly, legally, and equitably entitled.

## CLAIMS

What is claimed is:

1. A system for attaching one or more objects to bone tissue, comprising:
  - an anchoring member having proximal and distal ends, wherein the proximal end comprises a socket and an aperture, wherein the aperture is oblique to the axis of the length of the anchoring member; and
  - a locking member having proximal and distal ends, wherein the proximal end comprises a socket;
  - wherein the aperture of the anchoring member is adapted for insertion of the locking member therethrough.
2. The system of claim 1, further comprising at least one fastener, wherein the fastener is adapted to fit to a socket in the proximal end of the anchoring member, adapted to fit to a socket in the proximal end of the locking member, or both.
3. The system of claim 1, further comprising first and second fasteners, wherein the first fastener is adapted to fit to a socket in the proximal end of the anchoring member and the second fastener is adapted to fit to a socket in the proximal end of the locking member.
4. The system of claim 3, wherein the angle on the head of the second fastener corresponds to the angulation of the locking member inserted into the anchoring member.

5. The system of claim 1, wherein the anchoring member, the locking member, or both have a rough surface.
6. The system of claim 1, wherein the surface of the inner wall of the aperture is smooth, rough, or threaded.
7. The system of claim 2, wherein the angle between the axis of the length of the anchoring member and the axis of the length of the locking member is between 1 and 89 degrees.
8. The system of claim 2, wherein the angle between the axis of the length of the anchoring member and the axis of the length of the locking member is between 10 and 75 degrees.
9. The system of claim 2, wherein the angle between the axis of the length of the anchoring member and the axis of the length of the locking member is between 10 and 50 degrees.
10. The system of claim 2, wherein the angle between the axis of the length of the anchoring member and the axis of the length of the locking member is between 10 and 35 degrees.
11. The system of claim 2, wherein the angle between the axis of the length of the anchoring member and the axis of the length of the locking member is between 25 and 30 degrees.
12. The system of claim 1, wherein the shape of the socket of the anchoring member and/or the shape of the socket of the locking member is hexagonal, pentagonal, square, triangular, cross-shaped, plus sign-shaped, linear, or star-shaped.
13. The system of claim 3, wherein the second fastener is a ball end hexagonal fastener.

14. A method of affixing one or more objects to bone, comprising the step of anchoring the object to the bone using the system of claim 1.
15. A kit comprising the system of claim 1.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3







FIG. 4



4/10








FIG. 8A




FIG. 8B




FIG. 8C




FIG. 8D




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A




FIG. 10B






FIG. 10C



*FIG. 11*



*FIG. 12*