

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
20 April 2006 (20.04.2006)

PCT

(10) International Publication Number
WO 2006/042084 A2

(51) International Patent Classification:
A61B 17/10 (2006.01)

(21) International Application Number:
PCT/US2005/036100

(22) International Filing Date: 7 October 2005 (07.10.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/617,104 8 October 2004 (08.10.2004) US
60/617,016 8 October 2004 (08.10.2004) US

(71) Applicant (for all designated States except US): **TYCO HEALTHCARE GROUP, LP** [US/US]; 195 McDermott Road, North Haven, CT 06473 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **WHITFIELD, Kenneth, H.** [US/US]; 335 Norton Street, New Haven, CT 06511 (US). **SORRENTINO, Greg** [US/US]; 50 Fairlawn Drive, Wallingford, CT 06492 (US).

(74) Agent: **TYCO HEALTHCARE GROUP LP**; 195 McDermott Road, North Haven, CT 06473 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ENDOSCOPIC SURGICAL CLIP APPLIER

(57) Abstract: An apparatus for application of surgical clips to body tissue has a handle portion and a body extending distally from the handle portion and defining a longitudinal axis. The apparatus also has a plurality of surgical clips disposed within the body, and a jaw assembly mounted adjacent a distal end portion of the body. The jaw assembly includes first and second jaw portions movable between a spaced-apart and an approximated position. The apparatus also has a wedge plate longitudinally movable between the first and the second jaw portions, and a clip pusher configured to individually distally advance a surgical clip to the jaw assembly while the jaw portions are in the spaced apart position. The apparatus still further has an actuator at least partially disposed within the body and longitudinally movable in response to actuation of the handle portion and a jaw closure member positioned adjacent the first and second jaw portions to move the jaw portions to the approximated position.

WO 2006/042084 A2

ENDOSCOPIC SURGICAL CLIP APPLIER**CROSS REFERENCE TO RELATED PATENT APPLICATIONS**

The instant patent application claims priority to United States Provisional Patent
5 Application Serial No.: 60/617,104 filed on October 8, 2004 and United States Provisional Patent
Application Serial No.: 60/617,016 filed on October 8, 2004 which are both herein incorporated
by reference in its entirety.

TECHNICAL FIELD:

10 The technical field relates to surgical clip appliers. More particularly, the present
disclosure relates to an endoscopic surgical clip applier having a mechanism for stabilizing the
jaw structure during the insertion of a surgical clip.

DESCRIPTION OF THE RELATED ART

15 Endoscopic staplers and clip appliers are known in the art and are used for a number of
distinct and useful surgical procedures. In the case of a laparoscopic surgical procedure, access
to the interior of an abdomen is achieved through narrow tubes or cannulas inserted through a
small entrance incision in the skin. Minimally invasive procedures performed elsewhere in the
body are often generally referred to as endoscopic procedures. Typically, a tube or cannula
20 device is extended into the patient's body through the entrance incision to provide an access port.
The port allows the surgeon to insert a number of different surgical instruments therethrough
using a trocar and for performing surgical procedures far removed from the incision.

During a majority of these procedures, the surgeon must often terminate the flow of blood or another fluid through one or more vessels. The surgeon will often apply a surgical clip to a blood vessel or another duct to prevent the flow of body fluids therethrough during the procedure. An endoscopic clip applier is known in the art for applying a single clip during an entry to the body cavity. Such single clip appliers are typically fabricated from a biocompatible material and are usually compressed over a vessel. Once applied to the vessel, the compressed clip terminates the flow of fluid therethrough.

Endoscopic clip appliers that are able to apply multiple clips in endoscopic or laparoscopic procedures during a single entry into the body cavity are described in commonly- assigned U.S. Pat. Nos. 5,084,057 and 5,100,420 to Green et al., which are both incorporated by reference in their entirety. Another multiple endoscopic clip applier is disclosed in commonly- assigned U.S. Pat. No. 5,607,436 by Pratt et al., the contents of which is also hereby incorporated by reference herein in its entirety. These devices are typically, though not necessarily, used during a single surgical procedure. U.S. patent application Ser. No. 08/515,341 now U.S. Pat. No. 5,695, 502 to Pier et al., the disclosure of which is hereby incorporated by reference herein, discloses a resterilizable surgical clip applier. The clip applier advances and forms multiple clips during a single insertion into the body cavity. This resterilizable clip applier is configured to receive and cooperate with an interchangeable clip magazine so as to advance and form multiple clips during a single entry into a body cavity. One significant design goal is that the surgical clip be loaded between the jaws without any compression of the clip from the loading procedure. Such bending or torque of the clip during loading often has a number of unintended consequences. Such compression during loading may alter slightly the alignment of the clip between the jaws. This will cause the surgeon to remove the clip from between the jaws for

discarding the clip. Additionally such preloading compression may slight compress parts of the clip and change a geometry of the clip. This will cause the surgeon to remove the compressed clip from between the jaws for discarding the clip.

Endoscopic or laparoscopic procedures are often performed remotely from the incision. Consequently, application of clips may be complicated by a reduced field of view or reduced tactile feedback for the user at the proximal end of the device. It is therefore desirable to improve the operation of the instrument by providing indication to the user of a firing of an individual clip, the depletion of the clips contained in the loading unit, or any other surgical event. It is also desirable to provide a surgical clip applier that promotes a successful loading of the clip and that wedges the jaws of the surgical clip applier open, then loads the clip between the jaws in order to prevent any damage or excessive compression of the clip and prevents compression of the jaws on the clip before firing.

SUMMARY

According to a first aspect of the present disclosure, there is provided an apparatus for application of surgical clips to body tissue has a handle portion and a body extending distally from the handle portion and defining a longitudinal axis. The apparatus also has a plurality of surgical clips disposed within the body, and a jaw assembly mounted adjacent a distal end portion of the body. The jaw assembly includes first and second jaw portions movable between a spaced-apart and an approximated position. The apparatus also has a wedge plate longitudinally movable between the first and the second jaw portions, and a clip pusher configured to individually distally advance a surgical clip to the jaw assembly while the jaw portions are in the spaced apart position. The apparatus still further has an actuator at least

partially disposed within the body and longitudinally movable in response to actuation of the handle portion and a jaw closure member positioned adjacent the first and second jaw portions to move the jaw portions to the approximated position.

According to another aspect of the present disclosure, the apparatus has a wedge plate
5 that biases the first and the second jaw portions when the wedge plate is longitudinally moved between the first and the second jaw portions. The wedge plate maintains the first and the second jaw portions in a fixed predetermined relationship during loading of the clip. The fixed predetermined relationship prevents flexing of the first and the second jaw members during clip loading.

10 According to another aspect of the present disclosure, the apparatus has the wedge plate with a rounded distal tip.

According to another aspect of the present disclosure, the apparatus has the wedge plate with a first proximal window. The first proximal window is adapted to be engaged by a member disposed in the body and configured to hold the wedge plate in a distal most position. The distal
15 most position is between the first and the second jaw members.

According to another aspect of the present disclosure, the apparatus has the wedge plate with a second proximal window. The second proximal window is adapted to be engaged by the member and the second proximal window is configured to hold the wedge plate in a proximal most position. The proximal most position is retracted from the first and the second jaw
20 members. The proximal most position of the wedge plate is configured to allow the first and the second jaw members to compress the clip.

According to another aspect of the present disclosure, the apparatus has the member is movable from the second proximal window to first second proximal window by the actuator. The actuator moves the wedge plate distally. The member moves from the second proximal window to the first proximal window upon the wedge plate moving distally.

5 According to another aspect of the present disclosure, the actuator further comprises a cam link. The cam link is engageable with a cam slot in the wedge plate. The cam link moves the wedge plate distally.

 According to another aspect of the present disclosure, the member is a flexible leg.

 According to another aspect of the present disclosure, the apparatus has a cam slot with a
10 driving edge. The cam link engages the driving edge. The cam link is configured to longitudinally move the wedge plate distally.

 According to another aspect of the present disclosure, when the actuator is driven distally the cam link is driven distally. The cam link engages the driving edge of the cam slot. The cam link longitudinally moves the wedge plate to move the rounded distal end between the first and
15 the second jaw members. The member engages the first proximal window to hold the wedge plate between the first and second jaws for loading.

 According to another aspect of the present disclosure, when the cam link is driven further distally the cam link disengages the driving edge and traverses in the cam slot. The cam link permits the wedge plate to move the rounded distal end proximally from between the first and
20 the second jaw members. The member engages the second proximal window to hold the wedge plate in the proximal most position.

According to another aspect of the present disclosure, there is provided an apparatus for the application of surgical clips to body tissue. The apparatus has a handle portion, a body extending distally from the handle portion and defining a longitudinal axis, and a plurality of surgical clips disposed within the body. The apparatus also has a jaw assembly mounted adjacent a distal end portion of the body, and a clip pusher configured to individually distally advance a surgical clip to the jaw assembly. The apparatus further includes an actuator at least partially disposed within the body and longitudinally movable in response to actuation of the handle portion with a counter mechanism. The counter mechanism is associated with the handle portion and the counter mechanism indexes in response to actuation of the handle portion.

10 According to another aspect of the present disclosure, the counter mechanism comprises a liquid crystal display.

According to yet another aspect of the present disclosure, the counter mechanism comprises a backlight.

15 According to another aspect of the present disclosure, the counter mechanism is indexed upon full actuation of the handle portion.

According to another aspect of the present disclosure, the apparatus has a counter mechanism that is triggered by the actuator.

20 According to another aspect of the present disclosure, the counter mechanism is in the handle and connected to the actuator. The counter mechanism has a member connected to the actuator. The counter mechanism has a liquid crystal display having a display contact. The display contact is activated when the member contacts the display contact.

According to another aspect of the present disclosure, the member is rotatable. The member rotates in response to longitudinal movement of the actuator to contact the display contact.

5 According to another aspect of the present disclosure, the counter mechanism is a liquid crystal display having a lens. The liquid crystal display displays an image. The lens magnifies the image.

According to another aspect of the present disclosure, the actuator includes an opening. The counter mechanism with the member has a first arm and a second arm. The first arm is connected to the opening. When said actuator longitudinally moves in a distal direction the
10 actuator deflects the first arm and the member rotates in response to the movement. The second arm contacts the display contact in response to the rotation of the member. The display contact is activated when the second arm contacts the display contact.

According to another aspect of the present disclosure, there is provided an apparatus for the application of surgical clips to body tissue. The apparatus has a handle portion, a body
15 extending distally from the handle portion and defining a longitudinal axis, a plurality of surgical clips disposed within the body and a jaw assembly mounted adjacent a distal end portion of the body. The jaw assembly includes first and second jaw portions movable between a spaced-apart and an approximated position. The apparatus also has a clip pusher configured to individually distally advance a surgical clip to the jaw assembly while the jaw portions are in the spaced apart
20 position and an actuator at least partially disposed within the body and longitudinally movable in response to actuation of the handle portion. The apparatus also has a jaw closure member positioned adjacent the first and second jaw portions to move the jaw portions to the approximated position and a lockout mechanism configured to engage with the clip pusher to

prevent the application of the surgical clips to tissue when the plurality of clips are substantially exhausted.

According to another aspect of the present disclosure, the lockout mechanism has a member. The member is longitudinally movable with the actuator to a distal most position. The member reaches said distal most position and the member engages the clip pusher. The member prevents the clip pusher to distally advance the surgical clip to the jaw assembly.

According to another aspect of the present disclosure, the apparatus further comprises a clip follower. The clip follower distally biases the clips disposed in the body. The lockout mechanism includes a member. The member is longitudinally movable with the actuator to a distal most position. The member reaches the distal most position and the member engages the follower. The member prevents the follower from retracting proximally. Upon retraction of the clip pusher, the clip pusher engages the follower. The member prevents the clip pusher to distally advance the surgical clip to the jaw assembly.

According to another aspect of the present disclosure, the member is a lockout wedge.

According to another aspect of the present disclosure, the member has at least one member angled surface. The actuator has at least one actuator angled surface. As the actuator retracts proximally the at least one actuator angled surface engages the member angled surface. The engagement prevents the actuator from retracting proximal to a proximal most position.

According to another aspect of the present disclosure, there is provided an apparatus for the application of surgical clips to body tissue. The apparatus has a handle portion, and a body extending distally from the handle portion and defining a longitudinal axis. The apparatus also has a plurality of surgical clips disposed within the body, and a jaw assembly mounted adjacent a distal end portion of the body. The jaw assembly includes first and second jaw portions movable

between a spaced-apart and an approximated position. The apparatus also has a clip pusher configured to individually distally advance a surgical clip to the jaw assembly while the jaw portions are in the spaced apart position. The apparatus further has an actuator at least partially disposed within the body and longitudinally movable in response to actuation of the handle portion. The apparatus also has a jaw closure member positioned adjacent the first and second jaw portions to move the jaw portions to the approximated position, and a rack having a plurality of ratchet teeth being connected to the actuator. The apparatus also has a pawl with at least one tooth configured to engage the ratchet teeth. The pawl is biased in the handle portion. As the actuator is moved longitudinally, the ratchet teeth are passed over the pawl. The pawl is configured to prevent an inadvertent return of the actuator before full actuation of the apparatus. The apparatus also has a wedge plate longitudinally movable between the first and the second jaw portions.

According to another aspect of the present disclosure, the pawl is biased by a pawl spring. The pawl spring biases the pawl into engagement with the rack.

According to another aspect of the present disclosure, the apparatus further comprises a first and a second post connected to an interior side of the handle portion. The first and the second posts are configured to support the pawl spring.

According to another aspect of the present disclosure, there is provided an apparatus for the application of surgical clips to body tissue. The apparatus also has a handle portion, a body extending distally from the handle portion and defining a longitudinal axis, a plurality of surgical clips disposed within the body, and a jaw assembly mounted adjacent a distal end portion of the body. The jaw assembly includes first and second jaw portions movable between a spaced-apart and an approximated position. The apparatus also has a clip pusher configured to individually

distally advance a surgical clip to the jaw assembly while the jaw portions are in the spaced apart position, and an actuator at least partially disposed within the body and longitudinally movable in response to actuation of the handle portion. The apparatus further has a jaw closure member positioned adjacent the first and second jaw portions to move the jaw portions to the

5 approximated position. The body portion has an outer diameter. The jaw assembly has a width in the spaced apart position. The width is less than or equal to said outer diameter of the body.

According to another aspect of the present disclosure, the apparatus has the body with a length. The length is suitable to facilitate use in bariatric surgery. According to another aspect of the present disclosure, the apparatus with the length suitable to facilitate use in bariatric

10 surgery has the length being greater than thirty centimeters.

BRIEF DESCRIPTION OF THE DRAWINGS:

A particular embodiment of a surgical clip applier is disclosed herein with reference to the drawings wherein;

15 FIG. 1 is a perspective view of a surgical clip applier;

FIG. 2 is another perspective view of the surgical clip applier of FIG 1;

FIG. 3 is an enlarged perspective view of the jaw structure of the surgical clip applier;

FIG. 4 is a top view of the surgical clip applier;

FIG. 5 is a side view of the surgical clip applier;

20 FIG. 6 is a side view, with half of the body removed, of the handle assembly of the surgical clip applier;

FIG. 6A and 6B are perspective views, with half of the body removed, of the handle assembly of the surgical clip applier;

FIG. 6C is a side view, with half of the body removed, of the handle assembly of the surgical clip applier;

FIG. 6D is a perspective view, taken from the opposite side, of the handle assembly of the surgical clip applier with half the body removed;

5 FIG. 7 is an exploded perspective view of the handle of the clip applier, with shaft assembly;

FIG. 7A is a perspective view of a drive link and spindle connection;

FIG. 7B is a cross sectional view of the knob, bushing and retention pins;

FIG. 7C is a perspective view of the knob;

10 FIG. 7D is a perspective view of the proximal end of the outer tube;

FIG. 7E is a perspective view of the proximal end of the outer tube assembled with the bushing;

FIG. 8 is a perspective view of a pawl;

FIG. 9 is a perspective view of a rack;

15 FIG. 9A is another perspective view of the rack;

FIGS. 9B and 9C are opposite perspective views of an actuator plate;

FIG. 9D and 9E are opposite perspective views of a toggle arm;

FIG. 9F and 9G are opposite perspective views of a wishbone link;

FIG. 10 is an exploded perspective view of the shaft assembly of the surgical clip applier;

20 FIG. 10A is a perspective view of a feed bar;

FIG. 10B is a perspective view of a follower and surgical clips;

FIG. 10C and 10D are opposite perspective views of a trip block;

FIG. 10E is a perspective view of a spindle;

FIG. 10F is an enlarged area of detail of FIG. 10E;

FIG. 10G is an enlarged area of detail of FIG. 10E;

FIG. 10H is a perspective view of a follower illustrating an abutment surface on the underside of the follower;

5 FIG. 11 is a perspective view of the distal end of the spindle and a driver;

FIG. 12 is a perspective view of a trip lever mechanism on the spindle and lock out wedge;

FIG. 13 is a perspective view of a wedge plate and biasing spring;

FIGS. 14 and 15 are opposite perspective views of a filler component;

10 FIG. 16 is a perspective view of the rotation knob and shaft assembly;

FIG. 17 is a perspective view of the overpressure assembly;

FIG. 18 is a perspective view of the spindle and jaw assembly;

FIG. 19 is an enlarged area of detail of the spindle and jaw assembly of FIG. 18;

FIG. 20 is an enlarged area of detail of the spindle and trip lever of FIG. 18;

15 FIG. 21 is an enlarged view of the distal end of the surgical clip applier with outer tube removed;

FIG. 22 is a perspective view of the surgical clip applier shaft assembly with parts removed;

FIG. 23 is an enlarged area at detail of FIG. 22;

20 FIG. 24 is an enlarged area of detail of FIG. 22;

FIG. 25 is an enlarged area of detail of FIG. 22;

FIG. 26 is a perspective view of the spindle, driver and jaw assembly;

FIG. 27 is an enlarged area of detail of FIG. 26;

FIG. 28 is a perspective view of the cam link and wedge plate assembly;

FIG. 29 is an enlarged area of detail of FIG. 28;

FIG. 30 is an enlarged area of detail of FIG. 29;

FIG. 31 is a perspective view of the filler component and jaw assembly;

5 FIG. 32 is an enlarged perspective view of the jaw assembly of FIG. 31;

FIGS. 33 and 34 are perspective views of the distal end of the spindle including wedge plate and driver;

FIG. 35 is a side view, partially shown in section, of the surgical clip applier in a pre-fired condition;

10 FIG. 36 is in enlarged area of detail of FIG. 35;

FIG. 37 is an enlarged area of detail of FIG. 35;

FIG. 38 is in enlarged area of detail of FIG. 37 showing the trip lever;

FIG. 39 is an enlarged area of detail of FIG. 37 showing the follower;

FIG. 40 is an enlarged the area of detail of FIG. 37;

15 FIG. 41 is enlarged area of detail of FIG. 40;

FIG. 42 is a side view, shown in section, of the distal end of the surgical clip applier of FIG. 37;

FIG. 42A is a side view, shown in section, of a feedback pusher and lance on a channel;

FIG. 43 is a perspective view of the wedge plate and jaw assembly;

20 FIG. 44 is an enlarged area of detail of FIG. 43 showing the wedge plate and jaw members;

FIG. 45 is a top view of FIG. 43 taken along line 45-45;

FIG. 46 is an enlarged area of detail of FIG. 45 showing the jaw and the wedge plate;

FIG. 47 is an enlarged area of detail of FIG. 45 showing the wedge plate and cam link;

FIG. 48 is a side view, shown in section, of the handle housing at the beginning of an initial stroke;

FIG. 49 is an enlarged area of detail of FIG. 48 showing the rack and pawl;

5 FIG. 50 is an enlarged area of detail of FIG. 48 similar to FIG. 49;

FIG. 51 is a side view, shown in section, of the feed bar and trip lever;

FIG. 52 is a side view, shown in section, of the follower;

FIG. 53 is a side view, shown in section, of the endoscopic portion of the surgical clip applicator;

10 FIG. 54 is an enlarged area of detail of FIG. 53 illustrating the spindle movement;

FIG. 55 is a top view of the wedge plate and filler component illustrating the movement of the cam link;

FIG. 56 is a side view, shown in section, illustrating the feed bar advancing a clip;

FIG. 57 is a top view of the wedge plate and cam link moving distally;

15 FIG. 58 is a side view, shown in section, showing the movement of the flexible leg cammed out of a wedge plate window;

FIG. 59 is a side view, shown in section, illustrating a clip entering the jaws;

FIG. 60 is a further top view of the cam link and wedge plate movement;

20 FIG. 61 is a side view, shown in section, of the flexible leg and wedge plate disengagement

FIG. 62 is a top view of the wedge plate entering the jaw structure;

FIG. 63 is a perspective view illustrating the wedge plate camming open the jaw structure;

FIG. 64 is a top view illustrating further advancement of the cam link in the wedge plate;

FIG. 65 is a side view, shown in section, illustrating the trip lever engaged with the feed bar;

FIG. 66 is a side view, shown in section, illustrating the spindle camming the flexible leg out of engagement with the wedge plate;

FIG. 67 is a side view, shown in section, illustrating the feed bar loading a clip into the jaw structure;

FIG. 68 is a side view, shown in section, illustrating the trip lever being cammed out of engagement with the feed bar by means of a trip block.

FIG. 69 is a side view, shown in section, illustrating the retraction of the wedge plate and feed bar;

FIG. 69A is a perspective view, with half the body removed, illustrating initial actuation;

FIG. 70 is a side view, shown in section, illustrating further advancement of the spindle;

FIG. 71 is a side view, shown in section, illustrating the retraction of the wedge plate and further advancement of the spindle;

FIG. 72 is a perspective view of the wedge plate retracting from the jaw structure;

FIG. 73 is a side view, shown in section, with the spindle engaging the driver and a latch retractor engaging the spindle;

FIG. 74 is a side view of the handle housing with the trigger at full stroke;

FIG. 75 is an enlarged area of detail of FIG. 74 with the pawl clearing the teeth on the rack;

FIG. 76 is a side view, shown in section, of the driver camming the jaws closed about a surgical clip;

FIGS. 77 to 79 are sequential views of the driver camming the jaws closed about a surgical clip;

FIG. 80 is a view, shown in section, of the overpressure mechanism including the impact spring;

5 FIG. 81 is a perspective view of a surgical clip formed on a vessel;

FIG. 82 is an enlarged area of detail of the pawl resetting;

FIG. 83 is a side view, shown in section, illustrating the latch retractor resetting;

FIG. 84 is a side view, shown in section, illustrating the spindle retracting; and

FIGS. 85 and 86 are top views illustrating the cam link resetting within the wedge plate.

10 FIG. 87 is a side view of the distal end of the surgical clip applier illustrating the follower engagement with a lance;

FIG. 88 is a side view, partially showing section, of the lockout wedge engagement with the spindle; and

FIG. 89 is an enlarged view of the pawl and rack in a locked out condition.

15

DETAILED DESCRIPTION

There is disclosed a novel endoscopic surgical clip applier having a jaw control mechanism configured to maintain jaws of the surgical clip applier in a spaced apart and stable position during insertion of a surgical clip. It should be noted that, while the disclosed jaw control mechanism is shown and described in an endoscopic surgical clip applier, the disclosed jaw control mechanism is applicable to any surgical clip applier or other instrument having a pair of compressible jaws.

20

Referring now to Figs. 1-5, surgical clip applier 10 generally includes a handle assembly 12 and an endoscopic portion including an elongated tubular member 14 extending distally from handle assembly 12. Handle assembly 12 is formed of a plastic material while elongated tubular member 14 is formed of a biocompatible material such as stainless steel. Elongated tubular member 14 of surgical clip applier 10 may have various outer diameters such as an outer diameter of 5mm or 10mm depending on intended use. Further, elongated tubular member may have various elongated or shortened lengths depending on intended use, such as, for example, in bariatric surgery. In one embodiment, the elongated tubular member 14 in bariatric surgery may have a length that is in excess of 30 centimeters. In one preferred embodiment of bariatric surgery, the length of the elongated tubular member 14 is 33 centimeters. In another preferred embodiment, the length of the elongated tubular member 14 for bariatric surgery is 37 centimeters. In still another preferred embodiment, the length of the elongated tubular member 14 for bariatric surgery is 40 centimeters, however one skilled in the art should appreciate that the outer tubular member 14 may have any length in excess of 30 centimeters and the present disclosure is not limited to any of the above embodiments. A pair of jaws 16 are mounted on the distal end of elongated tubular member 14 and are actuated by a trigger 18 movably mounted in handle assembly 12. Jaws 16 are also formed of a biocompatible material such as stainless steel or titanium. Notably, in some embodiments, when jaws 16 are in an open condition relative to each other, the maximum width of jaws 16 measure less than or equal to the outer diameter of elongated tubular member 14 to allow insertion through a trocar or other part in a body in a open condition. This is particularly true of the 10mm clip applier. Jaws 16 are mounted such that they are longitudinally stationary relative to elongated tubular member 14. A knob 20 is rotatably mounted on a distal end of handle assembly 12 and affixed to elongated tubular member 14 to

provide 360 degree rotation of elongated tubular member 14 and jaws 16 about its longitudinal axis. Referring for the moment to FIG. 3, jaws 16 define a channel 22 for receipt of a surgical clip therein.

As best shown in FIGS. 2 and 4 a window 200 is provided in handle assembly 12 to view
5 an indicator, such as, for example, a counter mechanism associated with handle assembly 12.

Referring now to FIGS. 6 through 7, handle assembly 12 of clip applicator 10 is shown. Handle assembly 12 includes a longitudinally movable rack 202 which is connected to trigger 18 by means of a wishbone link 204. A pin 206 is provided to connect wishbone link 204 to rack 202. Rack 202 is provided for advancing and crimping a surgical clip between jaws 16 in
10 response to actuation of trigger 18. Rack 202 is biased to a proximal position by a return spring 208 positioned between rack 202 and a bushing 210 that is mounted within journal 36 in housing 12.

In order to prevent inadvertent return of trigger 18 and rack 202 before full actuation of surgical instrument 10, a pawl 212 is movably mounted on a pawl pin 214. Pawl 212 is
15 engageable with rack 202 in a manner discussed in more detail hereinbelow. A pawl spring 216 is provided between spring posts 218 in order to bias pawl 212 into engagement with rack 202.

Referring for the moment to FIG. 8, pawl 212 includes a pawl hole 220 for mounting pawl 212 on pawl pin 214. Pawl 212 also includes pawl teeth 222 engageable with rack 212 in a manner described below.

Referring to FIGS. 7, 9 and 9A, rack 212 generally includes a rack hole 224 for
20 connecting rack 212 to wishbone link 204 by means of pin 206. Rack 212 also includes rack teeth 226 which are engageable with pawl teeth 222 to restrict longitudinal movement of rack 212 within handle assembly 12. Rack 212 is also provided with a distal recess 228 and a

proximal recess 230. Recesses 228 and 230 are provided to allow pawl 212 to reverse and advance back over rack 202 when rack 202 reverses to proximal movement. A distal hook 232 is provided on rack 202 to engage rack 202 with the various drive mechanisms in a manner described hereinbelow. Thus, actuation of trigger 18 drives wish bone link 204, thereby driving rack 202 distally through wishbone link 204 and against the bias of return spring 208.

Referring for the moment to FIGS. 9F and 9G, wishbone link 204, as noted above, is provided to connect trigger 18 to rack 202. Specifically, wishbone link 204 includes a snap fit end or locking feature 234 which is engageable with a post (now shown) on trigger 18. Bores 236 formed at an opposing end of wishbone link 204 are provided to mount on rack pin 206. A slot 238 provided in wishbone link 204 allows wishbone link 204 to support rack 202 from opposite sides thereof. Linkage mechanism, including trigger 18 and wish bone link 204, allows for a greater mechanical advantage while minimizing the space the linkage mechanism occupies in handle assembly 12. Knob 20 includes a flange 34 which is also rotatably mounted in a journal 36 in housing 12.

Referring now to FIGS. 6A and 6B, and as noted above, handle assembly 12 is provided with a window 200 at a proximal end thereof revealing an indicator mechanism associated with handle assembly 12. Thus, there is provided a novel counter mechanism 240 which is configured to provide an indication of either the number of clips fired or the number of clips remaining within surgical instrument 10. Counter mechanism 240 is triggered by an actuator 242 associated with handle assembly 12 via a toggle arm 244 pivotally mounted to handle assembly 12. Counter mechanism 240 generally includes a counter 246 having an actuation feature 248, such as, a leaf spring and contact, button, etc. which is tripped or actuated by toggle arm 244 in response to actuation of trigger 18. A lens 250 is provided in between counter 246

and counter window 200 to protect counter 246 or enhance magnification of alpha-numeric digits during operation. Counter 246 can be of the liquid crystal display (LCD) light emitting diode (LED) or analog/mechanical type. Counter 246 may also include a printed circuit board, battery and a backlight or lighted display. Counter 246 can be configured to count down from the total number of surgical clips originally provided in surgical instrument 10 to indicate the number of clips remaining. Alternatively, counter 246 can count up from 0 to the total number of clips already fired. One contemplated counter 246 is an LCD counter module available from Golden View Display, Inc. The counter 246 may be any device known in the art to provide an indication of an event. The event may be related to the procedure or the operation of the clip applier 10.

10 The counter 246 in a preferred embodiment may be various types of liquid crystal displays. However, in another embodiment, the display may be one or more light emitting diodes, a luminescent display, a multi-color display, a digital display, an analog display, a passive display, an active display, a so called "twisted nematic" display, a so called "super twisted nematic" display, a "dual scan" display, a reflective display, a backlit display, an alpha numeric display, a

15 monochrome display, a so called "Low Temperature Polysilicon Thin Film Transistor" or LPTS TFT display, or any other display that indicates a parameter, information or graphics related to the procedure or the clip applier 10. In one embodiment, the display is a liquid crystal display or "LCD". The LCD may be a black and white or color display that displays one or more operating parameters of the clip applier 10 to the surgeon. In one embodiment, the displayed parameter

20 may be an amount of remaining clips, a number clips that have been used, a position parameter, a surgery time of usage, or any other parameter of the procedure.

Referring for the moment to FIGS. 9B and 9C, the specific structure of actuator 242 will now be described. As noted above, actuator 242 is configured to index counter mechanism 240

in response to movement of trigger 18 thus actuator 242 includes a drive slot 252 which is configured to be positioned about pin 206 extending through rack 202 and wishbone link 204. Drive slot 252 allows surgical instrument 10 to be actuated through a predetermined length of stroke prior to pin 206 engaging actuator 242. A connecting slot 254 is provided to engage a
5 corresponding pin on toggle arm 244 in order to bias toggle arm 244 against counter 246. In order to prevent any flexing or wobbling of actuator 242 during its reciprocal movement within handle assembly 12 actuator 242 is provided with a pair of fingers 256 which are configured to ride along a housing rail 258 formed in handle assembly 12 (FIG. 6B). A tab 260 (FIGS. 6C and 6D) is provided on actuator 242 to engage a return spring in a manner described in more detail
10 hereinbelow.

Referring for the moment to FIGS. 9D and 9E counter lever 244 includes a post 262 which is pivotally mounted into housing assembly 12. A first end of toggle arm 244 includes a pin 264 which is engageable within connecting slot 254 in actuator 242 such that longitudinal movement of actuator 242 within housing assembly 12 pivots counter lever 244 about stud 262.
15 An opposed end of toggle arm 244 includes a contact lever 268 which is configured to engage and depress counter button 248 on counter 246 to trigger or increment counter 246 in any number of predetermined fashions either up or down numerically.

The arrangement of the various components of the counter mechanism 240, actuator 242 and counter lever 244 mounted within handle assembly, is best illustrated in FIGS. 6B to 6D.
20 Referring initially to FIGS. 6B, wherein rack 202 has been removed for clarity, it can be seen that fingers 256 of actuator 244 ride along housing rail 258 formed in housing assembly 12. Pin 206 associated with wishbone link 204 rides within drive slot 252. At a proximal end of actuator 242 pin 264 on counter lever 244 is positioned within connecting slot 254.

Referring now to FIGS. 6C and 6D, in order to maintain counter lever 244 out of engagement with counter mechanism 240 prior to actuation of trigger 18 there is provided a compression spring 270 which is engageable with spring 260 on actuator 242. An opposed end of compression spring 270 engages a corresponding projection formed on opposed side of housing handle assembly 12 in order to bias actuator 242 in a proximal most direction.

Combinations of the various elements and mechanisms associated with clip applier 10 will now be described.

Referring to FIG. 10, a bushing 48, including retention pins 50, is provided to secure the bushing 210 to the knob 20. A drive link 272 is connected, to rack 202 (FIGS. 6 and 7) such that a proximal end of drive link 272 engages rack 202. Specifically, distal hook 232 of rack 202 engages a slot 274 in a proximal end of drive link 272. An over pressure mechanism including an impact spring 56 is provided about outer tube 14 between bushing 48 and housed in a bore of knob 20 to prevent over compression of jaws 16 during actuation of the instrument in a manner described in more detail hereinbelow. Drive link 272 extends within a bore 58 in knob 20.

A flange located at a proximal end of elongated tube member 14 abuts a proximal end of bushing 48 (FIGS. 7D and 7E).

With continued reference to FIG. 10, in order to actuate the various components there is provided an actuation mechanism or spindle 60 mounted for longitudinal movement through elongated tubular member 14. Spindle 60 includes a boss 62 at its proximal end which is engageable with a recess 64 on the distal end of spindle link 272. (FIG. 7A) by positioning boss 62 of spindle 60 within a recess 276 of spindle link 272, spindle 60 can rotate with the outer tube assembly independent of the longitudinal motion of spindle link 272 and spindle 60. As best

shown in FIG. 7B bushing 48 is positioned within knob 20 and secured therein by means of retention pins 50.

Referring for the moment to FIGS. 7C and 7E, bushing 48 is provided with a pair of opposed longitudinal ribs 278 which fit within corresponding slots 280 in knob 20 for the purpose of orientation.

Referring now to FIGS. 7D and 7E, it can be seen that tabs 282 formed on an inner surface of the proximal end of bushing 48 are configured to engage corresponding cutouts 284 on outer tube 14. Thus, outer tube 14 is allowed to rotate in response to rotation of knob 20.

Referring to FIG. 10, a camming mechanism including a driver 66 and a slider joint 68 extend from a distal end of spindle 60 to cam closed jaws 16 about a surgical clip.

Clip applicator 10 is configured to retain a plurality of surgical clips for application to tissue. Clip applicator 10 includes an elongated channel member 70 configured to retain a plurality of surgical clips 72 and convey surgical clips 72 to jaws 16. It should be noted that channel member 70 and jaws 16 do not move longitudinally relative to elongated tubular member 14. A follower 74 is biased by a spring 76 to urge surgical clips 72 distally within channel member 70. A channel cover 78 overlies channel 70 to retain and guide spring 76 and surgical clips 72 therein. A nose 80 is provided at a distal end of channel cover 78 to assist in directing surgical clips 72 into jaws 16.

A feeder mechanism including a feed bar 82 is provided for longitudinal movement relative to channel cover 78 in order to advance individual clips 72 into jaws 16. A trip block 84 having a guide pin 86 and a feed bar spring 88 are provided adjacent the proximal end of channel cover 78 to bias feed bar 82 in a proximal direction. Specifically, a proximal end 90 of guide pin 86 is interconnected with a hook 92 on an underside of feed bar 82 (FIG. 38A & B) and through

slot 94 in trip block 84. (See also FIGS. 10 A, C, & D) In order for spindle 60 to move feed bar 82, spindle 60 is provided with a trip lever 96 and a biasing spring 98. Trip lever 96 is engageable with a proximal end of feed bar 82 in a manner described in more detail herein below.

5 A notable advantage of presently disclosed clip applier 10 is that it is provided with a wedge plate 100 which is configured to advance into jaws 16 during actuation of surgical clip applier 10 and maintain jaws 16 in a spaced apart condition while receiving a surgical clip 72. Cam slot 136 (FIG. 13), described in detail hereinbelow, formed through wedge plate 100 and a filler component 102 mounted within elongated tubular member 14, cooperate in connection
10 with a cam link 104, provided on spindle 60, to move wedge plate 100 relative to filler component 102 and jaws 16. Filler component 102 is positioned directly behind jaws 16 and does not move relative to elongated tubular member 14.

Turning to FIG. 10A, and as noted above, feed bar 82 is provided to move surgical clips 72 into jaws 16. Feed bar 82 is driven by trip lever 96 on spindle 60. (See FIG. 10.)
15 Specifically, feed bar 82 is provided with an elongated window 106 which is configured to be engaged by trip lever 96 as spindle 60 is driven distally. Feed bar 82 also includes a window 286 for receipt of lockout structure as described herein below. To facilitate insertion of the clip into jaws 16, feed bar 82 is provided with a pusher 108 at its distal end which is configured to advance an individual clip 72 out of the line of clips 72 and into jaws 16. As shown in FIG. 10B,
20 follower 74 is positioned behind the line of clips to advance clips 72 through surgical clip applier 10. As shown in FIG. 10H, follower 74 includes an abutment surface 288 for engagement with further lockout structure located on a distal end of clip channel 70.

Referring to FIG. 10C, as noted above, trip block 84 includes a slot 94 to receive hook 92 of feed bar 82. In order to disengage trip lever 96 from window 106 and thus feed bar 82, trip block 84 is provided with an angled surfaces 110 which is configured to engage trip lever 96 and disengage it from window 106 of feed bar 82 as best shown in FIG. 10D.

5 Referring now to FIGS. 10E-10G, various features of spindle 60 will now be described. A perspective view of spindle 60, isolated from other components is shown in FIG. 10E. With specific reference to FIG. 10F, at a proximal end, spindle 60 includes a pivot point 112 for attachment of trip lever 96 at its proximal end. Additionally, a boss 114 is provided in spindle 60 for attachment of biasing spring 98 to bias trip lever 96 into engagement with window 106 of
10 feed bar 82. An angled surface 290 is provided to engage spindle 60 with lockout structure and prevent spindle from completely retracting after a final clip has been fired. With respect to FIG. 10G, at a distal end, spindle 60 is provided with a boss 116 for mounting cam link 104. Spindle 60 is additionally provided with a raised feature 118 which functions to disengage filler component 102 from wedge plate 100 in a manner described in hereinbelow.

15 Referring to FIG. 11, spindle 60 is provided to advance driver 66 into engagement with jaws 16 to close jaws 16 about a surgical clip after the surgical clip has been positioned within jaws 16. A distal end 120 of slider joint 68 resides in a recess 122 in driver 66. A proximal projection 124 of slider joint 68 rides within a longitudinal slot 126 in the distal end of spindle 60. The length of longitudinal slot 126 allows spindle 60 to move a predetermined longitudinal
20 distance before engaging and moving driver 66 longitudinally to close jaws 16 about a clip 72. A latch retractor 128 is integrally formed within a slot 130 in slider joint 68 so as to allow driver 66 to be driven distally after wedge plate 100 has been allowed to retract proximally in a manner described in more detail hereinbelow.

Referring to FIG. 12, clip applier 10 is provided with novel lock out structure to prevent actuation of clip applier 10 after a last clip 72 has been dispensed. Clip applier 10 includes a lockout wedge 292 which is movably mounted within a channel 294 in spindle 60. Lockout wedge 292 includes an angled surface 296 configured to cam against angled surface 290 on spindle 60. A raised projection 298 mates with window 286 in feed bar 82 to affix lockout wedge 292 to feed bar 82 during longitudinal movement thereof.

Referring now to FIG. 13, wedge plate 100 will be described in more detail. As noted above, wedge plate 100 is provided to bias and maintain jaws 16 in a spaced apart condition during loading of a surgical clip 72 within jaws 16. Additionally, the presence of wedge plate 100 provides stability to jaws 16 to prevent them from flexing during loading of surgical clip 72. As shown, wedge plate 100 includes a distal tip 134 which is configured to engage and cam jaws 16 open and maintain them in a spaced condition. Additionally, wedge plate 100 includes a cam slot 136 which is configured to cooperate with cam link 104 mounted on spindle 60 to control the motions of wedge plate 100 as discussed in more detail below. Further, distal and proximal windows 138 and 140, respectively, are provided to engage flexible structure on the filler component 102. A biasing spring 142 is provided on a mount 144 to bias wedge plate 100 generally proximally within elongated tubular member 14. Finally, a stop 146 is configured to engage corresponding structure on filler component 102.

Referring now to FIGS. 14 and 15, various aspects of filler component 102 will now be described. Filler component 102 includes a flexible leg 152 which is configured to engage distal and proximal windows 138 and 140 in wedge plate 100. Filler component 102 also includes an elongated cam slot 148 configured to receive part of cam link 104. A disengaging edge 150 is provided within cam slot 148 to facilitate disengaging cam link 104 from within cam slot 136 in

wedge plate 100. Filler component 102 additionally includes a stop 154 for engagement with tongue 146 on wedge plate 100 (FIG. 13), to limit the proximal retraction of wedge plate 100, as well as a longitudinal recess 156 to accommodate the length of return spring 142 of wedge plate 100.

5 FIGS. 16 and 17 illustrate the position of impact spring 56 relative to rotation knob 20. As noted above, impact spring 56 is provided as an over pressure mechanism to prevent over compression of jaws 16 during the crimping of a surgical clip 72 as described in more detail below with respect to the operation of surgical clip applier 10. The over pressure mechanism is designed to prevent overstroke of trigger 18 applied by the surgeon and ultimately prevent
10 damage to jaws 16.

 Referring to FIGS. 18-20, spindle 60 and related drive components are shown with elongated tubular member 14 removed. Specifically, with regard to FIG. 19, pusher 108 of feed bar 82 extends through a slot 158 in nose 80 to engage a surgical clip 72. Similarly, as shown in FIG. 20, at a proximal end of spindle 60, trip lever 96 extends through window 106 in feed bar
15 82. In this position, trip lever 96 can engage an edge of slot 106 to drive feed bar 82 distally along with spindle 60 through elongated tubular member 14. Lockout wedge 292 is longitudinally movable within channel 294 in spindle 60. Projection 298 on lockout wedge mates with window 286 in feedbar 82.

 Referring to FIG. 21, there is a view similar to FIG. 19, however, nose 80 has been
20 removed to illustrate pusher 108 engaging a surgical clip 72 located in channel 70. T-shaped tabs 300 are provided on channel 70 to hold channel cover 78 and nose 80 securely to channel 70.

Referring now to FIG. 22, spindle 60 and associated components are shown with feed bar 82 removed.

Referring to FIG. 23, there are illustrated multiple clips 72 positioned within channel 70 for supply to jaws 16 at a distal end of spindle 60. Clips 72 are arranged in longitudinal
5 alignment within channel 70. Retention fingers 71 are provided at a distal end of channel 70 to restrain a stack of a clips 72 within channel 70 until advanced into jaws 16 by feedbar 82. A lance 302 on channel 70 is configured to engage abutment surface 288 on feed bar 82.

Referring to FIG. 24, there is illustrated an intermediate section of spindle 60 assembled with follower 74 and follower spring 76. As noted, spring 76 biases follower 74 distally relative
10 to spindle 60.

With reference to FIG. 25, there is illustrated spindle 60 assembled with trip lever 96 and biasing spring 98, with trip lever 96 being biased into an upward most position by biasing spring 98. Lockout wedge 292 is positioned within channel 294.

Referring to FIGS. 26 and 27, an opposed side of spindle 60 assembled with driver 66
15 about jaws 16 is illustrated. As noted above, driver 66 is configured to cam jaws 16 closed about a surgical clip. Thus, jaws 16 include angled camming surfaces 160 for receipt of corresponding camming surfaces 184 (FIG. 34) of driver 66. A pocket 187 (FIG. 31) in the proximal end of jaws 16 limits the retraction of driver 66. Specifically, protrusion 186 of slider joint 68 engages pocket 187 of jaws 16. (See FIGS. 31 & 34).

Referring to FIGS. 28-30, the relative assembled positions of channel 70, trip lock 84,
20 wedge plate 100 and filler component 102 will now be described. Referring initially to FIGS. 29 and 30, filler component 102 is positioned on channel 70. Proximal end of filler component 102 abuts a stop 162 positioned on channel 70. The wedge plate 100 lies over filler component 102

in the manner shown. As best shown in FIG. 30, filler component 102 includes a cam slot 148 having a disengaging edge 150 formed within cam slot 148. Similarly, wedge plate 100 includes a cam slot 136. As noted above, a cam link 104 is provided attached to spindle 60 (not shown) in order to drive wedge plate 100 distally. To facilitate driving wedge plate 100, cam link 104 is provided with a cam link boss 164 which rides in cam slots 136 and 148 of wedge plate 100 and filler component 102 respectively. As cam link 104 is advanced distally relative to wedge plate 100 cam link boss 164 engages a driving edge 166 of wedge plate 100 to drive wedge plate 100 distally. In the manner described hereinafter, once cam link 104, and in particular cam link boss 164, engages disengaging edge 150 of filler component 102 cam link boss 164 is cammed out of engagement of driving edge 166.

Referring to FIG. 30, filler component 102 is provided with a flexible leg 152 which is movable between distal and proximal windows 138, 140, respectively, of wedge plate 100. In order to cam flexible leg 152 out of one of the proximal or distal windows, there is provided a cam surface 168 on flexible leg 152 which cams flexible leg 152 out of the windows in response to relative movement of wedge plate 100 relative to filler component 102.

As noted hereinabove, jaws 16 are provided to receive and crimp surgical clips 72 positioned therein. Referring to FIGS. 31 and 32, jaws 16 generally include a pair of flexible legs 170 fixed to a base 172. Jaw members 16A and 16B are located at a distal end of flexible legs 170. A pair of locking arms 174 extend distally from base 172 and terminate in tabs 176. Tabs 176 are configured to engage corresponding holes 177 on elongated tube 14 (FIG. 10) to secure jaws 16 to elongated tube 14. Jaws 16 include channel 22 for receipt of surgical clips 72. As shown, filler component 102 is positioned directly behind jaws 16 and, as with jaws 16, does not move longitudinally relative to outer tubular member 14.

Referring for the moment to FIG. 32, jaws 16 are configured to receive wedge plate 100 such that the distal tip 134 of wedge plate 100 is used to initially separate jaws section 16a and 16b and maintain them in a separated and aligned configuration during insertion of a surgical clip into jaws 16. As noted, this prevents any torquing or flexing of jaw 16a relative to jaw 16b while a surgical clip 72 is being loaded therein. Each of flexible legs 170 includes a cam edge 178 (see FIGS. 44 & 63) to guide distal tip 134 of wedge plate 100 within jaws 16.

Referring to FIG. 33, wedge plate 100 is illustrated positioned on spindle 60 such that latch retractor 128 extends through a slot 182 in wedge plate 100. As best shown in FIG. 34, with wedge plate 100 removed, it can be seen that a distal end of driver 60 is provided with camming surfaces 184. Camming surfaces 184 cooperate with cam surfaces 160 on jaws 16, (see FIG. 27), to cam jaws 16 together in response to longitudinal movement of driver 60 relative to jaws 16. Protrusion 186 on slider joint 68 extends through a slot 188 in wedge plate 100 to limit retraction of slider joint 68 relative to jaws 16.

The operation of surgical clip applier 10 to crimp a surgical clip around a target tissue, such as, for example, a vessel, will now be described. With reference to FIGS. 35 and 36, trigger 18 is in a generally uncompressed state with rack 202 and thus spindle 60 biased to a proximal most position by return spring 208. Additionally, actuator 242 is in a proximal most position holding counter lever 244 away from counter 246. Pawl 212 is positioned in distal recess 228 on rack 202. As best shown in FIGS. 37-42, and with initial reference to FIG. 38, in an unfired state, trip lever 96 carried by spindle 60, biased upwardly by biasing spring 98, is positioned adjacent to, and in contact with, a slot in feed bar 82. Trip block 84 is in a distal position relative to trip lever 96. Lockout wedge, affixed to feed bar 82, is in a proximal position.

Referring to FIG. 39, follower 74 is biased distally by a spring 76 such that clips 72 are biased in a distal direction.

Referring to FIG. 40, spindle 60 and feed bar 82 are stationery with latch retractor 128 biased to an upward position.

5 Referring to FIG. 41, flexible leg 152 of filler component 102 is in the distal window 138 of wedge plate 100. Raised feature 118 on spindle 60 is proximal of flexible leg 152.

As best shown in FIG. 42, at the distal end of surgical clip applier 10, when at rest in an unfired state, wedge plate 100 and feed bar 82 are in a proximal-most position relative to jaws 16. Pusher 108 is distal of lance 302 (FIG. 42A).

10 FIGS. 43-47 illustrate the initial at rest position of the wedge plate 100, jaws 16 and filler component 102.

Referring initially to FIGS. 43 and 44, as shown, wedge plate 100 is in a proximal-most position relative to jaws 16. As shown in FIG. 43, flexible leg 152 is in distal window 138 of wedge plate 100, while cam link 104 is in a proximal-most position relative to cam slot 136 in
15 wedge plate 100.

As best shown in FIGS. 45 and 46, wedge plate 100 is in a proximal most position relative to jaws 16 with distal tip 134 proximal of cam edges 178 of jaws 16.

Referring to FIG. 47, wedge plate 100 is in a proximal-most position relative to filler component 102, such that driving edge 166 of wedge plate 100 is proximal of disengaging edge
20 150 of filler component 102.

Referring to FIG. 48, to initiate actuation of clip applier 10, trigger 18 is moved through an initial swing wishbone link 204 drives rack 202 distally thereby driving spindle 60 distally. Actuator 242 remains in a proximal most position as pin 206 moves through drive slot 252 in

actuator 242. With reference for the moment to FIG. 50, if the trigger 18 is released at this point, rack teeth 226 would restrain pawl teeth 222 against proximal motion, preventing release of trigger 18 and partial or inadvertent partial actuation of surgical clip applier 10.

During the initial stroke, spindle 60 moves a predetermined distance. With regard to FIG. 51, as spindle 60 is driven an initial distal distance, trip lever 96 engages elongated window 106 feed bar 82 and moves feed bar 82 distally a similar distance. Lockout wedge 292 is carried distally by feed bar 82. As shown in FIG. 42 & 51, as feed bar 82 is driven distally and a clip 72 is driven into jaws 16, follower 74 moves distally (FIG. 52) due to the bias of spring 76 to urge the stack of surgical clips 72 distally.

With reference to FIG. 49, as rack 202 moves distally pawl 212 rotates clockwise such that pawl teeth 222 move out of distal recess 228 and begin to ride over rack teeth 226.

Referring to FIGS. 53 and 54, as spindle 60 and feed bar 82 move distally, spindle 60 drives cam link 104 distally an initial distance such that cam link boss 164 on cam link 104 engages wedge plate 100. As shown, flexible leg 152 of filler component 102 is positioned in distal-most window 138 of wedge plate 100.

As shown in FIG. 55, as cam link 104 moves distally with spindle 60, cam link boss 164 engages driving edge 166 on wedge plate 100 to urge wedge plate 100 distally relative to filler component 102.

Referring to FIG. 56, as feed bar 82 moves distally, pusher 108 at the distal end of feed bar 82 engages a clip 72 and begins to urge clip 72 into jaws 16. Notably, at this point, spindle 60 has not yet contacted driver 66, thereby preventing compression of jaws 16 prior to full insertion of surgical clip 72.

Turning again to FIG. 55, as surgical clip applicator 10 is actuated through a further second predetermined distance, cam boss 164 on cam link 104 continues to drive wedge plate 100 distally and flexible leg 152 is cammed out of distal window 138 and into proximal window 140 by cam surface 168 to engage wedge plate 100 with filler component 102. As shown in FIGS. 57 & 58, at this point, feed bar 82, wedge plate 100, spindle 60, clips 72 and follower 74 (FIG. 52) are all moving in a distal-most direction.

Referring to FIG. 59, feed bar 82 continues to urge pusher 108 at the distal end of feed bar 82 against a surgical clip 72 to urge clip 72 into channel 22 in jaws 16. Surgical clips 72 contained in channel 70 are biased in a distal direction by follower 74 (FIG. 52) and wedge plate 100 (FIG. 54) continues to move distally while driver 66 remains stationary relative to elongated tubular member 14.

Referring to FIG. 60, as spindle 60 is moved further, cam boss 164 of cam link 104 is cammed out of engagement with driving edge 166 of wedge plate 100 by means of disengaging edge 150 formed in filler component 102 as best shown by the arrows in FIG. 60. During this further stroke of a predetermined distance, flexible leg 152 of filler component 102 snaps into proximal window 140 of wedge plate 100, thereby preventing retraction of wedge plate 100 from its distal-most position.

As shown in FIG. 61, flexible leg 152 is positioned within proximal window 140 of wedge plate 100, thereby restraining wedge plate 100 against retraction, while feed bar 82 and spindle 60 continue to move in a distal direction as shown by the arrows.

As shown in FIGS. 62-63, distal tip 134 of wedge plate 100 urges jaw members 16a and 16b apart by engaging cam surfaces 178 in jaws 16a and 16b. As noted above, by positioning wedge plate 100 in cam surfaces 178 of jaw members 16a and 16b, wedge plate 100 not only

spreads the jaws 14 apart to properly receive surgical slip 72, but additionally restrains each individual jaw member 16a and 16b from flexing with respect to each other, thereby preventing any torque of clip 72 as it is being inserted into jaws 16.

Referring to FIG. 64, as noted above, flexible leg 152 restrains wedge plate 100 from proximal retraction while cam link 104 continues to advance through slots 148 and 136 in filler component 102 and wedge plate 100 (FIG. 64).

As best shown in FIG. 65, as spindle 60 continues to move distally through the stroke, trip lever 96 is urged distally with spindle 60 until trip lever 96 engages camming surface 110 (See FIG. 10D) of trip block 84. As camming surface 110 (FIG. 10D) of trip block 84 is urged against trip lever 96, trip lever 96 will be cammed out of engagement with elongated window 106 of feed bar 82 allowing feed bar 82 to return to a proximal position due to the bias of feed bar spring 88 (see FIG. 10).

Referring for the moment to FIG. 66, as spindle 60 continues to move through its stroke, raised feature 118 on spindle 60 begins to cam flexible leg 152 out of proximal window 140 of wedge plate 100, so that the wedge plate 100 will be able to retract prior to, and so that, surgical clip 72 is crimped between jaws 16. This is best illustrated in FIG. 67 where feed bar 82 has fully inserted clip 72 within jaws 16 and wedge plate 100 has retracted to a proximal-most position.

FIG. 68 illustrates trip lever 96 being cammed out of engagement with feed bar 82 by camming surface 110 of trip block 84 and against the bias of biasing spring 98 such that feed bar 82 is disengaged from trip lever 96 and feed bar 82 can start to retract proximally. As shown, in FIG. 69, pusher 108 of feed bar 82 is retracted to a proximal position behind the next distal-most clip 72 as wedge plate 100 retracts leaving clip 72 inserted into jaws 16.

Referring to FIG. 69A, as trigger 18 is continued to be compressed, pin 206 advances distally within drive slot 252 on actuator 242 until pin 206 engages a distal end 304 of drive slot 252. Thereafter, as trigger 18 is further compressed, pin 206 moves actuator 242 distally. Pin 264 on toggle arm 244 is rotated clockwise within connecting slot 254 thereby driving contact arm 268 on toggle arm 244 towards actuation feature 248.

Referring to FIG. 70, trip lever 96 is completely cammed down by cam surface 110 on trip block 84 and spindle 60 continues to move distally through a further predetermined stroke.

Referring for the moment to FIG. 71, as wedge plate 100 retracts proximally while spindle 60 continues to move distally, flexible leg 152 on filler component 102 snaps into distal window 138 of wedge plate 100. As shown in FIG. 72, wedge plate 100 is retracted to a proximal position relative to jaws 16.

Referring to FIG. 73, when latch retractor 128 is cammed downwardly relative to spindle 60, spindle 60 has moved distally to a predetermined distance. The action of spindle 60, now engaging driver 66, pushes driver 66 distally. Driver 66 draws slider joint 68 and simultaneously slider joint 68 drags latch retractor 128 distally mechanically forcing cam surface no. of latch retractor 128 downward to underside of jaw pad 172 and engaging latch retractor 128 with slot 126 of spindle 60.

Referring to FIGS. 74-75, as trigger 18 is fully compressed to drive spindle 60 to a distal-most position, upon complete compression of trigger 18 and fully forming of clip 72, and with reference to FIG. 74, counter lever is fully rotated clockwise driving bumper 268 against counter button 248 to thereby increment the number displayed by counter 246.

As noted hereinabove, the incrementation of the number illustrated in counter 246 can be either down from a full complement of surgical clips 72 contained within an original surgical

stapler 10 or can be counted up to indicate the number of clips dispensed by surgical instrument 10.

Referring for the moment to FIG. 75, on full firing of surgical instrument 10, pawl teeth 222 disengage from rack teeth 226 and reside within proximal recess 230. Notably, a full stroke 5 of the spindle 60 is required to take a clip 72 from an initial position to a fully inserted position in the jaws 16. As spindle 60 moves through its distal-most position, it moves driver 66 in the manner described hereinabove to crimp a surgical clip 72. For example, referring to FIGS. 76-79, driver 66 advances distally relative to camming surfaces 160 on jaws 16a and 16b, such that camming surfaces 184 on driver 66 cam jaws 16a and 16b closed thereby closing surgical clip 72 10 contained therebetween.

Referring for the moment to FIG. 80, a security mechanism is provided to prevent an overstroke condition and thereby excessive compression of clip 72 from damaging tissue, jaws 16 or driver 66. If trigger 18 is continued to be squeezed past a stroke required for a full forming of clip 72 impact spring 56 compresses within the space defined between knob 20 and bushing 15 48 thereby preventing any further distal movement of spindle 60.

A fully formed clip formed about vessel V is illustrated in FIG. 81.

Referring to FIG. 82, as trigger 18 is released (not shown), pawl 212 now rotates counter-clockwise against the bias of pawl spring 216 such that pawl teeth 222 ride along rack teeth 226 to reset the handle assembly. As shown in FIG. 83, when driver 66 retracts, latch retractor 128 is 20 again biased up into its upper-most position, thereby, resetting the drive mechanism.

Referring to FIGS. 84-86, as spindle 60 retracts, raised feature 118 of spindle 60 moves past flexible leg 152 in filler component 102. It should be noted that wedge plate 100 does not move as it has already fully retracted. As spindle 60 retracts, it draws cam link 104 proximally

within slots 136 and 148 of wedge plate 100 and filler component 102 to its initial position. As best seen in FIG. 86, in this position, clip applier 10 is again in an initial position to be refired and thus to attach another clip to a vessel.

Referring now to FIGS. 87 to 89 with initial reference to FIG. 87, once all surgical clips 5 72 have been discharged from surgical clip applier 10, follower 74 is in a distal-most position such that abutment surface 288 engages lance 302 on channel 70 thereby locking out or preventing proximal retraction of follower 74. As shown, pusher 108 on feed bar 82 upon retraction engages follower 74 and wedges between nose 80 and follower 74 such that feedbar 82 cannot retract proximally.

10 As shown in FIG. 88, since feed bar 82 is restrained in a distal-most position, lockout wedge 292, affixed to feed bar 82, is also restrained in a distal-most position. Thus, as spindle 60 attempts to retract proximally, angled surface 296 on lockout wedge 292 engages angled surface 290 on spindle 60 thereby preventing further retraction of spindle 60.

Referring to FIG. 89, because spindle 60 cannot retract completely proximally rack 202 15 cannot retract completely proximally. Rack teeth 226 engage pawl teeth 222 and prevent pawl 212 from rotating back into distal recess 228 thereby preventing resetting of the clip applier 10. In this manner, clip applier 10 is completely locked out from any further attempted firings after the last surgical clip 72 has been dispensed. Because pawl teeth 222 and rack teeth 226 prevent any distal movement of the drive mechanism, specifically trigger 18 is prevented from being 20 squeezed further.

WHAT IS CLAIMED IS:

Claim 1: An apparatus for application of surgical clips to body tissue, which comprises:

- a) a handle portion;
- b) a body extending distally from the handle portion and defining a longitudinal
5 axis;
- c) a plurality of surgical clips disposed within the body;
- d) a jaw assembly mounted adjacent a distal end portion of the body, the jaw
assembly including first and second jaw portions movable between a spaced-apart and an
approximated position;
- 10 e) a wedge plate longitudinally movable between the first and the second jaw
portions;
- f) a clip pusher configured to individually distally advance a surgical clip to the
jaw assembly while the jaw portions are in the spaced apart position;
- g) an actuator at least partially disposed within the body and longitudinally
15 movable in response to actuation of the handle portion; and
- h) a jaw closure member positioned adjacent the first and second jaw portions to
move the jaw portions to the approximated position.

Claim 2: The apparatus of claim 1, wherein said wedge plate biases the first and the
20 second jaw portions when said wedge plate is longitudinally moved between the first and the
second jaw portions; and

wherein said wedge plate maintains said first and said second jaw portions in a fixed predetermined relationship during loading of said clip, said fixed predetermined relationship preventing flexing of the first and the second jaw members during clip loading.

5 Claim 3: The apparatus of claim 2, wherein said wedge plate has a rounded distal tip.

 Claim 4: The apparatus of claim 2, wherein said wedge plate has a first proximal window, said first proximal window adapted to be engaged by a member disposed in said body configured to hold said wedge plate in a distal most position, said distal most position being
10 between said first and said second jaw members.

 Claim 5: The apparatus of claim 4, wherein said wedge plate has a second proximal window, said second proximal window adapted to be engaged by said member, said second proximal window configured to hold said wedge plate in a proximal most position, said proximal
15 most position being retracted from said first and said second jaw members, said proximal most position of said wedge plate configured to allow the first and the second jaw members to compress said clip.

 Claim 6: The apparatus of claim 5, wherein said member is movable from said second
20 proximal window to first second proximal window by said actuator, said actuator moving said wedge plate distally, wherein said member moves from said second proximal window to said first proximal window upon said wedge plate moving distally.

Claim 7: The apparatus of claim 1, wherein said actuator further comprises a cam link, said cam link engageable with a cam slot in said wedge plate, said cam link for moving said wedge plate distally.

5 Claim 8: The apparatus of claim 6, wherein said member is a flexible leg.

Claim 9: The apparatus of claim 7, wherein said cam slot has a driving edge, said cam link engaging said driving edge, said cam link configured to longitudinally move said wedge plate distally.

10

Claim 10: The apparatus of claim 9, wherein when said actuator is driven distally said cam link is driven distally, said cam link engaging said driving edge of said cam slot, said cam link longitudinally moving said wedge plate to move said rounded distal end between said first and said second jaw members, wherein said member engages said first proximal window to hold
15 said wedge plate between said first and said second jaws for loading.

Claim 11: The apparatus of claim 10, wherein when said cam link is driven further distally said cam link disengages said driving edge and traverses in said cam slot, said cam link permitting said wedge plate to move said rounded distal end proximally from between said first
20 and said second jaw members;

wherein said member engages said second proximal window to hold said wedge plate in said proximal most position.

Claim 12: An apparatus for application of surgical clips to body tissue, which comprises:

- a) a handle portion;
- b) a body extending distally from the handle portion and defining a longitudinal

axis;

- c) a plurality of surgical clips disposed within the body;
- d) a jaw assembly mounted adjacent a distal end portion of the body;
- e) a clip pusher configured to individually distally advance a surgical clip to the

jaw assembly;

- f) an actuator at least partially disposed within the body and longitudinally

movable in response to actuation of the handle portion;

- g) a counter mechanism associated with the handle portion, the counter

mechanism indexing in response to actuation of the handle portion.

Claim 13: The apparatus of claim 12, wherein the counter mechanism comprises a liquid

crystal display.

Claim 14: The apparatus of claim 12, wherein the counter mechanism comprises a

backlight.

Claim 15: The apparatus of claim 12, wherein the counter mechanism is indexed upon

full actuation of the handle portion.

Claim 16: The apparatus of claim 12, wherein said counter mechanism is triggered by the actuator.

5 Claim 17: The apparatus of claim 16, wherein said counter mechanism is in said handle and connected to said actuator, said counter mechanism having a member connected to said actuator, wherein said counter mechanism has a liquid crystal display having a display contact, said display contact being activated when said member contacts said display contact.

10 Claim 18: The apparatus of claim 17, wherein said member is rotatable, said member rotating in response to longitudinal movement of said actuator to contact said display contact.

Claim 19: The apparatus of claim 12, wherein said counter mechanism is a liquid crystal display having a lens, said liquid crystal display displaying an image, said lens magnifying said image.

15

Claim 20: The apparatus of claim 17, wherein said actuator includes an opening, said counter mechanism having said member with a first arm and a second arm, said first arm connected to said opening;

20 wherein when said actuator longitudinally moves in a distal direction said actuator deflects said first arm and said member rotates in response to the movement; and

wherein said second arm contacts said display contact in response to said rotation of said member, said display contact being activated when said second arm contacts said display contact.

Claim 21: An apparatus for application of surgical clips to body tissue, which comprises:

- a) a handle portion;
- 5 b) a body extending distally from the handle portion and defining a longitudinal axis;
- c) a plurality of surgical clips disposed within the body;
- d) a jaw assembly mounted adjacent a distal end portion of the body, the jaw assembly including first and second jaw portions movable between a spaced-apart and an
10 approximated position;
- e) a clip pusher configured to individually distally advance a surgical clip to the jaw assembly while the jaw portions are in the spaced apart position;
- f) an actuator at least partially disposed within the body and longitudinally movable in response to actuation of the handle portion;
- 15 g) a jaw closure member positioned adjacent the first and second jaw portions to move the jaw portions to the approximated position; and
- h) a lockout mechanism configured to engage with the clip pusher to prevent the application of the surgical clips to tissue when the plurality of clips are substantially exhausted.

20 Claim 22: The apparatus of claim 21, wherein said lockout mechanism has a member, said member being longitudinally movable with said actuator to a distal most position, wherein when said member reaches said distal most position, said member engages said clip pusher, said member preventing said clip pusher to distally advance said surgical clip to said jaw assembly.

Claim 23: The apparatus of claim 21, further comprising a clip follower, said clip follower distally biasing said plurality of clips disposed in said body;

wherein said lockout mechanism includes a member, said member being longitudinally movable with said actuator to a distal most position;

wherein when said member reaches said distal most position said member engages said follower, said member preventing said follower from retracting proximally;

wherein upon retraction of said clip pusher said clip pusher engages said follower, and wherein said member prevents said clip pusher to distally advance said surgical clip to said jaw assembly.

Claim 24: The apparatus of claim 22, wherein said member is a lockout wedge.

Claim 25: The apparatus of claim 23, wherein said member is a lockout wedge.

15

Claim 26: The apparatus of claim 23, wherein said member has at least one member angled surface, and wherein said actuator has at least one actuator angled surface, wherein as said actuator retracts proximally said at least one actuator angled surface engages said member angled surface, wherein said engagement prevents said actuator from retracting proximal to a proximal most position.

20

Claim 27: An apparatus for application of surgical clips to body tissue, which comprises:

- a) a handle portion;

- b) a body extending distally from the handle portion and defining a longitudinal axis;
- c) a plurality of surgical clips disposed within the body;
- d) a jaw assembly mounted adjacent a distal end portion of the body, the jaw assembly including first and second jaw portions movable between a spaced-apart and an approximated position;
- e) a clip pusher configured to individually distally advance a surgical clip to the jaw assembly while the jaw portions are in the spaced apart position;
- f) an actuator at least partially disposed within the body and longitudinally movable in response to actuation of the handle portion;
- g) a jaw closure member positioned adjacent the first and second jaw portions to move the jaw portions to the approximated position;
- h) a wedge plate longitudinally movable between the first and the second jaw portions;
- i) a rack having a plurality of ratchet teeth being connected to said actuator; and
- j) a pawl having at least one tooth configured to engage said ratchet teeth, said pawl being biased in said handle portion, wherein as said actuator is moved longitudinally, said plurality of ratchet teeth are passed over said pawl, said pawl configured to prevent inadvertent return of said actuator before full actuation of the apparatus.

20

Claim 28: The apparatus of claim 27, wherein said pawl is biased by a pawl spring, and wherein said pawl spring biases pawl into engagement with said rack.

Claim 29: The apparatus of claim 28, further comprising a first and a second post connected to an interior side of said handle portion, said first and said second posts configured to support said pawl spring.

- 5 Claim 30: An apparatus for application of surgical clips to body tissue, which comprises:
- a) a handle portion;
 - b) a body extending distally from the handle portion and defining a longitudinal axis;
 - 10 c) a plurality of surgical clips disposed within the body;
 - d) a jaw assembly mounted adjacent a distal end portion of the body, the jaw assembly including first and second jaw portions movable between a spaced-apart and an approximated position;
 - e) a clip pusher configured to individually distally advance a surgical clip to the
 - 15 jaw assembly while the jaw portions are in the spaced apart position;
 - f) an actuator at least partially disposed within the body and longitudinally movable in response to actuation of the handle portion;
 - g) a jaw closure member positioned adjacent the first and second jaw portions to
 - move the jaw portions to the approximated position, wherein the body portion has an outer
 - 20 diameter, and wherein said jaw assembly has a width in the spaced apart position; wherein said width is less than or equal to said outer diameter of said body.

Claim 31: The apparatus of claim 30, wherein said body has a length, said length suitable to facilitate use in bariatric surgery.

Claim 32: The apparatus of claim 31, wherein said length is greater than thirty
5 centimeters.




FIG. 1




FIG. 2

FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D










FIG. 7












FIG. 10








FIG. 11

FIG. 12




FIG. 13




FIG. 15

FIG. 14




FIG. 16





FIG. 17











FIG. 21














FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40




FIG. 41





FIG. 42

FIG. 42A






FIG. 45





FIG. 46





FIG. 47






FIG. 50

FIG. 51




FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57




FIG. 58




FIG. 59




FIG. 60




FIG. 61




FIG. 62




FIG. 63




FIG. 64




FIG. 65




FIG. 66




FIG. 67




FIG. 68





FIG. 69






FIG. 70




FIG. 71




FIG. 72




FIG. 73




FIG. 74

FIG. 75




FIG. 76




FIG. 77




FIG. 78




FIG. 79




FIG. 80




FIG. 81




FIG. 82





FIG. 83






FIG. 87




FIG. 88




FIG. 89