



US009604002B2

(12) **United States Patent**
Booth et al.

(10) **Patent No.:** **US 9,604,002 B2**
(45) **Date of Patent:** **Mar. 28, 2017**

(54) **INSULIN MANAGEMENT**

FOREIGN PATENT DOCUMENTS

(71) Applicant: **Aseko, Inc.**, Greenville, SC (US)

AU 199460325 A 8/1994
AU 2009283013 A1 2/2010

(72) Inventors: **Robert C. Booth**, Columbus, NC (US);
Harry Hebblewhite, Atlanta, GA (US)

(Continued)

(73) Assignee: **Aseko, Inc.**, Greenville, SC (US)

OTHER PUBLICATIONS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

Kim, Sarah et al., Hyperglycemia control of the Nil per os patient in the intensive care unit: Introduction of a simple subcutaneous insulin algorithm, Journal of Diabetes Science and Technology, Nov. 2012, vol. 6, Issue 6, pp. 1413-1419.

(Continued)

(21) Appl. No.: **15/272,972**

(22) Filed: **Sep. 22, 2016**

(65) **Prior Publication Data**

US 2017/0007761 A1 Jan. 12, 2017

Primary Examiner — Scott Medway

(74) Attorney, Agent, or Firm — Honigman Miller Schwartz and Cohn LLP

Related U.S. Application Data

(62) Division of application No. 14/511,060, filed on Oct. 9, 2014, now Pat. No. 9,486,580.
(Continued)

(51) **Int. Cl.**

A61M 5/172 (2006.01)

A61B 5/145 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **A61M 5/1723** (2013.01); **A61B 5/14532**
(2013.01); **A61B 5/4839** (2013.01); **A61M**
2005/14296 (2013.01)

(58) **Field of Classification Search**

CPC ... A61B 5/14532; A61B 5/742; A61B 5/1118;
A61B 5/4839; A61B 5/0432;
(Continued)

(56) **References Cited**


U.S. PATENT DOCUMENTS

561,422 A 6/1896 Minnis
4,055,175 A 10/1977 Clemens et al.
(Continued)

(57) **ABSTRACT**

A method of managing insulin includes receiving blood glucose measurements on a computing device from a glucometer. The blood glucose measurements are separated by a time interval. The method includes determining, using the computing device, an insulin dose rate based on the blood glucose measurements and determining a blood glucose drop rate based on the blood glucose measurements and the time interval. The method also includes determining a blood glucose percentage drop based on the blood glucose measurements. The method includes decreasing the time interval between blood glucose measurements by the glucometer when the blood glucose drop rate is greater than a threshold drop rate, and decreasing the time interval between blood glucose measurements by the glucometer when the blood glucose percentage drop is greater than a threshold percentage drop.

15 Claims, 20 Drawing Sheets



Related U.S. Application Data							
(60)	Provisional application No. 61/934,300, filed on Jan. 31, 2014.			7,901,625	B2	3/2011	Brown
				7,904,310	B2	3/2011	Brown
				7,912,688	B2	3/2011	Brown
				7,920,998	B2	4/2011	Brown
				7,949,507	B2	5/2011	Brown
(51)	Int. Cl. <i>A61B 5/00</i> (2006.01) <i>A61M 5/142</i> (2006.01)			7,985,848	B2	7/2011	Woo et al.
				8,088,731	B2	1/2012	Knudsen et al.
				8,117,020	B2	2/2012	Abensour et al.
				8,185,412	B1	5/2012	Harpale
				8,198,320	B2	6/2012	Liang et al.
(58)	Field of Classification Search CPC G06F 19/322; G06F 17/30312; G06F 17/30386; G06F 19/3456; A61M 5/1723; A61M 2205/3584; A61M 2230/201; A61M 2205/50; A61M 2205/52; A61M 2205/502; A61M 1/1603; A61M 2205/35 See application file for complete search history.			8,204,729	B2	6/2012	Sher
				8,206,340	B2	6/2012	Arefieg
				8,257,300	B2	9/2012	Budiman et al.
				8,257,735	B2	9/2012	Lau et al.
				8,318,221	B2	11/2012	Miller et al.
				8,329,232	B2	12/2012	Cheng et al.
				8,333,752	B2	12/2012	Veit et al.
				8,370,077	B2	2/2013	Bashan et al.
				8,398,616	B2	3/2013	Budiman
				8,420,125	B2	4/2013	Webster et al.
				8,420,621	B2	4/2013	Lai et al.
				8,457,901	B2	6/2013	Beshan et al.
				8,527,208	B2	9/2013	Prud'homme et al.
				8,532,933	B2	9/2013	Duke et al.
		(56)	References Cited U.S. PATENT DOCUMENTS			8,548,544	B2
				8,571,801	B2	10/2013	Anfinen et al.
				8,579,879	B2	11/2013	Palerm et al.
				8,600,682	B2	12/2013	Bashan et al.
				8,635,054	B2	1/2014	Brown
		8,679,016	B2	3/2014	Mastrototaro et al.		
		8,690,934	B2	4/2014	Boyden et al.		
		8,700,161	B2	4/2014	Harel et al.		
		8,703,183	B2	4/2014	Lara		
		8,718,949	B2	5/2014	Blomquist et al.		
		8,755,938	B2	6/2014	Weinert et al.		
		8,766,803	B2	7/2014	Bousamra et al.		
		8,828,390	B2	9/2014	Herrera et al.		
		8,834,367	B2	9/2014	Laan et al.		
		8,870,807	B2	10/2014	Mantri et al.		
		8,911,367	B2	12/2014	Brister et al.		
		8,919,180	B2	12/2014	Gottlieb et al.		
		8,992,464	B2	3/2015	Bashan et al.		
		2001/0002269	A1	5/2001	Zhao		
		2003/0028089	A1	2/2003	Galley et al.		
		2003/0050621	A1	3/2003	Lebel et al.		
		2003/0199445	A1	10/2003	Knudsen et al.		
		2003/0208110	A1	11/2003	Mault et al.		
		2004/0042272	A1	3/2004	Kurata		
		2004/0044272	A1	3/2004	Moerman et al.		
		2004/0054263	A1	3/2004	Moerman et al.		
		2005/0020681	A1	1/2005	Takayama et al.		
		2005/0049179	A1	3/2005	Davidson et al.		
		2005/0054818	A1	3/2005	Brader et al.		
		2005/0055010	A1	3/2005	Pettis et al.		
		2005/0096637	A1	5/2005	Heruth		
		2005/0171503	A1	8/2005	Van Den Berghe et al.		
		2005/0176621	A1	8/2005	Brader et al.		
		2005/0177398	A1	8/2005	Watanabe et al.		
		2005/0187749	A1	8/2005	Singley		
		2005/0192494	A1	9/2005	Ginsberg		
		2005/0192557	A1	9/2005	Brauker et al.		
		2005/0197621	A1	9/2005	Poulsen et al.		
		2005/0267195	A1	12/2005	Mikoshiba et al.		
		2005/0272640	A1	12/2005	Doyle et al.		
		2006/0040003	A1	2/2006	Needleman et al.		
		2006/0078593	A1	4/2006	Strozier et al.		
		2006/0160722	A1	7/2006	Green et al.		
		2006/0173260	A1	8/2006	Gaoni et al.		
		2006/0188995	A1	8/2006	Ryan et al.		
		2006/0224109	A1	10/2006	Steil et al.		
		2006/0264895	A1	11/2006	Flanders		
		2007/0036872	A1	2/2007	Tsuboi et al.		
		2007/0060796	A1	3/2007	Kim		
		2007/0078314	A1	4/2007	Grounsell et al.		
		2007/0078818	A1	4/2007	Zivitz et al.		
		2007/0160678	A1	7/2007	Guimberteau et al.		
		2007/0168224	A1	7/2007	Letzt et al.		
		2007/0249916	A1	10/2007	Pesach et al.		
		2007/0282186	A1	12/2007	Gilmore		

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0293742	A1	12/2007	Simonsen et al.
2008/0097289	A1	4/2008	Steil et al.
2008/0119421	A1	5/2008	Tuszynski et al.
2008/0119705	A1	5/2008	Patel et al.
2008/0139511	A1	6/2008	Friesen
2008/0139907	A1	6/2008	Rao et al.
2008/0172030	A1	7/2008	Blomquist
2008/0188796	A1	8/2008	Steil et al.
2008/0214919	A1	9/2008	Harmon et al.
2008/0228056	A1	9/2008	Blomquist et al.
2008/0234943	A1	9/2008	Ray et al.
2008/0255707	A1	10/2008	Hebblewhite et al.
2008/0269585	A1	10/2008	Ginsberg
2008/0299079	A1	12/2008	Meezan et al.
2008/0306353	A1	12/2008	Douglas et al.
2009/0029933	A1	1/2009	Velloso et al.
2009/0036753	A1	2/2009	King
2009/0054753	A1	2/2009	Robinson et al.
2009/0069636	A1	3/2009	Zivitz et al.
2009/0099438	A1	4/2009	Flanders
2009/0110752	A1	4/2009	Shang et al.
2009/0214511	A1	8/2009	Tran et al.
2009/0227514	A1	9/2009	Oben
2009/0239944	A1	9/2009	D'orazio et al.
2009/0240127	A1	9/2009	Ray
2009/0242399	A1	10/2009	Kamath et al.
2009/0247982	A1	10/2009	Krulevitch et al.
2009/0253970	A1	10/2009	Bashan et al.
2009/0253973	A1	10/2009	Bashan et al.
2009/0281519	A1	11/2009	Rao et al.
2009/0299152	A1	12/2009	Taub et al.
2009/0312250	A1	12/2009	Ryu et al.
2010/0016700	A1	1/2010	Sieh et al.
2010/0035795	A1	2/2010	Boss et al.
2010/0137788	A1	6/2010	Braithwaite et al.
2010/0160740	A1	6/2010	Cohen et al.
2010/0161236	A1	6/2010	Cohen et al.
2010/0161346	A1	6/2010	Getschmann et al.
2010/0168660	A1	7/2010	Galley et al.
2010/0198142	A1	8/2010	Sloan et al.
2010/0256047	A1	10/2010	Sieh et al.
2010/0262434	A1	10/2010	Shaya
2010/0286601	A1	11/2010	Yodfat et al.
2010/0305545	A1	12/2010	Kanderian, Jr. et al.
2010/0324382	A1	12/2010	Cantwell et al.
2010/0331652	A1	12/2010	Groll et al.
2010/0331654	A1	12/2010	Jerdonek et al.
2010/0332142	A1	12/2010	Shadforth et al.
2011/0021894	A1	1/2011	Mohanty et al.
2011/0071365	A1	3/2011	Lee et al.
2011/0071464	A1	3/2011	Palerm
2011/0098548	A1	4/2011	Budiman et al.
2011/0115894	A1	5/2011	Burnett
2011/0119081	A1	5/2011	Vespasiani
2011/0152830	A1	6/2011	Ruchti et al.
2011/0178008	A1	7/2011	Arai et al.
2011/0213332	A1	9/2011	Mozayeny
2011/0217396	A1	9/2011	Oldani
2011/0218489	A1	9/2011	Mastrototaro et al.
2011/0229602	A1	9/2011	Aymard et al.
2011/0286984	A1	11/2011	Huang
2011/0305771	A1	12/2011	Sampalis
2011/0313674	A1	12/2011	Duke et al.
2011/0319322	A1	12/2011	Bashan et al.
2012/0003339	A1	1/2012	Minacapelli
2012/0022353	A1	1/2012	Bashan et al.
2012/0046606	A1	2/2012	Arefieg
2012/0053222	A1	3/2012	Gorrell et al.
2012/0058942	A1	3/2012	Dupre
2012/0065482	A1	3/2012	Robinson et al.
2012/0095311	A1	4/2012	Ramey et al.
2012/0123234	A1	5/2012	Atlas et al.
2012/0197358	A1	8/2012	Prescott
2012/0213886	A1	8/2012	Gannon et al.
2012/0227737	A1	9/2012	Mastrototaro et al.
2012/0232519	A1	9/2012	Georgiou et al.
2012/0232520	A1	9/2012	Sloan et al.
2012/0238853	A1	9/2012	Arefieg
2012/0244096	A1	9/2012	Xie et al.
2012/0295985	A1	11/2012	Miller et al.
2013/0022592	A1	1/2013	Vaughn et al.
2013/0030358	A1	1/2013	Yodfat et al.
2013/0052285	A1	2/2013	Song et al.
2013/0109620	A1	5/2013	Riis et al.
2013/0144283	A1	6/2013	Barman
2013/0158503	A1	6/2013	Kanderian, Jr. et al.
2013/0165901	A1	6/2013	Ruchti et al.
2013/0190583	A1	7/2013	Grosman et al.
2013/0225683	A1	8/2013	Gagnon et al.
2013/0233727	A1	9/2013	Tsai et al.
2013/0245547	A1	9/2013	El-Khatib et al.
2013/0267796	A1	10/2013	Enric Monte Moreno
2013/0281796	A1	10/2013	Pan
2013/0282301	A1	10/2013	Rush
2013/0289883	A1	10/2013	Bashan et al.
2013/0309750	A1	11/2013	Tajima et al.
2013/0316029	A1	11/2013	Pan et al.
2013/0317316	A1	11/2013	Kandeel
2013/0331323	A1	12/2013	Wu et al.
2013/0338209	A1	12/2013	Gambhire et al.
2013/0345664	A1	12/2013	Beck et al.
2014/0000338	A1	1/2014	Luo et al.
2014/0004211	A1	1/2014	Choi et al.
2014/0024907	A1	1/2014	Howell et al.
2014/0037749	A1	2/2014	Shea et al.
2014/0057331	A1	2/2014	Tajima et al.
2014/0066735	A1	3/2014	Engelhardt et al.
2014/0066888	A1	3/2014	Parikh et al.
2014/0081196	A1	3/2014	Chen
2014/0128706	A1	5/2014	Roy
2014/0170123	A1	6/2014	Alam et al.
2014/0178509	A1	6/2014	Jia
2014/0179629	A1	6/2014	Hamaker et al.
2014/0194788	A1	7/2014	Muehlbauer et al.
2014/0213963	A1	7/2014	Wu et al.
2014/0296943	A1	10/2014	Maxik et al.
2014/0303466	A1	10/2014	Fitzpatrick et al.
2014/0303552	A1	10/2014	Kanderian, Jr. et al.
2014/0337041	A1	11/2014	Madden et al.
2014/0347491	A1	11/2014	Connor
2014/0349256	A1	11/2014	Connor
2014/0349257	A1	11/2014	Connor
2014/0356420	A1	12/2014	Huang
2014/0363794	A1	12/2014	Angelides
2014/0365534	A1	12/2014	Bousamra et al.
2014/0378381	A1	12/2014	Chen et al.
2014/0378793	A1	12/2014	Kamath et al.
2015/0018633	A1	1/2015	Kovachev et al.
2015/0025496	A1	1/2015	Imran
2015/0025903	A1	1/2015	Mueller-Wolf
2015/0031053	A1	1/2015	Moerman
2015/0037406	A1	2/2015	Bernabeu Martinez et al.

FOREIGN PATENT DOCUMENTS

AU	2010330746	A1	7/2012
CA	2519249	A1	10/2004
CA	2670512	A1	7/2008
CA	2720302	A1	12/2009
CA	2720304	A1	12/2009
CA	2733593	A1	2/2010
CA	2752637	A1	9/2010
CA	2761647	A1	12/2010
CA	2766944	A1	1/2011
CA	2784143	A1	6/2011
CN	102016855	A	4/2011
CN	102016906	A	4/2011
CN	102300501	A	12/2011
CN	102395310	A	3/2012
CN	102481101	A	5/2012
CN	102946804	A	2/2013
DE	1082412	T1	10/2001
EP	461207	A1	12/1991
EP	483595	A2	5/1992

(56)

References Cited

FOREIGN PATENT DOCUMENTS

EP	557350	A1	9/1993	EP	2745225	A2	6/2014
EP	573499	A1	12/1993	EP	2760335	A1	8/2014
EP	768043	A2	4/1997	EP	2763722	A2	8/2014
EP	862648	A1	9/1998	EP	2798548	A1	11/2014
EP	910578	A2	4/1999	EP	2822647	A1	1/2015
EP	925792	A2	6/1999	JP	04800928	B2	10/2011
EP	1017414	A1	7/2000	KR	2011052664	A	5/2011
EP	1030557	A1	8/2000	KR	2012047841	A	5/2012
EP	1051141	A1	11/2000	RU	2011109016	A	9/2012
EP	1067925	A1	1/2001	WO	WO-9219260	A1	11/1992
EP	1082412	A2	3/2001	WO	WO-9609823	A1	4/1996
EP	1115389	A1	7/2001	WO	WO-9944496	A1	9/1999
EP	483595		12/2001	WO	WO-9963101	A2	12/1999
EP	1173482	A1	1/2002	WO	WO-02036139		5/2002
EP	1185321	A1	3/2002	WO	WO-03024468		3/2003
EP	1196445	A1	4/2002	WO	WO-03077895		9/2003
EP	1214596	A1	6/2002	WO	WO-03094927		11/2003
EP	1305018	A1	5/2003	WO	WO-2004084820	A2	10/2004
EP	1317190	A2	6/2003	WO	WO-2005041022	A1	5/2005
EP	1382363	A1	1/2004	WO	WO-2005081119	A2	9/2005
EP	1424074	A1	6/2004	WO	WO-2005081170	A2	9/2005
EP	1482919	A1	12/2004	WO	WO-2005081171	A2	9/2005
EP	1581095	A2	10/2005	WO	WO-2005081173	A1	9/2005
EP	1610758	A2	1/2006	WO	WO-2005110222	A1	11/2005
EP	1679009	A1	7/2006	WO	WO-2006022619	A2	3/2006
EP	1698898	A2	9/2006	WO	WO-2006022629	A1	3/2006
EP	1773860	A1	4/2007	WO	WO-2006022633	A1	3/2006
EP	1846002	A1	10/2007	WO	WO-2006022634	A1	3/2006
EP	1885392	A2	2/2008	WO	WO-2006022636	A1	3/2006
EP	1915171	A2	4/2008	WO	WO-2006022638	A1	3/2006
EP	1921981	A2	5/2008	WO	WO-2006044556	A2	4/2006
EP	2114491	A1	11/2009	WO	WO-03101177		7/2006
EP	2129277	A2	12/2009	WO	WO-2006079124	A2	7/2006
EP	2139393	A2	1/2010	WO	WO-2006091918	A2	8/2006
EP	2170430	A2	4/2010	WO	WO-2006130901	A1	12/2006
EP	2257218	A2	12/2010	WO	WO-2007116226	A2	10/2007
EP	2260423	A2	12/2010	WO	WO-2007149533	A2	12/2007
EP	2260462	A2	12/2010	WO	WO-2008005761	A2	1/2008
EP	2276405	A1	1/2011	WO	WO-2008013324	A1	1/2008
EP	2300046	A2	3/2011	WO	WO-2008057213	A2	5/2008
EP	2328608	A2	6/2011	WO	WO-2008057384	A2	5/2008
EP	2352456	A1	8/2011	WO	WO-2008067245	A2	6/2008
EP	2355669	A2	8/2011	WO	WO-2008088490	A1	7/2008
EP	2377465	A1	10/2011	WO	WO-2008112078	A2	9/2008
EP	2384750	A1	11/2011	WO	WO-2008124478	A1	10/2008
EP	2393419	A1	12/2011	WO	WO-2009002455	A1	12/2008
EP	2400882	A1	1/2012	WO	WO-2009005960	A2	1/2009
EP	2418972	A1	2/2012	WO	WO-2009075925	A1	6/2009
EP	2442719	A2	4/2012	WO	WO-2009139486	A1	11/2009
EP	2448432	A1	5/2012	WO	WO-2009146119	A2	12/2009
EP	2448468	A1	5/2012	WO	WO-2009146121	A2	12/2009
EP	2448469	A2	5/2012	WO	WO-2010021879	A2	2/2010
EP	2482712	A1	8/2012	WO	WO-2010056718	A2	5/2010
EP	2516671	A1	10/2012	WO	WO-2010075350	A1	7/2010
EP	2518655	A2	10/2012	WO	WO-2010089304	A1	8/2010
EP	2525863	A1	11/2012	WO	WO-2010089305	A1	8/2010
EP	2535831	A1	12/2012	WO	WO-2010089306	A1	8/2010
EP	2552313	A2	2/2013	WO	WO-2010089307	A1	8/2010
EP	2582297	A1	4/2013	WO	WO-2010091102	A1	8/2010
EP	2585133	A1	5/2013	WO	WO-2010097796	A1	9/2010
EP	2590559	A2	5/2013	WO	WO-2010135646	A1	11/2010
EP	2596448	A1	5/2013	WO	WO-2010147659	A2	12/2010
EP	2603133	A1	6/2013	WO	WO-2011008520	A2	1/2011
EP	2605819	A1	6/2013	WO	WO-2011037607	A2	3/2011
EP	2640373	A1	9/2013	WO	WO-2011075687	A1	6/2011
EP	2641084	A1	9/2013	WO	WO-2011089600	A1	7/2011
EP	2644088	A1	10/2013	WO	WO-2011094352	A1	8/2011
EP	2654777	A2	10/2013	WO	WO-2011157402	A1	12/2011
EP	2659407	A1	11/2013	WO	WO-2012023964	A1	2/2012
EP	2666369	A1	11/2013	WO	WO-2012047800	A1	4/2012
EP	2685895	A1	1/2014	WO	WO-2012065556	A1	5/2012
EP	2720713	A2	4/2014	WO	WO-2012097064	A1	7/2012
EP	2736404	A1	6/2014	WO	WO-2012122520	A1	9/2012
EP	2742447	A2	6/2014	WO	WO-2012148252	A2	11/2012
EP	2742449	A2	6/2014	WO	WO-2012161670	A2	11/2012
				WO	WO-2012177963	A1	12/2012
				WO	WO-2013040712	A1	3/2013
				WO	WO-2013050309	A1	4/2013
				WO	WO-2013086372	A1	6/2013

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO-2013096769	A1	6/2013
WO	WO-2013108262	A1	7/2013
WO	WO-2013134548	A2	9/2013
WO	WO-2013172833	A1	11/2013
WO	WO-2013177565	A1	11/2013
WO	WO-2014011488	A2	1/2014
WO	WO-2014012084	A1	1/2014
WO	WO-2014023834	A2	2/2014
WO	WO-2014024201	A1	2/2014
WO	WO-2014028607	A1	2/2014
WO	WO-2014068007	A1	5/2014
WO	WO-2014075135		5/2014
WO	WO-2014075135	A1	5/2014
WO	WO-2014099829		6/2014
WO	WO-2014099829	A1	6/2014
WO	WO-2014106263	A2	7/2014
WO	WO-2014145049	A2	9/2014
WO	WO-2014149535		9/2014
WO	WO-2014149535	A1	9/2014
WO	WO-2014149781	A1	9/2014
WO	WO-2014152704	A1	9/2014
WO	WO-2014162549	A1	10/2014
WO	WO-2014162549	A1	10/2014
WO	WO-2014164226	A2	10/2014

WO	WO-2014179171	A1	11/2014
WO	WO-2014187812	A1	11/2014
WO	WO-2014190231	A1	11/2014
WO	WO-2014202024	A1	12/2014
WO	WO-2014209630	A2	12/2014
WO	WO-2014209634	A1	12/2014

OTHER PUBLICATIONS

Vaidya, Anand et al., "Improving the management of diabetes in hospitalized patients: The result of a computer-based house staff training program", *Diabetes Technology & Therapeutics*, 2012, vol. 14, No. 7, pp. 610-618.

Lee, Joshua et al., "Indication-based ordering: A new paradigm for glycemic control in hospitalized inpatients", *Journal of Diabetes Science and Technology*, May 2008, vol. 2, Issue 3, pp. 349-356.

Nau, Konrad C. et al., "Glycemic Control in hospitalized patients not in intensive care: Beyond sliding-scale insulin", *American Family Physician*, May 1, 2010, vol. 81, No. 9, pp. 1130-1133.

International Search Report and Written Opinion for Application No. PCT/US2015/011559 dated Apr. 29, 2015.

International Search Report and Written Opinion for Application No. PCT/US2015/011086 dated Apr. 29, 2015.

International Search Report and Written Opinion for Application No. PCT/US2015/011574 dated Apr. 24, 2015.





FIG. 1A






FIG. 2A

New Patient Information

Name:	John Doe
Height:	5' 8"
Weight:	210
Date of Birth:	4/10/1938
Diabetes History	
Age:	75
Other:	

IV
SubQ

208a
116,146

FIG. 2B

New Patient Information						
Patient Name				Patient ID	Room	
209	Adkins, Frankie	IV	SubQ	704563	502	208a
	Anderson, Mike	IV	SubQ	705648	504	116,146
	Anton, Mike	IV	SubQ	712546	302	
	Briggs, George	IV	SubQ	702589	308	
	Brown, Dan	IV	SubQ	701112	506	
	Brown, Paul	IV	SubQ	709895	404	
	Burchfield, John	IV	SubQ	712544	412	

FIG. 2C

204a

Initial IV Dosing Information

Initial Multiplier: _____

Target Range:
Low Limit: _____
High Limit: _____

IV Meal Bolus ☐ ☐
 enable disable

Standard Hospital meal: 60 gms of carbohydrate

FIG. 2D




FIG. 3




FIG. 4A




FIG. 4B




FIG. 4C

Current Patient 116,146

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938 208a

Please enter the current blood glucose value

Enter BG Value: mg/dl

Re-Enter BG Value: mg/dl

Is this a pre-meal BG? ☒ Yes ☐ No

Meal Plan-Number of Carbs Per Meal:

230, 230c

Cancel Continue

Caution: Physician order required

FIG. 4D

Current Patient 116,146

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938 208a

230, 230c

Current Insulin 1.2 Units/hr	Last BG 119 mg/dl
Target Range 90-120 mg/dl	Insulin Concentration 90-120 mg/dl

57:33 430

Enter BG 436

Start Meal 438

FIG. 4E




FIG. 5A




FIG. 5B

FIG. 5C is a screenshot of a mobile application interface titled "Enter Blood Glucose Value". The interface is divided into several sections. At the top, there is a header bar with the title. Below the header, there is a patient information section containing fields for Name (John Doe), Room (302 (ER)), Patient ID (7045162), and Date of Birth (4/10/1938). Below this, there is a section titled "Please enter the current blood glucose value". This section contains three input fields: "Enter BG Value:" (with a unit of mg/dl), "Re-Enter BG Value:" (with a unit of mg/dl), and "Meal Plan-Number of Carbs Per Meal:" (with a value of 60). At the bottom of the screen, there are two buttons: "Cancel" and "Continue". A caution message "Caution: Physician order required" is displayed at the very bottom. Reference numerals 116,146, 208a, 230, and 230c are used to identify specific elements of the interface.

Enter Blood Glucose Value

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938

Please enter the current blood glucose value

Enter BG Value: mg/dl
Re-Enter BG Value: mg/dl
Meal Plan-Number of Carbs Per Meal:

Cancel Continue

Caution: Physician order required

FIG. 5C

FIG. 5D is a screenshot of a mobile application interface titled "Current Patient". The interface is divided into several sections. At the top, there is a header bar with the title. Below the header, there is a patient information section containing fields for Name (John Doe), Room (302 (ER)), Patient ID (7045162), and Date of Birth (4/10/1938). Below this, there is a section titled "Current Patient" which contains a table of patient data. The table has four columns: "Current Insulin", "Last BG", "Target Range", and "Insulin Concentration". The data in the table is as follows:

Current Insulin	Last BG	Target Range	Insulin Concentration
1.2 Units/hr	119 mg/dl	90-120 mg/dl	90-120 mg/dl

Below the table, there is a large digital display showing the time 57:33. To the right of the time display, there are three buttons: "Enter BG", "Start Meal", and "Meal Bolus Activated". Reference numerals 116,146, 208a, 230, 230c, 430, 436, 438, and 440 are used to identify specific elements of the interface.

Current Patient

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938

Current Insulin	Last BG	Target Range	Insulin Concentration
1.2 Units/hr	119 mg/dl	90-120 mg/dl	90-120 mg/dl

57:33

Enter BG
Start Meal
Meal Bolus Activated

FIG. 5D

Enter Blood Glucose Value

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938

Did the Patient Eat?

☐ Yes ☒ No

Cancel Continue

FIG. 5E

Enter Blood Glucose Value

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938

Did the Patient Eat?

☒ Yes ☐ No

How much did the Patient eat?

☐ 25% of Meal ☐ 50% of Meal
☐ 75% of Meal ☐ 100% of Meal
☒ Actual Number of Carbs:

Cancel Continue

FIG. 5F




FIG. 6A





FIG. 6B



Start SUBQ Patients

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938

Transition Patient to SubQ

Warning:
The A1C value of this patient is less than 6. Normally a patient with an A1C of less than 6 does not need to be transitioned to SubQ insulin therapy.


Are you sure you want to continue?

Caution: Physician order required

116,146

208a

FIG. 6C



Start SUBQ Patients

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938

After SubQ Transition:

☐ Continue patient on Glucomander SubQ
☐ Discontinue patient from Glucomander

Caution: Physician order required

116,146

208a

FIG. 6D

Start SUBQ Patients 116,146

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938 208a

After SubQ Transition:
☐ Continue patient on Glucomander SubQ
☐ Discontinue patient on Glucomander SubQ

Orderset
Type: Basal/Bolus + Correction ▼

Diabetes: Yes ▼ Basal Insulin: Lantus ▼

Basal % of TDD: 50% ▼ Daily Basal Distribution: 1 Dose Per Day ▼

Bolus % of TDD: 50% ▼ Basal Time: 00:00 ▼

Bolus Insulin: Novolog ▼

Caution: Physician order required

617

FIG. 6E

Start SUBQ Patients 116,146

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938 208a

Transition Patient to SubQ

Inject Patient With: 5 Units of Lantus Give Now ☐
Modify Dose Give Later ☐

WARNING:
Do not D/C insulin. System will prompt for hourly blood glucose checks... ☐

Caution: Physician order required

FIG. 6F

Transition Patient to SUBQ 116,146

Name: John Doe Room: 302 (ER)
Patient ID: 7045162 Date of Birth: 4/10/1938 208a

Transition Patient to SubQ

Discontinue IV Insulin ☐

WARNING: ☐
Patient is stable. Discontinue IV insulin to prevent hypoglycemia.

Note: Make sure potassium (K) is greater than 4.0...

Caution: Physician order required

FIG. 6G




FIG. 7

1

INSULIN MANAGEMENT**CROSS REFERENCE TO RELATED APPLICATIONS**

This U.S. patent application is a divisional of, and claims priority under 35 U.S.C. §121 from, U.S. patent application Ser. No. 14/511,060, filed on Oct. 9, 2014, which claims priority under 35 U.S.C. §119(e) to U.S. Provisional Application 61/934,300, filed on Jan. 31, 2014. The disclosures of these prior applications are considered part of the disclosure of this application and are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

This disclosure relates to a system for managing insulin administration or insulin dosing.

BACKGROUND

Today, nearly 40% of patients admitted to acute care hospitals in the United States experience either hyperglycemia or hypoglycemia, both serious medical conditions. Many of these patients have diabetes while others have fluctuating blood sugars due to trauma, drug reactions, stress and other factors. Nurses and doctors managing these patients manually calculate insulin doses using complex paper protocols.

Manual calculation may not be accurate due to human error, which can lead to patient safety issues. Different institutions use multiple and sometimes conflicting protocols to manually calculate an insulin dosage. Moreover, the protocols may include extra paperwork that nurses and physicians have to manage, which in turn leads to workflow inefficiencies, additional operating costs, and employee satisfaction issues. SCIP (Surgical Care Improvement Project) scores, length of stay, readmission and even mortality rates adversely affect sub-optimal glycemic management.

The prevalent method of regulating continuous intravenous insulin infusion is by using a set of written instructions, known as a paper protocol. Paper protocols often involve a tree of conditional statements and some use of tables of numbers, for which a given blood glucose value dictates the use of a different column of insulin rates. The complexity of these paper protocols multiplies the probability of error by the nurses using them. These errors can lead to hypoglycemic events.

SUMMARY

One aspect of the disclosure provides a method of managing insulin. The method includes receiving blood glucose measurements on a computing device from a glucometer. The blood glucose measurements are separated by a time interval. For each time interval, the method includes determining, using the computing device, an intravenous insulin infusion rate based on the blood glucose measurements of the time interval. The method further includes determining, using the computing device, a blood glucose percentage drop based on the blood glucose measurements (e.g., between a current blood glucose measurement and a previous blood glucose measurement). The method further includes determining, using the computing device, a blood glucose drop rate based on the blood glucose measurements and the time interval. The method also includes decreasing the time interval between blood glucose measurements by

2

the glucometer when the blood glucose percentage drop is greater than a threshold percentage drop and decreasing the time interval between blood glucose measurements by the glucometer when the blood glucose drop rate is greater than a threshold drop rate. The method further includes sending the intravenous insulin infusion rate from the computing device to an insulin administration device.

Implementations of the disclosure may include one or more of the following optional features. In some implementations, the method includes setting the time interval between the blood glucose measurements by the glucometer to a default time interval or a minimum of a preconfigured hypoglycemia time interval when a current blood glucose measurement is less than a threshold hypoglycemia blood glucose value. The method includes setting the time interval to a minimum of a preconfigured short time interval when the current blood glucose measurement is greater than the threshold hypoglycemia blood glucose value and less than a lower limit of a blood glucose target range and the blood glucose percentage drop is greater than a low blood glucose percentage drop limit or the current blood glucose measurement is greater than or equal to the lower limit of the blood glucose target range and the blood glucose percentage drop is greater than a regular blood glucose percentage drop limit. In some examples, the method includes setting the time interval to a minimum of a preconfigured blood glucose drop rate time interval when the blood glucose drop rate is greater than a blood glucose drop rate limit, a preconfigured long time interval when the blood glucose measurements have been within the blood glucose target range for a duration of time greater than a stable time period or a preconfigured meal bolus time interval when a meal bolus program is in operation. The preconfigured hypoglycemia time interval is less than the short time interval, the short time interval is less than the blood glucose drop rate time interval, the blood glucose drop rate time interval is less than the long time interval, and the meal bolus time interval is less than the long time interval.

In some examples, the method includes leaving the multiplier unchanged between time intervals when the current blood glucose measurement is greater than an upper limit of a blood glucose target range and a ratio of the current blood glucose measurement divided by a previous blood glucose measurement is less than or equal to a threshold ratio. The method further includes multiplying the multiplier by a change factor when the current blood glucose measurement divided by the previous blood glucose measurement is greater than the threshold ratio. Additionally or alternatively, the method may include the constant being equal to 60 mg/dl and the threshold ratio being equal to 0.85. The method may further include dividing the multiplier by the change factor when the current blood glucose measurement is less than a lower limit of the blood glucose target range.

The method may further include, in response to receiving an indication of patient solid food consumption, increasing the intravenous insulin infusion rate and maintaining the multiplier unchanged for at least two time intervals. In some examples, the method includes receiving, at the computing device, a number of estimated grams of carbohydrates for a meal and determining, using the computing device, an estimated meal bolus in units of insulin based on the number of estimated grams of carbohydrates and a carbohydrate-insulin-ratio. The method may further include determining, using the computing device, an estimated meal bolus insulin rate, based on the estimated meal bolus, an available delivery time, and a configurable constant, and determining, using the computing device, a total insulin rate as a sum of

the intravenous insulin rate and the estimated meal bolus insulin rate. The method may further include sending the total insulin rate from the computing device to the insulin administration device. Additionally or alternatively, the method may include dividing a total meal time into meal time sub-intervals, a first meal time sub-interval starting with a pre-meal blood glucose measurement before receiving the indication of patient solid food consumption, and determining, using the computing device, the total insulin rate for each meal time sub-interval in succession.

In some examples, the method includes receiving, at the computing device, a number of actual grams of carbohydrates for the meal during a subsequent time interval after the first time interval and determining, using the computing device, an actual meal bolus based on the number of actual grams of carbohydrates. The method also includes, determining an estimated delivered meal bolus by multiplying the estimated meal bolus rate times an elapsed delivery time. The method may further include determining a remaining meal bolus in units of insulin, using the computing device, by subtracting a product of the estimated delivered meal bolus insulin rate and an actual delivery time from the actual meal bolus. In addition, the method may include determining, using the computing device, a revised meal bolus insulin rate as the remaining meal bolus divided by a time remaining in the total meal time and determining, using the computing device, a revised total insulin rate as a sum of the intravenous insulin rate and the revised meal bolus insulin rate. Further, the method may include sending the revised total insulin rate from the computing device to the insulin administration device. The method may also include decreasing the time interval to less than the default time interval for the one or more meal time sub-intervals.

In some implementations, the method includes electronically displaying on a display in communication with the computing device a warning and blocking transition to a subcutaneous administration of insulin when the current blood glucose measurement is outside a stability target range and electronically displaying on the display a warning when the current blood glucose measurement is within the stability target range for less than a threshold stability period of time. The method may further include determining, using the computing device, a total daily dose of insulin based on the multiplier when the current blood glucose measurement is within a stability target range for a threshold period of time. The method further includes determining, using the computing device, recommended insulin dose comprising a daily basal insulin and a daily meal insulin for subcutaneous therapy as an apportioning of the total daily dose of insulin, wherein the daily basal insulin is half of the total daily dose of insulin and the daily meal insulin is half of the total daily dose of insulin. Further, the method includes sending the recommended insulin doses from the computing device to a subcutaneous injection device or electronically displaying the recommended insulin doses on a display in communication with the computing device.

In some examples, when the blood glucose drops more than a threshold percent of its previous value, the method includes decreasing the time interval. This threshold percent is configured with two values: 1) a lower (more sensitive) value when the blood glucose is below the low limit of the target range but above the hypo-threshold; and 2) a higher (less stringent) value when the blood glucose is above the low limit of the target range. The method may include setting the time interval to a hypoglycemia time interval of between about 15 minutes and about 30 minutes when the

current blood glucose measurement is below the hypo-threshold blood glucose level.

Implementations of the disclosure may include one or more of the following features. In some implementations, the method determining the insulin dose rate using the current blood glucose measurement, a constant (e.g., 60 mg/dl), and a unit-less multiplier.

The method includes adjusting the multiplier as follows: a) multiplying the multiplier by a change factor when the current blood glucose measurement is greater than an upper limit of the blood glucose target range, and the ratio of the current blood glucose to the previous blood glucose is greater than a threshold-ratio; b) dividing the multiplier by a change factor when the current blood glucose measurement is less than a lower limit of the blood glucose target range; c) re-use the previous multiplier for two or more intervals starting at the manual initiation of a meal bolus infusion process; and d) leaving the multiplier unchanged between time intervals when none of conditions a, b, or c are applicable.

The method includes leaving the multiplier unchanged between time intervals when the current blood glucose measurement is greater than an upper limit of the blood glucose target range and the blood glucose drop rate is greater than or equal to a threshold rate of descent, and multiplying the multiplier by a change factor when the current blood glucose measurement is greater than an upper limit of the blood glucose target range and the blood glucose drop rate is less than the threshold rate of descent. Additionally or alternatively, the method includes dividing the multiplier by a change factor when the current blood glucose measurement is less than a lower limit of a blood glucose target range and leaving the multiplier unchanged between time intervals when the current blood glucose measurement is within the blood glucose target range. In some examples, the method includes leaving the multiplier unchanged for at least two subsequent time intervals when the current blood glucose measurement is a pre-meal measurement.

In some examples, a meal bolus infusion process allows for the calculation of mealtime insulin for patients consuming oral carbohydrates. These examples may include leaving the multiplier unchanged for at least two subsequent time intervals when the current blood glucose measurement is a pre-meal measurement. In some examples, the method includes receiving, on the computing device, a number of carbohydrates for a meal and determining, using the computing device, a meal bolus rate based on the number of carbohydrates and an intravenous insulin rate based on the blood glucose level. In addition, the method includes determining a Total Insulin Rate including the sum of the meal bolus rate and the intravenous insulin rate based on a blood glucose value. The method may further include setting the time interval to about 30 minutes immediately following the pre-meal blood glucose and for the next glucose measurement time interval. If the blood glucose measurement is a second consecutive measurement after an initial pre-meal blood glucose measurement, the method includes setting the time interval to about 60 minutes.

In some implementations, the method includes decreasing the time interval when the current blood glucose measurement is greater than or equal to the lower limit of the blood glucose target range and the blood glucose drop rate exceeds a threshold drop rate. The method may also include setting the time interval to a default value of about one hour when the current blood glucose measurement is greater than or equal to the lower limit of the blood glucose target range and the blood glucose drop rate is less than or equal to a

5

threshold drop rate. The method may include setting the time interval to a hypoglycemia time interval of between about 15 minutes and about 30 minutes, when the current blood glucose measurement is below the lower limit of the blood glucose target range and greater than a hypo-threshold blood glucose level.

In some implementations, the method includes decreasing the time interval when the current blood glucose measurement is below the lower limit of the blood glucose target range and below the hypo-threshold blood glucose level, and the blood glucose drop rate is less than or equal to a threshold drop rate. The method may also include setting the time interval to a default value of about one hour when the current blood glucose measurement is below the lower limit of the blood glucose target range and below the hypo-threshold blood glucose level, and the blood glucose drop rate is greater than the threshold drop rate.

In some examples, the method includes receiving, on the computing device, a number of carbohydrates per meal and determining, using the computing device, an intravenous insulin rate. In addition, the method includes determining, using the computing device, a meal bolus rate based on the number of carbohydrates and the insulin dose rate based on the intravenous insulin rate and the estimated meal bolus rate. The method may further include setting the time interval to about 30 minutes. If the blood glucose measurement is a second consecutive measurement after an initial pre-meal blood glucose measurement, the method includes setting the time interval to about 60 minutes.

In some implementations, the method includes a function to transition the insulin delivery method from an intravenous to subcutaneous basal-bolus regimen. The transition method provides doses and parameters for starting the patient on basal-bolus subcutaneous treatment. The transition method includes electronically displaying on a display a warning and blocking transition to a subcutaneous administration of insulin when the current blood glucose measurement is outside a stability target range. In addition, the method includes electronically displaying on the display a warning when the current blood glucose measurement is within the stability target range for less than a threshold stability period of time. In some examples, the method includes determining a total daily dose of insulin based on the multiplier when the current blood glucose measurement is within a stability target range for a threshold stability period of time.

Another aspect of the disclosure includes a system for managing insulin. The system includes a glucometer measuring blood glucose measurements separated by a time interval, an insulin administration device, and a dosing controller in communication with the glucometer and the insulin administration device. The dosing controller includes a computing device and non-transitory memory in communication with the computing device. The non-transitory memory stores instructions that when executed by the computing device cause the computing device to perform operations. The operations include receiving blood glucose measurements on a computing device from a glucometer, the blood glucose measurements separated by a time interval. For each time interval, the system includes determining, using the computing device, an intravenous insulin infusion rate based on the blood glucose measurements of the time interval and determining, using the computing device, a blood glucose percentage drop based on the blood glucose measurements (e.g., between a current blood glucose measurement and a previous blood glucose measurement). The system further includes determining, using the computing device, a blood glucose drop rate based on the blood glucose

6

measurements and the time interval and decreasing the time interval between blood glucose measurements by the glucometer when the blood glucose percentage drop is greater than a threshold percentage drop. The system further includes decreasing the time interval between blood glucose measurements by the glucometer when the blood glucose drop rate is greater than a threshold drop rate and sending the intravenous insulin infusion rate from the computing device to the insulin administration device.

In some implementations, the system operations further include setting the time interval between the blood glucose measurements by the glucometer to a default time interval or a minimum of a preconfigured hypoglycemia time interval when a current blood glucose measurement is less than a threshold hypoglycemia blood glucose value or a preconfigured short time interval. The minimum of a preconfigured short time interval is set when the current blood glucose measurement is greater than the threshold hypoglycemia blood glucose value and less than a lower limit of a blood glucose target range and the blood glucose percentage drop is greater than a low blood glucose percentage drop limit or the current blood glucose measurement is greater than or equal to the lower limit of the blood glucose target range and the blood glucose percentage drop is greater than a regular blood glucose percentage drop limit. Further, the operations include setting the time interval between the blood glucose measurements by the glucometer to a minimum of a preconfigured blood glucose drop rate time interval when the blood glucose drop rate is greater than a blood glucose drop rate limit or a preconfigured long time interval when the blood glucose measurements have been within the blood glucose target range for a duration of time greater than a stable time period, or a preconfigured meal bolus time interval when a meal bolus program is in operation. The preconfigured hypoglycemia time interval is less than the short time interval, the short time interval is less than the blood glucose drop rate time interval, the blood glucose drop rate time interval is less than the long time interval, and the meal bolus time interval is less than the long time interval.

In some examples, the operations further include leaving the multiplier unchanged between time intervals when the current blood glucose measurement is greater than an upper limit of a blood glucose target range and a ratio of the current blood glucose measurement divided by a previous blood glucose measurement is less than or equal to a threshold ratio. The system further includes multiplying the multiplier by a change factor when the current blood glucose measurement is greater than the upper limit of the blood glucose target range and the ratio of the current blood glucose measurement divided by the previous blood glucose measurement is greater than the threshold ratio. In some examples, the constant equals 60 mg/dl and the threshold ratio is 0.85. Additionally or alternatively, the operations may further include dividing the multiplier by the change factor when the current blood glucose measurement is less than a lower limit of the blood glucose target range. In some implementations, the operations further include, in response to receiving an indication of patient solid food consumption, increasing the intravenous insulin infusion rate and maintaining the multiplier unchanged for at least two time intervals.

The system may further include receiving, at the computing device, a number of estimated grams of carbohydrates for a meal, determining, using the computing device, an estimated meal bolus in units of insulin based on the number of estimated grams of carbohydrates and a carbohydrate-insulin-ratio and determining, using the computing device,

an estimated meal bolus insulin rate, based on the estimated meal bolus, an available delivery time, and a configurable constant. The system may also include determining, using the computing device, a total insulin rate as a sum of the intravenous insulin rate and the estimated meal bolus insulin rate and sending the total insulin rate from the computing device to the insulin administration device. The system operations may further include dividing a total meal time into meal time sub-intervals, a first meal time sub-interval starting with a pre-meal bolus glucose measurement before receiving the indication of patient solid food consumption and determining, using the computing device, the total insulin rate for each meal time sub-interval in succession.

In some examples, the operations further include receiving, at the computing device, a number of actual grams of carbohydrates for the meal during a subsequent time interval after the first time interval, determining, using the computing device, an actual meal bolus based on the number of actual grams of carbohydrates and determining a meal bolus in units of insulin, using the computing device, by subtracting a product of the estimated meal bolus insulin rate and an actual delivery time from the actual meal bolus. The system may further include determining, using the computing device, a revised meal bolus insulin rate as the remaining meal bolus divided by a time remaining in the total meal time, determining, using the computing device, a revised total insulin rate as a sum of the intravenous insulin rate and the revised meal bolus insulin rate and sending the revised total insulin rate from the computing device to the insulin administration device. The operations may further comprise decreasing the time interval to less than the default time interval for the one or more meal time sub-intervals.

In some implementations, the operations include electronically displaying on a display in communication with the computing device a warning and blocking transition to a subcutaneous administration of insulin when the current blood glucose measurement is outside a stability target range and electronically displaying on the display a warning when the current blood glucose measurement is within the stability target range for less than a threshold stability period of time. In some examples, the operations include determining, using the computing device, a total daily dose of insulin based on the multiplier when the current blood glucose measurement is within a stability target range for a threshold stability period of time. The system also includes determining, using the computing device, recommended insulin dose including a daily basal insulin and a daily meal insulin for subcutaneous therapy as an apportioning of the total daily dose of insulin, wherein the daily basal insulin is half of the total daily dose of insulin and the daily meal insulin is half of the total daily dose of insulin. The system may further include sending the recommended insulin dose from the computing device to a subcutaneous injection device or electronically displaying the recommended insulin doses on a display in communication with the computing device.

The dosing controller may determine the insulin dose rate based on the current blood glucose measurement, a constant (e.g., 60 mg/dl), and a multiplier. The dosing controller leaves the multiplier unchanged between time intervals when the current blood glucose measurement is greater than an upper limit of the blood glucose target range and the blood glucose drop rate is greater than or equal to a threshold rate of descent. In addition, the dosing controller multiplies the multiplier by a change factor when the current blood glucose measurement is greater than an upper limit of the blood glucose target range and the blood glucose drop rate is less than the threshold rate of descent. The dosing controller

may leave the multiplier unchanged between time intervals when the current blood glucose measurement is less than a lower limit of the blood glucose target range, and it may divide the multiplier by a change factor when the current blood glucose measurement is within the blood glucose target range. In some examples, the dosing controller leaves the multiplier unchanged for at least two subsequent time intervals when the current blood glucose measurement is a pre-meal measurement.

In some implementations, the dosing controller decreases the time interval when the current blood glucose measurement is greater than or equal to the lower limit of the blood glucose target range and the blood glucose drop rate exceeds a threshold drop rate. In addition, the dosing controller sets the time interval to a default value of about one hour when the current blood glucose measurement is greater than or equal to the lower limit of the blood glucose target range and the blood glucose drop rate is less than or equal to a threshold drop rate. The dosing controller may set the time interval to a hypoglycemia time interval of between about 15 minutes and about 30 minutes, when the current blood glucose measurement is below the lower limit of the blood glucose target range and greater than a hypo-threshold blood glucose level.

In some examples, the dosing controller decreases the time interval when the current blood glucose measurement is below the lower limit of the blood glucose target range and below the hypo-threshold blood glucose level, and the blood glucose drop rate is less than or equal to a threshold drop rate. Moreover, the dosing controller sets the time interval to a default value of about one hour when the current blood glucose measurement is below the lower limit of the blood glucose target range and below the hypo-threshold blood glucose level, and the blood glucose drop rate is greater than the threshold drop rate.

In some examples, the dosing controller receives, on the computing device, a number of carbohydrates per meal, then determines, using the computing device, an intravenous insulin rate and a meal bolus rate based on the number of carbohydrates. Furthermore, the dosing controller determines, using the computing device, the insulin dose rate based on the intravenous insulin rate and the estimated meal bolus rate. The dosing controller may set the time interval to about 30 minutes. Additionally or alternatively, the dosing controller may set the time interval to about 60 minutes if the blood glucose measurement is a second consecutive measurement after an initial pre-meal blood glucose measurement.

In some examples, the dosing controller electronically displays on a display in communication with the dosing controller a warning and blocks transition to a subcutaneous administration of insulin when the current blood glucose measurement is outside a stability target range. The dosing controller electronically displays on the display a warning when the current blood glucose measurement is within the stability target range for less than a threshold stability period of time. The dosing controller may determine a total daily dose of insulin based on the multiplier when the current blood glucose measurement is within a stability target range for a threshold stability period of time.

The details of one or more implementations of the disclosure are set forth in the accompanying drawings and the description below. Other aspects, features, and advantages will be apparent from the description and drawings, and from the claims.

DESCRIPTION OF DRAWINGS

FIG. 1A is a schematic view of an exemplary system for monitoring blood glucose level of a patient.

FIG. 1B is a schematic view of an exemplary system for monitoring blood glucose level of a patient.

FIG. 2A is a schematic view of an exemplary process for monitoring the blood glucose level of a patient.

FIG. 2B is a schematic view of an exemplary display for inputting patient information.

FIG. 2C is a schematic view of an exemplary display for selecting a patient from a list of patients.

FIG. 2D is a schematic view of an exemplary display indicating initial intravenous dosing information.

FIG. 3 is a schematic view of an exemplary dose calculation process of FIG. 2A.

FIG. 4A is a schematic view of an exemplary calculation of the intravenous time interval of FIG. 2A.

FIGS. 4B and 4C are schematic views of an exemplary display showing the time a next blood glucose measurement is due.

FIG. 4D is a schematic view of an exemplary display for inputting patient information.

FIG. 4E is a schematic view of an exemplary display of patient information and a timer for a patient's next blood glucose measurement.

FIGS. 5A and 5B are schematic views of an exemplary meal bolus process of FIG. 2A.

FIG. 5C is a schematic view of an exemplary display for inputting a patient's blood glucose measurement.

FIG. 5D is a schematic view of an exemplary display of patient information and a timer for a patient's next blood glucose measurement.

FIGS. 5E and 5F are schematic views of exemplary displays requesting information from the user.

FIGS. 6A and 6B are schematic views of an exemplary subcutaneous transition process of FIG. 2A.

FIG. 6C is a schematic view of an exemplary warning to the user relating to the patient.

FIG. 6D is a schematic view of an exemplary display inquiring whether the patient should continue treatment or stop.

FIG. 6E is a schematic view of an exemplary display requesting information from the user relating to the patient.

FIG. 6F is a schematic view of an exemplary display showing the recommended dose of insulin.

FIG. 6G is a schematic view of an exemplary view to the user relating to transitioning a patient to subcutaneous delivery.

FIG. 7 is a schematic view of an exemplary arrangement of operations for administering insulin.

Like reference symbols in the various drawings indicate like elements.

DETAILED DESCRIPTION

Diabetic hospital patients who eat meals often have poor appetites; consequently, co-ordination of meal boluses and meals is difficult. Meal boluses without meals cause hypoglycemia; meals without meal boluses cause hyperglycemia. Different providers may use different methods of adjusting doses: some may use formulas of their own; some may use paper protocols that are complex and difficult for the nurse to follow, leading to a high incidence of human error; and some may use heuristic methods. There is no guarantee of consistency. Moreover, for diabetic patients who do not eat meals, there is no currently no computerized method of tracking the patient's status. For non-diabetic patient who get include due to "stress hyperglycemia" when they are very sick or undergoing surgery, there is no current method of monitoring their recovery when the stress subsides and

their need for insulin rapidly decreases. If the dose regimen does not decrease rapidly also, hypoglycemia may result. Therefore, it is desirable to have a clinical support system **100** (FIGS. 1A and 1B) that monitors patients' blood glucose level.

Referring to FIGS. 1A and 1B, in some implementations, a clinical decision support system **100** analyzes inputted patient condition parameters for a patient **10** and calculates a personalized dose of insulin to bring and maintain the patient's blood glucose level into a target range BG_{TR} . Moreover, the system **100** monitors the glucose levels of a patient **10** and calculates recommended intravenous or subcutaneous insulin dose to bring the patient's blood glucose into the preferred target range BG_{TR} over a recommended period of time. A qualified and trained healthcare professional **40** may use the system **100** along with clinical reasoning to determine the proper dosing administered to a patient **10**. Therefore, the system **100** is a glycemic management tool for evaluation a patient's current and cumulative blood glucose value BG while taking into consideration the patient's information such as age, weight, and height. The system **100** may also consider other information such as carbohydrate content of meals, insulin doses being administered to the patient **10**, e.g., long-acting insulin doses for basal insulin and rapid-acting insulin doses for meal boluses and correction boluses. Based on those measurements (that may be stored in non-transitory memory **24**, **114**, **144**), the system **100** recommends an intravenous dosage of insulin, glucose, or saline or a subcutaneous basal and bolus insulin dosing recommendation or prescribed dose to adjust and maintain the blood glucose level towards a configurable (based on the patient's information) physician's determined blood glucose target range BG_{TR} . The system **100** also considers a patient's insulin sensitivity or improved glycemic management and outcomes. The system **100** may take into account pertinent patient information such as demographics and previous results, leading to a more efficient use of healthcare resources. Finally, the system **100** provides a reporting platform for reporting the recommendations or prescribed dose(s) to the user **40** and the patient **10**. In addition, for diabetic patients who eat meals, the system **100** provides faster, more reliable, and more efficient insulin administration than a human monitoring the insulin administration. The system **100** reduces the probability of human error and insures consistent treatment, due to the system's capability of storing and tracking the patient's blood glucose levels BG , which may be used for statistical studies. As for patients who are tube-fed or do not eat meals, the system **100** provides dedicated subprograms, which in turn provide basal insulin and correction boluses but no meal boluses. Patients who are tube-fed or who do not eat usually have a higher basal insulin level than patients who eat, because the carbohydrates in the nutritive formula are accounted-for in the basal insulin. The system **100** provides a meal-by-meal adjustment of Meal Boluses without carbohydrate counting, by providing a dedicated subprogram that adjusts meal boluses based on the immediately preceding meal bolus and the BG that followed it. The system **100** provides a meal-by-meal adjustment of Meal Boluses with carbohydrate counting by providing a dedicated subprogram that adjusts meal boluses based a Carbohydrate-to-Insulin Ratio (CIR) that is adjusted at each meal, based on the CIR used at the immediately preceding meal bolus and the BG that followed it.

Hyperglycemia is a condition that exists when blood sugars are too high. While hyperglycemia is typically associated with diabetes, this condition can exist in many

11

patients who do not have diabetes, yet have elevated blood sugar levels caused by trauma or stress from surgery and other complications from hospital procedures. Insulin therapy is used to bring blood sugar levels back into a normal range.

Hypoglycemia may occur at any time when a patient's blood glucose level is below a preferred target. Appropriate management of blood glucose levels for critically ill patients reduces co-morbidities and is associated with a decrease in infection rates, length of hospital stay, and death. The treatment of hyperglycemia may differ depending on whether or not a patient has been diagnosed with Type 1 diabetes mellitus, Type 2 diabetes mellitus, gestational diabetes mellitus, or non-diabetic stress hyperglycemia. The blood glucose target range BG_{TR} is defined by a lower limit, i.e., a low target BG_{TRL} and an upper limit, i.e., a high target BG_{TRH} .

Stress-related hyperglycemia: Patients often get "stress hyperglycemia" if they are very sick or undergoing surgery. This condition requires insulin. In diabetic patients, the need for insulin is visibly increased. In non-diabetic patients, the stress accounts for the only need for insulin, and as the patients recover, the stress subsides, and their need for insulin rapidly decreases. For non-diabetic patients, the concern is that their need for insulin decreases faster than their dose regimen, leading to hypoglycemia.

Diabetes Mellitus has been treated for many years with insulin. Some recurring terms and phrases are described below:

Injection: Administering insulin by means of manual syringe or an insulin "pen," with a portable syringe named for its resemblance to the familiar writing implement.

Infusion: Administering insulin in a continuous manner by means of an insulin pump for subcutaneous insulin or an intravenous apparatus **123a**, both of which are capable of continuous administration.

Intravenous Insulin Therapy: Intravenous infusion of insulin has been approved by the U.S. Food and Drug Administration as an acceptable indication for use. Intravenous infusion is the fastest of all insulin administration routes and, typically, only available in the hospital setting. For instance, in intensive care units, the patients may be fed by intravenous glucose infusion, by intravenous Total Parenteral Nutrition (TPN), or by a tube to the stomach. Patients are often given insulin in an intravenous infusion at an insulin infusion rate IIR. The IIR is regulated by the frequent testing of blood glucose, typically at intervals between about 20 minutes and 2 hours. This is combined with a protocol in which a new IIR is computed after each blood glucose test.

Basal-Bolus Therapy: Basal-bolus therapy is a term that collectively refers to any insulin regimen involving basal insulin and boluses of insulin.

Basal Insulin: Insulin that is intended to metabolize the glucose released by a patient's the liver during a fasting state. Basal insulin is administered in such a way that it maintains a background level of insulin in the patient's blood, which is generally steady but may be varied in a programmed manner by an insulin pump **123a**. Basal insulin is a slow, relatively continuous supply of insulin throughout the day and night that provides the low, but present, insulin concentration necessary to balance glucose consumption (glucose uptake and oxidation) and glucose production (glucogenolysis and gluconeogenesis). A patient's Basal insulin needs are usually about 10 to 15 mU/kg/hr and account for 30% to 50% of the total daily insulin needs; however, considerable variation occurs based on the patient

12

Bolus Insulin: Insulin that is administered in discrete doses. There are two main types of boluses, Meal Bolus and Correction Bolus.

Meal Bolus: Taken just before a meal in an amount which is proportional to the anticipated immediate effect of carbohydrates in the meal entering the blood directly from the digestive system. The amounts of the Meal Boluses may be determined and prescribed by a physician **40** for each meal during the day, i.e., breakfast, lunch, and dinner. Alternatively, the Meal Bolus may be calculated in an amount generally proportional to the number of grams of carbohydrates in the meal. The amount of the Meal Bolus is calculated using a proportionality constant, which is a personalized number called the Carbohydrate-to-Insulin Ratio (CIR) and calculated as follows:

$$\text{Meal Insulin Bolus} = \{\text{grams of carbohydrates in the meal}\} / \text{CIR} \quad (1)$$

Correction Bolus CB: Injected immediately after a blood glucose measurement; the amount of the correction bolus is proportional to the error in the BG (i.e., the bolus is proportional to the difference between the blood glucose measurement BG and the patient's personalized Target blood glucose BG_{Target}). The proportionality constant is a personalized number called the Correction Factor, CF, and is calculated as follows:

$$\text{CB} = (\text{BG} - \text{BG}_{\text{Target}}) / \text{CF} \quad (2)$$

A Correction Bolus CB is generally administered in a fasting state, after the previously consumed meal has been digested. This often coincides with the time just before the next meal.

There are several kinds of Basal-Bolus insulin therapy including Insulin Pump therapy and Multiple Dose Injection therapy:

Insulin Pump Therapy: An insulin pump **123a** is a medical device used for the administration of insulin in the treatment of diabetes mellitus, also known as continuous subcutaneous insulin infusion therapy. The device includes: a pump, a disposable reservoir for insulin, and a disposable infusion set. The pump **123a** is an alternative to multiple daily injections of insulin by insulin syringe or an insulin pen and allows for intensive insulin therapy when used in conjunction with blood glucose monitoring and carbohydrate counting. The insulin pump **123a** is a battery-powered device about the size of a pager. It contains a cartridge of insulin, and it pumps the insulin into the patient via an "infusion set", which is a small plastic needle or "canula" fitted with an adhesive patch. Only rapid-acting insulin is used.

Multiple Dose Injection (MDI): MDI involves the subcutaneous manual injection of insulin several times per day using syringes or insulin pens **123b**. Meal insulin is supplied by injection of rapid-acting insulin before each meal in an amount proportional to the meal. Basal insulin is provided as a once, twice, or three time daily injection of a dose of long-acting insulin. Other dosage frequencies may be available. Advances continue to be made in developing different types of insulin, many of which are used to great advantage with MDI regimens:

Long-acting insulins are non-peaking and can be injected as infrequently as once per day. These insulins are widely used for Basal Insulin. They are administered in dosages that make them appropriate for the fasting state of the patient, in which the blood glucose is replenished by the liver to maintain a steady minimum blood glucose level.

Rapid-acting insulins act on a time scale shorter than natural insulin. They are appropriate for boluses.

13

In some examples, critically ill patients are ordered nil per os (NPO), which means that oral food and fluids are withheld from the patient 10. Typically these patients 10 are unconscious, have just completed an invasive surgical procedure, or generally have difficulty swallowing. Intravenous insulin infusion is typically the most effective method of managing blood glucose levels in these patients. A patient 10 may be NPO and receiving a steady infusion of intravenous glucose, Total Parenteral Nutrition, tube feeding, regular meals that include carbohydrates, or not receiving any nutrition at all. In cases where the patient 10 is not receiving any nutrition, blood glucose is typically replaced by endogenous production by the liver.

As a patient's condition improves, an NPO order may be lifted, allowing the patient 10 to commence an oral caloric intake. In patients 10 with glycemic abnormalities, additional insulin may be needed to cover the consumption of carbohydrates. These patients 10 generally receive one-time injections of insulin in the patient's subcutaneous tissue.

Subcutaneous administration of mealtime insulin in critically ill patients 10 can introduce a patient safety risk if, after receiving the insulin injection, the patient 10 decides not to eat, is unable to finish the meal, or experiences emesis.

Continuous intravenous infusion of mealtime insulin, over a predetermined time interval, allows for an incremental fulfillment of the patient's mealtime insulin requirement, while minimizing patient safety risks. If a patient 10 decides he/she is unable to eat, the continuous intravenous infusion may be stopped or, if a patient 10 is unable to finish the meal, the continuous intravenous infusion rate may be decreased to compensate for the reduction in caloric intake.

The pharmacokinetics (what the body does to a drug over a period of time, which includes the processes of absorption, distribution, localization in tissues, biotransformation, and excretion) and pharmacodynamics (what a drug does to the body) actions of insulin significantly improve when administering insulin via an intravenous route, which is a typical method of delivery for hospitalized patients 10. The management of prandial insulin requirements using an intravenous route can improve patient safety, insulin efficiency, and the accuracy of insulin dosing. The majority of patients who require continuous intravenous insulin infusion therapy may also need to be transitioned to a subcutaneous insulin regimen for ongoing control of blood glucose, regardless of diabetes mellitus (DM) diagnosis. Moreover, the timing, dosing, and process to transition patients 10 from a continuous intravenous route of insulin administration to a subcutaneous insulin regimen is complex and should be individualized based on various patient parameters. Failure to individualize this approach could increase the risk of severe hypoglycemia during the transition process. If not enough insulin is given, the patient 10 may experience acute post-transition hyperglycemia, requiring re-initiation of a continuous intravenous insulin infusion. Therefore, the clinical decision support system 100 calculates a personalized dose of insulin to bring and maintain the patient's blood glucose level into a target range BG_{TR} , while taking into consideration the condition of the patient 10.

The clinical decision support system 100 includes a glycemic management module 50, an integration module 60, a surveillance module 70, and a reporting module 80. Each module 50, 60, 70, 80 is in communication with the other modules 50, 60, 70, 80 via a network 20. In some examples, the network 24 (discussed below) provides access to cloud computing resources that allows for the performance of services on remote devices instead of the specific modules 50, 60, 70, 80. The glycemic management module 50

14

executes a process 200 (e.g., an executable instruction set) on a processor 112, 132, 142 or on the cloud computing resources. The integration module 60 allows for the interaction of users 40 with the system 100. The integration module 60 receives information inputted by a user 40 and allows the user 40 to retrieve previously inputted information stored on a storage system (e.g., one or more of cloud storage resources 24, a non-transitory memory 144 of a hospital's electronic medical system 140, a non-transitory memory 114 of the patient device 110, or other non-transitory storage media in communication with the integration module 60). Therefore, the integration module 60 allows for the interaction between the users 40 and the system 100 via a display 116, 146. The surveillance module 70 considers patient information 208a received from a user 40 via the integration module 60 and information received from a glucometer 124 that measures a patient's blood glucose value BG and determines if the patient 10 is within a threshold blood glucose value BG_{TH} . In some examples, the surveillance module 70 alerts the user 40 if a patient's blood glucose values BG are not within a threshold blood glucose value BG_{TH} . The surveillance module 70 may be preconfigured to alert the user 40 of other discrepancies between expected values and actual values based on pre-configured parameters (discussed below). For example, when a patient's blood glucose value BG drops below a lower limit of the threshold blood glucose value BG_{THL} . The reporting module 80 may be in communication with at least one display 116, 146 and provides information to the user 40 determined using the glycemic management module 50, the integration module 60, and/or the surveillance module 70. In some examples, the reporting module 80 provides a report that may be displayed on a display 116, 146 and/or is capable of being printed.

The system 100 is configured to evaluate a glucose level and nutritional intake of a patient 10. The system 100 also evaluates whether the patient 10 is transitioning to a subcutaneous insulin regime. Based on the evaluation and analysis of the data, the system 100 calculates an insulin dose, which is administered to the patient 10 to bring and maintain the blood glucose level of the patient 10 into the blood glucose target range BG_{TR} . The system 100 may be applied to various devices, including, but not limited to, intravenous infusion pumps 123a, subcutaneous insulin infusion pumps 123a, glucometers, continuous glucose monitoring systems, and glucose sensors. In some implementations, as the system 100 is monitoring the patient's blood glucose values BG and the patient's insulin intake, the system 100 notifies the user 40 if the patient 10 receives more than 500 units/hour of insulin because the system 100 considers these patients 10 to be insulin resistant.

In some examples the clinical decision support system 100 includes a network 20, a patient device 110, a dosing controller 160, and a service provider 130. The patient device 110 may include, but is not limited to, desktop computers or portable electronic device (e.g., cellular phone, smartphone, personal digital assistant, barcode reader, personal computer, or a wireless pad) or any other electronic device capable of sending and receiving information via the network 20.

The patient device 110 includes a data processor 112 (e.g., a computing device that executes instructions), and non-transitory memory 114 and a display 116 (e.g., touch display or non-touch display) in communication with the data processor 112. In some examples, the patient device 110 includes a keyboard 118, speakers 212, microphones, mouse, and a camera.

15

The service provider **130** may include a data processor **132** in communication with non-transitory memory **134**. The service provider **130** provides the patient **10** with a process **200** (see FIG. 2) (e.g., a mobile application, a web-site application, or a downloadable program that includes a set of instructions) executable on a processor **112**, **132**, **142** of the dosing controller **160** and accessible through the network **20** via the patient device **110**, intravenous infusion pumps **123a**, hospital electronic medical record systems **140**, or portable blood glucose measurement devices **124** (e.g., glucose meter or glucometer). Intravenous infusion pumps infuse fluids, medication or nutrients into a patient's circulatory system. Intravenous infusion pumps **123a** may be used intravenously and, in some instances, subcutaneous, arterial and epidural infusions are used. Intravenous infusion pumps **123a** typically administer fluids that are expensive or unreliable if administered manually (e.g., using a pen **123b**) by a nurse or doctor **40**. Intravenous infusion pumps **123a** can administer a 0.1 ml per hour injection, injections every minute, injections with repeated boluses requested by the patient, up to a maximum number per hours, or fluids whose volumes vary by the time of day.

In some implementations, an electronic medical record system **140** is located at a hospital **42** (or a doctor's office) and includes a data processor **142**, a non-transitory memory **144**, and a display **146** (e.g., touch display or non-touch display). The transitory memory **144** and the display **146** are in communication with the data processor **142**. In some examples, the hospital electronic medical system **140** includes a keyboard **148** in communication with the data processor **142** to allow a user **40** to input data, such as patient information **208a** (FIGS. 2A and 2B). The non-transitory memory **144** maintains patient records capable of being retrieved, viewed, and, in some examples, modified and updated by authorized hospital personal on the display **146**.

The dosing controller **160** is in communication with the glucometer **124** and includes a computing device **112**, **132**, **142** and non-transitory memory **114**, **134**, **144** in communication with the computing device **112**, **132**, **142**. The dosing controller **160** executes the process **200**. The dosing controller **160** stores patient related information retrieved from the glucometer **124** to determine an insulin dose rate IRR based on the received blood glucose measurement BG.

The network **20** may include any type of network that allows sending and receiving communication signals, such as a wireless telecommunication network, a cellular telephone network, a time division multiple access (TDMA) network, a code division multiple access (CDMA) network, Global system for mobile communications (GSM), a third generation (3G) network, fourth generation (4G) network, a satellite communications network, and other communication networks. The network **20** may include one or more of a Wide Area Network (WAN), a Local Area Network (LAN), and a Personal Area Network (PAN). In some examples, the network **20** includes a combination of data networks, telecommunication networks, and a combination of data and telecommunication networks. The patient device **110**, the service provider **130**, and the hospital electronic medical record system **140** communicate with each other by sending and receiving signals (wired or wireless) via the network **20**. In some examples, the network **20** provides access to cloud computing resources, which may be elastic/on-demand computing and/or storage resources **24** available over the network **20**. The term 'cloud' services generally refers to a service performed not locally on a user's device, but rather delivered from one or more remote devices accessible via one or more networks **20**.

16

Referring to FIGS. 1B and 2A-2C, the process **200** receives parameters (e.g., patient condition parameters) inputted via the client device **110**, the service provider **130**, and/or the hospital system **140**, analyzes the inputted parameters, and determines a personalized dose of insulin to bring and maintain a patient's blood glucose level BG into a preferred target range BG_{TR} .

In some implementations, before the process **200** begins to receive the parameters, the process **200** may receive a username and a password (e.g., at a login screen displayed on the display **116**, **146**) to verify that a qualified and trained healthcare professional **40** is initiating the process **200** and entering the correct information that the process **200** needs to accurately administer insulin to the patient **10**. The system **100** may customize the login screen to allow a user **40** to reset their password and/or username. Moreover, the system **100** may provide a logout button (not shown) that allows the user **40** to log out of the system **100**. The logout button may be displayed on the display **116**, **146** at any time during the execution of the process **200**.

The clinical decision support system **100** may include an alarm system **120** that alerts a user **40** when the patient's blood glucose level BG is outside the target range BG_{TR} . The alarm system **120** may produce an audible sound via speaker **122** in the form of a beep or some like audio sounding mechanism. In some examples, the alarm system **120** displays a warning message or other type of indication on the display **116** of the patient device **110** to provide a warning message. The alarm system **120** may also send the audible and/or visual notification via the network **20** to the hospital system **140** (or any other remote station) for display on the display **146** of the hospital system **140** or played through speakers **152** of the hospital system **140**.

The process **200** prompts a user **40** to input patient information **208a** at block **208**. The user **40** may input the patient information **208a**, for example, via the user device **110** or via the hospital electronic medical record systems **140** located at a hospital **42** (or a doctor's office). The user **40** may input new patient information **208a** as shown in FIG. 2B or retrieve previously stored patient information **208a** as shown in FIG. 2C. In some implementations, the process **200** provides the user **40** with a patient list **209** (FIG. 2C) where the user **40** selects one of the patient names from the patient list **209**, and the process **200** retrieves that patient's information **208a**. The process **200** may allow the user **40** to filter the patient list **209**, e.g., alphabetically (first name or last name), by location, patient identification. The process **200** may retrieve the patient information **208a** from the non-transitory memory **144** of the hospital's electronic medical system **140** or the non-transitory memory **114** of the patient device **110** (e.g., where the patient information **208a** was previously entered and stored). The patient information **208a** may include, but is not limited to, a patient's name, a patient's identification number (ID), a patient's height, weight, date of birth, diabetes history, physician name, emergency contact, hospital unit, diagnosis, gender, room number, and any other relevant information. In some examples, the diagnosis may include, but is not limited to, burn patients, Coronary artery bypass patients, stroke patients, diabetic ketoacidosis (DKA) patients, and trauma patients. After the user **40** completes inputting the patient information **208a**, the process **200** at block **202** determines whether the patient **10** is being treated with an intravenous treatment module by prompting the user **40** (e.g., on the display **116**, **146**) to input whether the patient **10** will be treated with an intravenous treatment module. If the patient **10** will not be treated with the intravenous treatment module,

the process 200 determines at block 210 whether the patient 10 will be treated with a subcutaneous treatment module, by asking the user 40 (e.g., by prompting the user 40 on the display 116, 146). If the user 40 indicates that the patient 10 will be treated with the subcutaneous treatment, the process 200 flows to block 216, where the user 40 enters patient subcutaneous information 216a, such as bolus insulin type, target range, basal insulin type and frequency of distribution (e.g., 1 does per day, 2 doses per day, 3 doses per day, etc.), patient diabetes status, subcutaneous type ordered for the patient (e.g., Basal/Bolus and correction that is intended for patients on a consistent carbohydrate diet, or Basal and correction that is intended for patients who are NPO or on continuous enteral feeds), frequency of patient blood glucose measurements, or any other relevant information. In some implementations, the patient subcutaneous information 216a is prepopulated with default parameters, which may be adjusted or modified. When the user 40 enters the patient subcutaneous information 216, the subcutaneous program begins at block 226. The process may determine whether the patient 10 is being treated with an intravenous treatment or a subcutaneous treatment by prompting the user 40 to select between two options (e.g., a button displayed on the display 116, 146), one being the intravenous treatment and the other begin the subcutaneous treatment.

In some implementations and referring back to block 202, if the process 200 determines that the patient 10 will be treated with the intravenous treatment module, the process 200 prompts the user 40 at block 204 for setup data 204a, such as patient parameters 204a relevant to the intravenous treatment mode. In some examples, the patient parameter 204a relating to the intravenous treatment may be prepopulated, for example, with default values that may be adjusted and modified by the user 40. These patient parameters 204a may include an insulin concentration (i.e., the strength of insulin being used for the intravenous dosing, which may be measured in units/milliliter), the type of insulin and rate being administered to the patient, the blood glucose target range BG_{TR} , the patient's diabetes history, a number of carbohydrates per meal, or any other relevant information. In some implementations, the type of insulin and the rate of insulin depend on the BG of the patient 10. For example, the rate and type of insulin administered to a patient 10 when the blood glucose value BG of the patient 10 is greater or equal to 250 mg/dl may be different than the rate and type of insulin administered to the patient 10 when the blood glucose value BG of the patient is greater than 250 ml/dl. The blood glucose target range BG_{TR} may be a configurable parameter, customized based on various patient factors. The blood glucose target range BG_{TR} may be limited to 40 mg/dl (e.g., 100-140 mg/dl, 140-180 mg/dl, and 120-160 mg/dl).

After the user 40 inputs patient parameters 204a for the intravenous treatment at block 204, the process 200 prompts the user 40 to input the blood glucose value BG of the patient 10 at block 206. The blood glucose value BG may be manually inputted by the user 40, sent via the network 20 from a glucometer 124, sent electronically from the hospital information or laboratory system 140, or other wireless device. The process 200 determines a personalized insulin dose rate, referred to as an insulin infusion rate IIR, using the blood glucose value BG of the patient 10 and a dose calculation process 300.

FIG. 3 provides a dose calculation process 300 for calculating the insulin infusion rate IIR of the patient 10 for intravenous treatment after the process 200 receives the patient information 208a discussed above (including the patients' blood glucose value BG). At block 301 the dose

calculation process 300 determines if the patient's blood glucose BG is less than a stop threshold value BG_{THstop} . If not, then at block 303 the dose calculation process 300 goes to block 304 without taking any action. If, however, the patient's blood glucose BG is less than a stop threshold value BG_{THstop} , then the calculation dose process sets the patient's regular insulin dose rate IRR to zero at block 302, which then goes to block 322. The dose calculation process 300 determines at decision block 304 if the inputted blood glucose value BG is the first inputted blood glucose value.

The patient's regular insulin dose rate IIR is calculated at block 320 in accordance with the following equation:

$$IIR = (BG - K) * M \quad (3A)$$

where K is a constant, known as the Offset Target, with the same unit of measure as blood glucose and M is a unit-less multiplier. In some examples, the Offset Target K is lower than the blood glucose target range of the patient 10. The Offset Target K allows the dose calculation process 300 to calculate a non-zero stable insulin dose rate even with a blood glucose result is in the blood glucose target range BG_{TR} .

The initial multiplier M_I , determined by the physician 40, approximates the sensitivity of a patient 10 to insulin. For example, the initial multiplier equals 0.02 for adults ages 18 and above. In some examples, the initial multiplier M_I equals 0.01 for frail elderly patients 10 who may be at risk for complications arising when their blood glucose level BG falls faster than 80 mg/dl/hr. Moreover, the physician 40 may order a higher initial multiplier M_I for patients 10 with special needs, such as CABG patients (i.e., patients who have undergone coronary artery bypass grafting) with BMI (Body Mass Index which is a measure for the human body shape based on the individual's mass and height) less than 30 might typically receive an initial multiplier of 0.05, whereas a patient 10 with BMI greater than 30 might receive an initial multiplier M_I of 0.06. In addition, a patient's weight may be considered in determining the value of the initial multiplier M_I , for examples, in pediatric treatments, the system 100 calculates a patient's initial multiplier M_I using the following equation:

$$M_I = 0.0002 \times \text{Weight of patient (in kilograms)} \quad (3B)$$

In some implementations, K is equal to 60 mg/dl. The dose calculation process 300 determines the target blood glucose target range BG_{TR} using two limits inputted by the user 40, a lower limit of the target range BG_{TRL} and an upper (high) limit of the target range BG_{TRH} . These limits are chosen by the user 40 so that they contain the desired blood glucose target as the midpoint. Additionally, the Offset Target K may be calculated dynamically in accordance with the following equation:

$$K = BG_{Target} - \text{Offset}, \quad (4)$$

where BG_{Target} is the midpoint of the blood glucose target range BG_{TR} and Offset is the preconfigured distance between the target center BG_{Target} and the Offset Target, K.

In some implementations, the insulin dose rate IRR may be determined by the following process on a processor 112, 132, 142. Other processes may also be used.

```
function IIR($sf, $current_bg, $bg_default = 60, $insulin_concentration,
Sins_units_of_measure = 'units/hr') {
    settype($sf, 'float');
    settype($bg_default, 'float');
```

19

-continued

```

settype($current_bg,'float');
settype($insulin_concentration,'float');
/*
  @param $sf = sensitivity factor from db
  @param $current_bg = the current bg value being submitted
  @param $db_default = the default "Stop Insulin When" value....If
  it isn't passed, it defaults to 60
  @param $insulin_concentration = the default insulin concentration
  from settings
  */
  if($current_bg > 60) {
    $iir = array( );
    $iir[0] = round(($current_bg - $bg_default) * $sf, 1);
    if ($ins_units_of_measure != 'units/hr') {
      $iir[1] = round(($current_bg - $bg_default) * $sf /
$insulin_concentration ,1);
    }
    return $iir;
  } else {
    return 0;
  }
}

```

Referring to decision block **304**, when the dose calculation process **300** determines that the inputted blood glucose value BG is the first inputted blood glucose value, then the dose calculation process **300** defines the value of the current multiplier M equal to an initial multiplier (A) at block **306**. The dose calculation process **300** then calculates, at block **320**, the Insulin Infusion Rate in accordance with the IIR equation (EQ. 3A) and returns to the process **200** (see FIG. 2).

However, referring back to decision block **304**, when the dose calculation process **300** determines that the inputted blood glucose value BG is not the first inputted blood glucose value, the dose calculation process **300** determines if the Meal Bolus Module has been activated at decision block **308**. If the dose calculation process **300** determines that the Meal Bolus Module has been activated, then the dose calculation process **300** begins a Meal Bolus process **500** (see FIG. 5).

Referring back to decision block **308**, if the Meal Bolus Module has not been activated, the dose calculation process **300** determines, at decision block **310**, if the current blood glucose value BG is greater than the upper limit BG_{TRH} of the blood glucose target range BG_{TR} . If the blood glucose value BG is greater than the upper limit BG_{TRH} of the blood glucose target range BG_{TR} , the dose calculation process **300** determines, at block **314**, a ratio of the current blood glucose value BG to the previous blood glucose value BG_P , where BG_P was measured at an earlier time than the current BG. The process **200** then determines if the ratio of the blood glucose to the previous blood glucose, BG/BG_P , is greater than a threshold value L_A , as shown in the following equation:

$$(BG/BG_P) > L_A \quad (5)$$

where BG is the patient's current blood glucose value; BG_P is the patient's previous blood glucose value; and L_A is the threshold ratio of BG/BG_P for blood glucose values above the upper limit of the blood glucose target range BG_{TRH} . If the ratio BG/BG_P exceeds the threshold ratio L_A , then the Multiplier M is increased. In some examples, the threshold ratio L_A equals 0.85.

If the dose calculation process **300** determines that the ratio (BG/BG_P) of the blood glucose value BG to the previous blood glucose value BG_P is not greater than the threshold ratio L_A for a blood glucose value BG above the upper limit BG_{TRH} of the blood glucose target range BG_{TR} ,

20

then the dose calculation process **300** sets the value of the current multiplier M to equal the value of the previous multiplier M_P , see block **312**.

$$M = M_P \quad (6)$$

Referring back to block **314**, if the dose calculation process **300** determines that the ratio (BG/BG_P) of the blood glucose value BG to the previous blood glucose BG_P is greater than the threshold ratio L_A for a blood glucose value above upper limit BG_{TRH} of the blood glucose target range BG_{TR} , then dose calculation process **300** multiplies the value of the current multiplier M by a desired Multiplier Change Factor (M_{CF}) at block **318**. The dose calculation process **300** then calculates the insulin infusion rate at block **320** using the IIR equation (EQ. 3A) and returns to the process **200** (see FIG. 2).

Referring back to block **310**, when the dose calculation process **300** determines that the current blood glucose value BG is not greater than the upper limit BG_{TRH} of the blood glucose target range BG_{TR} , the dose calculation process **300** then determines if the current blood glucose concentration BG is below the lower limit BG_{TRL} of the blood glucose target range BG_{TR} at decision block **311**. If the current blood glucose value BG is below the lower limit BG_{TRL} of the blood glucose target range BG_{TR} , the dose calculation process **300** at block **316** divides the value of the current multiplier M by the Multiplier Change Factor (M_{CF}), in accordance with the following equation:

$$M = M_P / M_{CF} \quad (7)$$

and calculates the current insulin infusion rate IIR using equation 3 at block **320** and returns to the process **200** (see FIG. 2).

At block **311**, if the dose calculation process **300** determines that the blood glucose value BG is not below the lower limit of the blood glucose target range BG_{TRL} , the dose calculation process **300** sets the value of the current multiplier to be equal to the value of the previous multiplier M_P at block **312** (see EQ. 6).

Referring again to FIG. 3, at block **311**, if the current blood glucose value BG is below the lower limit of the target range BG_{TRL} , logic passes to decision block **322**, where the process **300** determines if the current blood glucose concentration BG is below a hypoglycemia threshold BG_{Hypo} . If the current blood glucose BG is below the hypoglycemia threshold BG_{Hypo} , logic then passes to block **324**, where the process **300** recommends hypoglycemia treatment, either by a calculation of an individualized dose of intravenous glucose or oral hypoglycemia treatment.

Referring back to FIG. 2A, after the dose calculation process **300** calculates the insulin infusion rate IIR, the process **200** proceeds to a time calculation process **400** (FIG. 4A) for calculating a time interval T_{Next} until the next blood glucose measurement.

FIG. 4A shows the time interval calculation process **400** for calculating a time interval T_{Next} between the current blood glucose measurement BG and the next blood glucose measurement BG_{next} . The time-duration of blood glucose measurement intervals T_{Next} may vary and the starting time interval can either be inputted by a user **40** at the beginning of the process **200**, **300**, **400**, or defaulted to a predetermined time interval, $T_{Default}$ (e.g., one hour). The time interval T_{Next} is shortened if the blood glucose concentration BG of the patient **10** is decreasing excessively, or it may be lengthened if the blood glucose concentration BG of the patient **10** becomes stable within the blood glucose target range BG_{TR} .

21

The time-interval calculation process 400 determines a value for the time interval T_{Next} based on several conditions. The time-interval process 400 checks for the applicability of several conditions, where each condition has a value for T_{next} that is triggered by a logic-test (except $T_{default}$). The process 400 selects the lowest value of T_{next} from the values triggered by logic tests (not counting $T_{default}$). If no logic test was triggered, the process selects $T_{default}$. This is accomplished in FIG. 4A by the logic structure that selects the lowest values of T_{next} first. However, other logic structures are possible as well.

The time calculation process 400 determines at decision block 416 if the current blood glucose BG is below the lower limit BG_{TRL} (target range low limit) of the blood glucose target range BG_{TR} . If the current blood glucose BG is below the lower limit BG_{TRL} of the blood glucose target range BG_{TR} , then the time calculation process 400 determines, at decision block 418, if the current blood glucose BG is less than a hypoglycemia-threshold blood glucose level BG_{Hypo} .

If the current blood glucose BG is less than the hypoglycemia-threshold blood glucose level BG_{Hypo} , the time calculation process 400 sets the time interval T_{Next} to a hypoglycemia time interval T_{Hypo} , e.g., 15 or 30 minutes, at block 426. Then the time calculation process 400 is complete and returns to the process 200 (FIG. 2) at block 428.

If the current blood glucose BG is not less than (i.e., is greater than) the hypoglycemia-threshold blood glucose level BG_{Hypo} at block 418, the time calculation process 400 determines at block 422 if the most recent glucose percent drop $BG_{\% Drop}$ is greater than the threshold glucose percentage drop $\% Drop_{Low Limit}$ (for a low BG range) using the following equation:

$$BG_{\% drop} > \% Drop_{Low Limit} \quad (8A)$$

since

$$BG_{\% drop} = \left(\frac{(BG_P - BG)}{BG_P} \right) \quad (8B)$$

then,

$$\left(\frac{(BG_P - BG)}{BG_P} \right) > \% Drop_{Low Limit} \quad (8C)$$

where BG_P is a previously measured blood glucose.

If the current glucose percent drop $BG_{\% Drop}$ is not greater than the limit for glucose percent drop (for the low BG range) $\% Drop_{Low Limit}$, the time calculation process 400 passes the logic to block 412. In some examples, the low limit $\% Drop_{Low Limit}$ equals 25%.

Referring back to block 422, if the current glucose percent drop $BG_{\% Drop}$ is greater than the limit for glucose percent drop (for the low BG range) $\% Drop_{Low Limit}$, the time calculation process 400 at block 424 sets the time interval to a shortened time interval T_{Short} , for example 20 minutes, to accommodate for the increased drop rate of the blood glucose BG. Then the time calculation process 400 is complete and returns to the process 200 (FIG. 2) at block 428.

Referring back to decision block 416, if the time calculation process 400 determines that the current blood glucose BG is not below the lower limit BG_{TRL} for the blood glucose target range BG_{TR} , the time calculation process 400 determines at block 420 if the blood glucose BG has decreased by

22

a percent of the previous blood glucose that exceeds a limit $\% Drop_{Regular}$ (for the regular range, i.e., blood glucose value $BG > BG_{TRL}$), using the formula:

$$\left(\frac{(BG_P - BG)}{BG_P} \right) > \% Drop_{Regular} \quad (9)$$

If the blood glucose BG has decreased by a percentage that exceeds the regular threshold glucose percent drop (for the regular BG range) $\% Drop_{Regular}$, the time calculation process 400, at block 425, sets the time interval to the shortened time interval T_{Short} , for example 20 minutes. A reasonable value for $\% Drop_{Regular}$ for many implementations is 66%. Then the time calculation process 400 is complete and returns to the process 200 (FIG. 2) at block 428. If, however, the glucose has not decreased by a percent that exceeds the threshold glucose percent drop $\% Drop_{Regular}$ (for the regular BG range), the time calculation process 400 routes the logic to block 412. The process 400 determines, at block 412, a blood glucose rate of descent $BG_{DropRate}$ based on the following equation:

$$BG_{DropRate} = (BG_P - BG) / (T_{Current} - T_{Previous}) \quad (10)$$

where BG_P is the previous blood glucose measurement, $T_{Current}$ is the current time and $T_{Previous}$ is the previous time. Moreover, the process 400 at block 412 determines if the blood glucose rate of descent $BG_{DropRate}$ is greater than a preconfigured drop rate limit $BG_{dropRateLimit}$.

If the time calculation process 400 at block 412 determines that the blood glucose rate of descent $BG_{DropRate}$ has exceeded the preconfigured drop rate limit $BG_{dropRateLimit}$, the time interval T_{Next} until the next blood glucose measurement is shortened at block 414 to a glucose drop rate time interval T_{BGDR} , which is a relatively shorter time interval than the current time interval $T_{Current}$, as consideration for the fast drop. The preconfigured drop rate limit $BG_{dropRateLimit}$ may be about 100 mg/dl/hr. The glucose drop rate time interval T_{BGDR} may be 30 minutes, or any other predetermined time. In some examples, a reasonable value for $T_{Default}$ is one hour. Then the time calculation process 400 is complete and returns to the process 200 (FIG. 2) at block 428.

If the time calculation process 400 determines at block 412 that the glucose drop rate $BG_{DropRate}$ does not exceed the preconfigured limit $BG_{dropRateLimit}$, the time calculation process 400 determines, at block 408, if the patient's blood glucose concentration BG has been within the desired target range BG_{TR} (e.g., $BG_{TRL} < BG < BG_{TRH}$) for a period of time T_{Stable} . The criterion for stability in the blood glucose target range BG_{TR} is a specified time in the target range BG_{TR} or a specified number of consecutive blood glucose measurements in the target range BG_{TR} . For example, the stable period of time T_{Stable} may be one hour, two hours, two and a half hours, or up to 4 hours. If the stability criterion is met then the time interval T_{Next} until the next scheduled blood glucose measurement BG may be set at block 410 to a lengthened time interval T_{Long} (such as 2 hours) that is generally greater than the default time interval $T_{Default}$. Then the time calculation process 400 is complete and returns to the process 200 (FIG. 2) at block 428. If the time calculation process 400 determines that the patient 10 has not met the criteria for stability, the time calculation process 400 sets the time interval T_{Next} to a default time interval $T_{Default}$ at block 406. Then the time calculation process 400 is complete and returns to the process 200 (FIG. 2) at block 428.

23

Referring to FIGS. 4B and 4C, once the time calculation process 400 calculates the recommended time interval T_{Next} , the process 200 provides a countdown timer 430 that alerts the user 40 when the next blood glucose measurement is due. The countdown timer 430 may be on the display 116 of the patient device 110 or displayed on the display 146 of the hospital system 140. When the timer 430 is complete, a "BG Due!" message might be displayed as shown in FIG. 4B. The countdown timer 430 may include an overdue time 432 indicating the time late if a blood glucose value is not entered as scheduled.

In some implementations, the countdown timer 430 connects to the alarm system 120 of the user device 110. The alarm system 120 may produce an audible sound via the speaker 122 in the form of a beep or some like audio sounding mechanism. The audible and/or visual notification may also be sent via the network to the hospital system 140 (or any other remote station) and displayed on the display 146 of the hospital system 140 or played through speakers 152 of the hospital system 140, or routed to the cell phone or pager of the user. In some examples, the audible alarm using the speakers 122 is turned off by a user selection 434 on the display 116 or it is silenced for a preconfigured time. The display 116, 143 may show information 230 that includes the patient's intravenous treatment information 230a or to the patient's subcutaneous treatment information 230b. In some examples, the user 40 selects the countdown timer 430 when the timer 430 indicates that the patient 10 is due for his or her blood glucose measurement. When the user 40 selects the timer 430, the display 116, 146 allows the user 40 to enter the current blood glucose value BG as shown in FIG. 4D. For intravenous patients 10, the process 200 may ask the user 40 (via the display 116, 146) if the blood glucose is pre-meal blood glucose measurement (as shown in FIG. 4D). When the user 40 enters the information 230 (FIG. 4D), the user 40 selects a continue button to confirm the entered information 230, which leads to the display 116, 146 displaying blood glucose information 230c and a timer 430 showing when the next blood glucose measurement BG is due (FIG. 4E). In addition, the user 40 may enter the patient's blood glucose measurement BG at any time before the timer 430 expires, if the user 40 selects the 'enter BG' button 436. Therefore, the user 40 may input blood glucose values BG at any time, or the user 40 may choose to start the Meal Bolus module process 500 (see FIG. 5) by selecting the start meal button 438 (FIG. 4E), transition the patient to SubQ insulin therapy 600 (see FIG. 6), or discontinue treatment 220.

Referring to FIGS. 5A-5F, in some implementations, the process 200 includes a process where the patient's blood glucose level BG is measured prior to the consumption of caloric intake and calculates the recommended intravenous mealtime insulin requirement necessary to control the patient's expected rise in blood glucose levels during the prandial period. When a user 40 chooses to start the Meal Bolus process 500 (e.g., when the user 40 positively answers that this is a pre-meal blood glucose measurement in FIG. 4D, or when the user 40 selects the start meal button 438 in FIG. 4E), the Meal Bolus process 500, at decision block 504, requests the blood glucose BG of the patient 10 (as shown in FIG. 5C). The user 40 enters the blood glucose value BG at 501 or the system 100 receives the blood glucose BG from a glucometer 124. This blood glucose measurement is referred to herein as the Pre-Meal BG or BG1. In some examples, where the user 40 enters the information, the user 40 selects a continue button to confirm the entered information 230c. In some examples, the intravenous meal bolus

24

process 500 is administered to a patient 10 over a total period of time $T_{MealBolus}$. The total period of time $T_{MealBolus}$ is divided into multiple time intervals $T_{MealBolus1}$ to $T_{MealBolusN}$, where N is any integer greater than zero. In some examples, a first time interval $T_{MealBolus1}$ runs from a Pre-Meal blood glucose value BG1 at measured at time T_1 , to a second blood glucose value BG2 at measured at time T_2 . A second time interval $T_{MealBolus2}$ runs from the second blood glucose value BG2 measured at time T_2 to the third blood glucose value BG3 measured at time T_3 . A third time interval $T_{MealBolus3}$ runs from the third blood glucose value BG3 measured at time T_3 to a fourth blood glucose value BG4 measured at time T_4 . In some implementations where the time intervals $T_{MealBolusN}$ are smaller than $T_{Default}$, the user 40 should closely monitor and control over changes in the blood glucose of the patient 10. For example, a total period of time $T_{MealBolus}$ equals 2 hours, and may be comprised of: $T_{MealBolus1}$ =30 minutes, $T_{MealBolus2}$ =30 minutes, and $T_{MealBolus3}$ =1 hour. This example ends on the fourth blood glucose measurement. When the Meal Bolus process 500 has been activated, an indication 440 is displayed on the display 116, 146 informing the user 40 that the process 500 is in progress. The Meal Bolus process 500 prompts the user 40 if the entered blood glucose value BG is the first blood glucose value prior to the meal by displaying a question on the patient display 116. If the Meal Bolus process 500 determines that the entered blood glucose value BG is the first blood glucose value (BG1) prior to the meal, then the Meal Bolus process 500 freezes the current multiplier M from being adjusted and calculates a regular intravenous insulin rate IRR at block 512. The regular intravenous insulin rate IRR may be determined using EQ. 3A. Meanwhile, at block 502, the Meal Bolus process 500 loads preconfigured meal parameters, such as meal times, insulin type, default number of carbohydrates per meal, the total period of time of the meal bolus process $T_{MealBolus}$, interval lengths (e.g., $T_{MealBolus1}$, $T_{MealBolus1} \cdot \dots \cdot T_{MealBolusN}$), and the percent, "C", of the estimated meal bolus to be delivered in the first interval $T_{MealBolus1}$. In some examples, when the system 100 includes a hospital electronic medical record system 140, nutritional information and number of grams of carbohydrates are retrieved from the hospital electronic medical record systems 140 automatically. The Meal Bolus process 500 allows the user 40 to select whether to input a number of carbohydrates from a selection of standard meals (AcutalCarbs) or to use a custom input to input an estimated number of carbohydrates (EstimatedCarbs) that the patient 10 is likely to consume. The Meal Bolus process 500 then flows to block 506, where the estimated meal bolus rate for the meal is calculated. The calculation process in block 506 is explained in two steps. The first step is calculation of a meal bolus (in units of insulin) in accordance with the following equation:

$$\text{Estimated Meal Bolus} = \text{EstimatedCarbs} / \text{CIR} \quad (11A)$$

where CIR is the Carbohydrate-to-Insulin Ratio, previously discussed.

The Meal Bolus process 500 then determines the Estimated Meal Bolus Rate based on the following equation:

$$\text{Estimated Meal Bolus Rate} = \text{Estimated Meal Bolus} * C / T_{MealBolus1} \quad (11B)$$

Where, $T_{MealBolus1}$ is the time duration of the first time interval of the Meal Bolus total period of time $T_{MealBolus}$. C is a constant adjusted to infuse the optimum portion of the Estimated Meal Bolus during first time interval $T_{MealBolus1}$.

25

For instance: if Estimated Meal Bolus=6 units, $T_{MealBolus1}=0.5$ hours, and $C=25\%$, then applying Eq. 11A as an example:

$$\text{Estimated Meal Bolus Rate} = (6 \text{ units}) * 25\% / (0.5 \text{ hours}) = 3 \text{ units/hour} \quad (11C)$$

The Meal Bolus process **500** calculates the Total Insulin Rate at block **508** as follows:

$$\text{Total Insulin Infusion Rate} = \text{Estimated Meal Bolus Rate} + \text{Regular Intravenous Rate} \quad (12)$$

The Meal Bolus process **500** flows to block **510** where it sets the time interval for the first interval $T_{MealBolus1}$ to its configured value, (e.g., usually 30 minutes), which will end at the second meal bolus blood glucose (BG2).

After the first time interval $T_{MealBolus1}$ expires (e.g., after 30 minutes elapse), the Meal Bolus process **500** prompts the user **40** to enter the blood glucose value BG once again at block **501**. When the Meal Bolus process **500** determines that the entered blood glucose value BG is not the first blood glucose value BG1 entered at block **504** (i.e., the pre-meal BG, BG1, as previously discussed), the process **500** flows to block **514**. At block **514**, the Meal Bolus process **500** determines if the blood glucose value BG is the second value BG2 entered by the user **40**. If the user **40** confirms that the entered blood glucose value BG is the second blood glucose value BG2 entered, the Meal Bolus process **500** uses the just-entered blood glucose BG2 to calculate the intravenous insulin rate IRR at block **516** and flows to block **524**. Simultaneously, if the blood glucose is the second blood glucose BG2, the Meal Bolus process **500** prompts the user **40** to enter the actual amount of carbohydrates that the patient **10** received at block **518**. The Meal Bolus process **500** then determines at decision block **520** and based on the inputted amount of actual carbohydrates, if the patient did not eat, i.e., if the amount of carbohydrates is zero (see FIG. 5C). If the Meal Bolus process **500** determines that the patient did not eat, the Meal Bolus process **500** then flows to block **540**, where the meal bolus module process **500** is discontinued, the multiplier is no longer frozen, and the time interval T_{Next} is restored to the appropriate time interval T_{Next} as determined by process **400**. If however, the Meal Bolus process **500** determines that the patient **10** ate, i.e., the actual carbohydrates is not zero (see FIG. 5D), then The Meal Bolus process **500** flows to block **522**, where it calculates a Revised meal bolus rate according to the following equations, where the Revised Meal Bolus and then an amount of insulin (in units of insulin) are calculated:

$$\text{Revised Meal Bolus} = \text{ActualCarbs} / \text{CIR} \quad (13A)$$

The process at block **522** then determines the amount (in units of insulin) of estimated meal bolus that has been delivered to the patient **10** so far:

$$\text{Estimated Meal Bolus Delivered} = \text{Estimated Meal Bolus Rate} * (T_2 - T_1) \quad (13B)$$

where time T_1 is the time of when the first blood glucose value BG1 is measured and time T_2 is the time when the second blood glucose value BG2 is measured.

The process at block **522** then calculates the portion of the Revised Meal Bolus remaining to be delivered (i.e., the Meal Bolus that has not yet been delivered to the patient **10**) as follows:

$$\text{Revised Meal Bolus Remaining} = \text{Revised Meal Bolus} - \text{Estimated Meal Bolus Delivered} \quad (13C)$$

26

The process at block **522** then calculates the Revised Meal Bolus Rate as follows:

$$\text{Revised Meal Bolus Rate} = \text{Revised Meal Bolus Remaining} / \text{Time Remaining} \quad (14A)$$

where Time Remaining = $T_{MealBolus} - T_{MealBolus1}$. Since the total time interval $T_{MealBolus}$ and the first time interval $T_{MealBolus1}$ are preconfigured values, the Time Remaining may be determined.

The Meal Bolus process **500** calculates the total insulin rate at block **524** by adding the Revised Meal Bolus Rate to the regular Intravenous Rate (IIR), based on the blood glucose value BG:

$$\text{Total Insulin Rate} = \text{Revised Meal Bolus Rate} + \text{IIR} \quad (14B)$$

The Meal Bolus process **500** flows to block **526** where it sets the time interval T_{Next} to the second interval $T_{MealBolus2}$, which will end at the third meal bolus blood glucose BG3 e.g., usually 30 minutes.

After the second interval, $T_{MealBolus2}$ expires (e.g., 30 minutes), the Meal Bolus process **500** prompts the user **40** to enter the blood glucose value BG once again at block **501**. The Meal Bolus process **500** determines that the entered blood glucose value BG is not the first blood glucose value entered at block **504** (previously discussed) and flows to block **514**. The Meal Bolus process **500** determines that the entered blood glucose value BG is not the second blood glucose value entered at block **514** (previously discussed) and flows to block **528**. At block **528**, the Meal Bolus process **500** determines if the blood glucose value BG is the third value entered. If the entered blood glucose value BG is the third blood glucose value BG entered, the Meal Bolus process **500** calculates the intravenous insulin rate IRR at block **530** and flows to block **532**.

At block **532** the process determines the Total Insulin Rate by adding the newly-determined Regular Intravenous Insulin Rate (IIR) to the Revised Meal Bolus Rate, which was determined at BG2 and remains effective throughout the whole meal bolus time, $T_{mealbolus}$.

The Meal Bolus process **500** flows to block **534** where it sets the time interval T_{Next} to the third interval $T_{MealBolus3}$ for the fourth meal bolus blood glucose, e.g., usually 60 minutes. In some implementations, more than 3 intervals ($T_{MealBolus1}$, $T_{MealBolus2}$, $T_{MealBolus3}$) may be used. Additional intervals $T_{MealBolusN}$ may also be used and the process handles the additional intervals $T_{MealBolusN}$ similarly to how it handles the third time interval $T_{MealBolus3}$. As discussed in the current example, the third interval $T_{MealBolus3}$ is the last time interval, which ends with the measurement of the fourth blood glucose measurement BG4.

After the third time interval, $T_{MealBolus3}$, expires (e.g., 60 minutes), the Meal Bolus process **500** prompts the user **40** to enter the blood glucose value BG once again at block **501**. The Meal Bolus process **500** determines that the entered blood glucose value BG is not the first blood glucose value entered at block **504** (previously discussed) and flows to block **514**. The Meal Bolus process **500** determines that the entered blood glucose value BG is not the second blood glucose value entered at block **514** (previously discussed), nor the third blood glucose level entered at block **528** and flows to block **536**. At block **536**, the Meal Bolus process **500** determines that the inputted blood glucose is the fourth blood glucose value BG4. In this example, the fourth blood glucose value BG4 is the last one. The process **500** then flows to block **538** where the multiplier is no longer frozen, and the time interval T_{Next} is restored to the appropriate time interval T_{Next} as determined by the Timer Adjustment

27

process **400** (FIG. **4A**). At this time, the Meal Bolus process **500** ends and the user **40** is prompted with a message indicating that the Meal Bolus process **500** is no longer active.

As shown in FIG. **5D**, and previously discussed with respect to FIGS. **4B-4E**, the process **200** provides a countdown timer **430** that alerts the user **40** when the next blood glucose measurement is due. The countdown timer **430** may be on the display **116** of the patient device **110** or displayed on the display **146** of the hospital system **140**. When the timer **430** is complete, a "BG Due!" message might be displayed as shown in FIG. **4B**. Moreover, the timer **430** may be a countdown timer or a meal timer indicating a sequence of mealtime intervals (e.g., breakfast, lunch, dinner, bedtime, mid-sleep).

In some implementations, a Meal Bolus process **500** may be implemented by the following process on a processor **112**, **132**, **142**. Other processes may also be used.

```

function PreMealIIR($PatientID, $CurrentBG, $Multiplier,
$InsulinConcentration,
    $EstCarbs, $ActualCarbs, $TimeInterval, $InsulinUnitsOfMeasure,
$MealBolusCount) {
    $Iir = array( );
    $CarbInsulinRatio = CIR($PatientID);
    $NormalInsulin = ($CurrentBG - 60) * $Multiplier;
    if($MealBolusCount == 0)
    {
        //first run - Premeal Bolus
        $MealBolus = ($EstCarbs / $CarbInsulinRatio);
        if($MealBolus < 0)
        {
            $MealBolus = 0;
        }
        $Iir[0] = $NormalInsulin + ( $MealBolus * 5 );
        $Iir[2] = ( $MealBolus * 5 );
        /*
        print "Premeal: MX: " . $Multiplier . "<BR>";
        print ($CurrentBG - 60) * $Multiplier;
        print " + ";
        print ( $MealBolus * 5 );
        */
    } else if($MealBolusCount == 1){
        //second run Post Meal Bolus
        //third run time interval coming in is actually the
        //difference between the premeal BG and the first Post Meal BG
        (second run)
        $MealBolus = ($ActualCarbs / $CarbInsulinRatio);
        $OldMealBolus = ($EstCarbs / $CarbInsulinRatio);
        $CurrentMealBolus = ($MealBolus - ($OldMealBolus * 5 *
$TimeInterval))/1.5;
        if($CurrentMealBolus < 0)
        {
            $CurrentMealBolus = 0;
        }
        $Iir[0] = $NormalInsulin + $CurrentMealBolus;
        $Iir[2] = $CurrentMealBolus ;
        /*
        print "PlateCheck: <BR>MX: " . $Multiplier . "<BR>";
        print "Est Carbs: " . $EstCarbs . "<BR>";
        print "ActualCarbs: " . $ActualCarbs . "<BR>";
        print "CarbInsulinRatio: " . $CarbInsulinRatio . "<BR>";
        print "TimeInterval: " . $TimeInterval . "<BR>";
        print "Multiplier: " . $Multiplier;
        */
    }
    else
    {
        $MealBolus = ($ActualCarbs / $CarbInsulinRatio);
        $OldMealBolus = ($EstCarbs / $CarbInsulinRatio);
        /*
        print "Actual Carbs: " . $ActualCarbs . "<BR>";
        print "Est Carbs: " . $EstCarbs . "<BR>";
        print "CIR: " . $CarbInsulinRatio . "<BR>";
        print "Multiplier: " . $Multiplier . "<BR>";
        print "CurrentBG: " . $CurrentBG . "<BR>";
        print "IIR: " . (($CurrentBG - 60) * $Multiplier) . "<BR>";

```

28

-continued

```

    print "MealBolus: " . $MealBolus . "<BR>";
    print "OldMealBolus: " . $OldMealBolus . "<BR>";
    print "TimeInterval: " . $TimeInterval . "<BR>";
    */
    $CurrentMealBolus = ($MealBolus - ($OldMealBolus * 5 *
$TimeInterval))/1.5;
    if($CurrentMealBolus < 0)
    {
        $CurrentMealBolus = 0;
    }
    $Iir[0] = $NormalInsulin + $CurrentMealBolus;
    $Iir[2] = $CurrentMealBolus;
    /*
    print "Post PlateCheck: <BR>MX: " . $Multiplier . "<BR>";
    print "IIR: ";
    print ($CurrentBG - 60) * $Multiplier . "<BR>";
    print "Est Carbs: " . $EstCarbs . "<BR>";
    print "Actual Carbs: " . $ActualCarbs . "<BR>";
    print "Old Meal bolus: " . $OldMealBolus . "<BR>";
    print "TimeInterval: " . $TimeInterval . "<BR>";
    print "Meal bolus: " . $MealBolus . "<BR>";
    print "Final Calc: " . $Iir[0];
    */
    }
    if ($InsulinUnitsOfMeasure != "units/hr")
    {
        $Iir[0] = $Iir[0]/$InsulinConcentration;
    }
    return $Iir;
}

```

Referring to FIGS. **2A** and **6A**, if the user elects to initiate the SubQ Transition process **600**, the SubQ Transition process **600** determines at decision block **604** if the current blood glucose BG is within a preconfigured stability target range BG_{STR} , e.g., 70-180 mg/dl, which is usually wider than the prescribed Target Range, BG_{TR} . If the blood glucose BG is not within the preconfigured stability target range BG_{STR} (e.g., $BG_{Low} < BG < BG_{High}$), the SubQ Transition process **600** at block **606** displays a warning notification on the patient display **116**. Then, at lock **610**, the SubQ Transition process **600** is automatically discontinued.

Referring back to block **604**, if the blood glucose BG is within the preconfigured stability target range BG_{STR} (e.g., 70-180 mg/dl), the SubQ Transition process **600** at decision block **608** determines if the patient's blood glucose measurement BG has been in the patient's personalized prescribed target range BG_{TR} for the recommended stability period T_{Stable} , e.g., 4 hours. If the SubQ Transition process **600** determines that the blood glucose value BG has not been in the prescribed target range BG_{STR} for the recommended stability period T_{Stable} , the SubQ Transition process **600** moves to block **614** where the system **100** presents the user **40** with a warning notification on the patient display **116**, explaining that the patient **10** has not been in the prescribed target range for the recommended stability period (see FIG. **6C**). The SubQ Transition process **600** continues to decision block **618** where it determines whether the user **40** wants the patient **10** to continue the SubQ Transition process or to discontinue the SubQ Transition process. The SubQ Transition process **600** displays on the display **116** of the patient device **110** the question to the user **40** as shown in FIG. **6D**. If the user **40** chooses to discontinue the SubQ Transition process, the SubQ Transition process **600** flows to block **624**, where the SubQ Transition process is discontinued.

Referring back to block **618**, if the user **40** chooses to override the warning and continue the SubQ Transition process, the process **600** prompts the user **40** to enter SubQ information **617**. The SubQ Transition process **600** flows to block **616**, where the patient's SubQ Transition dose is

29

calculated as a patient's total daily dose TDD. In some implementations, TDD is calculated in accordance with equation:

$$\text{TDD} = \text{QuickTransitionConstant} * M_{\text{Trans}} \quad (15A)$$

where QuickTransitionConstant is usually 1000, and M_{Trans} is the patient's multiplier at the time of initiation of the SubQ transition process.

Referring again to block 616, in some implementations TDD is calculated by a statistical correlation of TDD as a function of body weight. The following equation is the correlation used:

$$\text{TDD} = 0.5 * \text{Weight (kg)} \quad (15B)$$

The SubQ Transition process 600 continues to block 620, where the recommended SubQ dose is presented to the user 40 (on the display 116) in the form of a Basal recommendation and a Meal Bolus recommendation (see FIG. 6F).

Referring again to decision block 608, if the SubQ Transition process 600 determines that the patient 10 has been in the prescribed target range BG_{TR} for the recommended stability period, T_{Stable} , SubQ Transition process 600 continues to block 612, where the patient's total daily dose TDD is calculated in accordance with the following equation:

$$\text{TDD} = (BG_{\text{Target}} - K) * (M_{\text{Trans}}) * 24 \quad (16)$$

where M_{Trans} is the patient's multiplier at the time of initiation of the SubQ transition process.

In some implementations, the patient's total daily dose TDD may be determined by the following process on a processor 112, 132, 142. Other processes may also be used.

```
function getIV_TDD($PatientID)
{
  //weight=getOneField("weight", "patients", "patientID",
  $PatientID);
  //return $weight/2;
  $CI=get_instance( );
  $CI->load->model('options');
  $d=$CI->options->GetIVTDDData($PatientID);
  $TargetHigh=$d["TargetHigh"];
  $TargetLow=$d["TargetLow"];
  $Multiplier=$d["Multiplier"];
  $MidPoint=($TargetHigh+$TargetLow)/2;
  $Formula=($MidPoint-60)*$Multiplier*24;
  return $Formula;
}
```

When the patient's total daily dose TDD is calculated, the SubQ Transition process 600 continues to block 620 where the recommended SubQ dose is presented to the user 40 as described above. The SubQ Transition process 600 continues to block 622, where the SubQ Transition process 600 provides information to the user 40 including a recommended dose of Basal insulin. The user 40 confirms that the Basal insulin has been given to the patient 10; this starts a transitions timer using the TransitionRunTime_{Next}, usually 4 hours. At this point, normal calculation rules governing the IIR are still in effect, including the intravenous IIR timer (Timer Adjustment process 400), which continues to prompt for blood glucose tests at time intervals T_{Next} as described previously. The SubQ Transition process 600 passes to decision block 626, which determines whether the recommended time interval TransitionRunTime has elapsed, e.g., 4 hours, after which time SubQ Transition process 600 continues to block 630, providing the user with subcutaneous insulin discharge orders and exiting the IV Insulin process in block 634.

30

FIG. 7 provides an arrangement of operations for a method 700 of administering intravenous insulin to a patient 10. The method 700 includes receiving 702 blood glucose measurements BG on a computing device (e.g., a processor 112 of a patient device 110, a processor 152 of a hospital electronic medical record system 150, or a data processor 132 of a service provider 130) of a dosing controller 160 from a blood glucose measurement device 124 (e.g., glucose meter or glucometer). The blood glucose measurements BG are separated by a time interval T_{Next} . The method 700 includes determining 704, using the computing device 112, 132, 152, an insulin dose rate IIR based on the blood glucose measurements BG. In some implementations, the method 700 determines the insulin dose rate IIR based on a current blood glucose measurement BG, a constant K, and a multiplier M (see EQ. 3A above). The constant K may equal 60 mg/dl. The method 700 includes leaving the multiplier M unchanged between time intervals T_{Next} when the current blood glucose measurement BG is greater than an upper limit BG_{TRH} of the blood glucose target range BG_{TR} and the blood glucose percent drop $BG_{\% \text{ Drop}}$ from the previous blood glucose value BG_P is greater than or equal to a desired percent drop BG % drop M (see EQ. 5). The method 700 also includes multiplying the multiplier M by a change factor M_{CF} when the current blood glucose measurement BG is greater than an upper limit BG_{TRH} of the blood glucose target range BG_{TR} and the blood glucose percent drop $BG_{\% \text{ Drop}}$ (or blood glucose percent drop) is less than the desired percent drop BG % drop M. Additionally or alternatively, the method 700 includes leaving the multiplier M unchanged between time intervals T_{Next} when the current blood glucose measurement BG is in the target range BG_{TR} i.e. when BG is less than an upper limit BG_{TRH} of the blood glucose target range and greater than the lower limit BG_{TRL} of the target range, BG_{TR} . The method 700 also includes dividing the multiplier M by a change factor M_{CF} when the current blood glucose measurement BG is less than the lower limit BG_{TRL} of the blood glucose target range BG_{TR} . The method 700 may include setting the time interval T_{Next} to a hypoglycemia time interval T_{Hypo} of between about 15 minutes and about 30 minutes, when the current blood glucose measurement BG is below a hypo-threshold blood glucose level BG_{Hypo} .

The method 700 includes determining 706 a blood glucose drop rate BG_{DropRate} based on the blood glucose measurements BG and the time interval T_{Next} . The method 700 includes determining 707 a blood glucose percent drop $BG_{\% \text{ Drop}}$, using the computing device 112, 132, 152 from a previous blood glucose measurement BG_P . When the blood glucose drop rate BG_{DropRate} is greater than a threshold drop rate $BG_{\text{DropRateLimit}}$, the method 700 includes decreasing at 708 the time interval T_{Next} between blood glucose measurements measure by the glucometer.

The method 700 also includes decreasing 710 the time interval T_{Next} between blood glucose measurements BG when the percent drop $BG_{\% \text{ Drop}}$ of the blood glucose BG is greater than the threshold of the percent drop % Drop_{Regular}, where the threshold of the percent drop % Drop_{Regular} depends on whether the current blood glucose measurement BG is below a lower limit BG_{TRL} of a blood glucose target range BG_{TR} . In some implementations, the method 700 includes decreasing the time interval T_{Next} when the current blood glucose measurement BG is greater than or equal to the lower limit BG_{TRL} of the blood glucose target range BG_{TR} and the blood glucose percent drop $BG_{\% \text{ Drop}}$ exceeds a threshold percent drop % Drop_{Regular}. In some implementations, the method 700 includes decreasing the time interval

31

T_{Next} when the current blood glucose measurement BG is below the lower limit BG_{TRL} of the blood glucose target range BG_{TR} and above the hypo-threshold blood glucose level BG_{Hypo} , and the blood glucose percent drop $BG\%_{Drop}$ is greater than or equal to a threshold percent drop $\% Drop_{LowLimit}$.

In some examples, the method 700 includes leaving the multiplier M unchanged for at least two subsequent time intervals, T_{Next} , when the current blood glucose measurement BG is a pre-meal measurement. In some examples, the method 700 includes receiving, on the computing device 112, 132, 142, a number of carbohydrates for a meal as well as a blood glucose measurement, and determining, using the computing device 112, 132, 142, an intravenous insulin rate IIR based on the blood glucose (this IIR may be calculated using EQ. 3A). In addition, the method 700 includes determining, using the computing device 112, 132, 142, a meal bolus insulin rate IIR based on the number of carbohydrates. The method 700 then calculates a Total insulin rate as the sum of the meal bolus rate and the regular intravenous rate as shown in EQ. 12. The method 700 may further include setting the time interval T_{Next} to about 30 minutes. If the blood glucose measurement BG is a second consecutive measurement after (but not including) an initial pre-meal blood glucose measurement BG, the method 700 includes setting the time interval T_{Next} to about 30 minutes.

In some implementations, the method 700 includes electronically displaying on a display 116, 146 a warning and blocking transition to a subcutaneous administration of insulin when the current blood glucose measurement BG is outside a stability target range BG_{STR} . In addition, the method 700 includes electronically displaying on the display 116, 146 a warning when the current blood glucose measurement BG is within the patient's personalized target range BG_{TR} for less than a threshold stability period of time T_{Stable} . In some examples, the method 700 includes determining a total daily dose of insulin TDD based on the multiplier M when the current blood glucose measurement BG is within a stability target range BG_{STR} for a threshold stability period of time T_{Stable} .

Various implementations of the systems and techniques described here can be realized in digital electronic circuitry, integrated circuitry, specially designed ASICs (application specific integrated circuits), computer hardware, firmware, software, and/or combinations thereof. These various implementations can include implementation in one or more computer programs that are executable and/or interpretable on a programmable system including at least one programmable processor, which may be special or general purpose, coupled to receive data and instructions from, and to transmit data and instructions to, a storage system, at least one input device, and at least one output device.

These computer programs (also known as programs, software, software applications or code) include machine instructions for a programmable processor and can be implemented in a high-level procedural and/or object-oriented programming language, and/or in assembly/machine language. As used herein, the terms "machine-readable medium" and "computer-readable medium" refer to any computer program product, apparatus and/or device (e.g., magnetic discs, optical disks, memory, Programmable Logic Devices (PLDs)) used to provide machine instructions and/or data to a programmable processor, including a machine-readable medium that receives machine instructions as a machine-readable signal. The term "machine-readable signal" refers to any signal used to provide machine instructions and/or data to a programmable processor.

32

Implementations of the subject matter and the functional operations described in this specification can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. Moreover, subject matter described in this specification can be implemented as one or more computer program products, i.e., one or more modules of computer program instructions encoded on a computer readable medium for execution by, or to control the operation of, data processing apparatus. The computer readable medium can be a machine-readable storage device, a machine-readable storage substrate, a memory device, a composition of matter affecting a machine-readable propagated signal, or a combination of one or more of them. The terms "data processing apparatus", "computing device" and "computing processor" encompass all apparatus, devices, and machines for processing data, including by way of example a programmable processor, a computer, or multiple processors or computers. The apparatus can include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, or a combination of one or more of them. A propagated signal is an artificially generated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus.

A computer program (also known as an application, program, software, software application, script, or code) can be written in any form of programming language, including compiled or interpreted languages, and it can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, or other unit suitable for use in a computing environment. A computer program does not necessarily correspond to a file in a file system. A program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

The processes and logic flows described in this specification can be performed by one or more programmable processors executing one or more computer programs to perform functions by operating on input data and generating output. The processes and logic flows can also be performed by, and apparatus can also be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit).

Processors suitable for the execution of a computer program include, by way of example, both general and special purpose microprocessors, and any one or more processors of any kind of digital computer. Generally, a processor will receive instructions and data from a read only memory or a random access memory or both. The essential elements of a computer are a processor for performing instructions and one or more memory devices for storing instructions and data. Generally, a computer will also include, or be operatively coupled to receive data from or transfer data to, or both, one or more mass storage devices for storing data, e.g., magnetic, magneto optical disks, or optical disks. However,

33

a computer need not have such devices. Moreover, a computer can be embedded in another device, e.g., a mobile telephone, a personal digital assistant (PDA), a mobile audio player, a Global Positioning System (GPS) receiver, to name just a few. Computer readable media suitable for storing computer program instructions and data include all forms of non-volatile memory, media and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto optical disks; and CD ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

To provide for interaction with a user, one or more aspects of the disclosure can be implemented on a computer having a display device, e.g., a CRT (cathode ray tube), LCD (liquid crystal display) monitor, or touch screen for displaying information to the user and optionally a keyboard and a pointing device, e.g., a mouse or a trackball, by which the user can provide input to the computer. Other kinds of devices can be used to provide interaction with a user as well; for example, feedback provided to the user can be any form of sensory feedback, e.g., visual feedback, auditory feedback, or tactile feedback; and input from the user can be received in any form, including acoustic, speech, or tactile input. In addition, a computer can interact with a user by sending documents to and receiving documents from a device that is used by the user; for example, by sending web pages to a web browser on a user's client device in response to requests received from the web browser.

One or more aspects of the disclosure can be implemented in a computing system that includes a backend component, e.g., as a data server, or that includes a middleware component, e.g., an application server, or that includes a frontend component, e.g., a client computer having a graphical user interface or a Web browser through which a user can interact with an implementation of the subject matter described in this specification, or any combination of one or more such backend, middleware, or frontend components. The components of the system can be interconnected by any form or medium of digital data communication, e.g., a communication network. Examples of communication networks include a local area network ("LAN") and a wide area network ("WAN"), an inter-network (e.g., the Internet), and peer-to-peer networks (e.g., ad hoc peer-to-peer networks).

The computing system can include clients and servers. A client and server are generally remote from each other and typically interact through a communication network. The relationship of client and server arises by virtue of computer programs running on the respective computers and having a client-server relationship to each other. In some implementations, a server transmits data (e.g., an HTML page) to a client device (e.g., for purposes of displaying data to and receiving user input from a user interacting with the client device). Data generated at the client device (e.g., a result of the user interaction) can be received from the client device at the server.

While this specification contains many specifics, these should not be construed as limitations on the scope of the disclosure or of what may be claimed, but rather as descriptions of features specific to particular implementations of the disclosure. Certain features that are described in this specification in the context of separate implementations can also be implemented in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented in multiple implementations separately or in any suitable sub-

34

combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may be directed to a sub-combination or variation of a sub-combination.

Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In certain circumstances, multi-tasking and parallel processing may be advantageous. Moreover, the separation of various system components in the embodiments described above should not be understood as requiring such separation in all embodiments, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

A number of implementations have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the disclosure. Accordingly, other implementations are within the scope of the following claims. For example, the actions recited in the claims can be performed in a different order and still achieve desirable results.

What is claimed is:

1. A system comprising:

a glucometer measuring blood glucose measurements separated by a time interval;

an insulin administration device; and

a dosing controller in communication with the glucometer and the insulin administration device, the dosing controller including data processing hardware and non-transitory memory in communication with the data processing hardware, the non-transitory memory storing instructions that when executed by the data processing hardware cause the data processing hardware to perform operations comprising:

receiving blood glucose measurements for a patient from the glucometer, the blood glucose measurements comprising a current blood glucose measurement measured at a current time and a previous blood glucose measurement measured at a previous time earlier than the current time, wherein an elapsed time between the current time and the previous time defines a current time interval;

determining an intravenous insulin infusion rate based on the current blood glucose measurement and the previous blood glucose measurement;

determining a blood glucose percentage drop based on the current blood glucose measurement and the previous blood glucose measurement;

determining a blood glucose drop rate based on the current blood glucose measurement, the previous blood glucose measurement, and the current time interval;

determining a next time interval from the current time until a next time of a next scheduled blood glucose measurement for the patient based on the current blood glucose measurement, the next time interval comprising a shorter duration of time than the current time interval when:

the blood glucose percentage drop is greater than a threshold percentage drop; or

the blood glucose drop rate is greater than a threshold drop rate; and

35

sending the intravenous insulin infusion rate from the data processing hardware to the insulin administration device in communication with the data processing hardware, and when the insulin administration device receives the intravenous insulin infusion rate, the insulin administration device configured to administer insulin to the patient intravenously using the intravenous insulin infusion rate.

2. The system of claim 1, wherein the operations further comprise:

obtaining patient information from the non-transitory memory, the patient information comprising:

a target blood glucose range for the patient comprising a range of blood glucose values between and including a lower limit blood glucose value and an upper limit blood glucose value greater than the lower limit blood glucose value;

a threshold hypoglycemia blood glucose value for the patient, the threshold hypoglycemia blood glucose value less than the lower limit blood glucose value of the target blood glucose range;

a low blood glucose percentage drop limit for the patient when the current blood glucose measurement is less than the lower limit blood glucose value of the target blood glucose range;

a regular blood glucose percentage drop limit for the patient when the current blood glucose measurement is greater than or equal to the lower limit blood glucose value of the target blood glucose range;

a blood glucose drop rate limit for the patient; and a stable time period comprising a recommended duration of time required for the current blood glucose measurement within the target blood glucose range to determine a blood glucose concentration for the patient is stable in the target blood glucose range,

wherein determining the next time interval comprises setting the next time interval to a default time interval or one:

a preconfigured hypoglycemia time interval when the current blood glucose measurement is less than the threshold hypoglycemia blood glucose value;

a preconfigured short time interval when:

the current blood glucose measurement is greater than the threshold hypoglycemia blood glucose value and less than the lower limit blood glucose value of the target blood glucose range and the blood glucose percentage drop is greater than the low blood glucose percentage drop limit; or

the current blood glucose measurement is greater than or equal to the lower limit blood glucose value of the target blood glucose range and the blood glucose percentage drop is greater than the regular blood glucose percentage drop limit;

a preconfigured blood glucose drop rate time interval when the blood glucose drop rate is greater than the blood glucose drop rate limit;

a preconfigured long time interval when the current blood glucose measurement has been within the blood glucose target range for a duration of time greater than the stable time period; or

a preconfigured meal bolus time interval when a meal bolus program is in operation, and

wherein the hypoglycemia time interval is less than the short time interval, the short time interval is less than the blood glucose drop rate time interval, the blood

36

glucose drop rate time interval is less than the long time interval, and the meal bolus time interval is less than the long time interval.

3. The system of claim 2, wherein determining the intravenous insulin infusion rate comprises calculating:

$$IIR = (BG - K) * M$$

wherein IIR is the intravenous insulin infusion rate, BG is the current blood glucose measurement, K is a constant, and M is a multiplier,

wherein determining the blood glucose percentage drop comprises calculating:

$$\text{Percentage drop} = \left(\frac{BG_{\text{Previous}} - BG}{BG_{\text{Previous}}} \right)$$

wherein BG_{Previous} is the previous blood glucose measurement and BG is the current blood glucose measurement, and

wherein determining the blood glucose drop rate comprises calculating:

$$BG_{\text{DropRate}} = (BG_{\text{Previous}} - BG) / (T_{\text{Current}} - T_{\text{Previous}})$$

wherein BG_{DropRate} is the blood glucose drop rate, BG is the current blood glucose measurement, BG_{Previous} is the previous blood glucose measurement, T_{Current} is the current time and T_{Previous} is the previous time.

4. The system of claim 3, wherein the operations further comprise:

leaving the multiplier unchanged between time intervals when the current blood glucose measurement is greater than the upper limit blood glucose value of the target blood glucose range and a ratio of the current blood glucose measurement divided by the previous blood glucose measurement is less than or equal to a threshold ratio; and

multiplying the multiplier by a change factor when the current blood glucose measurement is greater than the upper limit blood glucose value of the target blood glucose range and the ratio of the current blood glucose measurement divided by the previous blood glucose measurement is greater than the threshold ratio.

5. The system of claim 4, wherein the constant K equals 60 mg/dl and the threshold ratio is 0.85.

6. The system of claim 4, wherein the operations further comprise dividing the multiplier by the change factor when the current blood glucose measurement is less than the lower limit blood glucose value of the target blood glucose range.

7. The system of claim 3, wherein, in response to receiving an indication of patient solid food consumption, the operations further comprise increasing the intravenous insulin infusion rate and maintaining the multiplier unchanged for at least two time intervals.

8. The system of claim 7, wherein the operations further comprise:

receiving a number of estimated grams of carbohydrates for a meal;

determining an estimated meal bolus in units of insulin based on the number of estimated grams of carbohydrates and a carbohydrate-insulin-ratio;

determining an estimated meal bolus insulin rate, based on the estimated meal bolus, an available delivery time, and a configurable constant;

determining a total insulin rate as a sum of the intravenous insulin rate and the estimated meal bolus insulin rate; and

37

sending the total insulin rate from the data processing hardware to the insulin administration device.

9. The system of claim 8, wherein the operations further comprise:

dividing a total meal time into meal time sub-intervals, a first meal time sub-interval starting with a pre-meal blood glucose measurement before receiving the indication of patient solid food consumption; and determining the total insulin rate for each meal time sub-interval in succession.

10. The system of claim 9, wherein the operations further comprise:

receiving a number of actual grams of carbohydrates for the meal during a subsequent meal time sub-interval after the first meal time sub-interval; determining an actual meal bolus based on the number of actual grams of carbohydrates; determining an estimated delivered meal bolus by multiplying the estimated meal bolus rate by an elapsed delivery time; determining a remaining meal bolus in units of insulin by subtracting a product of the estimated delivered meal bolus insulin rate and an actual delivery time from the actual meal bolus; determining a revised meal bolus insulin rate as the remaining meal bolus divided by a time remaining in the total meal time; determining a revised total insulin rate as a sum of the intravenous insulin rate and the revised meal bolus insulin rate; and sending the revised total insulin rate from the data processing hardware to the insulin administration device.

11. The system of claim 10, wherein one or more of the meal time sub-intervals comprise a shorter duration of time than the default time interval.

12. The system of claim 11, wherein the operations further comprise:

electronically displaying on a display in communication with the data processing hardware a warning and blocking transition to a subcutaneous administration of insulin when the current blood glucose measurement is outside a stability target range included within the obtained patient information, the stability target range comprising a wider range of blood glucose values than

38

the range of blood glucose values associated with the target blood glucose range; and electronically displaying on the display a warning when the current blood glucose measurement is within the stability target range for less than a threshold stability period of time.

13. The system of claim 3, wherein the operations further comprise:

determining a total daily dose of insulin based on the multiplier when the current blood glucose measurement is within a stability target range for a threshold stability period of time;

determining recommended insulin doses comprising a daily basal insulin and a daily meal insulin for subcutaneous therapy as an apportioning of the total daily dose of insulin, wherein the daily basal insulin is half of the total daily dose of insulin and the daily meal insulin is half of the total daily dose of insulin; and

sending the recommended insulin doses from the data processing hardware to a subcutaneous injection device or electronically displaying the recommended insulin doses on a display in communication with the data processing hardware.

14. The system of claim 13, further comprising determining the total daily dose of insulin by calculating:

$$TDD = (BG_{Target} - K) * (M_{Trans}) * 24$$

wherein TDD is the total daily dose of insulin, M_{Trans} is a current multiplier at a moment of initiation of a process of a transition to subcutaneous insulin treatment; and

BG_{Target} is determined by calculating:

$$BG_{Target} = (BR_{TRH} + BR_{TRL}) / 2$$

wherein BR_{TRH} is the upper limit blood glucose value of the blood glucose target range and BR_{TRL} is the lower limit blood glucose value of the target blood glucose range.

15. The system of claim 13, further comprising determining the total daily dose of insulin as a function of a patient body weight by calculating:

$$TDD = 0.5 * \text{Weight}$$

wherein TDD is the total daily dose of insulin and Weight is a patient body weight in kilograms.

* * * * *