



(51) International Patent Classification:

C07C 4/18 (2006.01) C07C 15/06 (2006.01)

C07C 4/24 (2006.01) C07C 15/08 (2006.01)

C07C 6/12 (2006.01) C07C 15/04 (2006.01)

(21) International Application Number:

PCT/US2020/028614

(22) International Filing Date:

17 April 2020 (17.04.2020)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

16/388,563 18 April 2019 (18.04.2019) US

(71) Applicant: SAUDI ARABIAN OIL COMPANY
[SA/SA]; 1 Eastern Avenue, Dhahran, 31311 (SA).

(71) Applicant (for AG only): ARAMCO SERVICES COMPANY [US/US]; Law Department, Two Allen Center 1200 Smith St., 27th Floor, Houston, TX 77002 (US).

(72) Inventors: KOSEOGLU, Omer Refa; Saudi Arabian Oil Company, P. O. Box 8560, Saudi Aramco, Dhahran, 31311

(SA). HODGKINS, Robert; Saudi Arabian Oil Company, P. O. Box 10981, Saudi Aramco, Dhahran, 31311 (SA).

(74) Agent: RHEBERGEN, Constance Gall; Bracewell LLP, P.O. Box 61389, Houston, TX 77208-1389 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, ST, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,

(54) Title: METHODS AND SYSTEMS OF UPGRADING HEAVY AROMATICS STREAM TO PETROCHEMICAL FEEDS-TOCK




FIG. 1

(57) Abstract: Provided here are systems and methods that integrate a hydrodearylation process and a transalkylation process into an aromatic recovery complex. Various other embodiments may be disclosed and claimed.

TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
KM, ML, MR, NE, SN, TD, TG).

Published:

— *with international search report (Art. 21(3))*

PCT PATENT APPLICATION
METHODS AND SYSTEMS OF UPGRADING HEAVY AROMATICS STREAM
TO PETROCHEMICAL FEEDSTOCK

Inventors: Omer Refa KOSEOGLU
Robert HODGKINS

Technical Field

[0001] The disclosure relates to methods and systems of upgrading heavy aromatics stream to petrochemical feedstock, and more specifically to a combination of a hydrodearylation unit and a transalkylation unit in an aromatics recovery complex.

Background

[0002] In an aromatics complex, a variety of process units are used to convert naphtha or pyrolysis gasoline into benzene, toluene and mixed xylenes, which are basic petrochemical intermediates used for the production of various other chemical products. In order to maximize the production of benzene, toluene and mixed xylenes, the feed to an aromatics complex is generally limited from C₆ up to C₁₁ compounds. In most aromatic complexes, the mixed xylenes are processed within the complex to produce the particular isomer—para-xylene, which can be processed downstream to produce terephthalic acid. This terephthalic acid is used to make polyesters, such as polyethylene terephthalate. In order to increase the production of benzene and para-xylene, the toluene and C₉ and C₁₀ aromatics are processed within the complex through a toluene, C₉, C₁₀ transalkylation/toluene disproportionation (TA/TDP) process unit to produce benzene and xylenes. Any remaining toluene, C₉, and C₁₀ aromatics are recycled to extinction. Compounds heavier than

C₁₀ are generally not processed in the TA/TDP unit, as they tend to cause rapid deactivation of the catalysts used at the higher temperatures used in these units, often greater than 400 °C.

[0003] When para-xylene is recovered from mixed xylenes by a selective adsorption process unit in the complex, the C₈ feed to the selective adsorption unit is processed to eliminate olefins and alkenyl aromatics such as styrene in the feed. Olefinic material can react and occlude the pores of the zeolite adsorbent. The olefinic material is removed by passing a C₈₊ stream across a clay or acidic catalyst to react olefins and alkenyl aromatics with another (typically aromatic) molecule, forming heavier compounds (C₁₆₊). These heavier compounds are typically removed from the mixed xylenes by fractionation. The heavy compounds cannot be processed in the TA/TDP unit due to their tendency to deactivate the catalyst and are generally removed from the complex as lower value fuels blend stock. As many of the heavy alkyl aromatic compounds fractionate with the fractions containing greater than 10 carbon atoms, they are not typically sent as feedstock to the transalkylation unit, and instead are sent to gasoline blending or used as fuel oil.

SUMMARY OF THE INVENTION

[0004] A need has been recognized for the characterization and recovery of higher value light aromatics in the range from C₆ to C₁₀ from certain heavy compounds before processing aromatic streams through specialized product production units, such as the TA/TDP unit. Embodiments disclosed here include characterization of the products formed during the treatment of aromatics streams during processing of hydrocarbons. Certain embodiments include processes for recovery of alkyl mono-aromatic compounds. An embodiment of the process for recovery of alkyl mono-aromatic compounds includes the steps of (a) supplying a feed stream containing C₉₊ compounds from an aromatic complex to a separator to produce a first product stream containing C₉ and C₁₀ compounds and a second product stream containing one or more of heavy alkyl aromatic compounds and alkyl-bridged non-condensed alkyl multi-aromatic compounds; (b) supplying the first product stream containing C₉ and C₁₀ compounds to a transalkylation/toluene disproportionation process unit to yield a third product stream enriched in C₈ compounds; (c) allowing a hydrogen stream and the second product stream to react in presence of a catalyst under specific reaction conditions in a hydrodearylation reactor to yield a fourth product stream containing one or more alkyl mono-aromatic compounds and a fifth product stream containing C₁₁₊ compounds; and (d) supplying the fourth product stream to the toluene transalkylation/toluene disproportionation process unit to produce alkyl mono-aromatic compounds. In an embodiment, the fourth product stream and the first product stream containing C₉ and C₁₀ compounds are mixed to form a feed stream for the toluene transalkylation/toluene disproportionation process unit. The feed stream can be from a xylene rerun column of an aromatic recovery process. The feed stream can be undiluted by a solvent. A portion of the hydrogen stream may be supplied to a catalyst bed in the hydrodearylation reactor to quench the catalyst bed. The process can further include supplying the fourth product stream containing one or more alkyl mono-aromatic compounds to a separator to recover a benzene-containing stream; and supplying the benzene-containing stream to the toluene transalkylation/toluene disproportionation process unit to produce alkyl mono-aromatic compounds. The process can further include recovering a C₈ stream from the separator; and supplying the C₈ stream to a para-xylene unit to produce para-xylene. The process can further include recovering a C₉₊ stream from the separator; and supplying the C₉₊ stream to the toluene transalkylation/toluene disproportionation process unit to produce alkyl mono-aromatic compounds. The process can further include supplying the fourth product stream containing one

or more alkyl mono-aromatic compounds to a separator to recover a toluene-containing stream; and supplying the toluene-containing stream to the toluene transalkylation/toluene disproportionation process unit to produce alkyl mono-aromatic compounds.

[0005] The catalyst in the hydrodearylation reactor can include a support made of one or more of silica, alumina, titania, and a combination thereof. The catalyst in the hydrodearylation reactor can further include an acidic component being at least one member of the group consisting of amorphous silica-alumina, zeolite, and combinations thereof. The zeolite can be one or more of or derived from FAU, *BEA, MOR, MFI, or MWW framework types, wherein each of these codes correspond to a zeolite structure present in the database of zeolite structures as maintained by the Structure Commission of the International Zeolite Association. The catalyst in the hydrodearylation reactor can include an IUPAC Group 6-10 metal that is at least one member of the group consisting of iron, cobalt, nickel, molybdenum, tungsten, and combinations thereof. The IUPAC Group 8-10 metal can be present ranging from 2 to 20 percent by weight of the catalyst and the IUPAC Group 6 metal can be present ranging from 1 to 25 percent by weight of the catalyst. The conditions in the hydrodearylation reactor can include an operating temperature in the range of about 200 to 450 °C, or about 250 to 450 °C and an operating hydrogen partial pressure in the range of about 5 bar gauge to 100 bar gauge. One of the alkyl mono-aromatic compounds produced by the toluene transalkylation/toluene disproportionation is a para-xylene.

[0006] Certain embodiments include systems for recovery of alkyl mono-aromatic compounds. An embodiment of a system for conversion of alkyl-bridged non-condensed alkyl multi-aromatic compounds to alkyl mono-aromatic compounds includes the following components: (i) a first separator adapted to receive a feed stream containing one or more of heavy alkyl aromatic compounds and one or more alkyl-bridged non-condensed alkyl multi-aromatic compounds having at least two benzene rings connected by an alkyl bridge group with at least two carbons and the benzene rings being connected to different carbons of the alkyl bridge group, and produces a first product stream containing C₉ and C₁₀ compounds and a second product stream containing one or more of heavy alkyl aromatic compounds and alkyl-bridged non-condensed alkyl multi-aromatic compounds; (ii) a hydrodearylation reactor fluidly coupled to the first separator and adapted to receive a hydrogen stream and the second product stream and to produce a third product stream in presence of a catalyst, the third product stream containing one or more alkyl mono-aromatic compounds; and (iii) a second separator fluidly coupled to the hydrodearylation reactor and

adapted to receive the third product stream and to produce a benzene-containing stream, a toluene-containing stream, a C₈-rich stream, and a bottoms C₉₊ stream. The system can also include a transalkylation unit fluidly coupled to the second separator and adapted to receive the first product stream and one or more of the benzene-containing stream, the toluene-containing stream, and the bottoms C₉₊ stream, and to produce alkyl mono-aromatic compounds. The system can also include a para-xylene unit fluidly coupled to the second separator and adapted to receive the C₈-rich stream and to produce a para-xylene-rich stream.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] Embodiments will be readily understood by the following detailed description in conjunction with the accompanying drawings. Embodiments are illustrated by way of example and not by way of limitation in accompanying drawings.

[0008] **FIG. 1** is a schematic representation of certain components of an aromatics processing system that upgrades fuel oil to a petrochemical feedstock, according to an exemplary embodiment.

[0009] **FIG. 2** is a schematic representation of certain components of an aromatics processing system that upgrades fuel oil to a petrochemical feedstock, according to an exemplary embodiment.

[0010] **FIG. 3** is a schematic representation of certain components of an aromatics processing system that upgrades fuel oil to a petrochemical feedstock, according to an exemplary embodiment.

[0011] **FIG. 4** is a schematic representation of certain components of an aromatics processing system that upgrades fuel oil to a petrochemical feedstock, according to an exemplary embodiment.

DETAILED DESCRIPTION OF THE INVENTION

[0012] The present disclosure describes various embodiments related to processes, devices, and systems for conversion of alkyl-bridged non-condensed alkyl aromatic compounds to alkyl mono-aromatic compounds. Further embodiments are described and disclosed.

[0013] In the following description, numerous details are set forth in order to provide a thorough understanding of the various embodiments. In other instances, well-known processes, devices, and systems may not have been described in particular detail in order not to unnecessarily obscure the various embodiments. Additionally, illustrations of the various embodiments may omit certain features or details in order to not obscure the various embodiments. Here, reference is made to the accompanying drawings that form a part of this disclosure. The drawings may provide an illustration of some of the various embodiments in which the subject matter of the present disclosure may be practiced. Other embodiments may be utilized, and logical changes may be made without departing from the scope of this disclosure. Therefore, the following detailed description is not to be taken in a limiting sense.

[0014] The description may use the phrases “in some embodiments,” “in various embodiments,” “in an embodiment,” or “in embodiments,” which may each refer to one or more of the same or different embodiments. Furthermore, the terms “comprising,” “including,” “having,” and the like, as used with respect to embodiments of the present disclosure, are synonymous.

[0015] As used in this disclosure, the term “hydrodearylation” refers to a process for cleaving of the alkyl bridge of non-condensed alkyl-bridged multi-aromatics or heavy alkyl aromatic compounds to form alkyl mono-aromatics, in the presence a catalyst and hydrogen.

[0016] As used in this disclosure, the term “stream” (and variations of this term, such as hydrocarbon stream, feed stream, product stream, and the like) may include one or more of various hydrocarbon compounds, such as straight chain, branched or cyclical alkanes, alkenes, alkadienes, alkynes, alkyl aromatics, alkenyl aromatics, condensed and non-condensed di-, tri- and tetra-aromatics, and gases such as hydrogen and methane, C₂₊ hydrocarbons and further may include various impurities.

[0017] As used in this disclosure, the term “zone” refers to an area including one or more equipment, or one or more sub-zones. Equipment may include one or more reactors or reactor

vessels, heaters, heat exchangers, pipes, pumps, compressors, and controllers. Additionally, an equipment, such as reactor, dryer, or vessels, further may include one or more zones.

[0018] As used in this disclosure, the term “rich” means an amount of at least 30% or greater, by mole percentage of a compound or class of compounds in a stream. Certain streams rich in a compound or class of compounds can contain about 50% or greater, by mole percentage of the particular compound or class of compounds in the streams. In certain cases, mole percentage may be replaced by weight percentage, in accordance with standard industry usage.

[0019] As used in this disclosure, the term “mixed xylenes” refers to a mixture containing one or more C₈ aromatics, including any one of the three isomers of di-methylbenzene and ethylbenzene. As used in this disclosure, the term “conversion” refers to the conversion of compounds containing multiple aromatic rings or mono-aromatic compounds with heavy (C₄+) alkyl groups boiling above 210 °C to mono-aromatic compounds with a lighter alkyl groups boiling below 210 °C.

[0020] During hydrocarbon processing, compounds composed of an aromatic ring with one or more coupled alkyl groups containing three or more carbon molecules per alkyl group are formed. Formation of these compounds may be from processes used by petroleum refiners and petrochemical producers to produce aromatic compounds from non-aromatic hydrocarbons, such as catalytic reforming. As many of these heavy alkyl aromatic compounds fractionate with the fractions containing greater than 10 carbon atoms, they are not typically sent as feedstock to the transalkylation unit, and instead are sent to gasoline blending or used as fuel oil. The methods and systems disclosed here result in upgrading a low-value fuel oil to petrochemical feed.

[0021] Provided here is an embodiment of a process to fractionate an effluent stream of a xylene re-run column and supply it as a feed stream to a hydrodearylation unit. In an embodiment, this stream is either subsequently processed or used to upgrade the fuel oil components (heavy fraction) to petrochemical feedstock. Methods and system disclosed here create value by processing a reject/bottoms stream from an aromatic complex and by upgrading a significant proportion of fuel oil into petrochemical feedstock. In an embodiment, the C₉+ stream from a xylene re-run column is fractionated to remove C₉ and C₁₀, leaving a C₁₁+ stream, which is considered as a low-value fuel oil stream. The C₉ and C₁₀ stream is directed to a TA/TDP process unit to yield increased quantities of C₈ that can be further processed downstream to yield para-xylene. The C₁₁+ fuel oil stream is subjected to hydrodearylation and the hydrodearylated liquid products sent for processing

in a transalkylation unit. The unconverted C₁₁₊ (mainly condensed diaromatics) stream is directed as fuel oil.

[0022] Disclosed here is a process for recovery of alkyl mono-aromatic compounds that includes the following steps. A feed stream containing C₉₊ compounds from an aromatic complex is supplied to a separator to produce a first product stream containing C₉ and C₁₀ compounds and a second product stream containing one or more of heavy alkyl aromatic compounds and alkyl-bridged non-condensed alkyl multi-aromatic compounds. In an embodiment, the feed stream is from a xylene rerun column of an aromatic recovery process. In certain embodiments, the feed stream is undiluted by solvents and is directly supplied to the separator. In an embodiment, the second product stream contains C₁₁₊ compounds. This first product stream containing C₉ and C₁₀ compounds is supplied to a TA/TDP process unit to yield a third product stream enriched in C₈ compounds. The second product stream and a hydrogen stream are supplied to a hydrodearylation reactor to react in presence of a catalyst under specific reaction conditions to yield a fourth product stream containing C₉ and C₁₀ compounds and a fifth product stream containing unconverted C₁₁₊ compounds. The fourth product stream is supplied further to a TA/TDP process unit to supply and produce alkyl mono-aromatic compounds. In certain embodiments, the C₈ content in the fourth product stream increases following the processing in the TA/TDP process unit. In certain embodiments, the fifth product stream containing unconverted C₁₁₊ compounds can be recycled to the hydrodearylation reactor. In certain embodiments, the fourth product stream and the first product stream containing C₉ and C₁₀ compounds are mixed to form a feed stream for the TA/TDP process unit. In certain embodiments, the alkyl mono-aromatic compounds produced by the TA/TDP process unit is para-xylene. In certain embodiments, the hydrodearylated products are supplied to a separator to recover a benzene-containing stream. And this benzene-containing stream can be directed to an appropriate part of the TA/TPD process unit. In certain embodiments, the hydrodearylated products are supplied to a separator to recover a toluene-containing stream. And this toluene-containing stream can be directed to an appropriate part of the TA/TPD process unit.

[0023] In an embodiment, the feedstock to the hydrodearylation reactor (either whole or fractionated) is mixed with an excess of hydrogen gas in a mixing zone. A portion of the hydrogen gas is mixed with the feedstock to produce a hydrogen-enriched liquid hydrocarbon feedstock. This hydrogen-enriched liquid hydrocarbon feedstock and undissolved hydrogen is supplied to a

flashing zone in which at least a portion of undissolved hydrogen is flashed, and the hydrogen is recovered and recycled. The hydrogen-enriched liquid hydrocarbon feedstock from the flashing zone is supplied as a feed stream to the hydrodearylation reactor. The hydrodearylated liquid product stream that is recovered from the hydrodearylation reactor is further processed as provided here.

[0024] In certain embodiments, the hydrogen stream is combined with the second product stream before being supplied to the hydrodearylation reactor. In certain embodiments, the hydrogen stream includes a recycled hydrogen stream and a makeup hydrogen stream. In certain embodiments, the hydrogen stream comprises at least 70% hydrogen by weight. The catalyst can be presented as a catalyst bed in the reactor. In certain embodiments, a portion of the hydrogen stream is fed to the catalyst bed in the reactor to quench the catalyst bed. In certain embodiments, the catalyst bed is comprised of two or more catalyst beds. The catalyst can include a support that is at least one member of the group consisting of silica, alumina, titania, and combinations thereof, and further includes an acidic component that is at least one member of the group consisting of amorphous silica-alumina, zeolite, and combinations thereof. The zeolite can be one or more of or derived from FAU, *BEA, MOR, MFI, or MWW framework types, wherein each of these codes correspond to a zeolite structure present in the database of zeolite structures as maintained by the Structure Commission of the International Zeolite Association. In certain embodiments, the catalyst includes an IUPAC Group 8-10 metal and an IUPAC Group 6 metal. In certain embodiments, the catalyst includes an IUPAC Group 8-10 metal that is at least one member of the group consisting of iron, cobalt, and nickel, and combinations thereof. The catalyst includes an IUPAC Group 6 metal that is at least one member of the group consisting of molybdenum and tungsten, and combinations thereof. In certain embodiments, the IUPAC Group 8-10 metal is 2 to 20 percent by weight of the catalyst and the IUPAC Group 6 metal is 1 to 25 percent by weight of the catalyst. In certain embodiments, the catalyst is comprised of nickel, molybdenum, ultrastable Y-type zeolite, and silica-alumina support.

[0025] In certain embodiments, the specific reaction conditions include an operating temperature of the reactor during the hydrodearylation reaction that is in the range of 200 to 450 °C. In certain embodiments, the specific reaction conditions include an operating temperature of the reactor during the hydrodearylation reaction that is in the range of 250 to 350 °C. In certain embodiments, the specific reaction conditions include an operating temperature of the reactor during the

hydrodearylation reaction that is in the range of 300 to 350 °C. The specific reaction conditions can include a hydrogen partial pressure of the reactor during the hydrodearylation reaction that is in the range of 5 to 100 bar gauge. In certain embodiments, the specific reaction conditions can include a hydrogen partial pressure of the reactor during the hydrodearylation reaction that is in the range of 50 to 100 bar gauge. In certain embodiments, the specific reaction conditions can include a hydrogen partial pressure of the reactor during the hydrodearylation reaction that is in the range of 5 to 80 bar gauge. In certain embodiments, the specific reaction conditions can include a hydrogen partial pressure of the reactor during the hydrodearylation reaction that is in the range of 5 to 30 bar gauge. The hydrogen partial pressure of the reactor during the hydrodearylation reaction can be maintained at less than 20 bar gauge. The specific reaction conditions can include a feed rate of the hydrogen stream that is in the range of 100 to 1000 standard liter per liter of feedstock. The specific reaction conditions can include a feed rate of the hydrogen stream that is in the range of 100 to 300 standard liter per liter of feedstock.

[0026] In an embodiment, a system is provided for conversion of alkyl-bridged non-condensed alkyl multi-aromatic compounds to alkyl mono-aromatic compounds. The system includes (i) a first separator that receives a feed stream containing one or more of heavy alkyl aromatic compounds and one or more alkyl-bridged non-condensed alkyl multi-aromatic compounds having at least two benzene rings connected by an alkyl bridge group with at least two carbons and the benzene rings that is connected to different carbons of the alkyl bridge group, and produces a first product stream containing C₉ and C₁₀ compounds and a second product stream containing one or more of heavy alkyl aromatic compounds and alkyl-bridged non-condensed alkyl multi-aromatic compounds; (ii) a hydrodearylation reactor fluidly coupled to the first separator and adapted to receive a hydrogen stream and the second product stream and to produce a third product stream in presence of a catalyst, and the third product stream containing one or more alkyl mono-aromatic compounds; (iii) a second separator fluidly coupled to the hydrodearylation reactor and adapted to receive the third product stream and to produce a benzene-containing stream, a toluene-containing stream, a C₈-rich stream, and a bottoms C₉₊ stream. In certain embodiments, the system further includes a transalkylation unit that is adapted to receive the toluene-containing stream and the bottoms C₉₊ stream and to produce alkyl mono-aromatic compounds. In order to increase the production of benzene and para-xylene, the toluene and C₉ and C₁₀ aromatics are processed within the complex through a toluene, C₉, C₁₀ transalkylation/toluene disproportionation (TA/TDP)

process unit to produce benzene and xylenes. Any remaining toluene, C₉, and C₁₀ aromatics are recycled to extinction. In certain embodiments, the second product stream is a C₁₁₊ stream. In certain embodiments, the alkyl mono-aromatic compounds produced by the transalkylation unit includes para-xylene.

[0027] A typical refinery with an aromatic complex contains the following units: an atmospheric distillation unit, a diesel hydrotreating unit, an atmospheric residue unit, a naphtha hydrotreating unit, a naphtha reforming unit and an aromatics complex. The whole crude oil is distilled in an atmospheric distillation column to recover a naphtha fraction (compounds with a boiling point ranging from 36 °C to 180 °C), diesel fraction (compounds with a boiling point ranging from 180 °C to 370 °C) and atmospheric residue fraction (compounds with a boiling point at 370 °C or higher). The naphtha fraction is hydrotreated in a naphtha hydrotreating unit to reduce the sulfur and nitrogen content to less than 0.5 part per million by weight and the hydrotreated naphtha fraction is sent to a catalytic reforming unit to improve its quality, such as, an increase in the octane number to produce gasoline blending stream or feedstock for an aromatics recovery unit. Similarly, the diesel fraction is hydrotreated in a separate hydrotreating unit to desulfurize the diesel oil to obtain diesel fraction meeting the stringent specifications of sulfur content that is less than 10 parts per million. The atmospheric residue fraction is either used a fuel oil component or sent to other separation / conversion units to convert low value hydrocarbons to high value products. The reformat fraction from the catalytic reforming unit can be used as gasoline blending component or sent to an aromatic complex to recover high value aromatics, such as, benzene, toluene, and xylenes. The reformat fraction from catalytic reforming unit is split into two fractions: light and heavy reformat. The light reformat is sent to a benzene extraction unit to extract the benzene and recover gasoline that is substantially free of benzene. The heavy reformat stream is sent to a para-xylene (p-xylene) extraction unit to recover p-xylene. Other xylenes that are recovered from the p-xylene unit are sent to a xylene isomerization unit to convert them to p-xylene. The converted fraction is recycled to the p-xylene extraction unit. The heavy fraction from the p-xylene extraction unit is recovered as a process reject or bottoms stream. The aromatics bottoms fraction from an aromatic recovery complex is processed in two ways. One, the aromatics bottoms fraction is fractionated into a 180– °C fraction ((compounds with a boiling point less than 180 °C) and sent to a gasoline pool as blending components, and a 180+ °C fraction sent to a hydrodearylation unit. Alternatively, the aromatics bottoms fraction is sent directly to a

hydrodearylation unit to recover light alkyl mono-aromatic compounds from heavy alkyl aromatic and alkyl-bridged non-condensed alkyl aromatic compounds. A typical system for aromatic transalkylation to ethylbenzene and xylenes includes the following components: a first transalkylation reactor, a series of separators, a second transalkylation reactor, a stabilizer, and a p-xylene production unit. The feed stream to the first transalkylation reactor is a mixture of a C₉₊ alkyl aromatics mixture and benzene. This feed stream is brought into contact with a zeolite catalyst in the first transalkylation reactor. The effluent stream from this transalkylation reactor is directed to a separation column. This effluent stream may be combined with effluent streams from the second transalkylation reactor before entry into a separation column. There are three exit streams from the separation column: an overhead stream containing benzene, a bottoms stream of C₈₊ aromatics including ethylbenzene and xylenes, and a side-cut stream containing toluene. The overhead stream is recycled to the first transalkylation reactor. The bottoms stream is supplied to a second separation column. An overhead stream containing ethylbenzene and xylenes from the second separation column is directed to a para-xylene unit to produce a para-xylene product stream and a bottoms stream of C₉₊ alkylaromatics. The side-cut stream from the separation column is recycled to a second transalkylation unit with or without the recovery of toluene. This side-cut stream from the separation column can be combined with bottoms stream from second separation column to form a combined stream that is supplied to a third separation column. This separation column separates the combined stream into a bottoms stream of C₁₁₊ alkylaromatics ("heavies") and an overhead stream of C₉, C₁₀ alkylaromatics, and lighter compounds (including C₇ alkylaromatics) directed to a second transalkylation unit. Hydrogen is also supplied to the second transalkylation unit. Here, in the second transalkylation unit, the overhead stream and hydrogen are brought in contact with a transalkylation catalyst, and the effluent stream is directed to a stabilizer column. Two streams exit the stabilizer column: an overhead stream of light end hydrocarbons (generally comprising at least ethane) and a bottom stream of a second transalkylation product.

[0028] As previously described, the aromatic bottoms stream from an aromatic recovery complex can be directly supplied to a hydrodearylation unit and a hydrodearylated liquid product stream can be recovered for further processing. In an embodiment **100** as described in **FIG. 1**, the aromatic bottoms stream **104** from an aromatic recovery complex **102** is sent to a separator **106**. In an embodiment, this separator **106** can be a separation unit including a distillation column with

5 or more theoretical trays. In an embodiment, the separator **106** can be a flash vessel or a stripper. Two streams exit the separator **106**: an overhead stream **108** containing C₉ and C₁₀ compounds and a bottoms stream **110** containing C₁₁₊ compounds. In an embodiment, the overhead stream **108** contains about 50–99 wt.% of the C₉ and C₁₀ compounds. In another embodiment, the overhead stream **108** contains about 60–99 wt.% of the C₉ and C₁₀ compounds. In an embodiment, the overhead stream **108** contains about 80–99 wt.% of the C₉ and C₁₀ compounds. For example, simulated distillation data indicated that the overhead stream **108** contains about 90–99 wt.% of the C₉ and C₁₀ compounds. And this data aligned with the two-dimensional gas chromatography data obtained in this instance, which revealed the stream **104** as containing about 91 wt.% of the C₉ and C₁₀ compounds. The C₉₊ feed from a refinery can be “heavy” with a different composition. In other instances, the C₉ and C₁₀ compounds made up about 68 wt.% of the feed as determined by two-dimensional gas chromatography. The bottoms stream **110** containing C₁₁₊ compounds is directed to a hydrodearylation unit **112** for processing into a hydrodearylated liquid product stream **114**. In an embodiment, the bottoms stream **110** contains about 5–99 wt.% of C₁₁₊ compounds. In another embodiment, the bottoms stream **110** contains about 30–99 wt.% of C₁₁₊ compounds. In an embodiment, the bottoms stream **110** contains about 80–99 wt.% of C₁₁₊ compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains greater than 10 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains greater than 20 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains greater than 40 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains about 50 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains about 70 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains about 90 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains less than 70 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains less than 50 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains less than 40 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains less than 20 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **114** contains less than 10 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid

product stream **114** contains less than 1 wt.% of di-aromatic compounds. The overhead stream **108** containing C₉ and C₁₀ compounds is combined with the hydrodearylated liquid product stream **114** leaving the hydrodearylation unit, and this combined stream **116** is supplied to a transalkylation reactor for further processing.

[0029] In another embodiment, the aromatic bottoms stream from an aromatic recovery complex is sent to a separator. In an embodiment, this separator can be a separation unit including a distillation column with 5 or more theoretical trays. In an embodiment, the separator can be a flash vessel or a stripper. In an embodiment **200** as described in **FIG. 2**, the aromatic bottoms stream **204** from an aromatic recovery complex **202** is sent to a first separator **206**. Two streams exit the first separator **206**: an overhead stream **208** containing C₉ and C₁₀ compounds and a bottoms stream **210** containing C₁₁₊ compounds. In an embodiment, the overhead stream **208** contains about 50–99 wt.% of the C₉ and C₁₀ compounds. In another embodiment, the overhead stream **208** contains about 60–99 wt.% of the C₉ and C₁₀ compounds. In an embodiment, the overhead stream **208** contains about 80–99 wt.% of the C₉ and C₁₀ compounds. In an embodiment, the overhead stream **208** contains about 90–99 wt.% of the C₉ and C₁₀ compounds. The bottoms stream **210** containing C₁₁₊ compounds is directed to a hydrodearylation unit **212** for processing a hydrodearylated liquid product stream **214**. In an embodiment, the bottoms stream **210** contains about 5–99 wt.% of C₁₁₊ compounds. In another embodiment, the bottoms stream **210** contains about 30–99 wt.% of C₁₁₊ compounds. In an embodiment, the bottoms stream **210** contains about 80–99 wt.% of C₁₁₊ compounds. The hydrodearylated liquid product stream **214** is supplied to a second separator **216**. In an embodiment, the hydrodearylated liquid product stream **214** contains about 10 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains about 20 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains about 40 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains about 50 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains about 70 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains about 90 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains less than 70 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains less than 40 wt.% of di-aromatic compounds.

In an embodiment, the hydrodearylated liquid product stream **214** contains less than 20 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains less than 10 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **214** contains less than 1 wt.% of di-aromatic compounds. The hydrodearylated liquid product stream **214** is supplied to a second separator **216**. Four streams exit the second separator **216**: a benzene-containing stream **218**, a toluene-containing stream **220**, a C₈-containing stream **222**, and a bottoms C₉₊ stream **224**. In an embodiment, the benzene-containing stream **218** contains less than 30 wt.% of benzene. In another embodiment, the benzene-containing stream **218** contains less than 20 wt.% of benzene. In another embodiment, the benzene-containing stream **218** contains less than 10 wt.% of benzene. In another embodiment, the benzene-containing stream **218** contains less than 5 wt.% of benzene. The toluene-containing stream **220** can be directed to a transalkylation reactor as a feed stream. In the transalkylation reactor, the toluene is combined with a C₉₊ stream to produce alkyl mono-aromatic compounds. In an embodiment, the toluene-containing stream **220** contains less than 30 wt.% of toluene. In another embodiment, the toluene-containing stream **220** contains less than 20 wt.% of toluene. In another embodiment, the toluene-containing stream **220** contains less than 15 wt.% of toluene. In another embodiment, the toluene-containing stream **220** contains less than 10 wt.% of toluene. The C₈-containing stream **222** is directed to the p-xylene production unit. In an embodiment, the C₈-containing stream **222** contains less than 30 wt.% of C₈ compounds, such as xylene and ethylbenzene. In another embodiment, the C₈-containing stream **222** contains less than 20 wt.% of these C₈ compounds. In another embodiment, the C₈-containing stream **222** contains less than 10 wt.% of these C₈ compounds. The C₉₊ stream **224** can be supplied as part of a feed stream **226** to a transalkylation unit. In an embodiment, the C₉₊ stream **224** is combined with the overhead stream **208** containing C₉ and C₁₀ compounds and supplied as part of a feed stream **226** to the transalkylation unit.

[0030] In an embodiment **300** as described in **FIG. 3**, the aromatic bottoms stream from an aromatic recovery complex is sent to a first separator **302**. Two streams exit the first separator **302**: an overhead stream **304** containing C₉ and C₁₀ compounds and a bottoms stream **306** containing C₁₁₊ compounds. In an embodiment, the overhead stream **304** contains about 50–99 wt.% of the C₉ and C₁₀ compounds. In another embodiment, the overhead stream **304** contains about 60–99 wt.% of the C₉ and C₁₀ compounds. In an embodiment, the overhead stream **304** contains about

80–99 wt.% of the C₉ and C₁₀ compounds. For example, simulated distillation data indicated that the overhead stream **304** contains about 90–99 wt.% of the C₉ and C₁₀ compounds.

[0031] In an embodiment, the overhead stream **304** containing C₉ and C₁₀ compounds can be supplied as part of a feed stream **320** to a transalkylation unit. The bottoms stream **306** containing C₁₁₊ compounds is directed to a hydrodearylation unit **308** for processing into a hydrodearylated liquid product stream **310**. In an embodiment, the bottoms stream **306** contains about 5–99 wt.% of C₁₁₊ compounds. In another embodiment, the bottoms stream **306** contains about 30–99 wt.% of C₁₁₊ compounds. In an embodiment, the bottoms stream **306** contains about 80–99 wt.% of C₁₁₊ compounds. The hydrodearylated liquid product stream **310** is sent to a second separator **312**. In an embodiment, the hydrodearylated liquid product stream **310** contains about 10 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains about 20 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains about 40 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains about 50 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains about 70 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains about 90 wt.% of alkyl mono-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains less than 70 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains less than 40 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains less than 20 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains less than 10 wt.% of di-aromatic compounds. In an embodiment, the hydrodearylated liquid product stream **310** contains less than 1 wt.% of di-aromatic compounds.

[0032] Four streams exit the second separator **312**: a benzene-containing stream **314**, a first toluene-containing stream **316**, a first C₈-containing stream **318**, and a bottoms C₉₊ stream. In an embodiment, the benzene-containing stream **314** contains less than 30 wt.% of benzene. In another embodiment, the benzene-containing stream **314** contains less than 20 wt.% of benzene. In another embodiment, the benzene-containing stream **314** contains less than 10 wt.% of benzene. In another embodiment, the benzene-containing stream **314** contains less than 5 wt.% of benzene. In an embodiment, the first toluene-containing stream **316** contains less than 30 wt.% of toluene. In

another embodiment, the first toluene-containing stream **316** contains less than 20 wt.% of toluene. In another embodiment, the first toluene-containing stream **316** contains less than 15 wt.% of toluene. In another embodiment, the first toluene-containing stream **316** contains less than 10 wt.% of toluene.

[0033] In an embodiment, the first C₈-containing stream **318** contains less than 30 wt.% of C₈ compounds, such as xylene and ethylbenzene. In another embodiment, the first C₈-containing stream **318** contains less than 20 wt.% of these C₈ compounds. In another embodiment, the first C₈-containing stream **318** contains less than 10 wt.% of these C₈ compounds.

[0034] In an embodiment, the bottoms C₉₊ stream is supplied as part of a feed stream **320** to a transalkylation unit. The benzene-containing stream **314** is sent to a third separator **322**. Two streams exit the third separator **322**: a benzene-enriched stream **324** that is directed to a transalkylation reactor, and a second toluene-containing stream **326** that is directed to a fourth separator **328**, either as a separate feed stream or as a mixture with the first toluene-containing stream **316**. The first toluene-containing stream **316** can be supplied independently to the fourth separator **328**. Two streams exit the fourth separator **328**: a toluene-enriched stream **330** that is directed to a transalkylation reactor, and a second C₈-containing stream **332** that is directed to a fifth separator **334**, either as a separate feed stream or as a mixture with the first C₈-rich stream **318**. The first C₈-rich stream **318** can be supplied independently to the fifth separator **334**. Two streams exit the fifth separator **334**: a C₈-rich stream **336** that is directed to a p-xylene production unit, and a C₉₊-containing stream **338** that is directed to the transalkylation unit, either as a separate feed stream or as a mixture with the bottoms C₉₊ stream **320**. In an embodiment, the C₉₊-containing stream **338** is combined with the overhead stream **304** containing C₉ and C₁₀ compounds from the first separator **302** and supplied as a feed stream **340** to the transalkylation unit. In another embodiment, the overhead stream **304** containing C₉ and C₁₀ compounds from the first separator **302**, the bottoms C₉₊ stream **320** from the second separator **312**, and the C₉₊-containing stream **338** from the fifth separator **334** are combined and supplied as a feed stream **340** to a transalkylation unit. In another embodiment, each of these streams can be separately supplied to the first transalkylation unit.

[0035] Described here is a method and a system used for aromatic transalkylation to ethylbenzene and xylenes. In an embodiment **400** as described in **FIG. 4**, the aromatic bottoms stream from an

aromatic recovery complex is sent to a hydrodearylation unit **402**. The hydrodearylated liquid product stream **404**, exiting from the hydrodearylation unit **402**, may also contain benzene, toluene and C₈ compounds, along with C₉₊ alkyl aromatics. The hydrodearylated liquid product stream **404** is mixed with a benzene-containing stream **406** to form a feed stream **408**. The feed stream **408** is supplied to a transalkylation reactor **410** either with or without an additional hydrogen stream **412**. The feed stream **408** in the presence of a catalyst is converted to a first product stream **414** containing benzene, C₈₊ aromatics including ethylbenzene and xylenes, and toluene. The first product stream **414** from the transalkylation reactor is directed to a first separation column **416**. The first product stream **414** is separated into three fractions: a first overhead stream **418** containing benzene, a first bottoms stream **420** containing C₈₊ aromatics including ethylbenzene and xylenes, and a side-cut stream **422** containing toluene. The overhead stream **418** is recycled to the first transalkylation unit after benzene is removed via stream **424**. The first bottoms stream **420** of C₈₊ aromatics, including ethylbenzene and xylenes, from the first separation column **416** is directed to a second separation column **426**. Two streams are recovered from this second separation column **426**: a second overhead stream **428** of ethylbenzene and xylenes, which is directed to a para-xylene unit **430** to produce a para-xylene-rich stream **432**, and a second bottoms stream **434** of C₉₊ alkylaromatics. The side-cut stream **422** from the first separation column **416** is supplied as part of a feed stream **436** to a third separation column **438** after additional toluene is added or removed (not shown in **FIG. 4**). Toluene is normally recycled to extinction by reacting with C₉ and C₁₀ to produce benzene and C₈. If there is a decrease or lack of toluene in the system, make-up toluene may be required. If there is a decrease or lack of C₉/C₁₀, the amount of toluene can be proportionately reduced to make the stoichiometry. Certain market conditions may influence the removal of toluene from the system. The side-cut stream **422** is mixed with the second bottoms stream **434** of C₉₊ alkylaromatics to form a combined feed stream **436** that is supplied to the third separation column **438**. Two streams are recovered from this third separation column **438**: a third bottoms stream **440** of C₁₁₊ alkylaromatics and an overhead stream **442** of C₉ and C₁₀ alkylaromatics and lighter compounds (including C₇ alkylaromatics) directed to the transalkylation unit **410**. In certain embodiments, the unconverted products can be recycled to the hydrodearylation unit **402** (not shown in **FIG. 4**).

[0036] Described here are processes and systems to fractionate the reject/bottoms stream of a xylene re-run column and to upgrade the fuel oil components (heavy fraction) to petrochemical

feedstock. Also described are embodiments to upgrade the as-received reject/bottoms stream from the xylene re-run column. The C₉₊ stream from a xylene re-run column is fractionated to remove C₉ and C₁₀, leaving a C₁₁₊ stream, which is considered as a low-value fuel oil stream. The C₉ and C₁₀ stream is directed to a TA/TDP process unit to be processed to yield increased quantities of C₈ that can be further processed downstream to yield para-xylene. The C₁₁₊ fuel oil stream is subjected to hydrodearylation. The unconverted C₁₁₊ (mainly condensed diaromatics) stream is directed as fuel oil (approximately 25 wt.% of the original fuel oil stream). The methods and systems disclosed here allow a low-value fuel oil stream to be upgraded into petrochemical feedstock. Approximately 75% of the fuel oil is converted to isomer grade mixed xylenes.

Examples

A couple of methods and systems for integration of a hydrodearylation process with a transalkylation process are illustrated here. While the particular example provided below is for a stream containing C₉₊ compounds, the methods and systems for integration of a hydrodearylation process with a transalkylation process can utilize a C₁₁₊ feed.

[0037] Example 1

[0038] About 7.97 kilograms of an aromatic bottoms fraction, derived from a non-fractionated C₉₊ feed, was distilled using a lab-scale true boiling point distillation column with 15 or more theoretical plate using the ASTM D2892 method. The feed stream contains about 83 weight percent (wt.%) of a gasoline fraction (compounds with a boiling point ranging from 36 °C to 180 °C) and about 17 wt.% of a residue fraction (compounds with a boiling point above 180 °C).

[0039] Properties and composition of the feed stream are shown in **Tables 1** and **2**.

[0040] Table 1

Property	Feedstock Aromatics Bottoms	Gasoline Fraction	Residue Fraction
Density	0.8834	0.8762	0.9181
Octane Number ASTM D2799	Not applicable	108	Not applicable

[0041] *Table 2*

Property	Boiling Point, °C (Feedstock Aromatics Bottoms)	Boiling Point, °C (Gasoline Fraction)	Boiling Point, °C (Residue Fraction)
Initial Boiling Point	153	154	163
10 wt. %	163	164	190
30 wt. %	166	166	202
50 wt. %	172	171	231
70 wt. %	175	174	289
90 wt. %	191	183	324
Final Boiling point	337	204	359

[0042] In an example of a hydrodearylation process, a feedstock consisting of a non-fractionated xylene rerun column bottoms stream with the above described properties was treated in a hydrodearylation reaction zone containing a catalyst having nickel and molybdenum with ultrastable Y-type (USY) zeolite on a silica-alumina support operated at hydrodearylation conditions including a temperature ranging from 280 to 340 °C, at a hydrogen partial pressure of 15 or 30 bar, a liquid hourly space velocity of 1.7 hr⁻¹. Feed and hydrodearylated liquid product compositions, as analyzed by two-dimensional gas chromatography, are provided in *Table 3*.

[0043] *Table 3*

Run	Temperature	Pressure	MA	NMA	MN	DN	P	NDA	DA	TrA
#	°C	Bar	Wt. %	Wt. %	Wt. %	Wt. %	Wt. %	Wt. %	Wt. %	Wt. %
Feed	0	0	92.28	1.82	0.15	0.12	0.37	0.59	4.34	0.33
1	340	30	91.67	2.91	2.1	0.43	0.94	0.43	1.38	0.15
3	320	30	92.95	3.04	1.56	0.33	0.37	0.45	1.16	0.13

5	300	30	92.98	3.13	1.33	0.29	0.34	0.51	1.3	0.13
7	280	30	93.2	3.1	0.95	0.23	0.3	0.54	1.55	0.14
15	340	15	93.47	2.38	0.46	0.17	0.55	0.59	2.13	0.26
17	320	15	93.69	2.15	0.34	0.1	0.4	0.72	2.34	0.26
19	300	15	93.73	2.1	0.29	0.08	0.35	0.71	2.46	0.29
21	280	15	93.63	2.09	0.27	0.08	0.33	0.77	2.54	0.28

Key for Table 2- MA: Mono Aromatics; NMA: Naphtheno Mono Aromatics; MN: Mono-Naphthenes; DN: Di-naphthenes; P: Paraffins; NDA: Naphtheno Di Aromatics; DA: Diaromatics; and TrA: Tri Aromatics

[0044] For example, subjecting the feed to hydrodearylation conditions in the presence of the catalyst and hydrogen at 320 °C and 30 bar, there is an approximately 75% reduction in diaromatic content. The decrease in the diaromatic content demonstrates that hydrodearylation has occurred and the low-value heavy components of the stream have been upgraded to higher value components. The technology also takes a low-value fuel oil from an aromatic bottoms/reject stream from an aromatic complex and upgrades the fuel oil to petrochemical feedstock.

[0045] Ranges may be expressed herein as from about one particular value and to about another particular value. When such a range is expressed, it is to be understood that another embodiment is from the one particular value and/or to the other particular value, along with all combinations within said range. Where the range of values is described or referenced here, the interval encompasses each intervening value between the upper limit and the lower limit as well as the upper limit and the lower limit and includes smaller ranges of the interval subject to any specific exclusion provided. Where a method comprising two or more defined steps is recited or referenced herein, the defined steps can be carried out in any order or simultaneously except where the context excludes that possibility. While various embodiments have been described in detail for the purpose of illustration, they are not to be construed as limiting, but are intended to cover all the changes and modifications within the spirit and scope thereof.

CLAIMS

What is claimed is:

1. A process for recovery of alkyl mono-aromatic compounds, the process comprising the steps of:

supplying a feed stream containing C₉₊ compounds from an aromatic complex to a separator to produce a first product stream containing C₉ and C₁₀ compounds and a second product stream containing one or more of heavy alkyl aromatic compounds and alkyl-bridged non-condensed alkyl multi-aromatic compounds;

supplying the first product stream containing C₉ and C₁₀ compounds to a transalkylation/toluene disproportionation process unit to yield a third product stream enriched in C₈ compounds;

allowing a hydrogen stream and the second product stream to react in presence of a catalyst under specific reaction conditions in a hydrodearylation reactor to yield a fourth product stream containing one or more alkyl mono-aromatic compounds and a fifth product stream containing C₁₁₊ compounds; and

supplying the fourth product stream to the toluene transalkylation/toluene disproportionation process unit to produce alkyl mono-aromatic compounds.

2. The process of claim 1, wherein the fourth product stream and the first product stream containing C₉ and C₁₀ compounds are mixed to form a feed stream for the toluene transalkylation/toluene disproportionation process unit.
3. The process of claim 1, wherein the feed stream is from a xylene rerun column of an aromatic recovery process.
4. The process of any one of claims 1 to 3, wherein the feed stream is undiluted by a solvent.
5. The process of any one of claims 1 to 4, wherein a portion of the hydrogen stream is supplied to a catalyst bed in the hydrodearylation reactor to quench the catalyst bed.
6. The process of any one of claims 1 to 5, wherein the catalyst includes a support being at least one member of the group consisting of silica, alumina, titania, and combinations thereof, and

further includes an acidic component being at least one member of the group consisting of amorphous silica-alumina, alumina, zeolite, and combinations thereof.

7. The process of claim 6, wherein the zeolite is one or more of or derived from FAU, *BEA, MOR, MFI, or MWW framework types.

8. The process of any one of claims 1 to 7, wherein the catalyst includes an IUPAC Group 6-10 metal being at least one member of the group consisting of iron, cobalt, nickel, molybdenum, tungsten, and combinations thereof.

9. The process of claim 8, wherein the wherein the IUPAC Group 8-10 metal is 2 to 20 percent by weight of the catalyst and the IUPAC Group 6 metal is 1 to 25 percent by weight of the catalyst.

10. The process of any one of claims 1 to 9, wherein conditions in the hydrodearylation reactor include an operating temperature in the range of 200 to 450 °C.

11. The process of any one of claims 1 to 9, wherein conditions in the hydrodearylation reactor include an operating temperature in the range of 250 to 450 °C.

12. The process of any one of claims 1 to 11, wherein conditions in the hydrodearylation reactor include an operating hydrogen partial pressure in the range of 5 bar gauge to 100 bar gauge.

13. The process of any one of claims 1 to 12, wherein one of the alkyl mono-aromatic compounds produced by the toluene transalkylation/toluene disproportionation is a para-xylene.

14. The process of any one of claims 1 to 13, further comprising:

supplying the fourth product stream containing one or more alkyl mono-aromatic compounds to a separator to recover a benzene-containing stream; and

supplying the benzene-containing stream to the toluene transalkylation/toluene disproportionation process unit to produce alkyl mono-aromatic compounds.

15. The process of claim 14, further comprising:

recovering a C₈ stream from the separator; and

supplying the C₈ stream to a para-xylene unit to produce para-xylene.

16. The process of claim 14, further comprising:

recovering a C₉₊ stream from the separator; and

supplying the C₉₊ stream to the toluene transalkylation/toluene disproportionation process unit to produce alkyl mono-aromatic compounds.

17. The process of any one of claims 1 to 13, further comprising:

supplying the fourth product stream containing one or more alkyl mono-aromatic compounds to a separator to recover a toluene-containing stream; and

supplying the toluene-containing stream to the toluene transalkylation/toluene disproportionation process unit to produce alkyl mono-aromatic compounds.

18. A system for conversion of alkyl-bridged non-condensed alkyl multi-aromatic compounds to alkyl mono-aromatic compounds, the system comprising:

a first separator adapted to receive a feed stream containing one or more of heavy alkyl aromatic compounds and one or more alkyl-bridged non-condensed alkyl multi-aromatic compounds having at least two benzene rings connected by an alkyl bridge group with at least two carbons and the benzene rings being connected to different carbons of the alkyl bridge group, and produces a first product stream containing C₉ and C₁₀ compounds and a second product stream containing one or more of heavy alkyl aromatic compounds and alkyl-bridged non-condensed alkyl multi-aromatic compounds;

a hydrodearylation reactor fluidly coupled to the first separator and adapted to receive a hydrogen stream and the second product stream and to produce a third product stream in presence of a catalyst, the third product stream containing one or more alkyl mono-aromatic compounds; and

a second separator fluidly coupled to the hydrodearylation reactor and adapted to receive the third product stream and to produce a benzene-containing stream, a toluene-containing stream, a C₈-rich stream, and a bottoms C₉₊ stream.

19. The system of claim 18, further comprising:

a transalkylation unit fluidly coupled to the second separator and adapted to receive the first product stream and one or more of the benzene-containing streams, the toluene-containing stream, and the bottoms C₉₊ stream, and to produce alkyl mono-aromatic compounds.

20. The system of claim 18 or claim 19, further comprising:

a para-xylene unit fluidly coupled to the second separator and adapted to receive the C₈-rich stream and to produce a para-xylene-rich stream.




FIG. 1




FIG. 2

300




FIG. 3




FIG. 4

INTERNATIONAL SEARCH REPORT

International application No
PCT/US2020/028614

A. CLASSIFICATION OF SUBJECT MATTER

INV. C07C4/18 C07C4/24 C07C6/12 C07C15/06 C07C15/08
C07C15/04

ADD.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 2018/127812 A1 (SABIC GLOBAL TECHNOLOGIES BV [NL]) 12 July 2018 (2018-07-12) figure 1 paragraph [0005] paragraph [0038] - paragraph [0052] paragraph [0073] - paragraph [0078] page 26 - page 27; table 3 page 27 - page 29; example 4; table 4 -----	1-20



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

7 July 2020

Date of mailing of the international search report

15/07/2020

Name and mailing address of the ISA/

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040,
Fax: (+31-70) 340-3016

Authorized officer

Patteux, Claudine

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No

PCT/US2020/028614

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2018127812 A1	12-07-2018	CN 110139915 A	16-08-2019
		EP 3565869 A1	13-11-2019
		JP 2020514297 A	21-05-2020
		US 2020017773 A1	16-01-2020
		WO 2018127812 A1	12-07-2018
