

United States Patent [19]

Grote et al.

[11] E

[45] Reissued Date of Patent: Apr. 12, 1994

[54] SHAMPOO COMPOSITIONS

- [75] Inventors: Mark B. Grote, Cincinnati; Glen D. Russell, Loveland, both of Ohio
- [73] Assignce: The Procter & Gamble Company, Cincinnati, Ohio
- [21] Appl. No.: 517,111
- [22] Filed: May 1, 1990

Related U.S. Patent Documents

Reissue of:

[64]	Patent No.:	4,741,855
	Issued:	May 3, 1988
	Appl. No.:	80,022
	Filed:	May 3, 1988

- U.S. Applications:
- [63] Continuation of Ser. No. 795,285, Nov. 5, 1985, abandoned, which is a continuation-in-part of Ser. No. 670,189, Nov. 9, 1984, abandoned.
- [51] Int. Cl.⁵ A61K 7/075; C11D 3/20; C11D 9/36; C11D 17/08
- - 424/73
- [58] Field of Search 252/DIG. 13, 89.1, 142, 252/174.15, 312, 546, 547, 548, DIG. 5, 173; .424/70, 73

[56] References Cited

U.S. PATENT DOCUMENTS

2,406,671	8/1946	Diamond	252/49.6
2,523,281	9/1950	Currie	106/3
2,584,413	2/1952	Baer et al	106/11
2,586,211	2/1952	Currie	
2,595,928	5/1952	Currie et al.	252/358
2,666,685	1/1954	Hommel et al	106/38.22
2,702,276	2/1955	Green	252/8.6
2,755,194	7/1956	Volkmann et al	106/285
2,757,094	7/1956	Guss	106/8

2,757,152	7/1956	Solomon 260/29.2
2,799,599	7/1957	Koch 117/141
2,803,614	8/1957	Solomon 260/29.4
2.826.551	3/1958	Geen .
2.829.112	4/1958	Solomon 252/358
2,833,658	5/1958	May 106/38.24
2.891.920		Hyde et al
2.955.047		Terry 106/3
		Johnson et al 260/29.2
		Chevalier
3,136,696	6/1964	Harrison 167/85
		Dawson et al 117/138.8
3,140,120	1/1204	Dawson ct al

Patent Number: Re. 34,584

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

1261276	9/1989	Canada .			
103450	1/1966	Denmark			
35899	9/1981	European	Pat.	Off.	
57837	8/1982	European	Pat.	Off.	

(List continued on next page.)

OTHER PUBLICATIONS

Bennett, H., Editor, 1974, Chemical Formulary, vol. XVIII, p. 167.

Ash et al., 1980, A Formulary of Detergents and Other Cleansing Agents, p. 76.

(List continued on next page.)

Primary Examiner-Linda Skaling

Attorney, Agent, or Firm-Steven J. Goldstein

[57] ABSTRACT

Shampoos are disclosed which comprise a synthetic surfactant, an insoluble, non-volatile silicone, a suspending agent and water. Suitable suspending agents include long chain esters of ethylene glycol, esters of long chain fatty acids, long chain amine oxides among many others.

20 Claims, No Drawings

•• .

U.S. PATENT DOCUMENTS

3,185,627	5/1965	Kass 167/90
3,200,080	8/1965	Martin et al 252/358
3,210,208 10	0/1965	Grass et al 106/148
	2/1966	Nitzsche et al 252/358
3,294,709 12	2/1966	Nitzsche et al 260/23
3,336,231	8/1967	Marsh et al 252/152
3,382,150	5/1968	Grass et al 167/82
3,393,078	7/1968	Lockhart et al 106/8
3,395,028	7/1968	Mackles 106/8
3,423,340	1/1969	Marshall et al 260/13
3,433,780	3/1969	Cekada et al 260/29.2
3,488,217	1/1970	Ryan 117/138.8
3,510,433	5/1970	Pasowicz 252/180
	2/1970	Holdstock et al 260/29.2
3,634,285	1/1972	Brooks 252/312
3,650,979	3/1972	Steinbach et al 252/358
3,653,955	4/1972	Habib 117/139.5
3,655,865	4/1972	Murphy 424/45
3,691,091	9/1972	Koerner 252/358
3,755,560	8/1973	Dickert et al 424/78
3,795,538	3/1974	Evans et al 117/139.5
3,836,647	9/1974	Lange 424/184
3,847,622 1	1/1974	Brandl et al 106/10
3,849,348 1	1/1974	Hewitt 252/547
3,852,075 1	2/1974	Basadur 106/11
3,872,038	3/1975	Adams et al 260/13
3,925,242 1	2/1975	Sagi et al 252/321
3,929,492 1	2/1975	Chapman et al 106/3
3,931,079	1/1976	Wise et al 260/28.5
3,950,510	4/1976	Adams 424/70
3,957,970	5/1976	Korkis 424/70
3,964,500	6/1976	Drakoff 132/7
3,965,518	6/1976	Muoio 15/104
3,975,294	8/1976	Dumoulin 252/354
3,980,617	9/1976	Jacquet et al 260/47
4,005,044	1/1977	Raleigh 252/358
4,012,334	3/1977	Raleigh 252/321
4,013,475	3/1977	Liebowitz et al 106/10
4,020,199	4/1977	Nomura et al 427/334
4,032,473	6/1977	Berg et al 252/358
4,039,469	8/1977	Raleigh 252/358
	0/1977	Buhler 424/358
4,061,585 1	2/1977	Finn et al 252/89 R
4,071,468	1/1978	Abel et al 252/321
4,075,118	2/1978	Gault et al 252/135
4,080,310	3/1978	Ng et al 252/544
4,089,882	7/1978	Lang et al 424/59
4,113,677	9/1978	Svedas et al 260/23
	10/1978	Horiuchi et al 106/38
4,118,423	10/1978	Vanierberghe et al 260/584
4,151,301	4/1979	Kalopissis 424/316

4,177,177	12/1979	Vanderhoff et al 260/29.2
4,179,426	12/1979	Steinbach et al
4,183,917	1/1980	Iwao et al 424/70
4,185,087	1/1980	Morlino 424/70
4,194,988	3/1980	Schneider et al 252/312
4,208,301	6/1980	Gammon 252/321
4,218,250	8/1980	Kasprzak 106/3
4,225,456	9/1980	Schmidt et al 252/321
4,229,479	10/1980	Brickl et al 424/331
4,244,742	1/1981	Huber et al 106/38.22
4,244,948	1/1981	Boghosian et al 424/230
4,246,029	1/1981	Sanders et al 106/3
4,254,104	3/1981	Suzuki 424/170
4,269,739	5/1981	Grejsner 252/547
4,272,519	6/1981	Herrold et al 424/83
4,273,584	6/1981	D'Angelo et al 106/3
4,274,977	6/1981	Koerner et al 252/358
4,275,222	6/1981	Scala, Jr 560/103
4,278,657	7/1981	Tezuka et al 424/63
4,281,201	7/1981	Abend 564/506
4,288,356	9/1981	Huebner et al
4,302,364	11/1981	Gosset et al 252/545
4,333,862	6/1982	Smith et al 252/547
4,337,166	6/1982	Hill et al 252/174.15
4,338,375	7/1982	Hashimoto et al 428/412
4,341,799	7/1982	Good 424/365
4,342,742	8/1982	Sebag et al 424/59
4,345,080	8/1982	Bolich 546/6
4,364,837	12/1982	Pader
4,383,062	5/1983	Saad et al
4,388,437	6/1983	Ona
4,390,451	6/1983	Havinga et al 252/311
4,391,765	7/1983	Lee et al
4,395,352	7/1983	Kulkarni et al 252/321
4,405,490	9/1983	Maas et al
4,412,943	11/1983	Hirota et al
4,421,656	12/1983	Donatelli et al 252/8.5 P Dixon et al
4,421,769	12/1983	Dixon et al
4,423,041	12/1983	Clum et al 424/184 Vanlerberghe et al 424/358
4,425,364	1/1984 2/1984	Puhringer
4,433,013		Albanese
4,439,342	3/1984 4/1984	Shimizu et al
4,443,359	6/1984	Bolich, Jr
4,452,732 4,465,619	8/1984	Boskamp
4,470,982	9/1984	Winkler
4,473.667	9/1984	Sands
4,476,282	10/1984	Koerner et al
4,479,893	10/1984	Hirota et al
4,497,919	2/1985	Varga et al
4,501.619	2/1985	Gee
4,001,019	4, 1705	

(List continued on next page.)

.

U.S. PATENT DOCUMENTS

•			
4,509,981	4/1985	Sanders, Jr. et al	106/3
4,509,984	4/1985	Scheiderich et al	. 106/38.22
4,511,489	4/1985	Requejo et al	252/172
4,518,727	5/1985	Traver	524/35
4,522,808	6/1985	Jacquet et al	424/59
4,524,172	6/1985	Steinberger et al	524/506
4,525,502	6/1985	Traver	524/96
4,529,586	7/1985	DeMarco et al	424/70
4,529,758	7/1985	Traver	524/43
4,534,981	8/1985	Zabotto et al	514/783
4,541,936	9/1985	Ona et al.	252/8.6
4,559,162	12/1985	Abel et al	252/321
4,559,227	12/1985	Chandra	
4,567,038	1/1986	Ciaudelli et al	
4,582,874	4/1986	Grape et al	524/588
4,584,125	4/1986	Griswold et al	252/358
4,590,069	5/1986	Deckner et al	424/70
4,597,962	7/1986	Grollier et al	
4,600,436	7/1986	Traver et al	
4,601,902	7/1986	Fridd et al.	424/70
4,609,75 0	9/1986	Kollmeier et al	550/419
4,613,646	9/1986	Sandvick	524/476
4,620,878	11/1986	Gee	106/287
4,639,489	1/1987	Aizawa et al	524/588
4,648,904	3/1987	DePasquale et al	106/2
4,654,161	3/1987	Kollmeier et al	252/174.15
4,658,839	4/1987	Dallal et al	132/7
4,663,157	5/1987	Brock	424/59
4,673,568	6/1987	Grollier et al.	424/4/
4,675,125	6/1987	Sturwold	252/118
4,675,179	6/1987	Suzuki et al	424/0/
4,678,815	7/1987	Hoffman	523/122
4,689,168	8/1987	Requejo	252/139
4,698,178	10/1987	Huttinger et al	252/309
4,704,272	11/1987	Oh et al.	424/70
4,710,314	12/1987	Madrange et al	252/11/
4,728,457	3/1988	Fieler	252/174
4,732,612	3/1988	Steer et al.	
4,782,095	11/1988	Gum	514/937
4,788,001	11/1988	Narula	252/312
4,788,006	11/1988	Bolich, Jr. et al	232/350
4,801,447	1/1989	Gum	424/68
4,820,308	4/1989	Madrange et al	
4,842,849	6/1989	Grollier et al.	
4,874,547	10/1989	Narula	252/312

FOREIGN PATENT DOCUMENTS

95238	11/1983	European Pat. Off
77920	5/1984	European Pat. Off
108517	5/1984	European Pat. Off.
141593	5/1985	European Pat. Off.
0152194	6/1985	European Pat. Off.
152194	8/1985	European Pat. Off
155806	9/1985	European Pat. Off
166232	1/1986	European Pat. Off.
180464	5/1986	European Pat. Off.
181773A2	5/1988	European Pat. Off
285388A2	10/1988	European Pat. Off
412705A2	2/1991	European Pat. Off
1444314	4/1969	Fed. Rep. of Germany .
2725714	12/1977	Fed. Rep. of Germany .
2912485	10/1980	Fed. Rep. of Germany .
3327840	9/1984	Fed. Rep. of Germany .
3417912	7/1985	Fed. Rep. of Germany .
1125918	11/1956	France.
2162463	7/1973	France .
50-31193	3/1975	Japan .
52-038485	3/1977	Japan .
56-016405	2/1981	Japan .
56-022712	3/1981	Japan .
56-086113	7/1981	Japan .
56-129300	10/1981	Japan .
56-167799	12/1981	Japan .
57-050909	3/1982	Japan .
57-056413	4/1982	Japan .
57-064606	4/1982	Japan .
58-113300	7/1983	Japan .
58-177909	10/1983	Japan .
59-110612	6/1984	Japan .
60-126209	7/1985	Japan .
60-166400	8/1985	Japan .
849433	9/1960	United Kingdom .
964837	7/1964	United Kingdom .
992087	5/1965	United Kingdom .
1034782	7/1966	United Kingdom .
1191289	5/1970	United Kingdom .
1549180	7/1979	United Kingdom .
2039512	8/1980	United Kingdom .
2058103	4/1981	United Kingdom
1598567	9/1981	United Kingdom .
1598845	9/1981	United Kingdom .
2074184	10/1981	United Kingdom .

OTHER PUBLICATIONS

Bennett, H., Editor, 1971, Chemical Formulary, vol. XVI, pp. 81, 82, 120.

McCutcheon's Detergents and Emulsifiers, North American Edition, 1978, pp. 238 and 240.

Bennett, H., Editor, 1973, Chemical Formulary, vol. XVII, p. 125.

Starch et al., "Silicones in Skin-Care Products", Cosmetic Technology, Nov., 1982, pp. 22-27.

Hunting, Encyclopedia of Shampoo Ingredients, Micelle Press, 1985, pp. 35, 50, 78, 95, 143, 204-205, 421.

Rothemann, Das Grosse Reseptbuch Der Haut-Und Korperpflegemittel, 1969, Dr. Alfred Huthig Verlag, Heidelberg, pp. 175, 247, 248, 608.

Merck Index, Tenth Edition, 1983, pp. 1258-1259.

Harry's Cosmeticology Treatise, 7th edition, 1982, pp. 446-457.

Liquid soap formulation (Dow Corning)—Product Description Sheet. I Like My Gray shampoo (Clairol)—Product description, analysis and label.

deNavarre, Maison G., The Chemistry and Manufacture of Cosmetics, vol. IV, Second Edition, 1975, pp. 1297-1304.

Kirk-Othmer Encyclopedia of Chemical Technology, vol. 8, pp. 830, 831, 837.

Ullmanns Encyclopedia, 1976, Verlag Chemie, p. 542.

Janistyn Treatise, Handbuch der Kosmetika und Riechstoffe, Dr. Alfred Huthig Verlag, Heidelberg, 1978, p. 837.

Henkel Trade Leaflet, Mar., 1980-Coconut fatty acid monoethanolamide.

Jergens Lotion Enriched Soap-product description--from Cosmetic Research USA News, May, 1981.

IVORY Shampoo product label.

Hunting, Anthony L.L., Opacifiers and Pearling Agents in Shampoos, Cosmetics and Toiletries, vol. 96, pp. 65-78 (1981).

ť

5

SHAMPOO COMPOSITIONS

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

CROSS REFERENCE TO RELATED APPLICATION

This is a continuation of application Ser. No. 795,285, filed on Nov. 5, 1985, now abandoned, which is a continuation-in-part of our copending application Ser. No. 670,189, filed Nov. 9, 1984, now abandoned.

TECHNICAL FIELD

The present invention is related to conditioning shampoos which have a dispersed, non-volatile silicone phase and are stabilized through the use of certain long chain materials.

BACKGROUND OF THE INVENTION

Human hair becomes soiled due to its contact with the surrounding atmosphere and, to a greater extent, from sebum secreted by the head. The build-up of the 25 herein are by weight. sebum causes the hair to have a dirty feel and an unattractive appearance. The soiling of the hair necessitates it being shampooed with frequent regularity.

Shampooing the hair cleans by removing excess soil and sebum. However, the shampooing process has dis- 30 advantages in that the hair is left in a wet, tangled and generally unmanageable state. A variety of approaches have been developed to alleviate the after-shampoo problems. These range from the inclusion of hair conditioning aids in shampoos to post-shampoo application of 35 hair conditioners, i.e., hair rinses. Hair rinses typically work by depositing a polymeric film or other material onto the hair. However, such solutions to a very prevalent problem have not been fully satisfactory. For one thing, hair rinses are generally liquid in nature and must 40 be applied in a separate step following the shampooing, left on the hair for a length of time, and rinsed with fresh water. This, of course, is time consuming and is not convenient.

While shampoos have been disclosed which contain 45 conditioning aids, they have not been totally satisfactory for a variety of reasons. One problem relates to compatibility problems between good cleaning anionic surfactants and the fatty cationic agents which are good conditioning agents. This caused other surfactants such 50 as nonionics, amphoterics and zwitterionics to be examined by workers in the field. Many of these efforts are reflected in patients issued in the conditioning shampoo are. See for example U.S. Pat. No. 3,849,348, Nov. 19, 1974 to Hewitt; U.S. Pat. No. 3,990,991, Nov. 9, 1961 to 55 are the sodium, ammonium, potassium or triethanol-Gerstein; and U.S. Pat. No. 3,822,312, July 2, 1974 to Sato.

The use of these other surfactants solved many of the compatibility problems but still did not provide comtioners may not deliver the desired level of softness desired by users. Materials which can provide increased softness are silicones, both those which are soluble as well as insoluble in the shampoo matrix.

closed in a number of different publications. Such publications include U.S. Pat. No. 2,826,551, Mar. 11, 1958 to Geen; U.S. Pat. No. 3,964,500, June 22, 1976 to Drakoff;

U.S. Pat. No. 4,364,837, Dec. 21, 1982 to Pader; and British Pat. No. 849,433, Sept. 28, 1960 to Woolston. While these patents disclose silicone containing compositions, they also do not provide answers to all of the problems encountered in making a totally satisfactory product. One problem is that of keeping a dispersed, insoluble silicone material suspended and the total product stable. A variety of materials have been included in silicone containing shampoos for purposes of thickening 10 and stabilization but totally satisfactory solutions are lacking. It has been surprisingly found that certain long chain acyl derivatives and certain other long chain derivatives can provide stabilization without interfering unduly with deposit of the silicone material onto the 15 hair and other shampoo functions.

It is an object of the present invention to provide a stable silicone containing conditioning shampoo.

It is a further object of the present invention to pro-20 vide silicone shampoo compositions containing certain long chain derivatives.

These and other objects will become readily apparent from the detailed description which follows.

Unless otherwise indicated, all percentages and ratios

SUMMARY OF THE INVENTION

The present invention relates to shampoo compositions comprising from about 5% to about 70% of a synthetic surfactant, about 0.01% to about 10.0% of an insoluble, non-volatile silicone, about 0.5% to about 5.0% of a certain long chain derivative and water. These as well as optional components are described in detail below.

DETAILED DESCRIPTION

The essential components of the present invention are given in the following paragraphs.

Surfactant

An essential component of the present compositions is a surfactant. The surfactant, which may be selected from any of a wide variety of synthetic anionic, amphoteric, zwitterionic and nonionic surfactants, is present at a level of from about 5% to about 70%, preferably from about 10% to about 30%, most preferably from about 10% to about 22%.

Synthetic anionic surfactants can be exemplified by the alkali metal salts of organic sulfuric reaction products having in their molecular structure an alkyl radical containing from 8-22 carbon atoms and a sulfonic acid or sulfuric acid ester radical (included in the term alkyl is the alkyl portion of higher acyl radicals). Preferred amine alkyl sulfates, especially those obtained by sulfating the higher alcohols (C_8-C_{18} carbon atoms), sodium coconut oil fatty acid monoglyceride sulfates and sulfonates; sodium or potassium salts of sulfuric acid esters of plete answers in all areas. For instance cationic condi- 60 the reaction product of 1 mole of a higher fatty alcohol (e.g., tallow or coconut oil alcohols) and 1 to 12 moles of ethylene oxide; sodium or potassium salts of alkyl phenol ethylene oxide ether sulfate with 1 to 10 units of ethylene oxide per molecule and in which the alkyl Silicones in shampoo compositions have been dis- 65 radicals contain from 8 to 12 carbon atoms, sodium alkyl glyceryl ether sulfonates; the reaction product of fatty acids having from 10 to 22 carbon atoms esterified with isethionic acid and neutralized with sodium hydroxide; water soluble salts of condensation products of fatty acids with sarcosine; and other known in the art.

Zwitterionic surfactants can be exemplified by those which can be broadly described as derivatives of aliphatic quaternary ammonium, phosphonium, and sulfo-5 nium compounds, in which the aliphatic radicals can be straight chain or branched, and wherein one of the aliphatic substituents contains from about 8 to 18 carbon atoms and one contains an anionic water-solubilizing group, e.g., carboxyl, sulfonate, sulfate, phosphate, or 10 phosphonate. A general formula for these compounds is:

$$(R^3) x$$

 $R^2 Y^{(+)} CH_2 R^4 Z^{(-)}$

wherein \mathbb{R}^2 contains an alkyl, alkenyl, or hydroxy alkyl radical of from about 8 to about 18 carbon atoms, from 0 to about 10 ethylene oxide moieties and from 0 to 1 glyceryl moiety; Y is selected from the group consisting ²⁰ of nitrogen, phosphorus, and sulfur atoms; \mathbb{R}^3 is an alkyl or monohydroxyalkyl group containing 1 to about 3 carbon atoms; X is 1 when Y is a sulfur atom and 2 when Y is a nitrogen or phosphorus atom; \mathbb{R}^4 is an alkylene or hydroxyalkylene of from 1 to about 4 carbon atoms and ²⁵ Z is a radical selected from the group consisting of carboxylate, sulfonate, sulfate, phosphonate, and phosphate groups.

Examples include:

- 4-[N,N-di(2-hydroxyethyl)-N-octadecylammonio]butane-1-carboxylate;
- 5-[S-3-hydroxypropyl-S-hexadecylsulfonio]-3-hydroxypentane-1-sulfate;
- 3-[P,P-diethyl-P-3,6,9-trioxatetradexocylphosphonio]-2-hydroxypropane-1-phosphate;
- 3-[N,N-dipropyl-N-3-dodecoxy-2-hydroxypropylammonio]-propane-1-phosphonate;
- 3-(N,N-dimethyl-N-hexadecylammonio)propane-1-sulfonate;
- 3-(N,N-dimethyl-N-hexadecylammonio)-2-hydroxypropane-1-sulfonate;
- 4-[N,N-di(2-hydroxyethyl)-N-(2-hydroxydodecyl)ammonio]-butane-1-carboxylate;
- 3-[S-ethyl-S-(3-dodecoxy-2-hydroxypropyl)sulfonio]propane-1-phosphate;
- 3-[P,P-dimethyl-P-dodecylphosphonio]-propane-1phosphonate; and
- 5-[N,N-di(3-hydroxypropyl)-N-hexadecylammonio]-2hydroxypentane-1-sulfate.

Other zwitterionics such as betaines are also useful in 50 the present invention. Examples of betaines useful herein include the high alkyl betaines such as coco dimethyl carboxymethyl betaine, lauryl dimethyl carboxymethyl betaine, lauryl dimethyl alpha-carboxyethyl betaine, cetyl dimethyl carboxymethyl betaine, 55 lauryl bis-(2-hydroxy-ethyl)carboxy methyl betaine, stearyl bis-(2-hydroxy-propyl)carboxymethyl betaine, oleyl dimethyl gamma-carboxypropyl betaine, lauryl bis-(2-hydroxypropyl)alpha-carboxyethyl betaine, etc. The sulfobetaines may be represented by coco dimethyl 60 sulfopropyl betaine, stearyl dimethyl sulfopropyl betaine, lauryl dimethyl sulfoethyl betaine, lauryl bis-(2hydroxy-ethyl)sulfopropyl betaine and the like; amido and amidosulfobetaines, wherein betaines the RCONH(CH₂)₃ radical is attached to the nitrogen atom 65 of the betaine are also useful in this invention. The amido betaines are preferred for use in some of the compositions of this invention. A particularly preferred

composition utilizes an amido betaine, a quaternary compound, a silicone, a suspending agent and has a pH of from about 2 to about 4.

Examples of amphoteric surfactants which can be used in the compositions of the present invention are those which can be broadly described as derivatives of aliphatic secondary and tertiary amines in which the aliphatic radical can be straight chain or branched and wherein one of the aliphatic substituents contains from about 8 to about 18 carbon atoms and one contains an anionic water solubilizing group, e.g., carboxy, sulfonate, sulfate, phosphate, or phosphonate. Examples of compounds falling within this definition are sodium 3-dodecylaminopropionate, sodium 3-dodecylamino-¹⁵ propane sulfonate, N-alkyltaurines such as the one prepared by reacting dodecylamine with sodium isethionate according to the teaching of U.S. Pat. No. 2,658,072, N-higher alkyl aspartic acids such as those produced according to the teaching of U.S. Pat. No. 2,438,091, and the products sold under the trade name "Miranol" and described in U.S. Pat. No. 2,528,378.

Nonionic surfactants, which are preferably used in combination with an anionic, amphoteric or zwitterionic surfactant, can be broadly defined as compounds produced by the condensation of alkylene oxide groups (hydrophilic in nature) with an organic hydrophobic compound, which may be aliphatic or alkyl aromatic in nature. Examples of preferred classes of nonionic surfactants are:

The polyethylene oxide condensates of alkyl phenols, e.g., the condensation products of alkyl phenols having an alkyl group containing from about 6 to 12 carbon atoms in either a straight chain or branched
 chain configuration, with ethylene oxide, the said ethylene oxide being present in amounts equal to 10 to 60 moles of ethylene oxide per mole of alkyl phenol. The alkyl substituent in such compounds may be derived from polymerized propylene, diisobutylene, octane, or 40 nonane, for example.

2. Those derived from the condensation of ethylene oxide with the product resulting from the reaction of propylene oxide and ethylene diamine products which may be varied in composition depending upon the bal-45 ance between the hydrophobic and hydrophilic elements which is desired. For example, compounds containing from about 40% to about 80% polyoxyethylene by weight and having a molecular weight of from about 5,000 to about 11,000 resulting from the reaction of 50 ethylene oxide groups with a hydrophobic base constituted of the reaction product of ethylene diamine and excess propylene oxide, said base having a molecular weight of the order of 2,500 to 3,000, are satisfactory.

3. The condensation product of aliphatic alcohols having from 8 to 18 carbon atoms, in either straight chain or branched chain configuration, with ethylene oxide, e.g., a coconut alcohol ethylene oxide condensate having from 10 to 30 moles of ethylene oxide per mole of coconut alcohol, the coconut alcohol fraction having from 10 to 14 carbon atoms.

4. Long chain tertiary amine oxides corresponding to the following general formula:

R₁R₂R₃N O

wherein R_1 contains an alkyl, alkenyl or monohydroxy alkyl radical of from about 8 to about 18 carbon atoms, from 0 to about 10 ethylene oxide moieties, and from 0 19

to 1 glyceryl moiety, and R₂ and R₃ contain from 1 to about 3 carbon atoms and from 0 to about 1 hydroxy group, e.g., methyl, ethyl, propyl, hydroxy ethyl, or hydroxy propyl radicals. The arrow in the formula is a 5 conventional representation of a semipolar bond. Examples of amine oxides suitable for use in this invention include dimethyl-dodecylamine oxide, oleyldi(2hydroxyethyl)amine oxide, dimethyloctylamine oxide, dimethyl-decylamine oxide, dimethyltetradecylamine 10 oxide, 3,6,9-trioxaheptadecyldiethylamine oxide, di(2hydroxyethyl)-tetradecylamine oxide, 2-dode-coxyeoxide. 3-dodecoxy-2-hydroxythyldimethylamine propyldi(3-hydroxypropyl)amine oxide, dimethylhexadecylamine oxide.

5. Long chain tertiary phosphine oxides corresponding to the following general formula:

RR'R"P O

wherein R contains an alkyl, alkenyl or monohydroxyalkyl radical ranging from 8 to 18 carbon atoms in chain length, from 0 to about 10 ethylene oxide moieties and from 0 to 1 glyceryl moiety and R' and R" are each alkyl or monohydroxyalkyl groups containing from 1 to 25 3 carbon atoms. The arrow in the formula is a conventional representation of a semipolar bond. Examples of suitable phosphine oxides are: dodecyldimethylphosphine oxide, tetradecyldimethylphosphine oxide, tetradecylmethylethylphosphine oxide, 3,6,9,-trioxaoc- 30 tadecyldimethylphosphine oxide, cetyldimethylphosphine oxide, 3-dodecoxy-2-hydroxypropyldi(2-hydroxyethyl)phosphine oxide, stearyldimethylphosphine oxide, cetylethylpropylphosphine oxide, oleyldiethyl-35 phosphine oxide, dodecyldiethylphosphine oxide, tetradecyldiethylphosphine oxide, dodecyldipropylphosphine oxide, dodecyldi(hydroxymethyl)phosphine oxide, dodecyldi(2-hydroxyethyl)phosphine oxide, tetradecylmethyl-2-hydroxypropylphosphine oxide, oleyl-40 dimethylphosphine oxide, 2-hydroxydodecyldimethylphosphine oxide.

6. Long chain dialkyl sulfoxides containing one short chain alkyl or hydroxy alkyl radical of 1 to about 3 carbon atoms (usually methyl) and one long hydropho-45 bic chain which contain alkyl, alkenyl, hydroxy alkyl, or keto alkyl radicals containing from about 8 to about 20 carbon atoms, from 0 to about 10 ethylene oxide moieties and from 0 to 1 glyceryl moiety. Examples include: octadecyl methyl sulfoxide, 2-ketotridecyl ⁵⁰ methyl sulfoxide, 3,6,9,-trioxaoctadecyl 2-hydroxyethyl sulfoxide, dodecyl methyl sulfoxide, oleyl 3-hydroxypropyl sulfoxide, tetradecyl methyl sulfoxide, 3methoxytridecyl methyl sulfoxide, 3-hydroxytridecyl methyl sulfoxide, 3-hydroxy-4-dodecoxybutyl methyl ⁵⁵ sulfoxide.

Many additional nonsoap surfactants are described in McCUTCHEON'S, DETERGENTS AND EMULSI-FIERS, 1979 ANNUAL, published by Allured Publishing Corporation, which is incorporated herein by reference.

The above-mentioned surfactants can be used alone or in combination in the shampoo compositions of the present invention. The anionic surfactants, particularly 65 the alkyl sulfates, the ethoxylated alkyl sulfates and mixtures thereof are preferred for use herein as well as the amido betaines.

6

Non-Volatile Silicone Fluid

Silicone fluids are a suitable non-volatile silicone that may be used in the present compositions.

The non-volatile silicone fluid may be either a polyalkyl siloxane, a polyaryl siloxane, a polyalkylaryl siloxane or a polyether siloxane copolymer and is present at a level of from about 0.1% to about 10.00% preferably from about 0.5% to about 5.0%. Mixtures of these fluids may also be used and are preferred in certain executions. The dispersed silicone particles should also be insoluble in the shampoo matrix. This is the meaning of "insoluble" as used hereinbefore and hereinafter.

The essentially non-volatile polyalkyl siloxane fluids 15 that may be used include, for example, polydimethyl siloxanes with viscosities ranging from about 5 to 600,000 centistokes at 25° C. These siloxanes are available, for example, from the General Electric Company as the Viscasil series and from Dow Corning as the 20 Dow Corning 200 series. The viscosity can be measured by means of a glass capillary viscometer as set forth in Dow Corning Corporate Test Method CTM0004, July 20, 1970. Preferably the viscosity ranges from about 350 centistokes to about 100,000 centistokes.

The essentially non-volatile polyalkylaryl siloxane fluids that may be used include, for example, polymethylphenylsiloxanes having viscosities of about 15 to 30,000 centistokes at 25° C. These siloxanes are available, for example, from the General Electric Company as SF 1075 methyl phenyl fluid or from Dow Corning as 556 Cosmetic Grade Fluid.

The essentially non-volatile polyether sioxane copolymer that may be used is, for example, a polypropylene oxide modified dimethylpolysiloxane (e.g., Dow Corning DC-1248) although ethylene oxide or mixtures of ethylene oxide and propylene oxide may also be used.

References disclosing suitable silicone fluids include the previously mentioned U.S. Pat. No. 2,826,551 to Geen; U.S. Pat. No. 3,964,500, June 22, 1976 to Drakoff; U.S. Pat. No. 4,364,837 to Pader and British Pat. No. 849,433 to Woolston. All of these patents are incorporated herein by reference. Also incorporated herein by reference is Silicon Compounds distributed by Petrarch Systems, Inc., 1984. This reference provides a very good listing of suitable silicone materials.

Another silicone material found especially useful in the present compositions to provide good dry combing is a silicone gum. Silicone gums described by Petrarch and others including U.S. Pat. No. 4,152,416, May 1, 1979 to Spitzer, et al. and Noll, Walter, Chemistry and Technology of Silicones, New York: Academic Press 1968. Also describing silicone gums are General Electric Silicone Rubber Product Data Sheets SE 30, SE 33, SE 54 and SE 76. All of these described references are 55 incorporated herein by reference. "Silicone gum" materials denote high molecular weight polydiorganosiloxanes having a mass molecular weight of from about 200,000 to about 1,000,000. Specific examples include polydimethylsiloxane, (polydimethylsiloxane) (methylvinylsiloxane) copolymer, poly(dimethylsiloxane) (diphenyl) (methylvinylsiloxane) copolymer and mixtures thereof.

Long Chain Derivative Suspending Agent

The suspending agent useful in the present compositions can be any of several long chain acyl derivative materials or mixtures of such materials. Included are ethylene glycol esters of fatty acids having from about

.

16 to about 22 carbon atoms. Preferred are the ethylene glycol stearates, both mono and distearate, but particularly the distearate containing less than about 7% of the mono stearate. Other suspending agents found useful are alkanol amides of fatty acids, having from about 16⁵ to about 22 carbon atoms, preferably from 16 to 18 carbon atoms. Preferred alkanol amides are stearic monoethanolamide, stearic diethanolamide, stearic monoisopropanolamide and stearic monoethanolamide 10 stearate. Other long chain acyl derivatives include long chain esters of long chain fatty acids (e.g., stearyl stearate, cetyl palmitate, etc.); glyceryl esters (e.g., glyceryl distearate) and long chain esters of long chain alkanol amides (e.g., stearamide DEA distearate, stearamide 15 MEA stearate).

Still other suitable suspending agents are alkyl (C16-22) dimethyl amide oxides such as stearyl dimethyl amine oxide. If the compositions contain an amide oxide or a long chain acyl derivative as a surfactant the sus- 20 pending function could also be provided and additional suspending agent may not be needed if the level of those materials are at least the minimum level given below.

The suspending agent is present at a level of from about 0.50% to about 5.0%, preferably from about 25 0.5% to about 3.0%. The suspending agent serves to assist in suspending the silicone material and may give pearlescence to the product. Mixtures of suspending agents are also suitable for use in the compositions of 30 this invention.

Water

Water is the last essential component of the present invention and forms the remainder of the composition. 35 It is generally present at a level of from about 20% to about 95%, preferably from about 60% to about 85%.

Optional Components

The shampoos herein can contain a variety of non- 40 essential optional components suitable for rendering such compositions more acceptable. Such conventional optional ingredients are well known to those skilled in the art, e.g. preservatives such as benzyl alcohol, methyl paraben, propyl paraben and imidazolidinyl 45 urea; cationic surfactants such as cetyl trimethyl ammonium chloride, lauryl trimethyl ammonium chloride, tricetyl methyl ammonium chloride, stearyldimethyl benzyl ammonium chloride, and di(partially hydrogenated tallow)dimethylammonium chloride; thickeners 50 and viscosity modifiers such as a diethanolamide of a long chain fatty acid (e.g., PEG 3lauramide), block polymers of ethylene oxide and propylene oxide such as Pluronic F88 offered by BASF Wyandotte, sodium 55 chloride, sodium sulfate, polyvinyl alcohol, and ethyl alcohol; pH adjusting agents such as citric acid, succinic acid, phosphoric acid, sodium hydroxide, sodium carbonate, etc.; perfumes; dyes; and, sequestering agents such as disodium ethylenediamine tetraacetate. Such 60 agents generally are used individually at a level of from about 0.01% to about 10%, preferably from about 0.5% to about 5.0% by weight of the composition.

The pH of the present compositions is not critical and may be in the range of from about 2 to about 10. How- 65 . ever, as set forth earlier certain zwitterionic/quaternary compositions preferably have pH's of from about 2 to about 4.

METHOD OF MANUFACTURE

The shampoos of the present invention can be made by mixing the materials together and heating to about 72° C. The mixture is mixed thoroughly for about 10 minutes at the 72° C. temperature before being pumped through a high shear mill and then through a heat exchanger to cool it to about 27° C.

The high shear mill is used to achieve adequate dispersion of the silicone fluid. This is achieved by having the average particle size of the silicones preferably to about 10 microns or less.

In the cooling step, the acyl derivative is preferably crystallized into particles having an average particle size of about 10 microns or less.

INDUSTRIAL APPLICABILITY

The present compositions are used in a conventional manner for cleaning hair. From about 0.1 g to about 10 g of a composition is applied to hair that has been wetted, generally with water, worked through the hair and then rinsed out.

The following Examples further describe and demonstrate the preferred embodiments within the scope of the present invention. The Examples are given solely for the purpose of illustration and are not to be construed as limitations of the present invention as many variations thereof are possible without departing from its spirit and scope.

EXAMPLES I-V

The following compositions are representative of the present invention.

			Weight	%	
Component	I	n	111	IV	v
Cocamidopropyl	18.00	18.00	18.00	18.00	18.00
Betaine	4.00	2.00	2.00	2.00	2.00
Di-partially					
hydrogenated tallow					
dimethyl ammonium chloride					
Cetyltrimethylammonium	2.00	2.00	2.00	2.00	2.00
chloride					
DC-200 Fluid (350 csk) ¹		1.00	_	1.75	
DC-200 Fluid (12500 csk) ²	1.00	_	_		_
DC-1248 ³	_	_	1.00	_	-
DC-X28107	_	_		-	1.00
Citric Acid	3.50	3.50	3.50	3.50	3.50
Ethylene Glycol	1.50	1.50	1.50	1.50	1.50
Distearate					
PEG-3 Alkyl amide ⁴	3.00	4.50	4.50	4.50	4.50
Sodium Chloride	-		1.00		
Preservative, Dyc.			1.00.0	W	
Perfume and Water		•	a 100.0	170	
	20		3.0	3.0	3.0
pH	3.0	3.0	3.0	3.0	3.0

Dimethylpolysilozane offered by Dow Chemical

²Dimethylpolysiloxane offered by Dow Chemical Co. ³A dimethicone offered by Dow Chemical Co.

PEG-3 Allyl (98% C12) Amide - Mazamide C-2 Experime

These compositions are stable and deliver good conditioning to hair that is washed with the compositions.

EXAMPLES VI & VII

The following are two anionic shampoo compositions of the present invention.

	Weight %	
Component	vi	VII
TEA C12-C14 Alkyl Sulfate	15.00	_

9

	Weight %		
Component	VI	VII	
NH4 C12-C14 Alkyl (Ethoxy)3 Sulfate	_	7.90	
Sodium C12C14 Alkyl Sulfate	_	7.90	
Cocamide MEA	3.00	1.50	
Dimethicone DC-200 ¹	3.00	3.00	
Ethylene Glycol Distearate	1.50	1.50	
Citric Acid	0.60	0.60	
Trisodium Citrate	0.30	_	1
Q.S. Color, Preservative,	q.s. 100%	q.s. 100%	1
Perfume and Water			

¹Polydimethylsiloxane having a viscosity of 12,500 centistokes

These compositions are also stable and deliver good hair conditioning.

EXAMPLE VIII

To demonstrate the benefit given by the ethylene glycol distearate to the present compositions, the compositions of Examples I-V are prepared without the ²⁰ material. When samples were stored at 50° F., 80° F. and 100° F., all of the compositions without EGDS demonstrated instability with the silicone rising to the top in a clear layer. None of the compositions of the present invention demonstrated any instability. This ²⁵ clearly demonstrates the superiority of the present invention.

What is claimed is:

1. A shampoo composition comprising

- (a) from about 5% to about 70% of a synthetic surfactant selected from the group consisting of anionic surfactants, zwitterionic surfactants, amphoteric surfactants and mixtures thereof;
- (b) from about 0.01% to about 10% of a dispersed, insoluble, nonvolatile silicone in the form of fluids ³⁵ or gums selected from the group consisting of polyalkyl siloxanes, polyaryl siloxanes, polyalkylaryl siloxanes, polyether siloxane copolymers, and mixtures thereof;
- (c) from about 0.5% to about 5% of a long chain 40 (C₁₆-C₂₂) acyl derivative or long chain (C₁₆-C₂₂) amine oxide suspending agent selected from the group consisting of ethylene glycol long chain esters, alkanol amides of long chain fatty acids, long chain esters of long chain fatty acids, glyceryl long chain esters, long chain esters of long chain alkanolamides, long chain alkyl dimethyl amine oxides and mixtures thereof; and

(d) the remainder water.

2. A shampoo composition according to claim 1 ⁵⁰ wherein the non-volatile silicone is selected from the group consisting of polydimethylsiloxanes having viscosities of from about 5 to about 100,000 centistokes at 25° C., polypropylene oxide modified dimethylsiloxanes and silicone gums. 55

3. A shampoo composition according to claim 2 wherein the surfactant is selected from the group consisting of amphoteric surfactants, zwitterionic surfactants and mixtures thereof.

4. A shampoo composition according to claim 2 60 wherein the surfactant is anionic.

5. A shampoo composition according to claim 3 wherein the non-volatile silicone is selected from the group consisting of polydimethylsiloxanes having viscosities of from about 5 to about 100,000 centistokes at 65 10

25° C. and polypropylene oxide modified dimethylsiloxanes.

6. A shampoo composition according to claim 5 which in addition contains from about 0.01% to about 10% of a quaternary ammonium compound.

7. A shampoo composition according to claim 6 wherein the surfactant is a betaine.

 A shampoo composition according to claim 7 wherein the acyl derivative is ethylene glycol distearate.

9. A shampoo composition according to claim 8 wherein the shampoo composition has a pH of from about 2 to about 4.

10. A shampoo composition comprising

- (a) from about 5% to about 70% of a synthetic surfactant selected from the group consisting of anionic surfactants, zwitterionic surfactants, amphoteric surfactants, and mixtures thereof;
- (b) from about 0.01% to about 10% of a dispersed, insoluble, non-volatile silicone in the form of fluids or gums selected from the group consisting of polyalkyl siloxanes, polyaryl siloxanes, polyalkylaryl siloxanes, polyether siloxane copolymers, and mixture thereof;
- (c) from about 0.5% to about 5% of a long chain $(C_{16}-C_{22})$ acyl derivative suspending agent selected from the group consisting of long chain $(C_{16}-C_{22})$ esters, long chain $(C_{16}-C_{22})$ ethanol amides, and mixtures thereof, said suspending agent being present in the shampoo composition in crystalline form; and (d) the remainder water.

11. A shampoo composition according to claim 10 wherein the crystals of the suspending agent in the shampoo composition have an average particle size of about 10 microns or less.

12. A shampoo composition according to claim 11 wherein the non-volatile silicone is selected from the group consisting of polydimethylsiloxanes having viscosities of from about 5 to about 100,000 centistokes at 25° C., polypropylene oxide modified dimethylsiloxanes, and silicone gums, and mixtures thereof.

13. A shampoo composition according to claim 12 wherein the non-volatile silicone is selected from the group consisting of polydimethylsiloxanes having viscosities of from about 5 to about 100,000 centistokes at 25° C., poly-

propylene oxide modified dimethylsiloxanes, and mixtures thereof.

14. A shampoo composition according to claim 12 wherein the surfactant is anionic.

15. A shampoo composition according to claim 12 wherein the surfactant is selected from the group consisting of amphoteric surfactants, zwitterionic surfactants, and mixtures thereof.

16. A shampoo composition according to claim 15 wherein the surfactant is a betaine.

17. A shampoo composition according to claim 14 wherein the acyl derivative is ethylene glycol distearate.

18. A shampoo composition according to claim 14 which in addition contains from about 0.01% to about 10% of a quaternary ammonium compound.

19. A shampoo composition according to claim 14 having a pH of from about 2 to about 4.

20. A shampoo composition according to claim 10 wherein the silicone has an average particle size of about 10 microns or less.

.

UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO. : Re. 34,584

DATED : April 12, 1994

INVENTOR(S) : Mark B. Grote and Glen D. Russell

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 10, line 27, should read "esters, long chain (C₁₆-C₂₂) alkanol amides, and".

Signed and Sealed this

Thirty-first Day of January, 1995

Attest:

Attesting Officer

ince tehman

BRUCE LEHMAN Commissioner of Patents and Trademarks