



US00RE39831E

(19) **United States**
(12) **Reissued Patent**
Le et al.

(10) **Patent Number:** **US RE39,831 E**
(45) **Date of Reissued Patent:** **Sep. 11, 2007**

(54) **METHOD AND APPARATUS FOR PROVIDING POSITIONAL INFORMATION ON A DISK**

(75) Inventors: **Me Van Le**, Milpitas, CA (US);
William E. Wevers, San Jose, CA (US)

(73) Assignee: **Samsung Electronics Co., Ltd.**,
Suwon-si (KR)

(21) Appl. No.: **10/096,662**

(22) Filed: **Mar. 14, 2002**

Related U.S. Patent Documents

Reissue of:

(64) Patent No.: **6,038,097**
Issued: **Mar. 14, 2000**
Appl. No.: **08/807,232**
Filed: **Feb. 28, 1997**

(51) **Int. Cl.**
G11B 5/596 (2006.01)

(52) **U.S. Cl.** **360/78.14; 360/77.08**

(58) **Field of Classification Search** None
See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

4,823,212 A * 4/1989 Knowles et al. 360/77.08
5,523,902 A * 6/1996 Pederson 360/77.08
5,600,506 A * 2/1997 Baum et al. 360/78.14
5,631,783 A * 5/1997 Park 360/51
5,666,238 A * 9/1997 Igari et al. 360/77.08
6,075,667 A * 6/2000 Kisaka et al. 360/49

FOREIGN PATENT DOCUMENTS

EP 0718827 A2 * 6/1996
GB 2285165 * 6/1995
GB 2307089 * 5/1997
GB 2308488 * 6/1997
WO WO 95/24035 * 9/1995
WO WO 96/23305 * 8/1996

* cited by examiner

Primary Examiner—Paul Huber

(74) Attorney, Agent, or Firm—Staas & Halsey LLP

(57) **ABSTRACT**

The present invention is a method and apparatus for providing positional information of a disk. The disk has at least one side with a plurality of tracks, each having a first burst in a first servo field and a second burst in a second servo field. The first burst provides a first portion of track position information while the second burst provides a second portion of track position information. When combined, the first and second portions provide a position of a corresponding track. Each track further includes a third and a fourth burst that provides a first portion and a second portion of disk side position information. When combined, the first and second portions of disk side position information provide the disk side position of the disk. Each track also includes a burst that provides the quadrant position of the disk. In one embodiment, the first and second bursts are located on consecutive sectors, and each track includes a servo sector sequence burst with a sector sequence number that identifies the sequence position of the consecutive sectors. The first portion, the second portion and their corresponding sector sequence number in combination provide a position of a corresponding track.

45 Claims, 5 Drawing Sheets




FIG. 1 (PRIOR ART)





FIG. 2






FIG. 3A

FIG. 3B





1

METHOD AND APPARATUS FOR PROVIDING POSITIONAL INFORMATION ON A DISK

Matter enclosed in heavy brackets [] appears in the original patent but forms no part of this reissue specification; matter printed in italics indicates the additions made by reissue.

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates in general to disk storage systems and more particularly, to a method and apparatus for providing positional information on a disk in a hard drive assembly.

2. Description of the Related Art

Disk drives are magnetic recording devices used for the storage of information. The information is typically recorded on concentric tracks on either surface of one or more magnetic recording disks. To facilitate the storage and retrieval of data in an orderly manner, disks are typically organized in blocks called sectors. These sectors are located on the disk by a set of unique specifiers called cylinder (or track), head (or side) and sector number. The disks are rotatably mounted to a spin motor and information is accessed by means of read/write heads that are mounted to actuator arms which are rotated by a voice coil motor. The voice coil motor is excited with a current to rotate the actuator and move the heads.

The movement of the actuator is controlled by a servo system, utilizing servo information recorded on one or more of the magnetic recording disks. By reading this servo information, the actual radial positions of the heads can be determined, and after comparison with the desired head radial positions, control signals can be sent to move the actuator accordingly. Servo information is typically stored on a disk in one of two ways. In the first, a dedicated servo system, a set of several tracks on the disk or the entire disk surface, is reserved exclusively for storing information associated with the characteristic of the particular drive. Such information includes servo parameters and read/write channel parameters. A servo head reads this information to provide a continuous signal indicating the position of the servo head with respect to the servo disk. In the second type of servo system, the embedded servo system, sectors of servo information are interspersed with sectors of data on each disk surface. As a read head follows the data track around, it regularly reads a fresh sample of servo information from each servo sector with which to control its position.

FIG. 1 illustrates a typical sector on a disk of a hard disk drive. As shown, a typical sector **10** has a preamble field **20** which includes automatic gain control (AGC) information and synchronization information, a servo address mark **22** which signifies the beginning of a sector, an index field **24** which indicates the beginning of the first sector of the track, an identification field **26** which includes identification bits, a head identification field **28** for identification of head location, a gray code field **30** that identifies the particular cylinder (tracks) of the sector, a servo bit field **32** which includes a number of servo bits A, B, C, D, and a data field **34** which contains the data. The servo bits A, B, C and D are used to maintain the read/write head on the ceterline CL of a corresponding track. The identification field **26** typically includes an index bit and 7 bits of angular position information; the head identification field **28** typically includes 3

2

bits of data for identifying the head (or side) position of the disk pack and the gray code field **30** typically includes 13 bits of data for providing track identification. In conventional disk drives, absolute positional information is stored in graycode in the gray code field **30** of a particular sector **10**. Due to power consumption, cost and throughput concerns, reduction of media space used in providing the servo information is highly desirable. However, most of the segments of the sector **10** are head and/or media dependent and reduction of these segments is difficult.

Accordingly, there is a need in the technology for a method and apparatus for providing servo information on a disk in a hard drive assembly while reducing the media space required for the provision of such information.

BRIEF SUMMARY OF THE INVENTION

The present invention is a method and apparatus for providing positional information of a disk. The disk has at least one side with a plurality of tracks, each having a first burst in a first servo field and a second burst in a second servo field. The first burst provides a first portion of track position information while the second burst provides a second portion of track position information. When combined, the first and second portions provide a position of a corresponding track. Each track further includes a third and a fourth burst that provides a first portion and a second portion of disk side position information. When combined, the first and second portions of disk side position information provide the disk side position of the disk. Each track also includes a burst that provides the quadrant position of the disk. In one embodiment, the first and second bursts are located on consecutive sectors, and each track includes a servo sector sequence burst with a sector sequence number that identifies the sequence position of the consecutive sectors. The first portion, the second portion and their corresponding sector sequence number in combination provide a position of a corresponding track.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates a typical data sector of a disk in a disk drive assembly of the prior art.

FIG. 2 is a top view of a hard disk drive assembly which utilizes the apparatus and method of the present invention.

FIG. 3A illustrates exemplary sectors on heads H0-H3 (sides 1-4) of the disk pack **100** of FIG. 2.

FIG. 3B illustrates an enlarged view of a typical sector of on one side of the disk pack **100** of FIG. 3A as provided in accordance with the teachings of the present invention.

FIG. 4A illustrates a plurality of consecutive sectors on one side of the disk pack **100**, in accordance with the teachings of the present invention.

FIG. 4B illustrates four bits of head position information as provided by the SDAT fields of sector **2** and **3** in FIG. 4A respectively.

FIG. 4C illustrates the thirteen bits of track position information, of which bits **8-13** are provided by the SDAT fields of sectors **4-6** of FIG. 4A and of which bits **0-7** are provided by the Graycode field from each sector of FIG. 4A.

DETAILED DESCRIPTION OF THE INVENTION

Referring to the drawings more particularly by reference numbers, FIG. 2 illustrates a hard disk drive **50** which utilizes the method of the present invention. The disk drive **50** includes a disk pack **100** with a plurality of disks **102** that

are collectively rotated by a spin motor **104**. The spin motor **104** is mounted to a base plate **106**. Also mounted to the base plate **106** is an actuator arm assembly **108**. The actuator arm assembly **108** includes a number of read/write (R/W) heads **110a-d** mounted to corresponding flexure arms **112**. The flexure arms **112** are attached to an actuator arm **114** that can rotate about a bearing assembly **116**. The assembly **108** also contains a voice coil motor **118** which moves the heads **110a-d** collectively relative to the disks **102**. There is typically a single head **110a**, **110b**, **110c**, or **110d** for disk head side **H0**, **H1**, **H2** or **H3** (not shown), respectively, of the disk pack **100**. The spin motor **104**, voice coil motor **118** and the R/W heads **110a-d** are coupled to a number of electronic circuits **120** mounted to a printed circuit board **122**. The electronic circuits **120** typically include a read channel chip, a microprocessor-based controller and a random access memory (RAM) device.

As shown in FIG. 3A, data is typically stored within sectors **140₁**, **140₂** and **140₃** of radially concentric tracks located across any one of the disk heads **H0-H3** of the disk pack **100**. For discussion purposes, any one of the sectors **140₁**, **140₂** and **140₃** will be referred to as sector **140**. In one embodiment, as shown in FIG. 3B, each sector **140** has a preamble field **150** which includes automatic gain control (AGC) information and synchronization information, an address mark **152** which signifies the beginning of the sector **140**, an index field **154** which indicates the beginning of the first sector of the track, a servo sector sequence number (SSN) field **156** that identifies the sector sequence location number of sector **140** as identified among a plurality of consecutive sectors, a servo multiplex data (SDAT) field **158** that provides the higher order bit information related to positional information of the particular cylinder (track) of the sector **140**, a gray code field **160** that provides the lower order bit information related to positional information of the particular cylinder (track) of the sector **140**, a synchronization field **162**, a servo bit field **164** which includes a number of servo bits A, B, C, D, and a data field **166** which contains the data. For present purposes, fields **150-164** will be referred to as the servo field while field **166** will be referred to as the data field. The electronic circuits **120** (see FIG. 2) utilize the servo bits A, B, C and D to maintain the heads **110a-d** on the centerline CL of a corresponding track. The heads **110a-d** can magnetize and sense the magnetic field of the disk heads **H0-H3** to as to provide the information located on the above-described fields **150-166**.

In one embodiment, positional information is provided by reading the SSN field **156**, the SDAT field **158** and the graycode field **160** of six consecutive bursts of servo data. Table 1 illustrates an example of positional information that is provided in the SSN field **156**, the SDAT field **158** and the graycode field **160**, and the interrelationship between the fields. Together, the information located in the SSN field **156**, the SDAT field **158** and the graycode field **160** provide a matrix of positional information for identifying the quadrant, the head and track position of the disk pack **100**.

As shown in Table 1, there are **72** servo sectors on an exemplary head, head **4** (**H3**) of the disk pack **100**, each labeled from **0-71**. The **72** servo sectors are divided into groups each having six consecutive sectors. Each of the six consecutive sectors can be identified by an SSN of **0-7**, since a minimum of 3 bits are required, as provided in the SSN field **156** of each sector **140** (see FIG. 3B). As discussed earlier, the (SDAT) field **158** provides the higher order bit information related to positional information of the particular cylinder (track) of the sector **140**, while the gray code field **160** provides the lower order bit information related to

positional information of the particular cylinder (track) of the sector **140**.

In one embodiment, index information is provided in field **156₀** of sector **0** as **7** (binary 111). In one alternate embodiment, index information is provided in both sectors **0** and **1**. In this case, the index information is provided in SSN field **156₀** as **7** (binary 111) and in SSN field **156₁**, as **6** (binary 110).

TABLE 1

Example of data in servo pattern at Cylinder 24CDH, Heads 4.					
Binary CDH = Graycode CDH					
Binary 24H = Graycode 26H					
Servo Sector	SSN	SDAT <1:0>	OFFSET <7:0>	COMMENTS	
0	7	1,1	CDH	Index position, SSN = 7	
1	1	1,0	CDH	SDAT = 00 for 1st 1/4 rev.	
2	2	0,1	CDH	SDAT = Hd <3:0>	
3	3	1,0	CDH	SDAT = Hd <1:0>	
4	4	0,1	CDH	SDAT = Cyl <13:12>	
5	5	1,0	CDH	SDAT = Cyl <11:10>	
6	0	0,0	CDH	SDAT = Cyl <9:8>	
7	1	1,0	CDH	SSN = 0 so SDAT = 0	
8	2	0,1	CDH	SDAT = Hd <3:2>	
9	3	1,0	CDH	SDAT = Hd <1:0>	
10	4	0,1	CDH	SDAT = Cyl <13:12>	
11	5	1,0	CDH	SDAT = Cyl <11:10>	
12	0	0,0	CDH	SDAT = Cyl <9:8>	
13	1	1,0	CDH	.	
...	
18	0	0,1	CDH	SDAT = 01 for 2nd 1/4rev.	
...	
36	0	1,0	CDH	SDAT = 10 for 3rd 1/4rev.	
...	
54	0	1,1	CDH	SDAT = 11 for 4th 1/4rev.	
...	
68	2	0,1	CDH	.	
69	3	0,0	CDH	.	
70	4	0,1	CDH	.	
71	5	0,1	CDH	.	

In the present example, the combination of SSN=0 and an SDAT number identifies the quadrant position on a disk in the disk pack **100**. For example, the combination of SSN=0 and SDAT=00 identifies a particular position as the first quadrant of a disk; while the combination of SSN=0 and SDAT=01 identifies a particular position as the second quadrant of the disk. Similarly, the combination of SSN=0 and SDAT=10 identifies a particular position as the third quadrant of the disk; while the combination of SSN=0 and SDAT=11 identifies a particular position as the further quadrant of the disk. However, where SSN=7 and SDAT=00, it indicates that a particular position is the first sector in the first quadrant of the disk.

In addition, the combination of SSN=1 or SSN=2 with an SDAT number identifies a particular position as the head (or side position) of the disk pack **100**. With reference to Table 1, the combination of SSN=1 and SDAT=10 identifies a particular position as head **4** or **H3** of the disk pack **100**, while the combination of SSN=1 and SDAT=01 identifies a particular position as head **3** or **H2** of the disk pack **100**. Similarly, the combination of SSN=2 and SDAT=01 identifies a particular position as head **2** or **H1** of the disk pack, while the combination of SSN=2 and SDAT=10 identifies a particular position as head **1** or **H0** of the disk pack **100**.

Finally, the combination of SSN=3, 4 or 5 and an SDAT number provides the higher order bit information related to positional information of the particular cylinder (track) of a disk in the disk pack **100**. For example, the combination of

5

SSN=3 and SDAT=10 or 01 provides the position information of bits **13** and **12**, where the bit positions are identified from 0-13 (the 14th and 13th bits among 14 bits) of graycode information required to completely identify the cylinder or track on a disk. Similarly, the combination of SSN=4 and SDAT=01 or 10 provides position information of bits **11** and **10** (the 12th and 11th bits among 14 bits) of the graycode information required to completely identify the cylinder, while the combination of SSN=5 and SDAT=10 or 01 provides positional information for bits **9** and **8** (the 10th and 9th bits among 14 bits) of graycode information required to completely identify the cylinder. The remaining 8 bits of graycode information is located in the graycode field **160** located in each sector **140**.

FIG. 4 A illustrates an example of how the present invention may be implemented utilizing six consecutive sectors on a typical track. The six sectors, SECTORS **0-5**, each has an SSN field **156₀-156₅**, an SDAT field **158₀-158₅** and a graycode field **160₀-160₅**. Each SSN field **156₀-156₅** provides 3 bits of information related to the sector sequence position of each sector SECTORS **0-5** among the 6 sectors, while each SDAT field **158₀-158₅** provides 2 bits of information which provides any of the following information when used in combination with the SSN number: (1) identifies the quadrant position of a disk in the disk pack **100**; (2) identifies the head (or side) of the disk pack **100** or (3) provides 2 of six upper bits of information related to the track position information; and each graycode field **160₀-160₅** provides the 8 lower bits of information related to track position information.

As discussed earlier, the combination of SSN=0 and an SDAT number identifies the quadrant position on a disk in the disk pack **100**. In addition, the combination of SSN=1 or SSN=2 with an SDAT number identifies a particular position as the head (or side position) or the disk pack **100**. Finally, the combination of SSN=3, 4 or 5 and an SDAT number provides the higher order bit information related to positional information of the particular cylinder (track) of a disk in the disk pack **100**.

FIG. 4B illustrates the 4 bits of information that may be obtained from two of the six sectors, SECTORS **1** and **2**, which together identifies head (or side) position of a disk pack **100**. As shown, when the SSN field **156** preceding an SDAT field **158** indicates that the SSN is 1 (binary 001), the following SDAT field **158** will provide the upper 2 bits of head positional information. When the SSN field **156** preceding an SDAT field **158** indicates that the SSN is 2 (binary 010), the following SDAT field **158** will provide the lower 2 bits of head positional information. After reading the SSN fields **156₁** and **156₂** of the sectors SECTORS **1** and **2**, one will obtain the head position information of a particular location of the disk pack **100**.

FIG. 4C illustrates the 14 bits of information that may be obtained from three of six sectors, SECTORS **3-5**, which together identifies the track (or cylinder) position of a disk pack **100**. As shown, each graycode field **160₀-160₅** provides the 8 lower bits of information related to track position information. When one of the R/W heads **100 a-d** is reading from a track within a particular band of tracks, where there are 256 tracks in one band, the information from the 8 lower bits is sufficient to identify the position of the head. However, when any of the R/W heads **100a-d** is moving from one band to another, additional information is required to identify its location. As shown, when the SSN field **156** preceding an SDAT field **158** indicates that the SSN is 3 (binary 011), the following SDAT field will provide the two uppermost bits (bits **13** and **12**) of the 14 bits of data

6

required to provide track position. When the SSN field **158** indicates that the SSN is 4 (binary 100), the following SDAT field **158** will provide the following two uppermost bits (bits **11** and **10**) of the 14 bits of data required to provide track information. Finally, when the SSN field **156** indicates that the SSN is 5 (binary 101), the following SDAT field **158** will provide the last of the uppermost bits (bits **9** and **8**) of the 14 bits of data required to provide track position. Thus, by scanning the SSN field **156**, the SDAT field **158** and the graycode field **160** of at least 6 consecutive sectors as provided by the present invention, complete positional information of a particular location on the disk pack **100** may be obtained.

Through the implementation of the technique of the present invention, servo information on a disk in a hard drive assembly may be provided while reducing the media space required for the provision of such information. As a result, more media space may be utilized for the storage of data.

While certain exemplary embodiments have been described and shown in the accompanying drawings, it is to be understood that such embodiments are merely illustrative of and not restrictive on the broad invention, and that this invention not be limited to the specific constructions and arrangements shown and described, since various other modifications may occur to those ordinarily skilled in the art.

What is claimed is:

1. A disk for a hard disk drive, comprising:

a disk including at least one side having a plurality of tracks, each track including a group having first and second sectors, each of the first and second sectors within said group includes first and second servo fields, the first servo field in each of the first and second sectors providing a portion of higher order bits of a track position information, the second servo field in each of the first and second sectors providing lower order bits of the track position information, the first servo fields of the first and second sectors and the second servo field in one of the first and second sectors, in combination, providing the track position information.

2. The disk as recited in claim 1, wherein the group includes a third sector having first and second servo fields, the first servo field in the third sector providing a portion of higher order bits of the track position information, and the second servo field in the third sector providing lower order bits of the track position information, the first servo fields of the first, second, and third sectors and the second servo field in one of the first, second, and third sectors, in combination, providing the track position information.

3. The disk as recited in claim 2, wherein the group includes a fourth sector having a first servo field, the first servo field in the fourth sector of the group providing a disk side position of the disk.

4. The disk as recited in claim 3, wherein the group includes a fifth sector having a first servo field, the first servo field in the fourth and fifth sectors, in combination, providing the disk side position of the disk.

5. The disk as recited in claim 4, wherein the group includes a sixth sector having a first servo field, the first servo field in the sixth sector providing a quadrant of the disk.

6. The disk as recited in claim 5, wherein each track includes a plurality of groups each having six sectors, wherein complete disk positional information is obtained by reading one of the plurality of groups of six sectors.

7. The disk as recited in claim 1, wherein the first servo field of the first and second sectors each includes a sector

7

sequence number field and a servo multiplex data field, a sequence number in the sector sequence number field identifies a value in the corresponding servo multiplex data field as the portion of the track position information.

8. The disk as recited in claim 5, wherein the first servo field in each of the first through six sectors of the group includes a sector sequence number field and a servo multiplex data field, a sequence number in the sector sequence number field identifies a value in the corresponding servo multiplex data field.

9. The disk as recited in claim 8 wherein when the sequence number is at a first number, the value in the corresponding servo multiplex data field represents the portion of the higher order bits of the track position information, where when the sequence number is at a second number, the value in the corresponding servo multiplex data field represents a portion of the disk side portion of the disk, and wherein when the sequence number is at a third number, the value in the corresponding servo multiplex data field represents the quadrant of the disk.

10. A hard disk drive, comprising:

a housing;

a spin motor mounted to said housing;

an actuator arm mounted to said spin motor;

a disk attached to said spin motor, said disk having at least one side with a plurality of tracks, each track including a group having first and second sectors, each of the first and second sectors within said group includes first and second servo fields, the first servo field in each of the first and second sectors providing a portion of higher order bits of a track position information, the second servo field in each of the first and second sectors providing lower order bits of the track position information, the first servo fields of the first and second sectors and the second servo field in one of the first and second sectors, in combination, providing the track position information; and

a read/write head mounted to said actuator arm for reading said at least one side of said disk.

11. The hard disk drive as recited in claim 10, wherein the group includes a third sector having first and second servo fields, the first servo field in the third sector providing a portion of higher order bits of the track position information, and the second servo field in the third sector providing lower order bits of the track position information, the first servo fields of the first, second, and third sectors and the second servo field in one of the first, second, and third sectors, in combination, providing the track position information.

12. The hard disk drive as recited in claim 11, wherein the group includes a fourth sector having a first servo field, the first servo field in the fourth sector of the group providing a disk side position of the disk.

13. The hard disk drive as recited in claim 12, wherein the group includes a fifth sector having a first servo field, the first servo field in the fourth and fifth sectors, in combination, providing the disk side position of the disk.

14. The hard disk drive as recited in claim 13, wherein the group includes a sixth sector having a first servo field, the first servo field in the sixth sector providing a quadrant of the disk.

15. The hard disk drive as recited in claim 14, wherein the first servo field in each of the first through six sectors of the group includes a sector sequence number field and a servo multiplex data field, a sequence number in the sector sequence number field identifies a value in the corresponding servo multiplex data field.

8

16. The hard disk drive as recited in claim 15 wherein when the sequence number is at a first number, the value in the corresponding servo multiplex data field represents the portion of the higher order bits of the track position information, where when the sequence number is at a second number, the value in the corresponding servo multiplex data field represents a portion of the disk side position of the disk, and wherein when the sequence number is at a third number, the value in the corresponding servo multiplex data field represents the quadrant of the disk.

17. A method for providing servo information on a disk in a hard disk drive, comprising:

a) providing a disk having at least one side with a plurality of tracks, each track including a group having first and second sectors, each of the first and second sectors within said group includes first and second servo fields, the first servo field in each of the first and second sectors providing a portion of higher order bits of a track position information, the second servo field in each of the first and second sectors providing lower order bits of the track position information;

b) reading the first servo fields of the first and second sectors and the second servo field in one of the first and second sectors; and

c) determining track position information of the disk in response to reading the first servo fields of the first and second sectors and the second servo field in one of the first and second sectors.

18. The method as recited in claim 17, wherein the group includes a third sector having a first servo field providing a disk side position of the disk, and wherein reading comprises reading the first servo fields of the first through third sectors and the second servo field in one of the first and second sectors, and wherein determining comprises determining track position information and disk side position of the disk.

19. The method as recited in claim 18 wherein the group includes a fourth sector having a first servo field providing a quadrant of the disk, and wherein reading comprises reading the first servo fields of the first through fourth sectors and the second servo field in one of the first and second sectors, and wherein determining comprises determining track position information, disk side position, and quadrant of the disk.

20. The method as recited in claim 17, wherein each track includes a plurality of groups.

21. A data storage medium having N number of tracks, comprising:

a plurality of sectors, at least one of said plurality of sectors including a first track identification information for identifying a corresponding particular track to which said at least one of said plurality of sectors belong, said first track identification information consisting of M number of bits, said M being an integer less than $\log_2 N$.

22. The data storage medium according to claim 21, wherein:

at least a portion of said first track identification information is encoded in graycode encoding.

23. The data storage medium according to claim 21, further comprising:

one or more consecutive sectors adjacent to said at least one of said plurality of sectors, said one or more consecutive sectors each including a remainder track identification information, said first track identification information and said remainder track information from each of said one or more consecutive sectors being

combined together to identify said corresponding particular track to which said at least one of said plurality of sectors belong.

24. A data storage device, comprising:

a data storage medium having N number of tracks and a plurality of sectors, at least one of said plurality of sectors including a first track identification information for identifying a corresponding particular track to which said at least one of said plurality of sectors belong, said first track identification information consisting of M number of bits, said M being less than $\log_2 N$.

25. The data storage device according to claim 24, wherein:

at least a portion of said first track identification information is encoded in graycode encoding.

26. The data storage device according to claim 24, wherein:

said data storage medium further comprises one or more consecutive sectors adjacent to said at least one of said plurality of sectors, said one or more consecutive sectors each including a remainder track identification information, said first track identification information and said remainder track information from said one or more consecutive sectors being combined together to identify said corresponding particular track to which said at least one of said plurality of sectors belong.

27. A method of recording track information on a data storage medium having N number of tracks, each including a plurality of sectors, comprising:

recording in at least one of said plurality of sectors a first track identification information for identifying a corresponding particular track to which said at least one of said plurality of sectors belong, said first track identification information consisting of M number of bits, said M being less than $\log_2 N$.

28. The method of recording track information in accordance with claim 27, wherein:

at least a portion of said first track identification information is encoded in graycode encoding.

29. The method of recording track information in accordance with claim 27, further comprising:

recording in one or more consecutive sectors adjacent to said at least one of said plurality of sectors a remainder track identification information, said first track identification information and said remainder track information from each of said one or more consecutive sectors being combined together to identify said corresponding particular track to which said at least one of said plurality of sectors belong.

30. A data storage device, comprising:

one or more data storage media collectively having N number of tracks and a plurality of sectors, at least one of said plurality of sectors including a first track identification information for identifying a corresponding particular track to which said at least one of said plurality of sectors belong, said first track identification information consisting of M number of bits, said M being less than $\log_2 N$.

31. The data storage device according to claim 30, wherein:

at least a portion of said first track identification information is encoded in graycode encoding.

32. The data storage device according to claim 30, wherein:

said one or more data storage media further comprises one or more consecutive sectors adjacent to said at

least one of said plurality of sectors, said one or more consecutive sectors each including a remainder track identification information, said first track identification information and said remainder track information from said one or more consecutive sectors being combined together to identify said corresponding particular track to which said at least one of said plurality of sectors belong.

33. A method of recording track information in a data storage device having one or more data storage media collectively having N number of tracks and a plurality of sectors, comprising:

recording in at least one of said plurality of sectors a first track identification information for identifying a corresponding particular track to which said at least one of said plurality of sectors belong, said first track identification information consisting of M number of bits, said M being less than $\log_2 N$.

34. The method of recording track information in accordance with claim 33, wherein:

at least a portion of said first track identification information is encoded in graycode encoding.

35. The method of recording track information in accordance with claim 33, further comprising:

recording in one or more consecutive sectors adjacent to said at least one of said plurality of sectors a remainder track identification information, said first track identification information and said remainder track information from each of said one or more consecutive sectors being combined together to identify said corresponding particular track to which said at least one of said plurality of sectors belong.

36. A data storage medium having a plurality of tracks, comprising:

a first sector including a first track identification field, said first identification field consisting of a number of bits, which is less than a total number of bits required to individually address all of said plurality of tracks on said data storage medium; and

one or more consecutive sectors adjacent to said first sectors, said first sector and said one or more consecutive sectors being on an identical one of said plurality of tracks;

wherein said one or more consecutive sectors each includes a remainder track identification field, said first identification field and said remainder track identification field from said one or more consecutive sectors combined together completely identify said identical one of said plurality of tracks.

37. The data storage medium according to claim 36, wherein:

at least a portion of said first track identification field and said remainder track identification field is encoded in graycode encoding.

38. A data storage device, comprising:

a data storage medium including a plurality of tracks, said data storage medium having a first sector including a first track identification field, said first identification field consisting of a number of bits, which is less than a total number of bits required to individually address all of said plurality of tracks on said data storage medium, said data storage medium further including one or more consecutive sectors adjacent to said first sector, said first sector and said one or more consecutive sectors being on an identical one of said plurality of tracks, said one or more consecutive sec-

11

tors each including a remainder track identification field, wherein said first identification field and said remainder track identification field from said one or more consecutive sectors combined together completely identify said identical one of said plurality of tracks.

39. The data storage device according to claim 38, wherein:

at least a portion of said first track identification field and said remainder track identification field is encoded in graycode encoding.

40. A data storage device, comprising:

one or more data storage media collectively including a plurality of tracks, said data storage media having a first sector including a first track identification field, said first identification field consisting of a number of bits, which is less than a total number of bits required to individually address all of said plurality of tracks on said one or more data storage media, said one or more data storage media further including one or more consecutive sectors adjacent to said first sector, said first sector and said one or more consecutive sectors being on an identical one of said plurality of tracks, said one or more consecutive sectors each including a remainder track identification field, said first identification field and said remainder track identification field from said one or more consecutive sectors combined together completely identify said identical one of said plurality of tracks.

41. The data storage device according to claim 40, wherein:

at least a portion of said first track identification field and said remainder track identification field is encoded in graycode encoding.

42. A method of recording track number information in a data storage device employing a data storage medium having a plurality of tracks, comprising:

writing in a first sector of said data storage medium a first track identification, said first identification consisting of a number of bits, which is less than a total number of bits required to individually address all of said plurality of tracks on said data storage medium; and

12

writing in each of one or more consecutive sectors adjacent to said first sector a remainder track identification, said first sector and said one or more consecutive sectors being on an identical one of said plurality of tracks, said first identification and said remainder track identification from said one or more consecutive sectors combined together completely identify said identical one of said plurality of tracks.

43. The method of recording track number information in accordance with claim 42, wherein said writing of said first identification and said remainder track identification further comprises:

encoding at least a portion of said first track identification and said remainder track identification in graycode encoding.

44. A method of recording track number information in a data storage device employing one or more data storage media collectively having a plurality of tracks, comprising:

writing in a first sector of said one or more data storage media a first track identification; said first track identification consisting of a number of bits, which is less than a total number of bits required to individually address all of said plurality of tracks on said one or more data storage media; and

writing in each of one or more consecutive sectors adjacent to said first sector a remainder track identification, said first sector and said one or more consecutive sectors being on an identical one of said plurality of tracks, said first track identification and said remainder track identification from said one or more consecutive sectors combined together completely identify said identical one of said plurality of tracks.

45. The method of recording track number information in accordance with claim 44, wherein said writing of said first identification and said remainder track identification further comprises:

encoding at least a portion of said first track identification and said remainder track identification in graycode encoding.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : RE 39,831 E
APPLICATION NO. : 10/096662
DATED : September 11, 2007
INVENTOR(S) : Me Van Le et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 7, Line 17 after “side” change “portion” to --position--


Column 8, Line 45 change “clam” to --claim--

Column 10, Line 42 change “sectors,” to --sector,--

Column 12, Line 22 change “identification;” to --identification,--

Signed and Sealed this

Fifth Day of January, 2010

A handwritten signature in black ink, reading "David J. Kappos". The signature is written in a cursive, flowing style with a large, stylized "K".

David J. Kappos
Director of the United States Patent and Trademark Office