

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 February 2006 (23.02.2006)

PCT

(10) International Publication Number
WO 2006/020107 A2

(51) International Patent Classification:
F17C 9/02 (2006.01) *F25J 1/00* (2006.01)

(21) International Application Number:
PCT/US2005/025266

(22) International Filing Date: 18 July 2005 (18.07.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/894,355 18 July 2004 (18.07.2004) US

(71) Applicant (for all designated States except US): **MUS-TANG ENGINEERING, L.P.** [US/US]; 16001 Park Ten Place, Houston, TX 77084 (US).

(72) Inventors: **BRADFORD, S., Hubbard**; 2918 Redbud, katy, TX 77493 (US). **BAUDAT, Ned**; 1721 Greystone, New Branfels, TX 78132 (US). **WORTHINGTON, W., Scott**; 14834 La Quinta, Houston, TX 77493 (US).

(74) Agent: **GILBRETH, J., M., (Mark)**; Gilbreth & Associates, P.C., P.O. Box 2428, Bellaire, TX 77402-2428 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: APPARATUS FOR CRYOGENIC FLUIDS HAVING FLOATING LIQUEFACTION UNIT AND FLOATING REGASIFICATION UNIT CONNECTED BY SHUTTLE VESSEL, AND CRYOGENIC FLUID METHODS



(57) Abstract: Methods and systems for transportation of a cryogenic fluid. The system includes a floating liquefaction unit receiving a gas from a source, a shuttle vessel for carrying liquefied gas away from the liquefaction unit, and a floating regasification unit for receiving the liquefied gas from the vessel, regassifying the liquefied gas and providing the gas to a distribution system.

APPARATUS FOR CRYOGENIC FLUIDS HAVING FLOATING
LIQUEFACTION UNIT AND FLOATING REGASIFICATION
UNIT CONNECTED BY SHUTTLE VESSEL, AND CRYOGENIC
FLUID METHODS

INVENTOR: Bradford Scot Hubbard
 Ned Baudat
 W. Scott Worthington

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to cryogenic fluids. In another aspect, the present invention
relates to methods and apparatus for processing, transporting and/or storing cryogenic fluids. In
even another aspect, the present invention relates to receiving and/or dispensing terminals for
cryogenic fluids and to methods of receiving, dispensing and/or storing cryogenic fluids. In still
another aspect, the present invention relates a cryogenic fluid system having a floating
liquefaction unit receiving a gas from a source, a shuttle vessel for carrying liquefied gas away
10 from the liquefaction unit, and a floating regasification unit for receiving the liquefied gas from
the vessel, regassifying the liquefied gas and providing the gas to a distribution system.

- 2 -

2. Description of the Related Art

Most conveniently, natural gas is transported from the location where it is produced to the location where it is consumed by a pipeline. However, given certain barriers of geography, economics, and/or politics, transportation by pipeline is not always possible, economic or permitted. Without an effective way to transport the natural gas to a location where there is a commercial demand, the gas may be burned as it is produced, which is wasteful or reinjected into a subsurface reservoir which is costly and defers the utilization of the gas.

Liquefaction of the natural gas facilitates storage and transportation of the natural gas (a mixture of hydrocarbons, typically 65 to 99 percent methane, with smaller amounts of ethane, propane and butane). When natural gas is chilled to below its boiling point (in the neighborhood of -260°F depending upon the composition) it becomes an odorless, colorless liquid having a volume which is less than one six hundredth (1/600) of its volume at ambient atmospheric surface temperature and pressure. Thus, it will be appreciated that a 50,000 cubic meter LNG tanker ship is capable of carrying the equivalent of 1.1 billion cubic feet of natural gas.

When LNG is warmed above its boiling point, it boils reverting back to its gaseous form.

The growing demand for natural gas has stimulated the transportation of LNG by special tanker ships. Natural gas produced in remote locations, such as Algeria, Malaysia, Brunei, or Indonesia, may be liquefied and shipped overseas in this manner to Europe, Japan, United States, or neighboring countries needing gas. Typically, the natural gas is gathered through one or more pipelines to a land-based liquefaction facility. The LNG is then loaded onto a tanker equipped with cryogenic compartments (such a tanker may be referred to as an LNG carrier or "LNGC") by pumping it through a relatively short pipeline. After the LNGC reaches the destination port,

- 3 -

the LNG is offloaded by cryogenic pump to a land-based regasification facility, where it may be stored in a liquid state or regasified. If regasified, the resulting natural gas then may be distributed through a pipeline system to various locations where it is consumed.

Of the known liquid energy gases, liquid natural gas is the most difficult to handle because it is so intensely cold. Complex handling, shipping and storage apparatus and procedures are required to prevent unwanted thermal rise in the LNG with resultant regassification. Storage vessels, whether part of LNG tanker ships or land-based, are closely analogous to giant thermos bottles with outer walls, inner walls and effective types and amounts of insulation in between.

A number of patents disclose transportation of cryogenic fluids.

U.S. Pat. No. 3,830,180, issued August 20, 1974 to Bolton, discloses a ship for the transportation of volatile liquids having holds which contain a number of elongated vessels for containing cargo fluids where each vessel has a primary barrier for isolating cargo fluids from the hull and an insulating wall:

U.S. Patent No. 4,317,474, issued March 2, 1982 to Kentosh, describes a mooring and cargo transfer terminal for use in transferring a fluid such as LNG (liquified natural gas) which is supercooled and therefore likely to cause severe icing of pipes and joints. The terminal includes a table support in the form of a tower extending from a base at the sea floor up to the sea surface, and a table device rotatable about a vertical axis at the top of the table support. The table device carries a pair of fenders that can press directly against the side of a ship, hawser couplings for tying the table device to a set of hawsers that hold it tightly against the ship, and one or more loading arms which can extend beyond the table device to connect to an LNG

- 4 -

coupling on the ship. A pipe carries LNG from an underwater pipeline up to a fluid swivel at the top of the table support, and the rotatable portion of the fluid swivel connects to the loading arms to deliver the LNG thereto. The direct abutment of the rotatable table with the side of a ship near the bow thereof, enables loading arms of minimal length to be utilized to carry the LNG to the ship.

U.S. Patent No. 4,202,648, issued May 13, 1980 to Kvamsdal, discloses a floating plant for offshore liquefaction, temporary storage and loading of LNG, made as a semi-submersible platform with storage tanks for LNG arranged in the submerged section of the platform. The storage tanks are independent spherical tanks which are supported inside the submerged section of the platform and completely surrounded thereby.

U.S. Pat. No. 6,085,528, issued June 11, 2000, Woodall et al, discloses an improved system for processing, storing, and transporting LNG, and describes containers and transportation vessels for storage and marine transportation of pressurized liquefied natural gas (PLNG) at a pressure in the broad range of about 1035 kPa (150 psia) to about 7590 kPa (1100 psia) and at a temperature in the broad range of about -123.degree. C. (-190.degree. F.) to about -62.degree. C. (-80.degree. F.). Containers described in the PLNG Patent are constructed from ultra-high strength, low alloy steels containing less than 9 wt % nickel and having tensile strengths greater than 830 MPa (120 ksi) and adequate toughness for containing PLNG.

U.S. No. 6,460,721, issued October 8, 2002 to Bowen et al., discloses systems and methods for producing and storing pressurized liquefied natural gas (PLNG), wherein the systems and methods include (a) a natural gas processing plant suitable for producing PLNG; and (b) at least one container suitable for storing the PLNG, the at least one container comprising (i)

- 5 -

a load-bearing vessel made from a composite material and (ii) a substantially non-load-bearing liner in contact with the vessel, said liner providing a substantially impermeable barrier to the PLNG. The systems and methods also preferably include (c) means for transporting the at least one container containing PLNG to an import terminal.

5 U.S. Patent No. 6,560,988, issued May 13, 2003 to Kimble, describes systems and methods for delivering pressurized liquefied natural gas to an import terminal equipped with containers and vaporization facilities suitable for conventional LNG. The pressurized liquefied natural gas cargo, or any fraction thereof, is converted into conventional liquefied natural gas and sent to storage tanks suitable for conventional liquefied natural gas. Any of the cargo not
10 converted to conventional liquefied natural gas can be compressed and warmed to pipeline specifications. This gas can then pass into a sendout pipeline.

U.S. Patent No. 6,637,479, issued October 28, 2003 to Eide, et al., discloses a system for offshore transfer of liquefied natural gas between two vessels. The system comprises a coupling head mounted at one end of a flexible pipe means and arranged for attachment on a platform at
15 one end of one vessel when it is not in use, and a connection unit mounted at one end of the other vessel and comprising a pull-in funnel shaped for guided pull-in of the coupling head to a locking position in which the pipe means can be connected to transfer pipes on the other vessel via a valve means arranged in the coupling head. The coupling head is provided with a guide means and is connected to at least one pull-in wire for guided pull-in of the coupling head into the
20 connection unit by a winch means on the other vessel.

All of the patents cited in this specification, are herein incorporated by reference.

However, in spite of the above advancements, there still exists a need in the art for

- 6 -

apparatus and methods for processing, transporting, and/or storing LNG.

This and other needs in the art will become apparent to those of skill in the art upon review of this specification, including its drawings and claims.

SUMMARY OF THE INVENTION

It is an object of the present invention to provide for improved apparatus and methods for processing, transporting, and/or storing LNG.

This and other objects of the present invention will become apparent to those of skill in the art upon review of this specification, including its drawings and claims.

According to one embodiment of the present invention, there is provided an apparatus for transporting a gas. The apparatus includes a floating liquifaction unit having a first docking system. The apparatus also includes a floating regassification unit having a second docking system. The apparatus also includes a shuttle vessel comprising a third docking system. The shuttle vessel may be docked with the liquifaction unit, docked with the gassification unit, or traveling between the liquifaction unit and the regassification unit. The third docking system is connectable with the first docking system when the vessel is docked with the liquifaction unit, and connectable with the second docking system when the vessel is docked with the gassification unit. As further embodiments of this embodiment, the floating liquifaction unit may be connected to a gas source, and the floating regassification unit is connected to a gas distribution system. As even further embodiments, the liquifaction unit, the gassification unit, and the vessel are all floating on a body of water. As still further embodiments, there are provided methods of operating such an apparatus, and methods of transporting a gas.

According to another embodiment of the present invention, there is provided a method of transporting a gas. The method includes receiving the gas into a floating liquifaction unit. The method further includes liquifying the gas to form a liquified gas. The method further

includes transferring the liquified gas from the liquifaction unit into a marine vessel. The method further includes transferring the liquified gas from the marine vessel into a floating regassification unit. The method further includes regassifying the liquified gas into a regassified gas. The method may also include providing the regassified gas to a distribution system.

5 According to even another embodiment of the present invention, there is provided a floating liquifaction unit, methods of operating such a unit, and methods of liquifacation.

 According to still another embodiment of the present invention, there is provided a floating regassification unit, methods of operating such a unit, and methods of regassification.

 These and other embodiments of the present invention will become apparent to those of
10 skill in the art upon review of this specification, including its drawings and claims.

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, it should be understood that like reference numbers refer to like members.

5 FIG. 1 is a schematic representation of natural gas transportation system 100, showing floating liquefaction unit 30, floating regasification unit 50, and shuttle vessel 70 traveling therebetween.

DETAILED DESCRIPTION OF THE INVENTION

While some descriptions of the present invention may make reference to natural gas and to liquefied natural gas ("LNG"), it should be understood that the present invention is not limited to utility with natural gas and LNG, but rather has broad utility with gases and cryogenic fluids in general, preferably cryogenic fluids formed from flammable gases.

The apparatus of the present invention will find utility for processing, storing, and/or transporting (i.e., including but not limited to, receiving, dispensing, distributing, moving) gases and cryogenic fluids, a non-limiting example of which are natural gas and liquefied natural gas ("LNG").

According to the present invention, there are provided a floating liquefaction unit, a floating regasification unit, a shuttle vessel traveling therebetween.

Further according to the present invention, there is provided a system comprising a floating liquefaction unit receiving a gas from a source, a shuttle vessel for carrying liquefied gas away from the liquefaction unit, and a floating regasification unit for receiving the liquefied gas from the vessel, regassifying the liquefied gas and providing the gas to a distribution system.

Referring now to FIG. 1, there is shown a schematic representation of natural gas transportation system 100, showing floating liquefaction unit 30, floating regasification unit 50, and shuttle vessel 70 traveling therebetween.

Floating liquefaction unit 30 is positioned on a body of water 40 and may be permanently or periodically connected via connection 31 to a source of natural gas 5. This source of natural gas 5 may be a direct pipeline connection to natural gas being produced from a well(s), mobile a mobile vessel(s), or to storage tanks. Periodic connections could also be made to land or

- 11 -

marine transport vessels carrying storage tanks of natural gas.

Natural gas liquefaction units are well known in the art. In the present invention, floating liquefaction unit 30 will generally include all of the necessary components of a natural gas liquefaction unit as are known to those of skill in the art. Optionally, floating liquefaction unit 30 may include storage tanks for the incoming natural gas. As for storage tanks for the LNG, they may be provided, or optionally, LNG may be produced while shuttle vessel 70 is connected via connection 33 and pumped directly into shuttle vessel 70 without the need to store LNG on floating liquefaction unit 30.

Shuttle vessels for transporting LNG are well known in the art, and any of the known vessels may be utilized in the present invention as shuttle vessel 70.

LNG regasification units are well known in the art.

In the present invention, floating regasification unit 50 will generally include all of the necessary components of a regasification unit as are known to those of skill in the art. Floating regasification unit 50 may include storage tanks for receiving the LNG, or shuttle vessel 70 may serve as a storage tank by remaining docked with floating regasification unit 50 during the regasification process. Floating regasification unit 50 may also include storage tanks for the regasified natural gas, this gas may be provided to off-unit storage into mobile vessels during regasification. Connection 53 may be connected to a distribution system 85, which may be a pipeline system, storage tanks or mobile vessels.

In operation of transportation system 100, natural gas 5, whether directly from a well, storage tank or mobile vehicle, is provided via connection 31 to liquefaction unit 30. This natural gas is then liquefied in liquefaction unit 30, where it may or may not be stored first before being

- 12 -

pumped via docking connection 33 into shuttle vessel 70. This shuttle vessel 70 then traverses body of water 40 to regasification unit 50. Docking connection 51 facilitates offloading of the LNG to regasification unit 50, either into storage tanks or directly into the regasification process. Once the LNG is regasified, it may be stored on regasification unit 50 or provided via connection 53 to off-unit storage tanks, a distribution pipeline, or to mobile vessels.

The present invention may incorporate any desirable apparatus and method features as described and/or taught in any of U.S. Patent Application Nos. 10/782,736 (filed 2/19/04), 10/777,506 (filed 2/11/04), 10/816,793 (filed 4/1/04), and 10/869,461 (filed 6/15/04), all by applicant Ned P. Baudat, the specifications of which are all herein incorporated by reference for all that they disclose and teach.

- 13 -

While the illustrative embodiments of the invention have been described with particularity, it will be understood that various other modifications will be apparent to and can be readily made by those skilled in the art without departing from the spirit and scope of the invention. Accordingly, it is not intended that the scope of the claims appended hereto be limited to the examples and descriptions set forth herein but rather that the claims be construed as encompassing all the features of patentable novelty which reside in the present invention, including all features which would be treated as equivalents thereof by those skilled in the art to which this invention pertains.

5

- 14 -

I CLAIM:

11. An apparatus for transporting a gas, the apparatus comprising:
 - 2 a floating liquifaction unit comprising a first docking system;
 - 3 a floating regassification unit comprising a second docking system; and,
 - 4 a shuttle vessel comprising a third docking system, wherein the shuttle vessel may be
5docked with the liquifaction unit, docked with the gassification unit, or traveling between the
6liquifaction unit and the regassification unit, and wherein the third docking system is connectable
7with the first docking system when the vessel is docked with the liquifaction unit, and
8connectable with the second docking system when the vessel is docked with the gassification
9unit.
12. The apparatus of claim 1, wherein the floating liquifaction unit is connected to a gas
2source, and the floating regassification unit is connected to a gas distribution system.
13. The apparatus of claim 2, wherein the liquifaction unit, the gassification unit, and the
2vessel are all floating on a body of water.
14. A method of transporting a gas, comprising;
 - 2 (A) receiving the gas into a floating liquifaction unit,
 - 3 (B) liquifying the gas to form a liquified gas;
 - 4 (C) transferring the liquified gas from the liquifaction unit into a marine vessel;
 - 5 (D) transferring the liquified gas from the marine vessel into a floating regassification

- 15 -

6unit; and

7 (E) regassifying the liquified gas into a regassified gas.

15. The method of claim 4, wherein the gas of step (A) is from a gas pipeline, a well, mobile
2vessel, or a storage tank.




Fig. 1