




(86) Date de dépôt PCT/PCT Filing Date: 2006/01/06
 (87) Date publication PCT/PCT Publication Date: 2006/07/13
 (45) Date de délivrance/Issue Date: 2013/08/20
 (85) Entrée phase nationale/National Entry: 2007/07/05
 (86) N° demande PCT/PCT Application No.: US 2006/000587
 (87) N° publication PCT/PCT Publication No.: 2006/074425
 (30) Priorités/Priorities: 2005/01/06 (US60/593,350);
 2005/05/19 (US PCT/US2005/017793)

(51) Cl.Int./Int.Cl. *F24F 13/068* (2006.01),
F24F 11/00 (2006.01), *F24F 7/08* (2006.01)
 (72) Inventeurs/Inventors:
 BAGWELL, RICK A., US;
 LIVCHAK, ANDREY, US
 (73) Propriétaire/Owner:
 OY HALTON GROUP, LTD, FI
 (74) Agent: RICHES, MCKENZIE & HERBERT LLP

(54) Titre : SYSTEME DE VENTILATION A DEPLACEMENT AUTOMATIQUE DOTE D'UN MODE DE CHAUFFAGE
 (54) Title: AUTOMATIC DISPLACEMENT VENTILATION SYSTEM WITH HEATING MODE



(57) Abrégé/Abstract:

Displacement ventilation systems are generally poor performers when it comes to heating. The instant patent application discusses devices and systems for improving heating performance while retaining the benefits of displacement ventilation without wholesale co- location of independent space conditioning systems.



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 July 2006 (13.07.2006)

PCT

(10) International Publication Number
WO 2006/074425 A1

(51) International Patent Classification:

F24F 13/068 (2006.01) *F24F 11/00* (2006.01)
F24F 7/08 (2006.01)

(74) Agent: CATAN, Mark; PROSKAUER ROSE LLP, 1233
20th Street, N.w., Suite 800, Washington, District Of Co-
lumbia 20036 (US).

(21) International Application Number:

PCT/US2006/000587

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV,
LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI,
NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG,
SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US,
UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 6 January 2006 (06.01.2006)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

60/593,350 6 January 2005 (06.01.2005) US
PCT/US2005/017793 19 May 2005 (19.05.2005) US

(71) Applicant (*for all designated States except US*): HALTON
OY; Niittyvillankuja 4, FI-FIN-01510 Vantaa (FI).

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT,
RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA,
GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant and

(72) Inventor: BAGWELL, Rick A [US/US]; 168 Lake View
Circle, Scottsville, Kentucky 42164 (US).

(72) Inventor; and


(75) Inventor/Applicant (*for US only*): LIVCHAK, Andrey
[US/US]; 706 Newberry Street, Bowling Green, Kentucky
42103 (US).

Published:

— with international search report

[Continued on next page]

(54) Title: VENTILATION REGISTER AND VENTILATION SYSTEMS



(57) Abstract: Displacement ventilation systems are generally poor performers when it comes to heating. The instant patent application discusses devices and systems for improving heating performance while retaining the benefits of displacement ventilation without wholesale co- location of independent space conditioning systems.

WO 2006/074425 A1

WO 2006/074425 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

AUTOMATIC DISPLACEMENT VENTILATION SYSTEM WITH HEATING MODE

FIELD OF THE INVENTION

[Para 1] The present invention relates to ventilation systems. More particularly, the present invention relates to displacement-type ventilation systems and methods thereof.

BACKGROUND OF THE INVENTION

[Para 2] In the past, there have been many types of displacement ventilation systems. For example, European application no. EP 1 323 988 discloses a system for ventilation of a room wherein at least one supply air means is arranged to supply clean air to the room, and, at least one air discharge means is arranged to remove used indoor air from the room. The respective air flows through the supply means and discharge means are controlled so as to provide a clean air zone in a specific part of the room. The air supply means can be located at the floor of the room to be ventilated, while the air discharge means can be located close to the ceiling.

[Para 3] From U.S. Patent No. 2,928,330, it is known to have a process and means for heating, cooling and distribution of pre-conditioned air into several rooms through ventilators in their walls.

SUMMARY OF THE INVENTION

[Para 4] Accordingly, it is an object of this invention to at least partially overcome some of the disadvantages of the prior art. Also, it is an object of this invention to provide an improved type of automatic displacement and ventilation system with heating mode.

[Para 5] Accordingly, in one aspect, the present invention provides a ventilation system for an occupied space, comprising: at least one supply register configured as a displacement-type diffuser providing a flow of ventilation air at non-mixing rates; at least one first return register configured to withdraw air at a level proximate a ceiling of said occupied space and at least one second return register configured to withdraw air from said occupied space at a level near a floor of said occupied space; a control system configured to control the flow of heated or cooled air to said at least one supply register and selectively to

control the flow of air into said at least one first return register and said at least one second return register such that: during cooling, cooled air is supplied through said at least one supply register and air is withdrawn through said at least one first return register, and during heating, warm air is supplied through said at least one supply register and air is withdrawn through said at least one second return register.

[Para 6] Further aspects of the invention will become apparent upon reading the following detailed description and drawings, which illustrate the invention and preferred embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[Para 7] Figs. 1A and 1B illustrates a conditioned space with configurable mixing/displacement ventilation registers in displacement and mixing modes, respectively.

[Para 8] Figs. 2A and 2B illustrate a first embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively.

[Para 9] Figs. 3A and 3B illustrate a second embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively.

[Para 10] Figs. 4A and 4B illustrate a third embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively.

[Para 11] Figs. 5A and 5B illustrate a fourth embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively.

[Para 12] Figs. 6A and 6B illustrate a fifth embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively.

[Para 13] Figs. 7A and 7B illustrate a sixth embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively.

[Para 14] Figs. 8A and 8B illustrate an alternative embodiment in which the return registers are changed over from heating to cooling mode, but the supply registers are the same.

[Para 15] Figs. 9A and 9B illustrate an alternative embodiment in which the return registers are changed over from heating to cooling mode, and hydronic heating is used in place of force air heating.

[Para 16] Fig. 10 is an illustration of a central control system that may be used with various embodiments discussed herein.

[Para 17] Fig. 11 shows a plan view of a room with multiple discharge registers 1125, 1135, and 1145.

[Para 17a] Figs. 12A and 12B show an embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively, in which independent dampers are used to modulate total air volume, for example based on a VAV scheme.

[Para 17b] Fig. 13 illustrates a simple example of a controller for VAV control as well as mode switching for a configurable mixing/displacement ventilation register such as illustrated at Figs. 12A and 12B.

[Para 17c] Fig. 14 illustrates seventh embodiment of a configurable mixing/displacement ventilation register.

[Para 17d] These figures are intended to show the concept and are not intended to show details of components whose designs are well understood in the field such as linkages, motor details, bearings, supports, etc. These are within the competence of skilled practitioners and are not discussed in detail herein.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[Para 17e] FIG. 1A and FIG. 1B illustrates a configurable mixing/displacement ventilation register 550 in an occupied room 570. People 510 in the room are warmer than the surrounding air, causing air to rise by convection. The room also contains a cooling-mode return register 530 in the upper portion of the room, and a heating mode return register 535 in the lower portion of the room. The temperature of the air within the room 570 is illustrated by isothermal layers of constant temperature air 505.

[Para 17f] When the room is in displacement mode, which is generally used for cooling the conditioned space, the mixing/displacement ventilation register 550 supplies cooled air at a low velocity from a relatively high portion and over a relatively large face area of the mixing/displacement ventilation register 550. This cool air flows along the lower portion of the room. Any heat source within the room such as the occupants 510, causes air warmed by

that source to rise by convective forces resulting in warm zones indicated by dips in contours of constant temperature 515. This rising air draws fresh cool air pooled near a floor 521 to replace the polluted and stale air surrounding the occupants 510. The warm air pools near the ceiling and is withdrawn by the return register 530. The higher regions of the room 570 remain relatively undisturbed and since it is not within the lower part of the room – the inhabited space – the air in contact with and breathed by occupants is relatively fresh. By not cooling this uninhabited space, the cooling efficiency is increased. Also, the immediate replacement of air polluted by heat sources increases comfort.

[Para 18] Figure 1B illustrates the mixing mode for heating the occupied space. In this mode, the mixing/displacement ventilation register 550 supplies heated air at a high velocity through a relatively small face area as illustrated by jets 551. This warm air flows rapidly along the lower portion of the room before it has time to rise from convection and encourages mixing of all the air in the room, as indicated by the randomly arranged and directed arrows 552. This rapid movement causes mixing of the air in the room due to the initial velocity of the jets 551, their turbulence, and the tendency of the heated air naturally to rise due to convection. The heating mode return register 535 removes cooled air which tends to sink from convection.

[Para 19] Figs. 2A and 2B illustrate a first embodiment of a configurable mixing/displacement ventilation register 550 in displacement and mixing modes, respectively. Referring now to Fig. 2A the first embodiment of a configurable mixing/displacement ventilation register 550 is in displacement, or cooling, mode. As the cool air 160 enters the ventilation register plenum 130 it causes a thermal actuator 105 to move a thrust rod 110 attached to a baffle cage 115 toward a lower section 120 of the configurable mixing/displacement ventilation register 550, thereby moving it to the floor base 150 of the configurable mixing/displacement ventilation register 550. The baffle cage 115 allows air to pass through it and serves to spread the flow over the large face area that includes a larger baffle housing 100 of the configurable mixing/displacement ventilation register 550. The open area of the baffles 100 and 115 is such as to cause resistance across the face of the baffles 100 and 115 thereby spreading the incoming flow 160 broadly over the face area of the baffles 110 and 115. This results in flow over the majority of the outer diffusion baffle 100 of the configurable mixing/displacement ventilation register 550 as

indicated by arrows 145. The air flowing from the baffle cage 115 and the baffle housing 110 therefore functions as displacement supply register venting air at a low velocity through relatively restrictive openings in the baffles of the baffle housing 100 and the baffle cage 115.

[Para 20] Fig. 2B illustrates the first embodiment in mixing, or heating, mode. As the warm air 165 enters the ventilation register plenum 135 it causes thermal actuator 105 to move the baffle cage 115 upwardly to uncover an open outlet 120 of the configurable mixing/displacement ventilation register 550. A bottom 116 of the baffle cage 115 has a high percentage open area and provides little resistance to flow as does the open outlet 120. As a result, a direct flow path through the plenum 135 to the open outlet 120 is created which results in low restriction – high velocity – flow of the warm air to the open outlet 120. Thus, most of the heating air 165 passes at a relatively high velocity out the lower, relatively small face area of the open outlet 120 of the configurable mixing/displacement ventilation register 550. Thus, in the present configuration, it functions as a mixing supply register.

[Para 21] Figs. 3A and 3B illustrate a second embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively. Fig. 3A illustrates the second embodiment of the configurable mixing/displacement ventilation register 551 in displacement, or cooling mode. A transmission 15 is indicated figuratively by a broken line. The transmission may be formed by any suitable means such as a pulley or gear system or by means of pushing or pulling or other rotating members. The details are outside the scope of invention and are readily created for various design arrangements.

[Para 22] As cool air 160 enters a ventilation register plenum 230 it causes the thermal actuator 10, by way of the transmission 15, to rotate a spring loaded capstan 220 which releases tension on a chord 225 allowing a spring-loaded cap plate 210 to pivot on an axis of the capstan/lever 215 to seal the end 212 of the ventilation register plenum 230. Cool air flow 270 is forced to spread the flow over the large face area of a flow-restricting baffle 250 and further distributed by an outer baffle 260. The capstan 220 also releases tension on a lower pull cord 235 releasing a spring loaded baffle panel 245 to pivot on a spring-loaded axel 240, securing it flush with the outer baffle 260 of the configurable mixing/displacement ventilation register 551.

[Para 23] Note that the transmission 15 and the pulley and capstan components are shown for illustration purposes only and can be replaced by any suitable mechanism for performing the described functions. These mechanisms could be mechanical or electromechanical and performed by means of a thermoactuator such as a wax motor or a linear actuator powered by electricity or pneumatic power or controls. There are many possible design variations and the details are unimportant for understanding the invention so they are not discussed at length here. Note also that the views of the present, foregoing, and further embodiments below are section views of suitable enclosures. They can be rectangular or other shapes. The materials used may be any combination of metal, plastic, or other materials suitable for conveying air.

[Para 24] The resulting configuration illustrated in Fig 3A allows the cool air 165 to flow through the outer baffle 260 of the configurable mixing/displacement ventilation register 551 in the manner of a displacement supply register. The open area of the baffle 260 is such as to cause resistance across the face of the baffle 260 and the baffle panel 245 thereby spreading the flow 160 broadly over the outer baffle 260 face area of the configurable mixing/displacement ventilation register 551 as indicated by arrows 265. It therefore functions as displacement supply register, venting air at a low velocity through relatively restrictive openings of the outer baffle 260 and the baffle panel 245.

[Para 25] Fig. 3B illustrates the second embodiment of the configurable mixing/displacement ventilation register 551 in mixing, or heating mode. As the heated air 165 enters the ventilation register plenum 230 it causes the thermal actuator 10 to act through the transmission 15 to rotate the spring-loaded capstan 220, exerting tension on the cap plate pull cord 225 causing the spring-loaded cap plate 210 to pivot on the axel 215 and open the end 212 of the plenum 230. The capstan 220 also exerts tension on the lower pull cord 235 causing the spring loaded baffle panel 245 to pivot on the axis 240, opening the lower portion of the configurable mixing/displacement ventilation register 551. As a result, most of the heated air 165 passes at a relatively high velocity out the lower, relatively small face area of an open outlet 243 of the configurable mixing/displacement ventilation register 551 so that it functions as a mixing supply register.

[Para 26] Figs. 4A and 4B illustrate a third embodiment of a configurable mixing/displacement ventilation register 552 in displacement and mixing modes, respectively. Fig. 4A illustrates the third embodiment of the configurable mixing/displacement ventilation register 552 in the displacement, or cooling, mode. As the cool air 160 enters the ventilation register plenum 330 it causes the thermal actuator 10 to act upon the transmission 15 to rotate a spring loaded capstan 320 which releases tension on a chord 325 allowing a spring-loaded cap plate 310 to pivot on an axis of capstan/lever 315 to seal the end 312 of a plenum 330. Cool air flow 370 is forced to spread over the large face area of a flow-restricting baffle 350. The capstan 320 also releases tension on a lower pull cord 335 releasing a spring loaded baffle panel 345 to pivot on an axel 340, securing it flush with an outer baffle 304 of the configurable mixing/displacement ventilation register 552. The releasing of the spring loaded baffle panel 345 also releases tension on a third pull chord 345 allowing a sliding baffle panel 306 to align with the outer baffle 304 allowing a cool air flow 370 flow through the large face area of the two baffle panels 304 and 306 which combine to form a single open baffle or grate 322A.

[Para 27] The resulting configuration illustrated in Fig 4A allows the cool air 160 to flow through the baffle/grate 322A of the configurable mixing/displacement ventilation register 552 in the manner of a displacement supply register. The open area of the baffle/grate 322 may be such as to cause substantial or little resistance across the face of the baffle/grate 322. The spreading of the flow may be provided by the inner baffle 350 or the outer baffle/grate 322 may assist by providing some resistance as well. By spreading the flow broadly over the face area of the configurable mixing/displacement ventilation register 552 as indicated by the arrows 365, it functions as displacement supply register.

[Para 28] Fig. 4B illustrates the third embodiment of the configurable mixing/displacement ventilation register 552 in mixing, or heating, mode. As the heated air 165 enters the ventilation register plenum 330, it causes the thermal actuator 10 to act upon the transmission 15 to rotate the spring loaded capstan 320 causing it to exert tension on the cap plate pull cord 325. This causes the spring-loaded cap plate 310 to pivot on the axel 315 and open the end of the plenum 330. The capstan 320 also exerts tension on the lower pull cord 335 causing the spring loaded baffle panel 345 to pivot on the axis 340, opening the lower portion of the configurable mixing/displacement ventilation register 552. The pivoting

of the spring loaded baffle panel 345 also removes tension on the third pull chord 345 allowing the sliding baffle panel 306 to close the baffle/shutter 322 preventing the warm air flow 330 from passing through it. The heated air 165 thus passes at a relatively high velocity out the lower, relatively small face area of an open outlet 343 of the configurable mixing/displacement ventilation register 552 so that the configurable mixing/displacement ventilation register 552 functions as a mixing supply register.

[Para 29] Figs. 5A and 5B illustrate a fourth embodiment of a configurable mixing/displacement ventilation register 553 in displacement and mixing modes, respectively. Fig. 5A illustrates the displacement, or cooling mode. As the cool air 160 enters a ventilation register plenum 425 it causes a rotating thermal actuator capstan 450 to act upon a pull chord 455 to rotate a spring loaded flap cover 440 on a pivot 460 to seal off plenum 430. This action causes the cooled air 160 to enter only a cooling plenum 405 which is separated from a heating plenum 430 by a middle wall 435. The open area of the baffle 404 is such as to cause resistance across the face of the baffle 404 thereby spreading the flow 160 broadly over the large face area of the configurable mixing/displacement ventilation register 553. This causes it to function as a displacement supply register venting air at a low velocity over a large area.

[Para 30] Fig. 5B illustrates the fourth embodiment of the configurable mixing/displacement ventilation register 553 in mixing, or heating, mode. As the warm air 165 enters the ventilation register plenum 425 it causes the rotating thermal actuator capstan 450 to act upon the pull chord 455 to rotate the spring loaded flap cover 440 on the pivot 460 to seal off the cooling plenum 405. This action causes the warm air 165 to enter only the warm plenum 430 which is bound by the middle wall 435 and a back wall 420. The relatively smaller face area of a heating mode outlet 475 builds greater back pressure within the warm (heating) plenum 430 causing the flow 160 to exit through the small face area of the outlet 475 of the configurable mixing/displacement ventilation register 553 at high velocity. As a result, the register 553 functions as a mixing supply register.

[Para 31] Figs. 6A and 6B illustrate a fifth embodiment of a configurable mixing/displacement ventilation register 554 in displacement and mixing modes, respectively. Fig. 6A illustrates the fifth embodiment in displacement, or cooling, mode. As

the cool air 160 enters a ventilation register a plenum 630 it causes the thermal actuator 10 to act upon a push rod 620 to rotate a cap plate 610 on a pivot 615 to seal the end of the plenum 630. Cool air flow 665 is forced to spread over the large face area of a flow-restricting inner baffle 650 and into a cooling plenum 605. The movement of the cap plate 610 also releases tension on a lower baffle panel 645 to pivot on an axel 640, securing it flush with an outer baffle 604 which forces a cool air flow 665 to spread over the large face area of a flow-restricting baffle 604.

[Para 32] The resulting configuration illustrated in Fig 6A allows the cool air 630 to flow through the flow-restricting inner baffle 650 then an outer baffle 604 of the configurable mixing/displacement ventilation register 554 in the manner of a displacement supply register. The open area of the baffle 604 is such as to cause resistance across the face of the baffle 604 and lower baffle panel 645 thereby spreading the flow 665 broadly over the face area of the configurable mixing/displacement ventilation register 554 as indicated by the arrows 665 and therefore functions as displacement supply register venting air at a low velocity through relatively restrictive openings within the outer baffles 604 and the baffle panel 645.

[Para 33] Fig. 6B illustrates the fifth embodiment of the configurable mixing/displacement ventilation register 554 in mixing, or heating mode. As the heated air 165 enters the ventilation register plenum 630 it causes the thermal actuator 10 to act upon the push rod 620 to rotate the cap plate 610 on the pivot 615 to open the end of the plenum 630. This causes engagement of the cap plate 610 and a lever arm 655 of the baffle panel 645 to swing the baffle panel 645 in an open position, opening the lower portion of the configurable mixing/displacement ventilation register 554. As a result, the heated air 165 passes at a relatively high velocity out the lower, relatively small face area of an open outlet 643 of the configurable mixing/displacement ventilation register 554 so that it functions as a mixing supply register.

[Para 34] Figs. 7A and 7B illustrate a sixth embodiment of a configurable mixing/displacement ventilation register in displacement and mixing modes, respectively. Fig. 7A illustrates the sixth embodiment in displacement, or cooling, mode. Note the present embodiment is similar to the embodiment of Figs. 6A and 6B so many of the reference numerals are common. As the cool air 160 enters the ventilation register plenum 630 it

causes the thermal actuator 10 to act upon the push rod 620 to rotate the cap plate 610 on the pivot 615 to seal the end of the plenum 630. The cool air flow 160 is forced to spread over the large face area of the flow-restricting inner baffle 650 and into the cooling plenum 605. The resulting configuration illustrated in Fig 7A allows the cool air 630 to flow through the flow-restricting inner baffle 650 then the very open outer baffle 700 of the configurable mixing/displacement ventilation register 555 in the manner of a displacement supply register. The resistance across the face of the baffle 650 is such as to cause resistance across the face of the baffle 650 thereby spreading the flow 750 broadly over the face area of the baffle 650 and out through the low restriction baffle 700 as indicated by the arrows 710 and therefore functions as displacement supply register venting air at a low velocity through relatively restrictive openings within the inner baffles 650 and the open baffle panel 700.

[Para 35] Fig. 7B illustrates the sixth embodiment of the configurable mixing/displacement ventilation register 555 in mixing, or heating mode. As the heated air 165 enters the ventilation register plenum 630 it causes the thermal actuator 10 to act upon the push rod 620 to rotate the cap plate 610 on the pivot 615 to open the end of the plenum 630. The heated air 165 thus predominately passes at a relatively high velocity out the lower, relatively small face area of an open outlet 643 of the configurable mixing/displacement ventilation register 555 so that it functions as a mixing supply register.

[Para 36] Figs. 8A and 8B illustrate an alternative embodiment in which the return registers are changed over from heating to cooling mode, but the supply registers are in the same configuration in both heating and cooling mode. Displacement registers 850 are located in a room 850. Displacement registers 850 are normal displacement registers installed in a system in which return air registers 830 and 835 exist. During cooling mode, the displacement registers 850 deliver cool air at floor level as illustrated and warm air stratified near the ceiling is returned via return registers 830. As in previous embodiments, displacement supply air flow near the floor 821 and is heated by occupants 810 causing thermal plumes 815 which are indicated by isothermal lines 805. Warm air 870 near the ceiling is drawn into the return air register and 830. An air recirculating fan 831, may optionally be provided to mix warm stratified air in the heating mode. The fan 831 may be positioned at any point in a room including near the floor or in the middle. Note that where mixing is used, return registers at only one level may suffice, for example, only one set of

return registers may be used such as those near the ceiling 830 or ones located at an intermediate height (not illustrated). The circulating fan 831 may be controlled locally using a sensor for detecting either cold temperatures near the floor, warm air near the ceiling, or a floor-ceiling differential temperature.

[Para 37] Fig. 8B illustrates the alternative embodiment of the conventional displacement ventilation register 850 in a heating mode. Heated air enters the room 820 at low velocity and rises. A return register located near the floor draws cooled air in. By arranging the return registers at a position remote from the displacement registers 850, a circulation pattern can be established in the room that mitigates the undesirable stratification that can occur when using non-mixing type supply registers during heating.

[Para 38] Figs. 9A and 9B illustrate an alternative embodiment in which the return registers are changed over from heating to cooling mode, and hydronic heating is used in place of force air heating. In the present embodiment, heating is done with a separate heating system under common control, for example hydronic heating using hydronic heaters 980. Displacement registers 950 are normal displacement registers installed in a system in which return air registers 930 and 935 exist. During cooling mode, the displacement registers 950 deliver cool air at floor level as illustrated and warm air stratified near the ceiling is returned via return registers 930. As in previous embodiments, displacement supply air flow near the floor and is heated by occupants 915. Warm air 970 near the ceiling is drawn into the return air register and 930.

[Para 39] Fig. 9B illustrates the alternative embodiment of the conventional displacement ventilation register 850 in a heating mode. Heated air enters the room from hydronic heaters. A return register 935 located near the floor draws cooled air in. By arranging the return registers at a position remote from the hydronic heaters 980, a circulation pattern can be established in the room that mitigates the undesirable stratification that can occur when using non-mixing type supply registers during heating.

[Para 40] In many commercial buildings, heat may be lost through only one or two walls of an occupied space. For example, in an office building this is commonly the case. In a preferred embodiment of the general Fig. 9B embodiment, the rear wall in which at least one of the return registers 935 is located corresponds to that wall. This is so that the coldest air,

which may be flowing downwardly along the surface of the "cold" wall, can be drawn into the one or more return registers 935 rather than mixing with the room air or causing the lower stratum of the room to get colder. The volume exchange rate may be sized to match the volume rate of the convective flow, which is readily predicted based on the outdoor air temperature, the conductivity and diffusivity of the wall, the film coefficients and so on according to known techniques. This is an excellent application for feed-forward or predictive model-based control because of the unsteady state of the wall system. In a preferred embodiment, such a model-based control scheme may take account of outdoor wind speed and direction, in addition to the obvious one of air temperature. In addition, such preferred embodiment may take account of conditioned space occupancy and predicted activity levels (for example, a lookup table based on time of day) so that activity-induced disturbances in the thermal convection field can be taken into account.

[Para 41] Obviously, a feed-forward scheme would not necessarily explicitly perform all such computations, for example, modeling the real-time temperature of the wall resulting from internal capacity and so on. But any control system controlling air exchanges based on the thermal flow from a cold wall would tend to exchange more air when it is colder outside than when it is less cold. This makes the air changes independent of the load, which for a given outdoor temperature (and possibly other conditions, as discussed), may vary depending on the activity level, which can add additional heat generation to the system (e.g. office machinery, lights, etc.). In addition, many commercial building heating systems do not alter the air exchange rate in response to load, but instead alter the delivery temperature. So a system configured to withdraw the air near a cold wall at a sufficient rate to keep the cold wall-plume from mixing well with room air would provide a volume flow rate that is higher when the load is higher (outdoor air is colder). In addition, the rates would tend to be higher, at times, than the minimum air change criteria (for ventilation purposes) would require.

[Para 42] A simple way of providing the additional level of control for ameliorating the effect of cold wall convection is to place temperature sensors on the cold walls or at the level of the floor near the cold wall or walls.

[Para 43] In many cases, the cold wall is the outside wall and may be fitted with a window. This may make the placement of the return register in the middle of the wall

difficult. However, one or more return registers 935 may be located at the ends of the cold wall on one or both adjacent perpendicular walls such that air is drawn from the same lower region of the cold wall.

[Para 44] The effect of providing substantial air changes in a space where non-mixing is provided is to push cold air near the floor out of the room so that warm air, which tends to stratify, can be pushed down toward the floor. If the flow rate is insufficient, the floor may remain cold (and therefore uncomfortable), continually replenished by a cold convective flow from the cold wall (or walls). Note that a beneficial side effect of this tradeoff of using displacement registers in heating mode is that the system, by avoiding mixing, may reduce the risk of injury due to contaminants in a space. In this case, consider that the general forced-convective flow is down toward the floor and out the return register. Referring to Fig. 10, in a central space conditioning system, one or more contaminant detectors 1016 may be located in a return air duct and the system shut down if dangerous contaminants are detected before such contaminants could be distributed in a building. Examples of detectable contaminants increase all the time due to enhancements in sensor technology, but examples include carbon monoxide, volatile organics, opacity, and particulate counts.

[Para 45] In many commercial buildings, heat may be lost through only one or two walls of an occupied space. For example, in an office building this is commonly the case. In a preferred embodiment of the general Fig. 9B embodiment, the rear wall in which at least one of the return registers 935 is located corresponds to that wall. This is so that the coldest air, which may be flowing downwardly along the surface of the "cold" wall, can be drawn into the one or more return registers 935 rather than mixing with the room air or causing the lower stratum of the room to get colder. The volume exchange rate may be sized to match the volume rate of the convective flow, which is readily predicted based on the outdoor air temperature, the conductivity and diffusivity of the wall, the film coefficients and so on according to known techniques. This is an excellent application for feedward or predictive model-based control because of the unsteady state of the wall system. In a preferred embodiment, such a model-based control scheme would take account of outdoor wind speed and direction, in addition to the obvious one of air temperature. In addition, such preferred embodiment may take account of conditioned space occupancy and predicted activity levels (for example, a lookup table based on time of day) so that activity-induced disturbances in the

thermal convection field can be taken into account. In many cases, the cold wall is the outside wall and may be fitted with a window. This may make the placement of the return register in the middle of the wall difficult. However, one or more return registers 935 may be located at the ends of the cold wall on one or both adjacent perpendicular walls such that air is drawn from the same lower region of the cold wall.

[Para 46] Fig. 10 is an illustration of a central control system that may be used with various embodiments discussed herein. A programmable controller 1000 is connected to various sensors such as outdoor air temperature 1010, indoor air temperature 1015, supply air temperature 1030, and return air temperature 1035. The controller 1000 is also connected to a clock/calendar 1020 and various actuators for controlling the mechanical state of a space conditioning system including the actuators of the described multimode displacement registers, separate heating and cooling systems, and other mechanical elements described above.

[Para 47] Fig. 11 shows a plan view of a room with multiple discharge registers 1125, 1135, and 1145. The discharge pattern of each of the registers 1125, 1135, and 1145, used individually, is shown at 1100, 1105, and 1110, respectively. In an embodiment of the invention, to increase mixing with a given volume flow rate and eliminate dead spots, a single supply volume is differentially applied to a number of different registers 1125, 1135, and 1145 with the majority of the flow being output by a subset of all the different registers 1125, 1135, and 1145 at any given time. Thus, for a given flow volume, the discharge velocity at any given time will be higher than if the same flow volume were distributed more uniformly to all registers 1125, 1135, and 1145. The above may be accomplished with any kind of register equipped with a flow-volume adjusting capability. The flow pattern may be shifted, for example, on a time-basis such that all flow is supplied to register 1125 for a period of a minute, then to register 1135 for a minute, and finally to register 1145 for a minute, then repeating and so on. The cycle of shifting can be varied to change faster or slower. Note that in the above embodiment, registers 1125, 1135, and 1145 may be configurable mixing/displacement ventilation registers according to any of the embodiments described herein. In one embodiment of the invention, flow may be cycled among the registers as described above, but only in the heating mode where a high velocity

mixing effect is used whilst in a cooling mode, all registers are used since displacement ventilation is employed for cooling.

[Para 48] In an alternative embodiment, a single register 1150 has multiple outlets, each aimed in different directions as indicated by arrows 1155. The flow is directed to each outlet in turn in a cycling pattern such that most of the supply flow is directed a single direction and then shifted to the next direction in turn. This creates varying flow patterns. The latter may be accomplished using a ventilation register device with an internal flow director such that only one inlet connection needs to be made to the supply ductwork.

[Para 49] Referring now to Fig. 14, a configurable mixing/displacement ventilation register 1400 has an internal plenum space 1430 defined by top, 1484, rear 1481, and side 1482 and 1483 panels and a tilted baffle plate 1415 toward a front 1440. Air is supplied to the internal plenum space 1430 through an inlet collar 1460 that is attachable to an external duct system. A movable bottom plate 1425 is hinged at an edge 1425A thereof. The bottom plate 1425 is shown in an intermediate position between a heating mode, in which the bottom plate 1425 drops down allowing air in the plenum space 1430 to exit through a slot 1475 and a cooling mode in which the bottom plate 1425 is in a raised position forcing all air through the tilted baffle panel 1415. The slot is partly defined by a horizontal plate 1420. The bottom plate 1425 may be actuated by, for example, by a mechanical actuator 1465 which may be a thermal motor, for example, or an actuator controlled by an external or internal control mechanism (not shown in the present drawing).

[Para 50] In the cooling mode, air flows into the plenum space 1430 and is forced through the tilted baffle panel 1415 and then through a front baffle panel 1410. Little or no air escapes through the slot 1475 because, in the cooling mode, the bottom plate 1425 is in the up, or closed, position, thereby separating the plenum space 1430 from the slot 1475. The angle of the tilted baffle panel 1415 makes the plenum space 1430 progressively narrower toward the end of the plenum space 1430 that is remote from the inlet collar 1460. This helps to make the flow through the tilted baffle panel 1415 uniform along its face. Air then exits the configurable mixing/displacement ventilation register 1400 through the front baffle panel 1410 by passing through the gap 1435. The size of the front baffle panel 1410 is relatively

large and the average velocity through the front baffle panel 1410 is relatively low consistent with the function of a displacement-type register.

[Para 51] The configurable mixing /displacement ventilation register 1400 is preferably located adjacent or near a floor. In the heating mode, the bottom plate 1425 drops down allowing air to escape from the plenum space 1430 into the slot 1475 and out. Although some air will still escape the plenum space 1430 by flowing through the tilted baffle panel 1415 and then through the front baffle panel 1410, much of it also escapes through the slot 1475. The configuration overall may be designed such that the flow through the slot 1475 in the heating mode is relatively high, consistent with mixing-type ventilation.

[Para 52] This causes heated air to be projected (along the floor, in applications where the configurable mixing/displacement ventilation register 1400 is located adjacent or near the floor) well into the ventilated space. The velocity through the slot 1475 may be such that warm air from the front baffle panel 1410 is induced into the flow from the slot 1475.

[Para 53] According to an optional feature of the Fig. 14 embodiment, one or more flow deflector plates 1455 may be provided to deflect flow through the tilted baffle panel 1415 in the cooling mode. In the heating mode, the flow deflector plates 1455 may pivot down and against the tilted baffle panel 1415.

[Para 54] In the heating mode the flow deflector plates 1455 may serve to partially (or completely) block the tilted baffle panel 1415 thereby forcing more air to pass through the slot. An arm may connect the flow deflector plates 1455 to the bottom plate 1425 so that the flow deflector plates 1455 are moved in unison with the bottom plate 1425 by the actuator 1465.

[Para 55] Note that in various foregoing embodiments, the bottom portion of the register remains fixed and flow is directed in a horizontal direction. By comparison, prior art multi-mode register devices, generally designed for commercial applications, direct air downwardly during a heating mode requiring the bottom to change configuration and may result in a change in overall height of the unit. According to inventive embodiments described herein, the bottom remains fixed and the space taken up by the register unit remains fixed. This is believed to be desirable in a floor-mounted register. Also, by directing high velocity flow

adjacent the floor, a more persistent jet - a wall jet - may be generated as compared to a free jet which tends to lose momentum faster.

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

1. A ventilation system for an occupied space, comprising:
 - at least one supply register configured as a displacement-type diffuser providing a flow of ventilation air at non-mixing rates;
 - at least one first return register configured to withdraw air at a level proximate a ceiling of said occupied space and at least one second return register configured to withdraw air from said occupied space at a level near a floor of said occupied space;
 - a control system configured to control the flow of heated or cooled air to said at least one supply register and selectively to control the flow of air into said at least one first return register and said at least one second return register such that:
 - during cooling, cooled air is supplied through said at least one supply register and air is withdrawn through said at least one first return register, and
 - during heating, warm air is supplied through said at least one supply register and air is withdrawn through said at least one second return register.
2. A system as in claim 1, wherein said control system is further configured to regulate a volume rate of flow through said at least one second return register such that the rate of air exchanged in said occupied space is responsive to outdoor air temperature.
3. A system as in claim 2, wherein said control system includes a feedforward control mechanism with at least one outdoor air temperature input.
4. A system as in claim 1, wherein said control system includes a contamination detector located in a central return duct and the control system is configured to deactivate a fan responsively to a detection of a contaminant by said contamination detector.
5. A system as in claim 1, further comprising an air circulating fan controlled to mix air in said occupied space during said heating.

6. A system as in claim 5, wherein said air circulating fan is controlled responsively to a local temperature gradient in said occupied space.
7. A system as in claim 1, wherein each said at least one supply register is configured such that a face area thereof, through which air is supplied to said occupied space, is adjusted by the control system based on a mode of the ventilation system, the mode being one of a heating mode for said heating and a cooling mode for said cooling.
8. A system as in claim 1, wherein the control system and the at least one supply register are configured such that:
 - during said, cooled air is supplied to said occupied space through a first face area of each said at least one supply register at a first velocity; and
 - during said heating mode, warm air is supplied to said occupied space through a second face area of each said at least one supply register at a second velocity, wherein the first face area is greater than the second face area, and the first velocity is less than the second velocity.
9. A system as in claim 1, wherein during said cooling the cooled air is supplied from said at least one supply register from a first output portion thereof, and during said heating, the warm air is supplied from said at least one supply register from a second output portion thereof, the first and second output portions being different.
10. A system as in claim 9, wherein the first output portion and the second output portion have no portion in common.
11. A system as in claim 9, wherein the first output portion is arranged relatively higher in said occupied space than said second output portion.
12. A system as in claim 1, wherein air flow output from said at least one supply

register is such that the air flow has a horizontal component as a primary component.

13. A system as in claim 1,
wherein the first and second return registers are exclusive return registers,
wherein the control system is configured to selectively control the flow of air into said at least one first return register and said at least one second return register in response to a mode of the ventilation system, the ventilation system having at least a heating mode and a cooling mode,
wherein in the cooling mode, the cooled air is supplied through said at least one supply register and air is withdrawn from said occupied space only through said at least one first return register, and
wherein in the heating mode, the warm air is supplied through said at least one supply register and air is withdrawn from said occupied space only through said at least one second return register.

14. A system as in claim 2, wherein said control system is configured to regulate the volume rate of flow through said at least one second return register such that the rate of air exchanged in said occupied space is responsive to outdoor air temperature during a heating mode.

15. A system as in claim 5, wherein said air circulating fan mixes warm, stratified air in said occupied space during said heating.

16. A system as in claim 5, wherein said air circulating fan hangs from the ceiling of said occupied space and extends into said occupied space.




Fig. 1A




Fig. 1B




Fig. 2A




Fig. 2B




Fig. 3A




Fig. 3B




Fig. 4A




Fig. 4B




Fig. 5A




Fig. 5B




Fig. 6A




Fig. 6B




Fig. 7A




Fig. 7B




Fig. 8A 835






Fig. 8B 835






Fig. 10




Fig. 11




Fig. 12A




Fig. 12B




Fig. 13




Fig. 14

